7 Spring Boot 整合 MyBatis

顺序:配置文件->Mapper.xml->entity->mapper类->service dao ->控制器



```
目录结构
      🔻 📄 java

▼ controller

            © % PersonController
          entity
            🕨 🕝 🦫 Person

    mapper

           🕨 📺 🍗 PersonMapper

▼ ■ service

            ▶ 🕝 🔓 PersonService
          ▶ 🦟 ¼ Start
      ▼ mesources
        mapper
             PersonMapper.xml
          🖿 static
          templates
          application.properties
1配置文件
server.port=8080
#mysql配置信息
spring.datasource.url=jdbc:mysql://192.168.1.129:3001/beandb
```

```
spring.datasource.username=bean
spring.datasource.password=1111111
spring.datasource.driver-class-name=com.mysql.jdbc.Driver
```

mybatis.mapper-locations=classpath:mapper/*Mapper.xml mybatis.type-aliases-package=com.bean.entity

<?xml version="1.0" encoding="utf-8" ?>

```
2 PersonMapper.xml
```

```
<!DOCTYPE mapper PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN" "http://</p>
mybatis.org/dtd/mybatis-3-mapper.dtd" >
<mapper namespace="com.bean.mapper.PersonMapper">
  <select id="getPersonList" resultType="com.bean.entity.Person">
    SELECT * FROM person
    <!--mysql表明区分大小写-->
  </select>
  <select id="getPersonById" resultType="com.bean.entity.Person">
    SELECT * FROM person WHERE id = #{id}
  </select>
</mapper>
```

```
3 PersonMapper.java
@Repository
@Mapper
public interface PersonMapper {
  public Person getPersonById(int ia);
  public List<Person> getPersonList();
}
4 PersonService.java
@Service
public class PersonService {
  a Autowired
  private JdbcTemplate jdbctpl; //idea2016bug:需要修改idea.properties,添加:idea.spring.boot.filter.autoconfig=false
  (a) Autowired
  private PersonMapper pm;
  public Person getPerson(int ia){
    return pm.getPersonById(ia);
  }
  public List<Person> getPersonList(){
    return pm.getPersonList();
  }
}
5 控制器
@RestController
public class PersonController {
  (a) Autowired
  private PersonService persev;
  @RequestMapping("/persons")
  public List<Person> getPeronsList(){
    List<Person> ps = persev.getPersonList();
    return ps;
  }
```

```
//用get把id传进去

@RequestMapping(value = "/person/{id}",method = RequestMethod.GET)

public Person getPeron(@PathVariable int ia) {
    Person ps = persev.getPerson(ia);

    return ps;
}
```