# Twisty Puzzle Masterz 2.0

## (Project Notes)

Idea Conceived: 05/05/2023

Update the project to API 33 and AndroidX  Add detailed comments that explain all magic numbers and algorithms.  Use proper code style guide for java (reference software engineering document)  Make Rayfuzu Learning YouTube video  Merge the opency code into this project's code base. Keep the 2D cube interface code	
as a debugging option that can be changed in settings.	
Try to merge my code and the opency code into the 2.0 repository	
<ul> <li>or try merging the opency code into my project?</li> </ul>	
- Create a copy to test the merging?	
Create design diagrams and descriptions on exactly how the data structure and	
algorithms work.	
Follow S.O.L.I.D. principles	
☐ How to make a proper Java library for the solver feature	

#### How to add OpenCV to android:

- https://www.youtube.com/watch?v=oIk2hTPxFqs&t=255s
  - At 6:28 whatever you name that module, open that folder in file explorer and paste everything from C:\Users\downs\Desktop\OpenCV-android-sdk\sdk into it
  - Update build.gradle for (:opencv) add this line
    - android {

Working Java Android Cube Solver and OpenCV <a href="https://github.com/ucchiee/AndroidRubikCubeSolver">https://github.com/ucchiee/AndroidRubikCubeSolver</a>

- namespace 'org.opencv'
- **Update build.gradle for (:opencv)** with 4 fields to match your project build.gradle

- a) compileSdkVersion
- b) buildToolsVersion
- c) minSdkVersion and
- d) targetSdkVersion.
- Comment out each line that is throwing an error inside of AsyncServiceHelper.java (I don't use that anywhere)
- <a href="https://www.youtube.com/watch?v=bR7IL886-uc&t=221s">https://www.youtube.com/watch?v=bR7IL886-uc&t=221s</a>
- Also helpful
  - <a href="https://stackoverflow.com/questions/63254458/could-not-import-the-opency-librar-vy-in-android-studio">https://stackoverflow.com/questions/63254458/could-not-import-the-opency-librar-vy-in-android-studio</a> (last post in this stackoverflow thread)
  - <a href="https://www.geeksforgeeks.org/how-to-add-opency-library-into-android-applicatio">https://www.geeksforgeeks.org/how-to-add-opency-library-into-android-applicatio</a> n-using-android-studio/
  - <a href="https://www.geeksforgeeks.org/different-ways-to-delete-a-module-in-android-stud">https://www.geeksforgeeks.org/different-ways-to-delete-a-module-in-android-stud</a> <a href="io/">io/</a>

#### Video Format Inspiration:

https://www.youtube.com/watch?v=fAX27 FyU9g

# How "Twisty Puzzle Masterz" solves the 3x3x3 Rubik's Cube

## 1. Terminology

- a. Location:
  - i. All interesting layers for the given cubie
- b. Orientation
  - i. Placement of the stickers on the given cubie with respect to their correct center piece colors.

#### 2. Cross

#### a. Solve Order

```
i. {[WHITE, GREEN], [WHITE, BLUE], [WHITE, ORANGE], [WHITE, RED]
```

## b. Steps

- i. Get all cross pieces on down layer
- ii. Rotate bottom layer until at least 2 pieces are in correct location
- iii. Set the cubies that are in correct locations to their correct orientation
- iv. Iff 2 cubies are in incorrect locations then swap them
  - 1. Set those 2 cubies to correct orientation Iff need to.

## c. Step 1

i. Get all cross pieces on down layer

#### d. Avoidance Maneuver

This is done by rotating the down layer such that there is no white cubie on the spot that itersets with the down and chosen layer to move.

```
// Chosen layer to move n = [L \text{ or } R]
```

- D (until no white edge cubic interests [n,D])
- n or n'
- IMPROVEMENT 1: At this point you already know which white edges have been solved so you don't need to (do while) rotate the down layer until you are above an unsolved piece.
- Instead, you can just keep track of those 4 pieces and which ones are solved and unsolved. That way you can know exactly what movements are needed to put the unsolved white edge piece under your solving cubie.
- IMPROVEMENT 2: If you have to do D D D then undo those steps and do a D'

#### e. If cubie on up layer

```
[top, right] => R2
[top, front] => F2
[top, left] => L2
[top, back] => B2
```

If there is a white edge cubic already located at [n, D] then use the <u>avoidance maneuver</u> to solve the cubic in the up layer.

#### f. If cubie on middle layer

```
[left, front] => L or F'
[right, front] => R' or F
[left, back] => L' or B
[right, back] => R or B'
```

Prefer the move that puts the cubie in the correct <u>location</u>.

Move that wont kick out an already positioned white cubie on the down layer.

#### g. If cubie on down layer

- i. Go to the next white edge cubic to solve. This one is already on the desired layer.
- ii. Maintain location on down layer while putting other cubies on down layer using the **avoidance maneuver**.

### h. Step 2

i. Rotate bottom layer until at least 2 pieces are in correct location

#### i. Step 3


- i. Set all cubies to their correct orientations.
- ii. If solving cubie is on **Right** 
  - 1. R2 U F R' F'
- iii. If solving cubie is on Front
  - 1. F2 U L F' L'
- iv. If solving cubie is on Left
  - 1. L2 U B L' B'
- v. If solving cubie is on **Back** 
  - 1. B2 U R B' R'
  - 2. *IMPROVEMENT 3:* Add Xw and Xw' to data structure possible rotations
    - 3. If solving cubie is on **Right** 
      - a. Execute: R Uw' R Uw
    - b. If solving cubie is on Front
      - i. Execute: F Uw' F Uw
    - 4. If solving cubie is on **Left** 
      - a. Execute: L Uw' L Uw
    - 5. If solving cubie is on Back
      - a. Execute: B Uw' B Uw

## j. Step 4


i. Iff 2 cubies are in incorrect locations then swap them

**NOTE**: Black squares on the below diagrams represents a white cubie on the down layer.

1.



2.



ii. Case 1:


R2 L2 U2 R2 L2

iii. Case 2:


F2 B2 U2 F2 B2

- 1. *IMPROVEMENT 4:* Improve the rubik's cube solution code and data structure to be able to handle whole cube rotations.
- 2. *IMPROVEMENT 5*: The above two cases can be swapped by rotating the up layer to match the alignment of 2, then executing the following:


3.




4.



5.



6.



- 7. To swap the white cubies in cases 3-6 above, use these four algorithms respectively:
  - a. R2, U, F2, U', R2

//[[D,F],[D,R]]

b. F2, U, L2, U', F2

//[[D,F],[D,L]]

c. L2, U, B2, U', L2

// [ [B,D] , [D,L] ]

d. B2, U, R2, U', B2

// [ [B,D] , [D,R] ]

- iv. *IMPROVEMENT* 6:If you have setup 3 above and they both need to be swapped and oriented, then you can use a single algorithm:
  - 1. F' R F R2

## 3. F2L

Corner on top, FL color facing side, edge colors match			
Case #	Case Image	Algorithm	
1		<b>U (R U' R')</b> R' F R F'	
3		U' R U R' U2 (R U' R')	
5		U' R U2' R' U2 (R U' R')	

a. F2L Configuration Format:

}

```
"Case 1": { < Cubie 1 Orientation > , < Cubie 2 Orientation > , < Correct Location > } ...
```

b. Cubie1 = {WHITE, RED, BLUE} -> {D,F,R} Cubie2 = {BLUE, RED} -> {F,R}

Cube Orientation = { {F->BLUE}, {U->YELLOW}, {R->RED} }

- c. Edge Cases (that require a specific correction algorithm)
  - i. White stickered Cubie is in the D layer in wrong location

- ii. White stickered Cubie is in the D layer in correct location with wrong orientation
- iii. F2L edge cubie is in wrong location in the middle layer

## d. F2L Solution Steps:

- i. Locate both cubies
- ii. Put them both on the top layer
- iii. Rotate top layer to correctly align the F2L pair
- iv. Execute the corresponding algorithm
  - 1. Improvement 7: Add algorithms for each F2L pair to be executed from any of the four cube orientations.

4. OLL

5. PLL

## Other Helpful Resources

- 1. You can use this website to generate an animation of the execution of the solution algorithm for those who don't know the rubik's cube notations:
  - a. <a href="https://ruwix.com/widget/3d/">https://ruwix.com/widget/3d/</a>? [ solution algorithm ]
  - b. This is helpful if my solution algorithm ends up being 80-100 movements
- 2. Working python OpenCV (using open source solver)
  - a. https://github.com/nicpatel963/CubeSolvingScript/blob/master/cubenew.py
- 3. Working Android OpenCV and Solver (But using USB cameras?)
  - a. https://github.com/geoffreywwang/CubeBot
- 4. <a href="https://www.youtube.com/watch?v=afAGtExoiLQ">https://www.youtube.com/watch?v=afAGtExoiLQ</a>
- 5. <a href="https://www.youtube.com/watch?v=RMo">https://www.youtube.com/watch?v=RMo</a> CLi1Z5q
- 6. <a href="https://www.youtube.com/watch?v=CWmKHcx1X6A">https://www.youtube.com/watch?v=CWmKHcx1X6A</a>
- 7. <a href="https://www.voutube.com/watch?v=3pgo6SMmtS4">https://www.voutube.com/watch?v=3pgo6SMmtS4</a>
- 8. 9 years old. Can't build into Android Project without Gradle.
  - a. https://sgelb.github.io/projects/arcs
- 9. 3D cube animation
  - a. https://github.com/cjurjiu/AnimCubeAndroid
  - b.