

INTRO to DATA SCIENCE

LECTURE 12: DECISION TREE CLASSIFIERS

Rob Hall

DAT5 SF // April 16, 2014

RECAP

LAST TIME:

- RECOMMENDATION SYSTEMS**
- RECOMMENDATION SYSTEMS IN PYTHON**

QUESTIONS?

AGENDA

I. DECISION TREES

II. BUILDING DECISION TREES

III. OPTIMIZATION FUNCTIONS

IV. PREVENTING OVERFITTING

V. (BRIEF INTRO TO) RANDOM FORESTS

EXERCISE:

V. IMPLEMENTING DECISION TREES WITH SCIKIT-LEARN

I. DECISION TREES

| | <i>continuous</i> | <i>categorical</i> |
|---------------------|-------------------|--------------------|
| <i>supervised</i> | ??? | ??? |
| <i>unsupervised</i> | ??? | ??? |

| | <i>continuous</i> | <i>categorical</i> |
|---------------------|----------------------------|-----------------------|
| <i>supervised</i> | <i>regression</i> | <i>classification</i> |
| <i>unsupervised</i> | <i>dimension reduction</i> | <i>clustering</i> |

Q: What is a decision tree?

Q: What is a decision tree?

A: A non-parametric hierarchical classification technique.

Q: What is a decision tree?

A: A non-parametric hierarchical classification technique.

non-parametric: *no parameters, no distribution assumptions*

Q: What is a decision tree?

A: A non-parametric hierarchical classification technique.

non-parametric: *no parameters, no distribution assumptions*

hierarchical: *consists of a sequence of questions which yield a class label when applied to any record*

Q: How is a decision tree represented?

Q: How is a decision tree represented?

*A: Using a configuration of **nodes** and **edges**.*

Q: How is a decision tree represented?

*A: Using a configuration of **nodes and edges**.*

*More concretely, as a multiway tree, which is a type of (directed acyclic) **graph**.*

Q: How is a decision tree represented?

*A: Using a configuration of **nodes** and **edges**.*

*More concretely, as a multiway tree, which is a type of (directed acyclic) **graph**.*

*In a decision tree, the nodes represent questions (**test conditions**) and the edges are the answers to these questions.*

*The top node of the tree is called the **root node**. This node has 0 incoming edges, and 2+ outgoing edges.*

*The top node of the tree is called the **root node**. This node has 0 incoming edges, and 2+ outgoing edges.*

*An **internal node** has 1 incoming edge, and 2+ outgoing edges. Internal nodes represent test conditions.*

*The top node of the tree is called the **root node**. This node has 0 incoming edges, and 2+ outgoing edges.*

*An **internal node** has 1 incoming edge, and 2+ outgoing edges. Internal nodes represent test conditions.*

*A **leaf node** has 1 incoming edge and, 0 outgoing edges. Leaf nodes correspond to class labels.*

*The top node of the tree is called the **root node**. This node has 0 incoming edges, and 2+ outgoing edges.*

*An **internal node** has 1 incoming edge, and 2+ outgoing edges. Internal nodes represent test conditions.*

*A **leaf node** has 1 incoming edge and, 0 outgoing edges. Leaf nodes correspond to class labels.*

NOTE

The nodes in our tree are connected by *directed edges*.

These directed edges lead from *parent nodes* to *child nodes*.

Table 4.1. The vertebrate data set.

| Name | Body Temperature | Skin Cover | Gives Birth | Aquatic Creature | Aerial Creature | Has Legs | Hibernates | Class Label |
|---------------|------------------|------------|-------------|------------------|-----------------|----------|------------|-------------|
| human | warm-blooded | hair | yes | no | no | yes | no | mammal |
| python | cold-blooded | scales | no | no | no | no | yes | reptile |
| salmon | cold-blooded | scales | no | yes | no | no | no | fish |
| whale | warm-blooded | hair | yes | yes | no | no | no | mammal |
| frog | cold-blooded | none | no | semi | no | yes | yes | amphibian |
| komodo dragon | cold-blooded | scales | no | no | no | yes | no | reptile |
| bat | warm-blooded | hair | yes | no | yes | yes | yes | mammal |
| pigeon | warm-blooded | feathers | no | no | yes | yes | no | bird |
| cat | warm-blooded | fur | yes | no | no | yes | no | mammal |
| leopard | cold-blooded | scales | yes | yes | no | no | no | fish |
| shark | | | | | | | | |
| turtle | cold-blooded | scales | no | semi | no | yes | no | reptile |
| penguin | warm-blooded | feathers | no | semi | no | yes | no | bird |
| porcupine | warm-blooded | quills | yes | no | no | yes | yes | mammal |
| eel | cold-blooded | scales | no | yes | no | no | no | fish |
| salamander | cold-blooded | none | no | semi | no | yes | yes | amphibian |




Figure 4.4. A decision tree for the mammal classification problem.




Figure 4.4. A decision tree for the mammal classification problem.

NOTE

Internal nodes represent test conditions which partition the records at that node.

EXAMPLE – DECISION TREE

| Name | Body Temperature | Skin Cover | Gives Birth | Aquatic Creature | Aerial Creature | Has Legs | Hibernates | Class Label |
|--------------|------------------|------------|-------------|------------------|-----------------|----------|------------|-------------|
| gila monster | cold-blooded | scales | no | no | no | yes | yes | ? |

Now, let's try an example...




Figure 4.4. A decision tree for the mammal classification problem.


Unlabeled
data

| Name | Body temperature | Gives Birth | ... | Class |
|----------|------------------|-------------|-----|-------|
| Flamingo | Warm | No | ... | ? |

And another example...

EXAMPLE – DECISION TREE

And another example...



II. BUILDING DECISION TREES

Q: How do we build a decision tree?

Q: How do we build a decision tree?

A: One possibility would be to evaluate all possible decision trees (eg, all permutations of test conditions) for a given dataset.

Q: How do we build a decision tree?

A: One possibility would be to evaluate all possible decision trees (eg, all permutations of test conditions) for a given dataset.

But this is generally too complex to be practical $\rightarrow O(2^n)$.

Q: How do we build a decision tree?

A: One possibility would be to evaluate all possible decision trees (eg, all permutations of test conditions) for a given dataset.

But this is generally too complex to be practical $\rightarrow O(2^n)$.

Q: How do we find a practical solution that works?

Q: How do we build a decision tree?

A: One possibility would be to evaluate all possible decision trees (eg, all permutations of test conditions) for a given dataset.

But this is generally too complex to be practical $\rightarrow O(2^n)$.

Q: How do we find a practical solution that works?

*A: Use a **heuristic** algorithm.*

The basic method used to build (or “grow”) a decision tree is Hunt’s algorithm.

*The basic method used to build (or “grow”) a decision tree is **Hunt’s algorithm**.*

*This is a **greedy recursive algorithm** that leads to a **local optimum**.*

*The basic method used to build (or “grow”) a decision tree is **Hunt’s algorithm**.*

*This is a **greedy recursive algorithm** that leads to a **local optimum**.*

greedy – *algorithm makes locally optimal decision at each step*

recursive – *splits task into subtasks, solves each the same way*

local optimum – *solution for a given neighborhood of points*

Hunt's algorithm builds a decision tree by recursively partitioning records into smaller & smaller subsets.

Hunt's algorithm builds a decision tree by recursively partitioning records into smaller & smaller subsets.

*The partitioning decision is made at each node according to a metric called **purity**.*

Hunt's algorithm builds a decision tree by recursively partitioning records into smaller & smaller subsets.

*The partitioning decision is made at each node according to a metric called **purity**.*

A partition is 100% pure when all of its records belong to a single class.

Consider a binary classification problem with classes X , Y . Given a set of records D_t at node t , Hunt's algorithm proceeds as follows:

Consider a binary classification problem with classes X , Y . Given a set of records D_t at node t , Hunt's algorithm proceeds as follows:

1) If all records in D_t belong to class X , then t is a leaf node corresponding to class X .

Consider a binary classification problem with classes X , Y . Given a set of records D_t at node t , Hunt's algorithm proceeds as follows:

1) If all records in D_t belong to class X , then t is a leaf node corresponding to class X .

NOTE

This is the *base case* for the recursive algorithm.

Consider a binary classification problem with classes X , Y . Given a set of records D_t at node t , Hunt's algorithm proceeds as follows:

2) If D_t contains records from both classes, then a test condition is created to partition the records further. In this case, t is an internal node whose outgoing edges correspond to the possible outcomes of this test condition.

Consider a binary classification problem with classes X, Y . Given a set of records D_t at node t , Hunt's algorithm proceeds as follows:

2) If D_t contains records from both classes, then a test condition is created to partition the records further. In this case, t is an internal node whose outgoing edges correspond to the possible outcomes of this test condition.

*These outgoing edges terminate in **child nodes**. A record d in D_t is assigned to one of these child nodes based on the outcome of the test condition applied to d .*

Consider a binary classification problem with classes X , Y . Given a set of records D_t at node t , Hunt's algorithm proceeds as follows:

3) These steps are then recursively applied to each child node.

Consider a binary classification problem with classes X , Y . Given a set of records D_t at node t , Hunt's algorithm proceeds as follows:

3) These steps are then recursively applied to each child node.

NOTE

Decision trees are easy to interpret, but the algorithms to create them are a bit complicated.

Q: How do we partition the training records?

Q: How do we partition the training records?

A: There are a few ways to do this.

Q: How do we partition the training records?

A: There are a few ways to do this.

*Test conditions can create **binary splits**:*

Q: How do we partition the training records?

A: There are a few ways to do this.

*Test conditions can create **binary splits**:*





Figure 4.8. Test condition for binary attributes.

(b) Binary split {by grouping attribute values}

Q: How do we partition the training records?

A: There are a few ways to do this.


*Alternatively, we can create **multiway splits**:*



Q: How do we partition the training records?

A: There are a few ways to do this.

Alternatively, we can create multiway splits:



(a) Multiway split

NOTE

Multiway splits can produce purer subsets, but may lead to overfitting!

Q: How do we partition the training records?

A: There are a few ways to do this.

For continuous features, we can use either method:





Figure 4.11. Test condition for continuous attributes.

Q: How do we partition the training records?

A: There are a few ways to do this.

For continuous features, we can use either method:

**NOTE**

There are optimizations that can improve the naïve quadratic complexity of determining the optimum split point for continuous attributes.

Figure 4.11. Test condition for continuous attributes.

Q: How do we determine the best split?

Q: How do we determine the best split?

A: Recall that no split is necessary (at a given node) when all records belong to the same class.

Q: How do we determine the best split?

A: Recall that no split is necessary (at a given node) when all records belong to the same class.

Therefore we want each step to create the partition with the highest possible purity.

Q: How do we determine the best split?

A: Recall that no split is necessary (at a given node) when all records belong to the same class.

Therefore we want each step to create the partition with the highest possible purity.

We need an objective function to optimize!

III. OPTIMIZATION FUNCTIONS

We want our objective function to measure the gain in purity from a particular split.

We want our objective function to measure the gain in purity from a particular split.

Therefore we want it to depend on the class distribution over the nodes (before and after the split).

We want our objective function to measure the gain in purity from a particular split.

Therefore we want it to depend on the class distribution over the nodes (before and after the split).

For example, let $p(i \mid t)$ be the probability of class i at node t (eg, the fraction of records labeled i at node t).

Then for a binary (0/1) classification problem,

Then for a binary (0/1) classification problem,

The minimum purity partition is given by the distribution:

$$p(0|t) = p(1|t) = 0.5$$

Then for a binary (0/1) classification problem,

The minimum purity partition is given by the distribution:

$$p(0|t) = p(1|t) = 0.5$$

The maximum purity partition is given (eg) by the distribution:

$$p(0|t) = 1 - p(1|t) = 1$$

Some measures of impurity include:

$$\text{Entropy}(t) = - \sum_{i=0}^{c-1} p(i|t) \log_2 p(i|t),$$

$$\text{Gini}(t) = 1 - \sum_{i=0}^{c-1} [p(i|t)]^2,$$

$$\text{Classification error}(t) = 1 - \max_i [p(i|t)],$$

Note that each measure achieves its max at 0.5, min at 0 & 1.




Figure 4.13. Comparison among the impurity measures for binary classification problems.

Note that each measure achieves its max at 0.5, min at 0 & 1.

NOTE

Despite consistency, different measures may create different splits.




Figure 4.13. Comparison among the impurity measures for binary classification problems.

Impurity measures put us on the right track, but on their own they are not enough to tell us how our split will do.

Impurity measures put us on the right track, but on their own they are not enough to tell us how our split will do.

Q: Why is this true?

Impurity measures put us on the right track, but on their own they are not enough to tell us how our split will do.

Q: Why is this true?

A: We still need to look at impurity before & after the split.

*We can make this comparison using the **gain**:*

$$\Delta = I(\text{parent}) - \sum_{\text{children } j} \frac{N_j}{N} I(\text{child } j)$$

*We can make this comparison using the **gain**:*

$$\Delta = I(\text{parent}) - \sum_{\text{children } j} \frac{N_j}{N} I(\text{child } j)$$

(Here I is the impurity measure, N_j denotes the number of records at child node j , and N denotes the number of records at the parent node.)

*We can make this comparison using the **gain**:*

$$\Delta = I(\text{parent}) - \sum_{\text{children } j} \frac{N_j}{N} I(\text{child } j)$$

(Here I is the impurity measure, N_j denotes the number of records at child node j , and N denotes the number of records at the parent node.)

*When I is the entropy, this quantity is called the **information gain**.*

Generally speaking, a test condition with a high number of outcomes can lead to overfitting (ex: a split with one outcome per record).

Generally speaking, a test condition with a high number of outcomes can lead to overfitting (ex: a split with one outcome per record).

One way of dealing with this is to restrict the algorithm to binary splits only (CART).

Generally speaking, a test condition with a high number of outcomes can lead to overfitting (ex: a split with one outcome per record).

One way of dealing with this is to restrict the algorithm to binary splits only (CART).

Another way is to use a splitting criterion which explicitly penalizes the number of outcomes (C4.5)

*We can use a function of the information gain called the **gain ratio** to explicitly penalize high numbers of outcomes:*

$$\text{gain ratio} = \frac{\Delta_{info}}{-\sum p(v_i) \log_2 p(v_i)}$$

(Where $p(v_i)$ refers to the probability of label i at node v)

*We can use a function of the information gain called the **gain ratio** to explicitly penalize high numbers of outcomes:*

$$\text{gain ratio} = \frac{\Delta_{info}}{-\sum p(v_i) \log_2 p(v_i)}$$

NOTE

This is a form of regularization!

(Where $p(v_i)$ refers to the probability of label i at node v)

IV. PREVENTING OVERFITTING

In addition to determining splits, we also need a stopping criterion to tell us when we're done.

In addition to determining splits, we also need a stopping criterion to tell us when we're done.

For example, we can stop when all records belong to the same class, or when all records have the same attributes.

In addition to determining splits, we also need a stopping criterion to tell us when we're done.

For example, we can stop when all records belong to the same class, or when all records have the same attributes.

This is correct in principle, but would likely lead to overfitting.

*One possibility is **pre-pruning**, which involves setting a minimum threshold on the gain, and stopping when no split achieves a gain above this threshold.*

*One possibility is **pre-pruning**, which involves setting a minimum threshold on the gain, and stopping when no split achieves a gain above this threshold.*

This prevents overfitting, but is difficult to calibrate in practice (may preserve bias!)

*Alternatively we could build the full tree, and then perform **pruning** as a post-processing step.*

*Alternatively we could build the full tree, and then perform **pruning** as a post-processing step.*

To prune a tree, we examine the nodes from the bottom-up and simplify pieces of the tree (according to some criteria).

Complicated subtrees can be replaced either with a single node, or with a simpler (child) subtree.

Complicated subtrees can be replaced either with a single node, or with a simpler (child) subtree.

*The first approach is called **subtree replacement**, and the second is **subtree raising**.*




Figure 4.29. Post-pruning of the decision tree for Web robot detection.

V. RANDOM FORESTS

RANDOM FORESTS

A random forest is an ensemble of decision trees where each base classifier is grown using a random effect.

RANDOM FORESTS

A random forest is an ensemble of decision trees where each base classifier is grown using a random effect.

One way to do this is to randomly choose one of the top k features to split each node.

RANDOM FORESTS

A random forest is an ensemble of decision trees where each base classifier is grown using a random effect.

One way to do this is to randomly choose one of the top k features to split each node.

For a small number of features, we can also create linear combinations of features and select splits from the enhanced feature set (Forest-RC).

RANDOM FORESTS

A random forest is an ensemble of decision trees where each base classifier is grown using a random effect.

One way to do this is to randomly choose one of the top k features to split each node.

For a small number of features, we can also create linear combinations of features and select splits from the enhanced feature set (Forest-RC).

Or, we can select splitting features completely at random (Forest-RI).

EX: DECISION TREES IN PYTHON