

Spark the Definitive Guide 2nd Edition

Chapter 02

A Gentle Overview to Spark

A Gentle Overview

Text Book



Spark's Basic Architecture 22

- ▶ Single Computers work pretty well
- ▶ Powerful
- ▶ But only one machine
- ▶ This limits what can be done
- ▶ Single machines don't have the necessary power or the parallel ability
- ▶ Multiple computers alone are not enough – you need a framework to control the data
 - ▶ To schedule data movement and data processing

Spark Cluster Manager

- ▶ Spark has its own software based cluster manager.
- ▶ Configurable out of the box
 - ▶ Simple config file denoting if the node is a slave or master
- ▶ Spark can also use existing cluster managers:
 - ▶ YARN from Hadoop 2.x/3.x
- ▶ Mesos
 - ▶ Cluster scheduler created by Twitter
 - ▶ Still in use, we won't focus on Mesos in this class
- ▶ We will work initially with the built in Spark cluster manager
- ▶ YARN later in the semester when we move to cluster work

Core Architecture




Figure 2-1. The architecture of a Spark Application

Figure 2: Spark Core Architecture

Spark Applications

- ▶ What makes up a Spark application?
 - ▶ Magic
- ▶ It is two things
 - ▶ A single **driver process** (like a main process in Java or Python)
 - ▶ A **set** of *executor processes*

More Application

- ▶ A Driver runs the Spark Applications `main()` function
- ▶ This process sits on a node in the cluster
 - ▶ Remember Spark is always assumed to be an 2+ node cluster with an additional master node
- ▶ The Main function does 3 things:
 - ▶ Maintain information about the running process
 - ▶ Respond a user's program or input
 - ▶ Analyzing, distributing, and scheduling work across the executor processes
- ▶ Driver process is essential to the running of the application (can't crash!)

Executors

- ▶ Responsible for carrying out the work that the Driver assigns them
- ▶ Executor then is responsible for two things:
 - ▶ Executing the code assigned by the Driver
 - ▶ Reporting the state of the execution back to the driver node

Architecture




Figure 2-1. The architecture of a Spark Application

Figure 3: Spark Core Architecture

How Many Executors

- ▶ User specifies how many **executor** processes should fall on each cluster node
 - ▶ This can be declared at run time
 - ▶ This can be declared in the code
- ▶ There is a Spark mode called *local*
 - ▶ This runs both the driver and executors as local CPU threads and not distributed
 - ▶ Good for a quick test mode

Spark Application Have

- ▶ Spark Applications have:
 - ▶ A Cluster Manager
 - ▶ Driver process
 - ▶ Executors
 - ▶ Code that is executed across executors

Spark Language APIs

- ▶ Spark takes your logic in different languages
 - ▶ Translates it to the Core Spark language
 - ▶ Everything in Spark runs and computes in the Core Spark Language
- ▶ Scala is the default shell
 - ▶ You can launch this by typing from the command line:
 - ▶ `spark-shell`
 - ▶ This assumes you already installed Spark
- ▶ Spark runs on the JVM
 - ▶ Only requirement is Java 8 JDK
 - ▶ OpenJDK works fine

Languages

- ▶ We have said this a few times but again, Spark supports natively:
 - ▶ Scala
 - ▶ Java
 - ▶ Python
 - ▶ SQL, ANSI 2003 standard
 - ▶ R though the SparkR package

API Architecture




Figure 2-2. The relationship between the SparkSession and Spark's Language API

Figure 4: Spark Executor Architecture

How to interact with the Spark Session

- ▶ Every compiled spark code interacts through a `SparkSession()` object
 - ▶ `spark-submit` is for running batch jobs
 - ▶ Each Spark application has only 1 `SparkSession()`

Code

- ▶ Open the CLI in your Ubuntu Virtual machine
 - ▶ type: `spark-shell` or `pyspark`
 - ▶ For Scala, type:
 - ▶ `val myRange = spark.range(1000).toDF("number")`
 - ▶ For Python, type:
 - ▶ `myRange = spark.range(1000).toDF("number")`
- ▶ The text offers both languages, I will tend to use Python more

DataFrame

- ▶ The previous code created a DataFrame
 - ▶ Containing 1000 rows
 - ▶ The numbers 0 to 999
 - ▶ It is a *distributed collection*
 - ▶ Depending on the number of **executors**, this range is divided across the cluster per executors

What a DataFrame is

- ▶ Most common Spark Structured API
- ▶ Simply a table of data with rows and columns
 - ▶ table has no relational capabilities
 - ▶ Must be typed, but on demand can be inferred
- ▶ DataFrames are common in R and Python
 - ▶ But those languages are limited to single systems
 - ▶ DataFrame can only be as large as memory on that PC
- ▶ In Spark, DataFrames are the same as Python and R
 - ▶ Same logic and operations
 - ▶ But can be distributed and larger than the set of data.

Partitions

- ▶ To allow every *executor* to perform work in parallel, Spark breaks the Data up into chunks called **partitions**
- ▶ A **partition** is a collection of rows that sits on a physical node in the cluster
- ▶ DataFrames therefore have partitions
- ▶ If you have only one partition, even with thousands of executor threads:
 - ▶ Your parallelism is still 1
- ▶ If you have only one executor thread, with many partitions:
 - ▶ Your parallelism is still 1
- ▶ For the most part, we cannot manipulate the partitions directly
 - ▶ Only issue high-level transformations to data

Transformations

- ▶ In Spark the core data structures are *immutable*
 - ▶ So data is immutable, strange?
 - ▶ How do we change or manipulate the data?
- ▶ In Spark we issue instructions on how to change or *transform* the data
- ▶ Scala
 - ▶ `val divisby2 = myRage.where("number % 2 = 0")`
- ▶ Python
 - ▶ `divisby2 = myRage.where("number % 2 = 0")`
- ▶ Notice no output will be returned... why?
- ▶ Spark will not perform the operation until we call an **action**

Types of Transformations

- ▶ Two types of Transformations:
 - ▶ Narrow dependencies
 - ▶ Wide dependencies
- ▶ Narrow are 1 to 1 transformations, to find all numbers divisible by 2.
 - ▶ the `where` clause is the clue for a narrow dependency
- ▶ Wide dependency will have *input partitions* contributing to many *output partitions*
 - ▶ Known as a *shuffle*
- ▶ Narrow transformations performed in-memory
- ▶ Wide result in writes to the disk (can be a temporary data write)

Lazy Evaluations

- ▶ Spark will wait until the very last moment to “execute the graph of computation instructions”
 - ▶ Spark doesn't modify the data immediately
- ▶ Spark builds up a plan of execution
- ▶ By waiting as long as possible, Spark can optimize this plan from a raw DataFrame to a streamlined physical plan to run as efficiently as possible across the cluster
- ▶ Also known as *predicate pushdown* on DataFrames
- ▶ So when does this “plan” get put into action?

Actions

- ▶ To trigger a computation plan we execute an **action**
 - ▶ An action causes Spark to calculate a result
 - ▶ Using the previous example: `divisby2.count()`
 - ▶ This will trigger an action that executes the entire plan and generates a result
- ▶ There are 3 kinds of actions:
 - ▶ Actions to view data in the console
 - ▶ Actions to collect data into native objects in their respective language
 - ▶ Actions to write to data output sources

Demo Time

- ▶ This lecture continues from P.28 of the e-book until the end of the chapter.
- ▶ We will execute a series of Spark commands on some sample data
- ▶ See the accompanying pages and or recording

Conclusion

- ▶ We learned about core architecture of Spark
 - ▶ We learned about executors
 - ▶ We learned about partitions
 - ▶ We learned about drivers
- ▶ We learned about datatypes
 - ▶ DataFrames
 - ▶ APIs
- ▶ We learned about transformations
- ▶ We learned about actions
- ▶ We learned how to put it together from the Spark CLI