



A Branch-and-Cut based Pricer for the Capacitated Vehicle Routing Problem

Graduate:

Davide PARO

ID: 1207154

Supervisor:

Prof. Domenico Salvagnin

Co-Supervisor:

Prof. Roberto Roberti

Master's Degree in Computer Engineering

July 14th, 2022 Academic Year: 2021–2022



















- CVRP defined on a complete graph. We are given:
 - The amount of available vehicles with their capacity.
 - A central depot where vehicles are stationed.
 - Customers' locations.
 - The demands of the individual customers.







- CVRP defined on a complete graph. We are given:
 - The amount of available vehicles with their capacity.
 - A central depot where vehicles are stationed.
 - Customers' locations.
 - The demands of the individual customers.
- Objective:
 - Minimize overall routing costs while meeting the needs of all customers.





■ Branch-price-and-cut (BPC) is an exact approach for solving combinatorial optimization problems.





- Branch-price-and-cut (BPC) is an **exact approach** for solving combinatorial optimization problems.
 - It is an extension of traditional branch-and-cut (BAC) frameworks.





- Branch-price-and-cut (BPC) is an **exact approach** for solving combinatorial optimization problems.
 - It is an extension of traditional branch-and-cut (BAC) frameworks.
 - State-of-the-art VRP solvers in the last two decades [2, 3, 4, 5, 6, 7, 8, 9, 10, 11].



- Branch-price-and-cut (BPC) is an **exact approach** for solving combinatorial optimization problems.
 - It is an extension of traditional branch-and-cut (BAC) frameworks
 - State-of-the-art VRP solvers in the last two decades [2, 3, 4, 5, 6, 7, 8, 9, 10, 11].
 - Compared to traditional BAC frameworks, can tackle huge mixed integer programming models described by exponential amounts of decision variables.

$$\min_{\lambda} \quad z_{\text{SC}}(\lambda) = \sum_{p \in P} c_p \lambda_p$$

$$\sum_{p \in P} \lambda_p = K$$

$$\sum_{p \in P} a_{ip} \lambda_p \ge 1 \quad \forall i \in V_0$$

$$\lambda_p \in \{0, 1\} \quad \forall p \in P.$$



- Branch-price-and-cut (BPC) is an **exact approach** for solving combinatorial optimization problems.
 - It is an extension of traditional branch-and-cut (BAC) frameworks
 - State-of-the-art VRP solvers in the last two decades [2, 3, 4, 5, 6, 7, 8, 9, 10, 11].
 - Compared to traditional BAC frameworks, can tackle huge mixed integer programming models described by exponential amounts of decision variables.
 - How?

$$egin{aligned} \min_{\lambda} & z_{\mathrm{SC}}(\lambda) = \sum_{p \in P} c_p \lambda_p \ & \sum_{p \in P} \lambda_p = K \ & \sum_{p \in P} a_{ip} \lambda_p \geq 1 \quad orall i \in V_0 \ & \lambda_p \in \{0,1\} \quad orall p \in P. \end{aligned}$$





- Branch-price-and-cut (BPC) is an exact approach for solving combinatorial optimization problems.
 - It is an extension of traditional branch-and-cut (BAC) frameworks
 - State-of-the-art VRP solvers in the last two decades [2. 3. 4. 5. 6. 7. 8. 9. 10. 11].
 - Compared to traditional BAC frameworks, can tackle huge mixed integer programming models described by exponential amounts of decision variables.

$$egin{aligned} \min_{\lambda} & z_{ ext{SC}}(\lambda) = \sum_{p \in P} c_p \lambda_p \ & \sum_{p \in P} \lambda_p = K \ & \sum_{p \in P} a_{ip} \lambda_p \geq 1 \quad orall i \in V_0 \ & \lambda_p \in \{0,1\} \quad orall p \in P. \end{aligned}$$

- How?
 - Column Generation (CG): decision variables are generated lazily.





- Branch-price-and-cut (BPC) is an **exact approach** for solving combinatorial optimization problems.
 - It is an extension of traditional branch-and-cut (BAC) frameworks
 - State-of-the-art VRP solvers in the last two decades [2, 3, 4, 5, 6, 7, 8, 9, 10, 11].
 - Compared to traditional BAC frameworks, can tackle huge mixed integer programming models described by exponential amounts of decision variables.

$$egin{aligned} \min_{\lambda} & z_{\mathrm{SC}}(\lambda) = \sum_{p \in P} c_p \lambda_p \ & \sum_{p \in P} \lambda_p = K \ & \sum_{p \in P} a_{ip} \lambda_p \geq 1 \quad orall i \in V_0 \ & \lambda_p \in \{0,1\} \quad orall p \in P. \end{aligned}$$

- How?
 - Column Generation (CG): decision variables are generated lazily.
 - In VRP, decision variables represent single vehicle feasible routes.





- Branch-price-and-cut (BPC) is an **exact approach** for solving combinatorial optimization problems.
 - It is an extension of traditional branch-and-cut (BAC) frameworks
 - State-of-the-art VRP solvers in the last two decades [2, 3, 4, 5, 6, 7, 8, 9, 10, 11].
 - Compared to traditional BAC frameworks, can tackle huge mixed integer programming models described by exponential amounts of decision variables.

$$egin{aligned} \min_{\lambda} & z_{ ext{SC}}(\lambda) = \sum_{p \in P} c_p \lambda_p \ & \sum_{p \in P} \lambda_p = K \ & \sum_{p \in P} a_{ip} \lambda_p \geq 1 \quad orall i \in V_0 \ & \lambda_p \in \{0,1\} \quad orall p \in P. \end{aligned}$$

■ How?

- Column Generation (CG): decision variables are generated lazily.
 - In VRP, decision variables represent single vehicle feasible routes.
- **Pricing** in CVRP, is the art of feeding the BPC approach with good reduced cost routes to bring it towards fast optimality convergence.









- Pricing Problem (PP) in its "natural" form is an NP-hard combinatorial optimization problem [12].
 - Relaxation of the PP to make it solvable in pseudo-polynomial time [13, 14].





- Pricing Problem (PP) in its "natural" form is an **NP-hard** combinatorial optimization problem [12].
 - Relaxation of the PP to make it solvable in pseudo-polynomial time [13, 14].
- Dynamic programming algorithms (exact and heuristics) to solve the relaxed PP:
 - labeling algorithm proposed in Desrochers et al. [15] and Feillet et al. [16]





- Pricing Problem (PP) in its "natural" form is an **NP-hard** combinatorial optimization problem [12].
 - Relaxation of the PP to make it solvable in pseudo-polynomial time [13, 14].
- Dynamic programming algorithms (exact and heuristics) to solve the relaxed PP:
 - labeling algorithm proposed in Desrochers et al. [15] and Feillet et al. [16]
- Two major issues with contemporary approaches:





- Pricing Problem (PP) in its "natural" form is an **NP-hard** combinatorial optimization problem [12].
 - Relaxation of the PP to make it solvable in pseudo-polynomial time [13, 14].
- Dynamic programming algorithms (exact and heuristics) to solve the relaxed PP:
 - labeling algorithm proposed in Desrochers et al. [15] and Feillet et al. [16]
- Two major issues with contemporary approaches:
 - (weak) relaxing the PP worsens the dual bounds fed to the BPC (increasing column generation time).
 - Improved in last decade thanks to "smart" relaxations [17].





- Pricing Problem (PP) in its "natural" form is an **NP-hard** combinatorial optimization problem [12].
 - Relaxation of the PP to make it solvable in pseudo-polynomial time [13, 14].
- Dynamic programming algorithms (exact and heuristics) to solve the relaxed PP:
 - labeling algorithm proposed in Desrochers et al. [15] and Feillet et al. [16]
- Two major issues with contemporary approaches:
 - 1 (weak) relaxing the PP worsens the dual bounds fed to the BPC (increasing column generation time).
 - Improved in last decade thanks to "smart" relaxations [17].
 - (strong) Labeling algorithm's performance degrades as the vehicle capacity increases (longer routes), limiting its applicability to modern distribution problems.



Contributions





- An exact branch-and-cut approach for the non-relaxed pricing problem.
 - Almost no works on this domain, except [18].
- 2 Verify its competitiveness at solving the PP as the vehicle capacity increases.



Implementation



- Branch-and-cut implementation based on the IBM ILOG CPLEX optimizer.
- The Capacitated Profitable Tour Problem (CPTP) [18] was used as the base IP formulation to model the PP.
- Implemented in C and available online under a permissive license.

ahttps://github.com/dparo/master-thesis



- Some implementation details:
 - Heuristics for warm-starting (constructive + local-search).
 - Separation of cutting-planes both for integral and fractional solutions:
 - GSEC, RCC [19], GLM [20].
 - Fractional separation through push relabel max-flow [21] and Gomory-Hu trees [22].



Empirical evaluation







- We've modified the commonly employed traditional instances proposed in [1, 23, 24, 25, 26, 27, 28].
- BaPCod: State-of-the-art BPC of [29] developed in France at the Bordeaux University and Bordeaux Research Center.
 - Parametrized accordingly (disabled non-robust inequalities).
- Time the *BaPCod*'s labeling algorithm [11] and our BAC in solving the harder PPs.
- Running time depicted through **performance profiles** [30].





Results (1/2)

















Results (2/2)

























Conclusions and Future Work



The proposed branch-and-cut pricer proved competitive at solving some PP:

- Branch-and-cut approaches may supplement the traditional labeling algorithm.
- Suggesting future research on branch-and-cut approaches in the context of pricing for the CVRP. Benefits:
 - Improve performance of contemporary CVRP solvers.



The end



Thank, you.

Additional material.



Integer Programming



MIP solvers are rather general and can be used to solve a wide range of problems from various fields [31]. MIP models are, in spirit, a way to mathematically program a solver to achieve the desired solution. A MIP solver can solve a mixed-integer linear programming formulation expressed as [32]:

$$\max_{x,y} \qquad c^T x + d^T y \tag{1}$$

s.t.
$$Ax + By \le b \tag{2}$$

$$x \in \mathbb{R}^n$$
 (3)

$$y \in \mathbb{Z}_+^k, \tag{4}$$

where $A \in \mathbb{R}^{m \times n}$, $B \in \mathbb{R}^{m \times k}$ are matrices and $c \in \mathbb{R}^n$, $d \in \mathbb{R}^k$, $b \in \mathbb{R}^m$ are vector coefficients. The bound in eq. (2) can also be rewritten in equality and/or greater form.



History on CVRP exact solvers



- 1961: First branch-and-price applied to the Cutting Stock Problem in [33].
- Up to late 80s: tree search algorithms employing branch-and-bound schemes: Lagrangian duality relaxation,
- 1984, 1989: First Column Generation attempts [34, 35].
- From late 80s to first 2000s: branch-and-cut approaches.
- 1992: labeling algorithm for pricing in [15].
- 1999: infant BPC framework in [36].
- 2006: Turning point in modern BPC frameworks thanks to [2].
- 2011: smart ng-routes relaxation for the pricing problem [17].
- 2014-now: State-of-the-art BPC algorithms [7, 10, 9, 37, 38, 11].



Set Covering formulation



Let $P = \{p \mid p \text{ is a single-truck elementary feasible route}\}$ be the set of all feasible routes.

$$\min_{\lambda} \quad z_{\text{SC}}(\lambda) = \sum_{p \in P} c_p \lambda_p \tag{5}$$

$$\sum_{p \in P} \lambda_p = K \tag{6}$$

$$\sum_{p \in P} a_{ip} \lambda_p \ge 1 \qquad \forall i \in V_0 \tag{7}$$

$$\lambda_p \in \{0,1\}$$
 $\forall p \in P.$ (8)



Master Problem (Primal)



$$\min_{\lambda} \quad z_{\text{MP}}(\lambda) = \sum_{\rho \in P} c_{\rho} \lambda_{\rho} \tag{9}$$

$$\sum_{p \in P} \lambda_p = K \tag{10}$$

$$\sum_{p \in P} a_{ip} \lambda_p = 1 \qquad \forall i \in V_0$$
 (11)

$$0 \le \lambda_p \le 1 \qquad \forall p \in P. \tag{12}$$



Master Problem (Dual)



$$\max_{\pi} \quad z_{\text{DMP}}(\pi) = K\pi_0 + \sum_{i \in V_0} \pi_i \tag{13}$$

$$\pi_0 + \sum_{i \in V_0} a_{ip} \pi_i \le c_p \qquad \forall p \in P \qquad (14)$$

$$\pi_0 \in \mathbb{R}$$
 (15)

$$\pi_i \in \mathbb{R}$$
 $\forall i \in V_0,$ (16)

where $\pi_0 \in \mathbb{R}, \pi_i \in \mathbb{R} \quad \forall i \in V_0$ represents the dual variables associated respectively with constraints (10) and (11).



Restricted Master Problem



Due to the enormous size of the set of routes P, evaluating the dual variables $\pi \in \mathbb{R}^N$ is computationally intractable. As a result, in BAP frameworks we consider only a small subset of columns $\mathscr{P} \subseteq P$:

$$\min_{\lambda} \quad z_{\text{RMP}}(\lambda) = \sum_{p \in \mathscr{P}} c_p \lambda_p \tag{17}$$

$$\sum_{p\in\mathscr{P}}\lambda_p=K\tag{18}$$

$$\sum_{p \in \mathscr{P}} a_{ip} \lambda_p = 1 \qquad \forall i \in V_0 \tag{19}$$

$$\lambda_p \ge 0$$
 $\forall p \in \mathscr{P}.$ (20)



Pricing sub-problem



We look for a column to enter the basis of the RMP, which in turn necessitates the resolution of the following sub-problem:

$$c_p^* = \min_{p \in P} \left\{ \bar{c}_p = \sum_{e = \{i, j\} \in E} \left(c_e - \frac{\pi_i + \pi_j}{2} \right) a_{ep} \right\},$$
 (21)

which takes the name of *Pricing Problem* (PP). Any $p \in P$ which satisfies $c_p < 0$ is a valid column which can enter the basis of the RMP. The column generation procedure stops mainly under two scenarios: (i) when no more negative reduced cost routes exist, i.e. the PP outputs a $p^* \in P$ achieving $c_p^* \ge 0$ or (ii) the CG procedure tails off.



The Pricing Sub-problem



To advance the column generation, the pricer, a critical component in BPC frameworks, needs to solve the pricing sub-problem (PP):

- An Elementary Shortest Path Problem with Capacity Constraints (ESPPCC) in a reduced cost network with negative cycles.
 - NP-hard problem [12].
- Relax elementarity condition to make it solvable in pseudo-polynomial time:
 - \blacksquare *q*-routes with 2-cycles elimination [39].
 - \blacksquare q-routes with arbitrary k-cycles elimination [16, 40].
 - ng-routes [17].
- State-of-the-art solutions for the relaxed PP are based on dynamic programming:
 - labeling algorithm [15, 16].



CPTP



(24)

(26)

$$\min_{x,y} \quad z_{\text{CPTP}}(x,y) = \sum_{i \in E} c_e x_e - \sum_{i \in V} p_i y_i \tag{22}$$

$$y_0 = 1 \tag{23}$$

$$\sum_{i\in V}q_iy_i\leq Q$$

$$\sum_{e \in \delta(i)} x_e = 2y_i$$

$$\forall i \in V$$
 (25)

 $\forall i \in S, \ \forall S \subset V_0, \ |S| > 2$

$$\sum_{e \in \delta(S)} x_e \ge 2y_i$$

$$\forall e \in E$$
 (27)

$$x_e \in \{0, 1\}$$

 $y_i \in \{0, 1\}$

$$\forall i \in V$$
.

$$y_i \in \{0, 1\}$$

References.



References I



- George B Dantzig and John H Ramser. "The Truck Dispatching Problem". In: *Management science* 6.1 (1959), pp. 80–91 (cit. on pp. 2–5, 22).
- Ricardo Fukasawa, Humberto Longo, Jens Lysgaard, Marcus Poggi de Aragão, Marcelo Reis, Eduardo Uchoa, and Renato F. Werneck. "Robust Branch-and-Cut-and-Price for the Capacitated Vehicle Routing Problem". In:

 Mathematical Programming 106.3 (May 2006), pp. 491–511. ISSN: 0025-5610, 1436-4646. DOI: 10.1007/s10107-005-0644-x. URL:

 http://link.springer.com/10.1007/s10107-005-0644-x (visited on 03/24/2022) (cit. on pp. 6–13, 31).
- Artur Pessoa, Marcus Poggi De Aragao, and Eduardo Uchoa. "Robust Branch-Cut-and-Price Algorithms for Vehicle Routing Problems". In: *The Vehicle Routing Problem: Latest Advances and New Challenges*. Springer, 2008, pp. 297–325 (cit. on pp. 6–13).



References II



- Gabriel Gutiérrez-Jarpa, Guy Desaulniers, Gilbert Laporte, and Vladimir Marianov. "A Branch-and-Price Algorithm for the Vehicle Routing Problem with Deliveries, Selective Pickups and Time Windows". In: *European Journal of Operational Research* 206.2 (2010), pp. 341–349 (cit. on pp. 6–13).
- Claudia Archetti, Mathieu Bouchard, and Guy Desaulniers. "Enhanced Branch and Price and Cut for Vehicle Routing with Split Deliveries and Time Windows". In: *Transportation Science* 45.3 (2011), pp. 285–298 (cit. on pp. 6–13).
- Andrea Bettinelli, Alberto Ceselli, and Giovanni Righini. "A Branch-and-Cut-and-Price Algorithm for the Multi-Depot Heterogeneous Vehicle Routing Problem with Time Windows". In: *Transportation Research Part C: Emerging Technologies* 19.5 (2011), pp. 723–740 (cit. on pp. 6–13).



References III



- Claudio Contardo and Rafael Martinelli. "A New Exact Algorithm for the Multi-Depot Vehicle Routing Problem under Capacity and Route Length Constraints". In: *Discrete Optimization* 12 (2014), pp. 129–146 (cit. on pp. 6–13, 31).
- Claudio Contardo, Guy Desaulniers, and François Lessard. "Reaching the Elementary Lower Bound in the Vehicle Routing Problem with Time Windows". In: *Networks. An International Journal* 65.1 (2015), pp. 88–99 (cit. on pp. 6–13).
- Diego Pecin, Claudio Contardo, Guy Desaulniers, and Eduardo Uchoa. "New Enhancements for the Exact Solution of the Vehicle Routing Problem with Time Windows". In: *INFORMS Journal on Computing* 29.3 (2017), pp. 489–502 (cit. on pp. 6–13, 31).



References IV



- Diego Pecin, Artur Pessoa, Marcus Poggi, and Eduardo Uchoa. "Improved Branch-Cut-and-Price for Capacitated Vehicle Routing". In: *Mathematical Programming Computation* 9.1 (2017), pp. 61–100. ISSN: 18672957. DOI: 10.1007/s12532-016-0108-8 (cit. on pp. 6–13, 31).
- Artur Pessoa, Ruslan Sadykov, Eduardo Uchoa, and François Vanderbeck. "A Generic Exact Solver for Vehicle Routing and Related Problems". In:

 Mathematical Programming 183.1-2 (2020), pp. 483–523. ISSN: 14364646. DOI: 10.1007/s10107-020-01523-z (cit. on pp. 6–13, 22, 31).
- Moshe Dror. "Note on the Complexity of the Shortest Path Models for Column Generation in VRPTW". In: Operations Research 42.5 (Oct. 1994), pp. 977-978. ISSN: 0030-364X, 1526-5463. DOI: 10.1287/opre.42.5.977. URL: http://pubsonline.informs.org/doi/abs/10.1287/opre.42.5.977 (visited on 03/24/2022) (cit. on pp. 14-19, 37).



References V



- Martin Desrochers and François Soumis. "A Generalized Permanent Labelling Algorithm for the Shortest Path Problem with Time Windows". In: *INFOR: Information Systems and Operational Research* 26.3 (1988), pp. 191–212 (cit. on pp. 14–19).
- Stefan Irnich and Guy Desaulniers. "Shortest Path Problems with Resource Constraints". In: *Column Generation*. Springer, 2005, pp. 33–65 (cit. on pp. 14–19).
- Martin Desrochers, Jacques Desrosiers, and Marius Solomon. "A New Optimization Algorithm for the Vehicle Routing Problem with Time Windows". In: *Operations research* 40.2 (1992), pp. 342–354 (cit. on pp. 14–19, 31, 37).

Davide Paro



References VI





Dominique Feillet, Pierre Dejax, Michel Gendreau, and Cyrille Gueguen. "An Exact Algorithm for the Elementary Shortest Path Problem with Resource Constraints: Application to Some Vehicle Routing Problems". In: *Networks* 44.3 (2004), pp. 216–229. ISSN: 00283045. DOI: 10.1002/net.20033 (cit. on pp. 14–19, 37).



Roberto Baldacci, Aristide Mingozzi, and Roberto Roberti. "New Route Relaxation and Pricing Strategies for the Vehicle Routing Problem". In: *Operations Research* 59.5 (2011), pp. 1269–1283. ISSN: 0030364X. DOI: 10.1287/opre.1110.0975 (cit. on pp. 14–19, 31, 37).



References VII



- Mads Kehlet Jepsen, Bjørn Petersen, Simon Spoorendonk, and David Pisinger. "A Branch-and-Cut Algorithm for the Capacitated Profitable Tour Problem". In: Discrete Optimization 14 (2014), pp. 78–96. ISSN: 15725286. DOI: 10.1016/j.disopt.2014.08.001. URL: http://dx.doi.org/10.1016/j.disopt.2014.08.001 (cit. on pp. 20, 21).
- G. Laporte and Y. Nobert. "A Branch and Bound Algorithm for the Capacitated Vehicle Routing Problem". In: *OR Spektrum* 5.2 (1983), pp. 77–85. ISSN: 01716468. DOI: 10.1007/BF01720015 (cit. on p. 21).
- Luis Gouveia. "A Result on Projection for the Vehicle Routing Problem". In:

 European Journal of Operational Research 85.3 (Sept. 1995), pp. 610-624. ISSN: 03772217. DOI: 10.1016/0377-2217(94)00025-8. URL:

 https://linkinghub.elsevier.com/retrieve/pii/0377221794000258
 (visited on 02/01/2022) (cit. on p. 21).



References VIII



- Andrew V Goldberg. "An Efficient Implementation of a Scaling Minimum-Cost Flow Algorithm". In: *Journal of algorithms* 22.1 (1997), pp. 1–29 (cit. on p. 21).
- Ralph E Gomory and Tien Chung Hu. "Multi-Terminal Network Flows". In: Journal of the Society for Industrial and Applied Mathematics 9.4 (1961), pp. 551–570 (cit. on p. 21).
- Nicos Christofides and Samuel Eilon. "An Algorithm for the Vehicle-Dispatching Problem". In: *Journal of the Operational Research Society* 20.3 (1969), pp. 309–318 (cit. on p. 22).
- TJ Gaskell. "Bases for Vehicle Fleet Scheduling". In: *Journal of the Operational Research Society* 18.3 (1967), pp. 281–295 (cit. on p. 22).



References IX



- Billy E Gillett and Leland R Miller. "A Heuristic Algorithm for the Vehicle-Dispatch Problem". In: *Operations research* 22.2 (1974), pp. 340–349 (cit. on p. 22).
- Nicos Christofides. "The Vehicle Routing Problem". In: *Combinatorial optimization* (1979) (cit. on p. 22).
- Marshall L. Fisher. "Optimal Solution of Vehicle Routing Problems Using Minimum K-Trees". In: *Operations Research* 42.4 (1994), pp. 626–642. JSTOR: 171617 (cit. on p. 22).
- P Augerat, J M Beleaguer, E Benavent, A Corberan, D Naddef, and G Rinaldi. "Computational Results with a Branch and Cut Code for the Capacitated Vehicle Routing Problem". In: (1995), p. 33 (cit. on p. 22).



References X



- Ruslan Sadykov, Eduardo Uchoa, and Artur Pessoa. "A Bucket Graph—Based Labeling Algorithm with Application to Vehicle Routing". In: *Transportation Science* 55.1 (2021), pp. 4–28. ISSN: 15265447. DOI: 10.1287/TRSC.2020.0985 (cit. on p. 22).
- E. D. Dolan and J.J. Moré. "Benchmarking Optimization Software with Performance Profiles". In: *Mathematical Programming* 91.2 (2002), pp. 201–213 (cit. on p. 22).
- Robert Bixby and Edward Rothberg. "Progress in Computational Mixed Integer Programming—a Look Back from the Other Side of the Tipping Point". In: Annals of Operations Research 149.1 (2007), p. 37 (cit. on p. 30).
- Laurence A Wolsey and George L Nemhauser. *Integer and Combinatorial Optimization*. Vol. 55. John Wiley & Sons, 1999 (cit. on p. 30).



References XI



- P. C. Gilmore and R. E. Gomory. "A Linear Programming Approach to the Cutting-Stock Problem". In: *Operations Research* 9.6 (1961), pp. 849–859. JSTOR: 167051 (cit. on p. 31).
- Jacques Desrosiers, François Soumis, and Martin Desrochers. "Routing with Time Windows by Column Generation". In: *Networks. An International Journal* 14.4 (1984), pp. 545–565 (cit. on p. 31).
- Yogesh Agarwal, Kamlesh Mathur, and Harvey M Salkin. "A Set-Partitioning-Based Exact Algorithm for the Vehicle Routing Problem". In: *Networks. An International Journal* 19.7 (1989), pp. 731–749 (cit. on p. 31).
- Niklas Kohl, Jacques Desrosiers, Oli BG Madsen, Marius M Solomon, and Francois Soumis. "2-Path Cuts for the Vehicle Routing Problem with Time Windows". In: *Transportation Science* 33.1 (1999), pp. 101–116 (cit. on p. 31).



References XII



- Artur Pessoa and Eduardo Uchoa. "Solving Bin Packing Problems Using VRPSolver Models". In: *Operations Research Forum*. Vol. 2. Springer, 2020, pp. 1–25 (cit. on p. 31).
- Ruslan Sadykov and François Vanderbeck. "BaPCod-a Generic Branch-and-Price Code". PhD thesis. Inria Bordeaux Sud-Ouest, 2021 (cit. on p. 31).
- N. Christofides, A. Mingozzi, and P. Toth. "Exact Algorithms for the Vehicle Routing Problem, Based on Spanning Tree and Shortest Path Relaxations". In: *Mathematical Programming* 20.1 (1981), pp. 255–282. ISSN: 00255610. DOI: 10.1007/BF01589353 (cit. on p. 37).
- Alain Chabrier. "Vehicle Routing Problem with Elementary Shortest Path Based Column Generation". In: Computers and Operations Research 33.10 (2006), pp. 2972–2990. ISSN: 03050548. DOI: 10.1016/j.cor.2005.02.029 (cit. on p. 37).





A Branch-and-Cut based Pricer for the Capacitated Vehicle Routing Problem

Graduate:

Davide PARO

ID: 1207154

Supervisor:

Prof. Domenico Salvagnin

Co-Supervisor:

Prof. Roberto Roberti

Master's Degree in Computer Engineering

July 14th, 2022 Academic Year: 2021–2022