Session 5

1. Create index.html using inline CSS

First, create index.html and add this code.

```
<!DOCTYPE html>
<html>
<head>
  <title>VIBRANCE 2026 - College Fest</title>
</head>
<body>

  <header style="background-color: #222; color: white;">
    <h1>VIBRANCE 2026 - College Fest</h1>
  </header>

  <main>

    <article>
      <h2>Events</h2>
      <p>
        VIBRANCE 2026 brings exciting events including
        dancing, singing, fashion shows, coding competitions,
        gaming tournaments and many other fun activities.
      </p>
    </article>
```

```
    <article>
      <h2>Guests</h2>
      <p>
        Famous singers, talented dancers, motivational
        speakers and special college alumni will join our
        festival to entertain and inspire all students.
      </p>
    </article>

    <article>
      <h2>Contact</h2>
      <p>
        For registration and festival information, contact
        the college fest organizing team at the student
        activity office or email fest@example.com.
      </p>
    </article>

  </main>

  <footer style="text-align: center;">
    <p>© 2026 VIBRANCE College Fest. All Rights Reserved.</p>
  </footer>

</body>
</html>
```

Task 1 complete: Header has a dark background and white text. Footer text is centred.

2. Move styling into the internal CSS

Now remove all inline style attributes and add a <style> tag inside the <head>.

Also:

- Add .highlight to two paragraphs.
- Add id="contact" to the Contact article.
- Use selectors for body, h1, h2, and p.

```
<!DOCTYPE html>
<html>
<head>
  <title>VIBRANCE 2026 - College Fest</title>

  <style>
    body {
      background-color: #f4f4f4;
      font-family: Arial, sans-serif;
    }

    h1 {
      background-color: #222;
      color: white;
      text-align: center;
      padding: 25px;
    }

    h2 {
      color: darkblue;
    }
```

```
      p {
        font-size: 18px;
        line-height: 1.6;
      }

      .highlight {
        background-color: yellow;
        padding: 10px;
      }

      #contact {
        border: 2px solid black;
        padding: 15px;
      }

      footer {
        text-align: center;
      }
    </style>
</head>
<body>

    <header>
      <h1>VIBRANCE 2026 - College Fest</h1>
    </header>

    <main>
```

```
  <article>
    <h2>Events</h2>
    <p class="highlight">
      VIBRANCE 2026 brings exciting events including
      dancing, singing, fashion shows, coding competitions,
      gaming tournaments and many other fun activities.
    </p>
  </article>

  <article>
    <h2>Guests</h2>
    <p class="highlight">
      Famous singers, talented dancers, motivational
      speakers and special college alumni will join our
      festival to entertain and inspire all students.
    </p>
  </article>

  <article id="contact">
    <h2>Contact</h2>
    <p>
      For registration and festival information, contact
      the college fest organizing team at the student
      activity office or email fest@example.com.
    </p>
  </article>

</main>
```

```
  <footer>
    <p>© 2026 VIBRANCE College Fest. All Rights Reserved.</p>
  </footer>

</body>
</html>
```

Task 2 complete: You now have element, class and ID selectors.

3. Create external CSS file style.css

Now move all CSS rules out of the HTML file.

Step 1: Create a new file called style.css in the same folder.

Step 2: Add the following CSS code.

```
/* Body styling */
body {
  background-color: #F4F4F4;
  font-family: Arial, Helvetica, sans-serif;
  margin: 0;
  padding: 20px;
}

/* Heading styling */
h1 {
  background-color: #222222;
  color: white;
  text-align: center;
  padding: 25px;
}
```

```
/* Subheading styling */
h2 {
   color: rgb(30, 60, 120);
   border-bottom: 2px solid orange;
   padding-bottom: 8px;
}

/* Paragraph styling */
p {
   color: #333333;
   font-size: 18px;
   line-height: 1.6;
}

/* Highlight class */
.highlight {
   background-color: #FFF2CC;
   padding: 12px;
   border-left: 5px solid orange;
}

/* Contact ID */
#contact {
   background-color: lightcyan;
   border: 2px solid #008080;
   padding: 15px;
}
```

```
/* Footer styling */
footer {
  text-align: center;
  background-color: #222222;
  color: white;
  padding: 15px;
}
```

Step 3: Now update index.html.

Remove the entire <style> section and put this link inside <head>:

```
<link rel="stylesheet" href="style.css">
```

Your updated HTML file:

```
<!DOCTYPE html>
<html>
<head>
  <title>VIBRANCE 2026 - College Fest</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>

  <header>
    <h1>VIBRANCE 2026 - College Fest</h1>
  </header>

  <main>

    <article>
```

```
    <h2>Events</h2>
    <p class="highlight">
      VIBRANCE 2026 brings exciting events including
      dancing, singing, fashion shows, coding competitions,
      gaming tournaments and many other fun activities.
    </p>
  </article>

  <article>
    <h2>Guests</h2>
    <p class="highlight">
      Famous singers, talented dancers, motivational
      speakers and special college alumni will join our
      festival to entertain and inspire all students.
    </p>
  </article>

  <article id="contact">
    <h2>Contact</h2>
    <p>
      For registration and festival information, contact
      the college fest organizing team at the student
      activity office or email fest@example.com.
    </p>
  </article>

</main>
```

```
  <footer>
    <p>© 2026 VIBRANCE College Fest. All Rights Reserved.</p>
  </footer>


</body>
</html>
```

Task 3 complete

Five colours used in this design:

Colour type	Example
Hex	#F4F4F4
Hex	#222222
RGB	rgb(30, 60, 120)
Colour name	white
Colour name	orange

The font-family uses Arial, Helvetica and sans-serif, so no Google Fonts are needed.

4. Add group and descendant selectors

Open style.css and add these two new rules at the bottom.

```
/* Group selector */
h1, h2 {
  font-family: Georgia, serif;
  letter-spacing: 2px;
}

/* Descendant selector */
footer p {
  background-color: orange;
```

```
  color: black;
  font-weight: bold;
  padding: 15px;
  border-radius: 8px;
}
```

Understanding these selectors:

1. h1, h2 is a group selector. It applies the same styling to both headings.
2. footer p is a descendant selector. It applies styling only to paragraphs inside the footer.

Both rules visibly change the webpage.

5. Create a public GitHub repository

Sharing repositories online — Introduction to version control with Git documentation

coderefinery.github.io

Follow these steps:

1. Open GitHub – Create new repository.
2. Repository name: college-fest-page.
3. Select Public.
4. Click Create repository.

6. Push your project to GitHub

Open your project folder in VS Code.

Open Terminal and run these commands:

```
git init

git add index.html style.css

git commit -m "Create college fest page"

git branch -M main
```

git remote add origin https://github.com/YOUR-USERNAME/college-fest-page.git

git push -u origin main

Replace YOUR-USERNAME with your actual GitHub username.

Final assignment checklist

Your progress

0/10

Created index.html with VIBRANCE 2026 heading

Added Events, Guests and Contact articles

Completed inline CSS (Task 1)

Added internal CSS with class and ID selectors (Task 2)

Created external style.css (Task 3)

Used five-colour palette and three font-family choices

Added group selector h1, h2

Added descendant selector footer p

Created public college-fest-page repository

Pushed both files to GitHub

Useful next step: I can help you check your GitHub project and fix any HTML or CSS errors after you push it.