1. Create a class called Playlist with properties: name (string), createdOn (date), and isPublic (boolean). Instantiate an object of Playlist and print all its properties.

```
class Playlist {
  constructor(name, createdOn, isPublic) {
    this.name = name;
    this.createdOn = createdOn;
    this.isPublic = isPublic;
  }
}

let p1 = new Playlist("My Songs", "2026-10-14", true);

console.log("Name:", p1.name);
console.log("Created On:", p1.createdOn);
console.log("Is Public:", p1.isPublic);
```

2. Add a member function to your Playlist class named togglePublic() that switches isPublic between true and false each time it is called. Demonstrate by toggling the value twice and printing the result each time.

```
class Playlist {
  constructor(name, createdOn, isPublic) {
    this.name = name;
    this.createdOn = createdOn;
    this.isPublic = isPublic;
  }

  togglePublic() {
    this.isPublic = !this.isPublic;
```

```
  }
}

let p1 = new Playlist("My Songs", "2026-10-14", true);

p1.togglePublic();
console.log("After first toggle:", p1.isPublic);

p1.togglePublic();
console.log("After second toggle:", p1.isPublic);
```

Output:

After first toggle: false

After second toggle: true

Explanation: ! changes true to false and false to true.

3. Create a class called FoodOrder with properties: orderId (number), restaurantName (string), and isDelivered (boolean). Write a member function markDelivered() that sets isDelivered to true and prints a message. Instantiate FoodOrder and call markDelivered().

```
class FoodOrder {
  constructor(orderId, restaurantName, isDelivered) {
    this.orderId = orderId;
    this.restaurantName = restaurantName;
    this.isDelivered = isDelivered;
  }

  markDelivered() {
    this.isDelivered = true;
    console.log("Order delivered successfully!");
```

```
  }
}

let order1 = new FoodOrder(101, "Pizza House", false);

order1.markDelivered();

console.log("Order ID:", order1.orderId);
console.log("Restaurant:", order1.restaurantName);
console.log("Is Delivered:", order1.isDelivered);
```

**4. Extend your Playlist class to include a member function addSong(songTitle) that adds the song title to an array property called songs. Demonstrate by adding three song titles and displaying the updated songs list.

Hint: Initialize songs as an empty array inside the constructor.**

```
class Playlist {
  constructor(name, createdOn, isPublic) {
    this.name = name;
    this.createdOn = createdOn;
    this.isPublic = isPublic;
    this.songs = [];
  }

  addSong(songTitle) {
    this.songs.push(songTitle);
  }
}
```

```
let p1 = new Playlist("My Songs", "2026-10-14", true);


p1.addSong("Perfect");
p1.addSong("Believer");
p1.addSong("Shape of You");


console.log("Playlist:", p1.name);
console.log("Songs:", p1.songs);
```

Output:

Playlist: My Songs

Songs: ['Perfect', 'Believer', 'Shape of You']

5. Refactor your FoodOrder class so that the constructor takes an object as a parameter (with keys orderId, restaurantName, isDelivered) instead of separate arguments. Update your instantiation code to use this new constructor signature.

```
class FoodOrder {
  constructor(order) {
    this.orderId = order.orderId;
    this.restaurantName = order.restaurantName;
    this.isDelivered = order.isDelivered;
  }

  markDelivered() {
    this.isDelivered = true;
    console.log("Order delivered successfully!");
  }
}

let order1 = new FoodOrder({
```

```
  orderId: 101,
  restaurantName: "Pizza House",
  isDelivered: false
});

console.log("Order ID:", order1.orderId);
console.log("Restaurant:", order1.restaurantName);
console.log("Is Delivered:", order1.isDelivered);

order1.markDelivered();

console.log("Updated Delivery Status:", order1.isDelivered);
```