**1. Create a text file called my_fav_songs.txt and write the names of your 5 favorite songs into it using ofstream.**

Use ofstream to create my_fav_songs.txt and write five song names.

```
#include <iostream>
#include <fstream>
using namespace std;

int main() {
   ofstream file("my_fav_songs.txt");

   file << "Kesariya" << endl;
   file << "Tum Hi Ho" << endl;
   file << "Perfect" << endl;
   file << "Believer" << endl;
   file << "Apna Bana Le" << endl;

   file.close();

   cout << "Songs saved successfully!";
   return 0;
}
```

**2. Read all song names from my_fav_songs.txt using ifstream and display each song on a new line in the console.**

Use ifstream to read the songs from my_fav_songs.txt.

```
#include <iostream>
#include <fstream>
#include <string>
using namespace std;

int main() {
   ifstream file("my_fav_songs.txt");
   string song;

   while (getline(file, song)) {
      cout << song << endl;
   }

   file.close();
   return 0;
}
```

**3. Modify your code to append a new song name entered by the user to my_fav_songs.txt without overwriting the existing list.<br><br>Hint: Open the file in append mode using ofstream.**

Use ios::app to add a new song at the end of the file.

```
#include <iostream>
#include <fstream>
#include <string>
using namespace std;
```

```
int main() {
   ofstream file("my_fav_songs.txt", ios::app);
   string song;

   cout << "Enter a new song name: ";
   getline(cin, song);

   file << song << endl;
   file.close();

   cout << "New song added successfully!";
   return 0;
}
```

**4. Build a Flipkart-style wishlist tracker: ask the user to enter 3 product names and prices, save them to a file called wishlist.txt, then read the file and display each product with its price.**

Enter three product names and their prices, save them in wishlist.txt, and then display the saved products.

```
#include <iostream>
#include <fstream>
#include <string>
using namespace std;

int main() {
   ofstream file("wishlist.txt");
   string name;
```

```
    float price;

    for (int i = 1; i <= 3; i++) {
        cout << "Enter product name: ";
        getline(cin, name);

        cout << "Enter product price: ";
        cin >> price;
        cin.ignore();

        file << name << " - Rs. " << price << endl;
    }

    file.close();

    ifstream readFile("wishlist.txt");
    string product;

    cout << "\n--- My Wishlist ---\n";

    while (getline(readFile, product)) {
        cout << product << endl;
    }

    readFile.close();
    return 0;
}
```

**5. Given a file called insta_followers.txt containing Instagram usernames (one per line), write a program to count and display the total number of followers listed in the file.<br><br>Constraint: Do not use any array or vector to store the names—just count as you read.**

Assume insta_followers.txt already contains one username per line. This program counts usernames without using an array or vector.

```
#include <iostream>
#include <fstream>
#include <string>
using namespace std;

int main() {
  ifstream file("insta_followers.txt");
  string username;
  int count = 0;

  if (!file) {
    cout << "File not found!";
    return 1;
  }

  while (getline(file, username)) {
    if (!username.empty()) {
      count++;
    }
  }
```

```
    cout << "Total followers: " << count;


    file.close();
    return 0;
}
```

Example file: insta_followers.txt

```
virat_kohli
dhruv_123
rohit_sharma
hardik_pandya
```

Output:

```
Total followers: 4
```