

R (programming language)

R is an open source programming language and software environment for statistical computing and graphics that is supported by the R Foundation for Statistical Computing.^[6] The R language is widely used among statisticians and data miners for developing statistical software^[7] and data analysis.^[8] Polls, surveys of data miners, and studies of scholarly literature databases show that R's popularity has increased substantially in recent years.^[9]

R is a GNU package.^[10] The source code for the R software environment is written primarily in C, Fortran, and R.^[11] R is freely available under the GNU General Public License, and pre-compiled binary versions are provided for various operating systems. While R has a command line interface, there are several graphical front-ends available.^[12]

1 History

R is an implementation of the S programming language combined with lexical scoping semantics inspired by Scheme.^[13] S was created by John Chambers while at Bell Labs. There are some important differences, but much of the code written for S runs unaltered.^[14]

R was created by Ross Ihaka and Robert Gentleman^[15] at the University of Auckland, New Zealand, and is currently developed by the *R Development Core Team*, of which Chambers is a member. R is named partly after the first names of the first two R authors and partly as a play on the name of S.^[16] The project was conceived in 1992, with an initial version released in 1995 and a stable beta version in 2000.^{[17][18][19]}

2 Statistical features

R and its libraries implement a wide variety of statistical and graphical techniques, including linear and nonlinear modeling, classical statistical tests, time-series analysis, classification, clustering, and others. R is easily extensible through functions and extensions, and the R community is noted for its active contributions in terms of packages. Many of R's standard functions are written in R itself, which makes it easy for users to follow the algorithmic choices made. For computationally intensive tasks, C, C++, and Fortran code can be linked and called at run time. Advanced users can write C, C++,^[20]

Java,^[21] .NET^[22] or Python code to manipulate R objects directly.^[23] R is highly extensible through the use of user-submitted packages for specific functions or specific areas of study. Due to its S heritage, R has stronger object-oriented programming facilities than most statistical computing languages. Extending R is also eased by its lexical scoping rules.^[24]

Another strength of R is static graphics, which can produce publication-quality graphs, including mathematical symbols. Dynamic and interactive graphics are available through additional packages.^[25]

R has Rd, its own LaTeX-like documentation format, which is used to supply comprehensive documentation, both on-line in a number of formats and in hard copy.^[26]

3 Programming features

R is an interpreted language; users typically access it through a command-line interpreter. If a user types 2+2 at the R command prompt and presses enter, the computer replies with 4, as shown below:

```
> 2+2 [1] 4
```

This calculation is interpreted as the sum of two single-element vectors, resulting in a single-element vector. The prefix [1] indicates that the list of elements following it on the same line starts with the *first* element of the vector (a feature that is useful when the output extends over multiple lines).

Like other similar languages such as APL and MATLAB, R supports matrix arithmetic. R's data structures include vectors, matrices, arrays, data frames (similar to tables in a relational database) and lists.^[27] R's extensible object system includes objects for (among others): regression models, time-series and geo-spatial coordinates. The scalar data type was never a data structure of R.^[28] Instead, a scalar is represented as a vector with length one.^[29]

R supports procedural programming with functions and, for some functions, object-oriented programming with generic functions. A generic function acts differently depending on the classes of arguments passed to it. In other words, the generic function dispatches the function (method) specific to that class of object. For example, R has a generic print function that can print almost every class of object in R with a simple print(objectname)

syntax.^[30]

Although used mainly by statisticians and other practitioners requiring an environment for statistical computation and software development, R can also operate as a **general matrix calculation** toolbox – with performance benchmarks comparable to **GNU Octave** or **MATLAB**.^[31] Arrays are stored in column-major order.^[32]

4 Packages

The capabilities of R are extended through user-created *packages*, which allow specialized statistical techniques, graphical devices (such as the **ggplot2** package developed by **Hadley Wickham**), import/export capabilities, reporting tools (**knitr**, **Sweave**), etc. These packages are developed primarily in R, and sometimes in **Java**, **C**, **C++**, and **Fortran**.

A core set of packages is included with the installation of R, with more than 10,500 additional packages (as of April 2017) available at the Comprehensive R Archive Network (CRAN),^[33] **Bioconductor**, **Omegahat**,^[34] **GitHub**, and other repositories.^[35]

The “Task Views” page (subject list) on the CRAN website^[36] lists a wide range of tasks (in fields such as Finance, Genetics, High Performance Computing, Machine Learning, Medical Imaging, Social Sciences and Spatial Statistics) to which R has been applied and for which packages are available. R has also been identified by the FDA as suitable for interpreting data from clinical research.^[37]

Other R package resources include Crantastic, a community site for rating and reviewing all CRAN packages, and R-Forge, a central platform for the collaborative development of R packages, R-related software, and projects. R-Forge also hosts many unpublished beta packages, and development versions of CRAN packages.^{[38][39]}

The **Bioconductor** project provides R packages for the analysis of genomic data, such as **Affymetrix** and **cDNA microarray** object-oriented data-handling and analysis tools, and has started to provide tools for analysis of data from next-generation **high-throughput sequencing** methods.^[40]

5 Milestones

A list of changes in R releases is maintained in various “news” files at CRAN.^[41] Some highlights are listed below for several major releases.

6 Interfaces

The most-commonly used graphical **integrated development environment** for R is **RStudio**. A similar development interface is **R Tools for Visual Studio**.

Interfaces with more of a point-and-click approach include **Rattle GUI**, **R Commander**, and **RKward**.

Some of the more common editors with varying levels of support for R include: **Eclipse**,^[46] **Emacs** (**Emacs Speaks Statistics**), **Kate**,^[47] **LyX**,^[48] **Notepad++**,^[49] **WinEdt**^[50], **Tinn-R**^[51].

R functionality is accessible from several scripting languages such as **Python**,^[52] **Perl**,^[53] **Ruby**,^[54] **F#**^[55] and **Julia**^[56]

7 Implementations

The main R implementation is written in R, C, and Fortran, and there are several other implementations aimed at improving speed or increasing extensibility. A closely related implementation is **pqR** (pretty quick R) by **Radford M. Neal** with improved memory management and support for automatic multithreading. **Renjin** and **FastR** are Java implementations of R for use in a Java Virtual Machine. **CXXR**, **rho**, and **Riposte**^[57] are implementations of R in **C++**. **Renjin**, **Riposte**, and **pqR** attempt to improve performance by using multiple processor cores and some form of deferred evaluation.^[58] Most of these alternative implementations are experimental and incomplete, with relatively few users, compared to the main implementation maintained by the R Development Core Team.

TIBCO built a **runtime engine** called **TERR**, which is part of **Spotfire**.^[59]

8 useR! conferences

The official annual gathering of R users is called “**useR!**”.^[60]

The first such event was **useR! 2004** in May 2004, **Vienna, Austria**.^[61] After skipping 2005, the useR conference has been held annually, usually alternating between locations in Europe and North America.^[62]

Subsequent conferences have included:^[60]

- useR! 2006, Vienna, Austria
- useR! 2007, Ames, Iowa, USA
- useR! 2008, Dortmund, Germany
- useR! 2009, Rennes, France
- useR! 2010, Gaithersburg, Maryland, USA

- useR! 2011, Coventry, United Kingdom
- useR! 2012, Nashville, Tennessee, USA
- useR! 2013, Albacete, Spain
- useR! 2014, Los Angeles, USA
- useR! 2015, Aalborg, Denmark
- useR! 2016, Stanford, California, USA
- useR! 2017, Brussels, Belgium

9 R Journal

The R Journal is the open access, refereed journal of the R project for statistical computing. It features short to medium length articles on the use, and development of R, including packages, programming tips, CRAN news, and foundation news.

10 Comparison with SAS, SPSS, and Stata

The general consensus is that R compares well with other popular statistical packages, such as SAS, SPSS, and Stata.^[63] In a comparison of all basic features for a statistical software R is heads up with the best of statistical software.

In January 2009, the *New York Times* ran an article about R gaining acceptance among data analysts and presenting a potential threat for the market share occupied by commercial statistical packages, such as SAS.^[64]

11 Commercial support for R

While R is an open source project supported by the community developing it, some companies strive to provide commercial support and/or extensions for their customers. In this section, some examples of those companies are mentioned.

In 2007, *Revolution Analytics* was founded to provide commercial support for Revolution R, its distribution of R, which also includes components developed by the company. Major additional components include: ParallelR, the R Productivity Environment IDE, RevoScaleR (for big data analysis), RevoDeployR, web services framework, and the ability for reading and writing data in the SAS file format.^[65] They also offer a distribution of R designed to comply with established IQ/OQ/PQ criteria which enables clients in the pharmaceutical sector to validate their installation of REvolution R.^[66] In 2015, Microsoft Corporation completed the acquisition of Revolution Analytics.^[67]

In October 2011, Oracle announced the *Big Data Appliance*, which integrates R, Apache Hadoop, Oracle Linux, and a NoSQL database with the Exadata hardware.^[68] Oracle R Enterprise^[69] is now one of two components of the “Oracle Advanced Analytics Option”^[70] (the other component is Oracle Data Mining).

IBM offers support for in-Hadoop execution of R,^[71] and provides a programming model for massively parallel in-database analytics in R.^[72]

Other major commercial software systems supporting connections to or integration with R include: JMP,^[73] Mathematica,^[74] MATLAB,^[75] Pentaho,^[76] Spotfire,^[77] SPSS,^[78] Statistica,^[79] Platform Symphony,^[80] SAS,^[81] Tableau Software,^[82] Esri ArcGis,^[83] Dundas^[84] and Statgraphics.^[85]

Tibco offers a runtime version R as a part of Spotfire.^[86]

12 Notable uses

FiveThirtyEight, a political prognosticator, used R to model the chances of the 2008 presidential election, 2010 midterm elections, 2012 presidential election, 2014 midterm elections, and 2016 presidential elections.

Further, R is used by both the Democratic National Committee and the Republican National Committee in order to identify potential voters, and manage efforts to get more people to vote. These were used by Hillary Clinton and Donald Trump, through the companies Cambridge Analytica and Ada.

13 Examples



13.1 Basic syntax

The following examples illustrate the basic syntax of the language and use of the command-line interface.

In R, the widely preferred^[87] assignment operator is an arrow made from two characters <-, although = can be used instead.^[88]

```
> x <- c(1,2,3,4,5,6) # Create ordered collection (vector)
> y <- x^2 # Square the elements of x
> print(y) # print (vector) y
[1] 1 4 9 16 25 36
> mean(y) # Calculate average (arithmetic mean) of (vector) y; result is scalar
[1] 15.16667
> var(y) # Calculate sample variance
[1] 178.9667
> lm_1 <- lm(y ~ x) # Fit a linear regression model "y = f(x)" or "y = B0 + (B1 * x)" # store the results as lm_1
> print(lm_1) # Print the model from the (linear model object) lm_1
Call: lm(formula = y ~ x)
Coefficients: (Intercept) x -9.333 7.000
> summary(lm_1) # Compute and print statistics for the fit
# of the (linear model object) lm_1
Call: lm(formula = y ~ x)
Residuals: 1 2 3 4 5 6 3.3333 -0.6667 -2.6667 -2.6667 -0.6667 3.3333
Coefficients: Estimate
```

```
Std. Error t value Pr(>|t|) (Intercept) -9.3333 2.8441
-3.282 0.030453 * x 7.0000 0.7303 9.585 0.000662
*** --- Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05
'.' 0.1 '.' 1 Residual standard error: 3.055 on 4 degrees
of freedom Multiple R-squared: 0.9583, Adjusted
R-squared: 0.9478 F-statistic: 91.88 on 1 and 4 DF,
p-value: 0.000662 > par(mfrow=c(2, 2)) # Request 2x2
plot layout > plot(lm_1) # Diagnostic plot of regression
model
```



13.2 Structure of a function

The ease of function creation by the user is one of the strengths of using R. Objects remain local to the function, which can be returned as any data type.^[89] Below is an example of the structure of a function:

```
functionname <- function(arg1, arg2, ... ){ # declare
name of function and function arguments statements #
declare statements return(object) # declare object data
type } sumofsquares <- function(x){ # a user-created
function return(sum(x^2)) # return the sum of squares
of the elements of vector x }
```

```
> sumofsquares(1:3) [1] 14
```

13.3 Mandelbrot set

Short R code calculating **Mandelbrot set** through the first 20 iterations of equation $z = z^2 + c$ plotted for different complex constants c . This example demonstrates:


- use of community-developed external libraries (called packages), in this case caTools package

Normal Q-Q

```
install.packages("caTools") # install external package
library(caTools) # external package providing write.gif
function jet.colors <- colorRampPalette(c("#00007F",
"blue", "#007FFF", "cyan", "#7FFF7F", "yellow",
"#FF7F00", "red", "#FF0000")) dx <- 400 # de-
fine width dy <- 400 # define height C <- complex(
1, real=rep(seq(-2.2, 1.0, length.out=dx), each=dy ),
imag=rep(seq(-1.2, 1.2, length.out=dy), dx ) ) C <-
matrix(C, dy, dx) # reshape as square matrix of complex
numbers Z <- 0 # initialize Z to zero X <- array(0,
c(dy, dx, 20)) # initialize output 3D array for (k in 1:20)
{ # loop with 20 iterations Z <- Z^2+C # the central
difference equation X[,k] <- exp(-abs(Z)) # capture
results } write.gif(X, "Mandelbrot.gif", col=jet.colors,
delay=900)
```

Theoretical Quantiles

Residuals vs Leverage



14 See also

- Comparison of numerical analysis software
- Comparison of statistical packages
- List of numerical analysis software
- List of statistical packages
- Programming with Big Data in R (pbdR)^[90]
- Rmetrics

15 References

- [1] Hornik, Kurt (November 26, 2015). "R FAQ". *The Comprehensive R Archive Network*. 2.1 What is R?. Retrieved 2015-12-06.
- [2] Ihaka, Ross (1998). *R : Past and Future History* (PDF) (Technical report). Statistics Department, The University of Auckland, Auckland, New Zealand.
- [3] "R News". CRAN. Retrieved 22 April 2017.
- [4] "R license". r-project. Retrieved 6 June 2016.
- [5] "Introduction". *The Julia Manual*. Read the Docs. Retrieved 2016-12-07.
- [6] R language and environment
 - Hornik, Kurt (November 26, 2015). "R FAQ". *The Comprehensive R Archive Network*. 2.1 What is R?. Retrieved 2015-12-06.
- R Foundation
 - Hornik, Kurt (November 26, 2015). "R FAQ". *The Comprehensive R Archive Network*. 2.13 What is the R Foundation?. Retrieved 2015-12-06.
- The R Core Team asks authors who use R in their data analysis to cite the software using:
 - R Core Team (2016). R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. URL <http://www.R-project.org/>.
- [7] widely used
 - Fox, John & Andersen, Robert (January 2005). "Using the R Statistical Computing Environment to Teach Social Statistics Courses" (PDF). Department of Sociology, McMaster University. Retrieved 2006-08-03.
 - Vance, Ashlee (2009-01-06). "Data Analysts Captivated by R's Power". *New York Times*. Retrieved 2009-04-28. R is also the name of a popular programming language used by a growing number of data analysts inside corporations and academia. It is becoming their lingua franca...
- [8] Vance, Ashlee (2009-01-06). "Data Analysts Captivated by R's Power". *New York Times*. Retrieved 2009-04-28. R is also the name of a popular programming language used by a growing number of data analysts inside corporations and academia. It is becoming their lingua franca...
- [9] R's popularity
 - David Smith (2012); *R Tops Data Mining Software Poll*, Java Developers Journal, May 31, 2012.
 - Karl Rexer, Heather Allen, & Paul Gearan (2011); *2011 Data Miner Survey Summary*, presented at Predictive Analytics World, Oct. 2011.
 - Robert A. Muenchen (2012). "The Popularity of Data Analysis Software".
 - Tippmann, Sylvia (29 December 2014). "Programming tools: Adventures with R". *Nature*. **517**: 109–110. doi:10.1038/517109a.
- [10] GNU project
 - "GNU R". Free Software Foundation (FSF) Free Software Directory. 19 July 2010. Retrieved 13 November 2012.
 - R Project (n.d.). "What is R?". Retrieved 2009-04-28.
- [11] "Wrathematics" (27 August 2011). "How Much of R Is Written in R". librestats. Retrieved 2011-12-01.
- [12] "7 of the Best Free Graphical User Interfaces for R". *linuxlinks.com*. Retrieved 9 February 2016.
- [13] Morandat, Frances; Hill, Brandon; Osvald, Leo; Vitek, Jan (2012). "Evaluating the design of the R language: objects and functions for data analysis" (PDF). *ECOOP'12 Proceedings of the 26th European conference on Object-Oriented Programming*. Retrieved 2016-05-17.
- [14] "R: What is R?". *R-Project*. Retrieved 7 February 2016.
- [15] Gentleman, Robert (9 December 2006). "Individual Expertise profile of Robert Gentleman". Archived from the original on 23 July 2011. Retrieved 2009-07-20.
- [16] Kurt Hornik. *The R FAQ: Why is R named R?*. ISBN 3-900051-08-9. Retrieved 2008-01-29.
- [17] "R : Past and Future History -- A Free Software Project". *cran.r-project.org*. Retrieved 2016-05-30.
- [18] "Over 16 years of R Project history". *Revolutions*. Retrieved 2016-05-30.
- [19] Ihaka, Ross. "The R Project: A Brief History and Thoughts About the Future" (PDF). *stat.auckland.ac.nz*.
- [20] Eddelbuettel, Dirk; Francois, Romain (2011). "Rcpp: Seamless R and C++ Integration". *Journal of Statistical Software*. **40** (8). doi:10.18637/jss.v040.i08.
- [21] Temple Lang, Duncan (6 November 2010). "Calling R from Java" (PDF). Nuiton. Retrieved 18 September 2013.
- [22] .NET Framework
 - "Making GUIs using C# and R with the help of R.NET".

- “R.NET homepage”.
 - Haynold, Oliver M. (April 2011). *An Rserve Client Implementation for CLI/.NET* (PDF). R/Finance 2011. Chicago, IL, USA.
- [23] Intellipaat. “Choosing between SAS, R and Python for Big Data Solution - Intellipaat Blog”. *intellipaat.com*. Retrieved 2 December 2016.
- [24] Jackman, Simon (Spring 2003). “R For the Political Methodologist” (PDF). *The Political Methodologist*. Political Methodology Section, American Political Science Association. **11** (1): 20–22. Archived from the original (PDF) on 2006-07-21. Retrieved 2006-08-03.
- [25] “CRAN Task View: Graphic Displays & Dynamic Graphics & Graphic Devices & Visualization”. The Comprehensive R Archive Network. Retrieved 2011-08-01.
- [26] “Rd format”. *hep.by*. Retrieved 9 February 2016.
- [27] Dalgaard, Peter (2002). *Introductory Statistics with R*. New York, Berlin, Heidelberg: Springer-Verlag. pp. 10–18, 34. ISBN 0387954759.
- [28] Ihaka, Ross; Gentleman, Robert (Sep 1996). “R: A Language for Data Analysis and Graphics” (PDF). *Journal of Computational and Graphical Statistics*. American Statistical Association. **5** (3): 299–314. doi:10.2307/1390807. Retrieved 2014-05-12.
- [29] “Data structures · Advanced R.”. *adv-r.had.co.nz*. Retrieved 2016-09-26.
- [30] R Core Team. “Print Values”. *R Documentation*. R Foundation for Statistical Computing. Retrieved 30 May 2016.
- [31] “Speed comparison of various number crunching packages (version 2)”. SciView. 2003. Retrieved 2007-11-03.
- [32] *An Introduction to R*, Section 5.1: Arrays. Retrieved in 2010-03 from <https://cran.r-project.org/doc/manuals/R-intro.html#Arrays>.
- [33] “The Comprehensive R Archive Network”.
- [34] “Omegahat.net”. Omegahat.net. Retrieved 2016-09-09.
- [35] packages available from repositories
- Robert A. Muenchen (2012). “The Popularity of Data Analysis Software”.
 - Tippmann, Sylvia (29 December 2014). “Programming tools: Adventures with R”. *Nature*. **517**: 109–110. doi:10.1038/517109a.
 - “Search all R packages and function manuals | Rdocumentation”. *Rdocumentation*. 2014-06-16. Retrieved 2014-06-16.
- [36] “CRAN Task Views”. *cran.r-project.org*. Retrieved 2014-07-03.
- [37] “FDA: R OK for drug trials”.
- [38] “It’s crantastic!”.
- [39] “R-Forge: Welcome”.
- [40] Huber, W; Carey, VJ; Gentleman, R; Anders, S; Carlson, M; Carvalho, BS; Bravo, HC; Davis, S; Gatto, L; Girke, T; Gottardo, R; Hahne, F; Hansen, KD; Irizarry, RA; Lawrence, M; Love, MI; MacDonald, J; Obenchain, V; Oleś, AK; Pagès, H; Reyes, A; Shannon, P; Smyth, GK; Tenenbaum, D; Waldron, L; Morgan, M (2015). “Orchestrating high-throughput genomic analysis with Bioconductor”. *Nature Methods*. Nature Publishing Group. **12** (2): 115–121. doi:10.1038/nmeth.3252. PMC 4509590 . PMID 25633503.
- [41] Changes in versions 3.0.0 onward:
- “R News”. *cran.r-project.org*. Retrieved 2014-07-03.
- Changes for earlier versions (by major release number):
- “NEWS.2”. *cran.r-project.org*. Retrieved 2017-04-08.
 - “NEWS.1”. *cran.r-project.org*. Retrieved 2017-04-08.
 - “NEWS.0”. *cran.r-project.org*. Retrieved 2017-04-08.
- [42] “Index of /src/base/R-0”.
- [43] “ANNOUNCE: CRAN”.
- [44] <https://cran.r-project.org/src/base/NEWS.0>
- [45] Peter Dalgaard. “R-1.0.0 is released”. Retrieved 2009-06-06.
- [46] Unknown. “StatET for R”.
- [47] “Syntax Highlighting”. Kate Development Team. Archived from the original on 2008-07-07. Retrieved 2008-07-09.
- [48] Paul E. Johnson and Gregor Gorjanc. “LyX with R through Sweave”. Retrieved 2017-04-04.
- [49] “NppToR: R in Notepad++”. *sourceforge.net*. 8 May 2013. Retrieved 2013-09-18.
- [50] Uwe Ligges. “RWinEdt: R Interface to 'WinEdt'”. Retrieved 2017-04-04.
- [51] “Tinn-R”. Retrieved 2017-04-04.
- [52] Gautier, Laurent (21 October 2012). “A simple and efficient access to R from Python”. Retrieved 18 September 2013.
- [53] Florent Angly. “Statistics::R - Perl interface with the R statistical program - metacpan.org”.
- [54] alexgutteridge. “GitHub - alexgutteridge/rsruby: Ruby - R bridge.”. *GitHub*.
- [55] BlueMountain Capital. “F# R Type Provider”.
- [56] <https://github.com/JuliaInterop/RCall.jl>. Missing or empty |title= (help)

- [57] Talbot, Justin; DeVito, Zachary; Hanrahan, Pat (1 January 2012). "Riposte: A Trace-driven Compiler and Parallel VM for Vector Code in R". *Proceedings of the 21st International Conference on Parallel Architectures and Compilation Techniques*. ACM: 43–52. doi:10.1145/2370816.2370825.
- [58] Neal, Radford (25 July 2013). "Deferred evaluation in Renjin, Riposte, and pqR". *Radford Neal's blog*. Retrieved 6 March 2017.
- [59] Jackson, Joab (May 16, 2013). TIBCO offers free R to the enterprise. *PC World*. Retrieved July 20, 2015.
- [60] "useR!". Retrieved from <https://www.r-project.org/conferences.html>
- [61] "useR! 2004 - The R User Conference". 27 May 2004. Retrieved 2013-09-18.
- [62] R Project (9 August 2013). "R-related Conferences". Retrieved 2013-09-18.
- [63] Burns, Patrick (27 February 2007). "Comparison of R to SAS, Stata and SPSS" (PDF). Retrieved 2013-09-18.
- [64] R as competition for commercial statistical packages
 - Vance, Ashlee (2009-01-07). "Data Analysts Are Mesmerized by the Power of Program R: [Business/Financial Desk]". *The New York Times*.
 - Vance, Ashlee (2009-01-08). "R You Ready for R?". *The New York Times*.
- [65] Morgan, Timothy Prickett (2011-02-07). "Red Hat for stats' goes toe-to-toe with SAS". *The Register*, 7 February 2011. Retrieved from http://www.theregister.co.uk/2011/02/07/revolution_r_sas_challenge/.
- [66] "Analyzing clinical trial data for FDA submissions with R". *Revolution Analytics*. January 14, 2009. Retrieved April 15, 2016.
- [67] Sirosh, Joseph. "Microsoft Closes Acquisition of Revolution Analytics". *blogs.technet.com*. Microsoft. Retrieved 2015-11-22.
- [68] Oracle Corporation's Big Data Appliance
 - Doug Henschen (2012); *Oracle Makes Big Data Appliance Move With Cloudera*, InformationWeek, January 10, 2012.
 - Jaikumar Vijayan (2012); *Oracle's Big Data Appliance brings focus to bundled approach*, ComputerWorld, January 11, 2012.
 - Timothy Prickett Morgan (2011); *Oracle rolls its own NoSQL and Hadoop Oracle rolls its own NoSQL and Hadoop*, The Register, October 3, 2011.
- [69] Chris Kanaracus (2012); *Oracle Stakes Claim in R With Advanced Analytics Launch*, PC World, February 8, 2012.
- [70] Doug Henschen (2012); *Oracle Stakes Claim in R With Advanced Analytics Launch*, InformationWeek, April 4, 2012.
- [71] "What's New in IBM InfoSphere BigInsights v2.1.2". IBM. Retrieved 8 May 2014.
- [72] "IBM PureData System for Analytics" (PDF). IBM. Retrieved 2014-05-08.
- [73] JMP (2013). "Analytical Application Development with JMP". SAS Institute Inc. Retrieved 2013-09-19.
- [74] "New in Mathematica 9: Built-in Integration with R". Wolfram. 2013. Retrieved 2013-09-18.
- [75] Henson, Robert (23 July 2013). "MATLAB R Link". The MathWorks, Inc. Retrieved 2013-09-18.
- [76] "Announcement - Data Science Pack". Pentaho Corporation. Retrieved 2017-04-20.
- [77] Gibson, Brendan (8 March 2010). "Spotfire Integration with S+ and R". Spotfire. Retrieved 2013-09-19.
- [78] Clark, Mike (October 2007). "Introduction to SPSS 16". University of North Texas Research and Statistical Support. Retrieved 19 September 2013.
- [79] StatSoft (n.d.). "Using the R Language Platform". StatSoft Inc. Retrieved 2013-09-20.
- [80] Parmar, Onkar (31 March 2011). "'R' integrated with Symphony". Platform Computing Corporation. Retrieved 2013-09-20.
- [81] SAS (11 November 2010). "Calling Functions in the R Language (SAS/IML)". Retrieved 2013-09-20.
- [82] Tableau (17 December 2013). "R is Here!". Retrieved 2015-01-29.
- [83] "Building a Bridge to the R Community". Esri. 20 July 2015. Retrieved 14 April 2016.
- [84] Dundas. "R Integrated with Dundas BI". Retrieved 2015-07-30.
- [85] "Statgraphics R Interface".
- [86] Tibco. "Unleash the agility of R for the Enterprise". Retrieved 2014-05-15.
- [87] most used assignment operator in R is <-
 - R Development Core Team. "Writing R Extensions". Retrieved 14 June 2012. [...] we recommend the consistent use of the preferred assignment operator '<-' (rather than '=') for assignment.
 - "Google's R Style Guide". Retrieved 2 June 2016.
 - Wickham, Hadley. "Style Guide". Retrieved 14 June 2012.
 - Bengtsson, Henrik (January 2009). "R Coding Conventions (RCC) – a draft". Retrieved 14 June 2012.
- [88] R Development Core Team. "Assignments with the = Operator". Retrieved 14 June 2012.
- [89] Kabacoff, Robert (2012). "Quick-R: User-Defined Functions". *statmethods.net*. Retrieved 2013-10-28.
- [90] Ostrouchov, G., Chen, W.-C., Schmidt, D., Patel, P. (2012). "Programming with Big Data in R".

16 External links

- [Official website of the R project](#)
- [An Introduction to R](#)
- [R books](#), has extensive list (with brief comments) of R-related books
- [R-bloggers](#), a daily news site about R, with 10,000+ articles, tutorials and case-studies, [contributed by](#) over 450 R bloggers.
- [The R Graphical Manual](#), a collection of R graphics from all R packages, and an index to all functions in all R packages
- [R seek](#), a custom frontend to Google search engine, to assist in finding results related to the R language
- [R Graph Gallery](#)

17 Text and image sources, contributors, and licenses

17.1 Text

- **R (programming language)** *Source:* [https://en.wikipedia.org/wiki/R_\(programming_language\)?oldid=778144192](https://en.wikipedia.org/wiki/R_(programming_language)?oldid=778144192) *Contributors:* Edward, Michael Hardy, Ixf64, Dcljr, Tomi, Minesweeper, Den fjättrade ankan~enwiki, Glenn, Ehn, Andrewman327, Maximus Rex, Jeffrey Smith, Omegatron, Joy, Dbabbitt, Penfold, Phil Boswell, Robbot, Schutz, Gak, RedWolf, Phatsphere, Rursus, Robinh, Giftlite, Lupin, Xerxes314, Dmb000006, Muzzle, RScheiber, Sdfisher, Jason Quinn, Macrakis, Adam McMaster, Neil, Mmm~enwiki, CryptoDerk, Fangz, Beland, OverlordQ, OwenBlacker, Two Bananas, Vsb, Andreas Kaufmann, Thorwald, Rich Farmbrough, Hidaspal, Lulu of the Lotus-Eaters, Gronky, Bender235, ZeroOne, Peco~enwiki, Elwikipedista~enwiki, Danakil, Lswartz, Etz Haim, Comtebenoit, O18, Billy-mac00, Shnout, 99of9, Landroni, Storm Rider, Alansohn, Thüringer, J.Voss, Miranche, Guy Harris, Avenue, Caesura, Freek de Bruijn, Forderud, Mahanga, Karnesky, RHaworth, Ruud Koot, Urod, Jeff3000, GregorB, Biomenne, LinkTiger, Marudubshinki, RichardWeiss, Rjwilmsi, Smoe, XP1, ElfQrin, Chobot, FrankTobia, Tommylommykins, Roboto de Ajvol, YurikBot, Wavelength, Hairy Dude, Waitak, RussBot, Arado, Manop, Friedfish, Brec, Brandon, TDogg310, Tony1, Leotohill, Maechler, Gzabers, Zeno McDohl, Fmccown, Cedar101, Belgrano~enwiki, Zeileis, JLaTondre, Gesslein, Andrew73, Jt14den, Deepdraft, SmackBot, Jasy jatere, Georgeryp, Lawrencekhoo, Jt-neill, Stifle, Djhurio, Kslays, MclD, Gilliam, Chris the speller, Thumperward, Zven, Hongooi, Exaudio, Martin Bean, Anthon.Eff, Rada-gast83, Krexer, Derek R Bullamore, Mwtowes, Where, Blauwkoe, Gaborgulya, Kuru, Soumya92, Tomhubbard, Tim bates, Arunrajmohan, JorisvS, Niczar, Chrisch, Vonnegutia, Julthep, Aarktica, GhostInTheMachine, Abalter, Kvng, Jpag87a, Pelotas, FatalError, Raysonho, Chrike, ShelfSkewed, Sanspeur, Cydebot, Ntsimp, Bsdaemon, YorkBW, Adailton, Argymeg, MicahElliott, Talgalili, Adamkriesberg, N5iln, Catsmoke, Davidhorman, Sherbrooke, Shyam.sundaram, Gioto, BenJWoodcroft, Lovibond, Ephery, VictorAnyakin, NapoliRoma, Dsp13, Grokmenow, Albany NY, DRHagen, Jarekt, Dlautzenheiser, Albmont, Jdfreivald, Bequw, Baccyak4H, Cardamon, Stan3, Ftier-cel, Gwern, Mjcrow, CommonsDelinker, Chtfn, Doc marseille, Abeliavsky, DomBot, Hmendonca, Faridani, McCsly, GongYi, Ammon86, Mutlay, Ischemia, RonFredericks, BB-Froggy, Sergivs-en, VolkovBot, Hitchiker42, Jim.Callahan,Orlando, Redgecko, Vrac, Markmat, TXiKiBoT, Oshwah, Achristoffersen, Id4abel, Bikestats, Genium, Wiae, Winterschlaefel, Belamp, Ceranthor, ThorstenStaerk~enwiki, SieBot, GJwkayon, Jerryobject, Vantey, Masgotatkaca, Free Software Knight, Rafesq, The Someday, Int21h, Svick, Fmark, Melcombe, Mrfebruary, ShelleyAdams, ImageRemovalBot, ClueBot, K14m-AWB, JustinClarkCasey, Iwannacrib, Tgirke, Excirial, Keoomsby, Cal-imo, Eddelbuettel~enwiki, Northernhenge, Sinashahandeh, Prozaker, Razorflame, Aitias, Bluemaster, Inductionheating, Qwfp, Johnuniq, Joswig, SF007, Xavierstuvw, DumZiBoT, Sunsetsky, XLinkBot, Ovis23, SilvononBot, MystBot, Neil.rubens, Dsimic, G2525, Tayste, Addbot, Pyerre, Mortense, GhettoBlast, DOI bot, Mhahsler, Fgnievinski, Ironholds, Calinucs, MrOllie, Download, Protonk, Ginos-bot, Vyom25, Numbo3-bot, Jarble, Alfie66, Margin1522, Lukas-bot, Yobot, Ptbogourou, TheMightyPirate, AnomieBOT, Jim1138, Tucoxn, Chuckiesdad, Neuwirthe, CeciliaPang, MaterialsScientist, Citation bot, Rcottiss, Lixiaoxu, Xqbot, Yonniet, Ohspite, Nonfamous, Purnank, Abishekravi, Ehsan.azhdari, Rstatx, BD597, MuffledThud, Constructive editor, Sudheerrao07, FrescoBot, Mark Renier, W Now-icki, ChryZ MUC, Schalice, Deadlyspider, Citation bot 1, Shiki2, Winterst, Tom.Reding, Bhinchliffe, Skyerise, Bob.Muenchen, Spasha, RedBot, MastiBot, Z, Mj, Full-date unlinking bot, Userask, Statr, Harrietaulcombe, FoxBot, TobeBot, Angelicapple, Emrahertr, Kmet-ler, Callanec, Panchoh, Persian knight shiraz, 777sms, Amkilpatrick, Diannaa, StatisticalSoftware, Melnakeeb, Jfmantis, RjwilmsiBot, Sulthan90, ButOnMethlts, Larry.europe, Zoolium, EmausBot, PrisonerOffice, Angrytoast, Xingmowang, Kercker, Efprime, GoingBatty, Peaceray, Mehmetzelim, Gimmetoo, JaeDyWolf, The Mysterious El Willstro, Dedwen, Dcirovic, DavidMCEddy, Bilbo571, H3llBot, Goodybuddy, Faidherbard, Lcnbst, Shootji, Kylecovington, Hfang80, Donner60, AlexBehrman, Macwhiz, Eliavs, Mister Mormon, Anup-parikh, ClueBot NG, Mathstat, Wikidilworth, Tdynes, Widr, Luke145, Timflute, Helpful Pixie Bot, RobSeb, Hapli, BG19bot, Bluemonty, Marcocapelle, Diogopro, Slowtortoise4, T.seppelt, BattyBot, Cyberbot II, Garamond Lethe, Dexbot, 4nn112, Codename Lisa, JustinEd-itor, R-project, AldezD, SFK2, MartinMichlmayr, Richierocks, Tech412, Bradhill14, SPECIFICO, Josiasseb, Mark viking, Bio7RCP, Denislopez, François Robere, Scottkosty (usurped), Newystats, Blythwood, Comp.arch, Evolution and evolvability, Cvanca02, Dame Etna, Wccsnow, Paul2520, Lampertkm, ScotXW, Pablodim91, Renkun-ken, Mathias.brandewinder, Alphonse.fisch, Oecology, Jayakumar RG, Lizmango, Aymannmogh, Lodop, Brandon ibm, Asdklf, JC713, Oiyarbepsy, Ananimo, Sdxu, Selva.prabhakaran, 20202020, KasparBot, Pankajtripathi94, EnriqueWikiEdit, Amithnagaraj, Kiwipidae, Msteejaert, Krisgenther, Urlaub, Sjnam, The Terrible Toes, Alea iacta est it, Bobbyhorvath133, Nnnfff, Httpheaders, RobbieIanMorrison, GreenC bot, Jaspervanm, Ericteung, SqlWaldorf, Bender the Bot, Vin-cent.Wu, Niuman Comas, Mitali pandey, Yangyi123, Beguiler, GrryT, Mikhail arkipov and Anonymous: 365

17.2 Images

- **File:8bit-dynamiclist_(reversed).gif** *Source:* https://upload.wikimedia.org/wikipedia/commons/c/cc/8bit-dynamiclist_%28reversed%29.gif *License:* CC-BY-SA-3.0 *Contributors:* This file was derived from: 8bit-dynamiclist.gif *Original artist:* Seahen, User:Rezonansoway
- **File:Ambox_important.svg** *Source:* https://upload.wikimedia.org/wikipedia/commons/b/b4/Ambox_important.svg *License:* Public do-main *Contributors:* Own work, based off of Image:Ambox scales.svg *Original artist:* Dsmurat (talk · contribs)
- **File:Commons-logo.svg** *Source:* <https://upload.wikimedia.org/wikipedia/en/4/4a/Commons-logo.svg> *License:* PD *Contributors:* ? *Original artist:* ?
- **File:Free_and_open-source_software_logo_(2009).svg** *Source:* https://upload.wikimedia.org/wikipedia/commons/3/31/Free_and_open-source_software_logo_%282009%29.svg *License:* Public domain *Contributors:* FOSS Logo.svg *Original artist:* Free Software Portal Logo.svg (FOSS Logo.svg): ViperSnake151
- **File:Lock-green.svg** *Source:* <https://upload.wikimedia.org/wikipedia/commons/6/65/Lock-green.svg> *License:* CC0 *Contributors:* en:File:Free-to-read_lock_75.svg *Original artist:* User:Trappist the monk
- **File:Mandelbrot_Creation_Animation.gif** *Source:* https://upload.wikimedia.org/wikipedia/commons/a/a7/Mandelbrot_Creation_Animation.gif *License:* GFDL *Contributors:* Own work *Original artist:* Jarekt
- **File:Plots_from_lm_example.svg** *Source:* https://upload.wikimedia.org/wikipedia/commons/f/f6/Plots_from_lm_example.svg *License:* CC BY-SA 3.0 *Contributors:* travail personnel (own work), SVG conversion from File:Plots from lm example.png *Original artist:* Calimo
- **File:Wikibooks-logo-en-noslogan.svg** *Source:* <https://upload.wikimedia.org/wikipedia/commons/d/df/Wikibooks-logo-en-noslogan.svg> *License:* CC BY-SA 3.0 *Contributors:* Own work *Original artist:* User:Bastique, User:Ramac et al.

- **File:Wikibooks-logo.svg** *Source:* <https://upload.wikimedia.org/wikipedia/commons/f/fa/Wikibooks-logo.svg> *License:* CC BY-SA 3.0 *Contributors:* Own work *Original artist:* User:Bastique, User:Ramac et al.
- **File:Wikiversity-logo-Snorky.svg** *Source:* <https://upload.wikimedia.org/wikipedia/commons/1/1b/Wikiversity-logo-en.svg> *License:* CC BY-SA 3.0 *Contributors:* Own work *Original artist:* Snorky

17.3 Content license

- Creative Commons Attribution-Share Alike 3.0