

## Practical -1

**Aim:** study of basic network command and network configuration command

### 1) Pathping:-

Pathping provides information about network latency and network loss at intermediate hops between a source address and destination address.

Pathping command has included many options as under

```

C:\Users\Dharmesh>pathping

Microsoft Windows [Version 10.0.17763.557]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Users\Dharmesh>pathping

Usage: pathping [-g host-list] [-h maximum_hops] [-i address] [-n]
               [-p period] [-q num_queries] [-w timeout]
               [-4] [-6] target_name

Options:
  -g host-list      Loose source route along host-list.
  -h maximum_hops  Maximum number of hops to search for target.
  -i address        Use the specified source address.
  -n               Do not resolve addresses to hostnames.
  -p period         Wait period milliseconds between pings.
  -q num_queries    Number of queries per hop.
  -w timeout        Wait timeout milliseconds for each reply.
  -4               Force using IPv4.
  -6               Force using IPv6.

C:\Users\Dharmesh>

```

Use of pathping:

```


C:\Users\Admin>pathping www.google.com

Tracing route to www.google.com [172.217.160.164]
over a maximum of 30 hops:
  0  407-B-15 [172.16.3.190]
  1  172.16.0.1
  2  172.24.195.242
  3  * * *
Computing statistics for 50 seconds...
Hop  RTT      Source to Here   This Node/Link   Address
  0                               0/ 100 = 0%      407-B-15 [172.16.3.190]
  1    0ms      0/ 100 = 0%      0/ 100 = 0%      172.16.0.1
  2   17ms      3/ 100 = 3%      0/ 100 = 0%      172.24.195.242
Trace complete.

```

**2) Ping:**

Ping is a computer network administration software utility used to test the reachability of a host on an Internet Protocol (IP) network. It is available for virtually all operating systems that have networking capability, including most embedded network administration software.



```

C:\Users\Dharmesh>ping www.edmodo.com

Pinging www.edmodo.com [34.214.175.43] with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 34.214.175.43:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Users\Dharmesh>

```

**3) Tracert (Trace Root):**

Tracert is a command which can show you the path a packet of information takes from your computer to one you specify. It will list all the routers it passes through until it reaches its destination, or fails to and is discarded. In addition to this, it will tell you how long each hop from router to router takes.



```

C:\Users\Admin>tracert www.google.com

Tracing route to www.google.com [172.217.160.164]
over a maximum of 30 hops:
  0  <1 ms    <1 ms    <1 ms    172.16.0.1
  1  3 ms     2 ms     2 ms     172.24.195.242
  2  *        *        *        Request timed out.
  3  10 ms    11 ms    10 ms    74.125.48.138
  4  *        *        *        Request timed out.
  5  9 ms     9 ms     9 ms     bom05s12-in-f4.1e100.net [172.217.160.164]

Trace complete.

```

**4) IPconfig:**

Type ipconfig to run the utility with default options. The output of the default command contains the IP address, network mask, and gateway for all physical and virtual network adapters.

```

C:\Users\Admin>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::8592:dc74:9f05:6a20%17
    IPv4 Address. . . . . : 172.16.3.190
    Subnet Mask . . . . . : 255.255.240.0
    Default Gateway . . . . . : 172.16.0.1

Tunnel adapter isatap.{164AD21F-11A6-4860-B9B8-88AD2262F90F}:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : 

```

### 5) Arp (Address resolution protocol)

Arp stands for address resolution protocol. Arp is used for mapping of IP address to a physical address (MAC address) in a network. Each host and routers have their own ARP cache in which they store their ARP table.

Arp -a command is used to show the arp table for the device.

```

C:\Users\Admin>arp -a

Interface: 172.16.3.190 --- 0x11
Internet Address      Physical Address      Type
172.16.0.1            00-1a-8c-6b-76-ac     dynamic
172.16.1.166          70-5a-0f-34-46-ef     dynamic
172.16.1.186          a0-d3-c1-2d-75-68     dynamic
172.16.2.129          80-ce-62-f1-41-47     dynamic
172.16.2.157          70-5a-0f-34-47-52     dynamic
172.16.2.166          70-5a-0f-34-4d-1e     dynamic
172.16.2.173          70-5a-0f-34-47-4f     dynamic
172.16.2.215          6c-3b-e5-33-49-2e     dynamic
172.16.3.42           18-60-24-86-d8-ae     dynamic
172.16.3.62           18-60-24-87-51-fb     dynamic
172.16.3.104          e0-69-95-b2-c1-db     dynamic
172.16.3.116          e0-69-95-b2-c2-00     dynamic
172.16.3.139          e0-69-95-b2-c2-db     dynamic
172.16.3.183          18-60-24-82-79-21     dynamic
172.16.3.188          18-60-24-82-79-28     dynamic
172.16.3.248          6c-3b-e5-38-13-3b     dynamic
172.16.4.100          98-90-96-de-d0-2d     dynamic
172.16.5.63           ec-b1-d7-42-e6-9c     dynamic
172.16.6.92           10-78-d2-51-f0-e6     dynamic
172.16.6.95           10-78-d2-51-ec-a6     dynamic
172.16.6.96           10-78-d2-51-d3-a2     dynamic
172.16.6.104          10-78-d2-4e-8c-0a     dynamic
172.16.6.105          10-78-d2-4e-89-58     dynamic
172.16.6.116          10-78-d2-4e-f5-aa     dynamic
172.16.6.118          10-78-d2-51-d2-b5     dynamic
172.16.6.119          54-04-a6-f3-94-21     dynamic
172.16.6.122          10-60-4b-89-65-67     dynamic
172.16.6.125          6c-3b-e5-33-ce-97     dynamic
172.16.6.145          6c-3b-e5-38-13-1e     dynamic
172.16.6.176          6c-3b-e5-2a-75-5e     dynamic
172.16.6.178          6c-3b-e5-3e-42-bc     dynamic
172.16.8.162          70-f3-5a-da-bc-c0     dynamic
172.16.9.137          50-65-f3-1a-bd-24     dynamic
172.16.9.146          6c-3b-e5-15-9d-48     dynamic
172.16.9.155          40-61-86-87-fa-f4     dynamic
172.16.12.27          6c-3b-e5-33-76-24     dynamic
172.16.12.71          10-78-d2-52-0a-e5     dynamic
172.16.12.101         10-78-d2-4e-85-fd     dynamic
172.16.12.114         40-a8-f0-5c-50-c8     dynamic
172.16.12.215         6c-3b-e5-38-13-1f     dynamic
172.16.13.48          80-ce-62-f1-40-d8     dynamic
172.16.13.56          a0-d3-c1-2d-73-0d     dynamic
172.16.14.25          a0-d3-c1-34-3c-b3     dynamic
172.16.14.28          40-a8-f0-4f-36-64     dynamic
172.16.15.166         e0-69-95-32-a1-74     dynamic
172.16.15.167         e0-69-95-b2-c2-c8     dynamic
172.16.15.171         e0-69-95-9f-87-ca     dynamic
172.16.15.255         ff-ff-ff-ff-ff-ff     static
224.0.0.252           01-00-5e-00-00-fc     static
224.0.1.129           01-00-5e-00-01-81     static
239.255.255.250      01-00-5e-7f-ff-fa     static

```

## 6) Netstat:

Netstat is a command line TCP/IP networking utility. Netstat provides information and statistics about protocols in use and current TCP/IP network connections.

```

CA Command Prompt
(c) 2017 Microsoft Corporation. All rights reserved.

C:\Users\DC>netstat -a

Active Connections

Proto Local Address           Foreign Address         State
TCP    0.0.0.0:135              LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:445              LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:5357             LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:8733             LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:13148            LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:49664            LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:49665            LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:49666            LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:49667            LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:49668            LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:49669            LAPTOP-4E01GPFO:0      LISTENING
TCP    0.0.0.0:49670            LAPTOP-4E01GPFO:0      LISTENING
TCP    127.0.0.1:5354           LAPTOP-4E01GPFO:0      LISTENING
TCP    127.0.0.1:5939           LAPTOP-4E01GPFO:0      LISTENING
TCP    127.0.0.1:8092           LAPTOP-4E01GPFO:0      LISTENING
TCP    192.168.43.168:139       LAPTOP-4E01GPFO:0      LISTENING
TCP    192.168.43.168:65243     40.90.189.152:https     ESTABLISHED
TCP    192.168.43.168:65321     52.114.74.45:https      TIME_WAIT
TCP    192.168.43.168:65323     bingforbusiness:https   ESTABLISHED
TCP    192.168.43.168:65324     13.107.18.254:https     ESTABLISHED
TCP    192.168.43.168:65326     131.253.33.254:https    ESTABLISHED
TCP    192.168.43.168:65327     204.79.197.222:https    ESTABLISHED
TCP    [::]:135                 LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:445                 LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:5357                LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:8733                LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:13148               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:49664               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:49665               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:49666               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:49667               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:49668               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:49669               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::]:49670               LAPTOP-4E01GPFO:0      LISTENING
TCP    [::1]:49696              LAPTOP-4E01GPFO:0      LISTENING
TCP    [2405:204:8581:4094:3156:cc88:c4c5:f15b]:65273 bom07s11-in-x03:https    ESTABLISHED

```

## 7) Nslookup:

The nslookup command is a network utility program used to obtain information about internet servers. It finds name server information for domains by querying the Domain name system.

```

C:\Users\Admin>nslookup www.google.com
Server:      UnKnown
Address:     172.16.0.1

Non-authoritative answer:
Name:        www.google.com
Addresses:   2404:6800:4009:80a::2004
             172.217.160.164

```