

F.No.21-20/2011-IA.III
Government of India
Ministry of Environment, Forests & Climate Change
(IA-III Section)

Vayu Wing, 3rd Floor,
Indira Paryavaran Bhawan,
Jor Bag Road, Aliganj,
New Delhi - 110 003

Dated: 19th September, 2014

To
The Chief Executive Officer & Managing Director,
M/s Delhi Mumbai Industrial Corridor Devl. Corp. Ltd.,
Room No. 341 – B, 3rd Floor,
Hotel Ashok, Diplomatic Enclave, 50-B,
Chanakya Puri, New Delhi – 110021

Contact Person Details:

Shri Talleen Kumar,
Phone: 011-26118883
Fax: 011-26118889
Email: ceo@dmicdc.com

Subject: Environmental Clearance for development of Dholera Special investment Region (DSIR) in Gujarat by M/s Delhi Mumbai Industrial Corridor Development Corporation Limited (DMICDC) – Reg.

This has reference to your application No. DO No.CEO/DMICDC/2014/46[II] dated 20.05.2014 seeking prior Environmental Clearance for the above project under the EIA Notification, 2006. The proposal has been appraised as per prescribed procedure in the lights of provisions under the EIA Notification, 2006 on the basis of the mandatory documents enclosed with the application viz., the Form-1 & 1A, Conceptual Plans and the additional clarifications furnished in response to the observations of the Expert Appraisal Committee constituted by the competent authority in its meeting held on 30th July, 2014 - 1st August, 2014 and recommended environmental clearance for the project.

2. It is inter-alia, noted that the project involves development of Dholera Special investment Region (DSIR) in Gujarat. The DSIR lies in the Ahmedabad District and comprises of an area of 920 km² spread across 22 villages. DSIR is located about 100 km south of Ahmedabad city in Gujarat. The site touches the Gulf of Khambhat on the eastern side. Its southern boundary associates with administrative boundary of Bhavnagar district. The north and east side boundary is associated with villages of Dholera Taluka. The existing settlements have been conserved in the concept master plan and sufficient area will be left for the expansion of the settlements in the future. CRZ area been

designed to develop Tourism & Recreation development, flood mitigation infrastructure, and linear utilities. No landuse development proposed in the forest land and forest diversion proposed only for limited linear utility infrastructure with prior Forest clearance. The catchment of Sukhbhadar, Lilka, Utavali River and the existing water bodies in the area will also be conserved. About 13.3 % of the total area has been demarcated for residential land use, 12.5 % for industrial land use, 6.2 % for transportation & other zones, 30% for green space, 38 % for CRZ area. The water requirement is about 950 MLD. The short term (100 MLD) option for sourcing water need is from Pariyej and Kanewal Reservoirs of Mahi based water supply scheme. Medium term water sourcing option (~500 MLD) will make use of treated wastewater from sewage treatment plants under the Ahmadabad Municipal Corporation and Urban Development Authority and the long term (~950 MLD) option will be to use desalinated sea water (to be set up downstream of Kalpasar project or fresh water from Kalpasar project). The total wastewater generation is about 652 MLD. The wastewater generated shall be treated in sewage treatment plants (STPs) and common effluent treatment plant (CETPs) proposed within DSIR and shall be recycled for the irrigation of agricultural land, parks and gardens, green spaces, forests and industrial use. Rainwater harvesting will be promoted through Development Control Regulations, for all new constructions in DSIR. Sukhbhadar, Lilka, Utavali rivers are ephemeral river which pass through DSIR and lead to water logging of area in Monsoon. In order to moderate this river bunding, de-silting and river training are proposed as flood mitigation measures. The power demand is about 1700 MW and sourced from Gujarat Electricity Board (GEB) which proposed gas based power plants will be considered. The municipal solid waste generation from residential, commercial and institutional areas has been estimated to be 1190.3 T/day, 396.8 T/day and 198.4 T/day respectively with 51.4 T/day of industrial refuse. A waste management system has been designed in compliance with the Municipal Solid Waste Management Rules, 2000. An area of about 200 ha identified for the Integrated Waste Management Facility (IWMPF), which will have - waste collection and storage facility, waste processing facility (segregation, reuse, recycle, recovery of valuables etc.) and waste treatment and disposal facility (waste to energy, creating compost, incineration and landfill). Green belts proposed to be developed on either side of surface water streams and creeks with vegetation/landscape area development. Two water treatment plant will be provided, one near Ottariya village (for phase 1 and phase 2) and other near Hebatpur (phase 2 and phase 3).

3. The concept master plan for the proposed DSIR has been designed to develop an urban settlement with industrial and commercial zones and all associated infrastructure facilities. The industrial areas have been planned to have better access to the road and rail links and away from residential areas. The industrial mix proposed for DSIR shall include clusters comprising of Electronics, High Tech and Emerging Technologies, Pharmaceuticals and Biotechnology, Heavy Engineering, Automobile and Auto Ancillary Industries, General Manufacturing, Metals and Metallurgical Products, Agro and Food Processing, IT/ITES along with Tourism and Education sectors. The proposed project shall be developed in three phases of 10 year each. Phase 1, 2 & 3 shall comprise of urban area of 11,505 Ha, 12,045 Ha and 10,147 Ha respectively.

4. The above proposal was examined by EAC in its 99th meeting held on 5th – 6th April, 2011 and finalized ToR including conduct of Public Hearing. The above proposal was again examined by EAC in its 100th meeting held on 11-12th May 2011 and finalized additional ToR. Extension of validity of ToR was granted during 126th EAC meeting dated 19th - 21st September, 2013. Public Hearing conducted on 03.01.2014 at a location within the proposed DSIR, Dholera.

5. The Expert Appraisal Committee, after due consideration of the relevant documents submitted by the project proponent have recommended for the grant of Environmental Clearance for the project mentioned above, Accordingly, the Ministry hereby accords necessary Environmental Clearance for the above project as per the provisions of Environmental Impact Assessment Notification – 2006 and its subsequent amendments, subject to strict compliance of the terms and conditions as follows:

PART A - SPECIFIC CONDITIONS

I. Construction Phase

- (i) "Consent for Establishment" shall be obtained from State Pollution Control Board under Air and Water Act and a copy shall be submitted to the Ministry before start of any construction work at the site.
- (ii) The proposal will require prior clearance of NBWL if the project falls in the Eco-Sensitive Zone (ESZ).
- (iii) SPV shall be responsible for the implementation of the project and the compliance of the Environmental Clearance (EC) conditions.
- (iv) No activity shall take place in the forest area. A resolution letter shall be submitted to the Ministry by the proponent in this regard.
- (v) No industrial activity should be undertaken in the CRZ area, except the activities which are permissible in the CRZ area under CRZ Notification 2011 after taking due clearance from the concerned authority. The matter related to CRZ issues shall be considered only when the recommendation from the State CZMA is received by the Ministry.
- (vi) Each industrial unit coming up in the industrial area has to seek separate environmental clearance individually after conducting the cumulative environmental impact assessment of the entire industrial area, for which the Environmental Clearance is accorded in terms of the advice of the Ministry to the meeting. (e.g the 19th industrial unit coming up in the industrial area has to conduct the cumulative EIA studies based on environmental impact caused by all 18 industrial units which are already set up in the area including their pollution load generated (solid, liquid, gas) in the entire industrial area.). However, the integration and cumulative assessment for the EIA will be routed through the

GIDB/DMICDC or its successor entities and endorsed by them before presentation to the concerned environment clearance authority.

- (vii) Each industrial unit has to submit the layout map superimposed on the same master plan of the industrial area for which the Environmental Clearance is accorded.
- (viii) NOCs should be obtained for the abstraction of water from various sources and submitted to the Ministry before commencement of the work.
- (ix) Buffer of 200 meters should be observed from the forest area if it is existing within the proposed Investment Region.
- (x) Green cover of minimum 33% should be provided in all plots of the proposed Industrial area development.
- (xi) As per the provision mentioned at Para 7. III. Stage (3) - Public Consultation, of EIA Notification 2006, 'all projects or activities located within industrial estates or parks (item 7(c) of the Schedule) approved by the concerned authorities, and which are not disallowed in such approvals' are exempted from the process of Public consultation.
- (xii) CETPs should be set up in a phased manner to treat the waste water generated from units which do not have individual ETPs.
- (xiii) CETPs should be installed at appropriate location based on the requirement of the industrial area to treat the industrial waste water in a phased manner.
- (xiv) Efforts should be made to promote Zero Liquid Discharge for the industrial estate.
- (xv) Municipal Solid Waste treatment and disposal facilities have to be established as per MSW (M&H) Notification, 2000. There shall be 100% collection and transportation arrangements for the Municipal Solid Waste for the entire industrial area. Wherever required transfer station has to be established to achieve 100% collection and transportation. The treatment and disposal facility should be based on the state of art technology. Each MSW treatment and disposal facility shall have scientific landfill site as defined under MSW Notification 2000 for final disposal of rejects. As far as possible the quantity of rejects should be very less.
- (xvi) Rain water harvesting proposals should be made with due safeguards for ground water quality. Maximize recycling of water and utilization of rain water.

- (xvii) As committed, an Environment Management & Monitoring Cell should be constituted at the Node/city level SPV who will be responsible to monitor all the environmental parameters regularly.
- (xviii) As committed, every individual industry should have an Online Self Monitoring System for environmental parameters (both for air and water) which will be displayed within their premises and will be simultaneously integrated with systems of respective SPCBs.
- (xix) Every industrial unit should submit a half yearly monitoring report to Regional Office of this Ministry at Bhopal and MoEF&CC in New Delhi with a copy to the node/city SPV.
- (xx) Permission from MoEF&CC is required for the transfer of Environmental Clearance to the SPV.
- (xxi) Violation of any of the conditions of Environmental Clearance should lead to cancellation of permit/license of the individual industry/ and also may lead to cancellation of Environmental Clearance of the entire Industrial Area.
- (xxii) Every individual unit shall comply with the Standards laid down by Central Pollution Control Board (CPCB)/ State Government.
- (xxiii) All emission sources in the Industrial area should be provided with adequate pollution control equipment and stack height as per CPCB/MoEF&CC norms.
- (xxiv) Thick green buffers should be provided on either side of the highways and along the periphery of Industrial areas to reduce spread of dust and particulates.
- (xxv) All boilers or other similar sources should be provided with multi-cyclones or bag filters as required.
- (xxvi) The part of the industrial area identified for hi-tech agriculture should be retained for agricultural purpose.
- (xxvii) Continuous online air quality monitoring should be undertaken by the Project Proponent (PP) or its successor entities at five vulnerable locations and as per the wind direction and displayed for the awareness and control. The data should be submitted with the compliance report to the SPCB and regional office of MoEF&CC.
- (xxviii) Recycling of waste water should be employed for residential and industrial facilities and zero discharge will be followed within the industrial area.
- (xxix) Rain water should be harvested and recharging of waste water to ground should be carried out using the surface ponding method

and also through recharging pit wherever possible after proper treatment.

- (xxx) All industrial operations should have acoustic enclosure and employ noise attenuation measures.
- (xxxix) As committed, a well designed MRTS should be proposed wherever possible which will improve the connectivity and reduce load on road traffic.
- (xxxii) Roads should be planned such that traffic jams do not occur so that air emissions and noise levels from vehicle movement are minimal.
- (xxxiii) As committed, primary road network within industrial region should be provided with service lanes, parking areas, cycle paths and pedestrian walkways.
- (xxxiv) All residential areas will be within 500 meters of public transportation.
- (xxxv) All villages within the proposed corridor should be 100% covered with sewerage network followed by a state of art sewage treatment facility with arrangement for Operation and Maintenance of the facility. There should not be any open defecation. The treatment plants should run throughout the year and the effluent should be recycled for industrial/agricultural use.
- (xxxvi) Integrated Hazardous Waste Treatment and Disposal facility including incineration facility shall be established within the proposed Industrial Area.
- (xxxvii) The SPCB should monitor the Environmental Activity in the zone and should conduct regular and surprise checks as it deems fit and necessary.
- (xxxviii) Fool proof water management plan should be prepared.
- (xxxix) Roads networks and intersections with the Highway should be such that there should be a smooth movement of traffic without interruption to the highway traffic.
- (xl) Residential areas should be separated from industries and oriented away from the predominant wind direction.
- (xli) As committed, all existing villages should be retained and adequate area will be demarcated for the expansion of these villages.
- (xlii) As committed ,all red and orange category industrial development should be proposed within the dedicated industrial hub and away from the proposed residential areas and existing settlements.

- (xliii) As committed, the green category industries should be located along the periphery of industrial area facing residential areas to act as an additional buffer for the polluting industries.
- (xliv) As committed, the master plan roads of minimum 60.0 m width should be proposed along with 30.0 m wide green buffer along either side to effectively manage the traffic during the operation phase of the project.
- (xlv) As committed, the building and plumbing code shall make dual plumbing mandatory to segregate the grey water and the wastewater at outlet source of generation using two pipe system.
- (xlvi) As committed, SCADA system should be implemented for monitoring leakages in the water and effluent conveyance system.
- (xlvii) SPV shall organize information forums with industry/commercial owners.
- (xlviii) As committed, the existing canal infrastructure, if any, should be retained and the irrigation water shall not be diverted for any other activity other than agriculture.
- (xlix) As committed the management of water supply for integrated water supply management (IWSM) should be carried out using an information technology application oriented analysis, design and development.
- (l) The Integrated Water Supply management should include:
- Leak and/or loss detection.
 - Optimum scheduling of water supply network operation; and
 - Improved monitoring and control of network.
- (li) A reliable technical department for maintenance and quality control should be established.
- (lii) As various industries will have a variety of types of industrial effluent, only industrial wastewater of a predefined quality will be permitted to enter the equalization tank of the effluent treatment plant. For any kind of specific treatment, industries will need to treat industrial wastewater in their own captive wastewater treatment facilities and discharge the wastewater of predefined quality into the collection system.
- (liii) Monitoring of ground water resources will be undertaken by GIDB/SPV at periodic intervals to identify any contaminations from leak or spills.

- (liv) The water supply and wastewater lines should be colour coded to differentiate.
- (lv) A Rain Water Harvesting (RWH) Monitoring Cell should be created which will be responsible for monitoring safe recharge. Areas shall be identified for groundwater recharge and should be delineated.
- (lvi) Roof Top RWH should be made mandatory for all residential, commercial and industrial buildings and shall be monitored by the Cell.
- (lvii) CETPs should be installed at appropriate location based on the requirement of the industrial area to treat the industrial waste water in phased manner.
- (lviii) The trees selected should be native to the extent possible with three levels of vegetation covers near industrial area (shrubs and evergreen trees). About 3-6 layers of trees will be maintained along the road.
- (lix) The project should ensure that use of low sulphur fuel (i.e. HSD) or other cleaner fuel in all the combustion systems.
- (lx) All manufacturing operations to be run as a closed system allowing permissible emissions to escape to the atmosphere.
- (lxi) Chemical recover system to be installed at all plants to prevent any loss of chemical to atmosphere.
- (lxii) All the fugitive emissions from various sources should be collected through ducts or hoods and treated along with channelized emissions.
- (lxiii) Continuous monitoring equipment in the stack and suitable height of the stacks for appropriate dispersion should be ensured.
- (lxiv) Well designed scrubbers will be provided for all point sources emissions to effectively remove effluent gases.
- (lxv) Nitrogen oxide (NOx) emissions will be reduced by using low-NOx burners and optimization of fuel usage.
- (lxvi) Preventive maintenance and equipment and materials management so as to minimize opportunities for evaporative losses, and other releases of potentially toxic chemicals should be adhered to.
- (lxvii) All building construction activities should adopt environmental friendly and energy efficient techniques such as promotion of alternate source of energy, building architecture, recycled material

for building construction, energy efficient appliances and lighting etc.

- (lxviii) Prior Clearance of Central Ground Water Authority should be obtained for extraction of ground water and recharge of ground water.
- (lxix) A First Aid Room will be provided in the project both during construction and operation of the project.
- (lxx) Adequate drinking water and sanitary facilities should be provided for construction workers at the site. Provision should be made for mobile toilets. The safe disposal of waste water and solid wastes generated during the development/construction phase should be ensured.
- (lxxi) All the topsoil excavated during development/construction activities should be stored for use in horticulture/landscape development within the project site.
- (lxxii) Disposal of muck during development/construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.
- (lxxiii) Soil and ground water samples will be tested to ascertain that there is no threat to ground water quality by leaching of heavy metals and other toxic contaminants.
- (lxxiv) Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate watercourses and the dump sites for such material must be secured so that they should not leach into the ground water.
- (lxxv) The diesel generator sets to be used during development/construction phase should be low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.
- (lxxvi) The diesel required for operating DG sets shall be stored in underground tanks and if required, clearance from Chief Controller of Explosives shall be taken.
- (lxxvii) Vehicles hired for bringing construction material to the site should be in good condition and should have a pollution check certificate and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.
- (lxxviii) Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the ambient air and noise quality should be closely monitored during

development/construction phase. Adequate measures should be made to reduce ambient air and noise level during construction phase, so as to conform to the stipulated standards by CPCB/SPCB.

- (lxxix) Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September, 1999 and amended as on 27th August, 2003. (The above condition is applicable only if the project site is located within the 100 Km of Thermal Power Stations).
- (lxxx) Ready mixed concrete must be used in site development and building construction.
- (lxxxi) Storm water control and its re-use as per CGWB and BIS standards for various applications.
- (lxxxii) Water demand during development/construction should be reduced by use of pre-mixed concrete, curing agents and other best practices referred.
- (lxxxiii) Separation of grey and black water should be done by the use of dual plumbing line for separation of grey and black water.
- (lxxxiv) Fixtures for showers, toilet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.
- (lxxxv) Use of glass may be reduced by upto 40% to reduce the electricity consumption and load on airconditioning. If necessary, use high quality double glass with special reflective coating in windows.
- (lxxxvi) Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material to fulfill requirement.
- (lxxxvii) Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all airconditioned spaces while it is aspirational for non-airconditioned spaces by use of appropriate thermal insulation material to fulfill requirement.
- (lxxxviii) The approval of the competent authority shall be obtained for structural safety of the buildings due to earthquake, adequacy of fire fighting equipments, etc. as per National Building Code including protection measures from lightening etc.
- (lxxxix) Regular supervision of the above and other measures for monitoring should be in place all through the development/construction phase, so as to avoid disturbance to the surroundings.

- (xc) Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.

II. Operation Phase

- (i) The construction, installation, operation and maintenance of the Common Effluent Treatment Plan (CETP) and R.O. shall be undertaken by the DMICDC Ltd. which should be certified by an independent expert and a report in this regard should be submitted to the Ministry before the project is commissioned for operation. The CETP Trust shall be responsible for the treatment of industrial effluent as per the norms laid down by State Pollution Control Board. Treated affluent emanating from CETP shall be recycled/reused to the maximum extent possible. Treatment of 100% grey water by decentralised treatment should be done. Necessary measures should be made to mitigate the odour problem from CETP.
- (ii) All the allottees/industrialist who shall set up their industries in the above investment region shall adopt latest process and technology for minimisation of chemical waste as well as waste water. DMICDC Ltd. would undertake regular monitoring of the waste water.
- (iii) The solid waste generated should be properly collected and segregated. Wet garbage should be composted and dry/inert solid waste should be disposed off to the approved sites for land filling after recovering recyclable material.
- (iv) A temporary hazardous waste storage facility should be developed in the CETP campus by the DMICDC Ltd. This facility should be used for temporary storage of the hazardous waste before finally sending it to an approved Hazardous Waste Treatment, Storage and Disposal Facility.
- (v) Diesel power generating sets proposed as source of back up power for elevators and common area illumination during operation phase should be of enclosed type and conform to rules made under the Environment (Protection) Act, 1986. The height of stack of DG sets should be equal to the height needed for the combined capacity of all proposed DG sets. The location of the DG sets may be decided with in consultation with State Pollution Control Board.
- (vi) Noise should be controlled to ensure that it does not exceed the prescribed standards. During night time the noise levels measured at the boundary of the building shall be restricted to the permissible levels to comply with the prevalent regulations.
- (vii) The green belt of the adequate width and density preferably with local species along the periphery of the plot shall be raised so as to provide protection against particulates and noise.

- (viii) Weep holes in the compound walls shall be provided to ensure natural drainage of rain water in the catchment area during the monsoon period.
- (ix) Rain water harvesting for roof run- off and surface run- off, as plan submitted should be implemented. Before recharging the surface run off, pre-treatment must be done to remove suspended matter, oil and grease. The borewell for rainwater recharging should be kept at least 4 mts. above the highest ground water table.
- (x) The ground water level and its quality should be monitored regularly in consultation with Central Ground Water Authority.
- (xi) Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking, loading and unloading should be fully internalized and no public space should be utilized.
- (xii) A Report on the energy conservation measures confirming to energy conservation norms finalise by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R & U Factors etc and submit to the Ministry in three months time.
- (xiii) Energy conservation measures like installation of CFLs/TFLs for the lighting the areas outside the building should be integral part of the project design and should be in place before project commissioning. Use CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/rules of the regulatory authority to avoid mercury contamination. Use of solar panels may be done to the extent possible.
- (xiv) Adequate measures should be taken to prevent odour problem from solid waste processing plant and CETP.
- (xv) The building should have adequate distance between them to allow movement of fresh air and passage of natural light, air and ventilation.

PART – B. GENERAL CONDITIONS

- i) The environmental safeguards contained in the EIA Report should be implemented in letter and spirit.
- ii) Provision should be made for supply of kerosene or cooking gas and pressure cooker to the labourers during construction phase.
- iii) Six monthly monitoring reports should be submitted to the Ministry and it's Regional Office, Bhopal.

6. Officials from the Regional Office of MoEF&CC, Bhopal who would be monitoring the implementation of environmental safeguards should be given full cooperation, facilities and documents/data by the project proponents during their inspection. A complete set of all the documents submitted to MoEF&CC should be forwarded to the CCF, Regional Office of MoEF&CC, Bhopal.

7. In the case of any change(s) in the scope of the project, the project would require a fresh appraisal by this Ministry.

8. The Ministry reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environmental clearance under the provisions of the Environmental (Protection) Act, 1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.

9. All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act, 1980 and Wildlife (Protection) Act, 1972 etc. shall be obtained, as applicable by project proponents from the respective competent authorities.

10. These stipulations would be enforced among others under the provisions of Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.

11. The project proponent should advertise in at least two local Newspapers widely circulated in the region, one of which shall be in the vernacular language informing that the project has been accorded Environmental Clearance and copies of clearance letters are available with the State Pollution Control Board and may also be seen on the website of the Ministry of Environment, Forests & Climate Change at <http://www.envfor.nic.in>. The advertisement should be made within 10 days from the date of receipt of the Clearance letter and a copy of the same should be forwarded to the Regional office of this Ministry at Bhopal.

12. This Clearance is subject to final order of the Hon'ble Supreme Court of India in the matter of Goa Foundation v/s. Union of India in Writ Petition (Civil) No.460 of 2004 as may be applicable to this project.

13. Any appeal against this clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.

14. A copy of the clearance letter shall be sent by the proponent to concerned Panchayat, Zilla Parisad/Municipal Corporation, Urban Local Body and the Local NGO, if any, from whom suggestions/ representations, if any, were received while processing the proposal. The clearance letter shall also be put on the website of the company by the proponent.

15. The proponent shall upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of MoEF&CC, the respective Zonal Office of CPCB and the SPCB. The criteria pollutant levels namely; SPM, RSPM, SO₂, NO_x (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.

16. The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of EC conditions and shall also be sent to the respective Regional Offices of MoEF&CC by e-mail.


(Lalit kapur)
Director (IA-III)

Copy to:

- (1) The Principal Secretary, Department of Forests & Environment and Chairman, GCZMA, Govt. of Gujarat, Sachivalaya, Gandhinagar, Gujarat.
- (2) The Chairman, CPCB, Parivesh Bhawan, CBD-cum-Office Complex, East Arjun Nagar, Delhi - 32.
- (3) The Chairman, Gujarat State Pollution Control Board, Paryavaran Bhawan, Sector 10 A, Gandhinagar-382 010.
- (4) The Chief Conservator of Forests, Ministry of Environment and Forests, Regional Office, Western Region, Kendriya Paryavaran Bhavan, Link Road No. 3, Ravishankar Nagar, Bhopal-462016 (M.P.)
- (5) Guard File.
- (6) Monitoring Cell, MoEF.


(Lalit Kapur)
Director (IA-III)