




Introduction to React.js

- React.js is a JavaScript library used for building user interfaces (UIs) and single-page applications.
- Created by **Jordan Walke** at **Facebook**.
- Most popular JavaScript library for frontend development.

How to Download and Install Nodejs



Finish the setup




Nodejs Installation

Verify the Installation

- Type **node -v** and press Enter to check the Node.js version.
- Type **npm -v** and press Enter to check the npm version.
- Both commands should return version numbers, confirming successful installation.

Vscode Setup :

Download Extensions : **ES7 React/Redux/GraphQL/React-Native snippets**



learn before React

HTML

CSS

JAVASCRIPT

Create React App:

Create react app : [npm create vite@latest](#)

- Project name
- React
- Javascript
- `cd <ProjectName>`
- `npm install`
- `npm run dev`

[Install Bun](#) : **Bun is an npm-compatible package manager.**

`npm i -g bun`

create react app using bun

`bun create vite`

- Project name
- React
- Javascript
- `cd <ProjectName>`
- `bun install`
- `bun dev`

Error in Vscode

bun : File C:\Users\HP\AppData\Roaming\npm\bun.ps1 cannot be loaded because running scripts is disabled on this system. For more information, see

about_Execution_Policies at
<https://go.microsoft.com/fwlink/?LinkID=135170>.

At line:1 char:1

+ bun create vite

+ ~

+ CategoryInfo : SecurityError: (:) [], PSSecurityException

+ FullyQualifiedErrorId : UnauthorizedAccess fix this

Open windows powershell

1. Get-ExecutionPolicy
2. Set-ExecutionPolicy RemoteSigned -Scope CurrentUser
3. Get-ExecutionPolicy

Project Structure

- **node_modules**
 - This is the folder which contains all the **necessary libraries & dependencies by React.js**.
 - You can ignore this folder completely.
- **public**
 - This folder contains all **static files** like images, videos, fonts, etc.
- **src**
 - This **folder contains all source files** (The source directory—here your React components, JavaScript files, and CSS are stored).
 - **App.jsx**
 - The main React component that acts as the root component.
 - There is also App.css with it, which contains styles for this component.
 - **main.jsx**
 - This is the **entry point to our React.js project**, which renders the App component.

Naming

- **camelCase**
 - It is used for variables, functions/methods, properties inside objects, file names, etc.
 - Capitalization of each word **except the first** is done.
- **PascalCase**
 - It is used for component names, class names, types, etc.
 - Capitalization of **each word** is done.
- **snake_case**
 - It is not common in JavaScript but is used heavily in Python.
 - Each word is separated by “_” and is in **small letters**.
- **kebab-case**
 - It is common for file names, CSS classes, IDs, etc.
 - Each word is separated by **hyphen (-)**.

JSX & Rendering Elements :

What is JSX?

- JSX is a syntax extension for JavaScript, similar to HTML.
- It allows writing HTML elements inside JavaScript.

Components in React :

Components in React are reusable and independent pieces of code that render specific parts of a user interface. They act as building blocks, allowing developers to divide complex UIs into manageable and testable units

Types of Components

- Functional Components
- Class Components

Functional Component Example

```
Welcome() {  
    return <h1>Welcome to React!</h1>;  
}  
  
export default Welcome;
```

React Fragments :

React Fragments are a feature that allow grouping multiple elements without adding an extra node to the DOM.

```
function MyComponent() {  
    return (  
        <>  
            <h1>Hello</h1>  
            <p>World</p>  
        </>  
    );  
}
```

Props in React

What are Props?

- Props (short for properties) allow passing data between components.

```
function Greeting(props) {  
  return <h1>Hello, {props.name}!</h1>;  
}  
  
function App() {  
  return <Greeting name="PIET" />;  
}
```

State in React

What is State?

- State is used to manage component data dynamically.

Example (Using useState Hook)

```
import { useState } from 'react';  
  
function Counter() {  
  const [count, setCount] = useState(0);  
  
  return (  
    <div>  
      <p>Count: {count}</p>  
      <button onClick={() => setCount(count + 1)}>Increment</button>  
    </div>  
  );  
}
```


Handling Events in React

Event Handling in React

- Events in React are handled similarly to DOM events but follow a camelCase convention.
- Use the onClick, onChange, onSubmit, etc., attributes.

```
function ButtonClick() {  
    function handleClick() {  
        alert("Button Clicked!");  
    }  
    return <button onClick={handleClick}>Click Me</button>;  
}
```

Conditional Rendering in React

What is Conditional Rendering?

- Rendering components or elements based on conditions.
- Use if-else, ternary operators, or logical && operators.

```
function Greeting(props) {  
    return props.isLoggedIn ? <h1>Welcome Back!</h1> : <h1>Please Sign In</h1>;  
}
```

Lists and Keys in React

Rendering Lists

- Use `map()` to render arrays dynamically.
- Use a unique key prop for better performance.

```
const items = ['Apple', 'Banana', 'Cherry'];

function ItemList() {

  return (

    <ul>

      {items.map((item, index) => (

        <li key={index}>{item}</li>

      ))}

    </ul>

  );

}
```

Forms in React

Controlled Components

- Forms in React use **state** to control input values.
- `onChange` event updates state as the user types.

Example: Controlled Input

```
import { useState } from "react";

function Form() {
  const [name, setName] = useState("");
  return (
    <div>
      <input type="text" value={name}
        onChange={(e) => setName(e.target.value)} />
      <p>Hello, {name}!</p>
    </div>
  );
}
```

React Hooks

Common Hooks

- `useState()`: Manage state.
- `useEffect()`: Handle side effects.
- `useContext()`: Share state across components.

Example: `useEffect` Hook

```
import { useState, useEffect } from "react";

function Timer() {
  const [time, setTime] = useState(0);
  useEffect(() => {
    const interval = setInterval(() => setTime((prev) => prev + 1), 1000);

    }, []);

  return <p>Time: {time}s</p>;
}
```

React Router (Navigation in React)

What is React Router?

- React Router is used to handle navigation in a React app.
- It allows single-page applications (SPA) to have multiple views.

Installation

```
npm install react-router-dom
```

Basic Example

```
import { BrowserRouter as Router, Routes, Route, Link } from "react-router-dom";

function Home() {
  return <h2>Home Page</h2>;
}

function About() {
  return <h2>About Page</h2>;
}

function App() {
  return (
    <Router>
      <nav>
        <Link to="/">Home</Link> | <Link to="/about">About</Link>
      </nav>
      <Routes>
        <Route path="/" element={<Home />} />
        <Route path="/about" element={<About />} />
      </Routes>
    </Router>
  );
}

export default App;
```