

Where the integration stands today


SSORT Rev 104 now builds the ready-made rapidIncident object inside the tool itself - the relay's job shrank to authenticating, validating six vocabulary fields, and submitting. One thing still blocks every live submission: which authentication scheme RAPID actually uses.

SSORT builds rapidIncident in-tool

Relay + tests built (stub mode)

Auth scheme unconfirmed

Submission trigger point undecided



The dashboard hop and the auth barrier are two different kinds of “not done yet.” The dashed grey line is ours to decide whenever we’re ready. The dashed amber line needs IADC/Softway to answer before it can be built at all - that’s what the email on page 4 asks for.

What a report goes through, step by step

- | | | |
|---|---|-----------|
| 1 | SSORT (Rev 104) builds the report and assembles a ready-made rapidIncident object in RAPID's own field shape - dates reformatted, numbers cast, booleans as yes/no, reporter name split from the creator field. | built |
| 2 | The report is saved like any other report and picked up by the existing dashboard ingestion pipeline (same scanner as every other report type). | built |
| 3 | Something on the dashboard triggers the actual RAPID submission. Exactly what - automatic on ingest, or a manual "submit" action - is not decided yet. | undecided |
| 4 | The relay authenticates to RAPID and checks the six controlled-vocabulary fields (rig, subunit, component, manufacturer, model, observed failure) against RAPID's own cached option lists. | built |
| 5 | The relay looks up this report's id. If RAPID already issued an incident number for it, the relay updates that incident instead of creating a duplicate. | built |
| 6 | The relay authenticates and submits rapidIncident to RAPID as-is. This step cannot go live until IADC confirms which authentication scheme is real. | blocked |
| 7 | Even once auth works, RAPID can still reject or warn on a submission that's missing a field the tool doesn't capture yet - see the gaps below. | open risk |

STILL OPEN

Gaps the tool doesn't close yet

when_did_the_event_occur

Required by RAPID, but its own schema defines no property for it - likely maps to work_phase, but that's a guess until IADC confirms.

pressure_rating_unit

We think this comes from our "Affected Circuit" field (s53_bore), but that mapping isn't confirmed.

drilling_fluids_into_environment

Not captured anywhere in the tool today - a plain yes/no field needs to be added.

reporter_first_name / reporter_last_name

The tool now splits these from the report creator's name automatically. What's still open is whether RAPID requires the name to match an authorised reporter on file for that rig, or accepts free text.

Four questions going to IADC / Softway

This is the official list from the reporting-tools handoff, unchanged by the Rev 104 update - the tool now builds the incident itself, but who's allowed to submit it to RAPID is still an open question.

1

Auth scheme

Which authentication actually applies to /incident: OAuth2 (as the inbound schema states), or the API-Key + username/password + HMAC-SHA256 scheme (as the outbound spec for the same portal states)? The two disagree.

2

when_did_the_event_occur

What does this field expect, given the schema defines no property for it at all?

3

Reporter matching

Must reporter_first_name / reporter_last_name match an authorised reporter returned by GET /rigs for that rig, or is free text accepted?

4

Sandbox access

Is there a sandbox or test environment available for submission testing, and if so, what are its rate limits?

Email draft

TO iadc_dev@softway.com; mike.kucharski@iadc.org
SUBJECT RAPID-S53 auth scheme - which spec is right? (+ 3 quick ones)

Hi Mike, hi Softway team,

I'm the Technical Superintendent overseeing this on our side, not a software engineer - I've been building this integration with AI-assisted development support, so if any answer below has real implementation nuance, a plain-language note alongside the technical detail would help a lot.

We're connecting our internal well-control incident reporting tool directly to the RAPID-S53 Inbound API, so incident reports post straight into RAPID-S53 instead of being re-keyed by hand. As of our latest build, the tool itself now assembles the finished incident record in RAPID's own format before it ever reaches our relay - so the remaining open items are really about how we're allowed to authenticate and submit, not about field mapping.

Four questions, most important first:

1. Which authentication actually applies to /incident: OAuth2 (as the inbound schema states), or the API-Key + username/password + HMAC-SHA256 scheme (as the outbound documentation for the same portal states)? The two disagree, and we don't want to build against the wrong one.
2. when_did_the_event_occur is listed as required, but the schema doesn't define a property for it at all. What value and type does this field actually expect?
3. Must reporter_first_name / reporter_last_name match an authorised reporter you return from GET /rigs for that rig, or is free text accepted?
4. Is there a sandbox or test environment available so we can validate submissions before we point this at production, and if so, what are its rate limits?

Happy to jump on a call if that's easier than email, especially for question 1 - I'd rather talk it through than misread a spec. Thanks for your patience while we get this right.

Best,
Dan Plant
Technical Superintendent, Well Control Engineering
Seadrill