FacePulseRate Toolbox: Input Video and Recording Environment Recommendations

Douglas Magill October, 2020

# **Input Video Requirements and Recommendations**

#### Maximum Video Frame Size

The input videos can be up to 5000 pixels in either height or width.

# Minimum Recommended Video Length

Consider using input videos of at least 3 minutes. The skin-detection algorithm and tailored skin-segmentation algorithm use skin-color samples from the face in the video to enhance their classifications. These algorithms require a minimum number of samples to be collected in order to be activated. For videos where face detections are not readily made, a longer length will be needed. These algorithms do not need to be enabled for proper operation, but their use may improve accuracy. A warning message will indicate when these algorithms were not activated due to an insufficient number of skin-color samples.

### Maximum Video Length

There is no established maximum length, but the RAM demands for videos over 1.5 hours may cause some systems to become unstable.

Beyond the RAM used by Matlab, this function may use around 1 gibabyte of RAM for a 20-minute input video. The RAM use will gradually increase for longer videos. RAM use faciliates efficiency by reducing frame re-reading and duplicate processing. For longer videos, RAM used should be monitored to determine whether it is within desired levels. If operation becomes noticably slower, this could indicate RAM use has exceeded RAM capacity and is being allocated to the hard drive. If RAM use is undesirable, consider breaking the video down to smaller segments. The function has been tested on a system with 8 gigabytes of RAM.

# For Best Appearance of Output Video

The legend that is displayed on the output video has only been implemented for input videos with dimesions  $1280 \times 720$  or  $1920 \times 1080$  where the video is in a landscape orientation. For other cases, the legend will not be displayed.

# For Faster Operation

Faster read performance will occur when argument StartTime is less than 10% the length of the full video.

# **Recording Environment**

Although the environment cannot always be changed, skin detection and skin segmentation will be more successful in some recording environments than others.

Best recording environments:

- The face is not more than a few feet from the video camera.
- The colors of the background are distinct from the colors of the face. Skin tends to have a red hue -- this is the case across individuals with different skin colors -- so care might be taken to avoid backgrounds with colors similar to skin that also have a red hue.
- The brightness of the face is not too dark. Skin segmentation will sometimes segment out pixels that are close to black, so ensuring proper brightness in the area of the face can avoid this. Note that, assuming brightness of the face is adequate, the skin-segmentation algorithm is robust across individuals with different skin colors as no skin color would be expected to approach pure black. Cases of inadequate brightness are often the result of video cameras automatically reducing their brightness or exposure when a bright light source is present in an area of the frame other than the face. For example, lamps, windows, and solid white objects, including clothing, can sometimes lead to a video automatically reducing the brightness of the face.