

BOTTB Brisbane — Recording Plan (draft for feedback)

Multitrack split + house-mix backup, 27 Aug 2026, The Triffid. Comments to Dean Povey (dean.povey@gmail.com).

Running Order & Contacts

Soundchecks run in reverse playing order; ~10-minute changeovers between sets. Total Loss set time follows the changeover pattern (their sheet said 9:30).

Slot	Band	Soundcheck	Set time	Songs	Contact
1	Off The Record	4:00 – 4:30 pm	7:20 – 7:45 pm	6	via Dean Povey (Epsonics) dean.povey@gmail.com
2	Epsonics	3:30 – 4:00 pm	7:55 – 8:20 pm	7	Dean Povey dean.povey@gmail.com
3	The ShipRex	3:00 – 3:30 pm	8:30 – 8:55 pm	5	Scott Warren swarren1@gmail.com
4	Jumbo Band	2:30 – 3:00 pm	9:05 – 9:30 pm	6	Graham Keeling 0423113154 / grke@grke.net
5	Total Loss	2:00 – 2:30 pm	9:40 – 10:05 pm (last)	6	Alistair Sutton 0435357550 - mail@alstairsutton.com

Recorder patch — fixed core (tracks 1–16, all night)

Trk	Source (desk ch)	Trk	Source (desk ch)
1	Kick In (ch 1)	9	OH L (ch 9)
2	Kick Out (ch 2)	10	OH R (ch 10)
3	Snare Top (ch 3)	11	Bass (DI or amp mic per band) (ch 11)
4	Snare Bottom * (ch 4)	12	Guitar 1 (ch 13)
5	Hi-Hat (ch 5)	13	Keys L (ch 17)
6	Rack Tom 1 (ch 6)	14	Keys R (ch 18)
7	Rack Tom 2 (ch 7)	15	Vox 2 (ch 20)
8	Floor Tom (ch 8)	16	Vox 3 (ch 21)

Swap tracks 17–20 — re-patched on the recorder leg at each changeover

Band	Trk 17	Trk 18	Trk 19	Trk 20
Off The Record	Guitar 2 (14)	—	—	—
Epsonics	Vox 1 (19)	Vox 4 (22)	Vox 5 (23)	Keytar (24)
The ShipRex	Vox 1 (19)	Vox 4 (22)	Vox 5 (23)	Erhu (24)
Jumbo Band	Vox 1 (19)	Vox 4 (22)	Guitar 3 (15)	—
Total Loss	Guitar 2 (14)	Guitar 3 (15)	Sax (24)	—

* ShipRex set only: track 4 swaps Snare Bottom → Guitar 2 (14) — ShipRex use 21 inputs, one over the recorder, and Snare Bottom is the sacrifice. Every other band has ALL of their inputs captured. Playback / backing tracks (26–27) go to the recorder's RCA line input. Crowd/ambience is not multitracked — house-mix Zoom + camera audio. MC/host uses a band vocal mic between sets — announcements land on the recorded vox tracks.

Recording — Multitrack Split & House-Mix Backup

The videographers supply a 20-channel splitter and recorder, with a dedicated audio operator. The 20 recorded tracks are the fold-down on the previous page — the split patch is FIXED all night, same as the desk patch.

Signal path

Multitrack: stage mic/DI lines → 20-ch splitter (passive/transformer) → leg A to the venue desk/stage box, leg B to the videographers' recorder. The split is taken BEFORE the desk, so recorder channels are raw mic level — the recorder's own preamps set gain, independent of the house engineer.

Crowd / ambience: not multitracked — covered by the house-mix Zoom below and the videographers' camera audio.

House mix: desk stereo out → 2 × XLR → Zoom recorder at FOH, POST-fade — it captures the engineer's actual balance, which is the one thing the pre-desk multitrack cannot reconstruct. (A pre-fader board mix would duplicate the multitrack as a static blend — not worth a bus.) If the house engineer can spare a matrix/aux copy of L/R, take that so record level trims without touching the PA; otherwise straight off the main outs with the Zoom padded down is fine. 32-bit float or -18 dBFS nominal; it is a safety/reference, not a mix.

Where to take the split

Venue desks (per the Triffid tech pack): **Avid SC48 at FOH** (15 m from the downstage edge) and a **second SC48 for monitors**. The SC48s offer **no usable digital/multitrack outputs** — there is no desk-capture fallback. Everything is a PRE-DESK analog split: both consoles take analog inputs, so the house already splits the stage lines for FOH + monitors, and our splitter inserts at that analog split point before either desk. Confirm with the venue PM (Jeff Hahn, production@thetriffid.com.au) whether that point lives side-stage at monitor world (recorder + operator side-stage) or where the FOH tails land (recorder at FOH) — either way it is upstream of the desks. Wing space is tight (2 m² USL / 2×3 m USR) — a side-stage recorder position needs advancing too.

Backing tracks: the recorder's RCA line input takes the playback feed (ch 26–27 source, line level) — so Eponics' video audio is captured without spending mic tracks. Full drum kit is covered: both racks + floor per the house kit.

Per-band recorder changes (without touching FOH)

Tracks 1–16 never move. Tracks 17–20 are re-patched per the swap table at each changeover — **on the RECORDER LEG ONLY**: each line runs mic → splitter in → thru → desk, so the desk end never moves and FOH keeps identical channels all night. Moves per changeover: into Eponics 4, into ShipRex 1 (the track-4 Snare Bottom → Guitar 2 borrow), into Jumbo 3, into Total Loss 4 — a couple of minutes each inside the 10-minute changeover, then line-check just the moved tracks. This captures EVERY input for every band except ShipRex's Snare Bottom (they use 21 inputs, one over). Bring F–F XLR barrels; never re-patch mid-set.

Schedule & venue asks

- **Access:** soundchecks start at **2:00 pm** (Total Loss), so the split must be patched BEFORE then — recordist in by ~1:00 pm. The venue pack's default access is 3 pm; the earlier access needs explicit PM approval (Jeff Hahn) and may cost — confirm it is locked. The split itself is a 60–90 min job IF tails are pre-labelled to the fixed patch (print the recorder-patch page and label both splitter legs before the day); patch alongside the venue tech, then line-check all 20 channels during the first soundcheck.
- **Requested from the venue:** confirmation of split point (above); a small table + chair for recorder and operator (FOH or side-stage per the split point); 2 × 240 V outlets on the same power circuit as the audio system (shared circuit + transformer-isolated splits avoids ground-loop hum); two spare XLRs FOH desk → Zoom.
- **Line-check discipline:** the operator confirms all 20 tracks show signal during each changeover line check — the patch never changes, so problems mean a cable, not a patch.