

Complete Notes: Installing & Using Kind Kubernetes Cluster (CKA 2024 Series #6)

Video Goal

Learn how to install Kubernetes **locally** using **kind** (Kubernetes IN Docker), setup clusters for Kubernetes CKA hands-on practice, and manage contexts to switch between clusters.

1 Why NOT Use Managed Kubernetes Cloud Providers?

- Managed services like **AKS, EKS, GKE** abstract away the control plane – no access to troubleshoot/control master nodes → less learning opportunity.
- For deep understanding and troubleshooting, **local Kubernetes installation** is preferred.
- Hence, learn Kubernetes using local clusters before using cloud-managed solutions.

2 What is Kind? (Kubernetes IN Docker)

- Kind runs Kubernetes **clusters in Docker containers** → each container acts like an individual node (either control-plane or worker).
- Lightweight → easy to setup and destroy clusters quickly for learning and testing.
- Great for hands-on Kubernetes practice.

3 Prerequisites

- **Go 1.16+** installed (not always mandatory if using pre-built binaries).
- Docker / Podman / NerdCTL installed (the container runtime).
- kubectl CLI installed (to interact with your Kubernetes cluster).

4 Install Kind CLI

Installation options:

- **Mac:** `brew install kind`
- **Windows:** `choco install kind` (chocolatey package manager)
- **Linux:** Download release binaries or install from source if preferred.

```
# Example on Mac  
brew install kind
```

5 Creating Your First Cluster with Kind

```
kind create cluster --image kindest/node:v1.29.4 --name cka-cluster1
```

- `--image`: specifies Kubernetes node image version to use (match exam version, here 1.29.4).
- `--name`: name of the cluster (default is `kind`).
- This command spins up Docker containers as nodes with the Kubernetes control plane and worker inside same node by default.

6 Verify Cluster Status

```
kubectl cluster-info --context kind-cka-cluster1  
kubectl get nodes
```

- Shows the API server URL and running nodes (single node with control plane and worker roles combined).
- `kubectl` interacts with Kubernetes clusters via **context**.
- Make sure `kubectl` CLI is installed. Check version:

```
kubectl version --client
```

7 Creating a Multi-Node Cluster with Kind (Control Plane + Workers)

Create a Kind config YAML file (`config.yml`):

```
kind: Cluster  
apiVersion: kind.x-k8s.io/v1alpha4  
nodes:  
  - role: control-plane  
  - role: worker  
  - role: worker
```

- 1 control plane node + 2 worker nodes → 3 nodes total.

Create cluster with config file:

```
kind create cluster --name cka-cluster2 --image kindest/node:v1.29.4 --config  
config.yml
```

8 Check nodes of new cluster:

```
kubectl get nodes
```

- Will show 3 nodes with roles: 1 control-plane + 2 worker nodes.

9 Managing Multiple Clusters with kubectl Contexts

- Each cluster has a **context** in kubeconfig.
- To list contexts:

```
kubectl config get-contexts
```

- * shows current context in use.
- To switch context (i.e. switch cluster you target commands to):

```
kubectl config use-context kind-cka-cluster1  
kubectl get nodes    # shows nodes from cluster 1
```

Switch back to cluster 2:

```
kubectl config use-context kind-cka-cluster2  
kubectl get nodes    # shows nodes from cluster 2
```

Important: In the CKA exam, make sure to switch to the right context before beginning each task.

10 Helpful Kubernetes CLI Command Tips

Task	Command
List all contexts	<code>kubectl config get-contexts</code>
Switch to a context	<code>kubectl config use-context</code>
Get cluster info	<code>kubectl cluster-info</code>
List nodes	<code>kubectl get nodes</code>


1 1 Useful Kubernetes Docs & Cheatsheets

- **Main docs:** kubernetes.io/docs
- **Cheat sheet:** Search for "kubectl cheat sheet" on kubernetes.io → essential for exam.

- **Exam note:** You will have access to official docs during the exam to copy long commands, so no need to memorize everything, but practice enough to be efficient.



Workflow Summary: Installing and Using Kind



💡 Key Takeaways:

- **Kind uses Docker containers as nodes** — simple, fast local k8s clusters.
- Always check & switch kubectl context before running commands.
- Multi-node cluster simulates real environments better than default single-node cluster.
- Use Kubernetes official docs and cheat sheets for exam reference.
- Practice common `kubectl` commands well for exam speed.

👁️ What's Next?

- Next video: Creating pods, difference between imperative vs declarative commands, and writing **YAML manifests** (basic Kubernetes resource files).

🌟 Happy Learning & Kubernetes Exploration! 🌟

Feel free to ask if you want diagrams or more detailed code examples!

🧱 kind Kubernetes Cluster Setup Notes

🔧 Basic Command Structure

```
kind create cluster [flags]
```

🧩 Common Flags:

Flag	Description
<code>--name <name></code>	Name your cluster
<code>--image <image></code>	Choose Kubernetes version (via kindest/node image)
<code>--config <file.yaml></code>	Use a custom cluster config file
<code>--wait</code>	Time to wait for cluster readiness (e.g. 60s)

🟢 Single Node Cluster

A **default cluster** created by `kind` is a single node (control plane only).

🧪 Create a single node cluster:

```
kind create cluster --name cka --image kindest/node:v1.30.0
```

✅ Verify:

```
kubectl cluster-info --context kind-cka
kubectl get nodes
```

Multi-Node Cluster (1 Control Plane + 2 Workers)

To create a multi-node cluster, you need a **YAML config file**.

Step 1: Create `cluster-config.yaml`

```
# cluster-config.yaml
kind: Cluster
apiVersion: kind.x-k8s.io/v1alpha4
nodes:
  - role: control-plane
  - role: worker
  - role: worker
```

Step 2: Create cluster using config

```
kind create cluster --name cka-multi --config cluster-config.yaml --image
kindest/node:v1.30.0
```

Verify:

```
kubectl get nodes
```

Expected output:

NAME	STATUS	ROLES	AGE	VERSION
cka-multi-control-plane	Ready	control-plane	1m	v1.30.0
cka-multi-worker	Ready	<none>	1m	v1.30.0
cka-multi-worker2	Ready	<none>	1m	v1.30.0

List All Clusters

```
kind get clusters
```




Delete Cluster

```
kind delete cluster --name cka  
kind delete cluster --name cka-multi
```



Pro Tips

- Always match **kind** version with your Kubernetes version.
 - Useful for **local testing**, **CI pipelines**, and **certification prep** (e.g., CKA).
 - Can expose ports by adding **extraPortMappings** in the config file.
 - Docker must be running .
-