

**Table 2**  
 Properties of FC-77 at saturation (3M Corporation, 1986, 2000) and other experimentally determined quantities.

| Quantity          | Value                 | Units                |
|-------------------|-----------------------|----------------------|
| $T_{\text{sat}}$  | 100.1–100.5           | (°C)                 |
| $P$               | 101,325               | (Pa)                 |
| $\rho_l$          | 1592                  | (kg/m <sup>3</sup> ) |
| $\rho_v$          | 14.7                  | (kg/m <sup>3</sup> ) |
| $\mu_l$           | 0.000442              | (kg/m s)             |
| $c_{p,l}$         | 1170                  | (J/kg K)             |
| $k_l$             | 0.057                 | (W/m K)              |
| $\alpha_l$        | $3.06 \times 10^{-8}$ | (m <sup>2</sup> /s)  |
| $h_{lv}$          | 89,000                | (J/kg)               |
| $g$               | 9.81                  | (m/s <sup>2</sup> )  |
| $\theta$          | 0.854                 | (radians)            |
| $\sigma$          | 0.0057                | (N/m)                |
| $\text{Pr}_l$     | 9.08                  | –                    |
| $T_{\text{crit}}$ | 495                   | (K)                  |
| $P_{\text{crit}}$ | $1.58 \times 10^6$    | (Pa)                 |
| $M$               | 416                   | (kg/kmol)            |
| $Ja$              | 8.56–36.06            | –                    |