

JEQL

A Language for Spatial Processing (and other things)

*Martin Davis
September 2011*

Spatial Data Challenges

- **Complex data model**
 - hierarchically structured, arbitrary-length data
 - higher order data structures (*e.g. polygonal coverages*)
- **Numerous (& complex) data formats**
 - Shapefile, GML, KML, GeoJSON, GeoRSS, *etc.etc.*
- **Large data volumes**
 - -> Performance is critical
- **Sophisticated algorithms**
 - needed for functionality, performance
 - often supplied by external libs (*e.g. JTS*)
- **Lots of time spent wrangling data**
 - "Spatial ETL"

Lots of Spatial Tools

- **Spatial libraries (JTS)**
 - powerful geometry processing
- **Spatial GUIs (JUMP, etc.)**
 - easy to use
 - graphical display
- **Spatial Databases (PostGIS, etc.)**
 - powerful
 - handles big data
 - SQL good for spatial & attribute manipulation

but...

- **Spatial libraries**

- complex to use
- need to be a programmer

- **Spatial GUIs**

- hard to capture & reuse process chains
- hard to extend

- **Spatial Databases**

- locked up inside database
- hard to access outside resources
- "impedance mismatch" with external languages


Idea!

- **Higher-level language**
 - easy to use
 - repeatable, sharable, understandable
 - follow SQL paradigm
- **Easy access to external data**
 - data file formats
 - databases
- **Full support for Spatial**
 - datatypes, operations, formats
- **Implement on Java platform**
 - Fast(er) to develop
 - cross-platform
 - excellent tools & libraries

JEQL

- **Java-based** - runs on the JVM
- **Easy** - simple to learn and use
- **Expressive** - higher-level syntax
- **Efficient** - performant execution model
- **Extensible** - using Java code and libraries
- **Embeddable** - as an engine in other apps
- **ETL** - core use case
- **Query** - SQL-based data manipulation
- **Language**

JEQL Architecture



JEQL Language Features

- **Types**

- Int, Double, Boolean, String, Date, Geometry

- **Variables, Functions & Expressions**

- similar to Java

- **Standard Library**

- String, Geom, RegEx, Date, System, File, etc. etc.

- **Commands**

- operations which are easier or faster in Java
 - e.g. I/O, complex spatial processes
- named in/out parameters
- multiple outputs

JEQL features from Java

- **Interpreted scripting language running on JVM**
 - popular approach - *Clojure, Jython, etc.*
- **Access to Java APIs**
 - Standard Java Library
 - Math, String, RegEx, I/O, JDBC, Java2D, etc.
 - 3rd-party APIs
 - JFreeChart, JTS, Proj4J, GeoTools, etc
- **Performance**
- **Memory management**
- **Easy for developers**
 - IDEs, tools, platform-independent
 - lots of code available
 - simple extensibility (dynamic class loading)

JEQL features from SQL

- **Tables are native datatypes**

- "Table-Oriented Programming"
- Tables map 1-1 to databases and other formats
 - low impedance mismatch

- **SELECT expressions**

```
SELECT DISTINCT ... FROM a LEFT OUTER JOIN b
WHERE ... GROUP BY ... ORDER BY ... LIMIT x OFFSET y
```

- declarative, higher-level code

- **Improvements**

- use good ideas from others (PostgreSQL!)
- `WITH` for factoring of common sub-expressions
- **table literals** - `TABLE t(a, b, c) ((...) ...)`
- `SPLIT BY` - inverse of `GROUP BY`

JEQL features for Spatial

- **Geometry** is first-class data type
 - Values, functions, table columns, etc.
 - WKT Literals - `POLYGON ((1 1, 2 2, ...))`
- **Spatial support provided by JTS**
 - OGC-compliant spatial data model
 - Extensive set of spatial functions
- **Proj4J for Coordinate System transformation**
- **Readers/Writers for spatial formats**
 - File: Shapefile, KML, GML,
 - DB: PostGIS, SQL Server, Oracle, ...
 - easy to add others
- **Spatial indexes** (*future*)

JEQL execution model

- **Streaming Evaluation**

- Not memory-bound
 - no limit on throughput size
- No penalty for factoring queries
- Materialize tables when needed for performance

- **Queries can use row order**

- different to SQL
- order is significant in some data formats
- more powerful processing of serialized datasets


JEQL - Applications

- Data format translation
- Model-to-model transformation
- Data export/import from databases
- Data generation
- Geometry manipulation and processing
- Coordinate system reprojection
- KML generation
- QA and data cleaning
- Plotting
- Charting
- Text processing
- XML/HTML generation

Examples

Read dataset, filter / reproject / buffer, write dataset

```
name,countryCode,lat,lon,pop
"les Escaldes","AD",42.50729,1.53414,15853
"Andorra la Vella","AD",42.50779,1.52109,20430
"Umm al Qaywayn","AE",25.5864,55.57603,44411
"Ra's al Khaymah","AE",25.78953,55.9432,115949
"Khawr Fakkan","AE",25.33132,56.34199,33575
"Dubai","AE",25.25817,55.30472,1137347
"Diba","AE",25.61955,56.27291,26395
"Sharjah","AE",25.35731,55.4033,543733
"Ar Ruwais","AE",24.11028,52.73056,16000
```



```
CSVReader tcityRaw hasColNames: file: "cities.csv";

/-- convert raw CSV to typed values
tcity = select name,
              Val.toDouble(lat) lat,
              Val.toDouble(lon) lon,
              Val.toInt(pop) population
from tcityRaw;

/--- PROJ4-style projections
projGoogleMerc = "+proj=merc +a=6378137 +b=6378137 +lat_ts=0.0 +lon_0=0.0 +x_0=0.0 +y_0=0.0 +datum=WGS84 +units=m +no_defs";

/--- select large cities, buffer by population
tcityBuf = select name,
                  population,
                  Geom.buffer(CRS.project(Geom.createPoint(lon, lat), projGoogleMerc),
                              population / 10) cityBuf
from tcity where population >= 1_000_000;

ShapefileWriter tcityBuf file: "cities_proj.shp";
```

Generate GML

```
//--- Data provided in table literal
t = TABLE t(id, type, lanes, Geometry) (
( 1, "HWY", 4, LINESTRING (1 1, 2 2))
( 2, "CITY", 2, LINESTRING (10 10, 20 20))
( 3, "CITY", 2, LINESTRING (100 100, 20 20, 300 300, 400 400))
) ;
```

```
//--- define GML id
tgml = select id gml_id, * from t;
```


```
GMLWriter tgml
  namespacePrefix: "ts"
  namespaceURI: "http://tsusiatsoftware.net/gml"
  featureCollectionTag: "RoadNetwork"
  featureTag: "RoadSegment"
  file: "test.gml";
```



```
<?xml version="1.0" encoding="UTF-8" standalone="yes" ?>
<RoadNetwork xmlns:gml="http://www.opengis.net/gml" xmlns:ts="http://tsusiatsoftware.net/gml">
  <gml:featureMember>
    <RoadSegment fid="1">
      <ts:id>1</ts:id>
      <ts:type>HWY</ts:type>
      <ts:lanes>4</ts:lanes>
      <ts:Geometry>
        <gml:LineString>
          <gml:coordinates>1.0,1.0 2.0,2.0</gml:coordinates>
        </gml:LineString>
      </ts:Geometry>
    </RoadSegment>
  </gml:featureMember>
  <gml:featureMember>
    <RoadSegment fid="2">
      <ts:id>2</ts:id>
```


Convert CSV File to KML - input & output

```
"Official Name","Feature Type","Feature Type Code","Mapsheet","Latitude","Longitude"
"Adade Yus Mountain","Mountain","2701","93N/7","55 18 00","124 41 00"
"Ksan","Locality","108","93M/4","55 15 00","127 40 00"
"100 Mile House","District Municipality (1)","35","92P/11","51 39 00","121 17 00"
"101 Mile Lake","Lake","951","92P/11","51 40 00","121 18 00"
"103 Mile Lake","Lake","951","92P/11","51 41 00","121 18 00"
"105 Mile House","Locality","108","92P/11","51 42 00","121 19 00"
"105 Mile Lake","Lake","951","92P/11","51 43 00","121 20 00"
"105 Mile Post 2, Réserve indienne","Réserve indienne","552","92I/11","50 44 00","121 19 00"
"105 Mile Post Indian Reserve 2","Indian Reserve","543","92I/11","50 44 00","121 19 00"
"108 Mile Lake","Lake","951","92P/11","51 45 00","121 21 00"
"108 Mile Ranch","Community","121","92P/11","51 45 00","121 21 00"
"111 Mile Creek","Creek (1)","602","92P/14","51 48 00","121 28 00"
"111 Mile House","Locality","108","92P/14","51 46 00","121 23 00"
"114 Mile House","Locality","108","92P/14","51 48 00","121 26 00"
"117 Mile Creek","Creek (1)","602","92P/14","51 49 00","121 29 00"
"12 Mile","Locality","108","92P/14","51 49 00","121 29 00"
"122 Mile House","Locality","108","92P/14","51 49 00","121 29 00"
"127 Mile House","Locality","108","92P/14","51 49 00","121 29 00"
"130 Mile Lake","Locality","108","92P/14","51 49 00","121 29 00"
"144 Mile","Locality","108","92P/14","51 49 00","121 29 00"
```



```
<Placemark>
  <name>Adrian, Mount</name>
  <styleUrl>#peak</styleUrl>
  <Point>
    <coordinates>-125.52944444444444,49.756388888888885</coordinates>
  </Point>
</Placemark>
```

Convert CSV File to KML - script

```
//--- Read data from CSV
CSVReader tCSV useColNames: file: "BC GAZETTEER 8Oct07.csv";

//--- Select mountain features
tMt = select * from tCSV where String.leftStr(Feature_Type, 5) == "Mount";

//--- Prepare KML dataset with name, location as POINT, named style
tKML = select    nameSafe as kmlName,
                  Geom.createPoint(lon, lat) as geometry,
                  "#peak" as kmlStyleUrl
    with {
      nameSafe = String.replaceAll(Official_Name, "&", "&");
      //--- convert textual DDMSS to decimal degrees
      lat =      Val.toDouble(String.substring(Latitude, 0, 2))
                + Val.toDouble(String.substring(Latitude, 3, 5)) / 60.0
                + Val.toDouble(String.substring(Latitude, 6, 8)) / 3600.0;
      lon =      - (Val.toDouble(String.substring(Longitude, 0, 3))
                + Val.toDouble(String.substring(Longitude, 4, 6)) / 60.0
                + Val.toDouble(String.substring(Longitude, 7, 9)) / 3600.0);
    }
    from tMt;

//--- KML styling for named style
tStyle = select * from table (
  ("peak", "#ff7fffff", "#ff00ff00", 0.6,
    "http://maps.google.com/mapfiles/kml/shapes/triangle.png")
  ) styles(id, labelStyleColor, iconStyleColor, iconStyleScale, iconStyleHref);

KMLWriter tKML
  styles: tStyle
  name: "B.C. Placenames"
  file: "bcNames.kml";
```


Air Routes Visualization - Data

C:\data\airports.dat														
1	"Goroka"	"Goroka"	"Papua New Guinea"	"GKA"	"AYGA"	-6.081689	145.391881	5282	10	"U"				
2	"Madang"	"Madang"	"Papua New Guinea"	"MAG"	"AYMD"	-5.207083	145.7887	20	10	"U"				
3	"Mount Hagen"	"Mount Hagen"	"Papua New Guinea"	"HGU"	"AYMH"	-5.826789	144.295861	5388						
4	"Nadzab"	"Nadzab"	"Papua New Guinea"	"LAE"	"AYNZ"	-6.569828	146.726242	239	10	"U"				
5	"Port Moresby Jacksons Intl"	"Port Moresby"	"Papua New Guinea"	"POM"	"AYPY"	-9.443383								
6	"Wewak Intl"	"Wewak"	"Papua New Guinea"	"WWK"	"AYWK"	-3.583828	143.669186	19	10	"U"				
7	"Narsarsuaq"	"Narssarssuaq"	"Greenland"	"UAK"	"BGBW"	61.160517	-45.425978	112	-3	"E"				
8	"Nuuk"	"Godthaab"	"Greenland"	"GOH"	"BGGH"	64.190922	-51.678064	283	-3	"E"				
9	"Sondre Stromfjord"	"Sondrestrom"	"Greenland"	"SFJ"	"BGSF"	67.016969	-50.689325	165	-3					
10	"Thule Air Base"	"Thule"	"Greenland"	"THU"	"BGTL"	76.531203	-68.703161	251	-4	"E"				
11	"Akureyri"	"Akureyri"	"Iceland"	"AEY"	"RIAR"	65.659994	-18.072703	6	0	"N"				
12	"Egilsstadir"	"Egilsstadir"	"Iceland"											
13	"Hornafjardur"	"Hofn"	"Iceland"											
14	"Husavik"	"Husavik"	"Iceland"											
15	"Isafjardur"	"Isafjardur"	"Iceland"											
16	"Keflavik Nas"	"Keflavik"	"Iceland"											
17	"Patreksfjardur"	"Patreksfjardur"	"Iceland"											
18	"Reykjavik"	"Reykjavik"	"Iceland"											
19	"Siglufjardur"	"Siglufjardur"	"Iceland"											
20	"Vestmannaeyjar"	"Vestmannaeyjar"	"Iceland"											
21	"Sault Ste Marie"	"Sault Sainte Marie"	"Canada"											
22	"Winnipeg St Andrews"	"Winnipeg"	"Canada"											
23	"Shearwater"	"Halifax"	"Canada"											
24	"St Anthony"	"St. Anthony"	"Canada"											
25	"Tofino"	"Tofino"	"Canada"	"YAZ"										
26	"Kugaaq"	"Pelly Bay"	"Canada"											

C:\data\routes.dat														
0B	1542	AGP	1230	BBU	1650			0	738					
0B	1542	ARW	1647	BBU	1650			0	340					
0B	1542	BBU	1650	AGP	1230			0	738					
0B	1542	BBU	1650	ARW	1647			0	340					
0B	1542	BBU	1650	BCN	1218			0	738					
0B	1542	BBU	1650	BGY	1525			0	733					
0B	1542	BBU	1650	BLQ	1538			0	735					
0B	1542	BBU	1650	BRU	302			0	738	733				
0B	1542	BBU	1650	BVA	1367			0	738	734	733			
0B	1542	BBU	1650	CLJ	1652			0	340					
0B	1542	BBU	1650	CND	1651			0	738					
0B	1542	BBU	1650	CTA	1509			0	738					
0B	1542	BBU	1650	CUF	1534			0	738	734				

Air Routes Visualization - prepare data

```
// Read airports with Id, city, and location
CSVReader tairportRaw file: "airports.dat";
tairport = select Val.toInt(col1) id,
                  col3 city,
                  col4 ctry,
                  Val.toDouble(col7, 0.0) lat,
                  Val.toDouble(col8, 0.0) lon
                  from tairportRaw;

// Read routes with from and to city IDs
CSVReader trouteRaw file: "routes.dat";
trouteAll = select rownum() rteID,
                  Val.toInt(col4, -1) fromID,
                  Val.toInt(col6, -1) toID
                  from trouteRaw;

// Keep only a single route for each city pair
troute = select distinct fromID, toID from trouteAll;

//-- compute route vectors by joining routes & airports
troute2 = select
  fromID, a1.city fromCity, a1.ctry fromCtry, a1.lat fromLat, a1.lon fromLon,
  toID,    a2.city toCity,    a2.ctry toCtry,    a2.lat toLat,    a2.lon toLon
  from troute r
  join tairport a1 on r.fromID == a1.id
  join tairport a2 on r.toID   == a2.id;

CSVWriter troute2 colNames: file: "routeLine.csv";
```


Air Routes Visualization -Plot



Air Routes Visualization - plot geodetic arcs

```
//----- Plot a global map of Air Routes
CSVReader troute hasColNames: file: "routeLine.csv";

trte = select    fromCity, toCity,
                Val.toDouble(fromLon) fromLon, Val.toDouble(fromLat) fromLat,
                Val.toDouble(toLon)   toLon,   Val.toDouble(toLat)   toLat
        from troute;


//----- Generate geodetic arcs
tlines = select fromCity, toCity, line, Geom.length(line) len
        with {
            line = Geodetic.split180(Geodetic.arc(fromLon, fromLat, toLon, toLat, 2));
        }
        from trte order by len desc;

//----- Colour-theme arcs by length
tplot = select line,
              Color.interpolate("ffffff", "0000ff", "000080", len / 80.0 ) lineColor,
              0.4 lineWidth
        from tlines;

//----- Plot world country polygons and borders for context
ShapefileReader tworld file: "world.shp";
tworldLine = select GEOMETRY, "22222277" lineColor from tworld;
tworldFill = select GEOMETRY, "333333"   fillColor from tworld;

width = 4000;
Plot    width: width    height: width / 2
        extent: LINESTRING(-180 -90, 180 90)
        data: tworldFill
        data: tplot
        data: tworldLine
        file: "routes.png";
```

Charting - output



Charting - script

```
CSVReader troute hasColNames: file: "routeLine.csv";

//--- Compute counts of routes from each city
tCityCount = select count(*) cnt, fromCity city
               from troute
               group by fromCity
               order by cnt desc;

//--- Limit to top 15
tchart = select city key, cnt value from tCityCount limit 15;

//--- Generate 3D bar chart with labels, axes
Chart type: "bar"
  data: tchart
  extrude:
  color: "00c0f0"
  showItemLabels:
  xAxisTitle: "Top Cities by Originating Air Routes"
  xAxisLabelRotation: -0.5
  width: 800
  file: "cityRoutes.png";
```


Database access

```
//--- read data from database query
DbReader t
    driver: "org.h2.Driver"
    url: "jdbc:h2:tcp://localhost/~/test"
    user: "sa"
    password: ""
    sql: $"
select f.id, f.name, loc.x, loc.y
from feature f
join location loc on f.id = loc.id
order by id" ;

//--- process data
t2 = select id, name, Geom.createPoint(x, y) from t;

//--- write data to DB table
DbWriter t2
    table: "TEST"
    driver: "oracle.jdbc.driver.OracleDriver"
    url: "jdbc:oracle:thin:@localhost:1521:xe"
    user: "test"
    password: "test"
```

JEQL for Developers

- **Easy to extend**
 - Functions are Java `public static` methods
 - Commands are Java classes
- **Easy to develop & debug**
 - Run & debug in any Java IDE
- **JEQL Engine is embeddable in other applications**
 - expose namespace of tables to JEQL
 - register functions & commands
 - e.g. Use as a query engine for OpenJUMP

Comparison with other products

- **ETL Tools**

- OGR
- GeoKettle, etc.

- **Spatial Processing Tools**

- GeoScript
- GMT - Generic Mapping Tools

- **Spatial Databases**

- PostGIS, etc.
- Spatialite, H2 (Jaspa, GeoDB), etc.

Future Plans

- **More data formats**
- **Better integration with databases**
 - Express DB queries directly in JEQL SQL
- **Spatial Indexing**
 - Automatically created when required
- **GUI Builder for scripts**
- **JEQL Workbench**
 - GUI for developing/running scripts
 - Viewer for tabular and spatial datasets
 - Visual programming?
 - *High-performance Integrated Development Environment*

Distribution & Support

- **Engine is freely available for download & distribution**
 - Open Source soon
- **Documentation**
 - Reference
 - Examples
- **Mailing List**

<http://tsusiatsoftware.net/jeql/main.html>