Digital Blocks

PWM

PWM

Pulse Width Modulator





PWM Signal

https://community.element14.com/products/devtools/technicallibrary/w/documents/11058/cypress-psoc-4-system-on-chip-overview

PWM Signal

“A Square Wave Signal with a Specified Duty Cycle”



$$\text{Duty Cycle} = \frac{T_{ON}}{T_{ON} + TOFF}$$

$$\text{Freq} = \frac{1}{T_{PERIOD}} = \frac{1}{T_{ON} + TOFF}$$

$$\text{Amplitude} = V_{HIGH} - V_{LOW}$$

https://en.wikipedia.org/wiki/Pulse-width_modulation

Generation (Method #1)




```c
#include "project.h"

#define PERIOD_COUNT 1000
#define DUTY_COUNT 750

int main(void)
{
    CyGlobalIntEnable; /* Enable global interrupts. */

    /* Set the Pin_PWM pin as an output pin */
    Pin_PWM_SetDriveMode(Pin_PWM_DM_STRONG);
    Pin_PWM_Write(0);

    for(;;)
    {
        /* Turn the Pin_PWM pin on for DUTY_COUNT cycles */
        Pin_PWM_Write(1);
        CyDelay(DUTY_COUNT);

        /* Turn the Pin_PWM pin off
        for (PERIOD_COUNT - DUTY_COUNT) cycles */
        Pin_PWM_Write(0);
        CyDelay(PERIOD_COUNT - DUTY_COUNT);
    }
}
```

https://en.wikipedia.org/wiki/Pulse-width_modulation

1kHz PWM signal with a 75% duty cycle

Generation (Method #2)

PWM Digital Block




```
#include "project.h"

int main(void)
{
    CyGlobalIntEnable; /* Enable global interrupts. */

    /* Start the PWM component */
    PWM_1_Start();

    /* Set the PWM period to 1ms (1KHz) */
    PWM_1_WritePeriod(1000);

    /* Set the PWM duty cycle to 75% */
    PWM_1_WriteCompare(750);

    for(;;)
    {
        /* Do nothing, the PWM runs in the background */
    }
}
```

https://en.wikipedia.org/wiki/Pulse-width_modulation

Component Settings



PWM Bits = 8bit (or 16bit)

PWM Period = 0-255 (or 0 to 65535)

PWM Compare = 0-255 (or 0 to 65535)

$$\text{Freq} = \frac{1}{T_{PERIOD}} = \frac{1}{\text{Period} * \text{Tclock}_{\_1}}$$

$$\text{Duty Cycle} = \frac{\text{Compare}}{\text{Period}}$$

https://en.wikipedia.org/wiki/Pulse-width_modulation

E.g., Settings



PWM Bits = 8bit

PWM Period = 200

PWM Compare = 50

$$\text{Freq} = \frac{1}{T_{\text{PERIOD}}} = \frac{1}{\text{Period} * \text{Tclock}_{\_1}} \; ?$$

$$\text{Duty Cycle} = \frac{\text{Compare}}{\text{Period}} \; ?$$

https://en.wikipedia.org/wiki/Pulse-width_modulation

Verilog 8bit PWM



PWM Bits = 8bit

PWM Period = 0-255

PWM Compare = 0-255

https://en.wikipedia.org/wiki/Pulse-width_modulation

```
module pwm_8bit(
  input clock,
  input reset,
  input [7:0] pwm_compare,
  input [7:0] pwm_period,
  output pwm
);
  reg [7:0] count = 0;
  reg pwm_temp = 1'b0;

  always @(posedge clock) begin
    if (reset) begin
      count <= 0;
    end else begin
      count <= (count == pwm_period) ? 0 : count + 1;
    end
  end

  always @(posedge clock) begin
    if (count < pwm_compare) begin
      pwm_temp <= 1'b1;
    end else begin
      pwm_temp <= 1'b0;
    end
  end

  assign pwm = pwm_temp;

endmodule
```

Applications

a. LED Brightness Ctrl



b. SMPS



$V_o = V_i$ X Duty Cycle

https://en.wikipedia.org/wiki/Pulse-width_modulation

Counter

Counter

“Used for Counting Events”



Bits = 8bit, 16bit …

Period ~ $0 - 2^{\text{Bits}}$

Direction = Up or Down

Count-Edge = Fall or Rise

- The block increments the counter value upon detecting edges (rising or falling) on its count input
- Clock is used for sampling inputs to the counter (to avoid setup violation) > 2x (Signal Freq at Count)
- ‘tc’ goes high when counter value equals the period (or terminal count). It stays high for one clock cycle

Counter - Verilog




```
module counter_8bit (
    input wire clk,
    input wire count,
    input wire reset,
    input wire enable,
    output reg [7:0] reg_counter
);

reg count_sampled;

always @(posedge clk) begin
    count_sampled <= count;
end

always @(posedge count_sampled) begin
    if (enable) begin
        if (reset) begin
            reg_counter <= 0;
        end else begin
            reg_counter <= reg_counter + 1;
        end
    end
end

endmodule
```

Bits = 8bit, Up Counter, Count-Edge ?

Reading

Why you need clock ? To synchronize asynchronous inputs such as “Count”

https://web.stanford.edu/class/ee183/handouts/synchronization_pres.pdf



https://en.wikipedia.org/wiki/Pulse-width_modulation

E.g., Detect Signal Freq

“Detect Frequency of a Unknown PWM Signal”



?

- The block increments the counter value upon detecting edges (rising or falling) on its count input
- Clock is used for sampling inputs to the counter (to avoid setup violation) > 2x (Signal Freq at Count)

https://en.wikipedia.org/wiki/Pulse-width_modulation
Ref – creative commons

E.g., Detect Sig Freq (…)

“Detect Frequency of a Unknown PWM Signal”



Enable Time ?

Period ?

- The block increments the counter value upon detecting edges (rising or falling) on its count input
- Clock is used for sampling inputs to the counter (to avoid setup violation) > 2x (Signal Freq at Count)

https://en.wikipedia.org/wiki/Pulse-width_modulation

E.g., Detect Sig Freq (…)

“Detect Frequency of a Unknown PWM Signal”





E.g., Detect Sig Freq (…)



Counter-Value = 3 (~ 3Hz)

Error % = (3-2.3)/2.3 = 30%



Counter-Value = 2 (~ 2Hz)

Error % = (2-2.3)/2.3 = -13%

Resolution of 1s enable signal is 1Hz. (i.e., counter-output thus could be only 2 or 3)

E.g., Detect Sig Freq (…)



Counter-Value = 11 or 12, i.e., 2.2 Hz or 2.4 Hz

Error = 100*(2.4-2.3)/2.3 = 4.3%, 100*(2.2-2.3)/2.3 = ?

Note – For enable of 5 seconds, 5 count correspond to 1Hz, i.e., 1 count corresponds to 0.2Hz

E.g., Detect Sig Freq (…)



i.e., in this setting a signal frequency less than 1Hz cannot be detected.

For enable of 1 seconds, 1 count correspond to 1 Hz → Resolution of the counter = 1 Hz

For enable of 5 seconds, 1 count correspond to 0.2 Hz → Resolution = 0.2 Hz

For enable of 10 seconds, 1 count correspond to 0.1 Hz → Resolution = 0.1 Hz

For enable of 100 seconds, 1 count correspond to 0.01 Hz → Resolution = 0.01 Hz

Question



- **EN Time = 1s, Sig Freq = 2.3456Hz, Counter Out ?**
- **EN Time = 1s, Sig Freq = 2.8456Hz, Counter Out ?**
- **EN Time = 10s, Sig Freq = 2.3456Hz, Counter Out ?**
- **EN Time = 100s, Sig Freq = 2.3456Hz, Counter Out ?**

Question ?

I need a resolution of 0.01 Hz with a 8bit counter to measure a signal with frequency range between 2 to 3 Hz. What to do ?



Resolution of 0.01 Hz require 100seconds of enable time ? A signal frequency in the range of 2 to 3Hz will technically require a counter which can count up to ? (3*100=300)

Solution → Averaging

I need a resolution of 0.01 Hz with a 8bit counter to measure a signal with frequency range between 2 to 3 Hz. What to do ?



Solution: Perform measurements a large number of time.

- Counter Outputs = 2 or 3
- 2 for 68% and 3 for 32%
- **Averaging → 2.32**

# of Measurements Required ?