



Prestige barbers 2.0

Report generated by Tenable Nessus™

Thu, 06 Nov 2025 00:55:36 EST

TABLE OF CONTENTS

Vulnerabilities by Host

• 192.168.1.36.....	4
---------------------	---

Nessus Essentials

Vulnerabilities by Host

192.168.1.36



Scan Information

Start time: Thu Nov 6 00:35:20 2025

End time: Thu Nov 6 00:55:35 2025

Host Information

IP: 192.168.1.36

MAC Address: DC:97:BA:4A:3D:D2

OS: Windows 11

Vulnerabilities

46803 - PHP expose_php Information Disclosure

Synopsis

The configuration of PHP on the remote host allows disclosure of sensitive information.

Description

The PHP install on the remote server is configured in a way that allows disclosure of potentially sensitive information to an attacker through a special URL. Such a URL triggers an Easter egg built into PHP itself.

Other such Easter eggs likely exist, but Nessus has not checked for them.

See Also

https://www.0php.com/php_easter_egg.php

<https://seclists.org/webappsec/2004/q4/324>

Solution

In the PHP configuration file, php.ini, set the value for 'expose_php' to 'Off' to disable this behavior. Restart the web server daemon to put this change into effect.

Risk Factor

Medium

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2010/06/03, Modified: 2022/04/11

Plugin Output

tcp/80/www

Nessus was able to verify the issue using the following URL :

<http://192.168.1.36/dashboard/phpinfo.php/?=PHPB8B5F2A0-3C92-11d3-A3A9-4C7B08C10000>

46803 - PHP expose_php Information Disclosure

Synopsis

The configuration of PHP on the remote host allows disclosure of sensitive information.

Description

The PHP install on the remote server is configured in a way that allows disclosure of potentially sensitive information to an attacker through a special URL. Such a URL triggers an Easter egg built into PHP itself.

Other such Easter eggs likely exist, but Nessus has not checked for them.

See Also

https://www.0php.com/php_easter_egg.php

<https://seclists.org/webappsec/2004/q4/324>

Solution

In the PHP configuration file, php.ini, set the value for 'expose_php' to 'Off' to disable this behavior. Restart the web server daemon to put this change into effect.

Risk Factor

Medium

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2010/06/03, Modified: 2022/04/11

Plugin Output

tcp/443/www

Nessus was able to verify the issue using the following URL :

<https://192.168.1.36/dashboard/phpinfo.php/?=PHPB8B5F2A0-3C92-11d3-A3A9-4C7B08C10000>

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

tcp/80/www

```
URL      : http://192.168.1.36/
Version  : unknown
Source   : Server: Apache
backported : 0
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

tcp/443/www

```
URL      : https://192.168.1.36/
Version  : unknown
Source   : Server: Apache
backported : 0
```

33817 - CGI Generic Tests Load Estimation (all tests)

Synopsis

Load estimation for web application tests.

Description

This script computes the maximum number of requests that would be done by the generic web tests, depending on miscellaneous options. It does not perform any test by itself.

The results can be used to estimate the duration of these tests, or the complexity of additional manual tests.

Note that the script does not try to compute this duration based on external factors such as the network and web servers loads.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/10/26, Modified: 2022/04/11

Plugin Output

tcp/3000/www

```
Here are the estimated number of requests in miscellaneous modes
for one method only (GET or POST) :
[Single / Some Pairs / All Pairs / Some Combinations / All Combinations]

local file inclusion           : S=22          SP=22          AP=166          SC=4
AC=4612
persistent XSS                : S=88          SP=88          AP=664          SC=16
AC=18448
web code injection            : S=22          SP=22          AP=166          SC=4
AC=4612
SSI injection                  : S=66          SP=66          AP=498          SC=12
AC=13836
directory traversal (extended test) : S=1122        SP=1122        AP=8466         SC=204
AC=235212
SQL injection (2nd order)      : S=22          SP=22          AP=166          SC=4
AC=4612
blind SQL injection           : S=264         SP=264         AP=1992         SC=48
AC=55344
cross-site scripting (comprehensive test): S=88          SP=88          AP=664          SC=16
AC=18448
blind SQL injection (4 requests) : S=88          SP=88          AP=664          SC=16
AC=18448
```

unseen parameters	: S=770	SP=770	AP=5810	SC=140
AC=161420				
SQL injection	: S=528	SP=528	AP=3984	SC=96
AC=110688				
XML injection	: S=22	SP=22	AP=166	SC=4
AC=4612				
arbitrary command execution (time based)	: S=132	SP=132	AP=996	SC=24
AC=27672				
directory traversal	: S=550	SP=550	AP=4150	SC=100
AC=115300				
injectable parameter	: S=44	SP=44	AP=332	SC=8
AC=9224				
format string	: S=44	SP=44	AP=332	SC=8
AC=9224				
directory traversal (write access)	: S=44	SP=44	AP=332	SC=8
AC=9224				
arbitrary command execution	[...]			

49704 - External URLs

Synopsis

Links to external sites were gathered.

Description

Nessus gathered HREF links to external sites by crawling the remote web server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/10/04, Modified: 2011/08/19

Plugin Output

tcp/80/www

```
57 external URLs were gathered on this web server :
URL... - Seen on...

http://app01.localhost - /dashboard/docs/configure-vhosts.html
http://app02.localhost - /dashboard/docs/configure-vhosts.html
http://cdnjs.cloudflare.com/ajax/libs/font-awesome/3.1.0/css/font-awesome.min.css - /dashboard/
http://client1/ - /dashboard/docs/configure-vhosts.html
http://client2/ - /dashboard/docs/configure-vhosts.html
http://code.google.com/p/gitextensions/ - /dashboard/docs/deploy-git-app.html
http://framework.zend.com/ - /dashboard/docs/create-framework-project-zf1.html
http://framework.zend.com/downloads/latest - /dashboard/docs/create-framework-project-zf1.html
http://framework.zend.com/manual/1.12/en/learning.html - /dashboard/docs/create-framework-project-
zf1.html
http://framework.zend.com/manual/2.3/en/user-guide/overview.html - /dashboard/docs/create-framework-
project-zf2.html
http://git-extensions-documentation.readthedocs.org/en/latest/getting_started.html - /dashboard/
docs/deploy-git-app.html
http://git-scm.com/ - /dashboard/docs/deploy-git-app.html
http://git-scm.com/book - /dashboard/docs/deploy-git-app.html
http://git-scm.com/download/win - /dashboard/docs/create-framework-project-zf2.html
http://localhost - /dashboard/docs/troubleshoot-apache.html
http://localhost/Slim - /dashboard/docs/deploy-git-app.html
http://localhost/example.php - /dashboard/docs/transfer-files-ftp.html
http://localhost/example/phpmailer.php - /dashboard/docs/send-mail.html
http://localhost/myapp - /dashboard/docs/create-framework-project-zf1.html
http://localhost/myapp/ - /dashboard/docs/create-framework-project-zf1.html
http://localhost/phpMyAdmin - /dashboard/docs/backup-restore-mysql.html
http://localhost/sendmail.php - /dashboard/docs/send-mail.html
http://lo [...]
```


49704 - External URLs

Synopsis

Links to external sites were gathered.

Description

Nessus gathered HREF links to external sites by crawling the remote web server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/10/04, Modified: 2011/08/19

Plugin Output

tcp/443/www

```
57 external URLs were gathered on this web server :
URL... - Seen on...

http://app01.localhost -
http://app02.localhost -
http://client1/ -
http://client2/ -
http://code.google.com/p/gitextensions/ -
http://framework.zend.com/ -
http://framework.zend.com/downloads/latest -
http://framework.zend.com/manual/1.12/en/learning.html -
http://framework.zend.com/manual/2.3/en/user-guide/overview.html -
http://git-extensions-documentation.readthedocs.org/en/latest/getting_started.html -
http://git-scm.com/ -
http://git-scm.com/book -
http://git-scm.com/download/win -
http://localhost -
http://localhost/Slim -
http://localhost/example.php -
http://localhost/example/phpmailer.php -
http://localhost/myapp -
http://localhost/myapp/ -
http://localhost/phpMyAdmin -
http://localhost/sendmail.php -
http://localhost/sqlite.php -
http://localhost/wordpress -
http://localhost/xampp/phpinfo.php -
http://localhost:8080/ -
http://myhost -
http://phpmailer.worxware.com/ -
```

```
http://sourceforge.net/projects/wincachegrind/ -  
http://sqlite.org/docs/ -  
http://support.microsoft.com/kb/841290 -  
http://wordpress.localhost -  
http://www.apachelounge.com/download/ -  
http://www.fastly.com/ -  
http://www.kaspersky.com/virusscanner -  
http://www.php.net/ -  
http://www.phpmyadmin.net/ -  
http://www.slimframework.com/ -  
http://www.sqlite.org/datatype3.html -  
http://www.zend.com/ -  
http://xdebug.org/ -  
http://xdebug.org/docs/ -  
https://bitnami.com/stack/xampp#wordpress -  
https://cdnjs.cloudflare.com/ajax/libs/ [...]
```

49704 - External URLs

Synopsis

Links to external sites were gathered.

Description

Nessus gathered HREF links to external sites by crawling the remote web server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/10/04, Modified: 2011/08/19

Plugin Output

tcp/3000/www

```
3 external URLs were gathered on this web server :  
URL... - Seen on...
```

```
https://fonts.googleapis.com - /  
https://fonts.googleapis.com/css2?family=Montserrat:ital,wght@0,100..900;1,100..900&display=swap - /  
https://fonts.gstatic.com - /
```

84502 - HSTS Missing From HTTPS Server

Synopsis

The remote web server is not enforcing HSTS.

Description

The remote HTTPS server is not enforcing HTTP Strict Transport Security (HSTS). HSTS is an optional response header that can be configured on the server to instruct the browser to only communicate via HTTPS. The lack of HSTS allows downgrade attacks, SSL-stripping man-in-the-middle attacks, and weakens cookie-hijacking protections.

See Also

<https://tools.ietf.org/html/rfc6797>

Solution

Configure the remote web server to use HSTS.

Risk Factor

None

Plugin Information

Published: 2015/07/02, Modified: 2024/08/09

Plugin Output

tcp/443/www

```
HTTP/1.1 302 Found
Date: Thu, 06 Nov 2025 05:37:50 GMT
Server: Apache
Location: https://192.168.1.36/dashboard/
Content-Length: 0
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

The remote HTTPS server does not send the HTTP
"Strict-Transport-Security" header.
```

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

```
/dashboard
/dashboard/docs
/dashboard/images
/dashboard/stylesheets
/icons
/img
/xampp
```

Based on tests of each method :

- HTTP methods ACL BASELINE-CONTROL BCOPY BDELETE BMOVE BPROPFIND
BPROPPATCH CHECKIN CHECKOUT COPY DEBUG DELETE GET HEAD INDEX
LABEL LOCK MERGE MKACTIVITY MKCOL MKWORKSPACE MOVE NOTIFY OPTIONS
ORDERPATCH PATCH POLL POST PROPFIND PROPPATCH PUT REPORT
RPC_IN_DATA RPC_OUT_DATA SEARCH SUBSCRIBE UNCHECKOUT UNLOCK
UNSUBSCRIBE UPDATE VERSION-CONTROL X-MS-ENUMATTS are allowed on :

```
/cgi-bin
```

- HTTP methods GET HEAD OPTIONS POST are allowed on :

```
/
/dashboard
```

- Invalid/unknown HTTP methods are allowed on :

```
/cgi-bin
```

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/443/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

```
/dashboard
/dashboard/docs
/dashboard/images
/dashboard/stylesheets
/icons
/img
/xampp
```

Based on tests of each method :

- HTTP methods ACL BASELINE-CONTROL BCOPY BDELETE BMOVE BPROPFIND
BPROPPATCH CHECKIN CHECKOUT COPY DEBUG DELETE GET HEAD INDEX
LABEL LOCK MERGE MKACTIVITY MKCOL MKWORKSPACE MOVE NOTIFY OPTIONS
ORDERPATCH PATCH POLL POST PROPFIND PROPPATCH PUT REPORT
RPC_IN_DATA RPC_OUT_DATA SEARCH SUBSCRIBE UNCHECKOUT UNLOCK
UNSUBSCRIBE UPDATE VERSION-CONTROL X-MS-ENUMATTS are allowed on :

```
/cgi-bin
```

- HTTP methods GET HEAD OPTIONS POST are allowed on :

```
/
/dashboard
```

- Invalid/unknown HTTP methods are allowed on :

```
/cgi-bin
```

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/3000/www

Based on tests of each method :

- HTTP methods ACL CHECKOUT are allowed on :

- /Barberos/B-Styles
 - /Cortes
 - /Cortes/C-Styles
 - /I-style
 - /Tienda
 - /Tienda/T-styles
 - /admin
 - /compra
 - /compra/C-Styles

- HTTP methods ACL CHECKOUT COPY DELETE GET HEAD LOCK MERGE
MKACTIVITY MKCOL MOVE NOTIFY OPTIONS PATCH POST PROPFIND
PROPPATCH PUT REPORT SEARCH SUBSCRIBE TRACE UNLOCK UNSUBSCRIBE
are allowed on :

- /
 - /Admin
 - /Barberos

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/443/www

```
The remote web server type is :  
Apache
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

```
Response Code : HTTP/1.1 302 Found

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : yes
Options allowed : (Not implemented)
Headers :

    Date: Thu, 06 Nov 2025 05:38:41 GMT
    Server: Apache
    Location: http://192.168.1.36/dashboard/
    Content-Length: 0
    Keep-Alive: timeout=5, max=98
    Connection: Keep-Alive
    Content-Type: text/html; charset=UTF-8

Response Body :
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/443/www

```
Response Code : HTTP/1.1 302 Found

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : yes
Keep-Alive : yes
Options allowed : (Not implemented)
Headers :

    Date: Thu, 06 Nov 2025 05:38:41 GMT
    Server: Apache
    Location: https://192.168.1.36/dashboard/
    Content-Length: 0
    Keep-Alive: timeout=5, max=98
    Connection: Keep-Alive
    Content-Type: text/html; charset=UTF-8

Response Body :
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/3000/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

```
Content-Security-Policy: default-src 'self' http://192.168.1.36:3000 http://localhost:3000 http://127.0.0.1:3000;style-src 'self' 'unsafe-inline' https://fonts.googleapis.com http://192.168.1.36:3000 http://localhost:3000;font-src 'self' https://fonts.gstatic.com http://192.168.1.36:3000 http://localhost:3000;img-src 'self' data: https://192.168.1.36:3000 http://localhost:3000;script-src 'self' 'unsafe-inline' 'unsafe-hashes' http://192.168.1.36:3000 http://localhost:3000 http://127.0.0.1:3000;script-src-attr 'unsafe-inline' 'unsafe-hashes';connect-src 'self' http://192.168.1.36:3000 http://localhost:3000 http://127.0.0.1:3000;frame-ancestors 'self';base-uri 'self';form-action 'self';object-src 'none';upgrade-insecure-requests
Cross-Origin-Opener-Policy: same-origin
Cross-Origin-Resource-Policy: same-origin
Origin-Agent-Cluster: ?1
Referrer-Policy: strict-origin-when-cross-origin
Strict-Transport-Security: max-age=31536000; includeSubDomains; preload
X-Content-Type-Options: nosniff
X-DNS-Prefetch-Control: off
X-Download-Options: noopen
```

```
X-Frame-Options: DENY
X-Permitted-Cross-Domain-Policies: none
X-XSS-Protection: 1; mode=block
Vary: Origin
Access-Control-Allow-Credentials: true
Access-Control-Expose-Headers: Content-Length,X-Request-Id
Permissions-Policy: geolocation=(), microphone=(), camera=()
Accept-Ranges: bytes
Cache-Control: public, max-age=0
Last-Modified: Tue, 04 Nov 2025 06:23:27 GMT
ETag: W/"3734-19a4d88e06a"
Content-Type: text/html; charset=utf-8
Content-Length: 14132
Date: Thu, 06 Nov 2025 05:38:41 GMT
Connection: keep-alive
Keep-Alive: timeout=5
```

Response Body :

```
<!DOCTYPE html>
<html lang="es">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Prestige Barbers</title>
  <link rel [...]
```

91634 - HyperText Transfer Protocol (HTTP) Redirect Information

Synopsis

The remote web server redirects requests to the root directory.

Description

The remote web server issues an HTTP redirect when requesting the root directory of the web server.

This plugin is informational only and does not denote a security problem.

Solution

Analyze the redirect(s) to verify that this is valid operation for your web server and/or application.

Risk Factor

None

Plugin Information

Published: 2016/06/16, Modified: 2025/11/03

Plugin Output

tcp/80/www

```
Request       : http://192.168.1.36/
HTTP response : HTTP/1.1 302 Found
Redirect to   : http://192.168.1.36/dashboard/
Redirect type  : 30x redirect

Final page    : http://192.168.1.36/dashboard/
HTTP response : HTTP/1.1 200 OK
```

91634 - HyperText Transfer Protocol (HTTP) Redirect Information

Synopsis

The remote web server redirects requests to the root directory.

Description

The remote web server issues an HTTP redirect when requesting the root directory of the web server.

This plugin is informational only and does not denote a security problem.

Solution

Analyze the redirect(s) to verify that this is valid operation for your web server and/or application.

Risk Factor

None

Plugin Information

Published: 2016/06/16, Modified: 2025/11/03

Plugin Output

tcp/443/www

```
Request      : https://192.168.1.36/
HTTP response : HTTP/1.1 302 Found
Redirect to   : https://192.168.1.36/dashboard/
Redirect type  : 30x redirect
```

Note that Nessus did not receive a 200 OK response from the last examined redirect.

50344 - Missing or Permissive Content-Security-Policy frame-ancestors HTTP Response Header

Synopsis

The remote web server does not take steps to mitigate a class of web application vulnerabilities.

Description

The remote web server in some responses sets a permissive Content-Security-Policy (CSP) frame-ancestors response header or does not set one at all.

The CSP frame-ancestors header has been proposed by the W3C Web Application Security Working Group as a way to mitigate cross-site scripting and clickjacking attacks.

See Also

<http://www.nessus.org/u?55aa8f57>

<http://www.nessus.org/u?07cc2a06>

<https://content-security-policy.com/>

<https://www.w3.org/TR/CSP2/>

Solution

Set a non-permissive Content-Security-Policy frame-ancestors header for all requested resources.

Risk Factor

None

Plugin Information

Published: 2010/10/26, Modified: 2021/01/19

Plugin Output

tcp/80/www

The following pages do not set a Content-Security-Policy frame-ancestors response header or set a permissive policy:

- <http://192.168.1.36/dashboard/>
- <http://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.html>
- <http://192.168.1.36/dashboard/docs/activate-use-xdebug.html>
- <http://192.168.1.36/dashboard/docs/auto-start-xampp.html>
- <http://192.168.1.36/dashboard/docs/backup-restore-mysql.html>
- <http://192.168.1.36/dashboard/docs/change-mysql-temp-dir.html>
- <http://192.168.1.36/dashboard/docs/configure-use-tomcat.html>
- <http://192.168.1.36/dashboard/docs/configure-vhosts.html>
- <http://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.html>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf1.html>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf2.html>

- <http://192.168.1.36/dashboard/docs/deploy-git-app.html>
- <http://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.html>
- <http://192.168.1.36/dashboard/docs/reset-mysql-password.html>
- <http://192.168.1.36/dashboard/docs/send-mail.html>
- <http://192.168.1.36/dashboard/docs/transfer-files-ftp.html>
- <http://192.168.1.36/dashboard/docs/troubleshoot-apache.html>
- <http://192.168.1.36/dashboard/docs/use-different-php-version.html>
- <http://192.168.1.36/dashboard/docs/use-php-fcgi.html>
- <http://192.168.1.36/dashboard/docs/use-sqlite.html>
- <http://192.168.1.36/dashboard/faq.html>
- <http://192.168.1.36/dashboard/howto.html>
- <http://192.168.1.36/dashboard/index.html>
- <http://192.168.1.36/dashboard/phpinfo.php>

50344 - Missing or Permissive Content-Security-Policy frame-ancestors HTTP Response Header

Synopsis

The remote web server does not take steps to mitigate a class of web application vulnerabilities.

Description

The remote web server in some responses sets a permissive Content-Security-Policy (CSP) frame-ancestors response header or does not set one at all.

The CSP frame-ancestors header has been proposed by the W3C Web Application Security Working Group as a way to mitigate cross-site scripting and clickjacking attacks.

See Also

<http://www.nessus.org/u?55aa8f57>

<http://www.nessus.org/u?07cc2a06>

<https://content-security-policy.com/>

<https://www.w3.org/TR/CSP2/>

Solution

Set a non-permissive Content-Security-Policy frame-ancestors header for all requested resources.

Risk Factor

None

Plugin Information

Published: 2010/10/26, Modified: 2021/01/19

Plugin Output

tcp/443/www

The following pages do not set a Content-Security-Policy frame-ancestors response header or set a permissive policy:

- <https://192.168.1.36/dashboard/>
- <https://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.html>
- <https://192.168.1.36/dashboard/docs/activate-use-xdebug.html>
- <https://192.168.1.36/dashboard/docs/auto-start-xampp.html>
- <https://192.168.1.36/dashboard/docs/backup-restore-mysql.html>
- <https://192.168.1.36/dashboard/docs/change-mysql-temp-dir.html>
- <https://192.168.1.36/dashboard/docs/configure-use-tomcat.html>
- <https://192.168.1.36/dashboard/docs/configure-vhosts.html>
- <https://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.html>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf1.html>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf2.html>

- <https://192.168.1.36/dashboard/docs/deploy-git-app.html>
- <https://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.html>
- <https://192.168.1.36/dashboard/docs/reset-mysql-password.html>
- <https://192.168.1.36/dashboard/docs/send-mail.html>
- <https://192.168.1.36/dashboard/docs/transfer-files-ftp.html>
- <https://192.168.1.36/dashboard/docs/troubleshoot-apache.html>
- <https://192.168.1.36/dashboard/docs/use-different-php-version.html>
- <https://192.168.1.36/dashboard/docs/use-php-fcgi.html>
- <https://192.168.1.36/dashboard/docs/use-sqlite.html>
- <https://192.168.1.36/dashboard/faq.html>
- <https://192.168.1.36/dashboard/howto.html>
- <https://192.168.1.36/dashboard/index.html>
- <https://192.168.1.36/dashboard/phpinfo.php>

50345 - Missing or Permissive X-Frame-Options HTTP Response Header

Synopsis

The remote web server does not take steps to mitigate a class of web application vulnerabilities.

Description

The remote web server in some responses sets a permissive X-Frame-Options response header or does not set one at all.

The X-Frame-Options header has been proposed by Microsoft as a way to mitigate clickjacking attacks and is currently supported by all major browser vendors

See Also

<https://en.wikipedia.org/wiki/Clickjacking>

<http://www.nessus.org/u?399b1f56>

Solution

Set a properly configured X-Frame-Options header for all requested resources.

Risk Factor

None

Plugin Information

Published: 2010/10/26, Modified: 2021/01/19

Plugin Output

tcp/80/www

The following pages do not set a X-Frame-Options response header or set a permissive policy:

- <http://192.168.1.36/dashboard/>
- <http://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.html>
- <http://192.168.1.36/dashboard/docs/activate-use-xdebug.html>
- <http://192.168.1.36/dashboard/docs/auto-start-xampp.html>
- <http://192.168.1.36/dashboard/docs/backup-restore-mysql.html>
- <http://192.168.1.36/dashboard/docs/change-mysql-temp-dir.html>
- <http://192.168.1.36/dashboard/docs/configure-use-tomcat.html>
- <http://192.168.1.36/dashboard/docs/configure-vhosts.html>
- <http://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.html>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf1.html>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf2.html>
- <http://192.168.1.36/dashboard/docs/deploy-git-app.html>
- <http://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.html>
- <http://192.168.1.36/dashboard/docs/reset-mysql-password.html>
- <http://192.168.1.36/dashboard/docs/send-mail.html>
- <http://192.168.1.36/dashboard/docs/transfer-files-ftp.html>

- <http://192.168.1.36/dashboard/docs/troubleshoot-apache.html>
- <http://192.168.1.36/dashboard/docs/use-different-php-version.html>
- <http://192.168.1.36/dashboard/docs/use-php-fcgi.html>
- <http://192.168.1.36/dashboard/docs/use-sqlite.html>
- <http://192.168.1.36/dashboard/faq.html>
- <http://192.168.1.36/dashboard/howto.html>
- <http://192.168.1.36/dashboard/index.html>
- <http://192.168.1.36/dashboard/phpinfo.php>

50345 - Missing or Permissive X-Frame-Options HTTP Response Header

Synopsis

The remote web server does not take steps to mitigate a class of web application vulnerabilities.

Description

The remote web server in some responses sets a permissive X-Frame-Options response header or does not set one at all.

The X-Frame-Options header has been proposed by Microsoft as a way to mitigate clickjacking attacks and is currently supported by all major browser vendors

See Also

<https://en.wikipedia.org/wiki/Clickjacking>

<http://www.nessus.org/u?399b1f56>

Solution

Set a properly configured X-Frame-Options header for all requested resources.

Risk Factor

None

Plugin Information

Published: 2010/10/26, Modified: 2021/01/19

Plugin Output

tcp/443/www

The following pages do not set a X-Frame-Options response header or set a permissive policy:

- <https://192.168.1.36/dashboard/>
- <https://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.html>
- <https://192.168.1.36/dashboard/docs/activate-use-xdebug.html>
- <https://192.168.1.36/dashboard/docs/auto-start-xampp.html>
- <https://192.168.1.36/dashboard/docs/backup-restore-mysql.html>
- <https://192.168.1.36/dashboard/docs/change-mysql-temp-dir.html>
- <https://192.168.1.36/dashboard/docs/configure-use-tomcat.html>
- <https://192.168.1.36/dashboard/docs/configure-vhosts.html>
- <https://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.html>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf1.html>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf2.html>
- <https://192.168.1.36/dashboard/docs/deploy-git-app.html>
- <https://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.html>
- <https://192.168.1.36/dashboard/docs/reset-mysql-password.html>
- <https://192.168.1.36/dashboard/docs/send-mail.html>
- <https://192.168.1.36/dashboard/docs/transfer-files-ftp.html>

- <https://192.168.1.36/dashboard/docs/troubleshoot-apache.html>
- <https://192.168.1.36/dashboard/docs/use-different-php-version.html>
- <https://192.168.1.36/dashboard/docs/use-php-fcgi.html>
- <https://192.168.1.36/dashboard/docs/use-sqlite.html>
- <https://192.168.1.36/dashboard/faq.html>
- <https://192.168.1.36/dashboard/howto.html>
- <https://192.168.1.36/dashboard/index.html>
- <https://192.168.1.36/dashboard/phpinfo.php>

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/135/epmap

```
Port 135/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/139/smb

```
Port 139/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/443/www

```
Port 443/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/1978

```
Port 1978/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/1979

```
Port 1979/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3000/www

```
Port 3000/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2025/10/29

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.10.1
Nessus build : 20010
Plugin feed version : 202511051810
Scanner edition used : Nessus Home
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : Prestige barbers 2.0
```

```
Scan policy used : Web Application Tests
Scanner IP : 192.168.1.112
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 98.678 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : enabled
Web application tests : enabled
Web app tests - Test mode : single
Web app tests - Try all HTTP methods : yes
Web app tests - Maximum run time : 5 minutes.
Web app tests - Stop at first flaw : CGI
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2025/11/6 0:35 EST (UTC -05:00)
Scan duration : 1205 sec
Scan for malware : no
```

Synopsis

The remote web server hosts linkable content that can be crawled by Nessus.

Description

The remote web server contains linkable content that can be used to gather information about a target.

See Also

<http://www.nessus.org/u?5496c8d9>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/06/24, Modified: 2016/06/24

Plugin Output

tcp/80/www

The following sitemap was created from crawling linkable content on the target host :

- <http://192.168.1.36/dashboard/>
- <http://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.html>
- <http://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.pdf>
- <http://192.168.1.36/dashboard/docs/activate-use-xdebug.html>
- <http://192.168.1.36/dashboard/docs/activate-use-xdebug.pdf>
- <http://192.168.1.36/dashboard/docs/auto-start-xampp.html>
- <http://192.168.1.36/dashboard/docs/auto-start-xampp.pdf>
- <http://192.168.1.36/dashboard/docs/backup-restore-mysql.html>
- <http://192.168.1.36/dashboard/docs/backup-restore-mysql.pdf>
- <http://192.168.1.36/dashboard/docs/change-mysql-temp-dir.html>
- <http://192.168.1.36/dashboard/docs/change-mysql-temp-dir.pdf>
- <http://192.168.1.36/dashboard/docs/configure-use-tomcat.html>
- <http://192.168.1.36/dashboard/docs/configure-use-tomcat.pdf>
- <http://192.168.1.36/dashboard/docs/configure-vhosts.html>
- <http://192.168.1.36/dashboard/docs/configure-vhosts.pdf>
- <http://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.html>
- <http://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.pdf>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf1.html>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf1.pdf>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf2.html>
- <http://192.168.1.36/dashboard/docs/create-framework-project-zf2.pdf>
- <http://192.168.1.36/dashboard/docs/deploy-git-app.html>

- <http://192.168.1.36/dashboard/docs/deploy-git-app.pdf>
- <http://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.html>
- <http://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.pdf>
- <http://192.168.1.36/dashboard/docs/reset-mysql-password.html>
- <http://192.168.1.36/dashboard/docs/reset-mysql-password.pdf>
- <http://192.168.1.36/dashboard/docs/send-mail.html>
- <http://192.168.1.36/dashboard/docs/send-mail.pdf>
- <http://192.168.1.36/dashboard/docs/transfer-files-ftp.html>
- [http://192.168.1.36/d \[...\]](http://192.168.1.36/d)

91815 - Web Application Sitemap

Synopsis

The remote web server hosts linkable content that can be crawled by Nessus.

Description

The remote web server contains linkable content that can be used to gather information about a target.

See Also

<http://www.nessus.org/u?5496c8d9>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/06/24, Modified: 2016/06/24

Plugin Output

tcp/443/www

The following sitemap was created from crawling linkable content on the target host :

- <https://192.168.1.36/dashboard/>
- <https://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.html>
- <https://192.168.1.36/dashboard/docs/access-phpmyadmin-remotely.pdf>
- <https://192.168.1.36/dashboard/docs/activate-use-xdebug.html>
- <https://192.168.1.36/dashboard/docs/activate-use-xdebug.pdf>
- <https://192.168.1.36/dashboard/docs/auto-start-xampp.html>
- <https://192.168.1.36/dashboard/docs/auto-start-xampp.pdf>
- <https://192.168.1.36/dashboard/docs/backup-restore-mysql.html>
- <https://192.168.1.36/dashboard/docs/backup-restore-mysql.pdf>
- <https://192.168.1.36/dashboard/docs/change-mysql-temp-dir.html>
- <https://192.168.1.36/dashboard/docs/change-mysql-temp-dir.pdf>
- <https://192.168.1.36/dashboard/docs/configure-use-tomcat.html>
- <https://192.168.1.36/dashboard/docs/configure-use-tomcat.pdf>
- <https://192.168.1.36/dashboard/docs/configure-vhosts.html>
- <https://192.168.1.36/dashboard/docs/configure-vhosts.pdf>
- <https://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.html>
- <https://192.168.1.36/dashboard/docs/configure-wildcard-subdomains.pdf>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf1.html>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf1.pdf>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf2.html>
- <https://192.168.1.36/dashboard/docs/create-framework-project-zf2.pdf>
- <https://192.168.1.36/dashboard/docs/deploy-git-app.html>

- <https://192.168.1.36/dashboard/docs/deploy-git-app.pdf>
- <https://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.html>
- <https://192.168.1.36/dashboard/docs/increase-php-file-upload-limit.pdf>
- <https://192.168.1.36/dashboard/docs/reset-mysql-password.html>
- <https://192.168.1.36/dashboard/docs/reset-mysql-password.pdf>
- <https://192.168.1.36/dashboard/docs/send-mail.html>
- <https://192.168.1.36/dashboard/docs/send-mail.pdf>
- <https://192.168.1.36/dashboard/docs/transfer-files-ftp.> [...]

91815 - Web Application Sitemap

Synopsis

The remote web server hosts linkable content that can be crawled by Nessus.

Description

The remote web server contains linkable content that can be used to gather information about a target.

See Also

<http://www.nessus.org/u?5496c8d9>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/06/24, Modified: 2016/06/24

Plugin Output

tcp/3000/www

The following sitemap was created from crawling linkable content on the target host :

- <http://192.168.1.36:3000/>
- <http://192.168.1.36:3000/Admin/>
- <http://192.168.1.36:3000/Admin/barberos.html>
- <http://192.168.1.36:3000/Admin/gestion-styles.css>
- <http://192.168.1.36:3000/Admin/gestion.html>
- <http://192.168.1.36:3000/Admin/index.html>
- <http://192.168.1.36:3000/Admin/productos-styles.css>
- <http://192.168.1.36:3000/Admin/productos.html>
- <http://192.168.1.36:3000/Barberos/>
- <http://192.168.1.36:3000/Barberos/B-Styles/styles.css>
- <http://192.168.1.36:3000/Barberos/index.html>
- <http://192.168.1.36:3000/Cortes/>
- <http://192.168.1.36:3000/Cortes/C-Styles/styles.css>
- <http://192.168.1.36:3000/Cortes/index.html>
- <http://192.168.1.36:3000/I-style/auth-modal.css>
- <http://192.168.1.36:3000/I-style/auth-modal.css?v=9>
- <http://192.168.1.36:3000/I-style/carrito-global.css>
- <http://192.168.1.36:3000/I-style/custom-modal.css>
- <http://192.168.1.36:3000/I-style/search-modal.css>
- <http://192.168.1.36:3000/I-style/styles.css>
- <http://192.168.1.36:3000/Tienda/>
- <http://192.168.1.36:3000/Tienda/T-styles/styles.css>

- <http://192.168.1.36:3000/Tienda/index.html>
- <http://192.168.1.36:3000/admin/>
- <http://192.168.1.36:3000/admin/barberos.html>
- <http://192.168.1.36:3000/admin/gestion-styles.css>
- <http://192.168.1.36:3000/admin/gestion.html>
- <http://192.168.1.36:3000/admin/index.html>
- <http://192.168.1.36:3000/admin/productos-styles.css>
- <http://192.168.1.36:3000/admin/productos.html>
- <http://192.168.1.36:3000/compra/>
- <http://192.168.1.36:3000/compra/C-Styles/carrito-modal.css>
- <http://192.168.1.36:3000/compra/C-Styles/modal-compra.css>
- <http://192.168.1.36:3000/compra/C-Styles/styles.css>
- <http://192.168.1.36:3000/index.html>

Attached is a copy of the sitemap file.

11032 - Web Server Directory Enumeration

Synopsis

It is possible to enumerate directories on the web server.

Description

This plugin attempts to determine the presence of various common directories on the remote web server. By sending a request for a directory, the web server response code indicates if it is a valid directory or not.

See Also

<http://projects.webappsec.org/w/page/13246953/Predictable%20Resource%20Location>

Solution

n/a

Risk Factor

None

References

XREF OWASP:OWASP-CM-006

Plugin Information

Published: 2002/06/26, Modified: 2024/06/07

Plugin Output

tcp/80/www

```
The following directories were discovered:  
/cgi-bin, /icons, /img, /xampp
```

```
While this is not, in and of itself, a bug, you should manually inspect  
these directories to ensure that they are in compliance with company  
security standards
```

11032 - Web Server Directory Enumeration

Synopsis

It is possible to enumerate directories on the web server.

Description

This plugin attempts to determine the presence of various common directories on the remote web server. By sending a request for a directory, the web server response code indicates if it is a valid directory or not.

See Also

<http://projects.webappsec.org/w/page/13246953/Predictable%20Resource%20Location>

Solution

n/a

Risk Factor

None

References

XREF OWASP:OWASP-CM-006

Plugin Information

Published: 2002/06/26, Modified: 2024/06/07

Plugin Output

tcp/443/www

```
The following directories were discovered:  
/cgi-bin, /icons, /img, /xampp
```

```
While this is not, in and of itself, a bug, you should manually inspect  
these directories to ensure that they are in compliance with company  
security standards
```

11032 - Web Server Directory Enumeration

Synopsis

It is possible to enumerate directories on the web server.

Description

This plugin attempts to determine the presence of various common directories on the remote web server. By sending a request for a directory, the web server response code indicates if it is a valid directory or not.

See Also

<http://projects.webappsec.org/w/page/13246953/Predictable%20Resource%20Location>

Solution

n/a

Risk Factor

None

References

XREF OWASP:OWASP-CM-006

Plugin Information

Published: 2002/06/26, Modified: 2024/06/07

Plugin Output

tcp/3000/www

```
The following directories were discovered:  
/Admin, /admin, /compra
```

```
While this is not, in and of itself, a bug, you should manually inspect  
these directories to ensure that they are in compliance with company  
security standards
```

Synopsis

The remote web server hosts office-related files.

Description

This plugin connects to the remote web server and attempts to find office-related files such as .doc, .ppt, .xls, .pdf etc.

Solution

Make sure that such files do not contain any confidential or otherwise sensitive information and that they are only accessible to those with valid credentials.

Risk Factor

None

Plugin Information

Published: 2003/03/19, Modified: 2025/09/29

Plugin Output

tcp/80/www

The following office-related files are available on the remote server :

- Adobe Acrobat files (.pdf) :
 - /dashboard/docs/access-phpmyadmin-remotely.pdf
 - /dashboard/docs/activate-use-xdebug.pdf
 - /dashboard/docs/create-framework-project-zf1.pdf
 - /dashboard/docs/create-framework-project-zf2.pdf
 - /dashboard/docs/deploy-git-app.pdf
 - /dashboard/docs/increase-php-file-upload-limit.pdf
 - /dashboard/docs/reset-mysql-password.pdf
 - /dashboard/docs/send-mail.pdf
 - /dashboard/docs/use-sqlite.pdf
 - /dashboard/docs/use-php-fcgi.pdf
 - /dashboard/docs/use-different-php-version.pdf
 - /dashboard/docs/troubleshoot-apache.pdf
 - /dashboard/docs/transfer-files-ftp.pdf
 - /dashboard/docs/configure-wildcard-subdomains.pdf
 - /dashboard/docs/configure-vhosts.pdf
 - /dashboard/docs/configure-use-tomcat.pdf
 - /dashboard/docs/change-mysql-temp-dir.pdf
 - /dashboard/docs/backup-restore-mysql.pdf
 - /dashboard/docs/auto-start-xampp.pdf

Synopsis

The remote web server hosts office-related files.

Description

This plugin connects to the remote web server and attempts to find office-related files such as .doc, .ppt, .xls, .pdf etc.

Solution

Make sure that such files do not contain any confidential or otherwise sensitive information and that they are only accessible to those with valid credentials.

Risk Factor

None

Plugin Information

Published: 2003/03/19, Modified: 2025/09/29

Plugin Output

tcp/443/www

The following office-related files are available on the remote server :

- Adobe Acrobat files (.pdf) :
 - /dashboard/docs/access-phpmyadmin-remotely.pdf
 - /dashboard/docs/activate-use-xdebug.pdf
 - /dashboard/docs/create-framework-project-zf1.pdf
 - /dashboard/docs/create-framework-project-zf2.pdf
 - /dashboard/docs/deploy-git-app.pdf
 - /dashboard/docs/increase-php-file-upload-limit.pdf
 - /dashboard/docs/reset-mysql-password.pdf
 - /dashboard/docs/send-mail.pdf
 - /dashboard/docs/use-sqlite.pdf
 - /dashboard/docs/use-php-fcgi.pdf
 - /dashboard/docs/use-different-php-version.pdf
 - /dashboard/docs/troubleshoot-apache.pdf
 - /dashboard/docs/transfer-files-ftp.pdf
 - /dashboard/docs/configure-wildcard-subdomains.pdf
 - /dashboard/docs/configure-vhosts.pdf
 - /dashboard/docs/configure-use-tomcat.pdf
 - /dashboard/docs/change-mysql-temp-dir.pdf
 - /dashboard/docs/backup-restore-mysql.pdf
 - /dashboard/docs/auto-start-xampp.pdf

10662 - Web mirroring

Synopsis

Nessus can crawl the remote website.

Description

This plugin makes a mirror of the remote website(s) and extracts the list of CGIs that are used by the remote host.

It is suggested that you change the number of pages to mirror in the 'Options' section of the client.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/05/04, Modified: 2025/11/03

Plugin Output

tcp/3000/www

```
Webmirror performed 54 queries in 1s (54.000 queries per second)
```

```
The following CGIs have been discovered :
```

```
+ CGI : /Admin/  
  Methods : GET  
  Argument : configOption  
  Value: principal  
  
+ CGI : /admin/  
  Methods : GET  
  Argument : configOption  
  Value: principal  
  
+ CGI : /Admin/productos.html  
  Methods : GET  
  Argument : categoria  
  Value: Accesorios  
  Argument : descripcion  
  Argument : imagen  
  Argument : marca  
  Argument : nombre  
  Argument : precio  
  Argument : stock
```

```
Argument : tamano  
Argument : tipo
```

```
+ CGI : /admin/productos.html  
Methods : GET  
Argument : categoria  
Value: Accesorios  
Argument : descripcion  
Argument : imagen  
Argument : marca  
Argument : nombre  
Argument : precio  
Argument : stock  
Argument : tamano  
Argument : tipo
```

```
+ CGI : /Admin/index.html  
Methods : GET  
Argument : configOption  
Value: principal
```

```
+ CGI : /admin/index.html  
Methods : GET  
Argument : configOption  
Value: principal
```