```
1 function [d] = perpDist2line (x,y,a,b,c)
2 % perpDist2line.m - calculates perpendicular distance from
                     a point to a line
3 | %
4 | %
5
  용
      Input x and y coordinates of a point & the coefficients of
6
  읭
          line A (a b c) of the form: aX + bY + c = 0
7
  용
8
  용
      Output: distance
9
  읭
10 \| Syntax: [d] = perp2line (x1,y1,a,b,c)
11 | %
13 % Other m-files required:
14 | %
15 % Subfunctions:
16 | %
17 % MAT-files required: none
18 | %
19 % See also: Survey Theory & Practice, 7th ed. J.Anderson, E.Mikhail
20 % pp. 1071, A20
22 % Author: Peter J Dailey, Carlos Ramierz
23 % 140 Sunset Drive Charleston WV 25301
24 % email: daileypj@mac.com
25 % Website: http://
26 % Last revision: 3-June-2009
28 | %
29 8 Copyright 2010 by Peter J Dailey
30 | %
31 % Permission to use, copy, modify, distribute, and sell this software and i
32 % documentation for any purpose is hereby granted without fee, provided tha
33 % the above copyright notice appear in all copies and that both that
34 % copyright notice and this permission notice appear in supporting
35 % documentation, and that the name of Peter J Dailey not be used in
36 % advertising or publicity pertaining to distribution of the software witho
37 % specific, written prior permission.
38\,\|\,\mbox{\%} Peter J Dailey makes no representations about the
39 % suitability of this software for any purpose. It is provided "as is"
40 % without express or implied warranty.
42 8
43 | if nargin<5
  error('Too few input arguments');
44
45 elseif nargin>5
46
    error('Too many input arguments');
47 end
48 \| % d = abs[(aX + bY +c)/srt(a^2 + b^2)]
49 \mid d = abs(((a*x) + (b*y) + c)/sqrt((a^2) + (b^2)));
50 end
51
```