

SBMLsqueezer 2: a context-sensitive rate law generator for biochemical networks with access to SABIO-RK

Andreas Dräger^{1,2,*}, Roland Keller², Matthias Rall², Johannes Eichner², Bernhard Ø. Palsson¹, Andreas Zell²

¹Systems Biology Research Group, University of California, San Diego, La Jolla, CA, United States

²Center for Bioinformatics Tuebingen (ZBIT), University of Tuebingen, Tübingen, Germany

Received on XXXXX; revised on XXXXX; accepted on XXXXX

Associate Editor: XXXXXXXX

ABSTRACT

Summary: Modeling metabolic networks belongs to the most laborious and error-prone tasks in systems biology. Size and complexity of published reconstructions are steadily increasing. In order to simulate the dynamics of quantitative models, kinetic equations need to be derived for each reaction. Parameters and units also need to be specified. The manual assignment of these equations is not practicable for large numbers of reactions. Complex test-and-evaluation cycles require automated methods for rate law assignment. The program SBMLsqueezer is a generator for kinetic equations, parameters, and units. It distinguishes between multiple types of reactions and selects only suitable rate laws. The user can influence all choices made by the program in order to assign the desired type of rate law to each reaction. Experimentally derived rate laws can be obtained through a connection to the kinetics database SABIO-RK. This platform-independent program can be used in a large variety of ways, enabling flexible solutions and use-case scenarios.

Availability: Program, source code, and documentation can be obtained under the terms of the GPL version 3 from the website <http://www.cogsys.cs.uni-tuebingen.de/software/SBMLsqueezer/>.

Contact: sbmlsqueezer@googlegroups.com

1 INTRODUCTION

The reconstruction of genome-scale networks has been recognized as a highly laborious long-term effort, which requires several iterations of curation (Thiele and Palsson, 2010). However, for the creation of dynamic network simulations, the formulation of such a structural network is just the first step. For each reaction within the network, a specific kinetic equation, a so-called rate law, needs to be derived. These rate laws typically contain parameters, such as Michaelis constants, or even plain numbers, which are not always intended to be dimensionless quantities. Reactive species in these models may cross compartments through transport reactions. Hence, their reaction space may change and consequently their molarity with the volume differences of each compartment. Ensuring unit consistency for the entire network requires careful consideration. When a model is finally used as the basis for technical applications, inconsistent units could compromise therapeutic procedures or even endanger health and safety of patients.

Manually deriving both, kinetic equations and all units, brings several problems with it, because it a) is highly error-prone, b) very time-consuming, and c) cannot be applied in large-scale or automated approaches. For these reasons, automatic procedures are required for the assembly of rate laws. Programs, such as COPASI (Hoops *et al.*, 2006), CellDesigner (Funahashi *et al.*, 2007), the MASS-Toolbox (<http://opencobra.github.io/MASS-Toolbox/>), and Cellerator (Shapiro *et al.*, 2002), provide pre-defined lists of kinetic equations and also allow the user to modify these rate laws or to even create customized equations. CellDesigner 4.3 provides a dialog that assists the user to obtain rate laws from the kinetics database SABIO-RK (Wittig *et al.*, 2012). The MASS-Toolbox focuses on the creation of elementary rate laws and automatically derives pseudo-elementary rate constants with their units. Inference programs, such as NetGenerator (Weber *et al.*, 2013), estimate a topology and generate specific rate laws for gene-regulatory processes. Odefy (Krumsiek *et al.*, 2010) converts discrete Boolean networks into quantitative differential equation systems by applying Hill-type rate laws to each transition.

In contrast, SBMLsqueezer applies several criteria to automatically select appropriate equations for each reaction. The user can influence these criteria and choose which rate law to apply. The aims of this approach are a) to ensure that only applicable rate laws can be selected and thus the consistency of the model, and b) to reduce the required human interaction to a minimum. SBMLsqueezer is intended to be useful for modeling not only metabolic networks but also signal transduction processes and gene-regulatory mechanisms.

2 RESULTS

Originally, SBMLsqueezer has been developed as a plug-in for CellDesigner (Dräger *et al.*, 2008). It was then extended to a stand-alone tool (Dräger *et al.*, 2010). SBMLsqueezer 2 can be used as a) on-line program, b) stand-alone tool via graphical user interface or command-line, c) plug-in for CellDesigner, d) Garuda gadget, and e) through its API in complex workflows and algorithms.

The vast majority of biochemical reactions can be categorized into a limited number of classes. SBMLsqueezer takes several features of the reaction into account in order to discriminate these classes. For each class it either determines all kinds of principally applicable rate laws, or the most suitable rate law. The user can influence how rate laws are picked. An equation preview assists the user to make this decision. The program equips all newly generated

*to whom correspondence should be addressed

Bornstein *et al.* (2008). LibSBML: an API library for SBML. *Bioinformatics*, **24**(6), 880–881.

Büchel *et al.* (2013). Large-scale generation of computational models from biochemical pathway maps. *BMC Syst Biol*, **7**(1), 116.

Courtot *et al.* (2011). Controlled vocabularies and semantics in systems biology. *Mol Syst Biol*, **7**, 543.

Dräger, A. (2011). *Computational Modeling of Biochemical Networks*. Ph.D. thesis, University of Tuebingen.

Dräger, *et al.* (2008). SBMLsqueezer: a CellDesigner plug-in to generate kinetic rate equations for biochemical networks. *BMC Syst Biol*, **2**(1), 39.

Dräger *et al.* (2009a). Modeling metabolic networks in *C. glutamicum*: a comparison of rate laws in combination with various parameter optimization strategies. *BMC Syst Biol*, **3**, 5.

Dräger *et al.* (2009b). SBML2 \LaTeX : Conversion of SBML files into human-readable reports. *Bioinformatics*, **25**(11), 1455–1456.

Dräger *et al.* (2010). *Systems Biology for Signaling Networks*, volume 2, chap. Automating mathematical modeling of biochemical reaction networks. Springer.

Dräger *et al.* (2011). JSBML: a flexible Java library for working with SBML. *Bioinformatics*, **27**(15), 2167–2168.

Funahashi *et al.* (2007). Integration of CellDesigner and SABIO-RK. *In Silico Biology*, **7**(2 Suppl), S81–S90.

Ghosh *et al.* (2011). Software for systems biology: from tools to integrated platforms. *Nat Rev Genet*, **12**(12), 821–832.

Goecks *et al.* (2010). Galaxy: a comprehensive approach for supporting accessible, reproducible, and transparent computational research in the life sciences. *Genome Biol*, **11**(8), R86.

Hoops *et al.* (2006). COPASI—a Complex Pathway Simulator. *Bioinformatics*, **22**(24), 3067–3074.

Hucka *et al.* (2004). Evolving a *lingua franca* and associated software infrastructure for computational systems biology: the Systems Biology Markup Language (SBML) project. *Systems Biology, IEEE*, **1**(1), 41–53.

Krumsiek *et al.* (2010). Odeify—from discrete to continuous models. *BMC Bioinformatics*, **11**, 233.

Shapiro *et al.* (2002). Cellerator: extending a computer algebra system to include biochemical arrows for signal transduction simulations. *Bioinformatics*, **19**(5), 677–678.

Thiele, I. and Palsson, B. Ø. (2010). A protocol for generating a high-quality genome-scale metabolic reconstruction. *Nat Protoc*, **5**(1), 93–121.

Weber *et al.* (2013). Inference of dynamical gene-regulatory networks based on time-resolved multi-stimuli multi-experiment data applying NetGenerator v2.0. *BMC Syst Biol*, **7**(1), 1.

Wittig *et al.* (2012). SABIO-RK—database for biochemical reaction kinetics. *Nucleic Acids Res.* **40**(Database issue), D790–D796.