nestself



Consultations and webinars

Private expert and employee video sessions, webinars for client companies and small group workshops on Amazon Chime SDK in Frankfurt. The plan, the decisions, the stories, and your ten answers as they were applied.

Epic NS-CALLS-01
Review copy, 24 October 2026

Status
Founder answers applied, v1.1

Full package
docs/tasks/calls-webinars/

START HERE

How to read this document

Forty minutes end to end. The yellow pages show your answers and what changed because of them.

Everything in this copy comes from the planning package on branch `feat/calls-webinars`. Each decision, story and spike keeps its id, so a comment like "change D-CW-17" or "drop WBN-14" lands exactly. The long engineering documents (backlog and implementation guidelines) are not reproduced here.

What is already fixed

The auth strategy chose Amazon Chime SDK in eu-central-1 behind an adapter, one join entry point with a time window, recording off by default and support diagnostics without content. This plan builds on that and does not reopen it.

What changed with your answers

Every webinar is recorded and attendees never have cameras; the floor is audio given by a host; audiences above 250 move up to M3; the end of a consultation leads to a follow-up with manager approval where the company wants it; the launch is Serbia only. Nothing waits on you: M0 can start.

Contents

01	The plan in brief: what we build, milestones, cost, risks	3
02	What you decided: ten answers and how each was applied	7
03	The decisions: thirty-eight rulings in one line each	10
04	The stories: 102 user stories with acceptance criteria	14
05	Closing: what is deliberately not written, next steps	33

settled follows from an earlier binding decision or a verified fact **ruled** taken here with a default you can overturn **spike pending** binds after a measurement in M0 **P0** needed for the pilot **P1** first quarter after **P2** later

THE PLAN IN BRIEF

What we build and the loop it closes

Three formats on one real-time layer. Epic NS-CALLS-01, milestones M0 to M4.

Private one-to-one consultations; webinars where employees watch one or two presenters without seeing each other; small workshops on video. All three share the Chime adapter, the session model, the client, the event ingestion and the diagnostics.

A consultation

1. **Neutral reminder**
   "Your NestSelf session", 24 h and 1 h before, private calendar entry.
2. **Pre-join check**
   Devices and network, camera off if wanted, blur, permission help.
3. **Private room**
   Only the two participants, 15 min before to 10 min after; not recorded.
4. **Outcome, then follow-up**
   The expert records the outcome and proposes a follow-up; the employee confirms or suggests a time; a manager approves if the company policy says so.
5. **Private feedback**
   Optional, one to five, never visible to the employer.

A webinar

1. **Discover and register**
   Eligible employees register; capacity enforced; "this webinar is recorded" stated up front.
2. **Lobby**
   Title, presenter, countdown; "your camera stays off; write to the hosts or raise your hand".
3. **Live**
   Presenter video and slides; no roster, no attendee cameras; chat to the hosts, published anonymously; polls; the floor (audio) given by a host.
4. **Replay**
   Presenter-only recording of every webinar, reviewed as content before anyone sees it.

In this epic

- A minimal appointment spine; the Chime adapter with a local fake
- Pre-join and in-call client; screens in both web apps
- Follow-up after a call, with manager approval by company policy
- Webinars: registration, reminders, chat, polls, the floor, moderation
- Presenter-only recording of every webinar, handoff to the CMS
- Diagnostics, audit, neutral emails, tests, infrastructure
- M3: audiences up to 1,000, certificates; M4: mobile, workshops, captions

Deliberately not in it

- Availability, booking, funding, rescheduling rules (a booking epic)
- Review and publication of replays (the CMS epic)
- Recording of consultations (not for now); attendee cameras (never)
- Extending a running session (replaced by the follow-up)
- Live captions; phone dial-in; SMS and push; professional notes
- Native mobile call modules, screen share from phones
- A Hungarian launch (the locale stays for Vojvodina)

THE PLAN IN BRIEF

Milestones, effort and cost

Effort is a planning range for engineers who already know the repository; prices are AWS list prices in October 2026.

Milestone	Outcome	What a demo shows	Person-days
M0	Foundation and spikes	The adapter with its fake, the dev video stack deployed, contracts, the appointment spine, sample data, eight spike results written down	8 to 14.5
M1	Consultations end to end, with the follow-up	An expert in the admin app and an employee in the workspace app meet in a private room; afterwards the expert proposes a follow-up, the employee confirms, and a manager approves it where the company policy requires	27.5 to 42.5
M2	Webinars live up to 250, always recorded	An operator publishes an occurrence, employees register, the recording starts with the webinar, the chat runs through the hosts, a host gives an attendee the floor, the replay lands in content review	22 to 33.5
M3	Scale, certificates, load test	An occurrence with 600 registrations runs on a replicated meeting; opt-in certificates with a neutral title; a load test before the first large webinar	6 to 9.5
M4	Mobile, workshops, captions	Joining from the phone app, a 25-person workshop, Serbian replay captions	7 to 10
Total	71 to 110 person-days bottom-up; plan 90 to 135 with a buffer for reviews, spike outcomes and rebases against the parallel auth work		71 to 110

0.0017

US dollars per attendee-minute, the only price that matters at pilot scale; a 45-minute consultation costs about 15 cents

87 to 114

US dollars per month at 500 consultations and one monthly webinar of 100 to 300 attendees with a replay

385 to 394

US dollars per month at 2,000 consultations and a 1,000-attendee webinar; volume pricing is worth a conversation after 1,000 consultations a month

How a webinar is delivered, by audience size

Audience	Model	Why	When
Up to 25	One meeting, everyone on video (workshop)	Fits the 25 concurrent video senders a meeting allows	M4
26 to 250	One meeting, receive-only audience	Attendees cannot send audio or video, so they cannot see or hear each other; simplest and cheapest	M2
251 to 1,000	One presenter meeting replicated into up to four audience meetings	Replica attendees receive only the presenters; adds about one cent per audience-meeting-minute	M3
Above 1,000	Presenter meeting streamed to Amazon IVS	Unlimited viewers at three to five seconds of delay; questions over our own channel	Documented only

THE PLAN IN BRIEF

Risks, and the legal checklist

Serbian law only. Checklist items are launch conditions for the production account and never block development.

Risks we accept knowingly

- **No maintained React Native module.** Mobile uses the web client inside the app; screen share from phones is not possible.
- **Serbian and Hungarian live captions.** Not supported by Chime transcription; replays are captioned later with review.
- **Recording pipeline quota.** Ten concurrent pipelines by default in Frankfurt; a quota request before the first busy month.
- **Corporate networks.** Blocked UDP falls back to TCP 443 with lower quality; client companies get a one-page network note.

Risks we watch

- **Parallel auth work.** Both efforts edit the action and template catalogue; those tasks go last and rebase first.
- **Undocumented idempotency.** Chime does not document what a repeated create request returns; the Redis lock is the real protection, measured in spike 1.
- **The floor in replicated meetings.** A reported audio dropout after 40 minutes; measured at the start of M3 before replication is built.
- **Approval policy without an approver.** A company that requires approval but names no approver for a unit: the proposal fails visibly and tells the employee to ask HR.
- **Recorded voices.** An attendee given the floor is on the recording; the notice before unmuting is logged, since Serbian law on recording is explicit about consent.

Before the first real consultation in production

1. DPIA under ZZPL Art.
2. Webinar recording notice: registration, confirmation email and lobby state that the webinar is recorded and that only presenters are on the recording; an attendee given the floor is told their voice is recorded (D-CW-34; LAW-10 on Art.
3. Product copy: "encrypted in transit and at rest", never "end-to-end encrypted" (LAW-07); the accessibility statement on captions (D-CW-23).
4. Expert credentials and confidentiality under Serbian law: psychologists' professional secrecy (LAW-15); the expert onboarding epic captures the licence; the Commissioner's position that an employer must never learn a diagnosis (LAW-14) is why the approval item of D-CW-37 carries no category.
5. Client-company network note: `*.chime.aws` on UDP 3478 and TCP 443, `*.sdkassets.chime.aws` on TCP 443 (CORE-30).
6. Service quota requests in eu-central-1 before scale (D-CW-31).
7. Volume pricing conversation with AWS after 1,000 consultations per month (COST-10).
8. Kept for a later Hungarian launch, not for now: Hungarian recording consent and telemedicine rules, psychotherapy licensing, NAIH practice (LAW-19 to LAW-25); Hungarian crisis hotlines in the crisis block.

THE PLAN IN BRIEF

The measurements that come first, and what happens next

Eight spikes run in M0 against the dev account before the lifecycle decisions bind.

Spike	Question	Method	Binds
SPIKE-CW-01	Does a repeated `ClientRequestToken` return the same meeting, a `ConflictException`, or a second meeting?	Script against the dev account, two calls 0 ms and 2 s apart	D-CW-07
SPIKE-CW-02	Does `CreateAttendee` with a repeated `ExternalUserId` return the existing attendee?	Same script	D-CW-08
SPIKE-CW-03	Does a media-pipeline attendee count against `Attendee.MaxCount`, and does it keep the meeting alive past 5 empty minutes?	Create a meeting with `MaxCount 2`, two attendees, start a capture pipeline	D-CW-10, D-CW-18
SPIKE-CW-04	Do `SelectedVideoStreams` and `CompositedVideo PresenterOnly` combine into one presenter-only composited MP4?	Record a 3-minute test webinar with one presenter and two receive-only attendees	D-CW-18
SPIKE-CW-05	Does the ticket web route join a meeting with audio and video inside the Expo app on iOS (WKWebView) and Android?	Prototype `apps/workspace/src/routes/call/$appointmentId.tsx` and open it with `react-native-webview` in the simulator and a device	D-CW-24
SPIKE-CW-06	Do attendees given the floor in replica meetings lose audio after 40 to 50 minutes (WEB-39)?	At the start of M3, before replication is built	D-CW-14, D-CW-36
SPIKE-CW-07	What is the delivery latency of direct SQS versus EventBridge to the queue?	Timestamps on 20 events	D-CW-12
SPIKE-CW-08	Can two Playwright Chromium contexts join one real meeting in CI?	Prototype the `video-smoke` workflow	D-CW-33

What happens next

1. Your answers are applied; nothing waits on you.
2. M0 starts: catalog additions and one install, the adapter with its fake, the dev video stack, the appointment spine, the eight spikes.
3. Spike results are written to the package; any decision marked spike pending binds or changes.
4. M1 delivers the first real consultation between the two web apps, then M2 the first webinar.
5. The DPIA and the legal checklist run before production.

WHAT YOU DECIDED

Ten answers, and how each was applied

Answered on 24 October 2026. Each answer changed the decisions, the stories and the backlog; the ids on the right lead to the detail.

F-CW-01 Will consultations be recorded (with dual consent)?

Your answer	Not for now. Every webinar is recorded.
Applied as	D-CW-34, D-CW-18, D-CW-19; recording moves into M2

F-CW-02 Webinar audience ceiling?

Your answer	No product ceiling; a technical ceiling is acceptable. 200 to 300 attendees expected in the first year. Attendees never have cameras; they write in the chat or raise a hand, and a host decides who gets audio.
Applied as	D-CW-35, D-CW-36; replication moves from M4 to M3; chat replaces Q&A; floor is audio only

F-CW-03 Certificates of attendance for webinars?

Your answer	Default accepted.
Applied as	Opt-in, neutral title, 60 percent threshold

F-CW-04 Ask the employee for their current location at the start of psychological sessions?

Your answer	Ask, never mandatory; declining is fine.
Applied as	Default confirmed (optional prompt, session-only storage)

F-CW-05 Native mobile call experience in the first year?

Your answer	No.
Applied as	D-CW-24 stands: web route inside the app

WHAT YOU DECIDED

Ten answers, and how each was applied (continued)

Continued from the previous page.

F-CW-06 May an expert extend a running session?

Your answer	No. A follow-up must be schedulable at the end of the call, with manager approval where the company's policy requires it; the end of the call needs a few minutes for that.
Applied as	D-CW-37: post-call follow-up proposal, confirmation, suggested times, approval items and the organisation policy

F-CW-07 Who may moderate webinars?

Your answer	Default accepted.
Applied as	`service_coordinator`, `client_operations`, `platform_owner` hold `event.moderate`

F-CW-08 Webinar audience default?

Your answer	Default accepted.
Applied as	`all_eligible` for NestSelf-run webinars; organisation-scoped for client-requested ones

F-CW-09 Retention periods?

Your answer	Defaults accepted.
Applied as	D-CW-29

F-CW-10 DPIA owner and date?

Your answer	Development must not be blocked.
Applied as	The DPIA runs in parallel with development and gates only the production launch; no task depends on it

Ten answers, and how each was applied (continued)

Continued from the previous page.

Launch

Where does NestSelf launch?

Your answer	Serbia only. Hungarian is the language of the minority in Vojvodina.
Applied as	D-CW-38: Serbian law in the checklist, Serbian hotlines in the crisis block, Serbian captions first, all four locales kept.

THE DECISIONS

Thirty-eight rulings, one line each

The full record has the alternatives, the evidence ids and the canonical names. D-CW-34 to D-CW-38 come from your answers.

D-CW-01 One epic, four milestones ruled, default applies

M0 foundation, M1 consultations with the end-of-call follow-up, M2 webinars live and always recorded, M3 scale and certificates, M4 mobile, workshops and captions. The formats share the adapter, the session model, the client and the diagnostics.

D-CW-02 A minimal appointment spine, not the booking engine ruled, default applies

Nothing about appointments exists in the code. The epic adds only what a call needs. Availability, booking, funding and rescheduling are a later epic behind a fixed contract seam.

D-CW-03 Webinar occurrences here, replays in the CMS ruled, default applies

Registration, live session, Q&A and the recording up to a finished MP4 are built here. Review and publication of the replay follow the CMS epic's workflow.

D-CW-04 Out of scope for the whole epic ruled, default applies

Phone dial-in and SMS, professional notes, settlement, employer reports, live captions, webinars above 1,000 attendees, native mobile modules and chat in consultations.

D-CW-05 A provider adapter with a fake for local work settled

A `VideoProvider` with the Chime implementation and a deterministic fake for development and tests. Only the current `chime-sdk-meetings` namespace is used.

D-CW-06 Everything in eu-central-1 settled

Control, media and pipeline regions are hard-coded and validated at start-up. Product copy says encrypted in transit and at rest, never end-to-end, because audio is mixed on the server.

D-CW-07 The meeting is created at the first join ruled, spike pending

A Chime meeting ends after five empty minutes, so it cannot be created at booking. A Redis lock serialises concurrent first joins; the idempotency token is a second line of defence.

D-CW-08 Rejoin reuses the same attendee ruled, default applies

Join tokens have no clock expiry. Credentials are cached in Redis for the window, never written to PostgreSQL or logs, and the response is marked no-store.

D-CW-09 Explicit end plus a safety net ruled, default applies

End for everyone deletes the meeting at once. A delayed job closes any room at the scheduled end plus 15 minutes. No extension: the follow-up is scheduled on the post-call screens instead.

D-CW-10 Meeting features per format ruled, default applies

720p video, echo reduction on, full HD content share. Capacity 4 for a consultation, 250 for a webinar, 30 for a workshop. Webinar attendees are receive-only.

THE DECISIONS

Thirty-eight rulings, one line each (continued)

Continued from the previous page.

D-CW-11 **Opaque identities towards the provider** ruled, default applies

Random per-session participant ids as external ids and the organisation id as tenant id. No name or email ever leaves the platform.

D-CW-12 **Provider events through a queue into the worker** ruled, default applies

Direct queue notifications plus an EventBridge backstop. Every event is stored once under a unique key and applied safely out of order; attendee-minutes are derived from events.

D-CW-13 **Client observability without content** ruled, default applies

The browser posts failure events and 30-second quality aggregates to the API. Kept 90 days. Alerts on join failures and slow starts.

D-CW-14 **Webinar delivery by audience size** ruled, default applies

One meeting up to 250 attendees in M2. Media replication to 1,000 in M3, because 200 to 300 attendees are expected in the first year. Streaming beyond that is documented, not built.

D-CW-15 **Attendee anonymity enforced on the server** ruled, default applies

Attendees never send video. No roster for attendees, a count for presenters, names only for the moderator. A host gives the floor, audio only; the attendee unmutes to speak; the host can take it back.

D-CW-16 **Interaction on Socket.IO and PostgreSQL** ruled, default applies

The webinar chat, hand-raise, polls and quick signals use the existing gateway with authorised rooms. Chime data messages and Chime messaging are not used.

D-CW-17 **Audience policy, registration and windows** ruled, default applies

All eligible members, chosen organisations or units. Capacity is locked at registration; the recording is announced there. Hosts join 30 minutes before, attendees 15. Employers never receive lists.

D-CW-18 **Every webinar is recorded, presenter-only** ruled, spike pending

Recording starts with the webinar and stops with it. Only presenter video and audio are captured into one MP4 in a KMS-encrypted Frankfurt bucket; everyone sees REC (spikes 3 and 4).

D-CW-19 **Consultations are not recorded for now** settled

Your answer to F-CW-01. The API role has no pipeline permission. The dual-consent data model stays specified for a later decision after the DPIA.

D-CW-20 **One web client package on the Chime JavaScript SDK** ruled, default applies

`@nestself/video` has its own hooks and components on the design tokens. The AWS React component library is not used because it brings its own styling.

THE DECISIONS

Thirty-eight rulings, one line each (continued)

Continued from the previous page.

D-CW-21 Pre-join is mandatory
ruled, default applies
Camera, microphone, speaker and network checks, join with camera off, opt-in blur and browser permission help. Camera on by default after the preview.

D-CW-22 In-call behaviour ruled, default applies
Speaker view, a three-state connection badge, degraded mode down to audio, two minutes of reconnection then rejoin, a five-minute cue that also reminds the expert of the follow-up, the crisis block with Serbian hotlines one tap away, keyboard and reduced-motion support.

D-CW-23 No live captions yet
ruled, default applies
Chime's transcription does not accept Serbian or Hungarian. Replay captions through batch transcription with human review are an M4 item.

D-CW-24 Mobile joins through the web client inside the app ruled, spike pending
No maintained React Native module exists. The app opens a ticketed web call route in a WebView. Native modules are a later epic (F-CW-05).

D-CW-25 Tables and tenancy
ruled, default applies
Nineteen tables under forced row-level security, including approval items and webinar messages. Outcomes hold a delivery status and connection data only, never notes. Feedback never reaches the employer.

D-CW-26 Neutral notifications
ruled, default applies
Reminders 24 hours and 1 hour before with a neutral subject and a private calendar entry, templates in four locales. No push or SMS in this epic.

D-CW-27 No chat in consultations
ruled, default applies
Only quick signals such as I cannot hear you and the expert's running-late message. Workshops get a chat kept for 24 hours.

D-CW-28 Support diagnostics
ruled, default applies
One endpoint with exactly the redacted field set of the auth strategy, proven by a serialisation test and audited on every view.

D-CW-29 Retention defaults
ruled, default applies
Session metadata 7 years, diagnostics 90 days, questions 12 months, feedback 24 months, raw recording segments 30 days. Pending your L-02 and L-03 answers.

D-CW-30 Employer isolation
ruled, default applies
No route returns participants, registrations, question authors or feedback to organisation-scoped principals. Aggregates only above a group of five, and those belong to the reporting epic.

THE DECISIONS

Thirty-eight rulings, one line each (continued)

Continued from the previous page.

D-CW-31 Infrastructure ruled, default applies

A video stack per stage: events queue, EventBridge rule, recordings bucket and two managed policies. The dev stage deploys it alone, like the auth stack.

D-CW-32 Dependencies ruled, default applies

Four AWS and Chime packages plus a test mock, and a WebView in M4, added to the catalog. Calendar files and date formatting are written in-house.

D-CW-33 Verification contract ruled, default applies

Authorisation golden cases, event idempotency tests, browser journeys with fake media, motion suite entries, a nightly real-provider smoke test and a load test before the first large webinar.

D-CW-34 Every webinar is recorded; consultations are not settled

Your answer to F-CW-01. No recording switch on an occurrence; the recording is announced at registration, in the email and in the lobby; the replay always goes to content review.

D-CW-35 Attendees never have cameras; chat and the floor settled

Your answer to F-CW-02. Hosts post to everyone; attendees write to the hosts and a host publishes, anonymously by default. A hand-raise can be given the floor: audio only, host-controlled.

D-CW-36 The ceiling is technical, not a product rule ruled, default applies

250 per meeting in M2, 1,000 with replication in M3. Until then the occurrence form refuses a larger capacity and says why.

D-CW-37 Follow-up on the post-call screens, approval by policy settled

Your answer to F-CW-06. The expert proposes a time after the outcome; the employee confirms, suggests three windows or declines; the organisation policy routes a manager approval that never shows the category.

D-CW-38 Serbia only; Hungarian is a language settled

Launch for client companies in Serbia. Hungarian serves the minority in Vojvodina. Serbian law in the checklist, Serbian hotlines in the crisis block, Serbian captions first.

THE STORIES

102 user stories with acceptance criteria

Ids are stable: CALL consultations, WBN webinars, WKS workshops, PLT platform and support. P0 is needed for the pilot. The grounding column (decision and evidence ids) is in the markdown.

Id	Pri	M	Story	Acceptance criteria
1. Consultations: employee side 17 stories				
CALL-01	P0	M1	As an employee, I receive reminders before my consultation so I do not miss it.	1. Email reminders sent at 24 h and 1 h before `startsAt` (`REMINDER_OFFSETS_MINUTES`). 2. Subject from `calls.email.reminder_subject`, no service category. 3. ICS attachment: `CLASS:PRIVATE`, neutral `SUMMARY`, authenticated join link in `DESCRIPTION`, `X-MICROSOFT-CDO-BUSYSTATUS:BUSY`. 4. Templates in all four locales. 5. Online employee sees a toast via `appointment.remind`.
CALL-02	P0	M1	As an employee, I join my consultation from the appointment page.	1. The appointment detail page at `/appointments/$appointmentId` shows a "Join session" button that becomes enabled at `startsAt` minus 15 minutes (`CALL_JOIN_WINDOW_BEFORE_MINUTES`). 2. Clicking "Join session" navigates to the pre-join screen. 3. The button is disabled and shows a "Come back at HH:MM" label (formatted in the appointment's `timeZone`) before the window opens. 4. `POST /appointments/:id/join` requires `consultation.join` on the appointment resource. A principal who is not the employee or the assigned expert receives 404.
CALL-03	P0	M1	As an employee, I complete a device check before entering the call so I know my camera, microphone and speaker work.	1. Pre-join runs `MeetingReadinessChecker` for camera, microphone, speaker and network. 2. Self-view preview and mic-level indicator visible. 3. Device selection dropdowns for camera, microphone and speaker. 4. Network quality indicator: green, yellow or red. 5. On browser permission denial, inline instructions for the detected browser appear (`calls.prejoin.permission_denied_<browser>`). 6. "Join" disabled until microphone access is granted.
CALL-04	P0	M1	As an employee, I choose to join with my camera off or with background blur so I control my privacy.	1. The pre-join screen offers a "Join with camera off" toggle (camera and microphone are on by default after the preview) and a "Background blur" toggle. 2. Background blur is opt-in, not enforced by default. 3. The chosen camera-off and blur preferences are each stored in `localStorage` under a device-specific key and restored on the next session. 4. Both choices persist into the call: camera-off joins with video muted, blur joins with the blur filter active.
CALL-05	P0	M1	As an employee, I see the expert's status while waiting so I know my session will begin.	1. The waiting state shows the expert's first name, photo and credentials from the appointment record. 2. It shows the appointment time formatted in the appointment's `timeZone`. 3. If the expert has not yet joined, the status reads "Your expert will join shortly" (`calls.consultation.waiting`). 4. If the expert sends a "running late" signal via `POST /appointments/:id/signal`, the message appears inline with the ETA. 5. Session tips from the `calls.consultation.tips` message key are displayed.
CALL-06	P0	M1	As an employee, I can still join after the scheduled start time if the window is open.	1. If the employee joins between `startsAt` and `startsAt` plus 10 minutes, the UI shows "Your session started at HH:MM. You can still join for the remaining time" (`calls.consultation.late_join`). 2. `POST /appointments/:id/join` succeeds and returns credentials. 3. The session timer reflects the remaining scheduled time, not a full session.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
CALL-07	P0	M1	As an employee, I see a clear message when the join window has closed.	1. After `startsAt` plus 10 minutes (`CALL_JOIN_WINDOW_AFTER_MINUTES`), `POST /appointments/:id/join` returns 403 with error code `join_window_closed`. 2. The appointment page shows "The join window for this session has closed" (`calls.errors.join_window_closed`) with a link to contact support. 3. Within 48 hours, the `calls.no_show_followup` job sends a follow-up email asking whether the absence was due to a technical issue, with links to report a technical problem and to the future booking epic.
CALL-08	P0	M1	As an employee, I use in-call controls during my consultation.	1. Control bar: mute/unmute, camera on/off, blur toggle, device switch, fullscreen, leave. 2. Speaker view: expert large, self-view movable PIP. Employee can hide self-view. 3. All controls keyboard-operable with visible focus. 4. Mute and camera changes announced through `LiveRegion`. 5. At 390 px: remote video fills screen, PIP floats, 44 px targets, secondary controls in overflow menu. 6. No recording controls or indicators appear for consultations (consultations are not recorded, D-CW-19, D-CW-34).
CALL-09	P0	M1	As an employee, I see a connection quality badge and the call gracefully degrades when my network is poor.	1. A persistent connection badge in the corner shows one of three states: strong (green), unstable (yellow) or poor (red), derived from 30-second aggregated `getStats()` metrics. 2. When quality drops below thresholds, the client first lowers outgoing video resolution, then pauses outgoing video and displays a banner "Video paused, audio only due to network quality" (`calls.consultation.degraded_mode`). 3. When quality recovers, outgoing video resumes automatically and the banner disappears.
CALL-10	P0	M1	As an employee, I can reconnect or rejoin if my connection drops.	1. On disconnect, the UI shows "Connection lost, reconnecting..." (`calls.consultation.reconnecting`) with a spinner. 2. The SDK attempts reconnection for up to 2 minutes. 3. If reconnection fails, the UI shows "Unable to reconnect" with a "Rejoin" button and a "Contact support" link. 4. Clicking "Rejoin" calls `POST /appointments/:id/join`, which returns the cached credentials from Redis (`call:{sessionId}:participant:{participantId}`). 5. If the join window has closed, rejoin returns 403 `join_window_closed` and the UI shows the closed-window message from CALL-07.
CALL-11	P0	M1	As an employee, I can send a quick signal when I have an audio or video problem.	1. A "I cannot hear you" button in the control bar sends a signal via `POST /appointments/:id/signal` with type `cannot_hear`. 2. The expert receives the signal as a `call.signal` event on the `call:{sessionId}` Socket.IO room. 3. The expert sees a transient toast with the signal text. 4. Signals are not persisted beyond the session. 5. The "I cannot see you" signal works identically with type `cannot_see`.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
CALL-12	P0	M1	As an employee, I can access crisis resources at any time during the call.	1. A persistent, unobtrusive "Crisis resources" button is visible throughout the call. 2. Clicking it opens the `CrisisBlock` component, the same one used by wellbeing check-ins. 3. The `CrisisBlock` shows Serbian hotlines and the platform disclaimer (D-CW-38; Hungarian hotlines are added only with a Hungarian launch). 4. The crisis block follows the Motion rule (animated open and close). 5. Opening the crisis block does not leave or mute the call.
CALL-13	P0	M1	As an employee, I see how much time remains in my session.	1. A session timer shows elapsed and remaining time based on `startsAt` and `endsAt`. 2. At 5 minutes before `endsAt`, a dismissable alert appears: "5 minutes remaining in your session" (`calls.consultation.five_min_warning`); the expert's variant adds "You can propose a follow-up on the post-call screen" (`calls.consultation.five_min_followup_hint`). 3. At `endsAt`, the UI shows "Session time has ended" (`calls.consultation.time_ended`). 4. At `endsAt` plus 10 minutes, a warning appears: "The room will close in 5 minutes." 5. At `endsAt` plus 15 minutes (`CALL_ROOM_CLOSE_AFTER_MINUTES`), the room closes and both participants are disconnected.
CALL-14	P0	M1	As an employee, I can leave the consultation at any time.	1. Clicking "Leave" disconnects the employee from the call and navigates to the post-call screen. 2. The expert receives a `call.participant.left` event on the `call:{sessionId}` Socket.IO room. 3. Leaving does not end the session for the expert.
CALL-15	P0	M1	As an employee, I give optional private feedback after my consultation.	1. The post-call screen appears 5 seconds after the call ends. 2. It offers a 1-to-5 star rating and an optional text comment. 3. The screen states "Your feedback is private and your employer will not see it" (`calls.consultation.feedback_privacy`). 4. A prominent skip button is available. 5. Submitting calls `POST /appointments/:id/feedback`, which writes to `call_feedback` and emits `call.feedback.submitted` as an audit event. 6. The feedback is visible to NestSelf operations in aggregate only, never to the employer.
CALL-16	P0	M1	As an employee, I report a technical problem after a failed or degraded call.	1. The post-call screen offers a "Report a technical problem" link. 2. Clicking it opens a form that sends a report. 3. The report auto-attaches connection metadata (duration, reconnect count, quality scores, browser, OS) from the client event log. 4. The report never contains session content, device labels or names. 5. The submitted report is visible to support operators with `support.troubleshoot`.
CALL-17	P0	M1	As an employee, my employer cannot see that I attended a consultation, its topic, its outcome or my feedback.	1. No endpoint accessible to employer-scoped principals (employer_owner, hr, team_manager, reporting_user) returns appointment, participant, outcome or feedback rows. 2. `GET /appointments` and `GET /ops/calls/:sessionId/diagnostics` return 404 for employer-scoped principals. 3. Default-deny CI test covers every route. 4. Authorisation golden cases assert 404 for employer-scoped principals on each route.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
2. Consultations: expert side 8 stories				
CALL-18	P0	M1	As an expert, I see my upcoming appointments in the admin app.	1. `GET /appointments` with the expert's principal returns only appointments where `expertUserId` matches the principal's user id. 2. The admin app route `/consultations` lists upcoming appointments sorted by `startsAt`. 3. Each row shows the employee's first name, the service category label, the scheduled time in the appointment's `timeZone` and the appointment status. 4. Tapping a row navigates to the appointment detail at `/consultations/$appointmentId`.
CALL-19	P0	M1	As an expert, I send a "running late" message to the employee before joining.	1. The appointment detail in the admin app shows a "Send running late" button when the current time is within the join window. 2. Clicking it calls `POST /appointments/:id/signal` with type `running_late` and an optional ETA in minutes. 3. The employee receives a `call.signal` event on the `call:{sessionId}` Socket.IO room and sees the message inline in the waiting state (CALL-05). 4. The signal requires `consultation.join` on the appointment resource.
CALL-20	P0	M1	As an expert, I join the consultation for my confirmed appointment.	1. The "Join session" button on the appointment detail becomes enabled at `startsAt` minus 15 minutes. 2. `POST /appointments/:id/join` requires `consultation.join` and the expert to be the assigned expert. 3. If the appointment status is not `confirmed`, the endpoint returns 409 with error code `appointment_not_joinable`. 4. On success, the endpoint returns Chime SDK credentials and the session transitions to `active`. 5. A `call.joined` audit event is recorded.
CALL-21	P0	M1	As an expert, I end the session for both participants.	1. The expert's control bar includes an "End for everyone" button not available to the employee. 2. Clicking it opens a confirmation dialog. 3. Confirming calls `POST /appointments/:id/end`, which invokes `DeleteMeeting` on the provider. 4. Both participants receive `call.session.ended` on the `call:{sessionId}` Socket.IO room and are disconnected. 5. A `call.ended` audit event is recorded. 6. The expert is navigated to the outcome capture form (CALL-23).
CALL-22	P0	M1	As an expert, I share my screen during the consultation.	1. The expert's control bar includes a "Share screen" button. 2. The expert has `SendReceive` capability on the content channel; the employee has `Receive` only. 3. While sharing, a persistent "You are sharing your screen" indicator is visible to the expert. 4. The employee sees the shared content in the main view.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
CALL-23	P0	M1	As an expert, I record the delivery outcome before starting another session.	1. After the call ends (or after "End for everyone"), the admin app shows the outcome capture form. 2. The form requires selecting one of: `completed`, `no_show_employee`, `no_show_expert`, `technical_failure`, `canceled`. 3. Submitting calls `POST /appointments/:id/outcome` with the `delivery.record` action on the appointment resource. 4. The endpoint writes to `call_outcomes` with the selected `call_outcome_status` and auto-attaches connection metadata (duration, reconnect count, aggregated quality scores). 5. A `call.outcome.recorded` audit event is recorded. 6. The appointment status transitions to the matching `appointment_status` (`completed`, `no_show`, `canceled`). 7. Once the outcome is `completed`, a "Propose a follow-up" card appears on the post-call screen (CALL-35).
CALL-24	P0	M1	As an expert, I cannot enter free-text notes in the delivery outcome because NestSelf does not store professional notes.	1. The outcome capture form has no free-text field. 2. The `POST /appointments/:id/outcome` request schema rejects a `notes` field. 3. A contract test asserts `CallOutcomeCreateRequestSchema` has no string field beyond the enum status.
CALL-25	--	--	Superseded by CALL-35 to CALL-42 (D-CW-37). The expert now proposes a follow-up directly on the post-call screen instead of linking to the booking epic.	Superseded. See CALL-35.
3. Appointment spine: coordinator and seed 6 stories				
CALL-26	P0	M1	As a service coordinator, I create an appointment for an employee with an assigned expert.	1. `POST /orgs/:orgId/appointments` requires `appointment.propose` or `bookings.coordinate` on the organisation resource. 2. The request body includes `employeeUserId`, `expertUserId`, `startsAt`, `endsAt`, `serviceCategory`, `timeZone` and an optional `fundingRef`. 3. The endpoint validates that both users exist and the expert holds `consultation.join`. 4. On success, it creates a row in `appointments` with status `confirmed` and emits an `appointment.created` audit event. 5. Reminder jobs (`appointment.remind`) are scheduled for 24 hours and 1 hour before `startsAt`.
CALL-27	P0	M1	As a service coordinator or the employee, I cancel an appointment.	1. `POST /appointments/:id/cancel` requires `appointment.cancel` on the appointment resource. 2. The appointment status transitions to `canceled`. 3. If a call session exists and is `active`, the provider's `DeleteMeeting` is called. 4. Reminder jobs for the appointment are removed. 5. An `appointment.canceled` audit event is recorded. 6. Both participants receive a cancellation email using the neutral template.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
CALL-28	P0	M1	As NestSelf operations, I list appointments by organisation.	1. `GET /appointments` with a platform-scoped or client_operations principal returns appointments for the principal's assigned organisations. 2. Results can be filtered by `orgId`, `status` and date range. 3. The response includes appointment id, employee first name, expert first name, schedule, status and service category. 4. No professional notes or outcome comments appear in the response.
CALL-29	P0	M1	As the platform, I store and display appointment times in the correct time zone.	1. `appointments.timeZone` is a required IANA time zone string validated by the Zod schema. 2. `startsAt` and `endsAt` are stored as `timestamptz`. 3. All client-facing time displays format using `Intl.DateTimeFormat` with the appointment's `timeZone`. 4. The ICS file uses the appointment's `timeZone` for `DTSTART` and `DTEND`.
CALL-30	P0	M1	As the platform, I enforce valid appointment status transitions.	1. Allowed transitions: `proposed` to `confirmed` (AUTOMATIC policy or expert picks a suggested time), `proposed` to `awaiting_approval` (MANAGER_APPROVAL policy), `proposed` to `declined` (employee declines), `awaiting_approval` to `confirmed` (approver approves), `awaiting_approval` to `declined` (approver rejects), `confirmed` to `completed`, `confirmed` to `canceled`, `confirmed` to `no_show`. 2. Any other transition returns 409 with error code `appointment_not_joinable`. 3. A contract test asserts the allowed transitions.
CALL-31	P0	M0	As the platform, I define the appointment contract seam for the future booking epic.	1. `packages/contracts/src/appointments.ts` exports the `Appointment` type with fields: `id`, `orgId`, `expertUserId`, `employeeUserId`, `startsAt`, `endsAt`, `status`, `serviceCategory`, `timeZone`, `fundingRef`, `followUpOf`. 2. The `status` enum includes `proposed`, `awaiting_approval`, `confirmed`, `completed`, `canceled`, `declined`, `no_show`. 3. The call layer reads only these fields. 4. A contract test asserts that no other fields are read by the call or session modules. 5. The booking epic (`NS-BOOKING-01`) may add columns but must not change the fields the call layer reads.
4. Webinars: attendee side 15 stories				
WBN-01	P0	M2	As an employee, I discover webinars I am eligible to attend.	1. `GET /webinars` returns only occurrences with status `published` whose audience policy includes the employee's organisation or organisational unit, or that are `all_eligible` and the employee's plan includes webinars. 2. Eligibility is evaluated server-side using `event.register` on the webinar resource. 3. Each result includes title per locale, presenter name, schedule and capacity remaining (every webinar is recorded; there is no per-occurrence recording switch, D-CW-34). 4. Occurrences the employee is not eligible for are not returned (not filtered client-side).

THE STORIES

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
WBN-02	P0	M2	As an employee, I register for a webinar while capacity remains.	1. `POST /webinars/:id/register` requires `event.register` on the webinar resource. 2. The endpoint uses `SELECT ... FOR UPDATE` on the occurrence row to enforce capacity atomically. 3. If the webinar is at capacity (`WEBINAR_SINGLE_MEETING_CAPACITY` = 250), the endpoint returns 409 with error code `webinar_full`. 4. If the webinar status is not `published`, the endpoint returns 409 `webinar_not_open`. 5. If the employee is already registered, the endpoint returns 409 `already_registered`. 6. If the employee is not eligible, the endpoint returns 403 `not_eligible`. 7. On success, a row is created in `webinar_registrations` and a `webinar.registered` audit event is recorded.
WBN-03	P0	M2	As an employee, I unregister from a webinar before it starts.	1. `DELETE /webinars/:id/register` requires `event.register` and the employee to have an existing registration. 2. On success, the registration row is soft-deleted, capacity is released, and a `webinar.unregistered` audit event is recorded. 3. After the webinar status is `live` or `ended`, unregistration returns 409 `registration_closed`.
WBN-04	P0	M2	As an employee, I receive a confirmation email with a neutral ICS after registering.	1. On successful registration, the system sends a confirmation email using the `calls.email.webinar_confirmation` template in the employee's locale. 2. The email subject contains no wellbeing category. 3. The email states that the webinar is recorded and that only the presenters are on the recording (`calls.email.webinar_recording_notice`). 4. The email attaches an ICS file with `CLASS:PRIVATE`, a neutral `SUMMARY` from `calls.email.webinar_ics_summary`, the authenticated join link in `DESCRIPTION`, and `X-MICROSOFT-CDO-BUSYSTATUS:BUSY`. 5. Templates exist in all four locales.
WBN-05	P0	M2	As an employee, I receive reminders before a webinar I registered for.	1. Reminder emails are sent at 24 hours and 1 hour before the webinar start time (`REMINDER_OFFSETS_MINUTES`). 2. Reminders use the `calls.email.webinar_reminder` template with neutral wording. 3. If the employee unregistered, reminders are not sent.
WBN-06	P0	M2	As an employee, I enter the webinar lobby before the session starts.	1. The webinar detail page at `/webinars/$webinarId` shows a "Join webinar" button that becomes enabled 15 minutes before the scheduled start. 2. Before the host starts the webinar, the lobby shows: the event title, presenter name, start time, a countdown, the sentence "This webinar is recorded; only the presenters are on the recording" (`calls.webinar.recording_notice`) and the sentence "Your camera stays off; you can write to the hosts and raise your hand to ask for the floor" (`calls.webinar.lobby_notice`). 3. No attendee list or attendee names are visible in the lobby. 4. The room closes at the scheduled end plus 15 minutes unless the moderator ends it earlier. Attendees may join from 15 minutes before the scheduled start; presenters and the moderator from 30 minutes before (`WEBINAR_HOST_JOIN_BEFORE_MINUTES`).

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
WBN-07	P0	M2	As an employee, I watch the live webinar stage.	1. `POST /webinars/:id/join` requires `event.register` and an active registration. 2. The attendee is created with capabilities `Audio: Receive, Video: Receive, Content: Receive` (no send on any channel). 3. The attendee sees only the presenter's video and screen share. No attendee tiles, names or counts are visible to other attendees. 4. Controls available: mute incoming audio, fullscreen, chat panel, hand-raise and leave. 5. No camera control exists in the attendee client; `UpdateAttendeeCapabilities` is never called with `Video: SendReceive` for an attendee (a unit test asserts this).
WBN-08	P0	M2	As an employee attending a webinar, I cannot see other attendees and they cannot see me.	1. Attendee capabilities are `Receive` only on audio and video; the attendee cannot send media. 2. No roster endpoint is exposed to attendees. 3. `ListAttendees` is never called by the client for attendees. 4. The webinar stage component renders no attendee tiles. 5. Attendee names are not emitted on the `webinar:{webinarId}` Socket.IO room. 6. No camera control exists in the attendee client and `UpdateAttendeeCapabilities` is never called with `Video: SendReceive` for an attendee; a unit test asserts it.
WBN-09	P0	M2	As an employee, I write to the hosts during a webinar, anonymous by default.	1. `POST /webinars/:id/messages` with `kind` = `attendee` or `question` requires `event.register`. 2. The request body includes `text`, `kind` and an optional `showFirstName` boolean (default `false`). 3. If `showFirstName` is false, the message is stored in `webinar_messages` without the author's name. 4. If `showFirstName` is true, the author's first name is attached. 5. The message is submitted with status `pending` and emitted as `webinar.message.submitted` on the `webinar:{webinarId}:moderation` room (visible to hosts only). 6. A `webinar.message.submitted` audit event is recorded. 7. `GET /webinars/:id/messages` for an attendee returns only messages with status `published`.
WBN-10	P0	M2	As an employee, I raise my hand and a host may give me the floor to speak.	1. `POST /webinars/:id/hand` requires `event.register`. 2. A `webinar.hand.raised` event is emitted on the `webinar:{webinarId}:moderation` room with the registration name. 3. The presenter sees only "A participant asked to speak" (`calls.webinar.hand_raised_presenter`). 4. If a host gives the attendee the floor (`POST /webinars/:id/participants/:participantId/give-floor`), the attendee's audio becomes `SendReceive` while video stays `Receive`; the attendee sees "You can speak now, unmute to talk" (`calls.webinar.floor_given`) and stays muted until they unmute. 5. Before unmuting, the attendee is told that their voice is part of the recording (`calls.webinar.floor_recording_notice`). 6. The host can take the floor back at any time (`POST .../take-floor`), which reverses audio to `Receive`. 7. `DELETE /webinars/:id/hand` lowers the hand. 8. Video never becomes `SendReceive` for an attendee.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
WBN-11	P0	M2	As an employee, I participate in polls during a webinar.	1. When the moderator opens a poll, a `webinar.poll.opened` event arrives on the `webinar:{webinarId}` room with the poll definition (question and options). 2. `POST /webinars/:id/polls/:pollId/vote` accepts the employee's vote. 3. Individual votes are stored without the voter id. 4. When the moderator closes the poll, `webinar.poll.closed` and `webinar.poll.results` events carry the aggregated results. 5. The UI displays results as percentages.
WBN-12	P0	M2	As an employee, I leave a webinar at any time without notifying other attendees.	1. Clicking "Leave" disconnects the attendee. 2. No exit message or notification is shown to other attendees. 3. The moderator's attendance count updates via `webinar.attendance.count` on the moderation room.
WBN-13	P1	M3	As an employee, I learn that a replay will be available after the webinar ends.	1. When the webinar ends, all attendees see "This webinar has ended. A replay will be available after review" (`calls.webinar.ended_replay`). Every webinar is recorded (D-CW-34), so this message always appears. 2. When the replay content item is published through the CMS, a notification email is sent to registered attendees.
WBN-14	P1	M3	As an employee, I opt in to a certificate of attendance.	1. After the webinar ends, an employee who attended at least 60 percent of the live minutes or completed the full replay is offered a certificate opt-in. 2. The certificate uses the neutral title "NestSelf webinar" and the date. The topic is included only if the employee explicitly chooses to include it. 3. `GET /webinars/:id/certificate` returns a PDF. 4. A `webinar.certificate.issued` audit event is recorded. 5. The certificate is available for re-download from the employee's session history.
WBN-15	P0	M2	As an employee with a disability, I can use the webinar with keyboard controls, reduced motion and I am told the captions status.	1. All webinar controls are keyboard-operable with visible focus indicators. 2. State changes (poll opened, message published, floor given) are announced through the `LiveRegion`. 3. When `prefers-reduced-motion` is active, all UI transitions use opacity-only fade of at most 50 ms. 4. The webinar detail page states "Live captions are not yet available. Replays are captioned after review" (`calls.webinar.captions_statement`).
5. Webinars: presenter side 8 stories				
WBN-16	P0	M2	As a presenter, I preview my setup before starting the webinar.	1. The presenter's pre-webinar screen runs camera, microphone and screen-share tests. 2. It shows session details: title, scheduled time, attendee count (number only, no names). 3. A "Start webinar" button is visible but does not begin the session until clicked. 4. `POST /webinars/:id/start` is `@Authenticated()`; the service checks `event.present` or `event.moderate` on the webinar resource with the authorization engine; a principal holding neither receives 404. 5. Presenters and the moderator may join from 30 minutes before the scheduled start (`WEBINAR_HOST_JOIN_BEFORE_MINUTES`).

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
WBN-17	P0	M2	As a presenter, I start the webinar.	1. `POST /webinars/:id/start` transitions the webinar status from `published` to `live`. 2. A `webinar.started` audit event is recorded. 3. A `webinar.state` event with payload `{ status: 'live' }` is emitted on the `webinar:{webinarId}` room. 4. Attendees in the lobby transition to the live stage.
WBN-18	P0	M2	As a presenter, I share my screen during the webinar.	1. The presenter has `Content: SendReceive` capability. 2. While sharing, a persistent "You are sharing your screen" indicator is visible. 3. Attendees see the shared content in the main stage view.
WBN-19	P0	M2	As a presenter, I see a live attendance count but no attendee names.	1. The presenter dashboard shows: live attendance count, published message count, hand-raise count and elapsed time. 2. Attendee names are never shown to the presenter during the session. 3. The count is updated via `webinar.attendance.count` on the `webinar:{webinarId}:moderation` room, relayed to the presenter component.
WBN-20	P0	M2	As a presenter, I see published messages and answered questions from attendees.	1. The presenter's chat panel shows only messages with status `published` or `answered`. 2. Messages with status `pending` or `dismissed` are not visible to the presenter. 3. Published messages arrive via `webinar.message.published` on the `webinar:{webinarId}` room; answered questions arrive via `webinar.message.answered`.
WBN-21	P0	M2	As a presenter, I end the webinar for all participants with a confirmation step.	1. The presenter's control bar includes "End webinar for all." 2. Clicking it opens a confirmation dialog: "End this webinar? All attendees will be disconnected" (`calls.webinar.end_confirm`). 3. Confirming calls `POST /webinars/:id/end`; the route is `@Authenticated()` and the service checks `event.present` or `event.moderate` on the webinar resource with the authorization engine; a principal holding neither receives 404. 4. The webinar status transitions to `ended`. 5. All attendees receive `webinar.ended` on the `webinar:{webinarId}` room and are disconnected. 6. A `webinar.ended` audit event is recorded.
WBN-22	P1	M3	As a presenter, I see aggregate analytics after the webinar.	1. Post-event, the presenter's dashboard shows: peak attendance, average attendance, total messages submitted, polls completed. 2. Individual attendee names are not visible to the presenter. 3. If peak attendance is below 5, the count is suppressed to protect anonymity.
WBN-37	P0	M2	As a host, I post a message to all attendees.	1. `POST /webinars/:id/messages` with `kind` = `host` requires `event.moderate` or `event.present`. 2. The message is created with status `published` immediately (host messages do not need moderation). 3. The message is emitted as `webinar.message.published` on the `webinar:{webinarId}` room and visible to all attendees. 4. Host messages are stored in `webinar_messages` with kind `host`. 5. `GET /webinars/:id/messages` for an attendee includes host messages alongside published attendee messages.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
6. Webinars: moderator side 7 stories				
WBN-23	P0	M2	As a moderator, I see all incoming messages with attendee names.	1. The moderator's queue shows all messages with status `pending`, including the author's registration name (even for anonymous messages, for operational follow-up). 2. Messages arrive via `webinar.message.submitted` on the `webinar:{webinarId}:moderation` room. 3. `event.moderate` on the webinar resource is required to subscribe to the moderation room. 4. `GET /webinars/:id/messages` for a host returns all messages regardless of status.
WBN-24	P0	M2	As a moderator, I publish, answer or dismiss a message.	1. `POST /webinars/:id/messages/:messageId/publish` sets status to `published` and emits `webinar.message.published` on the public room; the message becomes visible to all attendees. 2. `POST .../dismiss` sets status to `dismissed`; the message disappears from the public feed. 3. `POST .../answer` sets status to `answered` with the host's answer text and emits `webinar.message.answered` on the public room. 4. Each action requires `event.moderate` and records the corresponding audit event (`webinar.message.published`, `webinar.message.answered` or `webinar.message.dismissed`). 5. The moderator can edit the message text before publishing (the original is preserved in the `webinar_messages` row).
WBN-25	P0	M2	As a host, I give the floor to an attendee and take it back.	1. `POST /webinars/:id/participants/:participantId/give-floor` requires `event.moderate` or `event.present`. 2. The endpoint sends a `webinar.floor.given` event to the participant only. 3. `UpdateAttendeeCapabilities` sets `Audio: SendReceive`; video stays `Receive` (never `SendReceive` for an attendee). 4. The attendee sees "You can speak now, unmute to talk" (`calls.webinar.floor_given`) and stays muted until they unmute. 5. Before unmuting, the attendee is told that their voice is part of the recording (`calls.webinar.floor_recording_notice`). 6. `POST .../take-floor` reverses audio to `Receive` and sends `webinar.floor.taken` to that participant. 7. `webinar.floor.given` and `webinar.floor.taken` audit events are recorded. 8. The audience hears the voice and sees "A participant is speaking" (`calls.webinar.participant_speaking`).
WBN-26	P0	M2	As a host, I mute an attendee who has the floor.	1. The host can mute any attendee who has the floor. 2. Muting sets the attendee's audio to `Receive` only via `UpdateAttendeeCapabilities`. 3. Unmuting requires the attendee's consent: the attendee receives an "unmute request" notification and must confirm. 4. The host cannot force-unmute an attendee.
WBN-27	P0	M2	As a moderator, I open and close polls.	1. `POST /webinars/:id/polls/:pollId/open` requires `event.moderate` and emits `webinar.poll.opened` on the public room. 2. `POST .../close` emits `webinar.poll.closed` and `webinar.poll.results` with aggregated results. 3. Individual votes are never included in the results event. 4. `webinar.poll.opened` and `webinar.poll.closed` audit events are recorded.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
WBN-28	P0	M2	As the platform, recording starts automatically when the moderator starts the webinar and stops at the end.	1. When the webinar transitions to `live` (`POST /webinars/:id/start`), the `webinar.recording.start` job creates a media capture pipeline with `SelectedVideoStreams` set to the presenter participants' attendee ids and `CompositedVideo` layout `PresenterOnly` at HD. 2. A persistent "REC" indicator appears for all participants via the `webinar.recording` event on the `webinar:{webinarId}` room. 3. The moderator can stop recording early with `POST /webinars/:id/recording/stop` (`event.moderate`). 4. When the webinar ends, recording stops automatically. 5. `webinar.recording.started` and `webinar.recording.stopped` audit events are recorded. 6. An attendee given the floor is told before unmuting that their voice is recorded (`calls.webinar.floor_recording_notice`). 7. There is no per-occurrence recording switch; every webinar is recorded (D-CW-34).
WBN-29	P0	M2	As a moderator, I end the webinar.	1. The moderator's control bar includes "End webinar" with the same confirmation flow as the presenter (WBN-21). 2. `POST /webinars/:id/end` succeeds for a principal holding `event.present` or `event.moderate` on the webinar resource; the route is `@Authenticated()` and the service checks either action with the authorization engine; a principal with neither receives 404. 3. If recording is active, stopping the recording pipeline is triggered before `DeleteMeeting`.
7. Webinars: operations and content operator 7 stories				
WBN-30	P0	M2	As a content operator, I create and edit a webinar occurrence.	1. `POST /ops/webinars` requires `event.manage`. 2. Body: title per locale, presenter ids, moderator id, schedule, audience policy (`all_eligible`, org ids or OU ids), capacity (1 to 250). There is no recording-policy field (every webinar is recorded, D-CW-34). 3. Capacity above 250 is rejected with error code `capacity_above_limit` and a message naming the limit until M3 lands. 4. Created with status `draft`. 5. `PATCH /ops/webinars/:id` updates while `draft` or `published`. 6. `webinar.created` audit event recorded.
WBN-31	P0	M2	As a content operator, I publish a webinar occurrence so employees can register.	1. `POST /ops/webinars/:id/publish` requires `event.manage`. 2. The webinar status transitions from `draft` to `published`. 3. A `webinar.published` audit event is recorded. 4. The occurrence becomes visible to eligible employees via `GET /webinars`. 5. Publishing validates that at least one presenter and one moderator are assigned, the schedule is in the future, and the audience policy resolves to at least one organisation.
WBN-32	P0	M2	As a content operator, I cancel a published webinar and notify registered attendees.	1. `POST /ops/webinars/:id/cancel` requires `event.manage`. 2. The webinar status transitions to `canceled`. 3. All registered attendees receive a cancellation email using the neutral `calls.email.webinar_canceled` template. 4. Reminder jobs for the webinar are removed. 5. A `webinar.canceled` audit event is recorded. 6. Future registration attempts return 409 `webinar_not_open`.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
WBN-33	P0	M2	As NestSelf operations, I view the attendance report for a webinar.	1. `GET /ops/webinars/:id/attendance` requires `event.manage` or `event.moderate`. 2. The response includes: registered count, peak live attendance, per-registrant join and leave timestamps, attendance duration and completion percentage. 3. An employer-scoped principal receives 404. 4. The default-deny test and authorisation golden cases cover this route. 5. Viewing attendance is audited. 6. In M3 with media replication, the report aggregates attendance across all replicas (WBN-36).
WBN-34	P0	M2	As the platform, I hand the webinar recording to the CMS as a draft content item.	1. `webinar.recording.finalize` concatenates segments into one MP4 and writes the key to `webinar_recordings` with `handoff_status = 'pending'`. 2. If the CMS media interface exists, the job creates a draft content item through it. Otherwise `handoff_status` stays `pending`. 3. `webinar.recording.ready` and `webinar.recording.handed_off` audit events recorded at each stage. 4. Recordings bucket: eu-central-1, SSE-KMS on platform key, block-public-access, lifecycle expires raw segments after 30 days.
WBN-35	P0	M3	As the platform, an occurrence with capacity 251 to 1,000 uses media replication.	1. When capacity exceeds 250, `createSession` creates a primary meeting for hosts and replica meetings via `PrimaryMeetingId` for attendees. 2. Attendees join a replica; presenters and the moderator join the primary. 3. Replica attendees see only the primary's media and never each other. 4. An attendee given the floor from a replica can speak after SPIKE-CW-06 confirms the audio path works. 5. The delivery model is transparent to the rest of the application: the adapter decides based on `format` and `capacity`. 6. The occurrence form accepts capacity up to 1,000 once M3 lands.
WBN-36	P0	M3	As the platform, attendance and the chat work the same across replicas.	1. `webinar.attendance.count` aggregates attendance across all replicas. 2. The chat (`webinar_messages`) and hand-raise run on Socket.IO and PostgreSQL, not on Chime data messages, so they work identically regardless of how many meetings back the occurrence. 3. `GET /ops/webinars/:id/attendance` returns per-registrant data aggregated across replicas. 4. Polls and their results aggregate across replicas.
8. Workshops 5 stories				
WKS-01	P1	M4	As an employee, I register for a workshop and understand that other participants will see my name and video.	1. The registration page states "This is a group session. Other participants will see your name and video" (`calls.workshop.visibility_notice`). 2. The registration creates a row in `webinar_registrations` (reused for workshops) with format `workshop`. 3. Capacity is enforced at `WORKSHOP_CAPACITY` = 25.
WKS-02	P1	M4	As a workshop participant, I join a gallery-view session where everyone is on video.	1. All participants are created with `Audio: SendReceive, Video: SendReceive`. 2. The layout is gallery view with a configurable grid (up to 25 tiles). 3. The active speaker is highlighted. 4. Content share by the facilitator switches to stage view. 5. Camera is on by default (not off). Background blur is offered.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
WKS-03	P1	M4	As a facilitator, I control the workshop session.	1. The facilitator has additional controls: mute-all, unmute request (individual, requires participant consent), spotlight or pin participants, remove participant, and "End for everyone." 2. Only the facilitator and promoted participants can share content. 3. The facilitator has `Content: SendReceive`; other participants have `Content: Receive`.
WKS-04	P1	M4	As a facilitator, I use session chat that is retained for 24 hours after the session.	1. Workshop chat is enabled during the session via the `call:{sessionId}` Socket.IO room. 2. Chat messages are persisted in a workshop-specific table. 3. Messages are retained until the session ends plus 24 hours, then deleted by a cleanup job. 4. Chat is never shown to the employer.
WKS-05	P1	M4	As a facilitator, I collect anonymous aggregated feedback after the workshop.	1. After the session, participants see an optional feedback prompt (1-to-5 stars, optional comment). 2. Feedback is anonymous and aggregated: the facilitator sees average scores and comment themes, not individual responses. 3. The employer does not see feedback.
9. Platform, support and operations 18 stories				
PLT-01	P0	M1	As the platform, I provide a single join entry point with window and participant checks.	1. `POST /appointments/:id/join` is the only entry point for consultations. `POST /webinars/:id/join` is the only entry point for webinars. 2. A principal who is not a participant of the appointment receives 404 (not 403, to avoid revealing the appointment's existence). 3. A participant outside the join window receives 403 with error code `join_window_closed`. 4. A participant of a canceled appointment receives 409 with error code `appointment_not_joinable`. 5. These semantics are covered by authorisation golden-case tests.
PLT-02	P0	M0	As the platform, I send only opaque identities to the video provider.	1. `ExternalUserId` passed to the Chime SDK is the `call_participants.id` (a random id per session and participant), never the user id, name or email. 2. `TenantIds` carries the organisation id for consultations and workshops and the webinar id for webinars. 3. Tags carry only `stage`, `format` and `orgId`. 4. A serialisation test asserts that no PII field appears in the `CreateMeeting` or `CreateAttendee` request payload.
PLT-03	P0	M1	As the platform, I create meetings lazily, lock concurrent creation and clean up stale meetings.	1. First join triggers `CreateMeetingWithAttendees`; a `KeyValueStore.set('call:{sessionId}:create', ..., { onlyIfAbsent: true, ttl })` lock serialises concurrent first joins. 2. Second participant triggers `CreateAttendee` from `call_sessions.provider_meeting_id`. 3. Concurrent loser polls up to 3 s for `provider_meeting_id`. 4. `calls.cleanup` delayed job at `endsAt` plus 15 min deletes the meeting if the provider still reports it. 5. `calls.reconcile` runs every 5 min as a backstop. 6. `call.session.created` audit event recorded on creation.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
PLT-04	P0	M1	As the platform, I ingest Chime SDK events idempotently and tolerate out-of-order delivery.	1. `chime.events.consume` worker polls the SQS queue (long polling, 60 s visibility timeout). 2. Events written to `call_events` with unique key `(provider_meeting_id, event_type, provider_attendee_id, occurred_at)`; duplicates dropped. 3. `AttendeeJoined` sets `first_joined_at` only if null; `AttendeeLeft` / `AttendeeDropped` set `last_left_at` to max; `MeetingEnded` closes once. 4. Out-of-order events do not corrupt state. 5. SQS and EventBridge backstop duplicates are deduplicated.
PLT-05	P0	M1	As a support operator, I view diagnostics for a call session.	1. `GET /ops/calls/:sessionId/diagnostics` requires `support.troubleshoot` or `diagnostic.read`. 2. The response contains exactly: session id, appointment or webinar id, start and end, status, provider, provider meeting id, per-participant role, join and leave timestamps, reconnect count, aggregated quality metrics, provider and client error codes, browser and OS. 3. A serialisation test asserts the DTO has no other field. 4. Viewing diagnostics emits a `call.diagnostics.viewed` audit event. 5. An employer-scoped principal receives 404.
PLT-06	P0	M1	As the platform, I record audit events for all call and webinar actions without storing tokens or content.	1. Every mutation in the appointments, calls, webinars, feedback and diagnostics controllers calls `AuditWriter.record()` with the canonical event name from section 7 of the decision record. 2. No audit event's `details` object contains a key from the `FORBIDDEN_KEYS` set (which includes `token`). 3. Join tokens are never written to PostgreSQL and never logged. 4. The join response carries `Cache-Control: no-store`.
PLT-07	P0	M1	As the platform, I send notification emails using neutral templates in four locales.	1. Consultation reminders, webinar confirmations, webinar reminders, cancellation emails and no-show follow-ups use localised templates from the `calls` i18n namespace. 2. Templates exist in en, sr-Latn, sr-Cyrl and hu. 3. No template contains a service category, a diagnosis or any content that reveals the nature of the session on a lock screen or in an email subject line. 4. The mailer module at `apps/api/src/mailer/` abstracts the SES implementation.
PLT-08	P0	M0	As the platform, I provide sample-mode fixtures and the sample data banner for calls and webinars.	1. `packages/sample-data` exports `SAMPLE_APPOINTMENTS` (including one `proposed` and one `awaiting_approval` follow-up), `SAMPLE_CALL_SESSIONS`, `SAMPLE_WEBINARS`, `SAMPLE_WEBINAR_MESSAGES` and `SAMPLE_WEBINAR_POLLS`. 2. Each fixture has `sample: true`. 3. When `VITE_DATA_SOURCE=sample`, the workspace app renders consultation and webinar screens using these fixtures without calling the API. 4. The `SampleDataBanner` appears on every screen in sample mode. 5. The API seed inserts these fixtures when `NODE_ENV` is not `production`.
PLT-09	P0	M0	As the platform, I fall back gracefully when the video provider is disabled.	1. `VIDEO_PROVIDER=none` (default in dev and tests) selects `FakeVideoProvider`, which returns deterministic stubs and emits the same domain events through an in-process queue. 2. `POST /appointments/:id/join` succeeds with fake credentials. 3. All Playwright journeys run against `FakeVideoProvider` with Chromium fake media flags. 4. When `VIDEO_PROVIDER=chime` and the SDK errors, join returns 503 `video_provider_unavailable`.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
PLT-10	P0	M1	As the platform, I document client-company network requirements for video calls.	1. The client-company network note states: allow `*.chime.aws` on UDP 3478 and TCP 443, and `*.sdkassets.chime.aws` on TCP 443. 2. The support runbook includes these network requirements. 3. If the pre-join network check fails, the UI shows a message linking to the network requirements document.
PLT-11	P1	M2	As NestSelf operations, I request service quota increases before scaling.	1. Before the first webinar above 100 attendees, operations requests an increase for concurrent meetings and media pipelines in eu-central-1. 2. The default media-pipeline quota (10 concurrent pipelines in eu-central-1) is documented in the runbook with a threshold for when to request an increase (more than 5 recorded webinars in one month).
PLT-12	P0	M1	As NestSelf operations, I receive alerts when call infrastructure degrades.	1. An alert fires when the join failure rate exceeds 5 percent over 15 minutes. 2. An alert fires when p95 `meetingStartDurationMs` exceeds 5 seconds. 3. An alert fires on any `meetingFailed` burst. 4. Alerts are delivered through the observability stack's existing alarm channel.
PLT-13	P0	M1	As the platform, I run a nightly smoke test against the real Chime SDK in the dev account.	1. A CI workflow `video-smoke` joins a real meeting from two Chromium contexts with `--use-fake-device-for-media-stream` and `--use-fake-ui-for-media-stream`. 2. Both contexts send and receive audio and video for 30 seconds. 3. The workflow is gated on the `VIDEO_SMOKE_ENABLED` secret and allowed to be skipped locally. 4. Failure does not block the main CI pipeline but triggers an alert.
PLT-14	P0	M1	As the platform, I enforce a k-anonymity threshold of 5 on any aggregate visible to employers.	1. No endpoint in this epic that is accessible to employer-scoped principals returns a count derived from fewer than 5 individuals. 2. In this epic, no such endpoint exists (employer-scoped principals receive 404 on all routes). The rule applies to any future aggregate endpoint that the reporting epic adds for call or webinar data. 3. This is tested by the authorisation golden cases for every route.
PLT-15	P0	M1	As the platform, I target a join-to-media time budget that the team uses for planning and monitoring.	1. The planning target for time from "Join" click to first media frame is under 5 seconds at p95 (this is a planning target, not an SLA). 2. The `meetingStartDurationMs` metric from the Chime SDK client events is captured in `call_client_events` and used to compute p95. 3. An alert fires when p95 exceeds the target (PLT-12 criterion 2).
PLT-16	P0	M1	As the platform, I build all video controls to WCAG 2.2 AA.	1. All controls in `packages/video` are keyboard-operable with visible focus indicators. 2. State changes are announced through `LiveRegion`. 3. When `prefers-reduced-motion` is active, `useMotionPreset` returns an opacity-only fade of at most 50 ms with no translate or scale. 4. Every panel, sheet and banner in the video package follows the Motion rule. 5. The e2e motion suite has entries for every new panel and sheet. 6. The `CrisisBlock` lists Serbian hotlines (D-CW-38); Hungarian hotlines are added only with a Hungarian launch.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
PLT-17	P0	M0	As the platform, I apply retention defaults from the decision record.	1. Appointment and session metadata, participants, outcomes and provider events: 7-year retention tier. 2. Client diagnostics: 90-day retention. 3. Webinar messages: 12-month retention after the occurrence, then author links removed. 4. Feedback: 24-month retention. 5. Workshop chat: 24 hours after the session. 6. Webinar raw capture segments: 30-day lifecycle rule on the recordings bucket. 7. Approval items (`appointment_approvals`): 7-year retention tier (same as the appointment). 8. These defaults are in the retention seed and can be changed by the DPIA or the founder's answers to L-02 and L-03.
PLT-18	P0	M1	As NestSelf operations, I observe call and webinar health through client event data.	1. The web client posts Chime SDK client events (`meetingStartSucceeded`, `meetingStartFailed`, `meetingFailed`, `meetingReconnected`, `audioInputFailed`, `videoInputFailed`, `signalingDropped`) plus a 30-second `getStats()` aggregate to `POST /calls/:sessionId/client-events`. 2. Rows go to `call_client_events` with a 90-day retention. 3. Client event rows carry only metrics, device error names, browser and OS. They never carry device labels, names or content. 4. Chime's own `EventIngestionUrl` is not used; no client telemetry goes to a third endpoint.
10. Mobile	3 stories			
CALL-32	P1	M4	As an employee on mobile, I join a consultation through the ticket route.	1. The mobile app calls `POST /appointments/:id/call-ticket` (bearer auth), which returns a single-use ticket valid for `CALL_TICKET_TTL_SECONDS` = 30 seconds. 2. A `call.ticket.issued` audit event is recorded. 3. The mobile app opens the workspace web route `/call/$appointmentId?ticket=<ticket>` in an in-app browser view. 4. The web route exchanges the ticket at `POST /appointments/:id/join` for Chime SDK credentials. 5. If the ticket is expired or already used, the endpoint returns 401 with error code `invalid_ticket`. 6. The web client inside WKWebView or Android WebView renders the pre-join and in-call screens.
CALL-33	P1	M4	As an employee on mobile, I understand what features are unavailable.	1. Screen share is not available in the mobile in-app browser. The "Share screen" option does not appear. 2. The pre-join screen states "Screen sharing is not available on mobile" (`calls.prejoin.mobile_screen_share_unavailable`). 3. All other consultation features (audio, video, blur, controls, crisis block, feedback) function identically to the desktop web client.
CALL-34	P1	M1	As an employee starting a psychological consultation, I am optionally prompted for my current location so the expert has crisis-readiness context.	1. When the service category is a psychological session, the pre-join screen shows an optional free-text prompt: "Share your current location with the expert for safety purposes" (`calls.prejoin.location_prompt`). 2. The prompt is skippable and clearly labelled as optional. 3. If provided, the text is stored in `call_sessions.location_text`, visible only to the assigned expert during the session. 4. The location text is deleted when the session ends (not retained in audit details or diagnostics). 5. If the employee skips the prompt, `location_text` stays null and the session proceeds normally.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
11. Consultations: end-of-call follow-up 8 stories				
CALL-35	P0	M1	As an expert, I propose a follow-up on the post-call screen after the outcome is completed.	1. Once the outcome is `completed` (CALL-23), the post-call screen shows a "Propose a follow-up" card with date, time (in the appointment's time zone, from a simple picker), duration (same as this session by default) and a neutral note that the employee decides. 2. `POST /appointments/:id/follow-up` requires `appointment.propose` on the appointment resource; if the outcome is not `completed`, the endpoint returns 409 with error code `follow_up_not_allowed`. 3. On success, a new appointment is created with status `proposed` and `follow_up_of` set to the finished appointment's id. 4. `appointment.follow_up.proposed` is emitted on the `call:{sessionId}` Socket.IO room. 5. An `appointment.follow_up.proposed` audit event is recorded. 6. A neutral email "A follow-up was proposed" (`calls.email.follow_up_proposed`) is sent to the employee.
CALL-36	P0	M1	As an employee, I confirm a follow-up proposal on the post-call screen or the appointment page.	1. `POST /appointments/:id/confirm` requires the employee to be the appointment's `employeeUserId`; if the appointment status is not `proposed`, the endpoint returns 409 with error code `appointment_not_proposed`. 2. If the organisation's `follow_up_approval_policy` is `automatic`: the appointment transitions to `confirmed`, reminders are scheduled (`appointment.remind` jobs at 24 h and 1 h), and ICS is sent to both parties. 3. If the policy is `manager_approval`: the appointment transitions to `awaiting_approval`, an `appointment_approvals` row is created and routed to the holder of an approval authority covering the employee's organisational unit (`approval.decide`, with the self-approval rule and the alternate approver); the employee sees "Waiting for approval" (`calls.followUp.awaiting_approval`). 4. `appointment.confirmed` or `appointment.approval.requested` audit event is recorded.
CALL-37	P0	M1	As an employee, I suggest up to three alternative time windows for a proposed follow-up.	1. `POST /appointments/:id/suggest-times` accepts an array of up to three `{ startsAt, endsAt }` windows. 2. The appointment status stays `proposed`. 3. `appointment.times_suggested` is emitted on the `call:{sessionId}` room and an `appointment.times_suggested` audit event is recorded. 4. The expert sees the suggested windows on the appointment page and picks one with `POST /appointments/:id/schedule`, which updates the appointment's schedule and follows the same confirmation path as CALL-36.
CALL-38	P0	M1	As an employee, I decline a follow-up proposal.	1. `POST /appointments/:id/decline` requires the employee to be the appointment's `employeeUserId`; if the status is not `proposed`, the endpoint returns 409 `appointment_not_proposed`. 2. The appointment transitions to `declined`. 3. The expert is notified via `appointment.follow_up.declined` on the room and by email (`calls.email.follow_up_declined`). 4. An `appointment.declined` audit event is recorded. 5. No other state changes occur.

102 user stories with acceptance criteria (continued)

Continued from the previous page.

Id	Pri	M	Story	Acceptance criteria
CALL-39	P0	M1	As an approver, I approve or reject a follow-up appointment.	1. `GET /orgs/:orgId/appointment-approvals` returns pending approval items for the principal's approval authority; an approver whose authority does not cover the employee's unit receives 404. 2. Each item shows the employee's name, "follow-up session with a NestSelf expert", date and duration; it never shows the service category, the expert's specialty or any session content. 3. `POST /appointment-approvals/:id/approve` requires `approval.decide` with the self-approval rule; it transitions the appointment to `confirmed`, schedules reminders and ICS, and notifies both parties. 4. `POST /appointment-approvals/:id/reject` transitions the appointment to `declined` with the approver's safe reason shown to the employee; it notifies both parties. 5. `appointment.approval.approved` or `appointment.approval.rejected` audit event is recorded.
CALL-40	P0	M1	As the platform, I remind approvers about undecided follow-up approvals.	1. Job `appointment.approval.remind` fires after 5 working days (Monday to Friday in `Europe/Belgrade`) from the approval request. 2. The reminder email is sent to both the approver and the alternate approver. 3. An `appointment.approval.expired` audit event is recorded if still undecided after the reminder (the approval does not auto-expire; the item stays pending until decided).
CALL-41	P0	M1	As an HR administrator, I set the organisation's follow-up approval policy.	1. `PATCH /orgs/:orgId/settings/follow-up-approval` requires `program.overview` on the organisation resource. 2. The body accepts `policy` with values `automatic` (default) or `manager_approval`. 3. An `org.follow_up_policy.changed` audit event is recorded. 4. When set to `manager_approval` and no approval authority covers a unit, a follow-up proposal for an employee in that unit fails with a visible message telling the employee to ask HR to name an approver (`calls.errors.no_approver_for_unit`); the failure is audited.
CALL-42	P1	M1	As an employee, I see a follow-up proposal that arrived after I left the post-call screen.	1. The appointment list (`GET /appointments`) includes appointments with status `proposed`. 2. The appointment detail page shows the same "Confirm" and "Suggest another time" actions as the post-call screen (CALL-36, CALL-37). 3. A reminder email (`calls.email.follow_up_proposed`) was sent when the proposal was made (CALL-35 criterion 6).

CLOSING

Deliberately not written, and how to answer

Each item waits on one of your questions or on another epic.

Stories left out on purpose

- **Recording consultations (for now).** Dual consent model is specified in the guidelines for a future epic, but consultations are never recorded in this epic. (F-CW-01, D-CW-34)
- **Session extension (replaced by the follow-up, D-CW-37).** The room closes at `endsAt` plus 15 minutes. Instead of extending, the expert proposes a follow-up on the post-call screen. (F-CW-06, D-CW-37)
- **SMS reminders.** INFRA-R-21 forbids SMS at launch. Push notifications are not in this epic. (D-CW-04)
- **Native mobile Chime SDK modules.** The first version uses the web client in an in-app browser. Native modules through the Expo Modules API, CallKit and background audio are a later epic. (F-CW-05)
- **Live captions during sessions.** `StartMeetingTranscription` does not accept Serbian. A custom Transcribe streaming path is an M4 candidate at the earliest. (D-CW-23)
- **Replay captions (WebVTT).** Transcribe batch supports sr-RS, but caption review before publication is an M4 CMS handoff item. (D-CW-23)
- **Chat as a messaging channel in consultations.** Only quick signals ("I cannot hear you") are in scope. Full chat creates documentation risk. (D-CW-27)
- **Attendee video in webinars.** Attendees never get a camera; the floor gives audio only. This is a permanent constraint, not a deferral. (D-CW-35)
- **A Hungarian launch.** The platform launches for Serbia; Hungarian is a language for the minority in Vojvodina. Hungarian jurisdiction items (LAW-19 to LAW-25) are kept for a later launch. (D-CW-38)

How to change anything

Reply with the ids: "D-CW-27 add chat to consultations", "CALL-37 drop", "WBN-30 allow 400". Anything without an id is treated as a comment on the plan as a whole. The package, including this copy, is regenerated from the markdown, so a change lands in every document at once.

Where the detail lives

- `02-decisions.md`: the full decision record with alternatives and canonical names
- `03-epic.md`: the charter with architecture and provenance
- `04-user-stories.md`: the stories with their grounding column
- `05-tasks.md`: 27 tasks with files, steps, tests and gates
- `06-implementation-guidelines.md`: 120 engineering requirements
- `research/`: 227 dated, sourced facts and the codebase survey

Numbers in this copy

Effort ranges are planning assumptions. Prices are AWS list prices read on 24 October 2026 and carry their source ids in the research files. Thresholds (15 and 10 minute window, 250 attendees, 24 and 1 hour reminders, group of five) are decisions, not measurements, and can be changed by id.