NestSelf authentication and authorization: implementation guide


How identity, sessions, authorization, the data layer and the clients fit together, where each piece lives in the repository, and how to work on it. The companion `quick-guide.md` gives the one-page version and the reasoning; `docs/tasks/auth/auth-strategy.md` is the full specification (requirement ids such as `D-06` or `AUTHZ-R-61` below refer to it).

Last updated 2026-10-24 on branch `feat/auth-foundation`, after auth phase 2 (plan: `docs/superpowers/plans/2026-10-24-auth-phase-2.md`; status per task: `docs/tasks/auth/phase-2-readiness.md`).

Contents

1. The system in one picture
2. Running it locally
3. Repository map
4. The request pipeline
5. Identity provider layer
6. Sign-in flows
7. Sessions, cookies and CSRF
8. Mobile bearer tokens
9. Principal, grants and the authorization engine
10. Data layer: Drizzle, repositories and row-level security
11. Organization and operations administration
12. Audit log
13. WebSockets
14. Background jobs
15. Web clients
16. Mobile client
17. Infrastructure and the Cognito rollout
18. Configuration reference
19. Testing
20. Recipes
21. Known gaps and next steps

1. The system in one picture



Three ideas carry the whole design:

- **Identity is not authorization.** Cognito (or the local fake) only proves who the caller is. What they may do comes from `grants`, `assignments` and `memberships` in PostgreSQL, resolved per request into a `Principal` and evaluated by the pure `authorize()` function. Tokens carry no roles (D-02).
- **Browsers never see tokens.** Web clients hold an opaque session cookie; the API keeps the Cognito tokens encrypted in Redis (Backend-for-Frontend, D-06). Mobile holds Cognito tokens itself and calls the API with a bearer token (D-07).
- **Default deny, twice.** Every route must declare `@Public()`, `@Authenticated()` or `@Authorize()`, enforced by a CI test. Tenant tables also carry PostgreSQL row-level security policies, so a query that forgets its organization filter returns nothing (D-19, D-37).

2. Running it locally

Local development uses `AUTH_MODE=stub`: a fake identity provider in memory, an in-memory key-value store unless `REDIS_URL` is set, and a real PostgreSQL.

```
pnpm install
pnpm db:up                                  # Postgres 17 and Redis 7 via Docker Compose
cp apps/api/.env.example apps/api/.env      # defaults are fine for stub mode
pnpm --filter @nestself/api db:migrate      # apply apps/api/drizzle/*.sql
pnpm --filter @nestself/api db:seed         # fictional fixtures from packages/sample-data
pnpm --filter @nestself/api dev             # http://localhost:4000, Swagger at /api/docs
pnpm --filter @nestself/api worker:dev      # optional: the nightly jobs (needs REDIS_URL)
pnpm --filter @nestself/api job:run grants.reconcile   # run one job once, no queue
```

The seed creates the sample organization, org units, people, grants and an `external_identities` row per person. The fake identity provider is pre-loaded with the same people (`apps/api/src/identity/identity.module.ts`), so sign-in works out of the box:

Sample person	Email	Population	How to sign in
Jovan Petrović	`user_jovan@example.com`	employee	Email code; read it from the API log line `Fake identity provider: OTP for ... is 123456`, or set `FAKE_IDP_FIXED_OTP=123456`
Ivana Jovanović	`user_ivana@example.com`	employer HR admin and employer owner	Email code. The seed gives her `employer_owner` next to `hr_admin` (`EXTRA_SAMPLE_TEMPLATES` in `seed-lib.ts`), which is what opens `/hr/access`
Stefan Marković	`user_stefan@example.com`	team manager	Email code
Nikola Đorđević	`user_nikola@example.com`	operations staff	Password `Nestself-dev-1234!`, then authenticator enrolment on first sign-in
Milica Ristić	`user_milica@example.com`	expert	Password `Nestself-dev-1234!`, then authenticator enrolment
Dragan Podrašćanin	`user_dragan@example.com`	employer HR admin	Email code. Added 2026-10-24 as the developer account linked to the real dev pool; see section 17

For TOTP in development use any authenticator app with the QR code, or compute codes with `computeTotp(secret)` from `apps/api/src/identity/totp.ts`. The web apps run in sample mode by default (`VITE_DATA_SOURCE=sample`); set `VITE_DATA_SOURCE=api` in `apps/workspace/.env.local` or `apps/admin/.env.local` to use the real sign-in screens against the API. Set `SESSION_COOKIE_INSECURE_DEV=true` in the API env so the session cookie works on plain `http://localhost`.

`pnpm db:up` publishes Redis on `6379:6379`, so it fails when a local Redis or Valkey already owns that port. A machine that already runs PostgreSQL and Redis outside Docker needs only `DATABASE_URL` and `REDIS_URL` pointed at them; skip `db:up` entirely.

The worker boots the same `AppModule` as the API, so it needs the API's whole configuration (database, identity provider settings, session encryption key) plus `REDIS_URL`: the `sessions.reconcile-ttl` job revokes refresh tokens through `SessionService`.

`db:seed` grants each sample person only the templates mapped from their legacy role (plus `employee` for every member, plus Ivana's `employer_owner`). Run against a database seeded before 2026-10-24, it also deletes the over-broad sample grants the older seed created, when every person received every template without a legacy role. It stops early when a sample person's `external_identities` row was relinked to a real pool subject, because the upsert then collides on the row id; seed a fresh database instead.

Switching to a real Cognito pool is described in section 17.

3. Repository map

Path	What lives there
`apps/api/src/auth/`	HTTP sign-in layer: `auth.controller.ts`, `authentication.guard.ts`, the sign-in services, challenge store, throttle, bearer verifiers, `step-up.service.ts`, `me-response.builder.ts` (fills `effectiveActions`), `access-revocation.service.ts`, `profile.service.ts`
`apps/api/src/authz/`	Authorization: `authorize.ts` engine and helpers, `authorization.guard.ts`, `authorization.service.ts` (`require()`, `effectiveActions()`), `step-up-freshness.ts`, `throttles.ts`, `authorize.decorator.ts`, `public.decorator.ts`, `authenticated.decorator.ts`, `resolvers.ts`, `context-loader.ts`, golden decision table, `default-deny.test.ts`
`apps/api/src/principal/`	`principal-loader.ts` (user → `Principal` data with Redis caching), `cache-gateway.ts` (circuit breaker), `invalidation-subscriber.ts`
`apps/api/src/session/`	Redis sessions: `session.service.ts`, `session-cookie.ts`, `csrf.guard.ts`, `session-policy.ts` (lifetimes), `token-cipher.ts`
`apps/api/src/identity/`	`identity-provider.service.ts` (abstract contract), `cognito-identity-provider.ts` + helpers, `fake-identity-provider.ts` + `fake-user-store.ts`, `totp.ts`
`apps/api/src/redis/`	`KeyValueStore` contract, Redis and in-memory implementations, `redis-keys.ts` (every key and TTL), `redis-health.indicator.ts`
`apps/api/src/db/`	Drizzle: `db.service.ts`, `schema/*.ts`, `repositories/*.ts`, `seed/` (`seed-lib.ts`, `backfill-grants.ts`), `migrate.ts`
`apps/api/drizzle/`	SQL migrations and drizzle-kit snapshots
`apps/api/src/audit/`	`audit-writer.ts`, `audit-events.ts` (action catalogue and categories), `pino-redaction.ts`
`apps/api/src/invitations/`, `members/`, `org-units/`, `users/`	Organization and operations administration endpoints; `ops-invitations.controller.ts` and `ops-members.controller.ts` serve the `/ops/orgs/:orgId/*` mirrors
`apps/api/src/grants/`	Grant administration: `grants.controller.ts` (`/orgs/:orgId/grants`), `approval-authorities.controller.ts`, `ops-grants.controller.ts` (`/ops/grants`, `/ops/orgs/:orgId/grants`, `/ops/users/:userId/access`), `grants.service.ts`, `approval-authorities.service.ts`, `grant-rules.ts` (template, scope, condition and delegation-bound rules), `grant-mapper.ts`
`apps/api/src/professional/`	Confidential-domain reads under `/professional/*`; `professional-records.ts` holds the resource shape and the response views shared with emergency reads
`apps/api/src/emergency/`	Emergency access request, approval, denial, revocation and record reads under `/ops/emergency-access/*`
`apps/api/src/ws/`	Socket.IO adapter, gateway, handshake authentication, invalidation

Path	What lives there
`apps/api/src/jobs/`, `apps/api/src/worker/`	`maintenance-jobs.service.ts` (system jobs), `job-scheduler.service.ts` (BullMQ schedules), `job-authorization.ts` (wrapper for principal-bound processors); `worker/main.ts` is the worker entrypoint
`apps/api/src/common/`	`api-error.ts` (error envelope), exception filter, request metadata, Zod pipe
`apps/api/src/config/env.ts`	Zod schema of every environment variable, `AUTH_MODE` rules
`apps/api/test/`	Integration suites against a real PostgreSQL (`*.e2e.spec.ts`, `db/schema.spec.ts`)
`apps/api/docs/auth-core.md`	Route table and module map kept current with the code
`packages/contracts/src/`	Shared Zod schemas and types: `auth.ts`, `principal.ts`, `authorization.ts`, `actions.ts`, `templates.ts`, `org-admin.ts` (grants, approval authorities), `ops-admin.ts` (platform grants, user access, emergency access)
`packages/api-client/src/auth.ts`, `org-admin.ts`	Typed client for every auth endpoint (cookie or bearer mode); `createOrgAdminApi(client, { kind: 'org' | 'ops' })` for the grant administration routes
`apps/workspace/src/auth/`, `apps/admin/src/auth/`	`AuthProvider`, sign-in screens, error mapping, `step-up-dialog.tsx`, `with-step-up.ts`, `route-auth.ts` (route guards wait for the session)
`apps/workspace/src/features/access/`, `apps/admin/src/features/access/`	Access-management screens (section 15)
`apps/mobile/src/auth/`	Cognito public client (PKCE, email OTP), secure token store, `AuthProvider`
`infra/cdk/lib/auth-stack.ts`, `infra/cdk/lib/triggers/`	Cognito user pool, app clients, Lambda triggers, secrets
`packages/sample-data/src/fixtures/`	Fictional people, org units, credentials, `identities.ts` (fake pool subjects), `grants.ts` (`SAMPLE_GRANTS`), `case.ts` (`SAMPLE_CASE`: one conversation and one intake)

4. The request pipeline

Four global guards run in this order for every HTTP request (`apps/api/src/app.module.ts`):

1. **`AuthenticationGuard`** (`src/auth/authentication.guard.ts`). Skips `@Public()` routes. Otherwise it reads the session cookie or the `Authorization: Bearer` header, resolves a `Principal` and attaches `request.principal`, `request.session` (web only), `request.authMeta` and `request.csrfToken`. Missing or invalid credentials end the request with 401.
2. **`CsrfGuard`** (`src/session/csrf.guard.ts`). Only when a session cookie is present and the method is not safe: it checks `Sec-Fetch-Site`, the `Origin` header against the allowed surfaces and the double-submit token (`X-CSRF-Token` header must equal the CSRF cookie). WebSocket contexts are skipped. Failure is 403 `csrf_rejected`.
3. **`AuthorizationGuard`** (`src/authz/authorization.guard.ts`). Skips `@Public()` and `@Authenticated()` routes. For `@Authorize(action, resolver)` it calls the resolver to derive the `Resource`, builds the context

with `ContextLoader`, calls `authorize()`, writes an `access.denied` audit event on denial (the engine's reason is recorded there, never returned to the client) and answers 404 when the caller has no visibility into the organization and 403 otherwise (AUTHZ-R-61). Any principal holding a staff template counts as having visibility, so an operations caller denied in an organization they are not assigned to gets 403 `forbidden`, not 404. When the decision allows and the action has a step-up class, the guard then checks that the authentication is recent enough and answers 403 `step_up_required` otherwise (section 9, Step-up). A handler that carries no decorator at all is denied at runtime as well as by the CI test.

4. **`ThrottlerGuard`** (NestJS throttler, 60 requests per minute by default; sign-in and step-up routes carry tighter `@Throttle` values; grant, approval-authority and emergency-access writes use `WRITE_THROTTLE` from `src/authz/throttles.ts`, 10 per minute per route and client IP).

Decorators (`src/authz/`):

Decorator	Meaning
`@Public()`	No authentication. Sign-in, invitation preview and accept, health, leads.
`@Authenticated()`	A valid session or bearer token, no action check. `/auth/me`, sessions, sign-out, context switch, profile.
`@Authorize(ACTIONS['x.y'], resolver)`	Full grant-based check. The resolver returns `{ type, id?, orgId?, ... }`; use `orgResourceFromContext(type)` for `/orgs/:orgId/*` routes (it enforces that the active context is that organization, API-R-21), `operationsResource(type, idFn)` for `/ops/*` routes (session required, operations context) and `operationsOrgResource(type)` for `/ops/orgs/:orgId/*` routes (the same checks, plus the route organization in the resource so the engine applies the `assigned_clients` scope through the CLIENT assignment).
`@CurrentPrincipal()`	Parameter decorator returning `request.principal`.

`src/authz/default-deny.test.ts` boots the application and fails when any controller handler or gateway message handler lacks one of the three decorators. It runs with the normal test suite, so an undecorated route cannot reach `main`.

Errors use one envelope (`src/common/api-error.ts`, `api-exception.filter.ts`): `{ status, code, message, requestId, details? }`. Codes the clients map: `unauthenticated`, `session_expired`, `csrf_rejected`, `forbidden`, `not_found`, `context_mismatch`, `session_required`, `invalid_code`, `invalid_credentials`, `invalid_challenge`, `too_many_attempts`, `rate_limited`, `validation`, `conflict`, `duplicate_invitation`, `already_member`, `step_up_required`, `delegation_exceeds_boundary`, `subject_not_member`, `template_inactive`, `missing_conditions`, `self_approval_denied`, `emergency_not_active` (the list is `AUTH_ERROR_CODES` in `packages/contracts/src/auth.ts`).

5. Identity provider layer

`IdentityProviderService` (`src/identity/identity-provider.service.ts`) is an abstract class used as the DI token. It covers everything the API needs from the identity provider: start and answer the email OTP challenge, password sign-in and the `SOFTWARE_TOKEN_MFA`, `NEW_PASSWORD_REQUIRED` and `MFA_SETUP` challenges, TOTP association and verification, refresh and revocation, global sign-out, enable, disable, create, delete and find users, forgot-password. Sign-in services depend only on this contract, so swapping the provider never touches them.

- **`CognitoIdentityProvider`** (`AUTH_MODE=cognito`): AWS SDK v3 calls with the confidential web client (`SECRET_HASH` on every call). User-management calls live in `cognito-user-ops.ts`; `cognito-error-map.ts` turns Cognito exceptions into `IdentityProviderError` codes.
- **`FakeIdentityProvider`** (`AUTH_MODE=stub`): in-memory users, sessions, OTP codes and refresh-token families with the same challenge chain as Cognito (`fake-user-store.ts`). It refuses to construct when `NODE_ENV=production`, logs email codes, honours `FAKE_IDP_FIXED_OTP`, and is pre-seeded with the sample people in development.

Both return `AuthOutcome`, either `{ kind: 'tokens', tokens }` or `{ kind: 'challenge', challenge, session, username }`.

6. Sign-in flows

All flows start at `POST /auth/discover` (`discover.service.ts`), which answers `email_otp`, `password` or `sso` without revealing whether the address exists. Interactive steps are stitched together with **challenge tokens**: `ChallengeStore` (`src/auth/challenge-store.ts`) stores the provider session under `challenge:{sha256(token)}` for 5 minutes and consumes it on every use (`GETDEL`, so two concurrent answers cannot both reach the provider). Failed attempts count in `SignInThrottle` (`throttle:otp:{email}`): five failures lock the identifier for 15 minutes with 429 `too_many_attempts`. Unknown addresses go through the same timing (`neutral-delay.ts`) and receive a dummy challenge so responses do not reveal existence.

Cognito's EMAIL_OTP code is eight digits, unlike the six-digit codes it issues for sign-up confirmation, forgot-password and authenticator apps, and unlike the stub provider's `FAKE_IDP_FIXED_OTP`. `EMAIL_OTP_MIN_LENGTH` and `EMAIL_OTP_MAX_LENGTH` in `packages/contracts/src/auth.ts` hold that range; `EmailOtpVerifyRequestSchema`, `OtpInput` and the mobile field all read it. Before 2026-10-24 every one of them hard-coded six, so the input truncated the real code, the user could not type the last two digits, and Cognito answered `CodeMismatchException`.

A wrong email code can be retyped, up to three times per challenge. `emailOtpVerify` and the step-up `verify` consume the challenge before asking the provider. When the provider answers `invalid_code` (Cognito's `CodeMismatchException`, which keeps its own `Session` alive), `retainAfterWrongCode` in `sign-in.service.ts` puts the record back under the same token with `attempts + 1` through `ChallengeStore.put()`, and the API answers 401 `invalid_code`; the user corrects the code without requesting a new one. `put` keeps the deadline stamped at creation (`expiresAt`), so retries never extend the five minutes. The third wrong code (`MAX_EMAIL_OTP_ATTEMPTS = 3`) is not put back: the next attempt with that token answers 401 `invalid_challenge` and the screens ask for a new code. Any other provider error ends the challenge at once. Dummy challenges for unknown addresses follow the same budget so the answers stay identical. `SignInThrottle` still counts every wrong code, across challenges, and locks the address after five. Each wrong code is counted before the record is handed back, and the record that triggers the lock is not handed back; a challenge retained earlier answers 429 `too_many_attempts` once the address is locked (checked after `consume` for dummy and real challenges alike), so a lock cannot be outrun with a token that still has tries left.

Employees: email code. `POST /auth/email-otp/start` with `{ email, locale? }` → `{ challengeToken }` (`locale` is one of `en`, `sr-Latn`, `sr-Cyrl`, `hu`; the API forwards it to the provider as `ClientMetadata.locale`, which the CustomMessage trigger uses for the email's language when the user has no `custom:locale` attribute; the web screens send the language they are shown in and the mobile app sends its resolved device locale directly to Cognito); `POST /auth/email-otp/verify` with `{ challengeToken, code }` → tokens → `IdentityResolutionService.resolveIdentityAndCreateSession()` maps the token `sub` to an

`external_identities` row, loads the principal, creates the Redis session, sets the cookies and returns `{ principal, effectiveActions }`.

Experts and staff: password and authenticator. `POST /auth/password` returns either the signed-in principal or `{ step, challengeToken }` where `step` is `new_password`, `totp` or `totp_enrol`. `POST /auth/challenge` with `{ challengeToken, response }` answers one step and returns either the next `{ step, challengeToken }` (200) or the principal. For `totp_enrol` the client first calls `POST /auth/totp/enrol` with the challenge token to receive the `otpauth://` URI and a rotated challenge token, then `POST /auth/challenge` with the authenticator code; the API verifies the software token and completes `MFA_SETUP` in one step (`sign-in.service.ts`, `totp.service.ts`). `POST /auth/totp/confirm` is the signed-in variant for adding an authenticator later.

Password reset. `POST /auth/password-reset/start` and `/confirm` (`password-reset.service.ts`) wrap the provider's forgot-password flow with neutral responses.

Invitation acceptance. `GET /invitations/:token/preview` returns only the organization name; `POST /invitations/accept` (`src/invitations/invitation-activation.service.ts`) validates the hashed token, creates or links the user, ensures the identity-provider user and the `external_identities` row, creates the ACTIVE membership and the template grants in one transaction, then starts the right sign-in method: an email code for employees or a temporary-password flow for staff and experts.

SSO. `GET /auth/sso/start` and `/callback` are not implemented yet (phase 3); the discover step still reports `sso` when a verified domain matches an active connection.

Every sign-in writes `auth.sign_in.succeeded` or `auth.sign_in.failed` through `AuditWriter`.

7. Sessions, cookies and CSRF

`SessionService` (`src/session/session.service.ts`) stores one JSON record per session at `session:{sha256(sessionId)}` and indexes a user's sessions in `user_sessions:{userId}`. The record (`session.types.ts`) holds the user id, surface (`workspace` or `admin`), population, active context, authentication metadata, lifetimes, a hashed IP and user-agent family, the CSRF token, and the Cognito tokens encrypted with AES-256-GCM (`token-cipher.ts`, key `SESSION_ENCRYPTION_KEY`, dual-key rotation via `SESSION_ENCRYPTION_KEY_PREVIOUS`).

Cookies (`session-cookie.ts`): `__Host-nestself_session` and `__Host-nestself_csrf`, `Secure`, `HttpOnly` for the session, `SameSite=Lax`, `Path=/`. `SESSION_COOKIE_INSECURE_DEV=true` drops the `__Host-` prefix and `Secure` for plain-HTTP localhost. The CSRF cookie is readable by JavaScript on purpose: the API client copies it into `X-CSRF-Token`.

Lifetimes (`session-policy.ts`) depend on population and context, for example employee personal 30 minutes idle and 12 hours absolute, employee organization 60 minutes and 8 hours, expert 8 hours and 7 days, staff 60 minutes and 8 hours; `SESSION_LIFETIME_OVERRIDES` (JSON) adjusts them per environment within the 30-day idle and 90-day absolute caps. Each request extends the idle window; the absolute expiry never moves. The session id is regenerated at sign-in and again after a completed step-up (section 9).

No ETags on API responses. `main.ts` calls `set('etag', false)` on the Express instance. Express otherwise emits a weak ETag for every JSON response, the browser revalidates with `If-None-Match`, and the API answers `304 Not Modified` with no body. `@nestself/api-client` treats anything outside 2xx as a failure (`if (!response.ok)`), so a page refresh turned a live session into an `ApiError` with status 304 and bounced the user to `/sign-in` while the Redis session was still healthy. These responses are per-principal and already `Cache-Control: no-store`; they must never be revalidated.

Access-token refresh happens lazily: `ensureFreshAccessToken` refreshes through the identity provider under `lock:session:{hash}` so concurrent requests do not race; a failed refresh destroys the session.

Revocation paths: `POST /auth/sign-out` (current session), `POST /auth/sign-out-all` (every session, Cognito global sign-out), `DELETE /auth/sessions/:id` (another device), and `AccessRevocationService.revokeAllAccess()` (`src/auth/access-revocation.service.ts`), which membership end and suspension call: destroy sessions, `globalSignOut` for every external identity, publish the principal invalidation. It never throws; it reports what failed.

Context switch (`POST /auth/context`, `session-endpoints.service.ts`) changes the active context (`personal`, `organization`, `expert`, `operations`) after checking the principal actually holds it; it never extends the absolute expiry.

8. Mobile bearer tokens

Mobile apps authenticate against Cognito directly and send `Authorization: Bearer <access token>`. `AuthenticationGuard` passes the token to the `BEARER_VERIFIER` provider (`src/auth/bearer-verifier.ts`): `CognitoBearerVerifier` verifies signature and claims with `aws-jwt-verify` (`tokenUse: 'access'`, the mobile client id) and rejects tokens whose refresh family is listed in `revoked_family:{originJti}`; `StubBearerVerifier` accepts HS256 tokens signed with `JWT_SECRET` in stub mode. The guard then maps `sub` to the user through `external_identities`, records the family in `user_mobile_families:{userId}` and refreshes `mobile_family:{originJti}` (30-day TTL, AUTHZ-R-64) and assembles the principal with the default context for the user. Bearer callers cannot use `/ops/*` routes (API-R-28) and get 403 `session_required`. The nightly `mobile.prune-stale-families` job (section 14) denylists families whose last-seen key has expired.

Cognito access tokens carry `auth_time` but not the method, so `CognitoBearerVerifier` reports `email_otp` with no second factor. That is accurate today: the mobile app client only permits the email-code first factor (`USER_AUTH` with `EMAIL_OTP`), passwords and authenticators are web-only, and SSO (which would set `sso`) is phase 3. Bearer callers step up through the same `/auth/step-up/*` endpoints as the browser, never through claims; the result is stored under `stepup:{tokenFamily}` for 30 minutes (`STEP_UP_BEARER_TTL`). The mobile app has no step-up screen yet (section 21).

9. Principal, grants and the authorization engine

Shape. `Principal` (`packages/contracts/src/auth.ts`, `principal.ts`): `userId`, `displayName`, `initials`, `locale`, `memberships[]` (id, orgId, orgUnitId, status, dates), `staffTemplates[]`, `expert` (id and approved categories), `context`, `auth` (method, time, second factor, last step-up), `sessionId`, `tokenFamily`. It carries no grants; those are loaded per decision.

Loading and caching. `PrincipalLoader` (`src/principal/principal-loader.ts`) reads through the repositories and caches in Redis with jittered TTLs: `principal:{userId}` 30 s, `grants:{userId}:{orgId}` 60 s, `assignments:{userId}` 60 s, `org_tree:{orgId}` 5 min. `CacheGateway` wraps Redis with a circuit breaker (three failures open it for 5 s) and a small in-memory LRU fallback. Writes that change access call `invalidateUser(userId, orgIds)`, which deletes the keys and publishes on the `invalidate` channel; `InvalidationSubscriber` on every API instance drops its local copies, and the WebSocket layer re-authorizes connected sockets.

Delegated grants carry their ancestors. When the subject holds a delegated grant, `loadGrants` also loads its ancestor chain (`AuthorizationRepository.findDelegationAncestors`, a recursive walk over `parent_grant_id` in system context, revoked rows included) into the same `grants:{userId}:{orgId}` entry, because `validateDelegation` needs the whole chain to decide. A change to an ancestor reaches that entry only through the delegatee's own invalidation, so every path that revokes or adjusts a grant calls `PrincipalLoader.invalidateDelegatees(grantIds)`, which walks the tree downwards (`findDelegationDescendants`) and invalidates every subject below: grant revoke and update, membership end and the `grants.reconcile` job. It runs after the commit; if it fails, delegatees keep stale copies until the grants TTL ends.

Vocabulary. `ACTIONS` (`packages/contracts/src/actions.ts`) is the closed catalogue of dotted action strings (`people.invite`, `program.overview`, `conversation.read.assigned` ...). `PERMISSION_TEMPLATES` (`templates.ts`) are the 17 named starting sets (`platform_owner`, `client_operations`, `hr_admin`, `team_manager`, `employee`, `expert` ...) with default actions, scope type, conditions and step-up actions. A **grant** gives a user a list of actions within a scope (`own`, `org_unit` with optional descendants, `organization`, `platform`, `assigned_cases` ...) with optional Zod-validated conditions (spending ceiling, categories, confidential approver, time window), a validity window and, for delegated grants, a parent and depth limit of 3.

Deciding. `authorize(principal, action, resource, ctx)` (`src/authz/authorize.ts`) is pure and ordered: user state (suspended or deactivated denies everything), context validity (`context.ts`), confidential hard deny, assignments, grants with scope matching through the closure-table ancestor set (`scope.ts`), conditions (`conditions.ts`), validity window, self-approval rule, delegation envelope (`delegation.ts`). It returns `{ allowed, grantIds, assignmentIds, denialReason, explanation[] }`; `explain.ts`, `authorize-many.ts` and `effective-access.ts` build on it. `ContextLoader` (`context-loader.ts`) assembles the `AuthorizationContext` (grants, assignments, ancestor ids, organization settings, emergency access for confidential actions, which is never cached). Step 5 matches only grants whose `subjectUserId` is the principal's own; the ancestors loaded for a delegated grant serve `validateDelegation` and never lend their actions to the delegatee. The golden table `golden-table.json` (150 tuples, including the `CONF-DENY-01` to `06` confidential hard-deny rows and the `DELEG-ALLOW-01`, `DELEG-DENY-01` to `03` delegation rows) and fast-check property tests (`authorize.property.test.ts`) pin the behaviour: no cross-organization allow, delegation never exceeds the delegator, expired never allows, confidential never allowed by administrative scopes.

Using it outside a guard. `AuthorizationService.require(principal, action, resource)` is for service-layer checks whose resource needs row data a static resolver cannot load (the confidential domain and emergency record reads, section 11). It audits denials like the guard, maps them to 403 or 404 the same way, and applies the same step-up check. `effectiveActions(principal)` fills `effectiveActions` in every `MeResponse` through `MeResponseBuilder` (`src/auth/me-response.builder.ts`): sign-in completion, `GET /auth/me`, `POST /auth/context` (for the new context) and the two profile updates. Before 2026-10-24 every response carried an empty list, so every action-gated screen was unreachable in api mode. An action counts when any current grant allows it, and an `org_unit` grant is evaluated at its own unit, so team-scoped templates such as `team_manager` appear. Clients get the same answer client-side as a hint through `can()` in `packages/contracts/src/principal.ts`; it is never the enforcement.

Step-up. `STEP_UP_CLASS_BY_ACTION` (`packages/contracts/src/authorization.ts`) puts sensitive actions into five classes, each with a maximum age in `STEP_UP_MAX_AGE_SECONDS`:

Class	Maximum age	Actions
`emergency`	5 min	`access.emergency.request`, `access.emergency.approve`

Class	Maximum age	Actions
`restricted`	15 min	`conversation.read.assigned`, `notes.read.supervision`, `records.read.emergency`
`export`	15 min	`report.export`, `data.export.own`
`financial`	15 min	`spend.approve`, `funding.allocate`, `budget.allocate`
`administration`	30 min	`access.grant`, `access.revoke`, `access.delegate`, `people.deactivate`, `sso.manage`, `session.revoke.any`

`assertStepUpFresh` (`src/authz/step-up-freshness.ts`) runs after an allow decision, both in `AuthorizationGuard` and in `AuthorizationService.require()`. It takes the latest of `auth.time`, `auth.lastStepUpAt` and, for bearer callers, the `stepup:{tokenFamily}` record; when that is older than the class allows it throws 403 `step_up_required` with `details: { stepUpClass, maxAge, method: 'email_otp' }`. A caller who signed in again after an old step-up counts from the new sign-in. Denied callers keep their 403 or 404 and are never asked to step up. The `restricted` class is enforced as a plain 15-minute maximum age, not as "first access per session" as the strategy words it; the stricter reading can be added without a contract change.

`StepUpService` (`src/auth/step-up.service.ts`) serves `POST /auth/step-up/start` (200, `{ method: 'email_otp', challengeToken, ssoStartUrl: null }`) and `POST /auth/step-up/verify` (`{ challengeToken, code }`, 204). Both are `@Authenticated()` and limited to 5 requests per minute. Start sends an email code to the address of the principal's first Cognito identity and stores a challenge that records `stepUp.userId`; a principal without a native identity (federated users, until phase 3) gets 403 `forbidden`. Verify refuses a challenge minted for another user, or for sign-in, with 401 `invalid_challenge`, and `/auth/email-otp/verify` refuses step-up challenges the same way, so a step-up code can never mint a new session. A wrong code follows the three-attempt rule of section 6. On success a session caller gets `markStepUp`, then `regenerate`: the 204 carries a new session cookie and CSRF token. A bearer caller gets `stepup:{tokenFamily}` with a 30-minute TTL. The throwaway refresh token the provider issued is revoked, and `auth.step_up.completed` or `auth.step_up.failed` is audited.

Every class steps up with an email code, staff and experts who signed in with a password and an authenticator included, and the `emergency` class included, for which the strategy asks for an authenticator. Cognito's `USER_AUTH` flow cannot issue a `SOFTWARE_TOKEN_MFA` challenge without a password first, so an authenticator-only step-up would mean retyping the password. This deviation is an open owner decision (section 21).

10. Data layer: Drizzle, repositories and row-level security

Schema (`src/db/schema/`): `identity.ts` (users, external_identities), `organization.ts` (organizations, org_units, org_unit_closure, memberships, legacy_teams and the `teams` view), `authorization.ts` (permission_templates, grants, assignments, approval_authorities, emergency_access), `professional.ts` (conversations, conversation_messages, intake_records), `invitations.ts` (invitations, sso_connections, sso_domains), `audit.ts` (audit_events, retention_policies), `content.ts` (experts, credentials, content, channels, polls, leads, event requests), `relations.ts` for `db.query.*`. Since migration `0005` neither `users` nor `memberships` carries a legacy role: what a person may do comes from grants only. Conventions: snake_case columns (`casing: 'snake_case'`), text ids with `gen_random_uuid()::text` defaults, `timestamptz(3)`, `updated_at` maintained by Drizzle.

Row-level security. Tables with an organization column (`org_units`, `memberships`, `grants`, `approval_authorities`, `invitations`, `sso_connections`, `channels`, `event_requests`, `conversations`, `intake_records`) declare a `pgPolicy` whose predicate is `coalesce(current_setting('app.current_org_id', true), '') = '' OR org_id = current_setting('app.current_org_id', true)` (platform-wide grants with a null organization stay visible). Tables that reach their organization only through a join use `tenantPredicateVia()` with a correlated `EXISTS`: `posts` through `channels`, `polls`, `poll_options` and `poll_votes` through `legacy_teams`, `org_unit_closure` through `org_units` (migration `0002_rls_legacy_content_closure.sql`) and `conversation_messages` through `conversations` (migration `0003`). Every one of the sixteen tenant tables has RLS enabled and forced. `emergency_access` is platform-level and has no policy. `DbService.withOrgScope(orgId, fn)` runs `fn` in a transaction after `select set_config('app.current_org_id', $1, true)`; everything inside sees and writes only that organization. `DbService.withTransaction(fn)` is the same without the setting, for platform writes such as platform grants and emergency access. Code that runs without the setting (principal loading, seeds, jobs) is in system context and sees all rows. Policies bind only roles that are neither superuser nor table owner: migrations run as the owner, the API connects as a login that is a member of `nestself_app` (Docker: `nestself_api` created by `docker/initdb/01-app-role.sql`). A local Homebrew superuser is not restricted; `test/db/schema.spec.ts` proves the policies with a non-superuser login.

Repositories (`src/db/repositories/`): `identity`, `authorization` (grants, assignments, delegation walks, emergency access), `approval-authorities`, `professional`, `audit`, `leads`, `invitations`, `memberships`, `org-units`. They are the only place with Drizzle query builders; every method accepts an optional `tx` so services can compose them inside `withOrgScope`. Services depend on repositories, which is why unit tests mock plain methods and app-level tests override `DbService` with `{ ping, onModuleInit, onModuleDestroy }`.

Migrations. `pnpm --filter @nestself/api db:generate` diffs the schema against `drizzle/meta` and writes a new SQL file; `db:generate -- --custom --name=<name>` creates an empty file for hand-written SQL; `db:migrate` applies pending files (tracked in `drizzle.__drizzle_migrations`); `db:seed` upserts the fixtures. `0001_audit_partitions_rls_roles.sql` holds what drizzle-kit cannot express: monthly range partitions and `audit_events_ensure_partitions()`, the append-only triggers, the `nestself_app` role and its privileges, `FORCE ROW LEVEL SECURITY`. `0002_rls_legacy_content_closure.sql` adds the join-based policies above, forces them, and makes `audit_events_ensure_partitions()` `SECURITY DEFINER` so the application role can create partitions from the nightly job. Never let drizzle-kit alter `audit_events` directly; write a custom migration.

Phase 2 added three migrations. `0003_professional_domain.sql` creates the confidential-domain tables with their policies and forced RLS. `0004_emergency_access_request.sql` makes `emergency_access.approved_by_user_id` nullable and adds `approved_at` and `requested_duration_minutes` (default 240), so a request can wait for its approver. `0005_drop_legacy_roles.sql` drops `users.platform_role`, `memberships.role` and the `org_role` and `platform_role` enum types (D-36); a hand-written `DO $$` guard at its top raises, naming the first user, when a legacy role still lacks its backfilled grant. On a database that still holds legacy roles: migrate to `0004`, run `pnpm --filter @nestself/api db:backfill-grants`, then migrate again (`apps/api/README.md`, "Legacy role backfill"). A fresh database needs no backfill. `memberships.team_id`, `legacy_teams` and the community tables stay until the community feature is retired, and the contracts keep `OrgRole` and `PlatformRole` for sample mode.

11. Organization and operations administration

All `/orgs/:orgId/*` routes require the active context to be that organization (`orgResourceFromContext`). All `/ops/*` routes require a web session in the operations context (`operationsResource`, or `operationsOrgResource(type)` when the route names an organization). Writes run inside `withOrgScope` (or `withTransaction` for platform rows) and audit through `AuditWriter`.

Area	Routes and actions	Files
Invitations	`POST /orgs/:orgId/invitations` and `DELETE .../:invitationId` (`people.invite`), `POST .../import` (`people.import`); public `GET /invitations/:token/preview`, `POST /invitations/accept`	`src/invitations/` (`invitations.service.ts`, `invitation-activation.service.ts`, `invitation-token.ts`, `invitation-mailer.ts`, `ses-invitation-mailer.ts`)
Invitations for assigned clients	`POST /ops/orgs/:orgId/invitations` and `DELETE .../:invitationId` (`people.onboard`), `POST .../import` (`people.import`)	`src/invitations/ops-invitations.controller.ts`
Org units	`GET /orgs/:orgId/org-units` (`program.overview`), `POST`, `PATCH .../:unitId`, `POST .../:unitId/move` (`org_units.manage`)	`src/org-units/` (`closure-moves.ts` holds the pure closure-table algebra)
Members	`GET /orgs/:orgId/members` (`program.overview`; cursor pagination, filters), `PATCH .../:membershipId` (`people.move`), `POST .../:membershipId/end` (`people.deactivate`)	`src/members/`
Members of assigned clients	`GET /ops/orgs/:orgId/members` (`client.configure`), `POST .../:membershipId/end` (`people.deactivate`)	`src/members/ops-members.controller.ts`
Grants	`GET /orgs/:orgId/grants` (`access.preview`; `?subjectUserId=&includeRevoked=`), `GET .../preview?userId=` (`access.preview`), `POST` and `PATCH .../:grantId` (`access.grant`), `POST .../:grantId/revoke` (`access.revoke`), `POST .../delegate` (`access.delegate`)	`src/grants/`
Approval authorities	`GET /orgs/:orgId/approval-authorities` (`access.preview`), `POST` and `PATCH .../:id` (`access.grant`)	`src/grants/approval-authorities.*`
Grants, operations side	`GET` and `POST /ops/grants` (platform grants; `access.preview`, `access.grant`); `GET /ops/orgs/:orgId/grants`, `GET .../preview`, `POST`, `POST .../:grantId/revoke`; `GET /ops/users/:userId/access` (`access.preview`)	`src/grants/ops-grants.controller.ts`

Area	Routes and actions	Files
Users, operations side	`POST /ops/users/:userId/suspend`, `POST .../reinstate` (`people.deactivate`)	`src/users/`
Confidential domain	`GET /professional/conversations/:id` and `GET /professional/intake/:id` (`conversation.read.assigned`), `GET /professional/me/conversations/:id` (`conversation.participate`); `@Authenticated()`, authorized in the service	`src/professional/`
Emergency access	`GET /ops/emergency-access` (`audit.read`, optional `?userId=`), `POST` (`access.emergency.request`), `POST .../:id/approve`, `.../:id/deny`, `.../:id/revoke` (`access.emergency.approve`), `GET .../:id/records/:recordType/:recordId` (`@Authenticated()`, `records.read.emergency` in the service)	`src/emergency/`

The routes for assigned clients use different actions from their `/orgs` twins because the `client_operations` template holds `people.onboard` and `client.configure`, while `people.invite` and `program.overview` are HR actions (strategy 4.4). The ops invitation routes validate bodies with `ZodValidationPipe` and the `/orgs` invitation routes with a local helper, so their 400 bodies differ slightly.

Invitation tokens are 32 random bytes; only the SHA-256 hash is stored, with a 7-day expiry. In development the create response adds `devToken` and the logging mailer prints the link; with `SES_FROM_EMAIL` set the SES mailer sends it. Membership end sets `ENDED`, revokes the user's grants scoped to the organization and the whole delegation tree below them (`revokeGrantTree`: roots record `membership_ended`, descendants `parent_revoked`), audits first, invalidates every delegatee, then calls `revokeAllAccess` (SESS-R-22, SESS-R-23). Suspension sets `users.suspended_at`, disables the identity-provider user, audits `user.suspended` (SECURITY tier) and revokes all access; `authorize()` denies suspended users on the next request anyway.

`people.deactivate` is held by three templates: `hr_admin` (organization scope, ends memberships of its own organization through `/orgs/:orgId/members/:id/end`), `platform_owner` (platform scope, the only template that reaches `/ops/users/:id/suspend`, whose resource has no organization) and `client_operations` (scope `assigned_clients`, through `/ops/orgs/:orgId/members/:id/end` for an organization the caller holds a CLIENT assignment to). The sample data has no platform owner; tests create that grant from the template.

11.1 Grant administration

Create (`POST /orgs/:orgId/grants`, `{ templateKey, subjectUserId, scopeType, scopeOrgUnitId?, includeDescendants?, conditions, validFrom?, validUntil? }`). The template must be active (400 `template_inactive`) and belong to the `organization` workspace (400 `validation`). The scope is `organization` or `org_unit`, with a unit of this organization (404 otherwise). The subject must hold an ACTIVE membership (409 `subject_not_member`). Every `requiredConditionTypes` entry of the template must be present (400 `missing_conditions`, `details.missing`). Actions are copied from the template, `validFrom` defaults to now and `validUntil` must come after it.

Update (`PATCH`) changes conditions and the validity window only. A revoked grant answers 409 `conflict`, another organization's grant 404. When the patch changes conditions and the grant has active delegated

children, each child is checked against the patched parent; if any falls outside, the update is refused with 409 `conflict` and `details.children` naming them, so the administrator adjusts or revokes those first. A shorter validity window is not checked against the children: the engine denies them at runtime once the parent has expired.

Revoke takes a reason (3 to 500 characters) and revokes the grant and every descendant through `revokeGrantTree`; an already revoked grant answers 409. **Preview** (`?userId=`) requires the subject to be an active member (404 otherwise), runs `effectiveAccess` for the subject in this organization and drops the confidential actions (AUDIT-R-02).

Every write records one audit event (`grant.created`, `grant.adjusted`, `grant.revoked`, `grant.delegation_revoked` per descendant, `grant.delegated`) with field names, counts and condition types, never values, and invalidates the subject and every delegatee.

Operations side. `POST /ops/orgs/:orgId/grants`, its list, preview and revoke use the same service. `POST /ops/grants` creates a platform grant (`scope_org_id` null) from an `operations` workspace template at the template's own scope type, inside `DbService.withTransaction` with its audit call. `GET /ops/users/:userId/access` returns one context per active membership plus a platform context, each with actions (confidential ones dropped), grant ids and assignment ids. The ops side has no org-unit, update, delegation or approval-authority routes.

Who can administer grants today. Under the strategy's template table no organization template holds `access.grant` or `access.revoke`: `employer_owner` holds `access.delegate` and `access.preview`, and `hr_admin` holds none of the `access.*` actions. Only `platform_owner` holds all four. So NestSelf staff with `platform_owner` create and revoke organization grants through `/ops/orgs/:orgId/grants`, and an employer owner previews access and delegates from their own grants. The create, patch and revoke routes under `/orgs/:orgId/grants`, and the approval-authority writes, are reachable only with an ad hoc grant that carries `access.grant` or `access.revoke` (the e2e suite inserts one). Whether `employer_owner` or `hr_admin` should hold them is an open owner decision (section 21).

Delegation (`POST /orgs/:orgId/grants/delegate`, `{ parentGrantId, subjectUserId, actions, scopeType?, scopeOrgUnitId?, includeDescendants?, conditions }`). The checks run in this order, and each failure answers 403 `delegation_exceeds_boundary` with a `details.reason` unless noted:

1. the parent grant belongs to this organization (404 otherwise);
2. the parent's subject is the caller (`not_parent_subject`);
3. the scope is `organization` or `org_unit` inside the organization (400 or 404);
4. the delegatee is an active member (`subject_not_member`);
5. the new depth is at most 3 (`delegation_depth_exceeded`);
6. the parent grant bounds the child: actions are a subset, the scope sits within the parent's, a spending ceiling is not higher and categories are a subset (`actions_exceed_parent`, `scope_exceeds_parent`, `spending_ceiling_exceeds_parent`, `categories_exceed_parent`; `grant-rules.ts`);
7. `validateDelegation` over the parent chain loaded from the database, with the parent's `delegationEnvelope`, when present, as an extra restriction.

The delegated grant is stored with `templateKey: null`. Strategy AUTHZ-R-13 says a parent without an envelope may not be delegated from at all; here the parent grant itself is the bound in that case (AUTHZ-R-37), which is the reading the plan took. At runtime the delegatee's context carries the ancestor chain (section 9), so the delegated actions apply to them, and the revocation or expiry of any ancestor ends them at once, before a job runs.

Approval authorities. The approver and the alternate must both be active members (409 `subject_not_member`), the alternate must differ from the approver (400 `validation`) and the org unit must belong to the organization. A PATCH never changes `userId`, `orgId`, `orgUnitId` or `delegatedFromId`; an empty PATCH writes nothing. Each write audits `approval_authority.changed` with `details.changedFields`.

11.2 Confidential domain

`conversations`, `conversation_messages` and `intake_records` (`src/db/schema/professional.ts`, migration `0003`) are placeholder tables with the minimum columns, under forced RLS. No route writes them yet; the seed adds `conv_sample` and `intake_sample` for `case_sample` (`SAMPLE_CASE`) with a CASE assignment for Milica. The service loads the row (404 when it is missing), calls `AuthorizationService.require()` with `{ type, id: caseId, orgId, ownerId: employeeUserId, isConfidential: true }` and only then reads the messages. Two paths are allowed: the participant through `employee` (`own`) on `/professional/me/conversations/:id`, and the assigned expert through the `expert` template (`assigned_cases`) together with a CASE or SUPERVISION assignment whose `targetId` is the case id. The `expert` template gained `conversation.read.assigned` for that path on 2026-10-24. Organization, org-unit, platform and assigned-client grants are hard-denied (golden rows `CONF-DENY-01` to `06`). Bodies are never logged or audited.

`case_id` is free text with no organization binding, and the assignment match compares `targetId` only. That is harmless while nothing writes these tables; before any write path lands, add a `cases(id, org_id)` table with foreign keys (section 21).

11.3 Emergency access

- **Request**: `POST /ops/emergency-access` with `{ purpose (10 to 1000 characters), scopeKind: 'CASE' | 'USER_RECORDS', scopeId, durationMinutes (15 to 240, default 240) }` creates a pending row (`approvedByUserId` null) and audits `emergency_access.requested` with the purpose truncated to 500 characters.
- **Approve**: a second staff member with `access.emergency.approve`. The requester gets 403 `self_approval_denied`, audited as `access.denied`; a row that is not pending answers 409. The window restarts at approval and ends `min(durationMinutes, 240)` minutes later. One pino `warn` line `{ action: 'emergency_access.approved', emergencyAccessId }` feeds the `EmergencyAccessActivations` metric filter of the observability stack.
- **Deny** deletes a pending row (204, `emergency_access.denied`); **revoke** closes an active one (`emergency_access.revoked`, 409 `emergency_not_active` otherwise).
- **Read**: `GET /ops/emergency-access/:id/records/:recordType/:recordId` (`conversation` or `intake`) needs an operations session and a record that belongs to the caller, then `require(principal, 'records.read.emergency', resource)`, then the named record itself must be active and cover the resource (403 `emergency_not_active`). It returns the same view as the professional route and audits `emergency_access.used`. There is no list of records (CONF-R-09).

`findActiveEmergencyAccess` ignores unapproved rows and the engine checks `expiresAt` on every read, so an expired window is denied before the sweeper (section 14) closes the row. Request and approve are in the `emergency` step-up class (5 minutes), the read in `restricted` (15 minutes). Every write runs in `withTransaction` with its audit call and invalidates the requester's principal.

12. Audit log

`AuditWriter.record()` (`src/audit/audit-writer.ts`) inserts into `audit_events` with the category derived from the action (`audit-events.ts`: `auth.*` and `user.suspended` are SECURITY, `grant.*` and `access.denied` AUTHORIZATION, administration ADMIN, content CONTENT_ACCESS), the retention horizon from `retention_policies` (10-minute cache, defaults per tier), a keyed hash of the IP (HMAC with `IP_HASH_SALT`, falling back to the session encryption key, so it cannot be reversed from a table of all addresses) and the parsed user-agent family. Details are sanitised: forbidden keys (tokens, passwords, message bodies, intake text, notes, voucher codes, raw email) are dropped and strings truncated. `record()` never throws in production; tests set `strictMode`. The table is range-partitioned by month and protected by triggers that reject UPDATE and DELETE; the application role also lacks those privileges. `pino-redaction.ts` redacts the same fields from HTTP logs. Add a new action to `AUDIT_ACTIONS` before using it; the type will not compile otherwise. `record()` writes through its own connection, not the caller's transaction: in strict mode a failed audit write rolls the caller's transaction back, otherwise the change commits and the writer logs the failure.

13. WebSockets

`NestSelfIoAdapter` (`src/ws/nestself-io.adapter.ts`, installed in `main.ts`) serves Socket.IO under `/api/ws`. The handshake middleware (`ws-auth.service.ts`) checks the `Origin` against the allowed surfaces, then authenticates either the web session cookie (same code path as HTTP) or a mobile ticket from `POST /auth/ws-ticket`: 30-second TTL, hashed, consumed atomically with `GETDEL` (`ws_ticket:{hash}`). The gateway (`events.gateway.ts`) exposes `subscribe { room, action, resource }` and `unsubscribe`; each subscription runs `authorize()` (`subscription-authorizer.ts`) and denied rooms emit `subscribe:denied`. `ws-invalidation.service.ts` listens on the `invalidate` channel and, for connected sockets of that user, reloads the principal, disconnects suspended or deactivated users and leaves rooms whose grants are gone (`subscription:revoked`). `ws-connection-registry.ts` tracks sockets per user.

14. Background jobs

Two kinds of job live in `src/jobs/`.

Jobs on behalf of a principal. `JobAuthorization` (`job-authorization.ts`) wraps BullMQ processors. A job payload carries `{ principalId, context, action, resource, data }` and never tokens or grants (AUTHZ-R-54). At execution the wrapper reloads the principal, rebuilds the context and calls `authorize()`; an unknown, suspended or denied principal completes the job as `skipped` (not failed, so no retry) with an `access.denied` audit event, while allowed jobs run the handler and audit with `actorKind: 'JOB'`. Feature modules that enqueue work (exports, imports) wrap their processors with it.

System maintenance jobs. `MaintenanceJobsService` (`maintenance-jobs.service.ts`) holds idempotent jobs that run in system context (no tenant setting) and audit with `actorKind: 'JOB'`, `actorUserId: null`:

Job	Schedule (local)	What it does
`audit.ensure-partitions`	01:00	Calls `audit_events_ensure_partitions(3)` so the next three months' partitions exist (D-21)

Job	Schedule (local)	What it does
`grants.reconcile`	02:15	Closes grants whose `valid_until` passed (`grant.expired`), revokes delegations whose parent is revoked (`grant.delegation_revoked`), revokes organization-scoped grants whose subject has no ACTIVE membership (`grant.revoked`, reason `membership_ended`), then invalidates each affected principal and every delegatee below a closed grant (T-2.10, D-17)
`mobile.prune-stale-families`	02:30	Scans `user_mobile_families:*`; a family whose `mobile_family:{jti}` key has expired (30 days unseen) is denylisted in `revoked_family:{jti}` for 90 days, removed from the set and audited as `auth.mobile_family.revoked` (AUTHZ-R-64)
`sessions.reconcile-ttl`	02:45	Scans `session:*`; a record whose `absoluteExpiresAt` has passed (its key outlived its TTL) is destroyed through `SessionService.destroyOwnedByHash`, which revokes the refresh token, removes the hash from `user_sessions:{userId}` and publishes the invalidation. Malformed records are counted and left alone; a record whose destruction fails is counted in `failed` and retried on the next run (SESS-R-16)
`emergency.sweep-expired`	every 15 minutes	Sets `revoked_at` on approved emergency access whose `expires_at` has passed, audits `emergency_access.expired` and invalidates the requester. The engine already denies an expired window, so the sweep only closes the record

`JobSchedulerService` (`job-scheduler.service.ts`) registers these as BullMQ job schedulers on the `nestself-maintenance` queue (its own ioredis connection to `REDIS_URL`, cron in `JOBS_TIMEZONE`, default `Europe/Belgrade`, three attempts with exponential backoff) and runs a worker with concurrency 1. It is started only by the worker process: `src/worker/main.ts` boots the application context without an HTTP listener and calls `start()`; the ECS `worker` service runs `node dist/worker/main.js` from the same image as the API, locally `pnpm --filter @nestself/api worker:dev`. Without `REDIS_URL` the worker exits with an error. The worker boots the same `AppModule` as the API, so it also needs the API's identity provider settings and session encryption key: `sessions.reconcile-ttl` revokes refresh tokens through `SessionService`. `pnpm --filter @nestself/api job:run <name>` executes one job immediately through `scripts/run-job.ts` and prints its report, which is how to verify a job after a deploy or catch up after downtime. `KeyValueStore.scan()` exists for these jobs only; request paths never call it.

`worker:dev` and `job:run` do not boot today. Both run the TypeScript sources through `tsx`, whose esbuild transform emits no decorator metadata, so Nest cannot resolve constructor dependencies (on 2026-10-24: `Nest can't resolve dependencies of the AuthorizationService (?, ...)`; before phase 2 the same run failed one step earlier in `DbService`). The compiled worker boots: `pnpm --filter @nestself/api build`, then `pnpm --filter @nestself/api worker` (`node dist/worker/main.js`). Running one job from the compiled output, or running the scripts through a metadata-emitting loader, is a follow-up (section 21).

Unit tests (`maintenance-jobs.service.test.ts`) use mocked repositories and the in-memory store; `test/jobs.e2e.spec.ts` runs the reconciliation and partition jobs against the real database and checks the audit trail and the application role's permission to create partitions; `test/emergency.e2e.spec.ts` runs the emergency sweep.

15. Web clients

`packages/api-client/src/client.ts` works in cookie mode (default): `credentials: 'include'` and the CSRF cookie copied into `X-CSRF-Token` on mutating requests. `auth.ts` exposes typed functions for every endpoint (`discover`, `emailOtpStart`, `emailOtpVerify`, `password`, `challenge`, `totpEnrol`, `me`, `switchContext`, `signOut`, `listSessions`, `invitationAccept` ...) validated with the contracts schemas.

`apps/workspace/src/auth/` and `apps/admin/src/auth/`: `AuthProvider` calls `GET /auth/me` on mount and window focus and exposes `status`, `principal`, `effectiveActions` (computed by the API, section 9) and `stepUp()` through `useAuth()`; a 401 flips to unauthenticated. `sample-auth-provider.tsx` serves sample mode with `SAMPLE_PRINCIPALS`. `screens/sign-in-page.tsx` drives the identifier-first flow with one screen per step (`identifier`, `otp`, `password`, `new-password`, `totp`, `totp-enrol`); `map-auth-error.ts` maps error codes to localized messages (`packages/i18n/locales/*/auth.json`), with `error.unknown` for codes it does not know. Routes under `routes/_authenticated/` redirect to `/sign-in` without a principal and gate sections with `can()` (for example `_hr.tsx` requires `program.overview`); `routes/_public/invite.$token.tsx` handles invitation links.

Route guards wait for the session. The guards (`_authenticated` in both apps; `_hr`, `_manager` and `_hr/hr/access` in the workspace) await `resolveRouteAuth(context.auth)` from `auth/route-auth.ts` before deciding. On a full page load the router context starts without a principal; in api mode it carries `ensure()`, which resolves once the first `/auth/me` has settled, and the provider reuses that same request. A deep link to a signed-in page therefore opens the page instead of bouncing to `/sign-in`; a 401 still redirects, with `search.return` set to the path.

Step-up in the browser. `stepUp()` opens `StepUpDialog` (`auth/step-up-dialog.tsx`), rendered once inside the provider; concurrent callers share one dialog and one promise. The dialog calls `stepUpStart()` when it opens, takes the code in `OtpInput` with the email-code length bounds, calls `stepUpVerify()`, and maps failures into `FormErrorSummary` and the field message: `invalid_code`, `invalid_challenge`, 429, `network`, `forbidden` from start (`stepUp.unavailable`) and `error.unknown` for anything else. `withStepUp(stepUp, fn)` (`auth/with-step-up.ts`) runs a mutation and, on 403 `step_up_required`, awaits `stepUp()` and retries once. When the user cancels it throws `StepUpCancelledError`; callers treat that as "declined" (the access dialogs close without an error) and `handleApiError` ignores it. The sample providers resolve `stepUp()` to `true`.

Access screens. `createOrgAdminApi(client, { kind: 'org' | 'ops' })` in `@nestself/api-client` serves both apps; every mutation runs through `withStepUp`, and API codes map to translated copy under `access.errors.*` with `unknown` as the fallback.

- Workspace `/hr/access` (`features/access/`): the nav item and the route need `access.preview` and, because the route sits under `_hr`, `program.overview`. The screen switches to the organization context of the user's single active membership and shows the organization's grants. Assign (`access.grant`) offers organization templates at organization or org-unit scope with the required conditions; revoke (`access.revoke`) asks for a reason; delegate (`access.delegate`) hands a subset of one's own grant to another member; the effective-access panel previews any member.
- Admin `/organizations/:orgId/access` (a tab next to Overview) and `/access` (platform grants): both need `access.preview`, switch to the operations context and use the ops API. The organization page assigns at organization scope only, because the ops API has no org-unit route; org-unit grants are HR's job in the workspace. The platform page assigns `operations` templates at their own scope, has no revoke (there is no platform revoke route) and shows user ids rather than names in api mode. Both pages offer the user-access lookup (`/ops/users/:userId/access`).
- In sample mode the screens read `SAMPLE_GRANTS` and disable every mutation with a note.

- The grant table recomputes each row's status on every render, so a grant created a moment ago shows Active, not Scheduled.

The dialog, the helpers, `route-auth.ts` and the access screens exist once per app, because a shared package would need an install.

Popups inside dialogs. In `@nestself/ui`, Select and Menu popups opened inside a Dialog, AlertDialog or Sheet layer above it: the dialog's portal element sets `--z-popup` to one above `--z-dialog` (`src/lib/layers.ts`). Before 2026-10-24 the popup sat below the dialog and a pointer could not choose an option.

16. Mobile client

`apps/mobile/src/auth/`: `cognito-public-client.ts` talks to Cognito directly (`InitiateAuth` with `USER_AUTH` for email codes, refresh, revoke), `sso.ts` prepares the PKCE authorization-code flow through `expo-auth-session`, `token-store.ts` keeps tokens in `expo-secure-store` (device-only, unlocked access), `jwt.ts` decodes claims, `auth-state.ts` is the reducer and `auth-provider.tsx` orchestrates sign-in, refresh, sign-out and the sample mode. API calls use the bearer mode of the shared client; WebSocket connections fetch a ticket first. Mobile settings come from `EXPO_PUBLIC_COGNITO_*`. The email-code start sends the device locale as `ClientMetadata.locale`. There is no step-up screen yet: a `step_up_required` answer has no UI on mobile, although the API side accepts bearer callers (section 9).

17. Infrastructure and the Cognito rollout

`infra/cdk/lib/auth-stack.ts` defines the user pool `nestself-<stage>` (Essentials plan, email OTP and password first factors, optional TOTP, no self sign-up), three app clients (confidential web with secret, public mobile with PKCE, reserved machine-to-machine), the `CustomMessage` and `PreSignUp` Lambda triggers (`lib/triggers/`), the web client secret and the session encryption key in Secrets Manager, and optional WAF, SES and custom domain for staging and production. Outputs: `UserPoolId`, `WebClientId`, `MobileClientId`, `CognitoDomain`, `CognitoIssuer`, secret ARNs.

The CDK app contains only this stack unless `-c platform=true` is passed, which keeps the rollout to Cognito-only until the web applications ship (`infra/cdk/README.md`, "Rollout order"). To connect the API to a real pool:

```
pnpm --filter @nestself/cdk exec cdk bootstrap aws://<ACCOUNT_ID>/eu-central-1
pnpm --filter @nestself/cdk exec cdk deploy NestSelf-dev-Auth -c stage=dev -c account=
<ACCOUNT_ID>
node infra/cdk/scripts/env-from-outputs.mjs dev >> apps/api/.env     # COGNITO_* and the secret
```

The step-by-step account setup, credentials, IAM permissions and every environment variable are in `CDK-setup.md` at the repository root. Then set `AUTH_MODE=cognito`, `REDIS_URL` and `SESSION_ENCRYPTION_KEY` (from the stack secret) in `apps/api/.env`. Users must exist in the pool: create them through an invitation (the accept flow calls `AdminCreateUser`) or with the AWS console for a first test; the API links them by `sub` on first sign-in only when an `external_identities` row exists, so onboarding goes through invitations. `env-from-outputs.mjs <stage> --mobile` prints the `EXPO_PUBLIC_*` values for the app (`EXPO_PUBLIC_COGNITO_CLIENT_ID` is the name `apps/mobile/src/auth/config.ts` reads).

The API process needs AWS credentials for the Cognito admin calls (`AdminInitiateAuth`, `AdminRespondToAuthChallenge`, `AdminCreateUser`, `AdminDeleteUser`, `AdminDisableUser`, `AdminEnableUser`, `AdminGetUser`, `AdminSetUserPassword`, `AdminUserGlobalSignOut`, `GetTokensFromRefreshToken`, `RevokeToken`, `ListUsers`, `DescribeUserPoolClient`) and, when `SES_FROM_EMAIL` is set, `ses:SendEmail`. In AWS these come from the ECS task role (`infra/cdk/lib/constructs/ecs-task-roles.ts`); locally from the default credential chain (`AWS_PROFILE`). The compute stack's `worker` service runs `node dist/worker/main.js` (section 14) with the worker task role.

17.1 The dev pool as deployed

First deployed 2026-10-24 into a dedicated account. Current coordinates:

Account / region	`634972095709` / `eu-central-1`
Stacks	`CDKToolkit`, `NestSelf-dev-Auth`
User pool	`eu-central-1_g6OGYONQ0`, hosted domain `nestself-dev`
App clients	`nestself-web-dev`, `nestself-mobile-dev`, `nestself-m2m-dev`
Secrets	`nestself-dev/cognito/web-client-secret`, `nestself-dev/api/session-encryption-key`
Triggers	`nestself-dev-cognito-custom-message`, `nestself-dev-cognito-pre-sign-up`

Three things about this stack are easy to get wrong.

The username is the email address. `auth-stack.ts` sets `signInAliases: { email: true }` without `username: true`, which CDK compiles to `UsernameAttributes: ['email']`, not `AliasAttributes: ['email']`. `AdminCreateUser` therefore **requires** an email as `--username` and rejects a plain handle with `Username should be an email`. Cognito then generates the internal username itself, and it is the same UUID as `sub`, so a manually linked `external_identities` row gets that one value in both `subject` and `cognito_username`:

```
aws cognito-idp admin-create-user --user-pool-id eu-central-1_g6OGYONQ0   --username <address> --user-attributes Name=email,Value=<address> Name=email_verified,Value=true   --message-action SUPPRESS
```

`--message-action SUPPRESS` keeps AWS from sending anything at creation time; the first mail is the sign-in code. The `PreSignUp` trigger refuses self sign-up but does not block `AdminCreateUser`.

`USER_ID_FOR_SRP` is absent in the EMAIL_OTP challenge. `AdminInitiateAuth` with `PREFERRED_CHALLENGE: EMAIL_OTP` returns only `CODE_DELIVERY_DELIVERY_MEDIUM` and `CODE_DELIVERY_DESTINATION` in `ChallengeParameters`. `startEmailOtp` reads `ChallengeParameters['USER_ID_FOR_SRP'] ?? input.email`, so the fallback always wins and the email is the username in both the initiate and the respond call. That keeps `SECRET_HASH` consistent across the two calls, which is what the confidential web client requires.

The email code is eight digits, not six. See section 6. Anything that validates or caps the length must use `EMAIL_OTP_MIN_LENGTH` / `EMAIL_OTP_MAX_LENGTH`; a six-digit `maxLength` silently truncates and produces `CodeMismatchException`.

`AWS_PROFILE` in `apps/api/.env` needs the ConfigModule merge. `envSchema` is a plain `z.object`, which strips undeclared keys, and ConfigModule's `validate:` branch assigns only what the function returns back onto `process.env` (its `validationSchema:` branch merges them back, `validate:` does not). Before 2026-10-24 that silently dropped `AWS_PROFILE`, the SDK fell back to the machine's default profile, and the Cognito

calls failed with a cross-account `AccessDenied` that still named the correct pool id. `validateEnv` now returns `{ ...config, ...appEnv }`, which also preserves `AWS_ACCESS_KEY_ID`, `AWS_SESSION_TOKEN`, `HTTPS_PROXY` and `NODE_EXTRA_CA_CERTS`.

Tearing the pool down takes three calls in order, because the stack enables deletion protection and Cognito refuses to drop a pool that still has a domain:

```
aws cognito-idp update-user-pool --user-pool-id <id> --deletion-protection INACTIVE
aws cognito-idp delete-user-pool-domain --user-pool-id <id> --domain <prefix>
aws cognito-idp delete-user-pool --user-pool-id <id>
```

18. Configuration reference

Validated in `apps/api/src/config/env.ts`; documented in `docs/environment.md`.

Variable	Purpose
`AUTH_MODE`	`stub` (default; refused in production) or `cognito`
`DATABASE_URL`, `DATABASE_POOL_MAX`	PostgreSQL connection for the API (a `nestself_app` member in Docker and AWS)
`REDIS_URL`	Required in cognito mode; optional in stub mode (in-memory store)
`JWT_SECRET`, `JWT_EXPIRES_IN`	Stub-mode bearer tokens only; removed after cutover
`COGNITO_REGION`, `COGNITO_USER_POOL_ID`, `COGNITO_WEB_CLIENT_ID`, `COGNITO_WEB_CLIENT_SECRET`, `COGNITO_MOBILE_CLIENT_ID`, `COGNITO_DOMAIN`, `COGNITO_ISSUER`	Pool coordinates; `env-from-outputs.mjs` prints them
`SESSION_ENCRYPTION_KEY`, `SESSION_ENCRYPTION_KEY_PREVIOUS`	32-byte hex keys for token encryption at rest; derived from `JWT_SECRET` in stub mode
`IP_HASH_SALT`	Key for the audit and session IP hashes; defaults to the session encryption key
`SESSION_COOKIE_NAME`, `CSRF_COOKIE_NAME`, `SESSION_COOKIE_INSECURE_DEV`	Cookie names and the localhost switch
`SESSION_LIFETIME_OVERRIDES`	JSON overrides per `population:context`
`MARKETING_URL`, `WORKSPACE_URL`, `ADMIN_URL`, `API_PUBLIC_URL`	Allowed origins for CORS, CSRF and WebSocket handshakes; invitation links
`TRUST_PROXY_HOPS`	Trusted proxy depth for client IP extraction
`SES_FROM_EMAIL`	Enables the SES invitation mailer
`JOBS_TIMEZONE`	Worker process: IANA timezone of the nightly job schedules (default `Europe/Belgrade`)
`FAKE_IDP_FIXED_OTP`	Stub mode: an always-accepted six-digit code
`TEST_DATABASE_URL`	Integration tests; suites create `<name>_schema`, `<name>_auth`, ... databases

Variable	Purpose
`AWS_PROFILE`, `AWS_ACCESS_KEY_ID`, `AWS_SESSION_TOKEN`, `HTTPS_PROXY`, `NODE_EXTRA_CA_CERTS`	Not declared in `envSchema`, but passed through to `process.env` for the AWS SDK and the HTTP stack; see the merge in `validateEnv` and section 17.1

Anything not declared in `envSchema` is still forwarded to `process.env`, because `validateEnv` returns `{ ...config, ...appEnv }`. Removing that spread re-breaks every library that reads `process.env` directly instead of through `ConfigService`.

Redis keys and TTLs are listed in `apps/api/src/redis/redis-keys.ts`.

19. Testing

- Unit tests sit next to the code (`*.test.ts`, `*.spec.ts`) and mock repositories and services. The authorization engine has unit, property and golden-table tests; `step-up-freshness.test.ts`, `grant-rules.test.ts` and `effective-access.test.ts` cover the phase 2 rules.
- Integration suites in `apps/api/test/` boot the real application against a disposable PostgreSQL (`TEST_DATABASE_URL`, one database per suite via `test/db/test-database.ts`), use the fake identity provider and the in-memory store (the test environment ignores `.env` and `REDIS_URL`). Without `TEST_DATABASE_URL` they skip; locally use `TEST_DATABASE_URL=postgresql://nestself@localhost:54329/nestself_test`.

Suite	Covers
`auth.e2e.spec.ts`	Sign-in, CSRF, context switch, profile, sessions, lockout, the three-attempt email code, step-up start and verify, `effectiveActions` in `/auth/me`
`ops-clients.e2e.spec.ts`	`/ops/orgs/:orgId/members` and `/invitations` through the CLIENT assignment
`grants.e2e.spec.ts`	Organization grant administration, delegation bounds and depth, delegatee access and its revocation, approval authorities, the write throttle
`ops-grants.e2e.spec.ts`	Platform grants, ops organization grants, user access
`professional.e2e.spec.ts`	Confidential reads by participant and assigned expert, denials and their audit, step-up on a stale session
`emergency.e2e.spec.ts`	Request, self-approval refusal, approval, record read, expiry before the sweep, sweep, deny, revoke
`members.e2e.spec.ts`, `invitations.e2e.spec.ts`, `org-admin.e2e.spec.ts`, `ws.e2e.spec.ts`	Their areas; members also proves delegatee invalidation on membership end
`health.e2e.spec.ts`, `jobs.e2e.spec.ts`	Health with database and Redis; the maintenance jobs
`db/schema.spec.ts`	Six migrations, partitions, append-only triggers, RLS on all sixteen tenant tables, the seed's stale-grant cleanup
`db/authorization-repository.spec.ts`	Grant repository methods, delegation walks and emergency access queries under RLS

Suite	Covers
`db/backfill-grants.spec.ts`	The legacy role backfill and the `0005` guard

- Browser journeys live in `e2e/auth/` and run with `pnpm e2e:auth` (`playwright.auth.config.ts`): six tests, namely the workspace email-code sign-in, sign-out, guard redirect and wrong code, the staff password and authenticator sign-in, and `hr-access.spec.ts`, in which Ivana opens `/hr/access` by deep link, previews Ana Nikolić's access, delegates `people.invite` to Stefan Marković and finds it in his preview. They need the API in stub mode with `FAKE_IDP_FIXED_OTP=123456`, a seeded database and the web apps in `api` data mode. Every run adds one more delegated grant for Stefan to that database; the journey only requires at least one. TOTP enrolment state is kept in `e2e/.auth-state/`. See `e2e/README.md`, which also explains why a cognito-mode API on port 4000 must be stopped first.
- `pnpm --filter @nestself/api test` runs everything; `pnpm test` runs the whole repository. CI (`.github/workflows/ci.yml`) provides Postgres and Redis service containers.

20. Recipes

Add a protected route. Put the handler in the right controller, pick the action from `ACTIONS`, and decorate with `@Authorize(ACTIONS['x.y'], orgResourceFromContext('thing'))` (or `operationsResource`, or `operationsOrgResource` under `/ops/orgs/:orgId`). Step-up follows from the action's class; nothing to add. Access-administration writes also carry `@Throttle(WRITE_THROTTLE)`. When the decision needs row data (owner, case, confidentiality), mark the route `@Authenticated()`, load the row in the service and call `AuthorizationService.require()` before returning anything. Read the body with `@Body(new ZodValidationPipe(Schema))`; schemas live in `packages/contracts/src/org-admin.ts`. Do writes inside `dbService.withOrgScope(orgId, tx => repo.method(..., tx))`, audit through `AuditWriter`, and invalidate caches that your change affects (`PrincipalLoader.invalidateUser`, or `org_tree:{orgId}` for tree changes). The default-deny test tells you if you forgot the decorator; add an e2e case to the matching suite.

Add an action or template. Extend `ACTIONS` in `packages/contracts/src/actions.ts` (and `CONFIDENTIAL_ACTIONS` or `STEP_UP_CLASS_BY_ACTION` where relevant), add it to the template in `templates.ts`, add golden-table tuples in `apps/api/src/authz/golden-table.json`, and re-run the seed so sample grants pick it up.

Add a table or column. Edit `apps/api/src/db/schema/*.ts`, run `db:generate`, review the SQL in `apps/api/drizzle/`, add a `pgPolicy` with `tenantPredicate()` if the table has an organization column, run `db:migrate`, and extend the matching repository. Partitions, triggers and roles go in a `--custom` migration.

Add an audit action. Append to `AUDIT_ACTIONS` in `apps/api/src/audit/audit-events.ts` and map its category in `resolveCategory`; the spec file enumerates them.

Revoke someone's access programmatically. Write the audit event first, then `AccessRevocationService.revokeAllAccess(userId, { sessionsForOrgId?, orgIds? })`.

Call a sensitive action from a web screen. Wrap the mutation in `withStepUp(useAuth().stepUp, () => api.call(...))`, map its `ApiError` codes to translated copy, and treat `StepUpCancelledError` as the user declining (close or leave the form without an error).

Debug a denial. Call `explain(principal, action, resource, ctx)` from `src/authz/explain.ts` in a test, or read the `access.denied` audit row: `details.reason` carries the engine's denial reason.

21. Known gaps and next steps

Phase 2 (`docs/superpowers/plans/2026-10-24-auth-phase-2.md`) is done; `docs/tasks/auth/phase-2-readiness.md` has the status of every T-2.x task. What remains open, grouped by kind.

Owner decisions

- **Who administers grants inside an organization.** No organization template holds `access.grant` or `access.revoke` (section 11.1). Today NestSelf staff with `platform_owner` create and revoke organization grants through `/ops/orgs/:orgId/grants`, and employer owners preview and delegate. In development, the assign and revoke dialogs of `/hr/access` need a hand-made grant. Giving the actions to `employer_owner` or `hr_admin` is a template change plus golden rows.
- **Authenticator step-up for the `emergency` class.** Every class steps up with an email code (section 9); the strategy asks for an authenticator for `emergency`. Doing that means a password-plus-authenticator step-up or passkeys.
- **`/hr/access` under `_hr`.** The route also needs `program.overview`, so an employer owner without `hr_admin` cannot reach it. Moving it out of `_hr` is a small change once the template question above is settled.
- The `presenter` template (GAP-H02), retention periods (L-02, L-03), who may approve emergency access and whether a second approver is required (default: `platform_owner`, one approver), and the staging date. These carry over from `phase-2-readiness.md` section 4.

Blocker before any conversation write path

- `conversations.case_id` and `intake_records.case_id` are free text with no organization binding, and the assignment match compares `targetId` only. Before any route creates conversations or intakes, add a `cases(id, org_id)` table with foreign keys from both tables, or bind assignments to an organization. `schema/professional.ts` carries a `TODO(phase-2-readiness)` at both columns.

Not built in phase 2

- **Mobile step-up UI.** The API accepts bearer callers; the app has no screen for `step_up_required`.
- **T-2.8** security baseline, SCPs and the production account (waits for staging); **T-2.9 and T-2.11** file delivery and export authorization (nothing to authorize yet); **T-2.12** the weekly Cognito user export.
- **Remaining jobs:** the retention sweeper (needs L-02 and L-03), the audit export to S3 with Object Lock (AUDIT-R-06), the SSO certificate-expiry check (SSO-R-14). Each is a method on `MaintenanceJobsService` plus a schedule entry.
- **Enterprise SSO** (phase 3): connection management, home-realm discovery and the callback are stubs. Federated users get 403 `forbidden` on step-up start until then.
- **Community feature retirement:** `posts`, `polls`, `poll_options`, `poll_votes`, `legacy_teams` and `memberships.team_id` are tenant-isolated but deprecated; the contracts' `OrgRole` and `PlatformRole` remain for sample mode.
- **Compliance track** before the first real employee signs in: privacy notices, processing agreement, breach procedure, data-subject-rights endpoints (T-C.4).

To verify against the live pool

- Whether Cognito answers the third `CodeMismatchException` within one `Session` with `NotAuthorizedException` instead. The fake provider keeps the session alive for all three tries. If Cognito ends it sooner, the API treats that as any other provider error and ends the challenge, which is safe but gives the user fewer retries than the screens suggest.

Known limitations from the phase 2 reviews

- **Throttling.** Access-administration writes are limited to 10 per minute per route and client IP, not 10 per session across routes as AUTHZ-R-14 asks. Wrong step-up codes are bounded by the 5-per-minute route throttle and three tries per challenge only: there is no per-session `throttle:step_up` tracker and no `SignInThrottle` lockout for step-up. A provider-originated 429 shows different copy from the lock message.
- **Step-up edges.** Start answers a generic 403 `forbidden` for accounts without a native identity (a dedicated `step_up_unavailable` code would read better); a bearer principal without a token family is asked to step up but cannot start; an attempt to use another user's challenge is refused but not audited. The dialog has no resend cooldown or in-flight guard and keeps Cancel enabled during verify.
- **Audit outside the transaction.** `AuditWriter` writes through its own connection, so outside strict mode a grant or emergency change can commit while its audit row failed (the writer logs it). A writer that joins the caller's transaction is the follow-up. The emergency sweeper has the same shape and stops its loop on the first error.
- **Grants and delegation.** Delegatee invalidation runs after the commit, so a failure leaves caches stale for up to the grants TTL (about a minute). A PATCH that shortens a parent's validity does not re-check its children (the engine denies them once the parent expires), and a PATCH that changes both conditions and validity checks children against the stored validity. Repeated identical delegations are accepted and self-delegation is not refused. `grants.service.ts` is about 580 lines and should split platform grants and subject access into their own services. `POST /ops/grants` does not check the subject's population. An approval-authority PATCH cannot clear `validUntil` or `maxAmountMinor`.
- **Invitations.** `InvitationsService` accepts any template key, staff templates included, on both `/orgs` and `/ops` routes; restricting it to organization templates is a follow-up. The two route families return slightly different 400 bodies.
- **Confidential and emergency reads.** A missing id answers 404 before authorization and an existing denied one 403, so members and staff can tell whether an id exists. Pending emergency requests never lapse, the record list is ordered by `grantedAt`, which approval overwrites, and `listMessages` is unbounded.
- **Backfill.** Grant ids for a user's first organization still lack the organization; the HR admin chosen as `grantedByUserId` depends on a creation-time tie-break; an expert without approved credentials gets a grant without category conditions; the `0005` guard ignores `revoked_at` and validity.
- **Web.** Member pickers load the first 100 active members; spending ceilings assume two-decimal currencies; the user-access lookup cannot be re-run with the same id; 4xx alerts on the access screens arrive only after the query client's retries (about 7 seconds). A stalled `/auth/me` keeps a deep-linked page waiting with no timeout, and a 500 or network failure on `/auth/me` looks like being signed out (only a console warning). The codes `self_approval_denied` and `emergency_not_active` have no translated copy until an emergency screen exists. The access dialogs have smaller form-polish items (revoke errors pinned to the reason field, focus on a disabled confirm).
- **Local job tooling.** `worker:dev` and `job:run` fail at boot under `tsx` (no decorator metadata, section 14); only the compiled worker runs. This predates phase 2.

- **Health.** The Redis indicator detects memory mode with `instanceof`, and its 3-second timeout path is untested.
- **Tests.** Several API e2e suites share one session across cases or depend on case order, and the `ageSession` and `extractSessionId` helpers are duplicated across specs.
- **Email-code locale.** Sign-in and resend send the screen's language (section 6), but step-up start and the invitation-acceptance code still call `startEmailOtp` without one, and a `custom:locale` attribute on the pool user always wins over `ClientMetadata` in the trigger.
- **Mobile authentication strength** is reported as `email_otp` without a second factor because that is the only first factor the mobile client allows; it must be revisited when mobile gains passkeys or SSO.
- **The email code length is AWS's, not ours.** Cognito's managed `EMAIL_OTP` challenge always sends eight digits: there is no pool setting, no CDK property and no CLI parameter for it (verified 2026-10-24 against `describe-user-pool`, `update-user-pool` and `UserPoolProps`). Shortening it to four or six means leaving the managed flow for `CUSTOM_AUTH` with Define, Create and Verify Auth Challenge triggers, where the code, its delivery through SES, its expiry and its attempt counter all become ours. That is a deliberate trade: shorter codes are friendlier to type and materially weaker (four digits is 10,000 combinations), and the throttle would have to tighten to compensate. Not started.