Fundamentos de Java

Parte 9

Presenta

Alan Badillo Salas

Marzo 2023

```
public static void main(String[] args) {

    File myFile = new File("C:\\not_exists.txt");

}
```


File myFile = new File("C:\\not_exists.txt");
Add import for java.io.File
Create class "File" in package learn (Source Packages)
Create class "File" with construct java.lang.String)" in package learn (Source Packages)
Create class "File" in learn.LearnErr ndling_001
Create class "File" in learn.LearnErrorHandling_001
Remove unused "myFile"
Split into declaration and assignment
8
9
0
1

```java
import java.io.File;

public class LearnErrorHandling_001 {

    public static void main(String[] args) {

        File myFile = new File(pathname:"C:\\not_exists.txt");

    }

}
```


import java.io.File;
public class LearnErrorHandling_001 {
public static void main(String[] args) {
File myFile = new File(pathname:"C:\\not_exists.txt");
Scanner scanner = new Scanner(file);
Add import for java.util.Scanner
Create class "Scanner" in package learn
ce Packages)
Create class "Scanner" in learn.Learn
dling_001
Remove unused "scanner"
Split into declaration and assignment
}

```java
import java.io.File;
import java.util.Scanner;

public class LearnErrorHandling_001 {

    public static void main(String[] args) {

        File myFile = new File(pathname:"C:\\not_exists.txt");

        Scanner scanner = new Scanner(source: file);

    }

}
```

```
public static void main(String[] args) {

    File myFile = new File(pathname:"C:\\not_

    Scanner scanner = new Scanner(source: file);

}
```

cannot find symbol
  symbol: variable file
  location: class LearnErrorHandling_001

Explict type can be replaced with 'var'

(Alt-Enter shows hints)


public static void main(String[] args) {
File myFile = new File(pathname:"C:\\not
Scanner scanner = new Scanner(source: myFile);
}
unreported exception FileNotFoundException; must be caught or declared to be thrown
Explict type can be replaced with 'var'

(Alt-Enter shows hints)


8 public static void main(String[] args) {
9
10 File myFile = new File(pathname:"C:\\not_exists.txt");
11
Scanner scanner = new Scanner(source: myFile);
Add throws clause for java.io.FileNotFoundException
Surround Statement with try-catch
Surround Block with try-catch
Remove unused "scanner"
Replace explicit type with var
Split into declaration and assignment
15
16 }
17


Scanner scanner
Add throws clause for java.io.FileNotFoundException
Surround Statement with try-catch
Surround Block with try-catch
Remove unused "scanner"
Replace explicit type with var
Split into declaration and assignment
}
3
4
5
6
7

```
public static void main(String[] args) throws FileNotFoundException {

    File myFile = new File(pathname:"C:\\not_exists.txt");

    Scanner scanner = new Scanner(source: myFile);

}
```

UNHANDLED ERROR REPORTED

```
public static void main(String[] args) throws FileNotFoundException {

    File myFile = new File(pathname:"C:\\not_exists.txt");

    Scanner scanner = new Sc                                    myFile);

}
```



```
run:
Exception in thread "main" java.io.FileNotFoundException: C:\not_exists.txt (El sistema no puede encontrar el archivo especificado)
        at java.base/java.io.FileInputStream.open0(Native Method)
        at java.base/java.io.FileInputStream.open(FileInputStream.java:219)
        at java.base/java.io.FileInputStream.<init>(FileInputStream.java:158)
        at java.base/java.util.Scanner.<init>(Scanner.java:641)
        at learn.LearnErrorHandling_001.main(LearnErrorHandling_001.java:13)
C:\Users\drago\AppData\Local\NetBeans\Cache\17\executor-snippets\run.xml:111: The following error occurred while executing this line:
C:\Users\drago\AppData\Local\NetBeans\Cache\17\executor-snippets\run.xml:68: Java returned: 1
BUILD FAILED (total time: 0 seconds)
```

```
public static void main(String[] args) throws FileNotFoundException {

    File myFile = new File(pathname:"C:\\not_exists.txt");

    Scanner scanner = new Scanner(source: myFile);

}
```


9 public static void main(String[] args) {
10
11 File myFile = new File(pathname:"C:\\not_exists.txt");
12
Scanner scanner = new Scanner(source: myFile);
14
15
16
17 }
18
Add throws clause for java.io.FileNotFoundException
Surround Statement with try-catch
Surround Block with try-catch
Remove unused "scanner"

```java
import java.io.File;
import java.io.FileNotFoundException;
import java.util.Scanner;
import java.util.logging.Level;
import java.util.logging.Logger;

public class LearnErrorHandling_001 {

    public static void main(String[] args) {

        File myFile = new File(pathname:"C:\\not_exists.txt");

        try {
            Scanner scanner = new Scanner(source: myFile);
        } catch (FileNotFoundException ex) {
            Logger.getLogger(name: LearnErrorHandling_001.class.getName()).log(level:
        }

    }

}
```

```
public static void main(String[] args) {

    File myFile = new File(pathname:"C:\\not_exists.txt");

    try {
        Scanner scanner = new Scanner(source: myFile);
    } catch (FileNotFoundException ex) {
        System.out.println(x:"FILE NOT FOUND!!!!");
    }

}
```

```
run:
FILE NOT FOUND!!!!
BUILD SUCCESSFUL (total time: 0 seconds)
```

```java
public static void main(String[] args) {

    int a, b;

    Scanner scanner = new Scanner(source: System.in);

    System.out.print(s:"Give me A: ");
    a = scanner.nextInt();

    System.out.print(s:"Give me B: ");
    b = scanner.nextInt();

    int result = a / b;

    System.out.printf(format: "A / B = %d %n", args: result);

}
```


run:
Give me A: 15
Give me B: 3
A / B = 5
BUILD SUCCESSFUL (total time: 6 seconds)


run:
Give me A: 15
Give me B: 0

```
run:
Give me A: 15
Give me B: 0
Exception in thread "main" java.lang.ArithmeticException: / by zero
        at learn.LearnErrorHandling_002.main(LearnErrorHandling_002.ja
C:\Users\drago\AppData\Local\NetBeans\Cache\17\executor-snippets\run.x
C:\Users\drago\AppData\Local\NetBeans\Cache\17\executor-snippets\run.x
BUILD FAILED (total time: 25 seconds)
```

```java
public static void main(String[] args) {

    int a, b;

    Scanner scanner = new Scanner(source: System.in);

    System.out.print(s:"Give me A: ");
    a = scanner.nextInt();

    System.out.print(s:"Give me B: ");
    b = scanner.nextInt();

    try {
        int result = a / b;
        System.out.printf(format: "A / B = %d %n", args: result);
    } catch (ArithmeticException ex) {
        System.out.println(x:"DIVISION ERROR!!!!");
    }

}
```

```
run:
Give me A: 10
Give me B: 0
DIVISION ERROR!!!!
BUILD SUCCESSFUL (total time: 5 seconds)
```

```
try {
    int result = a / b;
    System.out.printf(format: "A / B = %d %n", args: result);
} catch (ArithmeticException ex) {
    System.out.println(x:"DIVISION ERROR!!!!");
} catch (Exception ex) {
    System.out.println(x:"ERROR!!!!");
    System.out.println(x:ex.getMessage());
}
```