RPKI Engine

1.0

Generated by Doxygen 1.6.3

Thu Apr 1 21:05:48 2010

Contents

1 RPKI Engine Reference Manual **1**

2 Further Reading **1**

3 Installation Guide **2**

4 Operation Guide **5**

4.1 Common Options 6

4.2 rpkid.py 7

4.3 pubd.py 8

4.4 rootd.py 9

4.5 irdbd.py 10

4.6 irbe_cli.py 11

4.7 cross_certify.py 14

4.8 cronjob.py 14

4.9 testbed.py: 15

4.10 testpoke.py 17

5 Left-right protocol **18**

5.1 Terminology 19

5.2 initiated by the IRBE 19

5.2.1 <self/> object 19

5.2.2 <bsc/> object 21

5.2.3 <parent/> object 22

5.2.4 <child/> object 23

5.2.5 <repository/> object 24

5.2.6 <route_origin/> object 25

5.3 Operations initiated by the RPKI engine 26

5.3.1 <list_resources/> messages 26

5.4 Error handling 27

6 Publication protocol **28**

6.1 Terminology 28
6.2 Publication control subprotocol 29
6.2.1 <config/> object 29
6.2.2 <client/> object 29
6.3 Publication subprotocol 30
6.3.1 <certificate/> object 30
6.3.2 <crl/> object 30
6.3.3 <manifest/> object 30
6.3.4 <roa/> object 30
6.4 Error handling 31
6.5 Additional access control considerations. 31

7 Namespace Documentation 32
7.1 Package irbe_cli 32
7.1.1 Detailed Description 34
7.1.2 Function Documentation 34
7.1.3 Variable Documentation 34
7.2 Package irdbd 37
7.2.1 Detailed Description 37
7.2.2 Function Documentation 38
7.2.3 Variable Documentation 38
7.3 Package pubd 41
7.3.1 Detailed Description 41
7.3.2 Function Documentation 42
7.3.3 Variable Documentation 42
7.4 Package rootd 42
7.4.1 Detailed Description 44
7.4.2 Function Documentation 45
7.4.3 Variable Documentation 46
7.5 Package rpki 50
7.6 Package rpki.async 51

7.6.1 Detailed Description 51
7.6.2 Function Documentation 52
7.6.3 Variable Documentation 53
7.7 Package rpki.cli 53
7.7.1 Detailed Description 53
7.7.2 Function Documentation 54
7.7.3 Variable Documentation 54
7.8 Package rpki.config 54
7.8.1 Detailed Description 55
7.9 Package rpki.exceptions 55
7.9.1 Detailed Description 57
7.10 Package rpki.https 57
7.10.1 Detailed Description 58
7.10.2 Function Documentation 59
7.10.3 Variable Documentation 59
7.11 Package rpki.ipaddrs 61
7.11.1 Detailed Description 61
7.12 Package rpki.left_right 62
7.12.1 Detailed Description 62
7.12.2 Variable Documentation 63
7.13 Package rpki.log 63
7.13.1 Detailed Description 64
7.13.2 Function Documentation 65
7.13.3 Variable Documentation 65
7.14 Package rpki.manifest 67
7.14.1 Detailed Description 67
7.15 Package rpki.oids 67
7.15.1 Detailed Description 68
7.15.2 Variable Documentation 68
7.16 Package rpki.publication 69
7.16.1 Detailed Description 69

7.17 Package rpki.relaxng 70
7.17.1 Variable Documentation 70
7.18 Package rpki.resource_set 71
7.18.1 Detailed Description 72
7.18.2 Function Documentation 72
7.18.3 Variable Documentation 73
7.19 Package rpki.roa 74
7.19.1 Detailed Description 74
7.20 Package rpki.rpki_engine 75
7.20.1 Detailed Description 75
7.21 Package rpki.sql 75
7.21.1 Detailed Description 76
7.22 Package rpki.sundial 76
7.22.1 Detailed Description 77
7.22.2 Function Documentation 77
7.23 Package rpki.up_down 78
7.23.1 Detailed Description 79
7.23.2 Variable Documentation 79
7.24 Package rpki.x509 80
7.24.1 Detailed Description 80
7.24.2 Function Documentation 81
7.25 Package rpki.xml_utils 82
7.25.1 Detailed Description 82
7.26 Package rpkid 82
7.26.1 Detailed Description 83
7.26.2 Function Documentation 83
7.26.3 Variable Documentation 84

8 Class Documentation 84

8.1 async_chat Class Reference 84
8.2 dispatcher Class Reference 84

8.3 Cmd Class Reference 84
8.4 Exception Class Reference 84
8.5 irbe_cli.bsc_elt Class Reference 85
8.5.1 Detailed Description 87
8.5.2 Member Function Documentation 87
8.5.3 Member Data Documentation 88
8.6 irbe_cli.certificate_elt Class Reference 88
8.6.1 Detailed Description 89
8.7 irbe_cli.child_elt Class Reference 90
8.7.1 Detailed Description 92
8.8 irbe_cli.client_elt Class Reference 92
8.8.1 Detailed Description 94
8.9 irbe_cli.cmd_elt_mixin Class Reference 94
8.9.1 Detailed Description 96
8.9.2 Member Function Documentation 96
8.9.3 Member Data Documentation 98
8.10 irbe_cli.cmd_msg_mixin Class Reference 99
8.10.1 Detailed Description 100
8.10.2 Member Function Documentation 100
8.11 irbe_cli.config_elt Class Reference 100
8.11.1 Detailed Description 102
8.11.2 Member Function Documentation 102
8.11.3 Member Data Documentation 102
8.12 irbe_cli.crl_elt Class Reference 102
8.12.1 Detailed Description 103
8.13 irbe_cli.left_right_cms_msg Class Reference 104
8.13.1 Detailed Description 105
8.13.2 Member Data Documentation 105
8.14 irbe_cli.left_right_msg Class Reference 105
8.14.1 Detailed Description 107
8.14.2 Member Data Documentation 107

8.15 irbe_cli.left_right_proto Class Reference 107
8.15.1 Detailed Description 108
8.15.2 Member Data Documentation 108
8.16 irbe_cli.left_right_sax_handler Class Reference 109
8.16.1 Detailed Description 110
8.16.2 Member Data Documentation 110
8.17 irbe_cli.list_published_objects_elt Class Reference 110
8.17.1 Detailed Description 112
8.17.2 Member Data Documentation 112
8.18 irbe_cli.list_received_resources_elt Class Reference 112
8.18.1 Detailed Description 114
8.18.2 Member Data Documentation 114
8.19 irbe_cli.manifest_elt Class Reference 114
8.19.1 Detailed Description 115
8.20 irbe_cli.parent_elt Class Reference 116
8.20.1 Detailed Description 118
8.21 irbe_cli.publication_cms_msg Class Reference 118
8.21.1 Detailed Description 119
8.21.2 Member Data Documentation 120
8.22 irbe_cli.publication_msg Class Reference 120
8.22.1 Detailed Description 122
8.22.2 Member Data Documentation 122
8.23 irbe_cli.publication_proto Class Reference 122
8.23.1 Detailed Description 123
8.23.2 Member Data Documentation 123
8.24 irbe_cli.publication_sax_handler Class Reference 124
8.24.1 Detailed Description 125
8.24.2 Member Data Documentation 125
8.25 irbe_cli.reply_elt_mixin Class Reference 125
8.25.1 Detailed Description 126
8.25.2 Member Function Documentation 126

8.25.3 Member Data Documentation 127
8.26 irbe_cli.report_error_elt Class Reference 127
8.26.1 Detailed Description 128
8.27 irbe_cli.repository_elt Class Reference 128
8.27.1 Detailed Description 130
8.28 irbe_cli.roa_elt Class Reference 130
8.28.1 Detailed Description 131
8.29 irbe_cli.self_elt Class Reference 132
8.29.1 Detailed Description 134
8.30 irbe_cli.UsageWrapper Class Reference 134
8.30.1 Detailed Description 134
8.30.2 Member Function Documentation 135
8.31 long Class Reference 135
8.32 object Class Reference 135
8.33 pubd.pubd_context Class Reference 135
8.33.1 Detailed Description 137
8.33.2 Member Function Documentation 137
8.33.3 Member Data Documentation 138
8.34 datetime Class Reference 140
8.35 timedelta Class Reference 140
8.36 rootd.cms_msg Class Reference 140
8.36.1 Detailed Description 141
8.36.2 Member Data Documentation 142
8.37 rootd.issue_pdu Class Reference 142
8.37.1 Detailed Description 143
8.37.2 Member Function Documentation 144
8.38 rootd.list_pdu Class Reference 144
8.38.1 Detailed Description 145
8.38.2 Member Function Documentation 146
8.39 rootd.message_pdu Class Reference 146
8.39.1 Detailed Description 148

8.39.2 Member Function Documentation 148
8.39.3 Member Data Documentation 148
8.40 rootd.revoke_pdu Class Reference 149
8.40.1 Detailed Description 150
8.40.2 Member Function Documentation 150
8.41 rootd.sax_handler Class Reference 150
8.41.1 Detailed Description 151
8.41.2 Member Data Documentation 152
8.42 rpki.async.gc_summary Class Reference 152
8.42.1 Detailed Description 153
8.42.2 Member Function Documentation 153
8.42.3 Member Data Documentation 153
8.43 rpki.async.iterator Class Reference 154
8.43.1 Detailed Description 155
8.43.2 Member Function Documentation 155
8.43.3 Member Data Documentation 156
8.44 rpki.async.sync_wrapper Class Reference 157
8.44.1 Detailed Description 159
8.44.2 Member Function Documentation 159
8.44.3 Member Data Documentation 159
8.45 rpki.async.timer Class Reference 160
8.45.1 Detailed Description 162
8.45.2 Member Function Documentation 163
8.45.3 Member Data Documentation 165
8.46 rpki.cli.Cmd Class Reference 166
8.46.1 Detailed Description 168
8.46.2 Member Function Documentation 168
8.46.3 Member Data Documentation 170
8.47 rpki.config.parser Class Reference 170
8.47.1 Detailed Description 172
8.47.2 Member Function Documentation 172

8.47.3 Member Data Documentation 174
8.48 rpki.exceptions.BadClassNameSyntax Class Reference 175
8.48.1 Detailed Description 176
8.49 rpki.exceptions.BadClientURL Class Reference 176
8.49.1 Detailed Description 177
8.50 rpki.exceptions.BadContactURL Class Reference 177
8.50.1 Detailed Description 178
8.51 rpki.exceptions.BadExtension Class Reference 178
8.51.1 Detailed Description 179
8.52 rpki.exceptions.BadIRDBReply Class Reference 179
8.52.1 Detailed Description 180
8.53 rpki.exceptions.BadIssueResponse Class Reference 180
8.53.1 Detailed Description 181
8.54 rpki.exceptions.BadPKCS10 Class Reference 181
8.54.1 Detailed Description 182
8.55 rpki.exceptions.BadPublicationReply Class Reference 182
8.55.1 Detailed Description 183
8.56 rpki.exceptions.BadQuery Class Reference 183
8.56.1 Detailed Description 184
8.57 rpki.exceptions.BadSender Class Reference 184
8.57.1 Detailed Description 185
8.58 rpki.exceptions.BadStatusCode Class Reference 185
8.58.1 Detailed Description 186
8.59 rpki.exceptions.BadURISyntax Class Reference 186
8.59.1 Detailed Description 187
8.60 rpki.exceptions.BSCNotFound Class Reference 187
8.60.1 Detailed Description 188
8.61 rpki.exceptions.BSCNotReady Class Reference 188
8.61.1 Detailed Description 189
8.62 rpki.exceptions.ChildNotFound Class Reference 189
8.62.1 Detailed Description 190

8.63 rpki.exceptions.ClassNameMismatch Class Reference 190
8.63.1 Detailed Description 191
8.64 rpki.exceptions.ClassNameUnknown Class Reference 191
8.64.1 Detailed Description 192
8.65 rpki.exceptions.ClientNotFound Class Reference 192
8.65.1 Detailed Description 193
8.66 rpki.exceptions.CMSContentNotSet Class Reference 193
8.66.1 Detailed Description 194
8.67 rpki.exceptions.CMSCRLNotSet Class Reference 195
8.67.1 Detailed Description 195
8.68 rpki.exceptions.CMSVerificationFailed Class Reference 196
8.68.1 Detailed Description 196
8.69 rpki.exceptions.DBConsistancyError Class Reference 197
8.69.1 Detailed Description 197
8.70 rpki.exceptions.DERObjectConversionError Class Reference 198
8.70.1 Detailed Description 198
8.71 rpki.exceptions.DuplicateObject Class Reference 199
8.71.1 Detailed Description 199
8.72 rpki.exceptions.EmptyPEM Class Reference 200
8.72.1 Detailed Description 200
8.73 rpki.exceptions.EmptyROAPrefixList Class Reference 201
8.73.1 Detailed Description 201
8.74 rpki.exceptions.ForbiddenURI Class Reference 202
8.74.1 Detailed Description 202
8.75 rpki.exceptions.HandleTranslationError Class Reference 203
8.75.1 Detailed Description 203
8.76 rpki.exceptions.HTTPRequestFailed Class Reference 204
8.76.1 Detailed Description 204
8.77 rpki.exceptions.HTTPSBadVersion Class Reference 205
8.77.1 Detailed Description 205
8.78 rpki.exceptions.HTTPSClientAborted Class Reference 206

8.78.1 Detailed Description 206
8.79 rpki.exceptions.HTTPSUnexpectedState Class Reference 207
8.79.1 Detailed Description 207
8.80 rpki.exceptions.MissingCMSCRL Class Reference 208
8.80.1 Detailed Description 208
8.81 rpki.exceptions.MissingCMSEEcert Class Reference 209
8.81.1 Detailed Description 209
8.82 rpki.exceptions.MultipleTLSEECert Class Reference 210
8.82.1 Detailed Description 211
8.83 rpki.exceptions.MustBePrefix Class Reference 211
8.83.1 Detailed Description 212
8.84 rpki.exceptions.NoActiveCA Class Reference 212
8.84.1 Detailed Description 213
8.85 rpki.exceptions.NoCoveringCertForROA Class Reference 213
8.85.1 Detailed Description 214
8.86 rpki.exceptions.NoObjectAtURI Class Reference 214
8.86.1 Detailed Description 215
8.87 rpki.exceptions.NotACertificateChain Class Reference 215
8.87.1 Detailed Description 216
8.88 rpki.exceptions.NotFound Class Reference 216
8.88.1 Detailed Description 217
8.89 rpki.exceptions.NotImplementedYet Class Reference 217
8.89.1 Detailed Description 218
8.90 rpki.exceptions.NotInDatabase Class Reference 218
8.90.1 Detailed Description 219
8.91 rpki.exceptions.ReceivedTLSCACert Class Reference 219
8.91.1 Detailed Description 220
8.92 rpki.exceptions.RPKI_Exception Class Reference 221
8.92.1 Detailed Description 222
8.93 rpki.exceptions.ServerShuttingDown Class Reference 222
8.93.1 Detailed Description 223

8.94 rpki.exceptions.SKIMismatch Class Reference 223
8.94.1 Detailed Description 224
8.95 rpki.exceptions.SubprocessError Class Reference 224
8.95.1 Detailed Description 225
8.96 rpki.exceptions.TLSValidationError Class Reference 225
8.96.1 Detailed Description 226
8.97 rpki.exceptions.UnexpectedCMSCerts Class Reference 227
8.97.1 Detailed Description 227
8.98 rpki.exceptions.UnexpectedCMSCRLs Class Reference 228
8.98.1 Detailed Description 228
8.99 rpki.exceptions.UnparsableCMSDER Class Reference 229
8.99.1 Detailed Description 229
8.100 rpki.exceptions.UpstreamError Class Reference 230
8.100.1 Detailed Description 230
8.101 rpki.exceptions.WrongEContentType Class Reference 231
8.101.1 Detailed Description 231
8.102 rpki.https.caller Class Reference 232
8.102.1 Detailed Description 233
8.102.2 Member Function Documentation 233
8.102.3 Member Data Documentation 233
8.103 rpki.https.http_client Class Reference 234
8.103.1 Detailed Description 236
8.103.2 Member Function Documentation 236
8.103.3 Member Data Documentation 238
8.104 rpki.https.http_listener Class Reference 240
8.104.1 Detailed Description 242
8.104.2 Member Function Documentation 242
8.104.3 Member Data Documentation 242
8.105 rpki.https.http_message Class Reference 243
8.105.1 Detailed Description 245
8.105.2 Member Function Documentation 245

8.105.3 Member Data Documentation 246
8.106 rpki.https.http_queue Class Reference 247
8.106.1 Detailed Description 248
8.106.2 Member Function Documentation 248
8.106.3 Member Data Documentation 249
8.107 rpki.https.http_request Class Reference 250
8.107.1 Detailed Description 252
8.107.2 Member Function Documentation 252
8.107.3 Member Data Documentation 252
8.108 rpki.https.http_response Class Reference 253
8.108.1 Detailed Description 255
8.108.2 Member Function Documentation 255
8.108.3 Member Data Documentation 255
8.109 rpki.https.http_server Class Reference 256
8.109.1 Detailed Description 257
8.109.2 Member Function Documentation 257
8.109.3 Member Data Documentation 258
8.110 rpki.https.http_stream Class Reference 260
8.110.1 Detailed Description 261
8.110.2 Member Function Documentation 262
8.110.3 Member Data Documentation 265
8.111 rpki.ipaddrs.v4addr Class Reference 266
8.111.1 Detailed Description 267
8.111.2 Member Function Documentation 268
8.111.3 Member Data Documentation 268
8.112 rpki.ipaddrs.v6addr Class Reference 269
8.112.1 Detailed Description 270
8.112.2 Member Function Documentation 270
8.112.3 Member Data Documentation 271
8.113 rpki.left_right.bsc_elt Class Reference 271
8.113.1 Detailed Description 273

8.113.2 Member Function Documentation 273
8.113.3 Member Data Documentation 274
8.114 rpki.left_right.child_elt Class Reference 276
8.114.1 Detailed Description 278
8.114.2 Member Function Documentation 278
8.114.3 Member Data Documentation 280
8.115 rpki.left_right.cms_msg Class Reference 281
8.115.1 Detailed Description 283
8.115.2 Member Data Documentation 283
8.116 rpki.left_right.data_elt Class Reference 283
8.116.1 Detailed Description 285
8.116.2 Member Function Documentation 285
8.116.3 Member Data Documentation 287
8.117 rpki.left_right.left_right_namespace Class Reference 287
8.117.1 Detailed Description 288
8.117.2 Member Data Documentation 288
8.118 rpki.left_right.list_published_objects_elt Class Reference 289
8.118.1 Detailed Description 291
8.118.2 Member Function Documentation 291
8.118.3 Member Data Documentation 292
8.119 rpki.left_right.list_received_resources_elt Class Reference 292
8.119.1 Detailed Description 294
8.119.2 Member Function Documentation 294
8.119.3 Member Data Documentation 294
8.120 rpki.left_right.list_resources_elt Class Reference 295
8.120.1 Detailed Description 297
8.120.2 Member Function Documentation 297
8.120.3 Member Data Documentation 298
8.121 rpki.left_right.list_roa_requests_elt Class Reference 299
8.121.1 Detailed Description 300
8.121.2 Member Function Documentation 300

8.121.3 Member Data Documentation 300
8.122 rpki.left_right.msg Class Reference 301
8.122.1 Detailed Description 303
8.122.2 Member Function Documentation 303
8.122.3 Member Data Documentation 303
8.123 rpki.left_right.parent_elt Class Reference 304
8.123.1 Detailed Description 306
8.123.2 Member Function Documentation 306
8.123.3 Member Data Documentation 308
8.124 rpki.left_right.report_error_elt Class Reference 310
8.124.1 Detailed Description 312
8.124.2 Member Function Documentation 312
8.124.3 Member Data Documentation 313
8.125 rpki.left_right.repository_elt Class Reference 314
8.125.1 Detailed Description 316
8.125.2 Member Function Documentation 316
8.125.3 Member Data Documentation 317
8.126 rpki.left_right.sax_handler Class Reference 318
8.126.1 Detailed Description 320
8.126.2 Member Data Documentation 320
8.127 rpki.left_right.self_elt Class Reference 320
8.127.1 Detailed Description 323
8.127.2 Member Function Documentation 323
8.127.3 Member Data Documentation 327
8.128 rpki.log.logger Class Reference 329
8.128.1 Detailed Description 330
8.128.2 Member Function Documentation 330
8.128.3 Member Data Documentation 330
8.129 rpki.manifest.FileAndHash Class Reference 331
8.129.1 Detailed Description 331
8.129.2 Member Function Documentation 332

8.129.3 Member Data Documentation 332
8.130 rpki.manifest.FilesAndHashes Class Reference 332
8.130.1 Detailed Description 333
8.130.2 Member Function Documentation 333
8.131 rpki.manifest.Manifest Class Reference 334
8.131.1 Detailed Description 335
8.131.2 Member Function Documentation 335
8.131.3 Member Data Documentation 335
8.132 rpki.publication.certificate_elt Class Reference 336
8.132.1 Detailed Description 338
8.132.2 Member Data Documentation 338
8.133 rpki.publication.client_elt Class Reference 338
8.133.1 Detailed Description 340
8.133.2 Member Function Documentation 340
8.133.3 Member Data Documentation 341
8.134 rpki.publication.cms_msg Class Reference 343
8.134.1 Detailed Description 345
8.134.2 Member Data Documentation 345
8.135 rpki.publication.config_elt Class Reference 345
8.135.1 Detailed Description 347
8.135.2 Member Function Documentation 347
8.135.3 Member Data Documentation 348
8.136 rpki.publication.control_elt Class Reference 349
8.136.1 Detailed Description 351
8.136.2 Member Function Documentation 351
8.137 rpki.publication.crl_elt Class Reference 351
8.137.1 Detailed Description 353
8.137.2 Member Data Documentation 353
8.138 rpki.publication.manifest_elt Class Reference 353
8.138.1 Detailed Description 355
8.138.2 Member Data Documentation 355

8.139 rpki.publication.msg Class Reference 355
8.139.1 Detailed Description 357
8.139.2 Member Function Documentation 357
8.139.3 Member Data Documentation 357
8.140 rpki.publication.publication_namespace Class Reference 358
8.140.1 Detailed Description 358
8.140.2 Member Data Documentation 359
8.141 rpki.publication.publication_object_elt Class Reference 359
8.141.1 Detailed Description 361
8.141.2 Member Function Documentation 361
8.141.3 Member Data Documentation 363
8.142 rpki.publication.report_error_elt Class Reference 364
8.142.1 Detailed Description 366
8.142.2 Member Function Documentation 366
8.142.3 Member Data Documentation 367
8.143 rpki.publication.roa_elt Class Reference 368
8.143.1 Detailed Description 370
8.143.2 Member Data Documentation 370
8.144 rpki.publication.sax_handler Class Reference 370
8.144.1 Detailed Description 372
8.144.2 Member Data Documentation 372
8.145 rpki.resource_set.resource_bag Class Reference 372
8.145.1 Detailed Description 374
8.145.2 Member Function Documentation 374
8.145.3 Member Data Documentation 376
8.146 rpki.resource_set.resource_range Class Reference 377
8.146.1 Detailed Description 378
8.146.2 Member Function Documentation 378
8.146.3 Member Data Documentation 378
8.147 rpki.resource_set.resource_range_as Class Reference 379
8.147.1 Detailed Description 380

8.147.2 Member Function Documentation 380
8.147.3 Member Data Documentation 380
8.148 rpki.resource_set.resource_range_ip Class Reference 381
8.148.1 Detailed Description 383
8.148.2 Member Function Documentation 383
8.149 rpki.resource_set.resource_range_ipv4 Class Reference 384
8.149.1 Detailed Description 386
8.149.2 Member Data Documentation 386
8.150 rpki.resource_set.resource_range_ipv6 Class Reference 386
8.150.1 Detailed Description 388
8.150.2 Member Data Documentation 388
8.151 rpki.resource_set.resource_set Class Reference 388
8.151.1 Detailed Description 390
8.151.2 Member Function Documentation 390
8.151.3 Member Data Documentation 392
8.152 rpki.resource_set.resource_set_as Class Reference 393
8.152.1 Detailed Description 394
8.152.2 Member Function Documentation 394
8.152.3 Member Data Documentation 395
8.153 rpki.resource_set.resource_set_ip Class Reference 395
8.153.1 Detailed Description 397
8.153.2 Member Function Documentation 397
8.153.3 Member Data Documentation 398
8.154 rpki.resource_set.resource_set_ipv4 Class Reference 398
8.154.1 Detailed Description 400
8.154.2 Member Data Documentation 400
8.155 rpki.resource_set.resource_set_ipv6 Class Reference 400
8.155.1 Detailed Description 402
8.155.2 Member Data Documentation 402
8.156 rpki.resource_set.roa_prefix Class Reference 402
8.156.1 Detailed Description 404

8.156.2 Member Function Documentation 404
8.156.3 Member Data Documentation 405
8.157 rpki.resource_set.roa_prefix_ipv4 Class Reference 406
8.157.1 Detailed Description 408
8.157.2 Member Data Documentation 408
8.158 rpki.resource_set.roa_prefix_ipv6 Class Reference 408
8.158.1 Detailed Description 410
8.158.2 Member Data Documentation 410
8.159 rpki.resource_set.roa_prefix_set Class Reference 410
8.159.1 Detailed Description 411
8.159.2 Member Function Documentation 412
8.160 rpki.resource_set.roa_prefix_set_ipv4 Class Reference 413
8.160.1 Detailed Description 415
8.160.2 Member Data Documentation 415
8.161 rpki.resource_set.roa_prefix_set_ipv6 Class Reference 415
8.161.1 Detailed Description 417
8.161.2 Member Data Documentation 417
8.162 rpki.roa.ROAIPAddress Class Reference 417
8.162.1 Detailed Description 418
8.162.2 Member Function Documentation 418
8.162.3 Member Data Documentation 419
8.163 rpki.roa.ROAIPAddresses Class Reference 419
8.163.1 Detailed Description 420
8.163.2 Member Function Documentation 420
8.164 rpki.roa.ROAIPAddressFamilies Class Reference 420
8.164.1 Detailed Description 421
8.164.2 Member Function Documentation 421
8.165 rpki.roa.ROAIPAddressFamily Class Reference 421
8.165.1 Detailed Description 422
8.165.2 Member Function Documentation 422
8.165.3 Member Data Documentation 423

8.166 rpki.roa.RouteOriginAttestation Class Reference 423
8.166.1 Detailed Description 424
8.166.2 Member Function Documentation 424
8.166.3 Member Data Documentation 424
8.167 rpki.rpki_engine.ca_detail_obj Class Reference 425
8.167.1 Detailed Description 427
8.167.2 Member Function Documentation 428
8.167.3 Member Data Documentation 432
8.168 rpki.rpki_engine.ca_obj Class Reference 434
8.168.1 Detailed Description 436
8.168.2 Member Function Documentation 436
8.168.3 Member Data Documentation 440
8.169 rpki.rpki_engine.child_cert_obj Class Reference 441
8.169.1 Detailed Description 443
8.169.2 Member Function Documentation 443
8.169.3 Member Data Documentation 445
8.170 rpki.rpki_engine.publication_queue Class Reference 446
8.170.1 Detailed Description 448
8.170.2 Member Function Documentation 448
8.170.3 Member Data Documentation 449
8.171 rpki.rpki_engine.revoked_cert_obj Class Reference 450
8.171.1 Detailed Description 451
8.171.2 Member Function Documentation 451
8.171.3 Member Data Documentation 452
8.172 rpki.rpki_engine.roa_obj Class Reference 453
8.172.1 Detailed Description 455
8.172.2 Member Function Documentation 455
8.172.3 Member Data Documentation 458
8.173 rpki.rpki_engine.rpkid_context Class Reference 460
8.173.1 Detailed Description 462
8.173.2 Member Function Documentation 463

8.173.3 Member Data Documentation 465
8.174 rpki.sql.session Class Reference 468
8.174.1 Detailed Description 469
8.174.2 Member Function Documentation 470
8.174.3 Member Data Documentation 471
8.175 rpki.sql.sql_persistent Class Reference 473
8.175.1 Detailed Description 475
8.175.2 Member Function Documentation 475
8.175.3 Member Data Documentation 479
8.176 rpki.sql.template Class Reference 480
8.176.1 Detailed Description 482
8.176.2 Member Function Documentation 482
8.176.3 Member Data Documentation 482
8.177 rpki.sundial.datetime Class Reference 483
8.177.1 Detailed Description 485
8.177.2 Member Function Documentation 485
8.177.3 Member Data Documentation 489
8.178 rpki.sundial.timedelta Class Reference 489
8.178.1 Detailed Description 491
8.178.2 Member Function Documentation 492
8.178.3 Member Data Documentation 494
8.179 rpki.up_down.base_elt Class Reference 495
8.179.1 Detailed Description 496
8.179.2 Member Function Documentation 496
8.180 rpki.up_down.certificate_elt Class Reference 497
8.180.1 Detailed Description 499
8.180.2 Member Function Documentation 499
8.180.3 Member Data Documentation 500
8.181 rpki.up_down.class_elt Class Reference 500
8.181.1 Detailed Description 502
8.181.2 Member Function Documentation 502

8.181.3 Member Data Documentation 503
8.182rpki.up_down.class_response_syntax Class Reference 505
8.182.1 Detailed Description 506
8.182.2 Member Function Documentation 506
8.182.3 Member Data Documentation 507
8.183rpki.up_down.cms_msg Class Reference 507
8.183.1 Detailed Description 509
8.183.2 Member Data Documentation 509
8.184rpki.up_down.error_response_pdu Class Reference 509
8.184.1 Detailed Description 511
8.184.2 Member Function Documentation 511
8.184.3 Member Data Documentation 512
8.185rpki.up_down.issue_pdu Class Reference 513
8.185.1 Detailed Description 515
8.185.2 Member Function Documentation 515
8.185.3 Member Data Documentation 516
8.186rpki.up_down.issue_response_pdu Class Reference 517
8.186.1 Detailed Description 518
8.186.2 Member Function Documentation 519
8.187rpki.up_down.list_pdu Class Reference 519
8.187.1 Detailed Description 521
8.187.2 Member Function Documentation 521
8.188rpki.up_down.list_response_pdu Class Reference 522
8.188.1 Detailed Description 522
8.189rpki.up_down.message_pdu Class Reference 523
8.189.1 Detailed Description 525
8.189.2 Member Function Documentation 525
8.189.3 Member Data Documentation 527
8.190rpki.up_down.multi_uri Class Reference 528
8.190.1 Detailed Description 529
8.190.2 Member Function Documentation 529

8.191 rpki.up_down.revoke_pdu Class Reference 530
8.191.1 Detailed Description 532
8.191.2 Member Function Documentation 532
8.191.3 Member Data Documentation 533
8.192 rpki.up_down.revoke_response_pdu Class Reference 533
8.192.1 Detailed Description 534
8.193 rpki.up_down.revoke_syntax Class Reference 535
8.193.1 Detailed Description 536
8.193.2 Member Function Documentation 536
8.193.3 Member Data Documentation 536
8.194 rpki.up_down.sax_handler Class Reference 537
8.194.1 Detailed Description 539
8.194.2 Member Data Documentation 539
8.195 rpki.x509.CMS_object Class Reference 539
8.195.1 Detailed Description 542
8.195.2 Member Function Documentation 542
8.195.3 Member Data Documentation 543
8.196 rpki.x509.CRL Class Reference 546
8.196.1 Detailed Description 547
8.196.2 Member Function Documentation 547
8.196.3 Member Data Documentation 549
8.197 rpki.x509.DeadDrop Class Reference 550
8.197.1 Detailed Description 551
8.197.2 Member Function Documentation 551
8.197.3 Member Data Documentation 551
8.198 rpki.x509.DER_CMS_object Class Reference 552
8.198.1 Detailed Description 553
8.198.2 Member Function Documentation 553
8.198.3 Member Data Documentation 553
8.199 rpki.x509.DER_object Class Reference 554
8.199.1 Detailed Description 556

8.199.2 Member Function Documentation 556
8.199.3 Member Data Documentation 561
8.200 rpki.x509.PEM_converter Class Reference 562
8.200.1 Detailed Description 563
8.200.2 Member Function Documentation 563
8.200.3 Member Data Documentation 564
8.201 rpki.x509.PKCS10 Class Reference 564
8.201.1 Detailed Description 566
8.201.2 Member Function Documentation 566
8.201.3 Member Data Documentation 567
8.202 rpki.x509.ROA Class Reference 568
8.202.1 Detailed Description 570
8.202.2 Member Function Documentation 570
8.202.3 Member Data Documentation 570
8.203 rpki.x509.RSA Class Reference 571
8.203.1 Detailed Description 573
8.203.2 Member Function Documentation 573
8.203.3 Member Data Documentation 574
8.204 rpki.x509.RSApublic Class Reference 575
8.204.1 Detailed Description 577
8.204.2 Member Function Documentation 577
8.204.3 Member Data Documentation 578
8.205 rpki.x509.SignedManifest Class Reference 579
8.205.1 Detailed Description 580
8.205.2 Member Function Documentation 580
8.205.3 Member Data Documentation 581
8.206 rpki.x509.X509 Class Reference 581
8.206.1 Detailed Description 583
8.206.2 Member Function Documentation 583
8.206.3 Member Data Documentation 586
8.207 rpki.x509.XML_CMS_object Class Reference 587

8.207.1 Detailed Description 589
8.207.2 Member Function Documentation 589
8.207.3 Member Data Documentation 591
8.208 rpki.xml_utils.base_elt Class Reference 591
8.208.1 Detailed Description 593
8.208.2 Member Function Documentation 593
8.208.3 Member Data Documentation 595
8.209 rpki.xml_utils.data_elt Class Reference 596
8.209.1 Detailed Description 598
8.209.2 Member Function Documentation 598
8.210 rpki.xml_utils.msg Class Reference 601
8.210.1 Detailed Description 603
8.210.2 Member Function Documentation 603
8.210.3 Member Data Documentation 604
8.211 rpki.xml_utils.sax_handler Class Reference 605
8.211.1 Detailed Description 606
8.211.2 Member Function Documentation 606
8.211.3 Member Data Documentation 608
8.212 rpki.xml_utils.text_elt Class Reference 609
8.212.1 Detailed Description 610
8.212.2 Member Function Documentation 610
8.212.3 Member Data Documentation 610
8.213 Sequence Class Reference 611
8.214 SequenceOf Class Reference 611
8.215 TextWrapper Class Reference 611
8.216 ContentHandler Class Reference 611

9 File Documentation **612**
9.1 __init__.py File Reference 612
9.2 async.py File Reference 612
9.3 cli.py File Reference 612

9.4 config.py File Reference 613
9.5 exceptions.py File Reference 613
9.6 https.py File Reference 615
9.7 ipaddrs.py File Reference 616
9.8 irbe_cli.py File Reference 616
9.9 irdbd.py File Reference 617
9.10 left_right.py File Reference 618
9.11 log.py File Reference 619
9.12 manifest.py File Reference 619
9.13 oids.py File Reference 620
9.14 pubd.py File Reference 620
9.15 publication.py File Reference 621
9.16 relaxng.py File Reference 621
9.17 resource_set.py File Reference 622
9.18 roa.py File Reference 623
9.19 rootd.py File Reference 623
9.20 rpki_engine.py File Reference 625
9.21 rpkid.py File Reference 625
9.22 sql.py File Reference 625
9.23 sundial.py File Reference 626
9.24 up_down.py File Reference 626
9.25 x509.py File Reference 627
9.26 xml_utils.py File Reference 627

1 RPKI Engine Reference Manual

This collection of Python modules implements a prototype of the RPKI Engine. This is a work in progress.

See `http://viewvc.hactrn.net/subvert-rpki.hactrn.net/` for code, design documents, a text mirror of portions of APNIC's Wiki, etc.

The RPKI Engine is an implementation of the production-side tools for generating certificates, CRLs, and ROAs. The `relying party tools` are a separate (and much simpler) package.

The Subversion repository for the entire project is available for (read-only) anonymous access at http://subvert-rpki.hactrn.net/.

The documentation you're reading is generated automatically by Doxygen from comments and documentation in the code.

Besides the automatically-generated code documentation, this manual also includes documentation of the overall package:

- The installation instructions
- The operation instructions
- A description of the left-right protocol
- A description of the publication protocol
- A description of the BPKI model used to secure the up-down, left-right, and publication protocols
- A description of the several SQL database schemas
- Some suggestions for further reading

This work was funded from 2006 through 2008 by ARIN, in collaboration with the other Regional Internet Registries. Current work is funded by DHS.

2 Further Reading

If you're interested in this package you might also be interested in:

- The rcynic validation tool
- A live sample of rcynic's summary output
- APNIC's Wiki
- APNIC's project Trac instance

3 Installation Guide

Preliminary installation instructions for rpkid et al.

These are the production-side RPKI tools, for Internet Registries (RIRs, LIRs, etc). See the "rcynic" program for relying party tools.

rpkid is a set of Python modules supporting generation and maintenance of resource certificates. Most of the code is in the rpkid/rpki/ directory. rpkid itself is a relatively small program that calls the library modules. There are several other programs that make use of the same libraries, as well as a collection of test programs.

At present the package is intended to be run out of its build directory. Setting up proper installation in a system area using the Python distutils package would likely not be very hard but has not yet been done.

Note that initial development of this code has been on FreeBSD, so installation will probably be easiest on FreeBSD.

Before attempting to build the package, you need to install any missing prerequisites. Note that the Python code requires Python version 2.5. rpkid et al are mostly self-contained, but do require a small number of external packages to run.

- If your Python installation does not already include the sources files needed to compile new Python extension modules, you will need to install whatever package does include those source files. The need for and name of this package varies from system to system. On FreeBSD, the base Python interpreter package includes the development sources; on at least some Linux distributions, you have to install a separate "python-devel" package or something similar. If you get compilation errors trying to build the POW code (below) and the error message says something about the file "Python.h" being missing, this is almost certainly your problem.
- http://codespeak.net/lxml/. lxml in turn requires the Gnome LibXML2 C libraries.
  - FreeBSD: /usr/ports/devel/py-lxml
  - Fedora: python-lxml.i386
  - Ubuntu: python-lxml
- http://sourceforge.net/projects/mysql-python/. MySQLdb in turn requires MySQL client and server. rpkid et al have been tested with MySQL 5.0 and 5.1.
  - FreeBSD: /usr/ports/databases/py-MySQLdb
  - Fedora: MySQL-python.i386
  - Ubuntu: python-mysqldb

rpkid et al also make heavy use of a modified copy of the Python OpenSSL Wrappers (POW) package, but this copy has enough modifications and additions that it's included in the subversion tree.

The next step is to build the OpenSSL and POW binaries. At present the OpenSSL code is just a snapshot of the OpenSSL development sources, compiled with special options to enable RFC 3779 support that ISC wrote under previous contract to ARIN.

The POW (Python OpenSSL Wrapper) library is an extended copy of the stock POW release.

To build these, cd to the top-level directory in the distribution and type "make".

```
$ cd $top
$ make
```

This should automatically build everything, in the right order, including staticly linking the POW extension module with the OpenSSL library to provide RFC 3779 support. If you get errors building POW, see the above discussion of Python development sources.

You will also need a MySQL installation. This code was developed using MySQL 5.1 and has been tested with MySQL 5.0 and 5.1.

The architecture is intended to support hardware signing modules (HSMs), but the code to support them has not been written.

At this point, you should have all the necessary software installed. You will probably want to test it. All tests should be run from the rpkid/ directory. The test suite requires a few more external packages, only one of which is Python code.

- http://pyyaml.org/. testpoke.py (an up-down protocol command line test client) and testbed.py (a test harness) use PyYAML.
  - FreeBSD: /usr/ports/devel/py-yaml
  - Ubuntu: python-yaml
- http://xmlsoft.org/XSLT/. Some of the test code uses xsltproc, from the Gnome LibXSLT package.
  - FreeBSD: /usr/ports/textproc/libxslt
  - Ubuntu: xsltproc
- http://w3m.sourceforge.net/. testbed.py uses w3m to display the summary output from rcynic. Nothing terrible will happen if w3m isn't available, testbed.py will just complain about it being missing and won't display rcynic's output.
  - FreeBSD: /usr/ports/www/w3m
  - Ubuntu: w3m

Some of the tests require MySQL databases to store their data. To set up all the databases that the tests will need, run the SQL commands in rpkid/testbed.setup.sql. The MySQL command line client is usually the easiest way to do this, eg:

```
$ cd $top/rpkid
$ mysql -u root -p <testbed.setup.sql
```

To run the tests, run "make all-tests":

```
$ cd $top/rpkid
$ make all-tests
```

If nothing explodes, your installation is probably ok. Any Python backtraces in the output indicate a problem.

There's a last set of tools that only developers should need, as they're only used when modifying schemas or regenerating the documentation. These tools are listed here for completeness.

- http://www.doxygen.org/. Doxygen in turn pulls in several other tools, notably Graphviz, pdfLaTeX, and Ghostscript.
  - FreeBSD: /usr/ports/devel/doxygen
  - Ubuntu: doxygen
- http://lynx.isc.org/current/. The documentation build process uses xsltproc and Lynx to dump flat text versions of a few critical documentation pages.
  - FreeBSD: /usr/ports/www/lynx
  - Ubuntu: lynx
- http://www.thaiopensource.com/relaxng/trang.html. Trang is used to convert RelaxNG schemas from the human-readable "compact" form to the XML form that LibXML2 understands. Trang in turn requires Java.
  - FreeBSD: /usr/ports/textproc/trang
- http://search.cpan.org/dist/SQL-Translator/. SQL-Translator, also known as "SQL Fairy", includes code to parse an SQL schema and dump a description of it as Graphviz input. SQL Fairy in turn requires Perl.
  - FreeBSD: /usr/ports/databases/p5-SQL-Translator

4 Operation Guide

Preliminary operation instructions for rpkid et al.

These are the production-side RPKI tools, for Internet Registries (RIRs, LIRs, etc). See rcynic/README for relying party tools.

Warning

> rpkid is still in development, and the code changes more often than the hand-maintained portions of this documentation. The following text was reasonably accurate at the time it was written but may be obsolete by the time you read it.

At present the package is intended to be run out of the `rpkid/` directory.

In addition to the library routines in the `rpkid/rpki/` directory, the package includes the following programs:

- `rpkid.py`: The main RPKI engine daemon.
- `pubd.py`: The publication engine daemon.
- `rootd.py`: A separate daemon for handling the root of an RPKI certificate tree. This is essentially a stripped down version of rpkid with no SQL database, no left-right protocol implementation, and only the parent side of the up-down protocol. It's separate because the root is a special case in several ways and it was simpler to keep the special cases out of the main daemon.
- `irdbd.py`: A sample implementation of an IR database daemon. rpkid calls into this to perform lookups via the left-right protocol.
- `irbe_cli.py`: A command-line client for the left-right control protocol.
- `cross_certify.py`: A BPKI cross-certification tool.
- `cronjob.py`: A trivial HTTP client used to drive rpkid cron events.
- `testbed.py`: A test tool for running a collection of rpkid and irdb instances under common control, driven by a unified test script.
- `testpoke.py`: A simple client for the up-down protocol, mostly compatable with APNIC's rpki_poke.pl tool.

Most of these programs take configuration files in a common format similar to that used by the OpenSSL command line tool. The test programs also take input in YAML format to drive the tests. Runs of the testbed.py test tool will generate a fairly complete set configuration files which may be useful as examples.

Basic operation consists of creating the appropriate MySQL databases, starting rpkid, pubd, rootd, and irdbd, using the left-right control protocol to set up rpkid's internal state, and setting up a cron job to invoke rpkid's cron action at regular intervals. All

other operations should occur either as a result of cron events or as a result of incoming left-right and up-down protocol requests.

Note that the full event-driven model for rpkid hasn't yet been implemented. The design is intended to allow an arbitrary number of hosted RPKI engines to run in a single rpkid instance, but without the event-driven tasking model one must set up a separate rpkid instance for each hosted RPKI engine.

At present the daemon programs all run in foreground, that is, if one wants them to run in background one must do so manually, eg, using Bourne shell syntax:

```
$ python whatever.py &
$ echo >whatever.pid  "$!"
```

All of the daemons use syslog by default. To make them log to stderr instead, use the "-d" option.

4.1 Common Options

Some of the options that the several daemons take are common to all daemons. Which daemon they affect depends only on which sections of which config files they are in.

The first group of options are debugging flags, which can be set to "true" or "false". If not specified, default values will be chosen (generally false).

- `debug_http` Enable verbose http debug logging.
- `debug_tls_certs` Enable verbose logging about tls certs.
- `want_persistent_client` Enable http 1.1 persistence, client side.
- `want_persistent_server` Enable http 1.1 persistence, server side.
- `debug_cms_certs` Enable verbose logging about cms certs.
- `sql_debug` Enable verbose logging about sql operations.
- `gc_debug` Enable scary garbage collector debugging.
- `timer_debug` Enable verbose logging of timer system.

There are also a few options that allow you to save CMS messages for audit or debugging. The save format is a simple MIME encoding in a Maildir-format mailbox. The current options are very crude, at some point we may provide finer grain controls.

- `dump_outbound_cms` Dump messages we send to this mailbox.
- `dump_inbound_cms` Dump messages we receive to this mailbox.

4.2 rpkid.py

rpkid is the main RPKI engine daemon. Configuration of rpkid is a two step process: a config file to bootstrap rpkid to the point where it can speak using the left-right protocol, followed by dynamic configuration via the left-right protocol. In production use the latter stage would be handled by the IRBE stub; for test and develoment purposes it's handled by the irbe_cli.py command line interface or by the testbed.py test framework.

rpkid stores dynamic data in an SQL database, which must have been created for it, as explained in the installation guide.

The default config file is rpkid.conf, start rpkid with "-c filename" to choose a different config file. All options are in the section "[rpkid]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `startup-message`: String to log on startup, useful when debugging a collection of rpkid instances at once.
- `sql-username`: Username to hand to MySQL when connecting to rpkid's database.
- `sql-database`: MySQL's database name for rpkid's database.
- `sql-password`: Password to hand to MySQL when connecting to rpkid's database.
- `bpki-ta`: Name of file containing BPKI trust anchor. All BPKI certificate verification within rpkid traces back to this trust anchor.
- `rpkid-cert`: Name of file containing rpkid's own BPKI EE certificate.
- `rpkid-key`: Name of file containing RSA key corresponding to rpkid-cert.
- `irbe-cert`: Name of file containing BPKI certificate used by IRBE when talking to rpkid.
- `irdb-cert`: Name of file containing BPKI certificate used by irdbd.
- `irdb-url`: Service URL for irdbd. Must be a https:// URL.
- `server-host`: Hostname or IP address on which to listen for HTTPS connections. Current default is INADDR_ANY (IPv4 0.0.0.0); this will need to be hacked to support IPv6 for production.
- `server-port`: TCP port on which to listen for HTTPS connections.

4.3 pubd.py

pubd is the publication daemon. It implements the server side of the publication protocol, and is used by rpkid to publish the certificates and other objects that rpkid generates.

pubd is separate from rpkid for two reasons:

- The hosting model allows entities which choose to run their own copies of rpkid to publish their output under a common publication point. In general, encouraging shared publication services where practical is a good thing for relying parties, as it will speed up rcynic synchronization time.

- The publication server has to run on (or at least close to) the publication point itself, which in turn must be on a publically reachable server to be useful. rpkid, on the other hand, need only be reachable by the IRBE and its children in the RPKI tree. rpkid is a much more complex piece of software than pubd, so in some situations it might make sense to wrap tighter firewall constraints around rpkid than would be practical if rpkid and pubd were a single program.

pubd stores dynamic data in an SQL database, which must have been created for it, as explained in the installation guide. pubd also stores the published objects themselves as disk files in a configurable location which should correspond to an appropriate module definition in rsync.conf.

The default config file is pubd.conf, start pubd with "-c filename" to choose a different config file. ALl options are in the section "[pubd]". Certifiates, keys, and trust anchors may be either DER or PEM format.

Config file options:

- `sql-username`: Username to hand to MySQL when connecting to pubd's database.

- `sql-database`: MySQL's database name for pubd's database.

- `sql-password`: Password to hand to MySQL when connecting to pubd's database.

- `bpki-ta`: Name of file containing master BPKI trust anchor for pubd. All BPKI validation in pubd traces back to this trust anchor.

- `irbe-cert`: Name of file containing BPKI certificate used by IRBE when talking to pubd.

- `pubd-cert`: Name of file containing BPKI certificate used by pubd.

- `pubd-key`: Name of file containing RSA key corresponding to `pubd-cert`.
- `server-host`: Hostname or IP address on which to listen for HTTPS connections. Current default is INADDR_ANY (IPv4 0.0.0.0); this will need to be hacked to support IPv6 for production.
- `server-port`: TCP port on which to listen for HTTPS connections.
- `publication-base`: Path to base of filesystem tree where pubd should store publishable objects. Default is "publication/".

4.4 rootd.py

rootd is a stripped down implmenetation of (only) the server side of the up-down protocol. It's a separate program because the root certificate of an RPKI certificate tree requires special handling and may also require a special handling policy. rootd is a simple implementation intended for test use, it's not suitable for use in a production system. All configuration comes via the config file.

The default config file is rootd.conf, start rootd with "-c filename" to choose a different config file. All options are in the section "[rootd]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `bpki-ta`: Name of file containing BPKI trust anchor. All BPKI certificate validation in rootd traces back to this trust anchor.
- `rootd-bpki-cert`: Name of file containing rootd's own BPKI certificate.
- `rootd-bpki-key`: Name of file containing RSA key corresponding to rootd-bpki-cert.
- `rootd-bpki-crl`: Name of file containing BPKI CRL that would cover rootd-bpki-cert had it been revoked.
- `child-bpki-cert`: Name of file containing BPKI certificate for rootd's one and only child (RPKI engine to which rootd issues an RPKI certificate).
- `server-host`: Hostname or IP address on which to listen for HTTPS connections. Default is localhost.
- `server-port`: TCP port on which to listen for HTTPS connections.

- `rpki-root-key`: Name of file containing RSA key to use in signing resource certificates.
- `rpki-root-cert`: Name of file containing self-signed root resource certificate corresponding to rpki-root-key.
- `rpki-root-dir`: Name of directory where rootd should write RPKI subject certificate, manifest, and CRL.
- `rpki-subject-cert`: Name of file that rootd should use to save the one and only certificate it issues. Default is "Subroot.cer".
- `rpki-root-crl`: Name of file to which rootd should save its RPKI CRL. Default is "Root.crl".
- `rpki-root-manifest`: Name of file to which rootd should save its RPKI manifest. Default is "Root.mnf".
- `rpki-subject-pkcs10`: Name of file that rootd should use when saving a copy of the received PKCS #10 request for a resource certificate. This is only used for debugging. Default is not to save the PKCS #10 request.

4.5 irdbd.py

irdbd is a sample implemntation of the server side of the IRDB callback subset of the left-right protocol. In production use this service is a function of the IRBE stub; irdbd may be suitable for production use in simple cases, but an IR with a complex IRDB may need to extend or rewrite irdbd.

irdbd requires a pre-populated database to represent the IR's customers. irdbd expects this database to use the SQL schema defined in rpkid/irdbd.sql. Once this database has been populated, the IRBE stub needs to create the appropriate objects in rpkid's database via the control subset of the left-right protocol, and store the linkage IDs (foreign keys into rpkid's database, basicly) in the IRDB.

irdbd's default config file is irdbd.conf, start irdbd with "-c filename" to choose a different config file. All options are in the section "[irdbd]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `startup-message`: String to log on startup, useful when debugging a collection of irdbd instances at once.
- `sql-username`: Username to hand to MySQL when connecting to irdbd's database.

- `sql-database`: MySQL's database name for irdbd's database.
- `sql-password`: Password to hand to MySQL when connecting to irdbd's database.
- `bpki-ta`: Name of file containing BPKI trust anchor. All BPKI certificate validation in irdbd traces back to this trust anchor.
- `irdbd-cert`: Name of file containing irdbd's own BPKI certificate.
- `irdbd-key`: Name of file containing RSA key corresponding to irdbd-cert.
- `rpkid-cert`: Name of file containing certificate used the one and only by rpkid instance authorized to contact this irdbd instance.
- `https-url`: Service URL for irdbd. Must be a https:// URL.

4.6 irbe_cli.py

irbe_cli is a simple command line client for the control subsets of the left-right and publication protocols. In production use this functionality would be part of the IRBE stub.

Basic configuration of irbe_cli is handled via a config file. The specific action or actions to be performed are specified on the command line, and map closely to the protocols themselves.

At present the user is assumed to be able to read the (XML) left-right and publication protocol messages, and with one exception, irdbd-cli makes no attempt to interpret the responses other than to check for signature and syntax errors. The one exception is that, if the `--pem_out` option is specified on the command line, any PKCS #10 requests received from rpkid will be written in PEM format to that file; this makes it easier to hand these requests off to the business PKI (BPKI in order to issue signing certs corresponding to newly generated business keys.

```
Command line IR back-end control program for rpkid and pubd.

$Id: irbe_cli.py 2799 2009-09-30 02:33:36Z sra $

Copyright (C) 2009  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
```

```
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Usage:

# Top-level options:
--config= --help --pem_out= --quiet --verbose

# left-right protocol:
parent --action= --tag= --self_handle= --parent_handle= --bsc_handle=
    --repository_handle= --peer_contact_uri= --sia_base=
    --sender_name= --recipient_name= --bpki_cms_cert= --bpki_cms_glue=
    --bpki_https_cert= --bpki_https_glue= --rekey --reissue --revoke
    --revoke_forgotten
repository --action= --tag= --self_handle= --repository_handle=
    --bsc_handle= --peer_contact_uri= --bpki_cert= --bpki_glue=
self --action= --tag= --self_handle= --crl_interval= --regen_margin=
    --bpki_cert= --bpki_glue= --rekey --reissue --revoke --run_now
    --publish_world_now --revoke_forgotten
child --action= --tag= --self_handle= --child_handle= --bsc_handle=
    --bpki_cert= --bpki_glue= --reissue
list_published_objects --self_handle= --tag=
bsc --action= --tag= --self_handle= --bsc_handle= --key_type=
    --hash_alg= --key_length= --signing_cert= --signing_cert_crl=
    --generate_keypair

# publication protocol:
certificate --action= --tag= --client_handle= --uri=
roa --action= --tag= --client_handle= --uri=
manifest --action= --tag= --client_handle= --uri=
client --action= --tag= --client_handle= --base_uri= --bpki_cert=
    --bpki_glue=
config --action= --tag= --bpki_crl=
crl --action= --tag= --client_handle= --uri=
```

Global options (`--config`, `--help`, `--pem_out`) come first, then zero or more commands (`parent`, `repository`, `self`, `child`, `bsc`, `config`, `client`), each followed by its own set of options. The commands map to elements in the protocols, and the command-specific options map to attributes or subelements for those com-

mands.

`--tag` is an optional arbitrary tag (think IMAP) to simplify matching up replies with batched queries.

`--*_handle` options refer to object primary keys.

The remaining options are specific to the particular commands, and follow directly from the protocol specifications.

A trailing "=" in the above option summary indicates that an option takes a value, eg, "--action create" or "--action=create". Options without a trailing "=" correspond to boolean control attributes.

The default config file for irbe_cli is irbe_cli.conf, start irbe_cli with "-c filename" (or "--config filename") to choose a different config file. All options are in the section "[irbe_cli]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `rpkid-bpki-ta`: Name of file containing BPKI trust anchor to use when authenticating messages from rpkid.
- `rpkid-irbe-cert`: Name of file containing BPKI certificate irbe_cli should use when talking to rpkid.
- `rpkid-irbe-key`: Name of file containing RSA key corresponding to rpkid-irbe-cert.
- `rpkid-cert`: Name of file containing rpkid's BPKI certificate.
- `rpkid-url`: Service URL for rpkid. Must be a https:// URL.
- `pubd-bpki-ta`: Name of file containing BPKI trust anchor to use when authenticating messages from pubd.
- `pubd-irbe-cert`: Name of file containing BPKI certificate irbe_cli should use when talking to pubd.
- `pubd-irbe-key`: Name of file containing RSA key corresponding to pubd-irbe-cert.
- `pubd-cert`: Name of file containing pubd's BPKI certificate.
- `pubd-url`: Service URL for pubd. Must be a https:// URL.

4.7 cross_certify.py

cross_certify.py is a small tool to extract certain fields from an existing X.509 certificate and generate issue a new certificate that can be used as part of a cross-certification chain. cross_certify doesn't take a config file, all of its arguments are specified on the command line.

```
python cross_certify.py { -i | --in     } input_cert
                        { -c | --ca     } issuing_cert
                        { -k | --key    } issuing_cert_key
                        { -s | --serial } serial_filename
                        [ { -h | --help } ]
                        [ { -o | --out  }     filename ]
                        [ { -l | --lifetime } timedelta ]
```

4.8 cronjob.py

This is a trivial program to trigger a cron run within rpkid. Ordinarilly rpkid runs its own internal cron process, but for scripted testing it is sometimes useful to be able to control when cron cycles occur.

The default config file is cronjob.conf, start cronjob with "-c filename" to choose a different config file. All options are in the section "[cronjob]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `bpki-ta`: Name of file containing BPKI trust anchor.
- `irbe-cert`: Name of file containing cronjob.py's BPKI certificate.
- `https-key`: Name of file containing RSA key corresponding to irbe-cert.
- `rpkid-cert`: Name of file containing rpkid's BPKI certificate.
- `https-url`: Service URL for rpkid. Must be a https:// URL.

4.9 testbed.py:

testbed is a test harness to set up and run a collection of rpkid and irdbd instances under scripted control. testbed is a very recent addition to the toolset and is still evolving rapidly.

Unlike the programs described above, testbed takes two configuration files in different languages. The first configuration file uses the same syntax as the above configuration

files but is completely optional. The second configuration file is the test script, which is encoded using the YAML serialization language (see http://www.yaml.org/ for more information on YAML). The YAML script is not optional, as it describes the test layout. testbed is designed to support running a fairly wide set of test configurations as canned scripts without writing any new control code. The intent is to make it possible to write meaningful regression tests.

All of the options in in the first (optional) configuration file are just overrides for wired-in default values. In most cases the defaults will suffice, and the set of options is still in flux, so only a few of the options are described here. The default name for this configuration file is testbed.conf, run testbed with "-c filename" to change it.

testbed.conf options:

- `testbed_dir:` Working directory into which testbed should write the (many) files it generates. Default is "testbed.dir".

- `irdb_db_pass:` MySQL password for the "irdb" user. Default is "fnord". You may want to override this.

- `rpki_db_pass:` MySQL password for the "rpki" user. Default is "fnord". You may want to override this.

- `rootd_sia:` rsync URI naming a (perhaps fictious) directory to use as the id-ad-caRepository SIA value in the generated root resource certificate. Default is "rsync://wombat.invalid/". You may want to override this if you intend to run an rsync server and test against the generated results using rcynic. This default will likely change if and when testbed learns how to run rcynic itself as part of the test suite.

The second configuration file is named testbed.yaml by default, run testbed with "-y filename" to change it. The YAML file contains multiple YAML "documents". The first document describes the initial test layout and resource allocations, subsequent documents describe modifications to the initial allocations and other parameters. Resources listed in the initial layout are aggregated automatically, so that a node in the resource hierarchy automatically receives the resources it needs to issue whatever its children are listed as holding. Actions in the subsequent documents are modifications to the current resource set, modifications to validity dates or other non-resource parameters, or special commands like "sleep". The details are still evolving, but here's an example of current usage:

```
name:           RIR
valid_for:      2d
sia_base:       "rsync://wombat.invalid/"
kids:
  - name: LIR0
```

```
 kids:
   - name: Alice
     ipv4: 192.0.2.1-192.0.2.33
     asn:  64533
---
- name: Alice
  valid_add:   10
---
- name: Alice
  add_as: 33
  valid_add:   2d
---
- name: Alice
  valid_sub:   2d
---
- name: Alice
  valid_for:   10d
```

This specifies an initial layout consisting of an RPKI engine named "RIR", with one child "LIR0", which in turn has one child "Alice". Alice has a set of assigned resources, and all resources in the system are initially set to be valid for two days from the time at which the test is started. The first subsequent document adds ten seconds to the validity interval for Alice's resources and makes no other modifications. The second subsequent document grants Alice additional resources and adds another two days to the validity interval for Alice's resources. The next document subtracts two days from the validity interval for Alice's resources. The final document sets the validity interval for Alice's resources to ten days.

Operators in subsequent (update) documents:

- `add_as`, `add_v4`, `add_v6`: These add ASN, IPv4, or IPv6 resources, respectively.
- `sub_as`, `sub_v4`, `sub_v6`: These subtract resources.
- `valid_until`: Set an absolute expiration date.
- `valid_for`: Set a relative expiration date.
- `valid_add`, `valid_sub`: Add to or subtract from validity interval.
- `sleep` [interval]: Sleep for specified interval, or until testbed receives a SIGALRM signal.

Absolute timestamps should be in the form shown (UTC timestamp format as used in XML).

Intervals (`valid_add`, `valid_sub`, `valid_for`, `sleep`) are either integers, in which case they're interpreted as seconds, or are a string of the form "wD xH yM zS" where w, x, y, and z are integers and D, H, M, and S indicate days, hours, minutes, and seconds. In the latter case all of the fields are optional, but at least one must be specified. For example, "3D4H" means "three days plus four hours".

4.10 testpoke.py

This is a command-line client for the up-down protocol. Unlike all of the above programs, testpoke does not accept a config file in OpenSSL-compatable format at all. Instead, it is configured exclusively by a YAML script. testpoke's design was constrained by a desire to have it be compatable with APNIC's rpki_poke.pl tool, so that the two tools could use a common configuration language to simplify scripted testing. There are minor variations due to slightly different feature sets, but YAML files intended for one program will usually work with the other.

README for APNIC's tool describing the input language can be found at http://mirin.apnic.net/svn/rpki_-engine/branches/gary-poker/client/poke/README.

testpoke.py takes a simplified command line and uses only one YAML input file.

```
Usage: python testpoke.py [ { -y | --yaml }    configfile ]
                          [ { -r | --request } requestname ]
                          [ { -h | --help } ]
```

Default configuration file is testpoke.yaml, override with --yaml option.

The --request option specifies the specific command within the YAML file to execute.

Sample configuration file:

```
---
# Sample YAML configuration file for testpoke.py

version: 1
posturl: https://localhost:4433/up-down/1
recipient-id: wombat
sender-id: "1"

cms-cert-file: biz-certs/Frank-EE.cer
cms-key-file: biz-certs/Frank-EE.key
cms-ca-cert-file: biz-certs/Bob-Root.cer
cms-cert-chain-file: [ biz-certs/Frank-CA.cer ]

ssl-cert-file: biz-certs/Frank-EE.cer
ssl-key-file: biz-certs/Frank-EE.key
ssl-ca-cert-file: biz-certs/Bob-Root.cer

requests:
```

```
 list:
type: list
 issue:
type: issue
class: 1
sia: [ "rsync://bandicoot.invalid/some/where/" ]
 revoke:
type: revoke
class: 1
ski: "CB5K6APY-4KcGAW9jaK_cVPXKX0"
```

testpoke adds one extension to the language described in APNIC's README: the cms-cert-chain-∗ and ssl-cert-chain-∗ options, which allow one to specify a chain of intermediate certificates to be presented in the CMS or TLS protocol. APNIC's initial implementation required direct knowledge of the issuing certificate (ie, it supported a maximum chain length of one); subsequent APNIC code changes have probably relaxed this restriction, and with luck APNIC has copied testpoke's syntax to express chains of intermediate certificates.

5 Left-right protocol

The left-right protocol is really two separate client/server protocols over separate channels between the RPKI engine and the IR back end (IRBE).

The IRBE is the client for one of the subprotocols, the RPKI engine is the client for the other.

5.1 Terminology

- *IRBE:* Internet Registry Back End
- *IRDB:* Internet Registry Data Base
- *BPKI:* Business PKI
- *RPKI:* Resource PKI

5.2 initiated by the IRBE

This part of the protcol uses a kind of message-passing. Each object that the RPKI engine knows about takes five messages: "create", "set", "get", "list", and "destroy". Actions which are not just data operations on objects are handled via an SNMP-like mechanism, as if they were fields to be set. For example, to generate a keypair one

"sets" the "generate-keypair" field of a BSC object, even though there is no such field in the object itself as stored in SQL. This is a bit of a kludge, but the reason for doing it as if these were variables being set is to allow composite operations such as creating a BSC, populating all of its data fields, and generating a keypair, all as a single operation. With this model, that's trivial, otherwise it's at least two round trips.

Fields can be set in either "create" or "set" operations, the difference just being whether the object already exists. A "get" operation returns all visible fields of the object. A "list" operation returns a list containing what "get" would have returned on each of those objects.

Left-right protocol objects are encoded as signed CMS messages containing XML as eContent and using an eContentType OID of `id-ct-xml` (1.2.840.113549.1.9.16.1.28). These CMS messages are in turn passed as the data for HTTPS POST operations, with an HTTP content type of "application/x-rpki" for both the POST data and the response data.

All operations allow an optional "tag" attribute which can be any alphanumeric token. The main purpose of the tag attribute is to allow batching of multiple requests into a single PDU.

5.2.1 <self/> object

A `<self/>` object represents one virtual RPKI engine. In simple cases where the RPKI engine operator operates the engine only on their own behalf, there will only be one `<self/>` object, representing the engine operator's organization, but in environments where the engine operator hosts other entities, there will be one `<self/> object` per hosted entity (probably including the engine operator's own organization, considered as a hosted customer of itself).

Some of the RPKI engine's configured parameters and data are shared by all hosted entities, but most are tied to a specific `<self/>` object. Data which are shared by all hosted entities are referred to as "per-engine" data, data which are specific to a particular `<self/>` object are "per-self" data.

Since all other RPKI engine objects refer to a `<self/>` object via a "self_handle" value, one must create a `<self/>` object before one can usefully configure any other left-right protocol objects.

Every `<self/>` object has a self_handle attribute, which must be specified for the "create", "set", "get", and "destroy" actions.

Payload data which can be configured in a `<self/>` object:

- `use_hsm` (attribute): Whether to use a Hardware Signing Module. At present this option has no effect, as the implementation does not yet support HSMs.

- `crl_interval` (attribute): Positive integer representing the planned lifetime of an RPKI CRL for this `<self/>`, measured in seconds.

- `regen_margin` (attribute): Positive integer representing how long before expiration of an RPKI certificiate a new one should be generated, measured in seconds. At present this only affects the one-off EE certificates associated with ROAs.

- `bpki_cert` (element): BPKI CA certificate for this `<self/>`. This is used as part of the certificate chain when validating incoming TLS and CMS messages, and should be the issuer of cross-certification BPKI certificates used in `<repository/>`, `<parent/>`, and `<child/>` objects. If the bpki_glue certificate is in use (below), the bpki_cert certificate should be issued by the bpki_glue certificate; otherwise, the bpki_cert certificate should be issued by the per-engine bpki_ta certificate.

- `bpki_glue` (element): Another BPKI CA certificate for this `<self/>`, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the bpki_glue certificate should be the issuer of the bpki_cert certificate and should be issued by the per-engine bpki_ta certificate; if not needed, the bpki_glue certificate should be left unset.

Control attributes that can be set to "yes" to force actions:

- `rekey`: Start a key rollover for every RPKI CA associated with every `<parent/>` object associated with this `<self/>` object. This is the first phase of a key rollover operation.

- `revoke`: Revoke any remaining certificates for any expired key associated with any RPKI CA for any `<parent/>` object associated with this `<self/>` object. This is the second (cleanup) phase for a key rollover operation; it's separate from the first phase to leave time for new RPKI certificates to propegate and be installed.

- `reissue`: Not implemented, may be removed from protocol. Original theory was that this operation would force reissuance of any object with a changed key, but as that happens automatically as part of the key rollover mechanism this operation seems unnecessary.

- `run_now`: Force immediate processing for all tasks associated with this `<self/>` object that would ordinarily be performed under cron. Not currently implemented.

- `publish_world_now`: Force (re)publication of every publishable object for this `<self/>` object. Not currently implemented. Intended to aid in recovery if RPKI engine and publication engine somehow get out of sync.

5.2.2 <bsc/> object

The <bsc/> ("business signing context") object represents all the BPKI data needed to sign outgoing CMS or HTTPS messages. Various other objects include pointers to a <bsc/> object. Whether a particular <self/> uses only one <bsc/> or multiple is a configuration decision based on external requirements: the RPKI engine code doesn't care, it just cares that, for any object representing a relationship for which it must sign messages, there be a <bsc/> object that it can use to produce that signature.

Every <bsc/> object has a bsc_handle, which must be specified for the "create", "get", "set", and "destroy" actions. Every <bsc/> also has a self_handle attribute which indicates the <self/> object with which this <bsc/> object is associated.

Payload data which can be configured in a <isc/> object:

- signing_cert (element): BPKI certificate to use when generating a signature.
- signing_cert_crl (element): CRL which would list signing_cert if it had been revoked.

Control attributes that can be set to "yes" to force actions:

- generate_keypair: Generate a new BPKI keypair and return a PKCS #10 certificate request. The resulting certificate, once issued, should be configured as this <bsc/> object's signing_cert.

Additional attributes which may be specified when specifying "generate_keypair":

- key_type: Type of BPKI keypair to generate. "rsa" is both the default and, at the moment, the only allowed value.
- hash_alg: Cryptographic hash algorithm to use with this keypair. "sha256" is both the default and, at the moment, the only allowed value.
- key_length: Length in bits of the keypair to be generated. "2048" is both the default and, at the moment, the only allowed value.

Replies to "create" and "set" actions that specify "generate-keypair" include a <bsc_pkcs10/> element, as do replies to "get" and "list" actions for a <bsc/> object for which a "generate-keypair" command has been issued. The RPKI engine stores the PKCS #10 request, which allows the IRBE to reuse the request if and when it needs to reissue the corresponding BPKI signing certificate.

5.2.3 <parent/> object

The <parent/> object represents the RPKI engine's view of a particular parent of the current <self/> object in the up-down protocol. Due to the way that the resource hierarchy works, a given <self/> may obtain resources from multiple parents, but it will always have at least one; in the case of IANA or an RIR, the parent RPKI engine may be a trivial stub.

Every <parent/> object has a parent_handle, which must be specified for the "create", "get", "set", and "destroy" actions. Every <parent/> also has a self_handle attribute which indicates the <self/> object with which this <parent/> object is associated, a bsc_handle attribute indicating the <bsc/> object to be used when signing messages sent to this parent, and a repository_handle indicating the <repository/> object to be used when publishing issued by the certificate issued by this parent.

Payload data which can be configured in a <parent/> object:

- peer_contact_uri (attribute): HTTPS URI used to contact this parent.
- sia_base (attribute): The leading portion of an rsync URI that the RPKI engine should use when composing the publication URI for objects issued by the RPKI certificate issued by this parent.
- sender_name (attribute): Sender name to use in the up-down protocol when talking to this parent. The RPKI engine doesn't really care what this value is, but other implementations of the up-down protocol do care.
- recipient_name (attribute): Recipient name to use in the up-down protocol when talking to this parent. The RPKI engine doesn't really care what this value is, but other implementations of the up-down protocol do care.
- bpki_cms_cert (element): BPKI CMS CA certificate for this <parent/>. This is used as part of the certificate chain when validating incoming CMS messages If the bpki_cms_glue certificate is in use (below), the bpki_cms_cert certificate should be issued by the bpki_cms_glue certificate; otherwise, the bpki_cms_cert certificate should be issued by the bpki_cert certificate in the <self/> object.
- bpki_cms_glue (element): Another BPKI CMS CA certificate for this <parent/>, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the bpki_cms_glue certificate should be the issuer of the bpki_cms_cert certificate and should be issued by the bpki_cert certificate in the <self/> object; if not needed, the bpki_cms_glue certificate should be left unset.

- bpki_https_cert (element): BPKI HTTPS CA certificate for this <parent/>. This is like the bpki_cms_cert object, only used for validating incoming TLS messages rather than CMS.

- bpki_cms_glue (element): Another BPKI HTTPS CA certificate for this <parent/>, usually not needed. This is like the bpki_cms_glue certificate, only used for validating incoming TLS messages rather than CMS.

Control attributes that can be set to "yes" to force actions:

- rekey: This is like the rekey command in the <self/> object, but limited to RPKI CAs under this parent.

- reissue: This is like the reissue command in the <self/> object, but limited to RPKI CAs under this parent.

- revoke: This is like the revoke command in the <self/> object, but limited to RPKI CAs under this parent.

5.2.4 <child/> object

The <child/> object represents the RPKI engine's view of particular child of the current <self/> in the up-down protocol.

Every <child/> object has a child_handle, which must be specified for the "create", "get", "set", and "destroy" actions. Every <child/> also has a self_handle attribute which indicates the <self/> object with which this <child/> object is associated.

Payload data which can be configured in a <child/> object:

- bpki_cert (element): BPKI CA certificate for this <child/>. This is used as part of the certificate chain when validating incoming TLS and CMS messages. If the bpki_glue certificate is in use (below), the bpki_cert certificate should be issued by the bpki_glue certificate; otherwise, the bpki_cert certificate should be issued by the bpki_cert certificate in the <self/> object.

- bpki_glue (element): Another BPKI CA certificate for this <child/>, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the bpki_glue certificate should be the issuer of the bpki_cert certificate and should be issued by the bpki_cert certificate in the <self/> object; if not needed, the bpki_glue certificate should be left unset.

Control attributes that can be set to "yes" to force actions:

- reissue: Not implemented, may be removed from protocol.

5.2.5 <repository/> object

The <repository/> object represents the RPKI engine's view of a particular publication repository used by the current <self/> object.

Every <repository/> object has a repository_handle, which must be specified for the "create", "get", "set", and "destroy" actions. Every <repository/> also has a self_handle attribute which indicates the <self/> object with which this <repository/> object is associated.

Payload data which can be configured in a <repository/> object:

- peer_contact_uri (attribute): HTTPS URI used to contact this repository.
- bpki_cms_cert (element): BPKI CMS CA certificate for this <repository/>. This is used as part of the certificate chain when validating incoming CMS messages If the bpki_cms_glue certificate is in use (below), the bpki_cms_cert certificate should be issued by the bpki_cms_glue certificate; otherwise, the bpki_cms_cert certificate should be issued by the bpki_cert certificate in the <self/> object.
- bpki_cms_glue (element): Another BPKI CMS CA certificate for this <repository/>, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the bpki_cms_glue certificate should be the issuer of the bpki_cms_cert certificate and should be issued by the bpki_cert certificate in the <self/> object; if not needed, the bpki_cms_glue certificate should be left unset.
- bpki_https_cert (element): BPKI HTTPS CA certificate for this <repository/>. This is like the bpki_cms_cert object, only used for validating incoming TLS messages rather than CMS.
- bpki_cms_glue (element): Another BPKI HTTPS CA certificate for this <repository/>, usually not needed. This is like the bpki_cms_glue certificate, only used for validating incoming TLS messages rather than CMS.

At present there are no control attributes for <repository/> objects.

5.2.6 <route_origin/> object

This section is out-of-date. The <route_origin/> object has been replaced by the <list_roa_requests/> IRDB query, but the documentation for that hasn't been written yet.

The <route_origin/> object is a kind of prototype for a ROA. It contains all the information needed to generate a ROA once the RPKI engine obtains the appropriate RPKI certificates from its parent(s).

Note that a <route_origin/> object represents a ROA to be generated on behalf of <self/>, not on behalf of a <child/>. Thus, a hosted entity that has no children but which does need to generate ROAs would be represented by a hosted <self/> with no <child/> objects but one or more <route_origin/> objects. While lumping ROA generation in with the other RPKI engine activities may seem a little odd at first, it's a natural consequence of the design requirement that the RPKI daemon never transmit private keys across the network in any form; given this requirement, the RPKI engine that holds the private keys for an RPKI certificate must also be the engine which generates any ROAs that derive from that RPKI certificate.

The precise content of the <route_origin/> has changed over time as the underlying ROA specification has changed. The current implementation as of this writing matches what we expect to see in draft-ietf-sidr-roa-format-03, once it is issued. In particular, note that the exactMatch boolean from the -02 draft has been replaced by the prefix and maxLength encoding used in the -03 draft.

Payload data which can be configured in a <route_origin/> object:

- asn (attribute): Autonomous System Number (ASN) to place in the generated ROA. A single ROA can only grant authorization to a single ASN; multiple ASNs require multiple ROAs, thus multiple <route_origin/> objects.

- ipv4 (attribute): List of IPv4 prefix and maxLength values, see below for format.

- ipv6 (attribute): List of IPv6 prefix and maxLength values, see below for format.

Control attributes that can be set to "yes" to force actions:

- suppress_publication: Not implemented, may be removed from protocol.

The lists of IPv4 and IPv6 prefix and maxLength values are represented as comma-separated text strings, with no whitespace permitted. Each entry in such a string represents a single prefix/maxLength pair.

ABNF for these address lists:

```
<ROAIPAddress> ::= <address> "/" <prefixlen> [ "-" <max_prefixlen> ]
                       ; Where <max_prefixlen> defaults to the same
                       ; value as <prefixlen>.
```

```
<ROAIPAddressList> ::= <ROAIPAddress> *( "," <ROAIPAddress> )
```

For example, `"10.0.1.0/24-32,10.0.2.0/24"`, which is a shorthand form of `"10.0.1.0/24-32,10.0.2.0/24-24"`.

5.3 Operations initiated by the RPKI engine

The left-right protocol also includes queries from the RPKI engine back to the IRDB. These queries do not follow the message-passing pattern used in the IRBE-initiated part of the protocol. Instead, there's a single query back to the IRDB, with a corresponding response. The CMS and HTTPS encoding are the same as in the rest of the protocol, but the BPKI certificates will be different as the back-queries and responses form a separate communication channel.

5.3.1 <list_resources/> messages

The `<list_resources/>` query and response allow the RPKI engine to ask the IRDB for information about resources assigned to a particular child. The query must include both a `"self_handle"` attribute naming the `<self/>` that is making the request and also a `"child_handle"` attribute naming the child that is the subject of the query. The query and response also allow an optional `"tag"` attribute of the same form used elsewhere in this protocol, to allow batching.

A `<list_resources/>` response includes the following attributes, along with the `tag` (if specified), `self_handle`, and `child_handle` copied from the request:

- `valid_until`: A timestamp indicating the date and time at which certificates generated by the RPKI engine for these data should expire. The timestamp is expressed as an XML `xsd:dateTime`, must be expressed in UTC, and must carry the "Z" suffix indicating UTC.

- `asn`: A list of autonomous sequence numbers, expressed as a comma-separated sequence of decimal integers with no whitespace.

- `ipv4`: A list of IPv4 address prefixes and ranges, expressed as a comma-separated list of prefixes and ranges with no whitespace. See below for format details.

- `ipv6`: A list of IPv6 address prefixes and ranges, expressed as a comma-separated list of prefixes and ranges with no whitespace. See below for format details.

Entries in a list of address prefixes and ranges can be either prefixes, which are written in the usual address/prefixlen notation, or ranges, which are expressed as a pair of addresses denoting the beginning and end of the range, written in ascending order separated by a single "-" character. This format is superficially similar to the format used for prefix and maxLength values in the `<route_origin/>` object, but the semantics differ: note in particular that `<route_origin/>` objects don't allow ranges, while `<list_resources/>` messages don't allow a maxLength specification.

5.4 Error handling

Error in this protocol are handled at two levels.

Since all messages in this protocol are conveyed over HTTPS connections, basic errors are indicated via the HTTP response code. 4xx and 5xx responses indicate that something bad happened. Errors that make it impossible to decode a query or encode a response are handled in this way.

Where possible, errors will result in a `<report_error/>` message which takes the place of the expected protocol response message. `<report_error/>` messages are CMS-signed XML messages like the rest of this protocol, and thus can be archived to provide an audit trail.

`<report_error/>` messages only appear in replies, never in queries. The `<report_error/>` message can appear on either the "forward" (IRBE as client of RPKI engine) or "back" (RPKI engine as client of IRDB) communication channel.

The `<report_error/>` message includes an optional `"tag"` attribute to assist in matching the error with a particular query when using batching, and also includes a `"self_handle"` attribute indicating the `<self/>` that issued the error.

The error itself is conveyed in the `error_code` (attribute). The value of this attribute is a token indicating the specific error that occurred. At present this will be the name of a Python exception; the production version of this protocol will nail down the allowed error tokens here, probably in the RelaxNG schema.

The body of the `<report_error/>` element itself is an optional text string; if present, this is debugging information. At present this capabilty is not used, debugging information goes to syslog.

6 Publication protocol

The publication protocol is really two separate client/server protocols, between different parties.

The first is a configuration protocol for an IRBE to use to configure a publication engine, the second is the interface by which authorized clients request publication of specific objects.

Much of the architecture of the publication protocol is borrowed from the left-right protocol: like the left-right protocol, the publication protocol uses CMS-wrapped XML over HTTPS with the same eContentType OID and the same HTTPS content-type, and the overall style of the XML messages is very similar to the left-right protocol. All operations allow an optional "tag" attribute to allow batching.

The publication engine operates a single HTTPS server which serves both of these subprotocols. The two subprotocols share a single server port, but use distinct URLs to allow demultiplexing.

6.1 Terminology

- *IRBE:* Internet Registry Back End
- *IRDB:* Internet Registry Data Base
- *BPKI:* Business PKI
- *RPKI:* Resource PKI

6.2 Publication control subprotocol

The control subprotocol reuses the message-passing design of the left-right protocol. Configured objects support the "create", "set", "get", "list", and "destroy" actions, or a subset thereof when the full set of actions doesn't make sense.

6.2.1 <config/> object

The <config/> object allows configuration of data that apply to the entire publication server rather than a particular client.

There is exactly one <config/> object in the publication server, and it only supports the "set" and "get" actions -- it cannot be created or destroyed.

Payload data which can be configured in a <config/> object:

- `bpki_crl` (element): This is the BPKI CRL used by the publication server when signing the CMS wrapper on responses in the publication subprotocol. As the CRL must be updated at regular intervals, it's not practical to restart the publication server when the BPKI CRL needs to be updated. The BPKI model doesn't require use of a BPKI CRL between the IRBE and the publication server, so we can use the publication control subprotocol to update the BPKI CRL.

6.2.2 <client/> object

The <client/> object represents one client authorized to use the publication server.

The <client/> object supports the full set of "create", "set", "get", "list", and "destroy" actions. Each client has a "client_handle" attribute, which is used in responses and must be specified in "create", "set", "get", or "destroy" actions.

Payload data which can be configured in a <client/> object:

- `base_uri` (attribute): This is the base URI below which this client is allowed to publish data. The publication server may impose additional constraints in the case of a child publishing beneath its parent.

- `bpki_cert` (element): BPKI CA certificate for this <client/>. This is used as part of the certificate chain when validating incoming TLS and CMS messages. If the bpki_glue certificate is in use (below), the bpki_cert certificate should be issued by the bpki_glue certificate; otherwise, the bpki_cert certificate should be issued by the publication engine's bpki_ta certificate.

- `bpki_glue` (element): Another BPKI CA certificate for this <client/>, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the bpki_glue certificate should be the issuer of the bpki_cert certificate and should be issued by the publication engine's bpki_ta certificate; if not needed, the bpki_glue certificate should be left unset.

6.3 Publication subprotocol

The publication subprotocol is structured somewhat differently from the publication control protocol. Objects in the publication subprotocol represent objects to be published or objects to be withdrawn from publication. Each kind of object supports two actions: "publish" and "withdraw". In each case the XML element representing hte object to be published or withdrawn has a "uri" attribute which contains the publication URI. For "publish" actions, the XML element body contains the DER object to be published, encoded in Base64; for "withdraw" actions, the XML element body is empty.

In theory, the detailed access control for each kind of object might be different. In practice, as of this writing, access control for all objects is a simple check that the client's `"base_uri"` is a leading substring of the publication URI. Details of why access control might need to become more complicated are discussed in a later section.

6.3.1 <certificate/> object

The <certificate/> object represents an RPKI certificate to be published or withdrawn.

6.3.2 <crl/> object

The <crl/> object represents an RPKI CRL to be published or withdrawn.

6.3.3 <manifest/> object

The <manifest/> object represents an RPKI publication manifest to be published or withdrawn.

Note that part of the reason for the batching support in the publication protocol is because *every* publication or withdrawal action requires a new manifest, thus every publication or withdrawal action will involve at least two objects.

6.3.4 <roa/> object

The <roa/> object represents a ROA to be published or withdrawn.

6.4 Error handling

Error in this protocol are handled at two levels.

Since all messages in this protocol are conveyed over HTTPS connections, basic errors are indicated via the HTTP response code. 4xx and 5xx responses indicate that something bad happened. Errors that make it impossible to decode a query or encode a response are handled in this way.

Where possible, errors will result in a <report_error/> message which takes the place of the expected protocol response message. <report_error/> messages are CMS-signed XML messages like the rest of this protocol, and thus can be archived to provide an audit trail.

<report_error/> messages only appear in replies, never in queries. The <report_error/> message can appear in both the control and publication subprotocols.

The <report_error/> message includes an optional `"tag"` attribute to assist in matching the error with a particular query when using batching.

The error itself is conveyed in the `error_code` (attribute). The value of this attribute is a token indicating the specific error that occurred. At present this will be the name of a Python exception; the production version of this protocol will nail down the allowed error tokens here, probably in the RelaxNG schema.

The body of the <report_error/> element itself is an optional text string; if present, this is debugging information. At present this capabilty is not used, debugging information goes to syslog.

6.5 Additional access control considerations.

As detailed above, the publication protocol is trivially simple. This glosses over two bits of potential complexity:

- In the case where parent and child are sharing a repository, we'd like to nest child under parent, because testing has demonstrated that even on relatively slow hardware the delays involved in setting up separate rsync connections tend to dominate synchronization time for relying parties.

- The repository operator might also want to do some checks to assure itself that what it's about to allow the RPKI engine to publish is not dangerous toxic waste.

The up-down protocol includes a mechanism by which a parent can suggest a publication URI to each of its children. The children are not required to accept this hint, and the children must make separate arrangements with the repository operator (who might or might not be the same as the entity that hosts the children's RPKI engine operations) to use the suggested publication point, but if everything works out, this allows children to nest cleanly under their parents publication points, which helps reduce synchronization time for relying parties.

In this case, one could argue that the publication server is responsible for preventing one of its clients (the child in the above description) from stomping on data published by another of its clients (the parent in the above description). This goes beyond the basic access check and requires the publication server to determine whether the parent has given its consent for the child to publish under the parent. Since the RPKI certificate profile requires the child's publication point to be indicated in an SIA extension in a certificate issued by the parent to the child, the publication engine can infer this permission from the parent's issuance of a certificate to the child. Since, by definition, the parent also uses this publication server, this is an easy check, as the publication server should already have the parent's certificate available by the time it needs to check the child's certificate.

The previous paragraph only covers a "publish" action for a <certificate/> object. For "publish" actions on other objects, the publication server would need to trace permission back to the certificate issued by the parent; for "withdraw" actions, the publication server would have to perform the same checks it would perform for a "publish" action, using the current published data before withdrawing it. The latter in turn implies an ordering constraint on "withdraw" actions in order to preserve the data necessary for these access control decisions; as this may prove impractical, the publication server may probably need to make periodic sweeps over its published data looking for orphaned objects, but that's probably a good idea anyway.

Note that, in this publication model, any agreement that the repository makes to publish the RPKI engine's output is conditional upon the object to be published passing whatever access control checks the publication server imposes.

7 Namespace Documentation

7.1 Package irbe_cli

Classes

- class bsc_elt
- class certificate_elt
- class child_elt
- class client_elt
- class cmd_elt_mixin
- class cmd_msg_mixin
- class config_elt
- class crl_elt
- class left_right_cms_msg
- class left_right_msg
- class left_right_proto
- class left_right_sax_handler
- class list_published_objects_elt
- class list_received_resources_elt
- class manifest_elt
- class parent_elt
- class publication_cms_msg
- class publication_msg
- class publication_proto
- class publication_sax_handler
- class reply_elt_mixin
- class report_error_elt
- class repository_elt
- class roa_elt
- class self_elt
- class UsageWrapper

Functions

- def usage

Variables

- list argv = sys.argv[1:]
- tuple call_pubd
- tuple call_rpkid
- tuple cfg = rpki.config.parser(cfg_file, "irbe_cli")
- string cfg_file = "irbe.conf"
- pem_out = None
- q_msg = q_msg_left_right
- list q_msg_left_right = [ ]
- list q_msg_publication = [ ]
- list q_pdu = left_right_msg.pdus[argv[0]]
- list top_opts = ["config=", "help", "pem_out=", "quiet", "verbose"]
- tuple usage_fill = UsageWrapper(subsequent_indent = " " ∗ 4)
- verbose = True

7.1.1 Detailed Description

```
Command line IR back-end control program for rpkid and pubd.

$Id: irbe_cli.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.1.2 Function Documentation

7.1.2.1 def irbe_cli.usage (*code* = 1)

Definition at line 240 of file irbe_cli.py.

7.1.3 Variable Documentation

7.1.3.1 tuple irbe_cli::argv = sys.argv[1:]

Definition at line 259 of file irbe_cli.py.

7.1.3.2 tuple irbe_cli.call_pubd

Initial value:

```
rpki.async.sync_wrapper(rpki.https.caller(
    proto       = publication_proto,
    client_key  = rpki.x509.RSA( Auto_file = cfg.get("pubd-irbe-key")),
    client_cert = rpki.x509.X509(Auto_file = cfg.get("pubd-irbe-cert")),
    server_ta   = rpki.x509.X509(Auto_file = cfg.get("pubd-bpki-ta")),
    server_cert = rpki.x509.X509(Auto_file = cfg.get("pubd-cert")),
    url         = cfg.get("pubd-url")),
    debug       = verbose)
```

Definition at line 323 of file irbe_cli.py.

7.1.3.3 tuple irbe_cli.call_rpkid

Initial value:

```
rpki.async.sync_wrapper(rpki.https.caller(
    proto       = left_right_proto,
    client_key  = rpki.x509.RSA( Auto_file = cfg.get("rpkid-irbe-key")),
    client_cert = rpki.x509.X509(Auto_file = cfg.get("rpkid-irbe-cert")),
    server_ta   = rpki.x509.X509(Auto_file = cfg.get("rpkid-bpki-ta")),
    server_cert = rpki.x509.X509(Auto_file = cfg.get("rpkid-cert")),
    url         = cfg.get("rpkid-url"),
    debug       = verbose))
```

Definition at line 306 of file irbe_cli.py.

7.1.3.4 tuple irbe_cli.cfg = rpki.config.parser(cfg_file, "irbe_cli")

Definition at line 283 of file irbe_cli.py.

7.1.3.5 irbe_cli.cfg_file = "irbe.conf"

Definition at line 264 of file irbe_cli.py.

7.1.3.6 irbe_cli.pem_out = None

Definition at line 39 of file irbe_cli.py.

7.1.3.7 irbe_cli.q_msg = q_msg_left_right

Definition at line 291 of file irbe_cli.py.

7.1.3.8 list irbe_cli.q_msg_left_right = [ ]

Definition at line 285 of file irbe_cli.py.

7.1.3.9 list irbe_cli.q_msg_publication = [ ]

Definition at line 286 of file irbe_cli.py.

7.1.3.10 list irbe_cli::q_pdu = left_right_msg.pdus[argv[0]]

Definition at line 290 of file irbe_cli.py.

7.1.3.11 list irbe_cli.top_opts = ["config=", "help", "pem_out=", "quiet", "verbose"]

Definition at line 238 of file irbe_cli.py.

7.1.3.12 tuple irbe_cli.usage_fill = UsageWrapper(subsequent_indent = " " ∗ 4)

Definition at line 50 of file irbe_cli.py.

7.1.3.13 irbe_cli.verbose = True

Definition at line 265 of file irbe_cli.py.

7.2 Package irdbd

Functions

- def handle_list_resources
- def handle_list_roa_requests
- def handler

Variables

- tuple bpki_ta = rpki.x509.X509(Auto_file = cfg.get("bpki-ta"))
- tuple cfg = rpki.config.parser(cfg_file, "irdbd")
- string cfg_file = "irdbd.conf"
- tuple client_ta = (bpki_ta, rpkid_cert)
- tuple cur = db.cursor()
- tuple db
- dictionary handle_dispatch
- tuple handlers = ((u.path, handler),)
- string host = "localhost"
- tuple irdbd_cert = rpki.x509.X509(Auto_file = cfg.get("irdbd-cert"))
- tuple irdbd_key = rpki.x509.RSA(Auto_file = cfg.get("irdbd-key"))
- int port = 443
- tuple rpkid_cert = rpki.x509.X509(Auto_file = cfg.get("rpkid-cert"))
- server_cert = irdbd_cert,

- tuple startup_msg = cfg.get("startup-message", "")
- tuple u = urlparse.urlparse(cfg.get("https-url"))

7.2.1 Detailed Description

```
IR database daemon.

Usage: python irdbd.py [ { -c | --config } configfile ] [ { -h | --help } ]

Default configuration file is irdbd.conf, override with --config option.

$Id: irdbd.py 2913 2009-12-28 20:55:38Z sra $

Copyright (C) 2009  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.2.2 Function Documentation

7.2.2.1 def irdbd.handle_list_resources (*q_pdu*, *r_msg*)

Definition at line 53 of file irdbd.py.

7.2.2.2 def irdbd.handle_list_roa_requests (*q_pdu*, *r_msg*)

Definition at line 90 of file irdbd.py.

7.2.2.3 def irdbd.handler (*query*, *path*, *cb*)

Definition at line 119 of file irdbd.py.

7.2.3 Variable Documentation

7.2.3.1 tuple irdbd.bpki_ta = rpki.x509.X509(Auto_file = cfg.get("bpki-ta"))

Definition at line 201 of file irdbd.py.

7.2.3.2 tuple irdbd.cfg = rpki.config.parser(cfg_file, "irdbd")

Definition at line 186 of file irdbd.py.

7.2.3.3 irdbd.cfg_file = "irdbd.conf"

Definition at line 170 of file irdbd.py.

7.2.3.4 tuple irdbd.client_ta = (bpki_ta, rpkid_cert)

Definition at line 217 of file irdbd.py.

7.2.3.5 tuple irdbd.cur = db.cursor()

Definition at line 198 of file irdbd.py.

7.2.3.6 tuple irdbd.db

Initial value:

```
MySQLdb.connect(user   = cfg.get("sql-username"),
                     db     = cfg.get("sql-database"),
                     passwd = cfg.get("sql-password"))
```

Definition at line 194 of file irdbd.py.

7.2.3.7 dictionary irdbd.handle_dispatch

Initial value:

```
{
  rpki.left_right.list_resources_elt : handle_list_resources,
  rpki.left_right.list_roa_requests_elt : handle_list_roa_requests }
```

Definition at line 115 of file irdbd.py.

7.2.3.8 tuple irdbd.handlers = ((u.path, handler),)

Definition at line 220 of file irdbd.py.

7.2.3.9 string irdbd.host = "localhost"

Definition at line 218 of file irdbd.py.

7.2.3.10 tuple irdbd.irdbd_cert = rpki.x509.X509(Auto_file = cfg.get("irdbd-cert"))

Definition at line 203 of file irdbd.py.

7.2.3.11 tuple irdbd.irdbd_key = rpki.x509.RSA(Auto_file = cfg.get("irdbd-key"))

Definition at line 204 of file irdbd.py.

7.2.3.12 int irdbd.port = 443

Definition at line 219 of file irdbd.py.

7.2.3.13 tuple irdbd.rpkid_cert = rpki.x509.X509(Auto_file = cfg.get("rpkid-cert"))

Definition at line 202 of file irdbd.py.

7.2.3.14 irdbd.server_cert = irdbd_cert,

Definition at line 216 of file irdbd.py.

7.2.3.15 tuple irdbd.startup_msg = cfg.get("startup-message", "")

Definition at line 188 of file irdbd.py.

7.2.3.16 tuple irdbd.u = urlparse.urlparse(cfg.get("https-url"))

Definition at line 206 of file irdbd.py.

7.3 Package pubd

Classes

- class pubd_context

Functions

- def main

Variables

- string cfg_file = "pubd.conf"
- profile = False

7.3.1 Detailed Description

```
RPKI publication engine.

Usage: python pubd.py [ { -c | --config } configfile ]
                    [ { -h | --help } ]
                    [ { -p | --profile } outputfile ]

Default configuration file is pubd.conf, override with --config option.

$Id: pubd.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.3.2 Function Documentation

7.3.2.1 def pubd.main ()

Definition at line 174 of file pubd.py.

7.3.3 Variable Documentation

7.3.3.1 pubd.cfg_file = "pubd.conf"

Definition at line 155 of file pubd.py.

7.3.3.2 pubd.profile = False

Definition at line 156 of file pubd.py.

7.4 Package rootd

Classes

- class cms_msg
- class issue_pdu
- class list_pdu
- class message_pdu
- class revoke_pdu
- class sax_handler

Functions

- def compose_response
- def del_subject_cert
- def del_subject_pkcs10
- def get_root_cert
- def get_subject_cert
- def get_subject_pkcs10
- def issue_subject_cert_maybe
- def root_newer_than_subject
- def set_subject_cert
- def set_subject_pkcs10
- def up_down_handler

Variables

- tuple bpki_ta = rpki.x509.X509(Auto_file = cfg.get("bpki-ta"))
- tuple cfg = rpki.config.parser(cfg_file, "rootd")
- string cfg_file = "rootd.conf"
- tuple child_bpki_cert = rpki.x509.X509(Auto_file = cfg.get("child-bpki-cert"))
- tuple client_ta = (bpki_ta, child_bpki_cert)
- handlers = up_down_handler)
- host = https_server_host,
- tuple https_server_host = cfg.get("server-host", "")
- tuple https_server_port = int(cfg.get("server-port"))
- port = https_server_port,
- tuple rootd_bpki_cert = rpki.x509.X509(Auto_file = cfg.get("rootd-bpki-cert"))
- tuple rootd_bpki_crl = rpki.x509.CRL(Auto_file = cfg.get("rootd-bpki-crl"))
- tuple rootd_bpki_key = rpki.x509.RSA(Auto_file = cfg.get("rootd-bpki-key"))
- tuple rpki_base_uri = cfg.get("rpki-base-uri", "rsync://" + rpki_class_name + ".invalid/")
- tuple rpki_class_name = cfg.get("rpki-class-name", "wombat")
- rpki_root_cert = None
- tuple rpki_root_cert_file = cfg.get("rpki-root-cert")
- tuple rpki_root_cert_uri = cfg.get("rpki-root-cert-uri", rpki_base_uri + "Root.cer")
- tuple rpki_root_crl = cfg.get("rpki-root-crl", "Root.crl")
- tuple rpki_root_dir = cfg.get("rpki-root-dir")
- tuple rpki_root_key = rpki.x509.RSA(Auto_file = cfg.get("rpki-root-key"))
- tuple rpki_root_manifest = cfg.get("rpki-root-manifest", "Root.mnf")
- tuple rpki_subject_cert = cfg.get("rpki-subject-cert", "Child.cer")
- tuple rpki_subject_lifetime = rpki.sundial.timedelta.parse(cfg.get("rpki-subject-lifetime", "30d"))
- tuple rpki_subject_pkcs10 = cfg.get("rpki-subject-pkcs10", "Child.pkcs10")
- tuple rpki_subject_regen = rpki.sundial.timedelta.parse(cfg.get("rpki-subject-regen", rpki_subject_lifetime.convert_to_seconds() / 2))
- server_cert = rootd_bpki_cert,

7.4.1 Detailed Description

```
Trivial RPKI up-down protocol root server, for testing.  Not suitable
for production use.  Overrides a bunch of method definitions from the
rpki.* classes in order to reuse as much code as possible.

Usage: python rootd.py [ { -c | --config } configfile ] [ { -h | --help } ]

Default configuration file is rootd.conf, override with --config option.

$Id: rootd.py 2913 2009-12-28 20:55:38Z sra $
```

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

7.4.2 Function Documentation

7.4.2.1 def rootd.compose_response (*r_msg*, *pkcs10* = `None`)

Definition at line 175 of file rootd.py.

7.4.2.2 def rootd.del_subject_cert ()

Definition at line 72 of file rootd.py.

7.4.2.3 def rootd.del_subject_pkcs10 ()

Definition at line 91 of file rootd.py.

7.4.2.4 def rootd.get_root_cert ()

Definition at line 48 of file rootd.py.

7.4.2.5 def rootd.get_subject_cert ()

Definition at line 56 of file rootd.py.

7.4.2.6 def rootd.get_subject_pkcs10 ()

Definition at line 77 of file rootd.py.

7.4.2.7 def rootd.issue_subject_cert_maybe (*new_pkcs10*)

Definition at line 98 of file rootd.py.

7.4.2.8 def rootd.root_newer_than_subject ()

Definition at line 53 of file rootd.py.

7.4.2.9 def rootd.set_subject_cert (*cert*)

Definition at line 65 of file rootd.py.

7.4.2.10 def rootd.set_subject_pkcs10 (*pkcs10*)

Definition at line 85 of file rootd.py.

7.4.2.11 def rootd.up_down_handler (*query*, *path*, *cb*)

Definition at line 238 of file rootd.py.

7.4.3 Variable Documentation

7.4.3.1 tuple rootd.bpki_ta = rpki.x509.X509(Auto_file = cfg.get("bpki-ta"))

Definition at line 288 of file rootd.py.

7.4.3.2 tuple rootd.cfg = rpki.config.parser(cfg_file, "rootd")

Definition at line 284 of file rootd.py.

7.4.3.3 rootd.cfg_file = "rootd.conf"

Definition at line 268 of file rootd.py.

7.4.3.4 tuple rootd.child_bpki_cert = rpki.x509.X509(Auto_file = cfg.get("child-bpki-cert"))

Definition at line 292 of file rootd.py.

7.4.3.5 tuple rootd.client_ta = (bpki_ta, child_bpki_cert)

Definition at line 316 of file rootd.py.

7.4.3.6 rootd.handlers = up_down_handler)

Definition at line 319 of file rootd.py.

7.4.3.7 rootd.host = https_server_host,

Definition at line 317 of file rootd.py.

7.4.3.8 tuple rootd.https_server_host = cfg.get("server-host", "")

Definition at line 294 of file rootd.py.

7.4.3.9 tuple rootd.https_server_port = int(cfg.get("server-port"))

Definition at line 295 of file rootd.py.

7.4.3.10 rootd.port = https_server_port,

Definition at line 318 of file rootd.py.

7.4.3.11 tuple rootd.rootd_bpki_cert = rpki.x509.X509(Auto_file = cfg.get("rootd-bpki-cert"))

Definition at line 290 of file rootd.py.

7.4.3.12 tuple rootd.rootd_bpki_crl = rpki.x509.CRL(Auto_file = cfg.get("rootd-bpki-crl"))

Definition at line 291 of file rootd.py.

7.4.3.13 tuple rootd.rootd_bpki_key = rpki.x509.RSA(Auto_file = cfg.get("rootd-bpki-key"))

Definition at line 289 of file rootd.py.

7.4.3.14 tuple rootd.rpki_base_uri = cfg.get("rpki-base-uri", "rsync://" + rpki_class_name + ".invalid/")

Definition at line 300 of file rootd.py.

7.4.3.15 tuple rootd.rpki_class_name = cfg.get("rpki-class-name", "wombat")

Definition at line 297 of file rootd.py.

7.4.3.16 rootd.rpki_root_cert = None

Definition at line 46 of file rootd.py.

7.4.3.17 tuple rootd.rpki_root_cert_file = cfg.get("rpki-root-cert")

Definition at line 303 of file rootd.py.

7.4.3.18 tuple rootd.rpki_root_cert_uri = cfg.get("rpki-root-cert-uri", rpki_base_uri + "Root.cer")

Definition at line 304 of file rootd.py.

7.4.3.19 tuple rootd.rpki_root_crl = cfg.get("rpki-root-crl", "Root.crl")

Definition at line 307 of file rootd.py.

7.4.3.20 tuple rootd.rpki_root_dir = cfg.get("rpki-root-dir")

Definition at line 299 of file rootd.py.

7.4.3.21 tuple rootd.rpki_root_key = rpki.x509.RSA(Auto_file = cfg.get("rpki-root-key"))

Definition at line 302 of file rootd.py.

7.4.3.22 tuple rootd.rpki_root_manifest = cfg.get("rpki-root-manifest", "Root.mnf")

Definition at line 306 of file rootd.py.

7.4.3.23 tuple rootd.rpki_subject_cert = cfg.get("rpki-subject-cert", "Child.cer")

Definition at line 308 of file rootd.py.

7.4.3.24 tuple rootd.rpki_subject_lifetime = rpki.sundial.timedelta.parse(cfg.get("rpki-subject-lifetime", "30d"))

Definition at line 311 of file rootd.py.

7.4.3.25 tuple rootd.rpki_subject_pkcs10 = cfg.get("rpki-subject-pkcs10", "Child.pkcs10")

Definition at line 309 of file rootd.py.

7.4.3.26 tuple rootd.rpki_subject_regen = rpki.sundial.timedelta.parse(cfg.get("rpki-subject-regen", rpki_subject_lifetime.convert_to_seconds() / 2))

Definition at line 312 of file rootd.py.

7.4.3.27 rootd.server_cert = rootd_bpki_cert,

Definition at line 315 of file rootd.py.

7.5 Package rpki

Packages

- package async
- package cli
- package config
- package exceptions
- package https
- package ipaddrs
- package left_right
- package log
- package manifest
- package oids
- package publication
- package relaxng
- package resource_set
- package roa
- package rpki_engine
- package sql
- package sundial
- package up_down
- package x509
- package xml_utils

7.6 Package rpki.async

Classes

- class gc_summary
- class iterator
- class sync_wrapper
- class timer

Functions

- def _raiseExitNow
- def defer
- def event_loop
- def exit_event_loop
- def run_deferred

Variables

- list deferred_queue = [ ]

  List to hold deferred actions.

- ExitNow = asyncore.ExitNow

7.6.1 Detailed Description

```
Utilities for event-driven programming.

$Id: async.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.6.2 Function Documentation

7.6.2.1 def rpki.async._raiseExitNow (*signum*, *frame*) [private]

```
Signal handler for event_loop().
```

Definition at line 267 of file async.py.

7.6.2.2 def rpki.async.defer (*thunk*)

```
Defer an action until the next pass through the event loop.
```

Definition at line 248 of file async.py.

7.6.2.3 def rpki.async.event_loop (*catch_signals* = (signal.SIGINT, signal.SIGTERM))

```
Replacement for asyncore.loop(), adding timer and signal support.
```

Definition at line 271 of file async.py.

7.6.2.4 def rpki.async.exit_event_loop ()

```
Force exit from event_loop().
```

Definition at line 350 of file async.py.

7.6.2.5 def rpki.async.run_deferred ()

```
Run deferred actions.
```

Definition at line 254 of file async.py.

7.6.3 Variable Documentation

7.6.3.1 rpki::async::deferred_queue = [ ]

List to hold deferred actions.

We used to do this with the timer queue, but that appears to confuse the garbage collector, and is overengineering for simple deferred actions in any case.

Definition at line 246 of file async.py.

7.6.3.2 rpki::async.ExitNow = asyncore.ExitNow

Definition at line 24 of file async.py.

7.7 Package rpki.cli

Classes

- class Cmd

Functions

- def yes_or_no

Variables

- dictionary _yes_or_no_prompts
- have_readline = True

7.7.1 Detailed Description

```
Utilities for writing command line tools.

$Id: cli.py 3074 2010-03-11 04:29:24Z sra $

Copyright (C) 2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.7.2 Function Documentation

7.7.2.1 def rpki.cli.yes_or_no (*prompt*, *default* = `None`, *require_full_word* = `False`)

```
Ask a yes-or-no question.
```

Definition at line 122 of file cli.py.

7.7.3 Variable Documentation

7.7.3.1 dictionary rpki::cli._yes_or_no_prompts

Initial value:

```
{
  True  : ' ("yes" or "no" ["yes"]) ',
  False : ' ("yes" or "no" ["no"]) ',
  None  : ' ("yes" or "no") ' }
```

Definition at line 137 of file cli.py.

7.7.3.2 rpki::cli.have_readline = True

Definition at line 25 of file cli.py.

7.8 Package rpki.config

Classes

- class parser

7.8.1 Detailed Description

```
Configuration file parsing utilities, layered on top of stock Python
ConfigParser module.

$Id: config.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
```

PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

7.9 Package rpki.exceptions

Classes

- class BadClassNameSyntax
- class BadClientURL
- class BadContactURL
- class BadExtension
- class BadIRDBReply
- class BadIssueResponse
- class BadPKCS10
- class BadPublicationReply
- class BadQuery
- class BadSender
- class BadStatusCode
- class BadURISyntax
- class BSCNotFound
- class BSCNotReady
- class ChildNotFound
- class ClassNameMismatch
- class ClassNameUnknown
- class ClientNotFound
- class CMSContentNotSet
- class CMSCRLNotSet
- class CMSVerificationFailed
- class DBConsistancyError
- class DERObjectConversionError
- class DuplicateObject
- class EmptyPEM
- class EmptyROAPrefixList

- class ForbiddenURI
- class HandleTranslationError
- class HTTPRequestFailed
- class HTTPSBadVersion
- class HTTPSClientAborted
- class HTTPSUnexpectedState
- class MissingCMSCRL
- class MissingCMSEEcert
- class MultipleTLSEECert
- class MustBePrefix
- class NoActiveCA
- class NoCoveringCertForROA
- class NoObjectAtURI
- class NotACertificateChain
- class NotFound
- class NotImplementedYet
- class NotInDatabase
- class ReceivedTLSCACert
- class RPKI_Exception
- class ServerShuttingDown
- class SKIMismatch
- class SubprocessError
- class TLSValidationError
- class UnexpectedCMSCerts
- class UnexpectedCMSCRLs
- class UnparsableCMSDER
- class UpstreamError
- class WrongEContentType

7.9.1 Detailed Description

```
Exception definitions for RPKI modules.

$Id: exceptions.py 2907 2009-12-23 20:48:19Z sra $

Copyright (C) 2009  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
```

OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

7.10 Package rpki.https

Classes

- class caller
- class http_client
- class http_listener
- class http_message
- class http_queue
- class http_request
- class http_response
- class http_server
- class http_stream

Functions

- def build_https_ta_cache
- def client
- def log_method
- def server

Variables

- dictionary client_queues = { }
- debug_http = False
- debug_tls_certs = False
- tuple default_client_timeout = rpki.sundial.timedelta(minutes = 15)
- tuple default_http_version = (1, 0)
- tuple default_server_timeout = rpki.sundial.timedelta(minutes = 20)

- string rpki_content_type = "application/x-rpki"
- tuple supported_address_families = (socket.AF_INET, socket.AF_INET6)
- want_persistent_client = False
- want_persistent_server = False

7.10.1 Detailed Description

```
HTTPS utilities, both client and server.

$Id: https.py 3131 2010-03-23 02:53:04Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.10.2 Function Documentation

7.10.2.1 def rpki.https.build_https_ta_cache (*certs*)

```
Package up a collection of certificates into a form suitable for use
as a dynamic HTTPS trust anchor set.  Precise format of this
collection is an internal conspiracy within the rpki.https module;
at one point it was a POW.X509Store object, at the moment it's a
Python set, what it will be tomorow is nobody else's business.
```

Definition at line 794 of file https.py.

7.10.2.2 def rpki.https.client (*msg*, *client_key*, *client_cert*, *server_ta*, *url*, *callback*, *errback*)

```
Open client HTTPS connection, send a message, set up callbacks to
handle response.
```

Definition at line 734 of file https.py.

7.10.2.3 def rpki.https.log_method (*self*, *msg*, *logger* = rpki.log.debug)

Definition at line 183 of file https.py.

7.10.2.4 def rpki.https.server (*handlers*, *server_key*, *server_cert*, *port*, *host* = `""`, *client_ta* = `()`, *dynamic_https_trust_anchor* = `None`, *address_families* = `supported_address_families`)

```
Run an HTTPS server and wait (forever) for connections.
```

Definition at line 779 of file https.py.

7.10.3 Variable Documentation

7.10.3.1 dictionary rpki::https.client_queues = {}

Definition at line 732 of file https.py.

7.10.3.2 rpki::https.debug_http = False

Definition at line 45 of file https.py.

7.10.3.3 rpki::https.debug_tls_certs = False

Definition at line 48 of file https.py.

7.10.3.4 tuple rpki::https.default_client_timeout = rpki.sundial.timedelta(minutes = 15)

Definition at line 58 of file https.py.

7.10.3.5 tuple rpki::https.default_http_version = (1, 0)

Definition at line 61 of file https.py.

7.10.3.6 tuple rpki::https.default_server_timeout = rpki.sundial.timedelta(minutes = 20)

Definition at line 59 of file https.py.

7.10.3.7 string rpki::https.rpki_content_type = "application/x-rpki"

Definition at line 39 of file https.py.

7.10.3.8 tuple rpki::https::supported_address_families = (socket.AF_INET, socket.AF_INET6)

Definition at line 73 of file https.py.

7.10.3.9 rpki::https.want_persistent_client = False

Definition at line 51 of file https.py.

7.10.3.10 rpki::https.want_persistent_server = False

Definition at line 52 of file https.py.

7.11 Package rpki.ipaddrs

Classes

- class v4addr
- class v6addr

7.11.1 Detailed Description

```
Classes to represent IP addresses.

Given some of the other operations we need to perform on them, it's
most convenient to represent IP addresses as Python "long" values.
The classes in this module just wrap suitable read/write syntax around
the underlying "long" type.

These classes also supply a "bits" attribute for use by other code
built on these classes; for the most part, IPv6 addresses really are
just IPv4 addresses with more bits, so we supply the number of bits
once, here, thus avoiding a lot of duplicate code elsewhere.

$Id: ipaddrs.py 2424 2009-05-11 06:37:32Z sra $

Copyright (C) 2009  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.12 Package rpki.left_right

Classes

- class bsc_elt
- class child_elt
- class cms_msg
- class data_elt
- class left_right_namespace
- class list_published_objects_elt
- class list_received_resources_elt
- class list_resources_elt
- class list_roa_requests_elt
- class msg
- class parent_elt
- class report_error_elt
- class repository_elt
- class sax_handler
- class self_elt

Variables

- enforce_strict_up_down_xml_sender = False

7.12.1 Detailed Description

```
RPKI "left-right" protocol.

$Id: left_right.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
```

copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

7.12.2 Variable Documentation

7.12.2.1 rpki::left_right.enforce_strict_up_down_xml_sender = False

Definition at line 40 of file left_right.py.

7.13 Package rpki.log

Classes

- class logger

Functions

- def init
- def set_trace
- def trace
- def traceback

Variables

- tuple debug = logger(syslog.LOG_DEBUG)
- enable_trace = False

  Whether call tracing is enabled.

- tuple error = logger(syslog.LOG_ERR)
- tuple info = logger(syslog.LOG_INFO)
- tuple note = logger(syslog.LOG_NOTICE)
- int pid = 0
- string tag = ""
- use_syslog = True

  Whether to use syslog.

- tuple warn = logger(syslog.LOG_WARNING)

7.13.1 Detailed Description

```
Logging facilities for RPKI libraries.

$Id: log.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.13.2 Function Documentation

7.13.2.1 def rpki.log.init (*ident* = `"rpki"`, *flags* = `syslog.LOG_PID`, *facility* = `syslog.LOG_DAEMON`)

```
Initialize logging system.
```

Definition at line 51 of file log.py.

7.13.2.2 def rpki.log.set_trace (*enable*)

```
Enable or disable call tracing.
```

Definition at line 63 of file log.py.

7.13.2.3 def rpki.log.trace ()

```
Execution trace -- where are we now, and whence came we here?
```

Definition at line 91 of file log.py.

7.13.2.4 def rpki.log.traceback ()

```
Consolidated backtrace facility with a bit of extra info.
```

Definition at line 100 of file log.py.

7.13.3 Variable Documentation

7.13.3.1 tuple rpki::log.debug = logger(syslog.LOG_DEBUG)

Definition at line 89 of file log.py.

7.13.3.2 rpki::log::enable_trace = False

Whether call tracing is enabled.

Definition at line 41 of file log.py.

7.13.3.3 tuple rpki::log.error = logger(syslog.LOG_ERR)

Definition at line 85 of file log.py.

7.13.3.4 tuple rpki::log.info = logger(syslog.LOG_INFO)

Definition at line 88 of file log.py.

7.13.3.5 tuple rpki::log.note = logger(syslog.LOG_NOTICE)

Definition at line 87 of file log.py.

7.13.3.6 int rpki::log.pid = 0

Definition at line 49 of file log.py.

7.13.3.7 string rpki::log.tag = ""

Definition at line 48 of file log.py.

7.13.3.8 rpki::log::use_syslog = True

Whether to use syslog.

Definition at line 46 of file log.py.

7.13.3.9 tuple rpki::log.warn = logger(syslog.LOG_WARNING)

Definition at line 86 of file log.py.

7.14 Package rpki.manifest

Classes

- class FileAndHash
- class FilesAndHashes
- class Manifest

7.14.1 Detailed Description

```
Signed manifests.  This is just the ASN.1 encoder, the rest is in
rpki.x509 with the rest of the DER_object code.

Note that rpki.x509.SignedManifest implements the signed manifest;
the structures here are just the payload of the CMS eContent field.

$Id: manifest.py 2424 2009-05-11 06:37:32Z sra $

Copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.15 Package rpki.oids

Variables

- tuple name2oid = dict((v, k) for k, v in oid2name.items())

  Mapping table of string names to OIDs.

- dictionary oid2name

  Mapping table of OIDs to conventional string names.

7.15.1 Detailed Description

```
OID database.

$Id: oids.py 2424 2009-05-11 06:37:32Z sra $

Copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
```

```
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.15.2 Variable Documentation

7.15.2.1 rpki::oids::name2oid = dict((v, k) for k, v in oid2name.items())

Mapping table of string names to OIDs.

Definition at line 58 of file oids.py.

7.15.2.2 rpki::oids::oid2name

Initial value:

```
{
  (1, 2, 840, 113549, 1, 1, 11)         : "sha256WithRSAEncryption",
  (1, 2, 840, 113549, 1, 1, 12)         : "sha384WithRSAEncryption",
  (1, 2, 840, 113549, 1, 1, 13)         : "sha512WithRSAEncryption",
  (1, 2, 840, 113549, 1, 7,  1)         : "id-data",
  (1, 2, 840, 113549, 1, 9, 16)         : "id-smime",
  (1, 2, 840, 113549, 1, 9, 16, 1)      : "id-ct",
  (1, 2, 840, 113549, 1, 9, 16, 1, 24)  : "id-ct-routeOriginAttestation",
  (1, 2, 840, 113549, 1, 9, 16, 1, 26)  : "id-ct-rpkiManifest",
  (1, 2, 840, 113549, 1, 9, 16, 1, 28)  : "id-ct-xml",
  (1, 3, 6, 1, 5, 5, 7, 1, 1)           : "authorityInfoAccess",
  (1, 3, 6, 1, 5, 5, 7, 1, 11)          : "subjectInfoAccess",
  (1, 3, 6, 1, 5, 5, 7, 1, 7)           : "sbgp-ipAddrBlock",
  (1, 3, 6, 1, 5, 5, 7, 1, 8)           : "sbgp-autonomousSysNum",
  (1, 3, 6, 1, 5, 5, 7, 14, 2)          : "id-cp-ipAddr-asNumber",
  (1, 3, 6, 1, 5, 5, 7, 48, 2)          : "id-ad-caIssuers",
  (1, 3, 6, 1, 5, 5, 7, 48, 5)          : "id-ad-caRepository",
  (1, 3, 6, 1, 5, 5, 7, 48, 9)          : "id-ad-signedObjectRepository",
  (1, 3, 6, 1, 5, 5, 7, 48, 10)         : "id-ad-rpkiManifest",
  (1, 3, 6, 1, 5, 5, 7, 48, 11)         : "id-ad-signedObject",
  (2, 16, 840, 1, 101, 3, 4, 2, 1)      : "id-sha256",
  (2, 5, 29, 14)                        : "subjectKeyIdentifier",
  (2, 5, 29, 15)                        : "keyUsage",
  (2, 5, 29, 19)                        : "basicConstraints",
  (2, 5, 29, 20)                        : "cRLNumber",
  (2, 5, 29, 31)                        : "cRLDistributionPoints",
  (2, 5, 29, 32)                        : "certificatePolicies",
  (2, 5, 29, 35)                        : "authorityKeyIdentifier",
  (2, 5, 4, 3)                          : "commonName",
}
```

Mapping table of OIDs to conventional string names.

Definition at line 24 of file oids.py.

7.16 Package rpki.publication

Classes

- class certificate_elt
- class client_elt
- class cms_msg
- class config_elt
- class control_elt
- class crl_elt
- class manifest_elt
- class msg
- class publication_namespace
- class publication_object_elt
- class report_error_elt
- class roa_elt
- class sax_handler

7.16.1 Detailed Description

```
RPKI "publication" protocol.

$Id: publication.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.17 Package rpki.relaxng

Variables

- tuple left_right

  Parsed RelaxNG left_right schema.

- tuple publication

  Parsed RelaxNG publication schema.

- tuple up_down

  Parsed RelaxNG up_down schema.

7.17.1 Variable Documentation

7.17.1.1 rpki::relaxng::left_right

Parsed RelaxNG left_right schema.

Definition at line 7 of file relaxng.py.

7.17.1.2 rpki::relaxng::publication

Parsed RelaxNG publication schema.

Definition at line 1252 of file relaxng.py.

7.17.1.3 rpki::relaxng::up_down

Parsed RelaxNG up_down schema.

Definition at line 998 of file relaxng.py.

7.18 Package rpki.resource_set

Classes

- class resource_bag

- class resource_range
- class resource_range_as
- class resource_range_ip
- class resource_range_ipv4
- class resource_range_ipv6
- class resource_set
- class resource_set_as
- class resource_set_ip
- class resource_set_ipv4
- class resource_set_ipv6
- class roa_prefix
- class roa_prefix_ipv4
- class roa_prefix_ipv6
- class roa_prefix_set
- class roa_prefix_set_ipv4
- class roa_prefix_set_ipv6

Functions

- def _bs2long
- def _long2bs
- def _rsplit
- def test1
- def test2

Variables

- string inherit_token = "<inherit>"

  Token used to indicate inheritance in read and print syntax.

7.18.1 Detailed Description

```
Classes dealing with sets of resources.

The basic mechanics of a resource set are the same for any of the
resources we handle (ASNs, IPv4 addresses, or IPv6 addresses), so we
can provide the same operations on any of them, even though the
underlying details vary.

We also provide some basic set operations (union, intersection, etc).

$Id: resource_set.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")
```

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

7.18.2 Function Documentation

7.18.2.1 def rpki.resource_set._bs2long (*bs*, *addrlen*, *fill*) [private]

```
Utility function to convert a bitstring (POW.pkix tuple
representation) into a Python long.
```

Definition at line 514 of file resource_set.py.

7.18.2.2 def rpki.resource_set._long2bs (*number*, *addrlen*, *prefixlen* = None, *strip* = None) [private]

```
Utility function to convert a Python long into a POW.pkix tuple
bitstring. This is a bit complicated because it supports the
fiendishly compact encoding used in RFC 3779.
```

Definition at line 526 of file resource_set.py.

7.18.2.3 def rpki.resource_set._rsplit (*rset*, *that*) [private]

```
Utility function to split a resource range into two resource ranges.
```

Definition at line 190 of file resource_set.py.

7.18.2.4 def rpki.resource_set.test1 (*t*, *s1*, *s2*)

Definition at line 884 of file resource_set.py.

7.18.2.5 def rpki.resource_set.test2 (*t*, *s1*, *s2*)

Definition at line 917 of file resource_set.py.

7.18.3 Variable Documentation

7.18.3.1 rpki::resource_set::inherit_token = "<inherit>"

Token used to indicate inheritance in read and print syntax.

Definition at line 48 of file resource_set.py.

7.19 Package rpki.roa

Classes

- class ROAIPAddress
- class ROAIPAddresses
- class ROAIPAddressFamilies
- class ROAIPAddressFamily
- class RouteOriginAttestation

7.19.1 Detailed Description

```
ROA (Route Origin Authorization).
```

```
At the moment this is just the ASN.1 encoder.

This corresponds to draft-ietf-sidr-roa-format, which is a work in
progress, so this may need updating later.

$Id: roa.py 2424 2009-05-11 06:37:32Z sra $

Copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

draft-ietf-sidr-roa-format-03 2.1.3.2 specifies:

   RouteOriginAttestation ::= SEQUENCE {
      version [0] INTEGER DEFAULT 0,
      asID  ASID,
      ipAddrBlocks SEQUENCE OF ROAIPAddressFamily }

   ASID ::= INTEGER

   ROAIPAddressFamily ::= SEQUENCE {
      addressFamily OCTET STRING (SIZE (2..3)),
      addresses SEQUENCE OF ROAIPAddress }

   ROAIPAddress ::= SEQUENCE {
      address IPAddress,
      maxLength INTEGER OPTIONAL }

   IPAddress ::= BIT STRING
```

7.20 Package rpki.rpki_engine

Classes

- class ca_detail_obj
- class ca_obj
- class child_cert_obj
- class publication_queue
- class revoked_cert_obj
- class roa_obj
- class rpkid_context

7.20.1 Detailed Description

```
Global context for rpkid.

$Id: rpki_engine.py 3107 2010-03-16 23:13:08Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.21 Package rpki.sql

Classes

- class session
- class sql_persistent
- class template

7.21.1 Detailed Description

```
SQL interface code.

$Id: sql.py 2895 2009-12-21 17:17:55Z sra $

Copyright (C) 2009  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
```

copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

7.22 Package rpki.sundial

Classes

- class datetime
- class timedelta

Functions

- def _cast
- def now
- def test

7.22.1 Detailed Description

Unified RPKI date/time handling, based on the standard Python datetime module.

Module name chosen to sidestep a nightmare of import-related errors
that occur with the more obvious module names.

List of arithmetic methods that require result casting was derived by
inspection of the datetime module, to wit:

```
>>> import datetime
>>> for t in (datetime.datetime, datetime.timedelta):
...  for k in t.__dict__.keys():
```

```
  ...   if k.startswith("__"):
  ...    print "%s.%s()" % (t.__name__, k)
```

```
$Id: sundial.py 3107 2010-03-16 23:13:08Z sra $
```


```
Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```


7.22.2 Function Documentation

7.22.2.1 def rpki.sundial._cast (*x*) [private]

```
Cast result of arithmetic operations back into correct subtype.
```

Definition at line 257 of file sundial.py.

7.22.2.2 def rpki.sundial.now ()

```
Get current timestamp.
```

Definition at line 50 of file sundial.py.

7.22.2.3 def rpki.sundial.test (*t*)

Definition at line 269 of file sundial.py.

7.23 Package rpki.up_down

Classes

- class base_elt
- class certificate_elt
- class class_elt
- class class_response_syntax
- class cms_msg
- class error_response_pdu
- class issue_pdu
- class issue_response_pdu
- class list_pdu
- class list_response_pdu
- class message_pdu
- class multi_uri
- class revoke_pdu
- class revoke_response_pdu
- class revoke_syntax
- class sax_handler

Variables

- dictionary nsmap = { None : xmlns }
- string xmlns = "http://www.apnic.net/specs/rescerts/up-down/"

7.23.1 Detailed Description

```
RPKI "up-down" protocol.

$Id: up_down.py 3144 2010-03-28 06:20:25Z sra $

Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
```

```
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.23.2 Variable Documentation

7.23.2.1 dictionary rpki::up_down.nsmap = { None : xmlns }

Definition at line 41 of file up_down.py.

7.23.2.2 string rpki::up_down.xmlns = "http://www.apnic.net/specs/rescerts/up-down/"

Definition at line 39 of file up_down.py.

7.24 Package rpki.x509

Classes

- class CMS_object
- class CRL
- class DeadDrop
- class DER_CMS_object
- class DER_object
- class PEM_converter
- class PKCS10
- class ROA

- class RSA
- class RSApublic
- class SignedManifest
- class X509
- class XML_CMS_object

Functions

- def _find_xia_uri
- def calculate_SKI
- def POWify_OID

7.24.1 Detailed Description

```
One X.509 implementation to rule them all...

...and in the darkness hide the twisty maze of partially overlapping
X.509 support packages in Python.

There are several existing packages, none of which do quite what I
need, due to age, lack of documentation, specialization, or lack of
foresight on somebody's part (perhaps mine).  This module attempts to
bring together the functionality I need in a way that hides at least
some of the nasty details.  This involves a lot of format conversion.

$Id: x509.py 3107 2010-03-16 23:13:08Z sra $


Copyright (C) 2009-2010  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.


Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
```

```
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.24.2 Function Documentation

7.24.2.1 def rpki.x509._find_xia_uri (*extension*, *name*) [private]

```
Find a rsync URI in an SIA or AIA extension.
Returns the URI if found, otherwise None.
```

Definition at line 105 of file x509.py.

7.24.2.2 def rpki.x509.calculate_SKI (*public_key_der*)

```
Calculate the SKI value given the DER representation of a public
key, which requires first peeling the ASN.1 wrapper off the key.
```

Definition at line 51 of file x509.py.

7.24.2.3 def rpki.x509.POWify_OID (*oid*)

```
Utility function to convert tuple form of an OID to the
dotted-decimal string form that POW uses.
```

Definition at line 725 of file x509.py.

7.25 Package rpki.xml_utils

Classes

- class base_elt
- class data_elt
- class msg
- class sax_handler
- class text_elt

7.25.1 Detailed Description

```
XML utilities.

$Id: xml_utils.py 2836 2009-10-26 22:31:16Z sra $

Copyright (C) 2009  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.26 Package rpkid

Functions

- def main

Variables

- string cfg_file = "rpkid.conf"
- profile = None

7.26.1 Detailed Description

```
RPKI engine daemon.  This is still very much a work in progress.

Usage: python rpkid.py [ { -c | --config } configfile ]
                    [ { -h | --help } ]
```

```
                  [ { -p | --profile } outputfile ]

Default configuration file is rpkid.conf, override with --config option.

$Id: rpkid.py 2913 2009-12-28 20:55:38Z sra $

Copyright (C) 2009  Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008  American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS.  IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
```

7.26.2 Function Documentation

7.26.2.1 def rpkid.main ()

Definition at line 68 of file rpkid.py.

7.26.3 Variable Documentation

7.26.3.1 rpkid.cfg_file = "rpkid.conf"

Definition at line 49 of file rpkid.py.

7.26.3.2 rpkid.profile = None

Definition at line 50 of file rpkid.py.

8 Class Documentation

8.1 async_chat Class Reference

Inherited by rpki.https.http_stream.

The documentation for this class was generated from the following file:

- https.py (3131)

8.2 dispatcher Class Reference

Inherited by rpki.https.http_listener.

The documentation for this class was generated from the following file:

- https.py (3131)

8.3 Cmd Class Reference

Inherited by rpki.cli.Cmd.

The documentation for this class was generated from the following file:

- cli.py (3074)

8.4 Exception Class Reference

Inherited by rpki.exceptions.RPKI_Exception.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.5 irbe_cli.bsc_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::left_right::bsc_elt.

Collaboration diagram for irbe_cli.bsc_elt:



Public Member Functions

- def client_query_signing_cert
- def client_query_signing_cert_crl
- def client_reply_decode

Public Attributes

- signing_cert
- signing_cert_crl

Static Public Attributes

- tuple excludes = ("pkcs10_request",)

  XML attributes and elements that should not be allowed as command line arguments.

8.5.1 Detailed Description

Definition at line 152 of file irbe_cli.py.

8.5.2 Member Function Documentation

8.5.2.1 def irbe_cli.bsc_elt.client_query_signing_cert (*self*, *arg*)

```
--signing_cert option.
```

Definition at line 156 of file irbe_cli.py.

8.5.2.2 def irbe_cli.bsc_elt.client_query_signing_cert_crl (*self*, *arg*)

```
--signing_cert_crl option.
```

Definition at line 160 of file irbe_cli.py.

8.5.2.3 def irbe_cli.bsc_elt.client_reply_decode (*self*)

Reimplemented from irbe_cli.reply_elt_mixin.

Definition at line 164 of file irbe_cli.py.

8.5.3 Member Data Documentation

8.5.3.1 tuple irbe_cli.bsc_elt.excludes = ("pkcs10_request",) `[static]`

XML attributes and elements that should not be allowed as command line arguments.

Reimplemented from irbe_cli.cmd_elt_mixin.

Definition at line 154 of file irbe_cli.py.

8.5.3.2 irbe_cli.bsc_elt.signing_cert

Reimplemented from rpki.left_right.bsc_elt.

Definition at line 158 of file irbe_cli.py.

8.5.3.3 irbe_cli.bsc_elt.signing_cert_crl

Reimplemented from rpki.left_right.bsc_elt.

Definition at line 162 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.6 irbe_cli.certificate_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::publication::certificate_elt.

Collaboration diagram for irbe_cli.certificate_elt:



8.6.1 Detailed Description

Definition at line 211 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.7 irbe_cli.child_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::left_right::child_elt.

Collaboration diagram for irbe_cli.child_elt:



8.7.1 Detailed Description

Definition at line 174 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.8 irbe_cli.client_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::publication::client_elt.

Collaboration diagram for irbe_cli.client_elt:



8.8.1 Detailed Description

Definition at line 208 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.9 irbe_cli.cmd_elt_mixin Class Reference

Inherits irbe_cli::reply_elt_mixin.

Inherited by irbe_cli.bsc_elt, irbe_cli.certificate_elt, irbe_cli.child_elt, irbe_cli.client_elt, irbe_cli.config_elt, irbe_cli.crl_elt, irbe_cli.list_published_objects_elt, irbe_cli.list_received_resources_elt, irbe_cli.manifest_elt, irbe_cli.parent_elt, irbe_cli.repository_elt, irbe_cli.roa_elt, and irbe_cli.self_elt.

Collaboration diagram for irbe_cli.cmd_elt_mixin:



Public Member Functions

- def client_getopt
- def client_query_bpki_cert
- def client_query_bpki_cms_cert
- def client_query_bpki_https_cert
- def client_query_cms_glue

- def client_query_glue
- def client_query_https_glue
- def usage

Public Attributes

- bpki_cert
- bpki_cms_cert
- bpki_cms_glue
- bpki_glue
- bpki_https_cert
- bpki_https_glue

Static Public Attributes

- tuple excludes = ()

  XML attributes and elements that should not be allowed as command line arguments.

- is_cmd = True

8.9.1 Detailed Description

```
Protocol mix-in for command line client element PDUs.
```

Definition at line 68 of file irbe_cli.py.

8.9.2 Member Function Documentation

8.9.2.1 def irbe_cli.cmd_elt_mixin.client_getopt (*self*, *argv*)

```
Parse options for this class.
```

Definition at line 92 of file irbe_cli.py.

8.9.2.2 def irbe_cli.cmd_elt_mixin.client_query_bpki_cert (*self*, *arg*)

```
Special handler for --bpki_cert option.
```

Definition at line 109 of file irbe_cli.py.

8.9.2.3 def irbe_cli.cmd_elt_mixin.client_query_bpki_cms_cert (*self*, *arg*)

```
Special handler for --bpki_cms_cert option.
```

Definition at line 117 of file irbe_cli.py.

8.9.2.4 def irbe_cli.cmd_elt_mixin.client_query_bpki_https_cert (*self*, *arg*)

```
Special handler for --bpki_https_cert option.
```

Definition at line 125 of file irbe_cli.py.

8.9.2.5 def irbe_cli.cmd_elt_mixin.client_query_cms_glue (*self*, *arg*)

```
Special handler for --bpki_cms_glue option.
```

Definition at line 121 of file irbe_cli.py.

8.9.2.6 def irbe_cli.cmd_elt_mixin.client_query_glue (*self*, *arg*)

```
Special handler for --bpki_glue option.
```

Definition at line 113 of file irbe_cli.py.

8.9.2.7 def irbe_cli.cmd_elt_mixin.client_query_https_glue (*self*, *arg*)

```
Special handler for --bpki_https_glue option.
```

Definition at line 129 of file irbe_cli.py.

8.9.2.8 def irbe_cli.cmd_elt_mixin.usage (*cls*)

```
Generate usage message for this PDU.
```

Definition at line 81 of file irbe_cli.py.

8.9.3 Member Data Documentation

8.9.3.1 irbe_cli.cmd_elt_mixin.bpki_cert

Definition at line 111 of file irbe_cli.py.

8.9.3.2 irbe_cli.cmd_elt_mixin.bpki_cms_cert

Definition at line 119 of file irbe_cli.py.

8.9.3.3 irbe_cli.cmd_elt_mixin.bpki_cms_glue

Definition at line 123 of file irbe_cli.py.

8.9.3.4 irbe_cli.cmd_elt_mixin.bpki_glue

Definition at line 115 of file irbe_cli.py.

8.9.3.5 irbe_cli.cmd_elt_mixin.bpki_https_cert

Definition at line 127 of file irbe_cli.py.

8.9.3.6 irbe_cli.cmd_elt_mixin.bpki_https_glue

Definition at line 131 of file irbe_cli.py.

8.9.3.7 irbe_cli.cmd_elt_mixin::excludes = () `[static]`

XML attributes and elements that should not be allowed as command line arguments.

Reimplemented in irbe_cli.bsc_elt, irbe_cli.list_published_objects_elt, and irbe_cli.list_received_resources_elt.

Definition at line 78 of file irbe_cli.py.

8.9.3.8 irbe_cli.cmd_elt_mixin.is_cmd = True [static]

Reimplemented from irbe_cli.reply_elt_mixin.

Definition at line 73 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.10 irbe_cli.cmd_msg_mixin Class Reference

Inherits object.

Inherited by irbe_cli.left_right_msg, and irbe_cli.publication_msg.

Collaboration diagram for irbe_cli.cmd_msg_mixin:



Public Member Functions

- def usage

8.10.1 Detailed Description

```
Protocol mix-in for command line client message PDUs.
```

Definition at line 133 of file irbe_cli.py.

8.10.2 Member Function Documentation

8.10.2.1 def irbe_cli.cmd_msg_mixin.usage (*cls*)

```
Generate usage message for this PDU.
```

Definition at line 139 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.11 irbe_cli.config_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::publication::config_elt.

Collaboration diagram for irbe_cli.config_elt:



Public Member Functions

- def client_query_bpki_crl

Public Attributes

- bpki_crl

8.11.1 Detailed Description

Definition at line 202 of file irbe_cli.py.

8.11.2 Member Function Documentation

8.11.2.1 def irbe_cli.config_elt.client_query_bpki_crl (*self*, *arg*)

```
Special handler for --bpki_crl option.
```

Definition at line 204 of file irbe_cli.py.

8.11.3 Member Data Documentation

8.11.3.1 irbe_cli.config_elt.bpki_crl

Definition at line 206 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.12 irbe_cli.crl_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::publication::crl_elt.

Collaboration diagram for irbe_cli.crl_elt:



8.12.1 Detailed Description

Definition at line 214 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.13 irbe_cli.left_right_cms_msg Class Reference

Inherits rpki::left_right::cms_msg.

Collaboration diagram for irbe_cli.left_right_cms_msg:



Static Public Attributes

- saxify = left_right_sax_handler.saxify

8.13.1 Detailed Description

Definition at line 197 of file irbe_cli.py.

8.13.2 Member Data Documentation

8.13.2.1 irbe_cli.left_right_cms_msg.saxify = left_right_sax_handler.saxify [static]

Reimplemented from rpki.left_right.cms_msg.

Definition at line 198 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.14 irbe_cli.left_right_msg Class Reference

Inherits irbe_cli::cmd_msg_mixin, and rpki::left_right::msg.

Collaboration diagram for irbe_cli.left_right_msg:



Static Public Attributes

- tuple pdus

  Dispatch table of PDUs for this protocol.

8.14.1 Detailed Description

Definition at line 189 of file irbe_cli.py.

8.14.2 Member Data Documentation

8.14.2.1 tuple irbe_cli.left_right_msg.pdus [static]

Initial value:

```
dict((x.element_name, x)
              for x in (self_elt, bsc_elt, parent_elt, child_elt, repository_elt,

                        list_published_objects_elt, list_received_resources_elt,
      report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented from rpki.left_right.msg.

Definition at line 190 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.15 irbe_cli.left_right_proto Class Reference

Inherits object.

Collaboration diagram for irbe_cli.left_right_proto:



Static Public Attributes

- cms_msg = left_right_cms_msg
- msg = left_right_msg

8.15.1 Detailed Description

Definition at line 302 of file irbe_cli.py.

8.15.2 Member Data Documentation

8.15.2.1 irbe_cli.left_right_proto.cms_msg = left_right_cms_msg [static]

Definition at line 303 of file irbe_cli.py.

8.15.2.2 irbe_cli.left_right_proto.msg = left_right_msg [static]

Definition at line 304 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.16 irbe_cli.left_right_sax_handler Class Reference

Inherits rpki::left_right::sax_handler.

Collaboration diagram for irbe_cli.left_right_sax_handler:



Static Public Attributes

- pdu = left_right_msg

8.16.1 Detailed Description

Definition at line 194 of file irbe_cli.py.

8.16.2 Member Data Documentation

8.16.2.1 irbe_cli.left_right_sax_handler.pdu = left_right_msg [static]

Reimplemented from rpki.left_right.sax_handler.

Definition at line 195 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.17 irbe_cli.list_published_objects_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::left_right::list_published_objects_elt.

Collaboration diagram for irbe_cli.list_published_objects_elt:



Static Public Attributes

- tuple excludes = ("uri",)

XML attributes and elements that should not be allowed as command line arguments.

8.17.1 Detailed Description

Definition at line 180 of file irbe_cli.py.

8.17.2 Member Data Documentation

8.17.2.1 tuple irbe_cli.list_published_objects_elt.excludes = ("uri",) [static]

XML attributes and elements that should not be allowed as command line arguments.

Reimplemented from irbe_cli.cmd_elt_mixin.

Definition at line 181 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.18 irbe_cli.list_received_resources_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::left_right::list_received_resources_elt.

Collaboration diagram for irbe_cli.list_received_resources_elt:



Static Public Attributes

- tuple excludes = ("notBefore", "notAfter", "uri", "sia_uri", "aia_uri", "asn", "ipv4", "ipv6")

  XML attributes and elements that should not be allowed as command line arguments.

8.18.1 Detailed Description

Definition at line 183 of file irbe_cli.py.

8.18.2 Member Data Documentation

8.18.2.1 tuple irbe_cli.list_received_resources_elt.excludes = ("notBefore", "notAfter", "uri", "sia_uri", "aia_uri", "asn", "ipv4", "ipv6") [static]

XML attributes and elements that should not be allowed as command line arguments.

Reimplemented from irbe_cli.cmd_elt_mixin.

Definition at line 184 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.19 irbe_cli.manifest_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::publication::manifest_elt.

Collaboration diagram for irbe_cli.manifest_elt:



8.19.1 Detailed Description

Definition at line 217 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.20 irbe_cli.parent_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::left_right::parent_elt.

Collaboration diagram for irbe_cli.parent_elt:



8.20.1 Detailed Description

Definition at line 171 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.21 irbe_cli.publication_cms_msg Class Reference

Inherits rpki::publication::cms_msg.

Collaboration diagram for irbe_cli.publication_cms_msg:



Static Public Attributes

- saxify = publication_sax_handler.saxify

8.21.1 Detailed Description

Definition at line 233 of file irbe_cli.py.

8.21.2 Member Data Documentation

8.21.2.1 irbe_cli.publication_cms_msg.saxify = publication_sax_handler.saxify [static]

Reimplemented from rpki.publication.cms_msg.

Definition at line 234 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.22 irbe_cli.publication_msg Class Reference

Inherits irbe_cli::cmd_msg_mixin, and rpki::publication::msg.

Collaboration diagram for irbe_cli.publication_msg:



Static Public Attributes

- tuple pdus

  Dispatch table of PDUs for this protocol.

8.22.1 Detailed Description

Definition at line 226 of file irbe_cli.py.

8.22.2 Member Data Documentation

8.22.2.1 tuple irbe_cli.publication_msg.pdus [static]

Initial value:

```
dict((x.element_name, x)
              for x in (config_elt, client_elt, certificate_elt, crl_elt, manifes
      t_elt, roa_elt, report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented from rpki.publication.msg.

Definition at line 227 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.23 irbe_cli.publication_proto Class Reference

Inherits object.

Collaboration diagram for irbe_cli.publication_proto:



Static Public Attributes

- cms_msg = publication_cms_msg
- msg = publication_msg

8.23.1 Detailed Description

Definition at line 319 of file irbe_cli.py.

8.23.2 Member Data Documentation

8.23.2.1 irbe_cli.publication_proto.cms_msg = publication_cms_msg [static]

Definition at line 321 of file irbe_cli.py.

8.23.2.2 irbe_cli.publication_proto.msg = publication_msg [static]

Definition at line 320 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.24 irbe_cli.publication_sax_handler Class Reference

Inherits rpki::publication::sax_handler.

Collaboration diagram for irbe_cli.publication_sax_handler:



Static Public Attributes

- pdu = publication_msg

8.24.1 Detailed Description

Definition at line 230 of file irbe_cli.py.

8.24.2 Member Data Documentation

8.24.2.1 irbe_cli.publication_sax_handler.pdu = publication_msg [static]

Reimplemented from rpki.publication.sax_handler.

Definition at line 231 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.25 irbe_cli.reply_elt_mixin Class Reference

Inherits object.

Inherited by irbe_cli.cmd_elt_mixin, irbe_cli.report_error_elt, and irbe_cli.report_error_elt.

Collaboration diagram for irbe_cli.reply_elt_mixin:



Public Member Functions

- def client_reply_decode
- def client_reply_show

Static Public Attributes

- is_cmd = False

8.25.1 Detailed Description

```
Protocol mix-in for printout of reply PDUs.
```

Definition at line 52 of file irbe_cli.py.

8.25.2 Member Function Documentation

8.25.2.1 def irbe_cli.reply_elt_mixin.client_reply_decode (*self*)

Reimplemented in irbe_cli.bsc_elt.

Definition at line 59 of file irbe_cli.py.

8.25.2.2 def irbe_cli.reply_elt_mixin.client_reply_show (*self*)

Definition at line 62 of file irbe_cli.py.

8.25.3 Member Data Documentation

8.25.3.1 irbe_cli.reply_elt_mixin.is_cmd = False `[static]`

Reimplemented in irbe_cli.cmd_elt_mixin.

Definition at line 57 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.26 irbe_cli.report_error_elt Class Reference

Inherits irbe_cli::reply_elt_mixin, rpki::publication::report_error_elt, irbe_cli::reply_-elt_mixin, and rpki::left_right::report_error_elt.

Collaboration diagram for irbe_cli.report_error_elt:



8.26.1 Detailed Description

Definition at line 186 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.27 irbe_cli.repository_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::left_right::repository_elt.

Collaboration diagram for irbe_cli.repository_elt:



8.27.1 Detailed Description

Definition at line 177 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.28 irbe_cli.roa_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::publication::roa_elt.

Collaboration diagram for irbe_cli.roa_elt:



8.28.1 Detailed Description

Definition at line 220 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.29 irbe_cli.self_elt Class Reference

Inherits irbe_cli::cmd_elt_mixin, and rpki::left_right::self_elt.

Collaboration diagram for irbe_cli.self_elt:



8.29.1 Detailed Description

Definition at line 149 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.30 irbe_cli.UsageWrapper Class Reference

Inherits textwrap::TextWrapper.

Collaboration diagram for irbe_cli.UsageWrapper:



Public Member Functions

- def __call__

8.30.1 Detailed Description

```
Call interface around Python textwrap.Textwrapper class.
```

Definition at line 41 of file irbe_cli.py.

8.30.2 Member Function Documentation

8.30.2.1 def irbe_cli.UsageWrapper.__call__ (*self*, *args*)

```
Format arguments, with TextWrapper indentation.
```

Definition at line 46 of file irbe_cli.py.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.31 long Class Reference

Inherited by rpki.ipaddrs.v4addr, and rpki.ipaddrs.v6addr.

The documentation for this class was generated from the following file:

- ipaddrs.py (2424)

8.32 object Class Reference

Inherited by irbe_cli.cmd_msg_mixin, irbe_cli.left_right_proto, irbe_cli.publication_proto, irbe_cli.reply_elt_mixin, pubd.pubd_context, rpki.async.gc_summary, rpki.async.iterator, rpki.async.sync_wrapper, rpki.async.timer, rpki.config.parser, rpki.https.caller, rpki.https.http_message, rpki.https.http_queue, rpki.left_right.left_right_namespace, rpki.log.logger, rpki.publication.publication_namespace, rpki.resource_set.resource_bag, rpki.resource_set.resource_range, rpki.resource_set.roa_prefix, rpki.rpki_engine.publication_queue, rpki.rpki_engine.rpkid_context, rpki.sql.session, rpki.sql.sql_persistent, rpki.sql.template, rpki.up_down.base_elt, rpki.x509.DeadDrop, rpki.x509.DER_object, rpki.x509.PEM_converter, and rpki.xml_utils.base_elt.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.33 pubd.pubd_context Class Reference

Inherits object.

Collaboration diagram for pubd.pubd_context:



Public Member Functions

- def __init__
- def build_https_ta_cache
- def clear_https_ta_cache

- def client_handler
- def control_handler
- def handler_common

Public Attributes

- bpki_ta
- https_server_host
- https_server_port
- irbe_cert
- pubd_cert
- pubd_key
- publication_base
- publication_multimodule
- sql

Static Public Attributes

- tuple client_url_regexp = re.compile("/client/([-A-Z0-9_/]+)$", re.I)
- https_ta_cache = None

  HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.

8.33.1 Detailed Description

```
A container for various pubd parameters.
```

Definition at line 46 of file pubd.py.

8.33.2 Member Function Documentation

8.33.2.1 def pubd.pubd_context.__init__ (*self*, *cfg*)

Definition at line 51 of file pubd.py.

8.33.2.2 def pubd.pubd_context.build_https_ta_cache (*self*)

```
Build dynamic TLS trust anchors.
```

Definition at line 140 of file pubd.py.

8.33.2.3 def pubd.pubd_context.clear_https_ta_cache (*self*)

```
Clear dynamic TLS trust anchors.
```

Definition at line 132 of file pubd.py.

8.33.2.4 def pubd.pubd_context.client_handler (*self*, *query*, *path*, *cb*)

```
Process one PDU from a client.
```

Definition at line 100 of file pubd.py.

8.33.2.5 def pubd.pubd_context.control_handler (*self*, *query*, *path*, *cb*)

```
Process one PDU from the IRBE.
```

Definition at line 80 of file pubd.py.

8.33.2.6 def pubd.pubd_context.handler_common (*self*, *query*, *client*, *cb*, *certs*, *crl* = `None`)

```
Common PDU handler code.
```

Definition at line 67 of file pubd.py.

8.33.3 Member Data Documentation

8.33.3.1 pubd.pubd_context.bpki_ta

Definition at line 55 of file pubd.py.

8.33.3.2 tuple pubd.pubd_context.client_url_regexp = re.compile("/client/([-A-Z0-9_/]+)$", re.I) [static]

Definition at line 98 of file pubd.py.

8.33.3.3 pubd.pubd_context.https_server_host

Definition at line 60 of file pubd.py.

8.33.3.4 pubd.pubd_context.https_server_port

Definition at line 61 of file pubd.py.

8.33.3.5 pubd.pubd_context::https_ta_cache = None [static]

HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.

Definition at line 130 of file pubd.py.

8.33.3.6 pubd.pubd_context.irbe_cert

Definition at line 56 of file pubd.py.

8.33.3.7 pubd.pubd_context.pubd_cert

Definition at line 57 of file pubd.py.

8.33.3.8 pubd.pubd_context.pubd_key

Definition at line 58 of file pubd.py.

8.33.3.9 pubd.pubd_context.publication_base

Definition at line 63 of file pubd.py.

8.33.3.10 pubd.pubd_context.publication_multimodule

Definition at line 65 of file pubd.py.

8.33.3.11 pubd.pubd_context.sql

Definition at line 53 of file pubd.py.

The documentation for this class was generated from the following file:

- pubd.py (3107)

8.34 datetime Class Reference

Inherited by rpki.sundial.datetime.

The documentation for this class was generated from the following file:

- sundial.py (3107)

8.35 timedelta Class Reference

Inherited by rpki.sundial.timedelta.

The documentation for this class was generated from the following file:

- sundial.py (3107)

8.36 rootd.cms_msg Class Reference

Inherits rpki::up_down::cms_msg.

Collaboration diagram for rootd.cms_msg:



Static Public Attributes

- saxify = sax_handler.saxify

8.36.1 Detailed Description

Definition at line 235 of file rootd.py.

8.36.2 Member Data Documentation

8.36.2.1 rootd.cms_msg.saxify = sax_handler.saxify [static]

Reimplemented from rpki.up_down.cms_msg.

Definition at line 236 of file rootd.py.

The documentation for this class was generated from the following file:

- rootd.py (2913)

8.37 rootd.issue_pdu Class Reference

Inherits rpki::up_down::issue_pdu.

Collaboration diagram for rootd.issue_pdu:



Public Member Functions

- def serve_pdu

8.37.1 Detailed Description

Definition at line 194 of file rootd.py.

8.37.2 Member Function Documentation

8.37.2.1 def rootd.issue_pdu.serve_pdu (*self*, *q_msg*, *r_msg*, *child*, *callback*, *errback*)

```
Serve one issue request PDU.
```

Reimplemented from rpki.up_down.issue_pdu.

Definition at line 195 of file rootd.py.

The documentation for this class was generated from the following file:

- rootd.py (2913)

8.38 rootd.list_pdu Class Reference

Inherits rpki::up_down::list_pdu.

Collaboration diagram for rootd.list_pdu:



Public Member Functions

- def serve_pdu

8.38.1 Detailed Description

Definition at line 188 of file rootd.py.

8.38.2 Member Function Documentation

8.38.2.1 def rootd.list_pdu.serve_pdu (*self*, *q_msg*, *r_msg*, *child*, *callback*, *errback*)

```
Serve one "list" PDU.
```

Reimplemented from rpki.up_down.list_pdu.

Definition at line 189 of file rootd.py.

The documentation for this class was generated from the following file:

- rootd.py (2913)

8.39 rootd.message_pdu Class Reference

Inherits rpki::up_down::message_pdu.

Collaboration diagram for rootd.message_pdu:



Public Member Functions

- def log_query

Static Public Attributes

- dictionary name2type

- tuple type2name = dict((v, k) for k, v in name2type.items())

8.39.1 Detailed Description

Definition at line 213 of file rootd.py.

8.39.2 Member Function Documentation

8.39.2.1 def rootd.message_pdu.log_query (*self*, *child*)

```
Log query we're handling.
```

Reimplemented from rpki.up_down.message_pdu.

Definition at line 226 of file rootd.py.

8.39.3 Member Data Documentation

8.39.3.1 dictionary rootd.message_pdu.name2type [static]

Initial value:

```
{
    "list"            : list_pdu,
    "list_response"   : rpki.up_down.list_response_pdu,
    "issue"           : issue_pdu,
    "issue_response"  : rpki.up_down.issue_response_pdu,
    "revoke"          : revoke_pdu,
    "revoke_response" : rpki.up_down.revoke_response_pdu,
    "error_response"  : rpki.up_down.error_response_pdu }
```

Reimplemented from rpki.up_down.message_pdu.

Definition at line 215 of file rootd.py.

8.39.3.2 tuple rootd.message_pdu.type2name = dict((v, k) for k, v in name2type.items()) [static]

Reimplemented from rpki.up_down.message_pdu.

Definition at line 224 of file rootd.py.

The documentation for this class was generated from the following file:

- rootd.py (2913)

8.40 rootd.revoke_pdu Class Reference

Inherits rpki::up_down::revoke_pdu.

Collaboration diagram for rootd.revoke_pdu:



Public Member Functions

- def serve_pdu

8.40.1 Detailed Description

Definition at line 201 of file rootd.py.

8.40.2 Member Function Documentation

8.40.2.1 def rootd.revoke_pdu.serve_pdu (*self*, *q_msg*, *r_msg*, *child*, *cb*, *eb*)

```
Serve one revoke request PDU.
```

Reimplemented from rpki.up_down.revoke_pdu.

Definition at line 202 of file rootd.py.

The documentation for this class was generated from the following file:

- rootd.py (2913)

8.41 rootd.sax_handler Class Reference

Inherits rpki::up_down::sax_handler.

Collaboration diagram for rootd.sax_handler:



Static Public Attributes

- pdu = message_pdu

8.41.1 Detailed Description

Definition at line 232 of file rootd.py.

8.41.2 Member Data Documentation

8.41.2.1 rootd.sax_handler.pdu = message_pdu [static]

Reimplemented from rpki.up_down.sax_handler.

Definition at line 233 of file rootd.py.

The documentation for this class was generated from the following file:

- rootd.py (2913)

8.42 rpki.async.gc_summary Class Reference

Inherits object.

Collaboration diagram for rpki.async.gc_summary:



Public Member Functions

- def __init__

- def handler

Public Attributes

- interval
- threshold
- timer

8.42.1 Detailed Description

```
Periodic summary of GC state, for tracking down memory bloat.
```

Definition at line 354 of file async.py.

8.42.2 Member Function Documentation

8.42.2.1 def rpki.async.gc_summary.__init__ (*self*, *interval*, *threshold* = 0)

Definition at line 359 of file async.py.

8.42.2.2 def rpki.async.gc_summary.handler (*self*)

Definition at line 367 of file async.py.

8.42.3 Member Data Documentation

8.42.3.1 rpki.async.gc_summary.interval

Definition at line 362 of file async.py.

8.42.3.2 rpki.async.gc_summary.threshold

Definition at line 363 of file async.py.

8.42.3.3 rpki.async.gc_summary.timer

Definition at line 364 of file async.py.

The documentation for this class was generated from the following file:

- async.py (3107)

8.43 rpki.async.iterator Class Reference

Inherits object.

Collaboration diagram for rpki.async.iterator:



Public Member Functions

- def __call__
- def __init__
- def __repr__
- def doit
- def ignore

Public Attributes

- caller_function
- done_callback
- item_callback
- iterator
- unwind_stack

8.43.1 Detailed Description

```
Iteration construct for event-driven code.  Takes three
arguments:

- Some kind of iterable object

- A callback to call on each item in the iteration

- A callback to call after the iteration terminates.

The item callback receives two arguments: the callable iterator
object and the current value of the iteration.  It should call the
iterator (or arrange for the iterator to be called) when it is time
to continue to the next item in the iteration.

The termination callback receives no arguments.
```

Definition at line 26 of file async.py.

8.43.2 Member Function Documentation

8.43.2.1 def rpki.async.iterator.__call__ (*self*)

Definition at line 64 of file async.py.

8.43.2.2 def rpki.async.iterator.__init__ (*self*, *iterable*, *item_callback*, *done_callback*, *unwind_stack* = `True`)

Definition at line 45 of file async.py.

8.43.2.3 def rpki.async.iterator.__repr__ (*self*)

Definition at line 59 of file async.py.

8.43.2.4 def rpki.async.iterator.doit (*self*)

Definition at line 70 of file async.py.

8.43.2.5 def rpki.async.iterator.ignore (*self*, *ignored*)

Definition at line 77 of file async.py.

8.43.3 Member Data Documentation

8.43.3.1 rpki.async.iterator.caller_function

Definition at line 48 of file async.py.

8.43.3.2 rpki.async.iterator.done_callback

Definition at line 47 of file async.py.

8.43.3.3 rpki.async.iterator.item_callback

Definition at line 46 of file async.py.

8.43.3.4 rpki.async.iterator.iterator

Definition at line 51 of file async.py.

8.43.3.5 rpki.async.iterator.unwind_stack

Definition at line 49 of file async.py.

The documentation for this class was generated from the following file:

- async.py (3107)

8.44 rpki.async.sync_wrapper Class Reference

Inherits object.

Collaboration diagram for rpki.async.sync_wrapper:



Public Member Functions

- def __call__
- def __init__
- def cb
- def eb

Public Attributes

- func

Static Public Attributes

- err = None
- res = None

8.44.1 Detailed Description

```
Synchronous wrapper around asynchronous functions.  Running in
asynchronous mode at all times makes sense for event-driven daemons,
but is kind of tedious for simple scripts, hence this wrapper.

The wrapped function should take at least two arguments: a callback
function and an errback function.  If any arguments are passed to
the wrapper, they will be passed as additional arguments to the
wrapped function.
```

Definition at line 303 of file async.py.

8.44.2 Member Function Documentation

8.44.2.1 def rpki.async.sync_wrapper.__call__ (*self*, *args*, *kwargs*)

Definition at line 330 of file async.py.

8.44.2.2 def rpki.async.sync_wrapper.__init__ (*self*, *func*)

Definition at line 318 of file async.py.

8.44.2.3 def rpki.async.sync_wrapper.cb (*self*, *res* = `None`)

Definition at line 321 of file async.py.

8.44.2.4 def rpki.async.sync_wrapper.eb (*self*, *err*)

Definition at line 325 of file async.py.

8.44.3 Member Data Documentation

8.44.3.1 rpki.async.sync_wrapper.err = None `[static]`

Definition at line 316 of file async.py.

8.44.3.2 rpki.async.sync_wrapper.func

Definition at line 319 of file async.py.

8.44.3.3 rpki.async.sync_wrapper.res = None [static]

Definition at line 315 of file async.py.

The documentation for this class was generated from the following file:

- async.py (3107)

8.45 rpki.async.timer Class Reference

Inherits object.

Collaboration diagram for rpki.async.timer:



Public Member Functions

- def __cmp__
- def __del__
- def __init__
- def __repr__
- def cancel

- def clear
- def errback
- def handler
- def is_set
- def runq
- def seconds_until_wakeup
- def set
- def set_errback
- def set_handler
- def trace

Public Attributes

- errback
- handler
- when

Static Public Attributes

- gc_debug = False

  Verbose chatter about timers states and garbage collection.

- list queue = [ ]

  Timer queue, shared by all timer instances (there can be only one queue).

- run_debug = False

  Verbose chatter about timers being run.

8.45.1 Detailed Description

```
Timer construct for event-driven code.  It can be used in either of two ways:

- As a virtual class, in which case the subclass should provide a
  handler() method to receive the wakup event when the timer expires; or

- By setting an explicit handler callback, either via the
  constructor or the set_handler() method.

Subclassing is probably more Pythonic, but setting an explict
handler turns out to be very convenient when combined with bound
methods to other objects.
```

Definition at line 80 of file async.py.

8.45.2 Member Function Documentation

8.45.2.1 def rpki.async.timer.__cmp__ (*self*, *other*)

Definition at line 140 of file async.py.

8.45.2.2 def rpki.async.timer.__del__ (*self*)

Definition at line 144 of file async.py.

8.45.2.3 def rpki.async.timer.__init__ (*self*, *handler* = `None`, *errback* = `None`)

Definition at line 107 of file async.py.

8.45.2.4 def rpki.async.timer.__repr__ (*self*)

Definition at line 207 of file async.py.

8.45.2.5 def rpki.async.timer.cancel (*self*)

```
Cancel a timer, if it was set.
```

Definition at line 147 of file async.py.

8.45.2.6 def rpki.async.timer.clear (*cls*)

```
Cancel every timer on the queue.  We could just throw away the
queue content, but this way we can notify subclasses that provide
their own cancel() method.
```

Definition at line 232 of file async.py.

8.45.2.7 def rpki.async.timer.errback (*self*, *e*)

```
Error callback.  May be overridden, or set with set_errback().
```

Definition at line 179 of file async.py.

8.45.2.8 def rpki.async.timer.handler (*self*)

```
Handle a timer that has expired.  This must either be overriden by
a subclass or set dynamically by set_handler().
```

Definition at line 162 of file async.py.

8.45.2.9 def rpki.async.timer.is_set (*self*)

```
Test whether this timer is currently set.
```

Definition at line 158 of file async.py.

8.45.2.10 def rpki.async.timer.runq (*cls*)

```
Run the timer queue: for each timer whose call time has passed,
pull the timer off the queue and call its handler() method.
```

Definition at line 191 of file async.py.

8.45.2.11 def rpki.async.timer.seconds_until_wakeup (*cls*)

```
Calculate delay until next timer expires, or None if no timers are
set and we should wait indefinitely.  Rounds up to avoid spinning
in select() or poll().  We could calculate fractional seconds in
the right units instead, but select() and poll() don't even take
the same units (argh!), and we're not doing anything that
hair-triggered, so rounding up is simplest.
```

Definition at line 211 of file async.py.

8.45.2.12 def rpki.async.timer.set (*self*, *when*)

```
Set a timer.  Argument can be a datetime, to specify an absolute
time, or a timedelta, to specify an offset time.
```

Definition at line 124 of file async.py.

8.45.2.13 def rpki.async.timer.set_errback (*self*, *errback*)

```
Set a timer's errback.  Like set_handler(), for errbacks.
```

Definition at line 186 of file async.py.

8.45.2.14 def rpki.async.timer.set_handler (*self*, *handler*)

```
Set timer's expiration handler.  This is an alternative to
subclassing the timer class, and may be easier to use when
integrating timers into other classes (eg, the handler can be a
bound method to an object in a class representing a network
connection).
```

Definition at line 169 of file async.py.

8.45.2.15 def rpki.async.timer.trace (*self*, *msg*)

```
Debug logging.
```

Definition at line 116 of file async.py.

8.45.3 Member Data Documentation

8.45.3.1 rpki.async.timer.errback

Definition at line 188 of file async.py.

8.45.3.2 rpki::async.timer::gc_debug = False [static]

Verbose chatter about timers states and garbage collection.

Definition at line 97 of file async.py.

8.45.3.3 rpki.async.timer.handler

Definition at line 177 of file async.py.

8.45.3.4 rpki::async.timer::queue = [] [static]

Timer queue, shared by all timer instances (there can be only one queue).

Definition at line 105 of file async.py.

8.45.3.5 rpki::async.timer::run_debug = False [static]

Verbose chatter about timers being run.

Definition at line 101 of file async.py.

8.45.3.6 rpki.async.timer.when

Definition at line 112 of file async.py.

The documentation for this class was generated from the following file:

- async.py (3107)

8.46 rpki.cli.Cmd Class Reference

Inherits cmd::Cmd.

Collaboration diagram for rpki.cli.Cmd:



Public Member Functions

- def __init__
- def cmdloop_with_history
- def complete_help
- def completenames
- def do_EOF

- def do_exit
- def emptyline
- def filename_complete
- def help_help

Static Public Attributes

- cmdloop_with_history = cmd.Cmd.cmdloop
- do_quit = do_exit
- emptyline_repeats_last_command = False
- EOF_exits_command_loop = True
- histfile = None
- string identchars = "/-."

8.46.1 Detailed Description

```
Customized subclass of Python cmd module.
```

Definition at line 29 of file cli.py.

8.46.2 Member Function Documentation

8.46.2.1 def rpki.cli.Cmd.__init__ (*self*, *argv* = `None`)

Definition at line 42 of file cli.py.

8.46.2.2 def rpki.cli.Cmd.cmdloop_with_history (*self*)

Definition at line 101 of file cli.py.

8.46.2.3 def rpki.cli.Cmd.complete_help (*self*, *text*, *ignored*)

Definition at line 92 of file cli.py.

8.46.2.4 def rpki.cli.Cmd.completenames (*self*, *args*)

Definition at line 79 of file cli.py.

8.46.2.5 def rpki.cli.Cmd.do_EOF (*self*, *arg*)

```
Exit program.
```

Definition at line 49 of file cli.py.

8.46.2.6 def rpki.cli.Cmd.do_exit (*self*, *arg*)

```
Exit program.
```

Definition at line 57 of file cli.py.

8.46.2.7 def rpki.cli.Cmd.emptyline (*self*)

Definition at line 65 of file cli.py.

8.46.2.8 def rpki.cli.Cmd.filename_complete (*self*, *text*, *line*, *begidx*, *endidx*)

Definition at line 69 of file cli.py.

8.46.2.9 def rpki.cli.Cmd.help_help (*self*)

```
Type "help [topic]" for help on a command,
or just "help" for a list of commands.
```

Definition at line 85 of file cli.py.

8.46.3 Member Data Documentation

8.46.3.1 rpki.cli.Cmd.cmdloop_with_history = cmd.Cmd.cmdloop [static]

Definition at line 118 of file cli.py.

8.46.3.2 rpki.cli.Cmd.do_quit = do_exit [static]

Definition at line 63 of file cli.py.

8.46.3.3 rpki.cli.Cmd.emptyline_repeats_last_command = False [static]

Definition at line 34 of file cli.py.

8.46.3.4 rpki.cli.Cmd.EOF_exits_command_loop = True [static]

Definition at line 36 of file cli.py.

8.46.3.5 rpki.cli.Cmd.histfile = None [static]

Definition at line 40 of file cli.py.

8.46.3.6 string rpki.cli.Cmd.identchars = "/-." [static]

Definition at line 38 of file cli.py.

The documentation for this class was generated from the following file:

- cli.py (3074)

8.47 rpki.config.parser Class Reference

Inherits object.

Collaboration diagram for rpki.config.parser:



Public Member Functions

- def __init__
- def get
- def getboolean
- def getint

- def getlong
- def has_option
- def has_section
- def multiget
- def set_global_flags

Public Attributes

- cfg
- default_section
- filename

Private Member Functions

- def _repl

Static Private Attributes

- tuple _regexp = re.compile("\\${(.*?)::(.*?)}")

8.47.1 Detailed Description

```
Extensions to stock Python ConfigParser:

Read config file and set default section while initializing parser object.

Support for OpenSSL-style subscripted options and a limited form of
OpenSSL-style indirect variable references (${section::option}).

get-methods with default values and default section name.
```

Definition at line 38 of file config.py.

8.47.2 Member Function Documentation

8.47.2.1 def rpki.config.parser.__init__ (*self*, *filename*, *section* = `None`, *allow_missing* = `False`)

```
Initialize this parser.
```

Definition at line 50 of file config.py.

8.47.2.2 def rpki.config.parser._repl (*self*, *m*) [private]

```
Replacement function for indirect variable substitution.
This is intended for use with re.subn().
```

Definition at line 101 of file config.py.

8.47.2.3 def rpki.config.parser.get (*self*, *option*, *default* = None, *section* = None)

```
Get an option, perhaps with a default value.
```

Definition at line 112 of file config.py.

8.47.2.4 def rpki.config.parser.getboolean (*self*, *option*, *default* = None, *section* = None)

```
Get a boolean option, perhaps with a default value.
```

Definition at line 126 of file config.py.

8.47.2.5 def rpki.config.parser.getint (*self*, *option*, *default* = None, *section* = None)

```
Get an integer option, perhaps with a default value.
```

Definition at line 138 of file config.py.

8.47.2.6 def rpki.config.parser.getlong (*self*, *option*, *default* = None, *section* = None)

```
Get a long integer option, perhaps with a default value.
```

Definition at line 144 of file config.py.

8.47.2.7 def rpki.config.parser.has_option (*self*, *option*, *section* = `None`)

```
Test whether an option exists.
```

Definition at line 71 of file config.py.

8.47.2.8 def rpki.config.parser.has_section (*self*, *section*)

```
Test whether a section exists.
```

Definition at line 64 of file config.py.

8.47.2.9 def rpki.config.parser.multiget (*self*, *option*, *section* = `None`)

```
Parse OpenSSL-style foo.0, foo.1, ... subscripted options.

Returns a list of values matching the specified option name.
```

Definition at line 80 of file config.py.

8.47.2.10 def rpki.config.parser.set_global_flags (*self*)

```
Consolidated control for all the little global control flags
scattered through the libraries.  This isn't a particularly good
place for this function to live, but it has to live somewhere and
making it a method of the config parser from which it gets all of
its data is less silly than the available alternatives.
```

Definition at line 150 of file config.py.

8.47.3 Member Data Documentation

8.47.3.1 tuple rpki.config.parser._regexp = re.compile("\\${(.*?)::(.*?)}") `[static, private]`

Definition at line 99 of file config.py.

8.47.3.2 rpki.config.parser.cfg

Definition at line 56 of file config.py.

8.47.3.3 rpki.config.parser.default_section

Definition at line 62 of file config.py.

8.47.3.4 rpki.config.parser.filename

Definition at line 55 of file config.py.

The documentation for this class was generated from the following file:

- config.py (3107)

8.48 rpki.exceptions.BadClassNameSyntax Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadClassNameSyntax:



8.48.1 Detailed Description

```
Illegal syntax for a class_name.
```

Definition at line 92 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.49 rpki.exceptions.BadClientURL Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadClientURL:



8.49.1 Detailed Description

```
URL given to HTTPS client does not match profile.
```

Definition at line 232 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.50 rpki.exceptions.BadContactURL Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadContactURL:



8.50.1 Detailed Description

```
Error trying to parse contact URL.
```

Definition at line 87 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.51 rpki.exceptions.BadExtension Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadExtension:



8.51.1 Detailed Description

```
Forbidden X.509 extension.
```

Definition at line 242 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.52 rpki.exceptions.BadIRDBReply Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadIRDBReply:



8.52.1 Detailed Description

```
Unexpected reply to IRDB query.
```

Definition at line 152 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.53 rpki.exceptions.BadIssueResponse Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadIssueResponse:



8.53.1 Detailed Description

```
issue_response PDU with wrong number of classes or certificates.
```

Definition at line 97 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.54 rpki.exceptions.BadPKCS10 Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadPKCS10:



8.54.1 Detailed Description

```
Bad PKCS #10 object.
```

Definition at line 107 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.55 rpki.exceptions.BadPublicationReply Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadPublicationReply:



8.55.1 Detailed Description

```
Unexpected reply to publication query.
```

Definition at line 257 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.56 rpki.exceptions.BadQuery Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadQuery:



8.56.1 Detailed Description

```
Unexpected protocol query.
```

Definition at line 55 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.57 rpki.exceptions.BadSender Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadSender:



8.57.1 Detailed Description

```
Unexpected XML sender value.
```

Definition at line 127 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.58 rpki.exceptions.BadStatusCode Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadStatusCode:



8.58.1 Detailed Description

```
Unrecognized protocol status code.
```

Definition at line 50 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.59 rpki.exceptions.BadURISyntax Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BadURISyntax:



8.59.1 Detailed Description

```
Illegal syntax for a URI.
```

Definition at line 45 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.60 rpki.exceptions.BSCNotFound Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BSCNotFound:



8.60.1 Detailed Description

```
Could not find specified BSC in database.
```

Definition at line 122 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.61 rpki.exceptions.BSCNotReady Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.BSCNotReady:



8.61.1 Detailed Description

```
BSC not yet in a usable state, signing_cert not set.
```

Definition at line 277 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.62 rpki.exceptions.ChildNotFound Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.ChildNotFound:



8.62.1 Detailed Description

```
Could not find specified child in database.
```

Definition at line 117 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.63 rpki.exceptions.ClassNameMismatch Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.ClassNameMismatch:



8.63.1 Detailed Description

```
class_name does not match child context.
```

Definition at line 132 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.64 rpki.exceptions.ClassNameUnknown Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.ClassNameUnknown:



8.64.1 Detailed Description

```
Unknown class_name.
```

Definition at line 137 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.65 rpki.exceptions.ClientNotFound Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.ClientNotFound:



8.65.1 Detailed Description

```
Could not find specified client in database.
```

Definition at line 237 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.66 rpki.exceptions.CMSContentNotSet Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.CMSContentNotSet:



8.66.1 Detailed Description

```
Inner content of a CMS_object has not been set.  If object is known
to be valid, the .extract() method should be able to set the
content; otherwise, only the .verify() method (which checks
signatures) is safe.
```

Definition at line 302 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.67 rpki.exceptions.CMSCRLNotSet Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.CMSCRLNotSet:



8.67.1 Detailed Description

```
CMS CRL has not been configured.
```

Definition at line 217 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.68 rpki.exceptions.CMSVerificationFailed Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.CMSVerificationFailed:



8.68.1 Detailed Description

```
Verification of a CMS message failed.
```

Definition at line 66 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.69 rpki.exceptions.DBConsistancyError Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.DBConsistancyError:



8.69.1 Detailed Description

```
Found multiple matches for a database query that shouldn't ever
return that.
```

Definition at line 60 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.70 rpki.exceptions.DERObjectConversionError Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.DERObjectConversionError:



8.70.1 Detailed Description

```
Error trying to convert a DER-based object from one representation
to another.
```

Definition at line 76 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.71 rpki.exceptions.DuplicateObject Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.DuplicateObject:



8.71.1 Detailed Description

```
Attempt to create an object that already exists.
```

Definition at line 262 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.72 rpki.exceptions.EmptyPEM Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.EmptyPEM:



8.72.1 Detailed Description

```
Couldn't find PEM block to convert.
```

Definition at line 187 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.73 rpki.exceptions.EmptyROAPrefixList Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.EmptyROAPrefixList:



8.73.1 Detailed Description

```
Can't create ROA with an empty prefix list.
```

Definition at line 267 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.74 rpki.exceptions.ForbiddenURI Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.ForbiddenURI:



8.74.1 Detailed Description

```
Forbidden URI, does not start with correct base URI.
```

Definition at line 247 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.75 rpki.exceptions.HandleTranslationError Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.HandleTranslationError:



8.75.1 Detailed Description

```
Internal error translating protocol handle -> SQL id.
```

Definition at line 292 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.76 rpki.exceptions.HTTPRequestFailed Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.HTTPRequestFailed:



8.76.1 Detailed Description

```
HTTP request failed.
```

Definition at line 71 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.77 rpki.exceptions.HTTPSBadVersion Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.HTTPSBadVersion:



8.77.1 Detailed Description

```
HTTPS couldn't parse HTTP version.
```

Definition at line 287 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.78 rpki.exceptions.HTTPSClientAborted Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.HTTPSClientAborted:



8.78.1 Detailed Description

```
HTTPS client connection closed while in request-sent state.
```

Definition at line 252 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.79 rpki.exceptions.HTTPSUnexpectedState Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.HTTPSUnexpectedState:



8.79.1 Detailed Description

```
HTTPS event occurred in an unexpected state.
```

Definition at line 282 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.80 rpki.exceptions.MissingCMSCRL Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.MissingCMSCRL:



8.80.1 Detailed Description

```
Didn't receive CMS CRL when expecting one.
```

Definition at line 207 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.81 rpki.exceptions.MissingCMSEEcert Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.MissingCMSEEcert:



8.81.1 Detailed Description

```
Didn't receive CMS EE cert when expecting one.
```

Definition at line 202 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.82 rpki.exceptions.MultipleTLSEECert Class Reference

Inherits rpki::exceptions::TLSValidationError.

Collaboration diagram for rpki.exceptions.MultipleTLSEECert:



8.82.1 Detailed Description

```
Received more than one TLS EE certificate.
```

Definition at line 172 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.83 rpki.exceptions.MustBePrefix Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.MustBePrefix:



8.83.1 Detailed Description

```
Resource range cannot be expressed as a prefix.
```

Definition at line 162 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.84 rpki.exceptions.NoActiveCA Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.NoActiveCA:



8.84.1 Detailed Description

```
No active ca_detail for specified class.
```

Definition at line 227 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.85 rpki.exceptions.NoCoveringCertForROA Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.NoCoveringCertForROA:



8.85.1 Detailed Description

```
Couldn't find a covering certificate to generate ROA.
```

Definition at line 272 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.86 rpki.exceptions.NoObjectAtURI Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.NoObjectAtURI:



8.86.1 Detailed Description

```
No object published at specified URI.
```

Definition at line 297 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.87 rpki.exceptions.NotACertificateChain Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.NotACertificateChain:



8.87.1 Detailed Description

```
Certificates don't form a proper chain.
```

Definition at line 82 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.88 rpki.exceptions.NotFound Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.NotFound:



8.88.1 Detailed Description

```
Object not found in database.
```

Definition at line 157 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.89 rpki.exceptions.NotImplementedYet Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.NotImplementedYet:



8.89.1 Detailed Description

```
Internal error -- not implemented yet.
```

Definition at line 102 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.90 rpki.exceptions.NotInDatabase Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.NotInDatabase:



8.90.1 Detailed Description

```
Lookup failed for an object expected to be in the database.
```

Definition at line 40 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.91 rpki.exceptions.ReceivedTLSCACert Class Reference

Inherits rpki::exceptions::TLSValidationError.

Collaboration diagram for rpki.exceptions.ReceivedTLSCACert:



8.91.1 Detailed Description

`Received CA certificate via TLS.`

Definition at line 177 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.92 rpki.exceptions.RPKI_Exception Class Reference

Inherits Exception.

Inherited by rpki.exceptions.BadClassNameSyntax, rpki.exceptions.BadClientURL, rpki.exceptions.BadContactURL, rpki.exceptions.BadExtension, rpki.exceptions.BadIRDBReply, rpki.exceptions.BadIssueResponse, rpki.exceptions.BadPKCS10, rpki.exceptions.BadPublicationReply, rpki.exceptions.BadQuery, rpki.exceptions.BadSender, rpki.exceptions.BadStatusCode, rpki.exceptions.BadURISyntax, rpki.exceptions.BSCNotFound, rpki.exceptions.BSCNotReady, rpki.exceptions.ChildNotFound, rpki.exceptions.ClassNameMismatch, rpki.exceptions.ClassNameUnknown, rpki.exceptions.ClientNotFound, rpki.exceptions.CMSContentNotSet, rpki.exceptions.CMSCRLNotSet, rpki.exceptions.CMSVerificationFailed, rpki.exceptions.DBConsistancyError, rpki.exceptions.DERObjectConversionError, rpki.exceptions.DuplicateObject, rpki.exceptions.EmptyPEM, rpki.exceptions.EmptyROAPrefixList, rpki.exceptions.ForbiddenURI, rpki.exceptions.HandleTranslationError, rpki.exceptions.HTTPRequestFailed, rpki.exceptions.HTTPSBadVersion, rpki.exceptions.HTTPSClientAborted, rpki.exceptions.HTTPSUnexpectedState, rpki.exceptions.MissingCMSCRL, rpki.exceptions.MissingCMSEEcert, rpki.exceptions.MustBePrefix, rpki.exceptions.NoActiveCA, rpki.exceptions.NoCoveringCertForROA, rpki.exceptions.NoObjectAtURI, rpki.exceptions.NotACertificateChain, rpki.exceptions.NotFound, rpki.exceptions.NotImplementedYet, rpki.exceptions.NotInDatabase, rpki.exceptions.ServerShuttingDown, rpki.exceptions.SKIMismatch, rpki.exceptions.SubprocessError, rpki.exceptions.TLSValidationError, rpki.exceptions.UnexpectedCMSCerts, rpki.exceptions.UnexpectedCMSCRLs, rpki.exceptions.UnparsableCMSDER, rpki.exceptions.UpstreamError, and rpki.exceptions.WrongEContentType.

Collaboration diagram for rpki.exceptions.RPKI_Exception:



8.92.1 Detailed Description

```
Base class for RPKI exceptions.
```

Definition at line 35 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.93 rpki.exceptions.ServerShuttingDown Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.ServerShuttingDown:



8.93.1 Detailed Description

```
Server is shutting down.
```

Definition at line 222 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.94 rpki.exceptions.SKIMismatch Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.SKIMismatch:



8.94.1 Detailed Description

```
SKI value in response does not match request.
```

Definition at line 142 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.95 rpki.exceptions.SubprocessError Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.SubprocessError:



8.95.1 Detailed Description

```
Subprocess returned unexpected error.
```

Definition at line 147 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.96 rpki.exceptions.TLSValidationError Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Inherited by rpki.exceptions.MultipleTLSEECert, and rpki.exceptions.ReceivedTLSCACert.

Collaboration diagram for rpki.exceptions.TLSValidationError:



8.96.1 Detailed Description

```
TLS certificate validation error.
```

Definition at line 167 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.97 rpki.exceptions.UnexpectedCMSCerts Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.UnexpectedCMSCerts:



8.97.1 Detailed Description

```
Received CMS certs when not expecting any.
```

Definition at line 192 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.98 rpki.exceptions.UnexpectedCMSCRLs Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.UnexpectedCMSCRLs:



8.98.1 Detailed Description

```
Received CMS CRLs when not expecting any.
```

Definition at line 197 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.99 rpki.exceptions.UnparsableCMSDER Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.UnparsableCMSDER:



8.99.1 Detailed Description

```
Alleged CMS DER wasn't parsable.
```

Definition at line 212 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.100 rpki.exceptions.UpstreamError Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.UpstreamError:



8.100.1 Detailed Description

```
Received an error from upstream.
```

Definition at line 112 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.101 rpki.exceptions.WrongEContentType Class Reference

Inherits rpki::exceptions::RPKI_Exception.

Collaboration diagram for rpki.exceptions.WrongEContentType:



8.101.1 Detailed Description

```
Received wrong CMS eContentType.
```

Definition at line 182 of file exceptions.py.

The documentation for this class was generated from the following file:

- exceptions.py (2907)

8.102 rpki.https.caller Class Reference

Inherits object.

Collaboration diagram for rpki.https.caller:



Public Member Functions

- def __call__
- def __init__

Public Attributes

- client_cert

- client_key
- proto
- server_cert
- server_ta
- url

Static Public Attributes

- debug = False

8.102.1 Detailed Description

```
Handle client-side mechanics for protocols based on HTTPS, CMS, and
rpki.xml_utils.  Calling sequence is intended to nest within
rpki.async.sync_wrapper.
```

Definition at line 805 of file https.py.

8.102.2 Member Function Documentation

8.102.2.1 def rpki.https.caller.__call__ (*self*, *cb*, *eb*, *pdus*)

Definition at line 824 of file https.py.

8.102.2.2 def rpki.https.caller.__init__ (*self*, *proto*, *client_key*, *client_cert*, *server_ta*, *server_cert*, *url*, *debug* = `None`)

Definition at line 814 of file https.py.

8.102.3 Member Data Documentation

8.102.3.1 rpki.https.caller.client_cert

Definition at line 817 of file https.py.

8.102.3.2 rpki.https.caller.client_key

Definition at line 816 of file https.py.

8.102.3.3 rpki.https.caller.debug = False [static]

Definition at line 812 of file https.py.

8.102.3.4 rpki.https.caller.proto

Definition at line 815 of file https.py.

8.102.3.5 rpki.https.caller.server_cert

Definition at line 819 of file https.py.

8.102.3.6 rpki.https.caller.server_ta

Definition at line 818 of file https.py.

8.102.3.7 rpki.https.caller.url

Definition at line 820 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.103 rpki.https.http_client Class Reference

Inherits rpki::https::http_stream.

Collaboration diagram for rpki.https.http_client:



Public Member Functions

- def __init__
- def handle_close
- def handle_connect
- def handle_error
- def handle_message

- def handle_no_content_length
- def handle_timeout
- def send_request
- def set_state
- def start
- def tls_connect

Public Attributes

- af
- cert
- expect_close
- hostport
- key
- queue
- retry_read
- retry_write
- state
- ta
- tls

Static Public Attributes

- parse_type = http_response
- timeout = default_client_timeout

8.103.1 Detailed Description

Definition at line 543 of file https.py.

8.103.2 Member Function Documentation

8.103.2.1 def rpki.https.http_client.__init__ (*self*, *queue*, *hostport*, *cert* = `None`, *key* = `None`, *ta* = `()`, *af* = supported_address_families`[0]`)

Definition at line 549 of file https.py.

8.103.2.2 def rpki.https.http_client.handle_close (*self*)

Reimplemented from rpki.https.http_stream.

Definition at line 639 of file https.py.

8.103.2.3 def rpki.https.http_client.handle_connect (*self*)

Definition at line 571 of file https.py.

8.103.2.4 def rpki.https.http_client.handle_error (*self*)

Reimplemented from rpki.https.http_stream.

Definition at line 654 of file https.py.

8.103.2.5 def rpki.https.http_client.handle_message (*self*)

Definition at line 612 of file https.py.

8.103.2.6 def rpki.https.http_client.handle_no_content_length (*self*)

Definition at line 601 of file https.py.

8.103.2.7 def rpki.https.http_client.handle_timeout (*self*)

Reimplemented from rpki.https.http_stream.

Definition at line 648 of file https.py.

8.103.2.8 def rpki.https.http_client.send_request (*self*, *msg*)

Definition at line 604 of file https.py.

8.103.2.9 def rpki.https.http_client.set_state (*self*, *state*)

Definition at line 597 of file https.py.

8.103.2.10 def rpki.https.http_client.start (*self*)

Definition at line 562 of file https.py.

8.103.2.11 def rpki.https.http_client.tls_connect (*self*)

Definition at line 585 of file https.py.

8.103.3 Member Data Documentation

8.103.3.1 rpki.https.http_client.af

Definition at line 560 of file https.py.

8.103.3.2 rpki.https.http_client.cert

Definition at line 557 of file https.py.

8.103.3.3 rpki.https.http_client.expect_close

Definition at line 556 of file https.py.

8.103.3.4 rpki.https.http_client.hostport

Definition at line 554 of file https.py.

8.103.3.5 rpki.https.http_client.key

Definition at line 558 of file https.py.

8.103.3.6 rpki.https.http_client.parse_type = http_response [static]

Definition at line 545 of file https.py.

8.103.3.7 rpki.https.http_client.queue

Definition at line 553 of file https.py.

8.103.3.8 rpki.https.http_client.retry_read

Reimplemented from rpki.https.http_stream.

Definition at line 589 of file https.py.

8.103.3.9 rpki.https.http_client.retry_write

Reimplemented from rpki.https.http_stream.

Definition at line 591 of file https.py.

8.103.3.10 rpki.https.http_client.state

Definition at line 555 of file https.py.

8.103.3.11 rpki.https.http_client.ta

Definition at line 559 of file https.py.

8.103.3.12 rpki.https.http_client.timeout = default_client_timeout [static]

Definition at line 547 of file https.py.

8.103.3.13 rpki.https.http_client.tls

Reimplemented from rpki.https.http_stream.

Definition at line 573 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.104 rpki.https.http_listener Class Reference

Inherits asyncore::dispatcher.

Collaboration diagram for rpki.https.http_listener:



Public Member Functions

- def __init__
- def handle_accept
- def handle_error

Public Attributes

- cert
- dynamic_ta
- handlers
- key
- ta

Static Public Attributes

- log = log_method

8.104.1 Detailed Description

Definition at line 501 of file https.py.

8.104.2 Member Function Documentation

8.104.2.1 def rpki.https.http_listener.__init__ (*self*, *handlers*, *port* = `80`, *host* = `""`, *cert* = `None`, *key* = `None`, *ta* = `None`, *dynamic_ta* = `None`, *af* = supported_address_families`[0]`)

Definition at line 505 of file https.py.

8.104.2.2 def rpki.https.http_listener.handle_accept (*self*)

Definition at line 526 of file https.py.

8.104.2.3 def rpki.https.http_listener.handle_error (*self*)

Definition at line 535 of file https.py.

8.104.3 Member Data Documentation

8.104.3.1 rpki.https.http_listener.cert

Definition at line 509 of file https.py.

8.104.3.2 rpki.https.http_listener.dynamic_ta

Definition at line 512 of file https.py.

8.104.3.3 rpki.https.http_listener.handlers

Definition at line 508 of file https.py.

8.104.3.4 rpki.https.http_listener.key

Definition at line 510 of file https.py.

8.104.3.5 rpki.https.http_listener.log = log_method `[static]`

Definition at line 503 of file https.py.

8.104.3.6 rpki.https.http_listener.ta

Definition at line 511 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.105 rpki.https.http_message Class Reference

Inherits object.

Inherited by rpki.https.http_request, and rpki.https.http_response.

Collaboration diagram for rpki.https.http_message:



Public Member Functions

- def __init__
- def __str__
- def format
- def normalize_headers
- def parse_from_wire
- def parse_version
- def persistent

Public Attributes

- body
- headers
- version

Static Public Attributes

- string software_name = "ISC RPKI library"

8.105.1 Detailed Description

Definition at line 77 of file https.py.

8.105.2 Member Function Documentation

8.105.2.1 def rpki.https.http_message.__init__ (*self*, *version* = `None`, *body* = `None`, *headers* = `None`)

Definition at line 81 of file https.py.

8.105.2.2 def rpki.https.http_message.__str__ (*self*)

Definition at line 129 of file https.py.

8.105.2.3 def rpki.https.http_message.format (*self*)

Definition at line 117 of file https.py.

8.105.2.4 def rpki.https.http_message.normalize_headers (*self*, *headers* = `None`)

Definition at line 87 of file https.py.

8.105.2.5 def rpki.https.http_message.parse_from_wire (*cls*, *headers*)

Definition at line 106 of file https.py.

8.105.2.6 def rpki.https.http_message.parse_version (*self*, *version*)

Definition at line 132 of file https.py.

8.105.2.7 def rpki.https.http_message.persistent (*self*)

Definition at line 137 of file https.py.

8.105.3 Member Data Documentation

8.105.3.1 rpki.https.http_message.body

Definition at line 83 of file https.py.

8.105.3.2 rpki.https.http_message.headers

Definition at line 84 of file https.py.

8.105.3.3 string rpki.https.http_message.software_name = "ISC RPKI library" [static]

Definition at line 79 of file https.py.

8.105.3.4 rpki.https.http_message.version

Definition at line 82 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.106 rpki.https.http_queue Class Reference

Inherits object.

Collaboration diagram for rpki.https.http_queue:



Public Member Functions

- def __init__
- def detach
- def request
- def restart
- def return_result
- def send_request

Public Attributes

- cert
- client
- hostport
- key
- queue
- ta

Static Public Attributes

- log = log_method

8.106.1 Detailed Description

Definition at line 661 of file https.py.

8.106.2 Member Function Documentation

8.106.2.1 def rpki.https.http_queue.__init__ (*self*, *hostport*, *cert* = `None`, *key* = `None`, *ta* = `()`)

Definition at line 665 of file https.py.

8.106.2.2 def rpki.https.http_queue.detach (*self*, *client*)

Definition at line 700 of file https.py.

8.106.2.3 def rpki.https.http_queue.request (*self*, *requests*)

Definition at line 675 of file https.py.

8.106.2.4 def rpki.https.http_queue.restart (*self*)

Definition at line 679 of file https.py.

8.106.2.5 def rpki.https.http_queue.return_result (*self*, *result*)

Definition at line 705 of file https.py.

8.106.2.6 def rpki.https.http_queue.send_request (*self*)

Definition at line 696 of file https.py.

8.106.3 Member Data Documentation

8.106.3.1 rpki.https.http_queue.cert

Definition at line 671 of file https.py.

8.106.3.2 rpki.https.http_queue.client

Definition at line 669 of file https.py.

8.106.3.3 rpki.https.http_queue.hostport

Definition at line 668 of file https.py.

8.106.3.4 rpki.https.http_queue.key

Definition at line 672 of file https.py.

8.106.3.5 rpki.https.http_queue.log = log_method [static]

Definition at line 663 of file https.py.

8.106.3.6 rpki.https.http_queue.queue

Definition at line 670 of file https.py.

8.106.3.7 rpki.https.http_queue.ta

Definition at line 673 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.107 rpki.https.http_request Class Reference

Inherits rpki::https::http_message.

Collaboration diagram for rpki.https.http_request:



Public Member Functions

- def __init__
- def format_first_line
- def parse_first_line

Public Attributes

- callback
- cmd
- errback
- path
- retried

8.107.1 Detailed Description

Definition at line 146 of file https.py.

8.107.2 Member Function Documentation

8.107.2.1 def rpki.https.http_request.__init__ (*self*, *cmd* = `None`, *path* = `None`, *version* = default_http_version, *body* = `None`, *callback* = `None`, *errback* = `None`, *headers*)

Definition at line 148 of file https.py.

8.107.2.2 def rpki.https.http_request.format_first_line (*self*)

Definition at line 162 of file https.py.

8.107.2.3 def rpki.https.http_request.parse_first_line (*self*, *cmd*, *path*, *version*)

Definition at line 157 of file https.py.

8.107.3 Member Data Documentation

8.107.3.1 rpki.https.http_request.callback

Definition at line 153 of file https.py.

8.107.3.2 rpki.https.http_request.cmd

Definition at line 151 of file https.py.

8.107.3.3 rpki.https.http_request.errback

Definition at line 154 of file https.py.

8.107.3.4 rpki.https.http_request.path

Definition at line 152 of file https.py.

8.107.3.5 rpki.https.http_request.retried

Definition at line 155 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.108 rpki.https.http_response Class Reference

Inherits rpki::https::http_message.

Collaboration diagram for rpki.https.http_response:



Public Member Functions

- def __init__
- def format_first_line
- def parse_first_line

Public Attributes

- code
- reason

8.108.1 Detailed Description

Definition at line 166 of file https.py.

8.108.2 Member Function Documentation

8.108.2.1 def rpki.https.http_response.__init__ (*self*, *code* = `None`, *reason* = `None`, *version* = default_http_version, *body* = `None`, *headers*)

Definition at line 168 of file https.py.

8.108.2.2 def rpki.https.http_response.format_first_line (*self*)

Definition at line 178 of file https.py.

8.108.2.3 def rpki.https.http_response.parse_first_line (*self*, *version*, *code*, *reason*)

Definition at line 173 of file https.py.

8.108.3 Member Data Documentation

8.108.3.1 rpki.https.http_response.code

Definition at line 170 of file https.py.

8.108.3.2 rpki.https.http_response.reason

Definition at line 171 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.109 rpki.https.http_server Class Reference

Inherits rpki::https::http_stream.

Collaboration diagram for rpki.https.http_server:



Public Member Functions

- def __init__
- def find_handler
- def handle_message
- def handle_no_content_length
- def send_error
- def send_message
- def send_reply
- def tls_accept

Public Attributes

- expect_close
- handlers
- retry_read
- retry_write
- tls

Static Public Attributes

- parse_type = http_request
- timeout = default_server_timeout

8.109.1 Detailed Description

Definition at line 398 of file https.py.

8.109.2 Member Function Documentation

8.109.2.1 def rpki.https.http_server.__init__ (*self*, *sock*, *handlers*, *cert* = `None`, *key* = `None`, *ta* = `()`, *dynamic_ta* = `None`)

Definition at line 404 of file https.py.

8.109.2.2 def rpki.https.http_server.find_handler (*self*, *path*)

```
Helper method to search self.handlers.
```

Definition at line 447 of file https.py.

8.109.2.3 def rpki.https.http_server.handle_message (*self*)

Definition at line 456 of file https.py.

8.109.2.4 def rpki.https.http_server.handle_no_content_length (*self*)

Definition at line 444 of file https.py.

8.109.2.5 def rpki.https.http_server.send_error (*self*, *code*, *reason*)

Definition at line 479 of file https.py.

8.109.2.6 def rpki.https.http_server.send_message (*self*, *code*, *reason* = `"OK"`, *body* = `None`)

Definition at line 485 of file https.py.

8.109.2.7 def rpki.https.http_server.send_reply (*self*, *code*, *body*)

Definition at line 482 of file https.py.

8.109.2.8 def rpki.https.http_server.tls_accept (*self*)

Definition at line 426 of file https.py.

8.109.3 Member Data Documentation

8.109.3.1 rpki.https.http_server.expect_close

Definition at line 408 of file https.py.

8.109.3.2 rpki.https.http_server.handlers

Definition at line 406 of file https.py.

8.109.3.3 rpki.https.http_server.parse_type = http_request [static]

Definition at line 400 of file https.py.

8.109.3.4 rpki.https.http_server.retry_read

Reimplemented from rpki.https.http_stream.

Definition at line 430 of file https.py.

8.109.3.5 rpki.https.http_server.retry_write

Reimplemented from rpki.https.http_stream.

Definition at line 432 of file https.py.

8.109.3.6 rpki.https.http_server.timeout = default_server_timeout [static]

Definition at line 402 of file https.py.

8.109.3.7 rpki.https.http_server.tls

Reimplemented from rpki.https.http_stream.

Definition at line 412 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.110 rpki.https.http_stream Class Reference

Inherits asynchat::async_chat.

Inherited by rpki.https.http_client, and rpki.https.http_server.

Collaboration diagram for rpki.https.http_stream:



Public Member Functions

- def __init__

- def chunk_body
- def chunk_discard_crlf
- def chunk_discard_trailer
- def chunk_header
- def close
- def collect_incoming_data
- def found_terminator
- def get_buffer
- def handle_body
- def handle_close
- def handle_error
- def handle_read
- def handle_timeout
- def handle_write
- def initiate_send
- def log_cert
- def readable
- def recv
- def restart
- def send
- def update_timeout
- def writeable

Public Attributes

- buffer
- chunk_handler
- msg
- timer

Static Public Attributes

- log = log_method
- retry_read = None
- retry_write = None
- tls = None

8.110.1 Detailed Description

Definition at line 188 of file https.py.

8.110.2 Member Function Documentation

8.110.2.1 def rpki.https.http_stream.__init__ (*self*, *sock* = `None`)

Definition at line 195 of file https.py.

8.110.2.2 def rpki.https.http_stream.chunk_body (*self*)

Definition at line 255 of file https.py.

8.110.2.3 def rpki.https.http_stream.chunk_discard_crlf (*self*)

Definition at line 262 of file https.py.

8.110.2.4 def rpki.https.http_stream.chunk_discard_trailer (*self*)

Definition at line 268 of file https.py.

8.110.2.5 def rpki.https.http_stream.chunk_header (*self*)

Definition at line 245 of file https.py.

8.110.2.6 def rpki.https.http_stream.close (*self*, *force* = `False`)

Definition at line 369 of file https.py.

8.110.2.7 def rpki.https.http_stream.collect_incoming_data (*self*, *data*)

```
Buffer the data
```

Definition at line 216 of file https.py.

8.110.2.8 def rpki.https.http_stream.found_terminator (*self*)

Definition at line 228 of file https.py.

8.110.2.9 def rpki.https.http_stream.get_buffer (*self*)

Definition at line 223 of file https.py.

8.110.2.10 def rpki.https.http_stream.handle_body (*self*)

Definition at line 275 of file https.py.

8.110.2.11 def rpki.https.http_stream.handle_close (*self*)

Reimplemented in rpki.https.http_client.

Definition at line 294 of file https.py.

8.110.2.12 def rpki.https.http_stream.handle_error (*self*)

Reimplemented in rpki.https.http_client.

Definition at line 279 of file https.py.

8.110.2.13 def rpki.https.http_stream.handle_read (*self*)

Definition at line 314 of file https.py.

8.110.2.14 def rpki.https.http_stream.handle_timeout (*self*)

Reimplemented in rpki.https.http_client.

Definition at line 290 of file https.py.

8.110.2.15 def rpki.https.http_stream.handle_write (*self*)

Definition at line 335 of file https.py.

8.110.2.16 def rpki.https.http_stream.initiate_send (*self*)

Definition at line 354 of file https.py.

8.110.2.17 def rpki.https.http_stream.log_cert (*self*, *tag*, *x*)

Definition at line 394 of file https.py.

8.110.2.18 def rpki.https.http_stream.readable (*self*)

Definition at line 308 of file https.py.

8.110.2.19 def rpki.https.http_stream.recv (*self*, *buffer_size*)

Definition at line 303 of file https.py.

8.110.2.20 def rpki.https.http_stream.restart (*self*)

Definition at line 201 of file https.py.

8.110.2.21 def rpki.https.http_stream.send (*self*, *data*)

Definition at line 298 of file https.py.

8.110.2.22 def rpki.https.http_stream.update_timeout (*self*)

Definition at line 210 of file https.py.

8.110.2.23 def rpki.https.http_stream.writeable (*self*)

Definition at line 311 of file https.py.

8.110.3 Member Data Documentation

8.110.3.1 rpki.https.http_stream.buffer

Definition at line 197 of file https.py.

8.110.3.2 rpki.https.http_stream.chunk_handler

Definition at line 203 of file https.py.

8.110.3.3 rpki.https.http_stream.log = log_method `[static]`

Definition at line 190 of file https.py.

8.110.3.4 rpki.https.http_stream.msg

Definition at line 235 of file https.py.

8.110.3.5 rpki.https.http_stream.retry_read = None `[static]`

Reimplemented in rpki.https.http_server, and rpki.https.http_client.

Definition at line 192 of file https.py.

8.110.3.6 rpki.https.http_stream.retry_write = None [static]

Reimplemented in rpki.https.http_server, and rpki.https.http_client.

Definition at line 193 of file https.py.

8.110.3.7 rpki.https.http_stream.timer

Definition at line 198 of file https.py.

8.110.3.8 rpki.https.http_stream.tls = None [static]

Reimplemented in rpki.https.http_server, and rpki.https.http_client.

Definition at line 191 of file https.py.

The documentation for this class was generated from the following file:

- https.py (3131)

8.111 rpki.ipaddrs.v4addr Class Reference

Inherits long.

Collaboration diagram for rpki.ipaddrs.v4addr:



Public Member Functions

- def __new__
- def __str__
- def from_bytes
- def to_bytes

Static Public Attributes

- int bits = 32

8.111.1 Detailed Description

```
IPv4 address.

Derived from long, but supports IPv4 print syntax.
```

Definition at line 47 of file ipaddrs.py.

8.111.2 Member Function Documentation

8.111.2.1 def rpki.ipaddrs.v4addr.__new__ (*cls*, *x*)

```
Construct a v4addr object.
```

Definition at line 56 of file ipaddrs.py.

8.111.2.2 def rpki.ipaddrs.v4addr.__str__ (*self*)

```
Convert a v4addr object to string format.
```

Definition at line 74 of file ipaddrs.py.

8.111.2.3 def rpki.ipaddrs.v4addr.from_bytes (*cls*, *x*)

```
Convert from a raw byte string to a v4addr object.
```

Definition at line 70 of file ipaddrs.py.

8.111.2.4 def rpki.ipaddrs.v4addr.to_bytes (*self*)

```
Convert a v4addr object to a raw byte string.
```

Definition at line 65 of file ipaddrs.py.

8.111.3 Member Data Documentation

8.111.3.1 int rpki.ipaddrs.v4addr.bits = 32 [static]

Definition at line 54 of file ipaddrs.py.

The documentation for this class was generated from the following file:

- ipaddrs.py (2424)

8.112 rpki.ipaddrs.v6addr Class Reference

Inherits long.

Collaboration diagram for rpki.ipaddrs.v6addr:



Public Member Functions

- def __new__
- def __str__
- def from_bytes
- def to_bytes

Static Public Attributes

- int bits = 128

8.112.1 Detailed Description

```
IPv6 address.

Derived from long, but supports IPv6 print syntax.
```

Definition at line 78 of file ipaddrs.py.

8.112.2 Member Function Documentation

8.112.2.1 def rpki.ipaddrs.v6addr.__new__ (*cls*, *x*)

```
Construct a v6addr object.
```

Definition at line 87 of file ipaddrs.py.

8.112.2.2 def rpki.ipaddrs.v6addr.__str__ (*self*)

```
Convert a v6addr object to string format.
```

Definition at line 104 of file ipaddrs.py.

8.112.2.3 def rpki.ipaddrs.v6addr.from_bytes (*cls*, *x*)

```
Convert from a raw byte string to a v6addr object.
```

Definition at line 99 of file ipaddrs.py.

8.112.2.4 def rpki.ipaddrs.v6addr.to_bytes (*self*)

```
Convert a v6addr object to a raw byte string.
```

Definition at line 94 of file ipaddrs.py.

8.112.3 Member Data Documentation

8.112.3.1 int rpki.ipaddrs.v6addr.bits = 128 [static]

Definition at line 85 of file ipaddrs.py.

The documentation for this class was generated from the following file:

- ipaddrs.py (2424)

8.113 rpki.left_right.bsc_elt Class Reference

Inherits rpki::left_right::data_elt.

Inherited by irbe_cli.bsc_elt.

Collaboration diagram for rpki.left_right.bsc_elt:



Public Member Functions

- def children
- def parents
- def repositories
- def serve_pre_save_hook

Static Public Attributes

- tuple attributes = ("action", "tag", "self_handle", "bsc_handle", "key_type", "hash_alg", "key_length")

  XML attributes for this element.

- tuple booleans = ("generate_keypair",)

  Boolean attributes (value "yes" or "no") for this element.

- string element_name = "bsc"
- tuple elements = ("signing_cert", "signing_cert_crl", "pkcs10_request")

  XML elements contained by this element.

- tuple handles = (("self", self_elt),)
- pkcs10_request = None
- private_key_id = None
- signing_cert = None
- signing_cert_crl = None
- tuple sql_template

8.113.1 Detailed Description

```
<bsc/> (Business Signing Context) element.
```

Definition at line 526 of file left_right.py.

8.113.2 Member Function Documentation

8.113.2.1 def rpki.left_right.bsc_elt.children (*self*)

```
Fetch all child objects that link to this BSC object.
```

Definition at line 557 of file left_right.py.

8.113.2.2 def rpki.left_right.bsc_elt.parents (*self*)

```
Fetch all parent objects that link to this BSC object.
```

Definition at line 553 of file left_right.py.

8.113.2.3 def rpki.left_right.bsc_elt.repositories (*self*)

```
Fetch all repository objects that link to this BSC object.
```

Definition at line 549 of file left_right.py.

8.113.2.4 def rpki.left_right.bsc_elt.serve_pre_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Extra server actions for bsc_elt -- handle key generation.  For
now this only allows RSA with SHA-256.
```

Reimplemented from rpki.left_right.data_elt.

Definition at line 561 of file left_right.py.

8.113.3 Member Data Documentation

8.113.3.1 tuple rpki.left_right.bsc_elt.attributes = ("action", "tag", "self_handle", "bsc_handle", "key_type", "hash_alg", "key_length") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 532 of file left_right.py.

8.113.3.2 tuple rpki.left_right.bsc_elt.booleans = ("generate_keypair",) [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 534 of file left_right.py.

8.113.3.3 string rpki.left_right.bsc_elt.element_name = "bsc" [static]

Definition at line 531 of file left_right.py.

8.113.3.4 tuple rpki.left_right.bsc_elt.elements = ("signing_cert", "signing_cert_crl", "pkcs10_request") [static]

XML elements contained by this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 533 of file left_right.py.

8.113.3.5 tuple rpki.left_right.bsc_elt.handles = (("self", self_elt),) [static]

Reimplemented from rpki.left_right.data_elt.

Definition at line 542 of file left_right.py.

8.113.3.6 rpki.left_right.bsc_elt.pkcs10_request = None [static]

Definition at line 545 of file left_right.py.

8.113.3.7 rpki.left_right.bsc_elt.private_key_id = None [static]

Definition at line 544 of file left_right.py.

8.113.3.8 rpki.left_right.bsc_elt.signing_cert = None [static]

Reimplemented in irbe_cli.bsc_elt.

Definition at line 546 of file left_right.py.

8.113.3.9 rpki.left_right.bsc_elt.signing_cert_crl = None [static]

Reimplemented in irbe_cli.bsc_elt.

Definition at line 547 of file left_right.py.

8.113.3.10 tuple rpki.left_right.bsc_elt.sql_template [static]

Initial value:

```
rpki.sql.template("bsc", "bsc_id", "bsc_handle",
                                   "self_id", "hash_alg",
                                   ("private_key_id", rpki.x509.RSA),
                                   ("pkcs10_request", rpki.x509.PKCS10),
                                   ("signing_cert", rpki.x509.X509),
                                   ("signing_cert_crl", rpki.x509.CRL))
```

Definition at line 536 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.114 rpki.left_right.child_elt Class Reference

Inherits rpki::left_right::data_elt.

Inherited by irbe_cli.child_elt.

Collaboration diagram for rpki.left_right.child_elt:



Public Member Functions

- def ca_from_class_name
- def child_certs
- def endElement
- def parents
- def serve_destroy_hook
- def serve_post_save_hook
- def serve_up_down

Static Public Attributes

- tuple attributes = ("action", "tag", "self_handle", "child_handle", "bsc_-handle")

  XML attributes for this element.

- tuple booleans = ("reissue",)

  Boolean attributes (value "yes" or "no") for this element.

- bpki_cert = None
- bpki_glue = None
- clear_https_ta_cache = False
- string element_name = "child"
- tuple elements = ("bpki_cert", "bpki_glue")

  XML elements contained by this element.

- tuple handles = (("self", self_elt), ("bsc", bsc_elt))
- tuple sql_template

8.114.1 Detailed Description

```
<child/> element.
```

Definition at line 802 of file left_right.py.

8.114.2 Member Function Documentation

8.114.2.1 def rpki.left_right.child_elt.ca_from_class_name (*self*, *class_name*)

```
Fetch the CA corresponding to an up-down class_name.
```

Definition at line 831 of file left_right.py.

8.114.2.2 def rpki.left_right.child_elt.child_certs (*self*, *ca_detail* = `None`, *ski* = `None`, *unique* = `False`)

```
Fetch all child_cert objects that link to this child object.
```

Definition at line 823 of file left_right.py.

8.114.2.3 def rpki.left_right.child_elt.endElement (*self*, *stack*, *name*, *text*)

```
Handle subelements of <child/> element.  These require special
handling because modifying them invalidates the HTTPS trust anchor
cache.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 863 of file left_right.py.

8.114.2.4 def rpki.left_right.child_elt.parents (*self*)

```
Fetch all parent objects that link to self object to which this child object links.
```

Definition at line 827 of file left_right.py.

8.114.2.5 def rpki.left_right.child_elt.serve_destroy_hook (*self*, *cb*, *eb*)

```
Extra server actions when destroying a child_elt.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 855 of file left_right.py.

8.114.2.6 def rpki.left_right.child_elt.serve_post_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Extra server actions for child_elt.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 845 of file left_right.py.

8.114.2.7 def rpki.left_right.child_elt.serve_up_down (*self*, *query*, *callback*)

```
Outer layer of server handling for one up-down PDU from this child.
```

Definition at line 873 of file left_right.py.

8.114.3 Member Data Documentation

8.114.3.1 tuple rpki.left_right.child_elt.attributes = ("action", "tag", "self_handle", "child_handle", "bsc_handle") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 808 of file left_right.py.

8.114.3.2 tuple rpki.left_right.child_elt.booleans = ("reissue",) [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 810 of file left_right.py.

8.114.3.3 rpki.left_right.child_elt.bpki_cert = None [static]

Definition at line 819 of file left_right.py.

8.114.3.4 rpki.left_right.child_elt.bpki_glue = None [static]

Definition at line 820 of file left_right.py.

8.114.3.5 rpki.left_right.child_elt.clear_https_ta_cache = False [static]

Definition at line 821 of file left_right.py.

8.114.3.6 string rpki.left_right.child_elt.element_name = "child" [static]

Definition at line 807 of file left_right.py.

8.114.3.7 tuple rpki.left_right.child_elt.elements = ("bpki_cert", "bpki_glue") [static]

XML elements contained by this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 809 of file left_right.py.

8.114.3.8 tuple rpki.left_right.child_elt.handles = (("self", self_elt), ("bsc", bsc_elt)) [static]

Reimplemented from rpki.left_right.data_elt.

Definition at line 817 of file left_right.py.

8.114.3.9 tuple rpki.left_right.child_elt.sql_template [static]

Initial value:

```
rpki.sql.template("child", "child_id", "child_handle",
                                  "self_id", "bsc_id",
                                  ("bpki_cert", rpki.x509.X509),
                                  ("bpki_glue", rpki.x509.X509))
```

Definition at line 812 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.115 rpki.left_right.cms_msg Class Reference

Inherits rpki::x509::XML_CMS_object.

Inherited by irbe_cli.left_right_cms_msg.

Collaboration diagram for rpki.left_right.cms_msg:



Static Public Attributes

- string encoding = "us-ascii"
- saxify = sax_handler.saxify
- schema = rpki.relaxng.left_right

8.115.1 Detailed Description

```
Class to hold a CMS-signed left-right PDU.
```

Definition at line 1117 of file left_right.py.

8.115.2 Member Data Documentation

8.115.2.1 string rpki.left_right.cms_msg.encoding = "us-ascii" [static]

Definition at line 1122 of file left_right.py.

8.115.2.2 rpki.left_right.cms_msg.saxify = sax_handler.saxify [static]

Reimplemented in irbe_cli.left_right_cms_msg.

Definition at line 1124 of file left_right.py.

8.115.2.3 rpki.left_right.cms_msg.schema = rpki.relaxng.left_right [static]

Definition at line 1123 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.116 rpki.left_right.data_elt Class Reference

Inherits rpki::xml_utils::data_elt, rpki::sql::sql_persistent, and rpki::left_right::left_-right_namespace.

Inherited by rpki.left_right.bsc_elt, rpki.left_right.child_elt, rpki.left_right.parent_elt, rpki.left_right.repository_elt, and rpki.left_right.self_elt.

Collaboration diagram for rpki.left_right.data_elt:



Public Member Functions

- def bsc
- def make_reply_clone_hook
- def self
- def serve_fetch_all
- def serve_fetch_handle
- def serve_fetch_one_maybe
- def serve_pre_save_hook

Static Public Attributes

- tuple handles = ()
- self_handle = None
- self_id = None

8.116.1 Detailed Description

```
Virtual class for top-level left-right protocol data elements.
```

Definition at line 50 of file left_right.py.

8.116.2 Member Function Documentation

8.116.2.1 def rpki.left_right.data_elt.bsc (*self*)

```
Return BSC object to which this object links.
```

Definition at line 64 of file left_right.py.

8.116.2.2 def rpki.left_right.data_elt.make_reply_clone_hook (*self*, *r_pdu*)

```
Set handles when cloning, including _id -> _handle translation.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 68 of file left_right.py.

8.116.2.3 def rpki.left_right.data_elt.self (*self*)

```
Fetch self object to which this object links.
```

Definition at line 60 of file left_right.py.

8.116.2.4 def rpki.left_right.data_elt.serve_fetch_all (*self*)

```
Find the objects on which a list method should operate.
```

Reimplemented in rpki.left_right.self_elt.

Definition at line 99 of file left_right.py.

8.116.2.5 def rpki.left_right.data_elt.serve_fetch_handle (*cls*, *gctx*, *self_id*, *handle*)

```
Find an object based on its handle.
```

Reimplemented in rpki.left_right.self_elt.

Definition at line 84 of file left_right.py.

8.116.2.6 def rpki.left_right.data_elt.serve_fetch_one_maybe (*self*)

```
Find the object on which a get, set, or destroy method should
operate, or which would conflict with a create method.
```

Reimplemented in rpki.left_right.self_elt.

Definition at line 90 of file left_right.py.

8.116.2.7 def rpki.left_right.data_elt.serve_pre_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Hook to do _handle => _id translation before saving.

self is always the object to be saved to SQL.  For create
operations, self and q_pdu are be the same object; for set
operations, self is the pre-existing object from SQL and q_pdu is
the set request received from the the IRBE.
```

Reimplemented from rpki.xml_utils.data_elt.

Reimplemented in rpki.left_right.bsc_elt.

Definition at line 106 of file left_right.py.

8.116.3 Member Data Documentation

8.116.3.1 tuple rpki.left_right.data_elt.handles = () [static]

Reimplemented in rpki.left_right.self_elt, rpki.left_right.bsc_elt, rpki.left_right.repository_elt, rpki.left_right.parent_elt, and rpki.left_right.child_elt.

Definition at line 55 of file left_right.py.

8.116.3.2 rpki.left_right.data_elt.self_handle = None [static]

Definition at line 58 of file left_right.py.

8.116.3.3 rpki.left_right.data_elt.self_id = None [static]

Definition at line 57 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.117 rpki.left_right.left_right_namespace Class Reference

Inherits object.

Inherited by rpki.left_right.data_elt, rpki.left_right.list_published_objects_elt, rpki.left_right.list_received_resources_elt, rpki.left_right.list_resources_elt, rpki.left_right.list_roa_requests_elt, rpki.left_right.msg, and rpki.left_right.report_error_elt.

Collaboration diagram for rpki.left_right.left_right_namespace:



Static Public Attributes

- dictionary nsmap = { None : xmlns }
- string xmlns = "http://www.hactrn.net/uris/rpki/left-right-spec/"

8.117.1 Detailed Description

```
XML namespace parameters for left-right protocol.
```

Definition at line 42 of file left_right.py.

8.117.2 Member Data Documentation

8.117.2.1 dictionary rpki.left_right.left_right_namespace.nsmap = { None : xmlns } [static]

Definition at line 48 of file left_right.py.

8.117.2.2 string rpki.left_right.left_right_namespace.xmlns = "http://www.hactrn.net/uris/rpki/left-right-spec/" [static]

Definition at line 47 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.118 rpki.left_right.list_published_objects_elt Class Reference

Inherits rpki::xml_utils::text_elt, and rpki::left_right::left_right_namespace.

Inherited by irbe_cli.list_published_objects_elt.

Collaboration diagram for rpki.left_right.list_published_objects_elt:



Public Member Functions

- def make_reply
- def serve_dispatch

Static Public Attributes

- tuple attributes = ("self_handle", "tag", "uri")

  XML attributes for this element.

- string element_name = "list_published_objects"
- obj = None
- string text_attribute = "obj"

  Name of the class attribute that holds the text value.

8.118.1 Detailed Description

```
<list_published_objects/> element.
```

Definition at line 965 of file left_right.py.

8.118.2 Member Function Documentation

8.118.2.1 def rpki.left_right.list_published_objects_elt.make_reply (*self*, *uri*, *obj*)

```
Generate one reply PDU.
```

Definition at line 992 of file left_right.py.

8.118.2.2 def rpki.left_right.list_published_objects_elt.serve_dispatch (*self*, *r_msg*, *cb*, *eb*)

```
Handle a <list_published_objects/> query.  The method name is a
misnomer here, there's no action attribute and no dispatch, we
just dump every published object for the specified <self/> and return.
```

Definition at line 976 of file left_right.py.

8.118.3 Member Data Documentation

8.118.3.1 tuple rpki.left_right.list_published_objects_elt.attributes = ("self_handle", "tag", "uri") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 971 of file left_right.py.

8.118.3.2 string rpki.left_right.list_published_objects_elt.element_name = "list_published_objects" [static]

Definition at line 970 of file left_right.py.

8.118.3.3 rpki.left_right.list_published_objects_elt.obj = None [static]

Definition at line 974 of file left_right.py.

8.118.3.4 string rpki.left_right.list_published_objects_elt.text_attribute = "obj" [static]

Name of the class attribute that holds the text value.

Reimplemented from rpki.xml_utils.text_elt.

Definition at line 972 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.119 rpki.left_right.list_received_resources_elt Class Reference

Inherits rpki::xml_utils::base_elt, and rpki::left_right::left_right_namespace.

Inherited by irbe_cli.list_received_resources_elt.

Collaboration diagram for rpki.left_right.list_received_resources_elt:



Public Member Functions

- def make_reply
- def serve_dispatch

Static Public Attributes

- tuple attributes

  XML attributes for this element.

- string element_name = "list_received_resources"

8.119.1 Detailed Description

```
<list_received_resources/> element.
```

Definition at line 1000 of file left_right.py.

8.119.2 Member Function Documentation

8.119.2.1 def rpki.left_right.list_received_resources_elt.make_reply (*self*, *uri*, *cert*)

```
Generate one reply PDU.
```

Definition at line 1023 of file left_right.py.

8.119.2.2 def rpki.left_right.list_received_resources_elt.serve_dispatch (*self*, *r_msg*, *cb*, *eb*)

```
Handle a <list_received_resources/> query.  The method name is a
misnomer here, there's no action attribute and no dispatch, we
just dump a bunch of data about every certificate issued to us by
one of our parents, then return.
```

Definition at line 1009 of file left_right.py.

8.119.3 Member Data Documentation

8.119.3.1 tuple rpki.left_right.list_received_resources_elt.attributes [static]

Initial value:

```
("self_handle", "tag",
                "notBefore", "notAfter", "uri", "sia_uri", "aia_uri", "asn", "ipv
      4", "ipv6")
```

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 1006 of file left_right.py.

8.119.3.2 string rpki.left_right.list_received_resources_elt.element_name = "list_received_resources" [static]

Definition at line 1005 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.120 rpki.left_right.list_resources_elt Class Reference

Inherits rpki::xml_utils::base_elt, and rpki::left_right::left_right_namespace.

Collaboration diagram for rpki.left_right.list_resources_elt:



Public Member Functions

- def startElement
- def toXML

Public Attributes

- asn

- ipv4
- ipv6

Static Public Attributes

- tuple attributes = ("self_handle", "tag", "child_handle", "valid_until", "asn", "ipv4", "ipv6")

  XML attributes for this element.

- string element_name = "list_resources"
- valid_until = None

8.120.1 Detailed Description

```
<list_resources/> element.
```

Definition at line 910 of file left_right.py.

8.120.2 Member Function Documentation

8.120.2.1 def rpki.left_right.list_resources_elt.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle <list_resources/> element.  This requires special handling
due to the data types of some of the attributes.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 919 of file left_right.py.

8.120.2.2 def rpki.left_right.list_resources_elt.toXML (*self*)

```
Generate <list_resources/> element.  This requires special
handling due to the data types of some of the attributes.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 935 of file left_right.py.

8.120.3 Member Data Documentation

8.120.3.1 rpki.left_right.list_resources_elt.asn

Definition at line 929 of file left_right.py.

8.120.3.2 tuple rpki.left_right.list_resources_elt.attributes = ("self_handle", "tag", "child_handle", "valid_until", "asn", "ipv4", "ipv6") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 916 of file left_right.py.

8.120.3.3 string rpki.left_right.list_resources_elt.element_name = "list_resources" [static]

Definition at line 915 of file left_right.py.

8.120.3.4 rpki.left_right.list_resources_elt.ipv4

Definition at line 931 of file left_right.py.

8.120.3.5 rpki.left_right.list_resources_elt.ipv6

Definition at line 933 of file left_right.py.

8.120.3.6 rpki.left_right.list_resources_elt.valid_until = None [static]

Definition at line 917 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.121 rpki.left_right.list_roa_requests_elt Class Reference

Inherits rpki::xml_utils::base_elt, and rpki::left_right::left_right_namespace.

Collaboration diagram for rpki.left_right.list_roa_requests_elt:



Public Member Functions

- def startElement

Public Attributes

- ipv4
- ipv6

Static Public Attributes

- tuple attributes = ("self_handle", "tag", "asn", "ipv4", "ipv6")

  XML attributes for this element.

- string element_name = "list_roa_requests"

8.121.1 Detailed Description

```
<list_roa_requests/> element.
```

Definition at line 945 of file left_right.py.

8.121.2 Member Function Documentation

8.121.2.1 def rpki.left_right.list_roa_requests_elt.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle <list_roa_requests/> element.  This requires special handling
due to the data types of some of the attributes.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 953 of file left_right.py.

8.121.3 Member Data Documentation

8.121.3.1 tuple rpki.left_right.list_roa_requests_elt.attributes = ("self_handle", "tag", "asn", "ipv4", "ipv6") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 951 of file left_right.py.

8.121.3.2 string rpki.left_right.list_roa_requests_elt.element_name = "list_roa_requests" [static]

Definition at line 950 of file left_right.py.

8.121.3.3 rpki.left_right.list_roa_requests_elt.ipv4

Definition at line 961 of file left_right.py.

8.121.3.4 rpki.left_right.list_roa_requests_elt.ipv6

Definition at line 963 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.122 rpki.left_right.msg Class Reference

Inherits rpki::xml_utils::msg, and rpki::left_right::left_right_namespace.

Inherited by irbe_cli.left_right_msg.

Collaboration diagram for rpki.left_right.msg:



Public Member Functions

- def serve_top_level

Static Public Attributes

- tuple pdus

Dispatch table of PDUs for this protocol.

- int version = 1

  Protocol version.

8.122.1 Detailed Description

```
Left-right PDU.
```

Definition at line 1063 of file left_right.py.

8.122.2 Member Function Documentation

8.122.2.1 def rpki.left_right.msg.serve_top_level (*self*, *gctx*, *cb*)

```
Serve one msg PDU.
```

Definition at line 1080 of file left_right.py.

8.122.3 Member Data Documentation

8.122.3.1 rpki::left_right.msg::pdus [static]

Initial value:

```
dict((x.element_name, x)
              for x in (self_elt, child_elt, parent_elt, bsc_elt, repository_elt,

                        list_resources_elt, list_roa_requests_elt,
                        list_published_objects_elt, list_received_resources_elt,
                        report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented in irbe_cli.left_right_msg.

Definition at line 1074 of file left_right.py.

8.122.3.2 rpki::left_right.msg::version = 1 [static]

Protocol version.

Reimplemented from rpki.xml_utils.msg.

Definition at line 1070 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.123 rpki.left_right.parent_elt Class Reference

Inherits rpki::left_right::data_elt.

Inherited by irbe_cli.parent_elt.

Collaboration diagram for rpki.left_right.parent_elt:



Public Member Functions

- def cas
- def query_up_down
- def repository
- def serve_post_save_hook
- def serve_rekey
- def serve_revoke
- def serve_revoke_forgotten

Static Public Attributes

- tuple attributes

  XML attributes for this element.

- tuple booleans = ("rekey", "reissue", "revoke", "revoke_forgotten")

  Boolean attributes (value "yes" or "no") for this element.

- bpki_cms_cert = None
- bpki_cms_glue = None
- bpki_https_cert = None
- bpki_https_glue = None
- string element_name = "parent"
- tuple elements = ("bpki_cms_cert", "bpki_cms_glue", "bpki_https_cert", "bpki_https_glue")

  XML elements contained by this element.

- tuple handles = (("self", self_elt), ("bsc", bsc_elt), ("repository", repository_elt))
- tuple sql_template

8.123.1 Detailed Description

```
<parent/> element.
```

Definition at line 653 of file left_right.py.

8.123.2 Member Function Documentation

8.123.2.1 def rpki.left_right.parent_elt.cas (*self*)

```
Fetch all CA objects that link to this parent object.
```

Definition at line 680 of file left_right.py.

8.123.2.2 def rpki.left_right.parent_elt.query_up_down (*self*, *q_pdu*, *cb*, *eb*)

```
Client code for sending one up-down query PDU to this parent.
```

Definition at line 756 of file left_right.py.

8.123.2.3 def rpki.left_right.parent_elt.repository (*self*)

```
Fetch repository object to which this parent object links.
```

Definition at line 676 of file left_right.py.

8.123.2.4 def rpki.left_right.parent_elt.serve_post_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Extra server actions for parent_elt.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 684 of file left_right.py.

8.123.2.5 def rpki.left_right.parent_elt.serve_rekey (*self*, *cb*, *eb*)

```
Handle a left-right rekey action for this parent.
```

Definition at line 700 of file left_right.py.

8.123.2.6 def rpki.left_right.parent_elt.serve_revoke (*self*, *cb*, *eb*)

```
Handle a left-right revoke action for this parent.
```

Definition at line 708 of file left_right.py.

8.123.2.7 def rpki.left_right.parent_elt.serve_revoke_forgotten (*self*, *cb*, *eb*)

```
Handle a left-right revoke_forgotten action for this parent.

This is a bit fiddly: we have to compare the result of an up-down
list query with what we have locally and identify the SKIs of any
certificates that have gone missing.  This should never happen in
ordinary operation, but can arise if we have somehow lost a
private key, in which case there is nothing more we can do with
the issued cert, so we have to clear it.  As this really is not
supposed to happen, we don't clear it automatically, instead we
require an explicit trigger.
```

Definition at line 716 of file left_right.py.

8.123.3 Member Data Documentation

8.123.3.1 tuple rpki.left_right.parent_elt.attributes [static]

Initial value:

```
("action", "tag", "self_handle", "parent_handle", "bsc_handle", "repository_handl
      e",
                "peer_contact_uri", "sia_base", "sender_name", "recipient_name")
```

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 659 of file left_right.py.

8.123.3.2 tuple rpki.left_right.parent_elt.booleans = ("rekey", "reissue", "revoke", "revoke_forgotten") [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 662 of file left_right.py.

8.123.3.3 rpki.left_right.parent_elt.bpki_cms_cert = None [static]

Definition at line 671 of file left_right.py.

8.123.3.4 rpki.left_right.parent_elt.bpki_cms_glue = None [static]

Definition at line 672 of file left_right.py.

8.123.3.5 rpki.left_right.parent_elt.bpki_https_cert = None [static]

Definition at line 673 of file left_right.py.

8.123.3.6 rpki.left_right.parent_elt.bpki_https_glue = None [static]

Definition at line 674 of file left_right.py.

8.123.3.7 string rpki.left_right.parent_elt.element_name = "parent" [static]

Definition at line 658 of file left_right.py.

8.123.3.8 tuple rpki.left_right.parent_elt.elements = ("bpki_cms_cert", "bpki_cms_glue", "bpki_https_cert", "bpki_https_glue") [static]

XML elements contained by this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 661 of file left_right.py.

8.123.3.9 tuple rpki.left_right.parent_elt.handles = (("self", self_elt), ("bsc", bsc_elt), ("repository", repository_elt)) [static]

Reimplemented from rpki.left_right.data_elt.

Definition at line 669 of file left_right.py.

8.123.3.10 tuple rpki.left_right.parent_elt.sql_template [static]

Initial value:

```
rpki.sql.template("parent", "parent_id", "parent_handle",
                                  "self_id", "bsc_id", "repository_id",
                                  ("bpki_cms_cert", rpki.x509.X509), ("bpki_cms_
      glue", rpki.x509.X509),
                                  ("bpki_https_cert", rpki.x509.X509), ("bpki_ht
      tps_glue", rpki.x509.X509),
                                  "peer_contact_uri", "sia_base", "sender_name",
       "recipient_name")
```

Definition at line 664 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.124 rpki.left_right.report_error_elt Class Reference

Inherits rpki::xml_utils::text_elt, and rpki::left_right::left_right_namespace.

Inherited by irbe_cli.report_error_elt.

Collaboration diagram for rpki.left_right.report_error_elt:



Public Member Functions

- def from_exception

Public Attributes

- error_code
- self_handle
- tag

Static Public Attributes

- tuple attributes = ("tag", "self_handle", "error_code")

  XML attributes for this element.

- string element_name = "report_error"
- error_text = None
- string text_attribute = "error_text"

  Name of the class attribute that holds the text value.

8.124.1 Detailed Description

```
<report_error/> element.
```

Definition at line 1040 of file left_right.py.

8.124.2 Member Function Documentation

8.124.2.1 def rpki.left_right.report_error_elt.from_exception (*cls*, *e*, *self_handle* = `None`, *tag* = `None`)

```
Generate a <report_error/> element from an exception.
```

Definition at line 1052 of file left_right.py.

8.124.3 Member Data Documentation

8.124.3.1 tuple rpki.left_right.report_error_elt.attributes = ("tag", "self_handle", "error_code") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 1046 of file left_right.py.

8.124.3.2 string rpki.left_right.report_error_elt.element_name = "report_error" [static]

Definition at line 1045 of file left_right.py.

8.124.3.3 rpki.left_right.report_error_elt.error_code

Definition at line 1059 of file left_right.py.

8.124.3.4 rpki.left_right.report_error_elt.error_text = None [static]

Definition at line 1049 of file left_right.py.

8.124.3.5 rpki.left_right.report_error_elt.self_handle

Definition at line 1057 of file left_right.py.

8.124.3.6 rpki.left_right.report_error_elt.tag

Definition at line 1058 of file left_right.py.

8.124.3.7 string rpki.left_right.report_error_elt.text_attribute = "error_text" [static]

Name of the class attribute that holds the text value.

Reimplemented from rpki.xml_utils.text_elt.

Definition at line 1047 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.125 rpki.left_right.repository_elt Class Reference

Inherits rpki::left_right::data_elt.

Inherited by irbe_cli.repository_elt.

Collaboration diagram for rpki.left_right.repository_elt:



Public Member Functions

- def call_pubd
- def default_pubd_handler
- def parents

Static Public Attributes

- tuple attributes = ("action", "tag", "self_handle", "repository_handle", "bsc_-handle", "peer_contact_uri")

  XML attributes for this element.

- bpki_cert = None
- bpki_glue = None
- string element_name = "repository"
- tuple elements = ("bpki_cert", "bpki_glue")

  XML elements contained by this element.

- tuple handles = (("self", self_elt), ("bsc", bsc_elt))
- tuple sql_template

8.125.1 Detailed Description

```
<repository/> element.
```

Definition at line 573 of file left_right.py.

8.125.2 Member Function Documentation

8.125.2.1 def rpki.left_right.repository_elt.call_pubd (*self*, *callback*, *errback*, *q_msg*, *handlers* = { })

```
Send a message to publication daemon and return the response.

As a convenience, attempting to send an empty message returns
immediate success without sending anything.

Handlers is a dict of handler functions to process the response
PDUs.  If the tag value in the response PDU appears in the dict,
the associated handler is called to process the PDU.  If no tag
matches, default_pubd_handler() is called.  A handler value of
False suppresses calling of the default handler.
```

Definition at line 601 of file left_right.py.

8.125.2.2 def rpki.left_right.repository_elt.default_pubd_handler (*pdu*)

```
Default handler for publication response PDUs.
```

Definition at line 595 of file left_right.py.

8.125.2.3 def rpki.left_right.repository_elt.parents (*self*)

```
Fetch all parent objects that link to this repository object.
```

Definition at line 590 of file left_right.py.

8.125.3 Member Data Documentation

8.125.3.1 tuple rpki.left_right.repository_elt.attributes = ("action", "tag", "self_handle", "repository_handle", "bsc_handle", "peer_contact_uri") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 579 of file left_right.py.

8.125.3.2 rpki.left_right.repository_elt.bpki_cert = None [static]

Definition at line 587 of file left_right.py.

8.125.3.3 rpki.left_right.repository_elt.bpki_glue = None [static]

Definition at line 588 of file left_right.py.

8.125.3.4 string rpki.left_right.repository_elt.element_name = "repository" [static]

Definition at line 578 of file left_right.py.

8.125.3.5 tuple rpki.left_right.repository_elt.elements = ("bpki_cert", "bpki_glue") [static]

XML elements contained by this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 580 of file left_right.py.

8.125.3.6 tuple rpki.left_right.repository_elt.handles = (("self", self_elt), ("bsc", bsc_elt)) [static]

Reimplemented from rpki.left_right.data_elt.

Definition at line 585 of file left_right.py.

8.125.3.7 tuple rpki.left_right.repository_elt.sql_template [static]

Initial value:

```
rpki.sql.template("repository", "repository_id", "repository_handle",
                                  "self_id", "bsc_id", "peer_contact_uri",
                                  ("bpki_cert", rpki.x509.X509), ("bpki_glue", r
      pki.x509.X509))
```

Definition at line 582 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.126 rpki.left_right.sax_handler Class Reference

Inherits rpki::xml_utils::sax_handler.

Inherited by irbe_cli.left_right_sax_handler.

Collaboration diagram for rpki.left_right.sax_handler:



Static Public Attributes

- string name = "msg"
- pdu = msg
- string version = "1"

8.126.1 Detailed Description

```
SAX handler for Left-Right protocol.
```

Definition at line 1108 of file left_right.py.

8.126.2 Member Data Documentation

8.126.2.1 string rpki.left_right.sax_handler.name = "msg" [static]

Definition at line 1114 of file left_right.py.

8.126.2.2 rpki.left_right.sax_handler.pdu = msg [static]

Reimplemented in irbe_cli.left_right_sax_handler.

Definition at line 1113 of file left_right.py.

8.126.2.3 string rpki.left_right.sax_handler.version = "1" [static]

Definition at line 1115 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.127 rpki.left_right.self_elt Class Reference

Inherits rpki::left_right::data_elt.

Inherited by irbe_cli.self_elt.

Collaboration diagram for rpki.left_right.self_elt:



Public Member Functions

- def bscs
- def children
- def client_poll
- def cron
- def parents
- def regenerate_crls_and_manifests
- def repositories
- def roas
- def serve_fetch_all
- def serve_fetch_handle
- def serve_fetch_one_maybe
- def serve_post_save_hook
- def serve_publish_world_now
- def serve_rekey
- def serve_revoke
- def serve_revoke_forgotten
- def serve_run_now
- def update_children
- def update_roas

Static Public Attributes

- tuple attributes = ("action", "tag", "self_handle", "crl_interval", "regen_-margin")

  XML attributes for this element.

- tuple booleans = ("rekey", "reissue", "revoke", "run_now", "publish_world_-now", "revoke_forgotten")

  Boolean attributes (value "yes" or "no") for this element.

- bpki_cert = None
- bpki_glue = None
- crl_interval = None
- string element_name = "self"
- tuple elements = ("bpki_cert", "bpki_glue")

  XML elements contained by this element.

- tuple handles = ()
- regen_margin = None
- tuple sql_template
- use_hsm = False

8.127.1 Detailed Description

```
<self/> element.
```

Definition at line 124 of file left_right.py.

8.127.2 Member Function Documentation

8.127.2.1 def rpki.left_right.self_elt.bscs (*self*)

```
Fetch all BSC objects that link to this self object.
```

Definition at line 145 of file left_right.py.

8.127.2.2 def rpki.left_right.self_elt.children (*self*)

```
Fetch all child objects that link to this self object.
```

Definition at line 157 of file left_right.py.

8.127.2.3 def rpki.left_right.self_elt.client_poll (*self*, *callback*)

```
Run the regular client poll cycle with each of this self's parents
in turn.
```

Definition at line 302 of file left_right.py.

8.127.2.4 def rpki.left_right.self_elt.cron (*self*, *cb*)

```
Periodic tasks.
```

Definition at line 274 of file left_right.py.

8.127.2.5 def rpki.left_right.self_elt.parents (*self*)

```
Fetch all parent objects that link to this self object.
```

Definition at line 153 of file left_right.py.

8.127.2.6 def rpki.left_right.self_elt.regenerate_crls_and_manifests (*self*, *cb*)

```
Generate new CRLs and manifests as necessary for all of this
self's CAs.  Extracting nextUpdate from a manifest is hard at the
moment due to implementation silliness, so for now we generate a
new manifest whenever we generate a new CRL

This method also cleans up tombstones left behind by revoked
ca_detail objects, since we're walking through the relevant
portions of the database anyway.
```

Definition at line 428 of file left_right.py.

8.127.2.7 def rpki.left_right.self_elt.repositories (*self*)

```
Fetch all repository objects that link to this self object.
```

Definition at line 149 of file left_right.py.

8.127.2.8 def rpki.left_right.self_elt.roas (*self*)

```
Fetch all ROA objects that link to this self object.
```

Definition at line 161 of file left_right.py.

8.127.2.9 def rpki.left_right.self_elt.serve_fetch_all (*self*)

```
Find the self objects upon which a list action should operate.
This is different from the list action for all other objects,
where list only works within a given self_id context.
```

Reimplemented from rpki.left_right.data_elt.

Definition at line 266 of file left_right.py.

8.127.2.10 def rpki.left_right.self_elt.serve_fetch_handle (*cls*, *gctx*, *self_id*, *self_handle*)

```
Find a self object based on its self_handle.
```

Reimplemented from rpki.left_right.data_elt.

Definition at line 260 of file left_right.py.

8.127.2.11 def rpki.left_right.self_elt.serve_fetch_one_maybe (*self*)

```
Find the self object upon which a get, set, or destroy action
should operate, or which would conflict with a create method.
```

Reimplemented from rpki.left_right.data_elt.

Definition at line 252 of file left_right.py.

8.127.2.12 def rpki.left_right.self_elt.serve_post_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Extra server actions for self_elt.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 165 of file left_right.py.

8.127.2.13 def rpki.left_right.self_elt.serve_publish_world_now (*self*, *cb*, *eb*)

```
Handle a left-right publish_world_now action for this self.

The publication stuff needs refactoring, right now publication is
interleaved with local operations in a way that forces far too
many bounces through the task system for any complex update.  The
whole thing ought to be rewritten to queue up outgoing publication
```

```
PDUs and only send them when we're all done or when we need to
force publication at a particular point in a multi-phase operation.

Once that reorganization has been done, this method should be
rewritten to reuse the low-level publish() methods that each
object will have...but we're not there yet.  So, for now, we just
do this via brute force.  Think of it as a trial version to see
whether we've identified everything that needs to be republished
for this operation.
```

Definition at line 213 of file left_right.py.

8.127.2.14 def rpki.left_right.self_elt.serve_rekey (*self*, *cb*, *eb*)

```
Handle a left-right rekey action for this self.
```

Definition at line 186 of file left_right.py.

8.127.2.15 def rpki.left_right.self_elt.serve_revoke (*self*, *cb*, *eb*)

```
Handle a left-right revoke action for this self.
```

Definition at line 195 of file left_right.py.

8.127.2.16 def rpki.left_right.self_elt.serve_revoke_forgotten (*self*, *cb*, *eb*)

```
Handle a left-right revoke_forgotten action for this self.
```

Definition at line 204 of file left_right.py.

8.127.2.17 def rpki.left_right.self_elt.serve_run_now (*self*, *cb*, *eb*)

```
Handle a left-right run_now action for this self.
```

Definition at line 245 of file left_right.py.

8.127.2.18 def rpki.left_right.self_elt.update_children (*self*, *cb*)

```
Check for updated IRDB data for all of this self's children and
issue new certs as necessary.  Must handle changes both in
resources and in expiration date.
```

Definition at line 361 of file left_right.py.

8.127.2.19 def rpki.left_right.self_elt.update_roas (*self*, *cb*)

```
Generate or update ROAs for this self.
```

Definition at line 470 of file left_right.py.

8.127.3 Member Data Documentation

8.127.3.1 tuple rpki.left_right.self_elt.attributes = ("action", "tag", "self_handle", "crl_interval", "regen_margin") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 130 of file left_right.py.

8.127.3.2 tuple rpki.left_right.self_elt.booleans = ("rekey", "reissue", "revoke", "run_now", "publish_world_now", "revoke_forgotten") [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 132 of file left_right.py.

8.127.3.3 rpki.left_right.self_elt.bpki_cert = None [static]

Definition at line 142 of file left_right.py.

8.127.3.4 rpki.left_right.self_elt.bpki_glue = None [static]

Definition at line 143 of file left_right.py.

8.127.3.5 rpki.left_right.self_elt.crl_interval = None [static]

Definition at line 140 of file left_right.py.

8.127.3.6 string rpki.left_right.self_elt.element_name = "self" [static]

Definition at line 129 of file left_right.py.

8.127.3.7 tuple rpki.left_right.self_elt.elements = ("bpki_cert", "bpki_glue") [static]

XML elements contained by this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 131 of file left_right.py.

8.127.3.8 tuple rpki.left_right.self_elt.handles = () [static]

Reimplemented from rpki.left_right.data_elt.

Definition at line 137 of file left_right.py.

8.127.3.9 rpki.left_right.self_elt.regen_margin = None [static]

Definition at line 141 of file left_right.py.

8.127.3.10 tuple rpki.left_right.self_elt.sql_template [static]

Initial value:

```
rpki.sql.template("self", "self_id", "self_handle",
                                  "use_hsm", "crl_interval", "regen_margin",
                                  ("bpki_cert", rpki.x509.X509), ("bpki_glue", r
      pki.x509.X509))
```

Definition at line 134 of file left_right.py.

8.127.3.11 rpki.left_right.self_elt.use_hsm = False [static]

Definition at line 139 of file left_right.py.

The documentation for this class was generated from the following file:

- left_right.py (3107)

8.128 rpki.log.logger Class Reference

Inherits object.

Collaboration diagram for rpki.log.logger:



Public Member Functions

- def __call__
- def __init__

Public Attributes

- priority

8.128.1 Detailed Description

```
Closure for logging.
```

Definition at line 71 of file log.py.

8.128.2 Member Function Documentation

8.128.2.1 def rpki.log.logger.__call__ (*self*, *message*)

Definition at line 79 of file log.py.

8.128.2.2 def rpki.log.logger.__init__ (*self*, *priority*)

Definition at line 76 of file log.py.

8.128.3 Member Data Documentation

8.128.3.1 rpki.log.logger.priority

Definition at line 77 of file log.py.

The documentation for this class was generated from the following file:

- log.py (3107)

8.129 rpki.manifest.FileAndHash Class Reference

Inherits Sequence.

Collaboration diagram for rpki.manifest.FileAndHash:



Public Member Functions

- def __init__

Public Attributes

- file
- hash

8.129.1 Detailed Description

Definition at line 27 of file manifest.py.

8.129.2 Member Function Documentation

8.129.2.1 def rpki.manifest.FileAndHash.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 28 of file manifest.py.

8.129.3 Member Data Documentation

8.129.3.1 rpki.manifest.FileAndHash.file

Definition at line 29 of file manifest.py.

8.129.3.2 rpki.manifest.FileAndHash.hash

Definition at line 30 of file manifest.py.

The documentation for this class was generated from the following file:

- manifest.py (2424)

8.130 rpki.manifest.FilesAndHashes Class Reference

Inherits SequenceOf.

Collaboration diagram for rpki.manifest.FilesAndHashes:



Public Member Functions

- def __init__

8.130.1 Detailed Description

Definition at line 34 of file manifest.py.

8.130.2 Member Function Documentation

8.130.2.1 def rpki.manifest.FilesAndHashes.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 35 of file manifest.py.

The documentation for this class was generated from the following file:

- manifest.py (2424)

8.131 rpki.manifest.Manifest Class Reference

Inherits Sequence.

Collaboration diagram for rpki.manifest.Manifest:



Public Member Functions

- def __init__

Public Attributes

- explicitVersion
- fileHashAlg
- fileList
- manifestNumber
- nextUpdate

- thisUpdate
- version

8.131.1 Detailed Description

Definition at line 38 of file manifest.py.

8.131.2 Member Function Documentation

8.131.2.1 def rpki.manifest.Manifest.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 39 of file manifest.py.

8.131.3 Member Data Documentation

8.131.3.1 rpki.manifest.Manifest.explicitVersion

Definition at line 41 of file manifest.py.

8.131.3.2 rpki.manifest.Manifest.fileHashAlg

Definition at line 45 of file manifest.py.

8.131.3.3 rpki.manifest.Manifest.fileList

Definition at line 46 of file manifest.py.

8.131.3.4 rpki.manifest.Manifest.manifestNumber

Definition at line 42 of file manifest.py.

8.131.3.5 rpki.manifest.Manifest.nextUpdate

Definition at line 44 of file manifest.py.

8.131.3.6 rpki.manifest.Manifest.thisUpdate

Definition at line 43 of file manifest.py.

8.131.3.7 rpki.manifest.Manifest.version

Definition at line 40 of file manifest.py.

The documentation for this class was generated from the following file:

- manifest.py (2424)

8.132 rpki.publication.certificate_elt Class Reference

Inherits rpki::publication::publication_object_elt.

Inherited by irbe_cli.certificate_elt.

Collaboration diagram for rpki.publication.certificate_elt:



Static Public Attributes

- string element_name = "certificate"
- payload_type = rpki.x509.X509

8.132.1 Detailed Description

`<certificate/> element.`

Definition at line 287 of file publication.py.

8.132.2 Member Data Documentation

8.132.2.1 string rpki.publication.certificate_elt.element_name = "certificate" [static]

Definition at line 292 of file publication.py.

8.132.2.2 rpki.publication.certificate_elt.payload_type = rpki.x509.X509 [static]

Reimplemented from rpki.publication.publication_object_elt.

Definition at line 293 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.133 rpki.publication.client_elt Class Reference

Inherits rpki::publication::control_elt.

Inherited by irbe_cli.client_elt.

Collaboration diagram for rpki.publication.client_elt:



Public Member Functions

- def check_allowed_uri
- def endElement
- def serve_fetch_all
- def serve_fetch_one_maybe
- def serve_post_save_hook

Static Public Attributes

- tuple attributes = ("action", "tag", "client_handle", "base_uri")

  XML attributes for this element.

- base_uri = None
- bpki_cert = None
- bpki_glue = None
- clear_https_ta_cache = False
- string element_name = "client"
- tuple elements = ("bpki_cert", "bpki_glue")

  XML elements contained by this element.

- tuple sql_template = rpki.sql.template("client", "client_id", "client_handle", "base_uri", ("bpki_cert", rpki.x509.X509), ("bpki_glue", rpki.x509.X509))

8.133.1 Detailed Description

```
<client/> element.
```

Definition at line 113 of file publication.py.

8.133.2 Member Function Documentation

8.133.2.1 def rpki.publication.client_elt.check_allowed_uri (*self*, *uri*)

Definition at line 160 of file publication.py.

8.133.2.2 def rpki.publication.client_elt.endElement (*self*, *stack*, *name*, *text*)

```
Handle subelements of <client/> element.  These require special
handling because modifying them invalidates the HTTPS trust anchor
cache.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 130 of file publication.py.

8.133.2.3 def rpki.publication.client_elt.serve_fetch_all (*self*)

```
Find client objects on which a list method should operate.
```

Definition at line 156 of file publication.py.

8.133.2.4 def rpki.publication.client_elt.serve_fetch_one_maybe (*self*)

```
Find the client object on which a get, set, or destroy method
should operate, or which would conflict with a create method.
```

Definition at line 149 of file publication.py.

8.133.2.5 def rpki.publication.client_elt.serve_post_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Extra server actions for client_elt.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 140 of file publication.py.

8.133.3 Member Data Documentation

8.133.3.1 tuple rpki.publication.client_elt.attributes = ("action", "tag", "client_handle", "base_uri") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 119 of file publication.py.

8.133.3.2 rpki.publication.client_elt.base_uri = None [static]

Definition at line 124 of file publication.py.

8.133.3.3 rpki.publication.client_elt.bpki_cert = None [static]

Definition at line 125 of file publication.py.

8.133.3.4 rpki.publication.client_elt.bpki_glue = None [static]

Definition at line 126 of file publication.py.

8.133.3.5 rpki.publication.client_elt.clear_https_ta_cache = False [static]

Definition at line 128 of file publication.py.

8.133.3.6 string rpki.publication.client_elt.element_name = "client" [static]

Definition at line 118 of file publication.py.

8.133.3.7 tuple rpki.publication.client_elt.elements = ("bpki_cert", "bpki_glue") [static]

XML elements contained by this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 120 of file publication.py.

8.133.3.8 tuple rpki.publication.client_elt.sql_template = rpki.sql.template("client", "client_id", "client_handle", "base_uri", ("bpki_cert", rpki.x509.X509), ("bpki_glue", rpki.x509.X509)) [static]

Definition at line 122 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.134 rpki.publication.cms_msg Class Reference

Inherits rpki::x509::XML_CMS_object.

Inherited by irbe_cli.publication_cms_msg.

Collaboration diagram for rpki.publication.cms_msg:



Static Public Attributes

- string encoding = "us-ascii"
- saxify = sax_handler.saxify
- schema = rpki.relaxng.publication

8.134.1 Detailed Description

```
Class to hold a CMS-signed publication PDU.
```

Definition at line 415 of file publication.py.

8.134.2 Member Data Documentation

8.134.2.1 string rpki.publication.cms_msg.encoding = "us-ascii" [static]

Definition at line 420 of file publication.py.

8.134.2.2 rpki.publication.cms_msg.saxify = sax_handler.saxify [static]

Reimplemented in irbe_cli.publication_cms_msg.

Definition at line 422 of file publication.py.

8.134.2.3 rpki.publication.cms_msg.schema = rpki.relaxng.publication [static]

Definition at line 421 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.135 rpki.publication.config_elt Class Reference

Inherits rpki::publication::control_elt.

Inherited by irbe_cli.config_elt.

Collaboration diagram for rpki.publication.config_elt:



Public Member Functions

- def fetch
- def serve_fetch_one_maybe
- def serve_set
- def startElement

Public Attributes

- config_id

Static Public Attributes

- tuple attributes = ("action", "tag")

  XML attributes for this element.

- string element_name = "config"
- tuple elements = ("bpki_crl",)

  XML elements contained by this element.

- tuple sql_template = rpki.sql.template("config", "config_id", ("bpki_crl", rpki.x509.CRL))
- int wired_in_config_id = 1

8.135.1 Detailed Description

```
<config/> element.  This is a little weird because there should
never be more than one row in the SQL config table, but we have to
put the BPKI CRL somewhere and SQL is the least bad place available.

So we reuse a lot of the SQL machinery, but we nail config_id at 1,
we don't expose it in the XML protocol, and we only support the get
and set actions.
```

Definition at line 61 of file publication.py.

8.135.2 Member Function Documentation

8.135.2.1 def rpki.publication.config_elt.fetch (*cls*, *gctx*)

```
Fetch the config object from SQL.  This requires special handling
because of the weird way we treat config_id.
```

Definition at line 89 of file publication.py.

8.135.2.2 def rpki.publication.config_elt.serve_fetch_one_maybe (*self*)

```
Find the config object on which a get or set method should
operate.
```

Definition at line 106 of file publication.py.

8.135.2.3 def rpki.publication.config_elt.serve_set (*self*, *r_msg*, *cb*, *eb*)

```
Handle a set action.  This requires special handling because
config doesn't support the create method.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 96 of file publication.py.

8.135.2.4 def rpki.publication.config_elt.startElement (*self*, *stack*, *name*, *attrs*)

```
StartElement() handler for config object.  This requires special
handling because of the weird way we treat config_id.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 80 of file publication.py.

8.135.3 Member Data Documentation

8.135.3.1 tuple rpki.publication.config_elt.attributes = ("action", "tag") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 72 of file publication.py.

8.135.3.2 rpki.publication.config_elt.config_id

Definition at line 86 of file publication.py.

8.135.3.3 string rpki.publication.config_elt.element_name = "config" [static]

Definition at line 73 of file publication.py.

8.135.3.4 tuple rpki.publication.config_elt.elements = ("bpki_crl",) [static]

XML elements contained by this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 74 of file publication.py.

8.135.3.5 tuple rpki.publication.config_elt.sql_template = rpki.sql.template("config", "config_id", ("bpki_crl", rpki.x509.CRL)) [static]

Definition at line 76 of file publication.py.

8.135.3.6 int rpki.publication.config_elt.wired_in_config_id = 1 [static]

Definition at line 78 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.136 rpki.publication.control_elt Class Reference

Inherits rpki::xml_utils::data_elt, rpki::sql::sql_persistent, and rpki::publication::publication_namespace.

Inherited by rpki.publication.client_elt, and rpki.publication.config_elt.

Collaboration diagram for rpki.publication.control_elt:



Public Member Functions

- def serve_dispatch

8.136.1 Detailed Description

```
Virtual class for control channel objects.
```

Definition at line 47 of file publication.py.

8.136.2 Member Function Documentation

8.136.2.1 def rpki.publication.control_elt.serve_dispatch (*self*, *r_msg*, *cb*, *eb*)

```
Action dispatch handler.  This needs special handling because we
need to make sure that this PDU arrived via the control channel.
```

Reimplemented from rpki.xml_utils.data_elt.

Definition at line 52 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.137 rpki.publication.crl_elt Class Reference

Inherits rpki::publication::publication_object_elt.

Inherited by irbe_cli.crl_elt.

Collaboration diagram for rpki.publication.crl_elt:



Static Public Attributes

- string element_name = "crl"
- payload_type = rpki.x509.CRL

8.137.1 Detailed Description

`<crl/> element.`

Definition at line 295 of file publication.py.

8.137.2 Member Data Documentation

8.137.2.1 string rpki.publication.crl_elt.element_name = "crl" [static]

Definition at line 300 of file publication.py.

8.137.2.2 rpki.publication.crl_elt.payload_type = rpki.x509.CRL [static]

Reimplemented from rpki.publication.publication_object_elt.

Definition at line 301 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.138 rpki.publication.manifest_elt Class Reference

Inherits rpki::publication::publication_object_elt.

Inherited by irbe_cli.manifest_elt.

Collaboration diagram for rpki.publication.manifest_elt:



Static Public Attributes

- string element_name = "manifest"
- payload_type = rpki.x509.SignedManifest

8.138.1 Detailed Description

```
<manifest/> element.
```

Definition at line 303 of file publication.py.

8.138.2 Member Data Documentation

8.138.2.1 string rpki.publication.manifest_elt.element_name = "manifest" [static]

Definition at line 308 of file publication.py.

8.138.2.2 rpki.publication.manifest_elt.payload_type = rpki.x509.SignedManifest [static]

Reimplemented from rpki.publication.publication_object_elt.

Definition at line 309 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.139 rpki.publication.msg Class Reference

Inherits rpki::xml_utils::msg, and rpki::publication::publication_namespace.

Inherited by irbe_cli.publication_msg.

Collaboration diagram for rpki.publication.msg:



Public Member Functions

- def serve_top_level

Static Public Attributes

- tuple pdus

  Dispatch table of PDUs for this protocol.

- int version = 1

  Protocol version.

8.139.1 Detailed Description

```
Publication PDU.
```

Definition at line 362 of file publication.py.

8.139.2 Member Function Documentation

8.139.2.1 def rpki.publication.msg.serve_top_level (*self*, *gctx*, *client*, *cb*)

```
Serve one msg PDU.
```

Definition at line 376 of file publication.py.

8.139.3 Member Data Documentation

8.139.3.1 rpki::publication.msg::pdus [static]

Initial value:

```
dict((x.element_name, x)
              for x in (config_elt, client_elt, certificate_elt, crl_elt, manifes
      t_elt, roa_elt, report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented in irbe_cli.publication_msg.

Definition at line 373 of file publication.py.

8.139.3.2 rpki::publication.msg::version = 1 [static]

Protocol version.

Reimplemented from rpki.xml_utils.msg.

Definition at line 369 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.140 rpki.publication.publication_namespace Class Reference

Inherits object.

Inherited by rpki.publication.control_elt, rpki.publication.msg, rpki.publication.publication_object_elt, and rpki.publication.report_error_elt.

Collaboration diagram for rpki.publication.publication_namespace:



Static Public Attributes

- dictionary nsmap = { None : xmlns }
- string xmlns = "http://www.hactrn.net/uris/rpki/publication-spec/"

8.140.1 Detailed Description

```
XML namespace parameters for publication protocol.
```

Definition at line 39 of file publication.py.

8.140.2 Member Data Documentation

8.140.2.1 dictionary rpki.publication.publication_namespace.nsmap = { None : xmlns } [static]

Definition at line 45 of file publication.py.

8.140.2.2 string rpki.publication.publication_namespace.xmlns = "http://www.hactrn.net/uris/rpki/publication-spec/" [static]

Definition at line 44 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.141 rpki.publication.publication_object_elt Class Reference

Inherits rpki::xml_utils::base_elt, and rpki::publication::publication_namespace.

Inherited by rpki.publication.certificate_elt, rpki.publication.crl_elt, rpki.publication.manifest_elt, and rpki.publication.roa_elt.

Collaboration diagram for rpki.publication.publication_object_elt:



Public Member Functions

- def endElement
- def make_publish
- def make_withdraw
- def raise_if_error
- def serve_dispatch
- def serve_publish
- def serve_withdraw
- def toXML
- def uri_to_filename

Static Public Attributes

- tuple attributes = ("action", "tag", "client_handle", "uri")

  XML attributes for this element.

- payload = None
- payload_type = None

8.141.1 Detailed Description

```
Virtual class for publishable objects.  These have very similar
syntax, differences lie in underlying datatype and methods.  XML
methods are a little different from the pattern used for objects
that support the create/set/get/list/destroy actions, but
publishable objects don't go in SQL either so these classes would be
different in any case.
```

Definition at line 164 of file publication.py.

8.141.2 Member Function Documentation

8.141.2.1 def rpki.publication.publication_object_elt.endElement (*self*, *stack*, *name*, *text*)

```
Handle a publishable element element.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 178 of file publication.py.

8.141.2.2 def rpki.publication.publication_object_elt.make_publish (*cls*, *uri*, *obj*, *tag* = None)

```
Construct a publication PDU.
```

Definition at line 266 of file publication.py.

8.141.2.3 def rpki.publication.publication_object_elt.make_withdraw (*cls*, *uri*, *obj*, *tag* = None)

```
Construct a withdrawal PDU.
```

Definition at line 274 of file publication.py.

8.141.2.4 def rpki.publication.publication_object_elt.raise_if_error (*self*)

```
No-op, since this is not a <report_error/> PDU.
```

Definition at line 281 of file publication.py.

8.141.2.5 def rpki.publication.publication_object_elt.serve_dispatch (*self*, *r_msg*, *cb*, *eb*)

```
Action dispatch handler.
```

Definition at line 196 of file publication.py.

8.141.2.6 def rpki.publication.publication_object_elt.serve_publish (*self*)

```
Publish an object.
```

Definition at line 221 of file publication.py.

8.141.2.7 def rpki.publication.publication_object_elt.serve_withdraw (*self*)

```
Withdraw an object.
```

Definition at line 236 of file publication.py.

8.141.2.8 def rpki.publication.publication_object_elt.toXML (*self*)

```
Generate XML element for publishable object.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 187 of file publication.py.

8.141.2.9 def rpki.publication.publication_object_elt.uri_to_filename (*self*)

```
Convert a URI to a local filename.
```

Definition at line 250 of file publication.py.

8.141.3 Member Data Documentation

8.141.3.1 tuple rpki.publication.publication_object_elt.attributes = ("action", "tag", "client_handle", "uri") [static]

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 174 of file publication.py.

8.141.3.2 rpki.publication.publication_object_elt.payload = None [static]

Definition at line 176 of file publication.py.

8.141.3.3 rpki.publication.publication_object_elt.payload_type = None [static]

Reimplemented in rpki.publication.certificate_elt, rpki.publication.crl_elt, rpki.publication.manifest_elt, and rpki.publication.roa_elt.

Definition at line 175 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.142 rpki.publication.report_error_elt Class Reference

Inherits rpki::xml_utils::text_elt, and rpki::publication::publication_namespace.

Inherited by irbe_cli.report_error_elt.

Collaboration diagram for rpki.publication.report_error_elt:



Public Member Functions

- def __str__
- def from_exception
- def raise_if_error

Public Attributes

- error_code
- tag

Static Public Attributes

- tuple attributes = ("tag", "error_code")

  XML attributes for this element.

- string element_name = "report_error"
- error_text = None
- string text_attribute = "error_text"

  Name of the class attribute that holds the text value.

8.142.1 Detailed Description

```
<report_error/> element.
```

Definition at line 321 of file publication.py.

8.142.2 Member Function Documentation

8.142.2.1 def rpki.publication.report_error_elt.__str__ (*self*)

```
Convert a base_elt object to string format.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 343 of file publication.py.

8.142.2.2 def rpki.publication.report_error_elt.from_exception (*cls*, *e*, *tag* = `None`)

```
Generate a <report_error/> element from an exception.
```

Definition at line 333 of file publication.py.

8.142.2.3 def rpki.publication.report_error_elt.raise_if_error (*self*)

```
Raise exception associated with this <report_error/> PDU.
```

Definition at line 352 of file publication.py.

8.142.3 Member Data Documentation

8.142.3.1 tuple rpki.publication.report_error_elt.attributes = ("tag", "error_code") `[static]`

XML attributes for this element.

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 327 of file publication.py.

8.142.3.2 string rpki.publication.report_error_elt.element_name = "report_error" `[static]`

Definition at line 326 of file publication.py.

8.142.3.3 rpki.publication.report_error_elt.error_code

Definition at line 339 of file publication.py.

8.142.3.4 rpki.publication.report_error_elt.error_text = None `[static]`

Definition at line 330 of file publication.py.

8.142.3.5 rpki.publication.report_error_elt.tag

Definition at line 338 of file publication.py.

8.142.3.6 string rpki.publication.report_error_elt.text_attribute = "error_text" [static]

Name of the class attribute that holds the text value.

Reimplemented from rpki.xml_utils.text_elt.

Definition at line 328 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.143 rpki.publication.roa_elt Class Reference

Inherits rpki::publication::publication_object_elt.

Inherited by irbe_cli.roa_elt.

Collaboration diagram for rpki.publication.roa_elt:



Static Public Attributes

- string element_name = "roa"
- payload_type = rpki.x509.ROA

8.143.1 Detailed Description

`<roa/> element.`

Definition at line 311 of file publication.py.

8.143.2 Member Data Documentation

8.143.2.1 string rpki.publication.roa_elt.element_name = "roa" [static]

Definition at line 316 of file publication.py.

8.143.2.2 rpki.publication.roa_elt.payload_type = rpki.x509.ROA [static]

Reimplemented from rpki.publication.publication_object_elt.

Definition at line 317 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.144 rpki.publication.sax_handler Class Reference

Inherits rpki::xml_utils::sax_handler.

Inherited by irbe_cli.publication_sax_handler.

Collaboration diagram for rpki.publication.sax_handler:



Static Public Attributes

- string name = "msg"
- pdu = msg
- string version = "1"

8.144.1 Detailed Description

```
SAX handler for publication protocol.
```

Definition at line 406 of file publication.py.

8.144.2 Member Data Documentation

8.144.2.1 string rpki.publication.sax_handler.name = "msg" [static]

Definition at line 412 of file publication.py.

8.144.2.2 rpki.publication.sax_handler.pdu = msg [static]

Reimplemented in irbe_cli.publication_sax_handler.

Definition at line 411 of file publication.py.

8.144.2.3 string rpki.publication.sax_handler.version = "1" [static]

Definition at line 413 of file publication.py.

The documentation for this class was generated from the following file:

- publication.py (3107)

8.145 rpki.resource_set.resource_bag Class Reference

Inherits object.

Collaboration diagram for rpki.resource_set.resource_bag:



Public Member Functions

- def __eq__
- def __init__
- def __ne__
- def __str__
- def empty
- def from_rfc3779_tuples
- def intersection

- def oversized
- def undersized
- def union

Public Attributes

- asn

  Set of Autonomous System Number resources.

- v4

  Set of IPv4 resources.

- v6

  Set of IPv6 resources.

- valid_until

  Expiration date of resources, for setting certificate notAfter field.

8.145.1 Detailed Description

```
Container to simplify passing around the usual triple of ASN, IPv4,
and IPv6 resource sets.
```

Definition at line 547 of file resource_set.py.

8.145.2 Member Function Documentation

8.145.2.1 def rpki.resource_set.resource_bag.__eq__ (*self*, *other*)

Definition at line 615 of file resource_set.py.

8.145.2.2 def rpki.resource_set.resource_bag.__init__ (*self*, *asn* = `None`, *v4* = `None`, *v6* = `None`, *valid_until* = `None`)

Definition at line 565 of file resource_set.py.

8.145.2.3 def rpki.resource_set.resource_bag.__ne__ (*self*, *other*)

Definition at line 621 of file resource_set.py.

8.145.2.4 def rpki.resource_set.resource_bag.__str__ (*self*)

Definition at line 644 of file resource_set.py.

8.145.2.5 def rpki.resource_set.resource_bag.empty (*self*)

```
True iff all resource sets in this bag are empty.
```

Definition at line 611 of file resource_set.py.

8.145.2.6 def rpki.resource_set.resource_bag.from_rfc3779_tuples (*cls*, *exts*)

```
Build a resource_bag from intermediate form generated by RFC 3779
ASN.1 decoder.
```

Definition at line 588 of file resource_set.py.

8.145.2.7 def rpki.resource_set.resource_bag.intersection (*self*, *other*)

```
Compute intersection with another resource_bag.  valid_until
attribute (if any) inherits from self.
```

Definition at line 624 of file resource_set.py.

8.145.2.8 def rpki.resource_set.resource_bag.oversized (*self*, *other*)

```
True iff self is oversized with respect to other.
```

Definition at line 571 of file resource_set.py.

8.145.2.9 def rpki.resource_set.resource_bag.undersized (*self*, *other*)

```
True iff self is undersized with respect to other.
```

Definition at line 579 of file resource_set.py.

8.145.2.10 def rpki.resource_set.resource_bag.union (*self*, *other*)

```
Compute union with another resource_bag.  valid_until attribute
(if any) inherits from self.
```

Definition at line 634 of file resource_set.py.

8.145.3 Member Data Documentation

8.145.3.1 rpki::resource_set.resource_bag::asn

Set of Autonomous System Number resources.

Definition at line 566 of file resource_set.py.

8.145.3.2 rpki::resource_set.resource_bag::v4

Set of IPv4 resources.

Definition at line 567 of file resource_set.py.

8.145.3.3 rpki::resource_set.resource_bag::v6

Set of IPv6 resources.

Definition at line 568 of file resource_set.py.

8.145.3.4 rpki::resource_set.resource_bag::valid_until

Expiration date of resources, for setting certificate notAfter field.

Definition at line 569 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.146 rpki.resource_set.resource_range Class Reference

Inherits object.

Inherited by rpki.resource_set.resource_range_as, and rpki.resource_set.resource_-range_ip.

Collaboration diagram for rpki.resource_set.resource_range:



Public Member Functions

- def __cmp__
- def __init__

Public Attributes

- max

- min

8.146.1 Detailed Description

```
Generic resource range type.  Assumes underlying type is some kind
of integer.

This is a virtual class.  You probably don't want to use this type
directly.
```

Definition at line 50 of file resource_set.py.

8.146.2 Member Function Documentation

8.146.2.1 def rpki.resource_set.resource_range.__cmp__ (*self*, *other*)

```
Compare two resource_range objects.
```

Definition at line 67 of file resource_set.py.

8.146.2.2 def rpki.resource_set.resource_range.__init__ (*self*, *min*, *max*)

```
Initialize and sanity check a resource_range.
```

Definition at line 59 of file resource_set.py.

8.146.3 Member Data Documentation

8.146.3.1 rpki.resource_set.resource_range.max

Definition at line 65 of file resource_set.py.

8.146.3.2 rpki.resource_set.resource_range.min

Reimplemented in rpki.resource_set.resource_range_as.

Definition at line 64 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.147 rpki.resource_set.resource_range_as Class Reference

Inherits rpki::resource_set::resource_range.

Collaboration diagram for rpki.resource_set.resource_range_as:



Public Member Functions

- def __str__
- def to_rfc3779_tuple

Public Attributes

- min

Static Public Attributes

- datum_type = long

  Type of underlying data (min and max).

8.147.1 Detailed Description

```
Range of Autonomous System Numbers.

Denotes a single ASN by a range whose min and max values are
identical.
```

Definition at line 78 of file resource_set.py.

8.147.2 Member Function Documentation

8.147.2.1 def rpki.resource_set.resource_range_as.__str__ (*self*)

```
Convert a resource_range_as to string format.
```

Definition at line 91 of file resource_set.py.

8.147.2.2 def rpki.resource_set.resource_range_as.to_rfc3779_tuple (*self*)

```
Convert a resource_range_as to tuple format for RFC 3779 ASN.1 encoding.
```

Definition at line 100 of file resource_set.py.

8.147.3 Member Data Documentation

8.147.3.1 rpki::resource_set.resource_range_as::datum_type = long [static]

Type of underlying data (min and max).

Definition at line 89 of file resource_set.py.

8.147.3.2 rpki.resource_set.resource_range_as.min

Reimplemented from rpki.resource_set.resource_range.

Definition at line 95 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.148 rpki.resource_set.resource_range_ip Class Reference

Inherits rpki::resource_set::resource_range.

Inherited by rpki.resource_set.resource_range_ipv4, and rpki.resource_set.resource_-range_ipv6.

Collaboration diagram for rpki.resource_set.resource_range_ip:



Public Member Functions

- def __str__
- def make_prefix
- def to_rfc3779_tuple

Private Member Functions

- def _prefixlen

8.148.1 Detailed Description

```
Range of (generic) IP addresses.

Prefixes are converted to ranges on input, and ranges that can be
represented as prefixes are written as prefixes on output.

This is a virtual class.  You probably don't want to use it
directly.
```

Definition at line 109 of file resource_set.py.

8.148.2 Member Function Documentation

8.148.2.1 def rpki.resource_set.resource_range_ip.__str__ (*self*)

```
Convert a resource_range_ip to string format.
```

Definition at line 137 of file resource_set.py.

8.148.2.2 def rpki.resource_set.resource_range_ip._prefixlen (*self*) [private]

```
Determine whether a resource_range_ip can be expressed as a
prefix.
```

Definition at line 120 of file resource_set.py.

8.148.2.3 def rpki.resource_set.resource_range_ip.make_prefix (*cls*, *prefix*, *prefixlen*)

```
Construct a resource range corresponding to a prefix.
```

Definition at line 160 of file resource_set.py.

8.148.2.4 def rpki.resource_set.resource_range_ip.to_rfc3779_tuple (*self*)

```
Convert a resource_range_ip to tuple format for RFC 3779 ASN.1
encoding.
```

Definition at line 147 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.149 rpki.resource_set.resource_range_ipv4 Class Reference

Inherits rpki::resource_set::resource_range_ip.

Collaboration diagram for rpki.resource_set.resource_range_ipv4:



Static Public Attributes

- datum_type = rpki.ipaddrs.v4addr

  Type of underlying data (min and max).

8.149.1 Detailed Description

```
Range of IPv4 addresses.
```

Definition at line 170 of file resource_set.py.

8.149.2 Member Data Documentation

8.149.2.1 rpki::resource_set.resource_range_ipv4::datum_type = rpki.ipaddrs.v4addr [static]

Type of underlying data (min and max).

Definition at line 178 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.150 rpki.resource_set.resource_range_ipv6 Class Reference

Inherits rpki::resource_set::resource_range_ip.

Collaboration diagram for rpki.resource_set.resource_range_ipv6:



Static Public Attributes

- datum_type = rpki.ipaddrs.v6addr

  Type of underlying data (min and max).

8.150.1 Detailed Description

```
Range of IPv6 addresses.
```

Definition at line 180 of file resource_set.py.

8.150.2 Member Data Documentation

8.150.2.1 rpki::resource_set.resource_range_ipv6::datum_type = rpki.ipaddrs.v6addr [static]

Type of underlying data (min and max).

Definition at line 188 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.151 rpki.resource_set.resource_set Class Reference

Inherits list.

Inherited by rpki.resource_set.resource_set_as, and rpki.resource_set.resource_set_ip.

Collaboration diagram for rpki.resource_set.resource_set:



Public Member Functions

- def __init__
- def __str__
- def contains
- def difference
- def from_sql
- def intersection
- def issubset
- def issuperset
- def symmetric_difference
- def union

Static Public Attributes

- inherit = False

  Boolean indicating whether this resource_set uses RFC 3779 inheritance.

Private Member Functions

- def _comm

8.151.1 Detailed Description

```
Generic resource set, a list subclass containing resource ranges.

This is a virtual class.  You probably don't want to use it
directly.
```

Definition at line 206 of file resource_set.py.

8.151.2 Member Function Documentation

8.151.2.1 def rpki.resource_set.resource_set.__init__ (*self*, *ini* = `None`)

```
Initialize a resource_set.
```

Definition at line 219 of file resource_set.py.

8.151.2.2 def rpki.resource_set.resource_set.__str__ (*self*)

```
Convert a resource_set to string format.
```

Definition at line 246 of file resource_set.py.

8.151.2.3 def rpki.resource_set.resource_set._comm (*self*, *other*) `[private]`

```
Like comm(1), sort of.

Returns a tuple of three resource sets: resources only in self,
```

```
resources only in other, and resources in both.  Used (not very
efficiently) as the basis for most set operations on resource
sets.
```

Definition at line 255 of file resource_set.py.

8.151.2.4 def rpki.resource_set.resource_set.contains (*self*, *item*)

```
Set membership test for resource sets.
```

Definition at line 332 of file resource_set.py.

8.151.2.5 def rpki.resource_set.resource_set.difference (*self*, *other*)

```
Set difference for resource sets.
```

Definition at line 323 of file resource_set.py.

8.151.2.6 def rpki.resource_set.resource_set.from_sql (*cls*, *sql*, *query*, *args* = None)

```
Create resource set from an SQL query.

sql is an object that supports execute() and fetchall() methods
like a DB API 2.0 cursor object.

query is an SQL query that returns a sequence of (min, max) pairs.
```

Definition at line 369 of file resource_set.py.

8.151.2.7 def rpki.resource_set.resource_set.intersection (*self*, *other*)

```
Set intersection for resource sets.
```

Definition at line 319 of file resource_set.py.

8.151.2.8 def rpki.resource_set.resource_set.issubset (*self*, *other*)

```
Test whether self is a subset (possibly improper) of other.
```

Definition at line 355 of file resource_set.py.

8.151.2.9 def rpki.resource_set.resource_set.issuperset (*self*, *other*)

```
Test whether self is a superset (possibly improper) of other.
```

Definition at line 364 of file resource_set.py.

8.151.2.10 def rpki.resource_set.resource_set.symmetric_difference (*self*, *other*)

```
Set symmetric difference (XOR) for resource sets.
```

Definition at line 327 of file resource_set.py.

8.151.2.11 def rpki.resource_set.resource_set.union (*self*, *other*)

```
Set union for resource sets.
```

Definition at line 288 of file resource_set.py.

8.151.3 Member Data Documentation

8.151.3.1 rpki::resource_set.resource_set::inherit = False [static]

Boolean indicating whether this resource_set uses RFC 3779 inheritance.

Reimplemented in rpki.resource_set.resource_set_as, and rpki.resource_set.resource_set_ip.

Definition at line 217 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.152 rpki.resource_set.resource_set_as Class Reference

Inherits rpki::resource_set::resource_set.

Collaboration diagram for rpki.resource_set.resource_set_as:



Public Member Functions

- def parse_rfc3779_tuple
- def parse_str
- def to_rfc3779_tuple

Public Attributes

- inherit

  Boolean indicating whether this resource_set uses RFC 3779 inheritance.

Static Public Attributes

- range_type = resource_range_as

  Type of range underlying this type of resource_set.

8.152.1 Detailed Description

```
Autonomous System Number resource set.
```

Definition at line 384 of file resource_set.py.

8.152.2 Member Function Documentation

8.152.2.1 def rpki.resource_set.resource_set_as.parse_rfc3779_tuple (*self*, *x*)

```
Parse ASN resource from tuple format generated by RFC 3779 ASN.1
decoder.
```

Definition at line 404 of file resource_set.py.

8.152.2.2 def rpki.resource_set.resource_set_as.parse_str (*self*, *x*)

```
Parse ASN resource sets from text (eg, XML attributes).
```

Definition at line 394 of file resource_set.py.

8.152.2.3 def rpki.resource_set.resource_set_as.to_rfc3779_tuple (*self*)

```
Convert ASN resource set into tuple format used for RFC 3779 ASN.1
encoding.
```

Definition at line 422 of file resource_set.py.

8.152.3 Member Data Documentation

8.152.3.1 rpki.resource_set.resource_set_as.inherit

Boolean indicating whether this resource_set uses RFC 3779 inheritance.

Reimplemented from rpki.resource_set.resource_set.

Definition at line 420 of file resource_set.py.

8.152.3.2 rpki::resource_set.resource_set_as::range_type = resource_range_as [static]

Type of range underlying this type of resource_set.

Definition at line 392 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.153 rpki.resource_set.resource_set_ip Class Reference

Inherits rpki::resource_set::resource_set.

Inherited by rpki.resource_set.resource_set_ipv4, and rpki.resource_set.resource_set_-ipv6.

Collaboration diagram for rpki.resource_set.resource_set_ip:



Public Member Functions

- def parse_rfc3779_tuple
- def parse_str
- def to_rfc3779_tuple

Public Attributes

- inherit

  Boolean indicating whether this resource_set uses RFC 3779 inheritance.

8.153.1 Detailed Description

```
(Generic) IP address resource set.

This is a virtual class.  You probably don't want to use it
directly.
```

Definition at line 434 of file resource_set.py.

8.153.2 Member Function Documentation

8.153.2.1 def rpki.resource_set.resource_set_ip.parse_rfc3779_tuple (*self*, *x*)

```
Parse IP address resource sets from tuple format generated by RFC
3779 ASN.1 decoder.
```

Definition at line 454 of file resource_set.py.

8.153.2.2 def rpki.resource_set.resource_set_ip.parse_str (*self*, *x*)

```
Parse IP address resource sets from text (eg, XML attributes).
```

Definition at line 442 of file resource_set.py.

8.153.2.3 def rpki.resource_set.resource_set_ip.to_rfc3779_tuple (*self*)

```
Convert IP resource set into tuple format used by RFC 3779 ASN.1
encoder.
```

Definition at line 472 of file resource_set.py.

8.153.3 Member Data Documentation

8.153.3.1 rpki.resource_set.resource_set_ip.inherit

Boolean indicating whether this resource_set uses RFC 3779 inheritance.

Reimplemented from rpki.resource_set.resource_set.

Definition at line 470 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.154 rpki.resource_set.resource_set_ipv4 Class Reference

Inherits rpki::resource_set::resource_set_ip.

Collaboration diagram for rpki.resource_set.resource_set_ipv4:



Static Public Attributes

- string afi = "\x00\x01"

  Address Family Identifier value for IPv4.

- range_type = resource_range_ipv4

  Type of range underlying this type of resource_set.

8.154.1 Detailed Description

```
IPv4 address resource set.
```

Definition at line 484 of file resource_set.py.

8.154.2 Member Data Documentation

8.154.2.1 rpki::resource_set.resource_set_ipv4::afi = "\x00\x01" [static]

Address Family Identifier value for IPv4.

Definition at line 497 of file resource_set.py.

8.154.2.2 rpki::resource_set.resource_set_ipv4::range_type = resource_range_ipv4 [static]

Type of range underlying this type of resource_set.

Definition at line 492 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.155 rpki.resource_set.resource_set_ipv6 Class Reference

Inherits rpki::resource_set::resource_set_ip.

Collaboration diagram for rpki.resource_set.resource_set_ipv6:



Static Public Attributes

- string afi = "\x00\x02"

  Address Family Identifier value for IPv6.

- range_type = resource_range_ipv6

  Type of range underlying this type of resource_set.

8.155.1 Detailed Description

```
IPv6 address resource set.
```

Definition at line 499 of file resource_set.py.

8.155.2 Member Data Documentation

8.155.2.1 rpki::resource_set.resource_set_ipv6::afi = "\x00\x02" [static]

Address Family Identifier value for IPv6.

Definition at line 512 of file resource_set.py.

8.155.2.2 rpki::resource_set.resource_set_ipv6::range_type = resource_range_ipv6 [static]

Type of range underlying this type of resource_set.

Definition at line 507 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.156 rpki.resource_set.roa_prefix Class Reference

Inherits object.

Inherited by rpki.resource_set.roa_prefix_ipv4, and rpki.resource_set.roa_prefix_ipv6.

Collaboration diagram for rpki.resource_set.roa_prefix:



Public Member Functions

- def __cmp__
- def __init__
- def __str__
- def max
- def min
- def to_resource_range
- def to_roa_tuple

Public Attributes

- max_prefixlen

Maxmimum prefix length.

- prefix

  The prefix itself, an IP address with bits beyond the prefix length zeroed.

- prefixlen

  (Minimum) prefix length.

8.156.1 Detailed Description

```
ROA prefix.  This is similar to the resource_range_ip class, but
differs in that it only represents prefixes, never ranges, and
includes the maximum prefix length as an additional value.

This is a virtual class, you probably don't want to use it directly.
```

Definition at line 666 of file resource_set.py.

8.156.2 Member Function Documentation

8.156.2.1 def rpki.resource_set.roa_prefix.__cmp__ (*self*, *other*)

```
Compare two ROA prefix objects.  Comparision is based on prefix,
prefixlen, and max_prefixlen, in that order.
```

Definition at line 697 of file resource_set.py.

8.156.2.2 def rpki.resource_set.roa_prefix.__init__ (*self*, *prefix*, *prefixlen*, *max_prefixlen* = `None`)

```
Initialize a ROA prefix.  max_prefixlen is optional and defaults
to prefixlen.  max_prefixlen must not be smaller than prefixlen.
```

Definition at line 685 of file resource_set.py.

8.156.2.3 def rpki.resource_set.roa_prefix.__str__ (*self*)

```
Convert a ROA prefix to string format.
```

Definition at line 710 of file resource_set.py.

8.156.2.4 def rpki.resource_set.roa_prefix.max (*self*)

```
Return highest address covered by prefix.
```

Definition at line 731 of file resource_set.py.

8.156.2.5 def rpki.resource_set.roa_prefix.min (*self*)

```
Return lowest address covered by prefix.
```

Definition at line 727 of file resource_set.py.

8.156.2.6 def rpki.resource_set.roa_prefix.to_resource_range (*self*)

```
Convert this ROA prefix to the equivilent resource_range_ip
object.  This is an irreversable transformation because it loses
the max_prefixlen attribute, nothing we can do about that.
```

Definition at line 719 of file resource_set.py.

8.156.2.7 def rpki.resource_set.roa_prefix.to_roa_tuple (*self*)

```
Convert a resource_range_ip to tuple format for ROA ASN.1
encoding.
```

Definition at line 738 of file resource_set.py.

8.156.3 Member Data Documentation

8.156.3.1 rpki::resource_set.roa_prefix::max_prefixlen

Maxmimum prefix length.

Definition at line 695 of file resource_set.py.

8.156.3.2 rpki::resource_set.roa_prefix::prefix

The prefix itself, an IP address with bits beyond the prefix length zeroed.

Definition at line 693 of file resource_set.py.

8.156.3.3 rpki::resource_set.roa_prefix::prefixlen

(Minimum) prefix length.

Definition at line 694 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.157 rpki.resource_set.roa_prefix_ipv4 Class Reference

Inherits rpki::resource_set::roa_prefix.

Collaboration diagram for rpki.resource_set.roa_prefix_ipv4:



Static Public Attributes

- range_type = resource_range_ipv4

  Type of corresponding resource_range_ip.

8.157.1 Detailed Description

```
IPv4 ROA prefix.
```

Definition at line 746 of file resource_set.py.

8.157.2 Member Data Documentation

8.157.2.1 rpki::resource_set.roa_prefix_ipv4::range_type = resource_range_ipv4 [static]

Type of corresponding resource_range_ip.

Definition at line 754 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.158 rpki.resource_set.roa_prefix_ipv6 Class Reference

Inherits rpki::resource_set::roa_prefix.

Collaboration diagram for rpki.resource_set.roa_prefix_ipv6:



Static Public Attributes

- range_type = resource_range_ipv6

  Type of corresponding resource_range_ip.

8.158.1 Detailed Description

```
IPv6 ROA prefix.
```

Definition at line 756 of file resource_set.py.

8.158.2 Member Data Documentation

8.158.2.1 rpki::resource_set.roa_prefix_ipv6::range_type = resource_range_ipv6 [static]

Type of corresponding resource_range_ip.

Definition at line 764 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.159 rpki.resource_set.roa_prefix_set Class Reference

Inherits list.

Inherited by rpki.resource_set.roa_prefix_set_ipv4, and rpki.resource_set.roa_prefix_-set_ipv6.

Collaboration diagram for rpki.resource_set.roa_prefix_set:



Public Member Functions

- def __init__
- def __str__
- def from_sql
- def parse_str
- def to_resource_set
- def to_roa_tuple

8.159.1 Detailed Description

```
Set of ROA prefixes, analogous to the resource_set_ip class.
```

Definition at line 766 of file resource_set.py.

8.159.2 Member Function Documentation

8.159.2.1 def rpki.resource_set.roa_prefix_set.__init__ (*self*, *ini* = `None`)

```
Initialize a ROA prefix set.
```

Definition at line 771 of file resource_set.py.

8.159.2.2 def rpki.resource_set.roa_prefix_set.__str__ (*self*)

```
Convert a ROA prefix set to string format.
```

Definition at line 791 of file resource_set.py.

8.159.2.3 def rpki.resource_set.roa_prefix_set.from_sql (*cls*, *sql*, *query*, *args* = `None`)

```
Create ROA prefix set from an SQL query.

sql is an object that supports execute() and fetchall() methods
like a DB API 2.0 cursor object.

query is an SQL query that returns a sequence of (prefix,
prefixlen, max_prefixlen) triples.
```

Definition at line 825 of file resource_set.py.

8.159.2.4 def rpki.resource_set.roa_prefix_set.parse_str (*self*, *x*)

```
Parse ROA prefix from text (eg, an XML attribute).
```

Definition at line 795 of file resource_set.py.

8.159.2.5 def rpki.resource_set.roa_prefix_set.to_resource_set (*self*)

```
Convert a ROA prefix set to a resource set.  This is an
irreversable transformation.  We have to compute a union here
because ROA prefix sets can include overlaps, while RFC 3779
resource sets cannot.  This is ugly, and there is almost certainly
a more efficient way to do this, but start by getting the output
right before worrying about making it fast or pretty.
```

Definition at line 807 of file resource_set.py.

8.159.2.6 def rpki.resource_set.roa_prefix_set.to_roa_tuple (*self*)

```
Convert ROA prefix set into tuple format used by ROA ASN.1
encoder.  This is a variation on the format used in RFC 3779.
```

Definition at line 840 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.160 rpki.resource_set.roa_prefix_set_ipv4 Class Reference

Inherits rpki::resource_set::roa_prefix_set.

Collaboration diagram for rpki.resource_set.roa_prefix_set_ipv4:



Static Public Attributes

- prefix_type = roa_prefix_ipv4

  Type of underlying roa_prefix.

- resource_set_type = resource_set_ipv4

  Type of corresponding resource_set_ip class.

8.160.1 Detailed Description

```
Set of IPv4 ROA prefixes.
```

Definition at line 850 of file resource_set.py.

8.160.2 Member Data Documentation

8.160.2.1 rpki::resource_set.roa_prefix_set_ipv4::prefix_type = roa_prefix_ipv4 [static]

Type of underlying roa_prefix.

Definition at line 858 of file resource_set.py.

8.160.2.2 rpki::resource_set.roa_prefix_set_ipv4::resource_set_type = resource_set_ipv4 [static]

Type of corresponding resource_set_ip class.

Definition at line 863 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.161 rpki.resource_set.roa_prefix_set_ipv6 Class Reference

Inherits rpki::resource_set::roa_prefix_set.

Collaboration diagram for rpki.resource_set.roa_prefix_set_ipv6:



Static Public Attributes

- prefix_type = roa_prefix_ipv6

  Type of underlying roa_prefix.

- resource_set_type = resource_set_ipv6

  Type of corresponding resource_set_ip class.

8.161.1 Detailed Description

```
Set of IPv6 ROA prefixes.
```

Definition at line 865 of file resource_set.py.

8.161.2 Member Data Documentation

8.161.2.1 rpki::resource_set.roa_prefix_set_ipv6::prefix_type = roa_prefix_ipv6 [static]

Type of underlying roa_prefix.

Definition at line 873 of file resource_set.py.

8.161.2.2 rpki::resource_set.roa_prefix_set_ipv6::resource_set_type = resource_set_ipv6 [static]

Type of corresponding resource_set_ip class.

Definition at line 878 of file resource_set.py.

The documentation for this class was generated from the following file:

- resource_set.py (3107)

8.162 rpki.roa.ROAIPAddress Class Reference

Inherits Sequence.

Collaboration diagram for rpki.roa.ROAIPAddress:



Public Member Functions

- def __init__

Public Attributes

- address
- maxLength

8.162.1 Detailed Description

Definition at line 47 of file roa.py.

8.162.2 Member Function Documentation

8.162.2.1 def rpki.roa.ROAIPAddress.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 48 of file roa.py.

8.162.3 Member Data Documentation

8.162.3.1 rpki.roa.ROAIPAddress.address

Definition at line 49 of file roa.py.

8.162.3.2 rpki.roa.ROAIPAddress.maxLength

Definition at line 50 of file roa.py.

The documentation for this class was generated from the following file:

- roa.py (2424)

8.163 rpki.roa.ROAIPAddresses Class Reference

Inherits SequenceOf.

Collaboration diagram for rpki.roa.ROAIPAddresses:



Public Member Functions

- def __init__

8.163.1 Detailed Description

Definition at line 54 of file roa.py.

8.163.2 Member Function Documentation

8.163.2.1 def rpki.roa.ROAIPAddresses.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 55 of file roa.py.

The documentation for this class was generated from the following file:

- roa.py (2424)

8.164 rpki.roa.ROAIPAddressFamilies Class Reference

Inherits SequenceOf.

Collaboration diagram for rpki.roa.ROAIPAddressFamilies:



Public Member Functions

- def __init__

8.164.1 Detailed Description

Definition at line 65 of file roa.py.

8.164.2 Member Function Documentation

8.164.2.1 def rpki.roa.ROAIPAddressFamilies.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 66 of file roa.py.

The documentation for this class was generated from the following file:

- roa.py (2424)

8.165 rpki.roa.ROAIPAddressFamily Class Reference

Inherits Sequence.

Collaboration diagram for rpki.roa.ROAIPAddressFamily:



Public Member Functions

- def __init__

Public Attributes

- addresses
- addressFamily

8.165.1 Detailed Description

Definition at line 58 of file roa.py.

8.165.2 Member Function Documentation

8.165.2.1 def rpki.roa.ROAIPAddressFamily.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 59 of file roa.py.

8.165.3 Member Data Documentation

8.165.3.1 rpki.roa.ROAIPAddressFamily.addresses

Definition at line 61 of file roa.py.

8.165.3.2 rpki.roa.ROAIPAddressFamily.addressFamily

Definition at line 60 of file roa.py.

The documentation for this class was generated from the following file:

- roa.py (2424)

8.166 rpki.roa.RouteOriginAttestation Class Reference

Inherits Sequence.

Collaboration diagram for rpki.roa.RouteOriginAttestation:



Public Member Functions

- def __init__

Public Attributes

- asID
- explicitVersion
- ipAddrBlocks
- version

8.166.1 Detailed Description

Definition at line 69 of file roa.py.

8.166.2 Member Function Documentation

8.166.2.1 def rpki.roa.RouteOriginAttestation.__init__ (*self*, *optional* = 0, *default* = '')

Definition at line 70 of file roa.py.

8.166.3 Member Data Documentation

8.166.3.1 rpki.roa.RouteOriginAttestation.asID

Definition at line 73 of file roa.py.

8.166.3.2 rpki.roa.RouteOriginAttestation.explicitVersion

Definition at line 72 of file roa.py.

8.166.3.3 rpki.roa.RouteOriginAttestation.ipAddrBlocks

Definition at line 74 of file roa.py.

8.166.3.4 rpki.roa.RouteOriginAttestation.version

Definition at line 71 of file roa.py.

The documentation for this class was generated from the following file:

- roa.py (2424)

8.167 rpki.rpki_engine.ca_detail_obj Class Reference

Inherits rpki::sql::sql_persistent.

Collaboration diagram for rpki.rpki_engine.ca_detail_obj:



Public Member Functions

- def activate
- def ca
- def child_certs
- def create
- def crl_published_callback

- def crl_uri
- def crl_uri_tail
- def delete
- def generate_crl
- def generate_manifest
- def generate_manifest_cert
- def issue
- def issue_ee
- def manifest_published_callback
- def manifest_uri
- def revoke
- def revoked_certs
- def roas
- def sql_decode
- def update

Public Attributes

- ca_cert_uri
- ca_id
- gctx
- latest_crl
- latest_manifest
- latest_manifest_cert
- manifest_private_key_id
- manifest_public_key
- nextUpdate
- private_key_id
- public_key
- state

Static Public Attributes

- crl_published = None
- latest_ca_cert = None
- manifest_published = None
- tuple sql_template

8.167.1 Detailed Description

```
Internal CA detail object.
```

Definition at line 562 of file rpki_engine.py.

8.167.2 Member Function Documentation

8.167.2.1 def rpki.rpki_engine.ca_detail_obj.activate (*self*, *ca*, *cert*, *uri*, *callback*, *errback*, *predecessor* = `None`)

```
Activate this ca_detail.
```

Definition at line 624 of file rpki_engine.py.

8.167.2.2 def rpki.rpki_engine.ca_detail_obj.ca (*self*)

```
Fetch CA object to which this ca_detail links.
```

Definition at line 596 of file rpki_engine.py.

8.167.2.3 def rpki.rpki_engine.ca_detail_obj.child_certs (*self*, *child* = `None`, *ski* = `None`, *unique* = `False`)

```
Fetch all child_cert objects that link to this ca_detail.
```

Definition at line 600 of file rpki_engine.py.

8.167.2.4 def rpki.rpki_engine.ca_detail_obj.create (*cls*, *ca*)

```
Create a new ca_detail object for a specified CA.
```

Definition at line 762 of file rpki_engine.py.

8.167.2.5 def rpki.rpki_engine.ca_detail_obj.crl_published_callback (*self*, *pdu*)

```
Check result of CRL publication.
```

Definition at line 885 of file rpki_engine.py.

8.167.2.6 def rpki.rpki_engine.ca_detail_obj.crl_uri (*self*, *ca*)

```
Return publication URI for this ca_detail's CRL.
```

Definition at line 612 of file rpki_engine.py.

8.167.2.7 def rpki.rpki_engine.ca_detail_obj.crl_uri_tail (*self*)

```
Return tail (filename portion) of publication URI for this ca_detail's CRL.
```

Definition at line 616 of file rpki_engine.py.

8.167.2.8 def rpki.rpki_engine.ca_detail_obj.delete (*self*, *ca*, *publisher*, *allow_failure* = `False`)

```
Delete this ca_detail and all of the certs it issued.

If allow_failure is true, we clean up as much as we can but don't
raise an exception.
```

Definition at line 649 of file rpki_engine.py.

8.167.2.9 def rpki.rpki_engine.ca_detail_obj.generate_crl (*self*, *publisher*, *nextUpdate* = `None`)

```
Generate a new CRL for this ca_detail.  At the moment this is
unconditional, that is, it is up to the caller to decide whether a
new CRL is needed.
```

Definition at line 849 of file rpki_engine.py.

8.167.2.10 def rpki.rpki_engine.ca_detail_obj.generate_manifest (*self*, *publisher*, *nextUpdate* = `None`)

```
Generate a new manifest for this ca_detail.
```

Definition at line 893 of file rpki_engine.py.

8.167.2.11 def rpki.rpki_engine.ca_detail_obj.generate_manifest_cert (*self*, *ca*)

```
Generate a new manifest certificate for this ca_detail.
```

Definition at line 797 of file rpki_engine.py.

8.167.2.12 def rpki.rpki_engine.ca_detail_obj.issue (*self*, *ca*, *child*, *subject_key*, *sia*, *resources*, *publisher*, *child_cert* = None)

```
Issue a new certificate to a child.  Optional child_cert argument
specifies an existing child_cert object to update in place; if not
specified, we create a new one.  Returns the child_cert object
containing the newly issued cert.
```

Definition at line 809 of file rpki_engine.py.

8.167.2.13 def rpki.rpki_engine.ca_detail_obj.issue_ee (*self*, *ca*, *resources*, *subject_key*, *sia* = None)

```
Issue a new EE certificate.
```

Definition at line 780 of file rpki_engine.py.

8.167.2.14 def rpki.rpki_engine.ca_detail_obj.manifest_published_callback (*self*, *pdu*)

```
Check result of manifest publication.
```

Definition at line 927 of file rpki_engine.py.

8.167.2.15 def rpki.rpki_engine.ca_detail_obj.manifest_uri (*self*, *ca*)

```
Return publication URI for this ca_detail's manifest.
```

Definition at line 620 of file rpki_engine.py.

8.167.2.16 def rpki.rpki_engine.ca_detail_obj.revoke (*self*, *cb*, *eb*)

```
Request revocation of all certificates whose SKI matches the key
for this ca_detail.

Tasks:

- Request revocation of old keypair by parent.

- Revoke all child certs issued by the old keypair.

- Generate a final CRL, signed with the old keypair, listing all
  the revoked certs, with a next CRL time after the last cert or
  CRL signed by the old keypair will have expired.

- Generate a corresponding final manifest.

- Destroy old keypairs.

- Leave final CRL and manifest in place until their nextupdate
  time has passed.
```

Definition at line 673 of file rpki_engine.py.

8.167.2.17 def rpki.rpki_engine.ca_detail_obj.revoked_certs (*self*)

```
Fetch all revoked_cert objects that link to this ca_detail.
```

Definition at line 604 of file rpki_engine.py.

8.167.2.18 def rpki.rpki_engine.ca_detail_obj.roas (*self*)

```
Fetch all ROA objects that link to this ca_detail.
```

Definition at line 608 of file rpki_engine.py.

8.167.2.19 def rpki.rpki_engine.ca_detail_obj.sql_decode (*self*, *vals*)

```
Extra assertions for SQL decode of a ca_detail_obj.
```

Reimplemented from rpki.sql.sql_persistent.

Definition at line 588 of file rpki_engine.py.

8.167.2.20 def rpki.rpki_engine.ca_detail_obj.update (*self*, *parent*, *ca*, *rc*, *sia_uri_changed*, *old_resources*, *callback*, *errback*)

```
Need to get a new certificate for this ca_detail and perhaps frob
children of this ca_detail.
```

Definition at line 737 of file rpki_engine.py.

8.167.3 Member Data Documentation

8.167.3.1 rpki.rpki_engine.ca_detail_obj.ca_cert_uri

Definition at line 632 of file rpki_engine.py.

8.167.3.2 rpki.rpki_engine.ca_detail_obj.ca_id

Definition at line 768 of file rpki_engine.py.

8.167.3.3 rpki.rpki_engine.ca_detail_obj.crl_published = None [static]

Definition at line 584 of file rpki_engine.py.

8.167.3.4 rpki.rpki_engine.ca_detail_obj.gctx

Reimplemented from rpki.sql.sql_persistent.

Definition at line 767 of file rpki_engine.py.

8.167.3.5 rpki.rpki_engine.ca_detail_obj.latest_ca_cert = None [static]

Definition at line 586 of file rpki_engine.py.

8.167.3.6 rpki.rpki_engine.ca_detail_obj.latest_crl

Definition at line 872 of file rpki_engine.py.

8.167.3.7 rpki.rpki_engine.ca_detail_obj.latest_manifest

Definition at line 913 of file rpki_engine.py.

8.167.3.8 rpki.rpki_engine.ca_detail_obj.latest_manifest_cert

Definition at line 730 of file rpki_engine.py.

8.167.3.9 rpki.rpki_engine.ca_detail_obj.manifest_private_key_id

Definition at line 728 of file rpki_engine.py.

8.167.3.10 rpki.rpki_engine.ca_detail_obj.manifest_public_key

Definition at line 729 of file rpki_engine.py.

8.167.3.11 rpki.rpki_engine.ca_detail_obj.manifest_published = None [static]

Definition at line 585 of file rpki_engine.py.

8.167.3.12 rpki.rpki_engine.ca_detail_obj.nextUpdate

Definition at line 706 of file rpki_engine.py.

8.167.3.13 rpki.rpki_engine.ca_detail_obj.private_key_id

Definition at line 727 of file rpki_engine.py.

8.167.3.14 rpki.rpki_engine.ca_detail_obj.public_key

Definition at line 772 of file rpki_engine.py.

8.167.3.15 tuple rpki.rpki_engine.ca_detail_obj.sql_template [static]

Initial value:

```
rpki.sql.template(
    "ca_detail",
    "ca_detail_id",
    ("private_key_id",          rpki.x509.RSA),
    ("public_key",              rpki.x509.RSApublic),
    ("latest_ca_cert",          rpki.x509.X509),
    ("manifest_private_key_id", rpki.x509.RSA),
    ("manifest_public_key",     rpki.x509.RSApublic),
    ("latest_manifest_cert",    rpki.x509.X509),
    ("latest_manifest",         rpki.x509.SignedManifest),
    ("latest_crl",              rpki.x509.CRL),
    ("crl_published",           rpki.sundial.datetime),
    ("manifest_published",      rpki.sundial.datetime),
    "state",
    "ca_cert_uri",
    "ca_id")
```

Definition at line 567 of file rpki_engine.py.

8.167.3.16 rpki.rpki_engine.ca_detail_obj.state

Definition at line 634 of file rpki_engine.py.

The documentation for this class was generated from the following file:

- rpki_engine.py (3107)

8.168 rpki.rpki_engine.ca_obj Class Reference

Inherits rpki::sql::sql_persistent.

Collaboration diagram for rpki.rpki_engine.ca_obj:



Public Member Functions

- def ca_details
- def check_for_updates
- def construct_sia_uri
- def create
- def delete

- def fetch_active
- def fetch_deprecated
- def fetch_issue_response_candidates
- def fetch_pending
- def fetch_revoked
- def next_crl_number
- def next_manifest_number
- def next_serial_number
- def parent
- def rekey
- def revoke

Public Attributes

- gctx
- parent_id
- parent_resource_class
- sia_uri

Static Public Attributes

- int last_crl_sn = 0
- int last_issued_sn = 0
- int last_manifest_sn = 0
- tuple sql_template

8.168.1 Detailed Description

```
Internal CA object.
```

Definition at line 308 of file rpki_engine.py.

8.168.2 Member Function Documentation

8.168.2.1 def rpki.rpki_engine.ca_obj.ca_details (*self*)

```
Fetch all ca_detail objects that link to this CA object.
```

Definition at line 330 of file rpki_engine.py.

8.168.2.2 def rpki.rpki_engine.ca_obj.check_for_updates (*self*, *parent*, *rc*, *cb*, *eb*)

```
Parent has signaled continued existance of a resource class we
already knew about, so we need to check for an updated
certificate, changes in resource coverage, revocation and reissue
with the same key, etc.
```

Definition at line 371 of file rpki_engine.py.

8.168.2.3 def rpki.rpki_engine.ca_obj.construct_sia_uri (*self*, *parent*, *rc*)

```
Construct the sia_uri value for this CA given configured
information and the parent's up-down protocol list_response PDU.
```

Definition at line 358 of file rpki_engine.py.

8.168.2.4 def rpki.rpki_engine.ca_obj.create (*cls*, *parent*, *rc*, *cb*, *eb*)

```
Parent has signaled existance of a new resource class, so we need
to create and set up a corresponding CA object.
```

Definition at line 451 of file rpki_engine.py.

8.168.2.5 def rpki.rpki_engine.ca_obj.delete (*self*, *parent*, *callback*)

```
The list of current resource classes received from parent does not
include the class corresponding to this CA, so we need to delete
it (and its little dog too...).

All certs published by this CA are now invalid, so need to
withdraw them, the CRL, and the manifest from the repository,
delete all child_cert and ca_detail records associated with this
CA, then finally delete this CA itself.
```

Definition at line 475 of file rpki_engine.py.

8.168.2.6 def rpki.rpki_engine.ca_obj.fetch_active (*self*)

```
Fetch the active ca_detail for this CA, if any.
```

Definition at line 338 of file rpki_engine.py.

8.168.2.7 def rpki.rpki_engine.ca_obj.fetch_deprecated (*self*)

```
Fetch deprecated ca_details for this CA, if any.
```

Definition at line 342 of file rpki_engine.py.

8.168.2.8 def rpki.rpki_engine.ca_obj.fetch_issue_response_candidates (*self*)

```
Fetch ca_details which are candidates for consideration when
processing an up-down issue_response PDU.
```

Definition at line 350 of file rpki_engine.py.

8.168.2.9 def rpki.rpki_engine.ca_obj.fetch_pending (*self*)

```
Fetch the pending ca_details for this CA, if any.
```

Definition at line 334 of file rpki_engine.py.

8.168.2.10 def rpki.rpki_engine.ca_obj.fetch_revoked (*self*)

```
Fetch revoked ca_details for this CA, if any.
```

Definition at line 346 of file rpki_engine.py.

8.168.2.11 def rpki.rpki_engine.ca_obj.next_crl_number (*self*)

```
Allocate a CRL serial number.
```

Definition at line 517 of file rpki_engine.py.

8.168.2.12 def rpki.rpki_engine.ca_obj.next_manifest_number (*self*)

```
Allocate a manifest serial number.
```

Definition at line 509 of file rpki_engine.py.

8.168.2.13 def rpki.rpki_engine.ca_obj.next_serial_number (*self*)

```
Allocate a certificate serial number.
```

Definition at line 501 of file rpki_engine.py.

8.168.2.14 def rpki.rpki_engine.ca_obj.parent (*self*)

```
Fetch parent object to which this CA object links.
```

Definition at line 326 of file rpki_engine.py.

8.168.2.15 def rpki.rpki_engine.ca_obj.rekey (*self*, *cb*, *eb*)

```
Initiate a rekey operation for this ca.  Generate a new keypair.
Request cert from parent using new keypair.  Mark result as our
active ca_detail.  Reissue all child certs issued by this ca using
the new ca_detail.
```

Definition at line 525 of file rpki_engine.py.

8.168.2.16 def rpki.rpki_engine.ca_obj.revoke (*self*, *cb*, *eb*)

```
Revoke deprecated ca_detail objects associated with this ca.
```

Definition at line 550 of file rpki_engine.py.

8.168.3 Member Data Documentation

8.168.3.1 rpki.rpki_engine.ca_obj.gctx

Reimplemented from rpki.sql.sql_persistent.

Definition at line 458 of file rpki_engine.py.

8.168.3.2 int rpki.rpki_engine.ca_obj.last_crl_sn = 0 [static]

Definition at line 322 of file rpki_engine.py.

8.168.3.3 int rpki.rpki_engine.ca_obj.last_issued_sn = 0 [static]

Definition at line 323 of file rpki_engine.py.

8.168.3.4 int rpki.rpki_engine.ca_obj.last_manifest_sn = 0 [static]

Definition at line 324 of file rpki_engine.py.

8.168.3.5 rpki.rpki_engine.ca_obj.parent_id

Definition at line 459 of file rpki_engine.py.

8.168.3.6 rpki.rpki_engine.ca_obj.parent_resource_class

Definition at line 460 of file rpki_engine.py.

8.168.3.7 rpki.rpki_engine.ca_obj.sia_uri

Definition at line 382 of file rpki_engine.py.

8.168.3.8 tuple rpki.rpki_engine.ca_obj.sql_template [static]

Initial value:

```
rpki.sql.template(
    "ca",
    "ca_id",
    "last_crl_sn",
    ("next_crl_update", rpki.sundial.datetime),
    "last_issued_sn", "last_manifest_sn",
    ("next_manifest_update", rpki.sundial.datetime),
    "sia_uri", "parent_id", "parent_resource_class")
```

Definition at line 313 of file rpki_engine.py.

The documentation for this class was generated from the following file:

- rpki_engine.py (3107)

8.169 rpki.rpki_engine.child_cert_obj Class Reference

Inherits rpki::sql::sql_persistent.

Collaboration diagram for rpki.rpki_engine.child_cert_obj:



Public Member Functions

- def __init__
- def ca_detail
- def child
- def fetch
- def published_callback

- def reissue
- def revoke
- def uri
- def uri_tail

Public Attributes

- ca_detail_id
- cert
- child_id
- gctx
- published

Static Public Attributes

- tuple sql_template

8.169.1 Detailed Description

```
Certificate that has been issued to a child.
```

Definition at line 936 of file rpki_engine.py.

8.169.2 Member Function Documentation

8.169.2.1 def rpki.rpki_engine.child_cert_obj.__init__ (*self*, *gctx* = `None`, *child_id* = `None`, *ca_detail_id* = `None`, *cert* = `None`)

```
Initialize a child_cert_obj.
```

Definition at line 950 of file rpki_engine.py.

8.169.2.2 def rpki.rpki_engine.child_cert_obj.ca_detail (*self*)

```
Fetch ca_detail object to which this child_cert object links.
```

Definition at line 967 of file rpki_engine.py.

8.169.2.3 def rpki.rpki_engine.child_cert_obj.child (*self*)

```
Fetch child object to which this child_cert object links.
```

Definition at line 963 of file rpki_engine.py.

8.169.2.4 def rpki.rpki_engine.child_cert_obj.fetch (*cls*, *gctx* = **None**, *child* = **None**, *ca_detail* = **None**, *ski* = **None**, *unique* = **False**)

```
Fetch all child_cert objects matching a particular set of
parameters.  This is a wrapper to consolidate various queries that
would otherwise be inline SQL WHERE expressions.  In most cases
code calls this indirectly, through methods in other classes.
```

Definition at line 1048 of file rpki_engine.py.

8.169.2.5 def rpki.rpki_engine.child_cert_obj.published_callback (*self*, *pdu*)

```
Publication callback: check result and mark published.
```

Definition at line 1080 of file rpki_engine.py.

8.169.2.6 def rpki.rpki_engine.child_cert_obj.reissue (*self*, *ca_detail*, *publisher*, *resources* = **None**, *sia* = **None**)

```
Reissue an existing child cert, reusing the public key.  If the
child cert we would generate is identical to the one we already
have, we just return the one we already have.  If we have to
revoke the old child cert when generating the new one, we have to
generate a new child_cert_obj, so calling code that needs the
updated child_cert_obj must use the return value from this method.
```

Definition at line 991 of file rpki_engine.py.

8.169.2.7 def rpki.rpki_engine.child_cert_obj.revoke (*self*, *publisher*)

```
Revoke a child cert.
```

Definition at line 979 of file rpki_engine.py.

8.169.2.8 def rpki.rpki_engine.child_cert_obj.uri (*self*, *ca*)

```
Return the publication URI for this child_cert.
```

Definition at line 975 of file rpki_engine.py.

8.169.2.9 def rpki.rpki_engine.child_cert_obj.uri_tail (*self*)

```
Return the tail (filename) portion of the URI for this child_cert.
```

Definition at line 971 of file rpki_engine.py.

8.169.3 Member Data Documentation

8.169.3.1 rpki.rpki_engine.child_cert_obj.ca_detail_id

Definition at line 957 of file rpki_engine.py.

8.169.3.2 rpki.rpki_engine.child_cert_obj.cert

Definition at line 958 of file rpki_engine.py.

8.169.3.3 rpki.rpki_engine.child_cert_obj.child_id

Definition at line 956 of file rpki_engine.py.

8.169.3.4 rpki.rpki_engine.child_cert_obj.gctx

Reimplemented from rpki.sql.sql_persistent.

Definition at line 955 of file rpki_engine.py.

8.169.3.5 rpki.rpki_engine.child_cert_obj.published

Definition at line 959 of file rpki_engine.py.

8.169.3.6 tuple rpki.rpki_engine.child_cert_obj.sql_template [static]

Initial value:

```
rpki.sql.template(
    "child_cert",
    "child_cert_id",
    ("cert", rpki.x509.X509),
    "child_id",
    "ca_detail_id",
    "ski",
    ("published", rpki.sundial.datetime))
```

Definition at line 941 of file rpki_engine.py.

The documentation for this class was generated from the following file:

- rpki_engine.py (3107)

8.170 rpki.rpki_engine.publication_queue Class Reference

Inherits object.

Collaboration diagram for rpki.rpki_engine.publication_queue:



Public Member Functions

- def __init__
- def call_pubd
- def publish
- def withdraw

Public Attributes

- handlers
- msgs
- repositories
- uris

Static Public Attributes

- replace = True

Private Member Functions

- def _add

8.170.1 Detailed Description

```
Utility to simplify publication from within rpkid.

General idea here is to accumulate a collection of objects to be
published, in one or more repositories, each potentially with its
own completion callback.  Eventually we want to publish everything
we've accumulated, at which point we need to iterate over the
collection and do repository.call_pubd() for each repository.
```

Definition at line 1366 of file rpki_engine.py.

8.170.2 Member Function Documentation

8.170.2.1 def rpki.rpki_engine.publication_queue.__init__ (*self*)

Definition at line 1379 of file rpki_engine.py.

8.170.2.2 def rpki.rpki_engine.publication_queue._add (*self*, *cls*, *uri*, *obj*, *repository*, *handler*, *withdraw*) `[private]`

Definition at line 1386 of file rpki_engine.py.

8.170.2.3 def rpki.rpki_engine.publication_queue.call_pubd (*self*, *cb*, *eb*)

Definition at line 1409 of file rpki_engine.py.

8.170.2.4 def rpki.rpki_engine.publication_queue.publish (*self*, *cls*, *uri*, *obj*, *repository*, *handler* = `None`)

Definition at line 1403 of file rpki_engine.py.

8.170.2.5 def rpki.rpki_engine.publication_queue.withdraw (*self*, *cls*, *uri*, *obj*, *repository*, *handler* = `None`)

Definition at line 1406 of file rpki_engine.py.

8.170.3 Member Data Documentation

8.170.3.1 rpki.rpki_engine.publication_queue.handlers

Definition at line 1382 of file rpki_engine.py.

8.170.3.2 rpki.rpki_engine.publication_queue.msgs

Definition at line 1381 of file rpki_engine.py.

8.170.3.3 rpki.rpki_engine.publication_queue.replace = True `[static]`

Definition at line 1377 of file rpki_engine.py.

8.170.3.4 rpki.rpki_engine.publication_queue.repositories

Definition at line 1380 of file rpki_engine.py.

8.170.3.5 rpki.rpki_engine.publication_queue.uris

Definition at line 1384 of file rpki_engine.py.

The documentation for this class was generated from the following file:

- rpki_engine.py (3107)

8.171 rpki.rpki_engine.revoked_cert_obj Class Reference

Inherits rpki::sql::sql_persistent.

Collaboration diagram for rpki.rpki_engine.revoked_cert_obj:



Public Member Functions

- def __init__
- def ca_detail

- def revoke

Public Attributes

- ca_detail_id
- expires
- gctx
- revoked
- serial

Static Public Attributes

- tuple sql_template

8.171.1 Detailed Description

```
Tombstone for a revoked certificate.
```

Definition at line 1088 of file rpki_engine.py.

8.171.2 Member Function Documentation

8.171.2.1 def rpki.rpki_engine.revoked_cert_obj.__init__ (*self*, *gctx* = None, *serial* = None, *revoked* = None, *expires* = None, *ca_detail_id* = None)

```
Initialize a revoked_cert_obj.
```

Definition at line 1101 of file rpki_engine.py.

8.171.2.2 def rpki.rpki_engine.revoked_cert_obj.ca_detail (*self*)

```
Fetch ca_detail object to which this revoked_cert_obj links.
```

Definition at line 1112 of file rpki_engine.py.

8.171.2.3 def rpki.rpki_engine.revoked_cert_obj.revoke (*cls*, *cert*, *ca_detail*)

```
Revoke a certificate.
```

Definition at line 1117 of file rpki_engine.py.

8.171.3 Member Data Documentation

8.171.3.1 rpki.rpki_engine.revoked_cert_obj.ca_detail_id

Definition at line 1108 of file rpki_engine.py.

8.171.3.2 rpki.rpki_engine.revoked_cert_obj.expires

Definition at line 1107 of file rpki_engine.py.

8.171.3.3 rpki.rpki_engine.revoked_cert_obj.gctx

Reimplemented from rpki.sql.sql_persistent.

Definition at line 1104 of file rpki_engine.py.

8.171.3.4 rpki.rpki_engine.revoked_cert_obj.revoked

Definition at line 1106 of file rpki_engine.py.

8.171.3.5 rpki.rpki_engine.revoked_cert_obj.serial

Definition at line 1105 of file rpki_engine.py.

8.171.3.6 tuple rpki.rpki_engine.revoked_cert_obj.sql_template [static]

Initial value:

```
rpki.sql.template(
    "revoked_cert",
    "revoked_cert_id",
    "serial",
    "ca_detail_id",
    ("revoked", rpki.sundial.datetime),
    ("expires", rpki.sundial.datetime))
```

Definition at line 1093 of file rpki_engine.py.

The documentation for this class was generated from the following file:

- rpki_engine.py (3107)

8.172 rpki.rpki_engine.roa_obj Class Reference

Inherits rpki::sql::sql_persistent.

Collaboration diagram for rpki.rpki_engine.roa_obj:



Public Member Functions

- def __init__
- def ca_detail
- def generate
- def published_callback
- def regenerate

- def revoke
- def self
- def sql_delete_hook
- def sql_fetch_hook
- def sql_insert_hook
- def update
- def uri
- def uri_tail

Public Attributes

- asn
- gctx
- ipv4
- ipv6
- self_id

Static Public Attributes

- ca_detail_id = None
- cert = None
- published = None
- roa = None
- tuple sql_template

8.172.1 Detailed Description

```
Route Origin Authorization.
```

Definition at line 1128 of file rpki_engine.py.

8.172.2 Member Function Documentation

8.172.2.1 def rpki.rpki_engine.roa_obj.__init__ (*self*, *gctx* = `None`, *self_id* = `None`, *asn* = `None`, *ipv4* = `None`, *ipv6* = `None`)

Definition at line 1194 of file rpki_engine.py.

8.172.2.2 def rpki.rpki_engine.roa_obj.ca_detail (*self*)

```
Fetch ca_detail object to which this roa_obj links.
```

Definition at line 1154 of file rpki_engine.py.

8.172.2.3 def rpki.rpki_engine.roa_obj.generate (*self*, *publisher*)

```
Generate a ROA.

At present this does not support ROAs with multiple signatures
(neither does the current CMS code).

At present we have no way of performing a direct lookup from a
desired set of resources to a covering certificate, so we have to
search.  This could be quite slow if we have a lot of active
ca_detail objects.  Punt on the issue for now, revisit if
profiling shows this as a hotspot.

Once we have the right covering certificate, we generate the ROA
payload, generate a new EE certificate, use the EE certificate to
sign the ROA payload, publish the result, then throw away the
private key for the EE cert, all per the ROA specification.  This
implies that generating a lot of ROAs will tend to thrash
/dev/random, but there is not much we can do about that.
```

Definition at line 1237 of file rpki_engine.py.

8.172.2.4 def rpki.rpki_engine.roa_obj.published_callback (*self*, *pdu*)

```
Check publication result.
```

Definition at line 1303 of file rpki_engine.py.

8.172.2.5 def rpki.rpki_engine.roa_obj.regenerate (*self*, *publisher*)

```
Reissue ROA associated with this roa_obj.
```

Definition at line 1343 of file rpki_engine.py.

8.172.2.6 def rpki.rpki_engine.roa_obj.revoke (*self*, *publisher*, *regenerate* = `False`, *allow_failure* = `False`)

```
Withdraw ROA associated with this roa_obj.

In order to preserve make-before-break properties without
duplicating code, this method also handles generating a
replacement ROA when requested.

If allow_failure is set, failing to withdraw the ROA will not be
considered an error.
```

Definition at line 1311 of file rpki_engine.py.

8.172.2.7 def rpki.rpki_engine.roa_obj.self (*self*)

```
Fetch self object to which this roa_obj links.
```

Definition at line 1148 of file rpki_engine.py.

8.172.2.8 def rpki.rpki_engine.roa_obj.sql_delete_hook (*self*)

```
Extra SQL delete actions for roa_obj -- handle prefix lists.
```

Reimplemented from rpki.sql.sql_persistent.

Definition at line 1188 of file rpki_engine.py.

8.172.2.9 def rpki.rpki_engine.roa_obj.sql_fetch_hook (*self*)

```
Extra SQL fetch actions for roa_obj -- handle prefix lists.
```

Reimplemented from rpki.sql.sql_persistent.

Definition at line 1160 of file rpki_engine.py.

8.172.2.10 def rpki.rpki_engine.roa_obj.sql_insert_hook (*self*)

```
Extra SQL insert actions for roa_obj -- handle prefix lists.
```

Reimplemented from rpki.sql.sql_persistent.

Definition at line 1174 of file rpki_engine.py.

8.172.2.11 def rpki.rpki_engine.roa_obj.update (*self*, *publisher*)

```
Bring this roa_obj's ROA up to date if necesssary.
```

Definition at line 1207 of file rpki_engine.py.

8.172.2.12 def rpki.rpki_engine.roa_obj.uri (*self*, *key* = `None`)

```
Return the publication URI for this roa_obj's ROA.
```

Definition at line 1352 of file rpki_engine.py.

8.172.2.13 def rpki.rpki_engine.roa_obj.uri_tail (*self*, *key* = `None`)

```
Return the tail (filename portion) of the publication URI for this
roa_obj's ROA.
```

Definition at line 1358 of file rpki_engine.py.

8.172.3 Member Data Documentation

8.172.3.1 rpki.rpki_engine.roa_obj.asn

Definition at line 1198 of file rpki_engine.py.

8.172.3.2 rpki.rpki_engine.roa_obj.ca_detail_id = None `[static]`

Definition at line 1143 of file rpki_engine.py.

8.172.3.3 rpki.rpki_engine.roa_obj.cert = None [static]

Definition at line 1144 of file rpki_engine.py.

8.172.3.4 rpki.rpki_engine.roa_obj.gctx

Reimplemented from rpki.sql.sql_persistent.

Definition at line 1196 of file rpki_engine.py.

8.172.3.5 rpki.rpki_engine.roa_obj.ipv4

Definition at line 1199 of file rpki_engine.py.

8.172.3.6 rpki.rpki_engine.roa_obj.ipv6

Definition at line 1200 of file rpki_engine.py.

8.172.3.7 rpki.rpki_engine.roa_obj.published = None [static]

Definition at line 1146 of file rpki_engine.py.

8.172.3.8 rpki.rpki_engine.roa_obj.roa = None [static]

Definition at line 1145 of file rpki_engine.py.

8.172.3.9 rpki.rpki_engine.roa_obj.self_id

Definition at line 1197 of file rpki_engine.py.

8.172.3.10 tuple rpki.rpki_engine.roa_obj.sql_template [static]

Initial value:

```
rpki.sql.template(
    "roa",
    "roa_id",
    "ca_detail_id",
    "self_id",
    "asn",
    ("roa", rpki.x509.ROA),
    ("cert", rpki.x509.X509),
    ("published", rpki.sundial.datetime))
```

Definition at line 1133 of file rpki_engine.py.

The documentation for this class was generated from the following file:

- rpki_engine.py (3107)

8.173 rpki.rpki_engine.rpkid_context Class Reference

Inherits object.

Collaboration diagram for rpki.rpki_engine.rpkid_context:

Public Member Functions

- def __init__
- def build_https_ta_cache
- def checkpoint
- def clear_https_ta_cache
- def cron

- def cronjob_handler
- def irdb_query
- def irdb_query_child_resources
- def irdb_query_roa_requests
- def left_right_handler
- def start_cron
- def up_down_handler

Public Attributes

- bpki_ta
- cron_keepalive
- cron_period
- cron_timeout
- cron_timer
- https_server_host
- https_server_port
- initial_delay
- irbe_cert
- irdb_cert
- irdb_url
- publication_kludge_base
- rpkid_cert
- rpkid_key
- sql
- use_internal_cron

Static Public Attributes

- https_ta_cache = None

  HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.

- tuple up_down_url_regexp = re.compile("/up-down/([-A-Z0-9_]+)/([-A-Z0-9_-]+)$", re.I)

8.173.1 Detailed Description

```
A container for various global rpkid parameters.
```

Definition at line 39 of file rpki_engine.py.

8.173.2 Member Function Documentation

8.173.2.1 def rpki.rpki_engine.rpkid_context.__init__ (*self*, *cfg*)

Definition at line 44 of file rpki_engine.py.

8.173.2.2 def rpki.rpki_engine.rpkid_context.build_https_ta_cache (*self*)

```
Build dynamic TLS trust anchors.
```

Definition at line 288 of file rpki_engine.py.

8.173.2.3 def rpki.rpki_engine.rpkid_context.checkpoint (*self*)

```
Record that we were still alive when we got here, by resetting
keepalive timer.
```

Definition at line 200 of file rpki_engine.py.

8.173.2.4 def rpki.rpki_engine.rpkid_context.clear_https_ta_cache (*self*)

```
Clear dynamic TLS trust anchors.
```

Definition at line 279 of file rpki_engine.py.

8.173.2.5 def rpki.rpki_engine.rpkid_context.cron (*self*, *cb* = `None`)

```
Periodic tasks.
```

Definition at line 207 of file rpki_engine.py.

8.173.2.6 def rpki.rpki_engine.rpkid_context.cronjob_handler (*self*, *query*, *path*, *cb*)

```
External trigger for periodic tasks.  This is somewhat obsolete
now that we have internal timers, but the test framework still
uses it.
```

Definition at line 263 of file rpki_engine.py.

8.173.2.7 def rpki.rpki_engine.rpkid_context.irdb_query (*self*, *q_pdu*, *callback*, *errback*)

```
Perform an IRDB callback query.
```

Definition at line 86 of file rpki_engine.py.

8.173.2.8 def rpki.rpki_engine.rpkid_context.irdb_query_child_resources (*self*, *self_handle*, *child_handle*, *callback*, *errback*)

```
Ask IRDB about a child's resources.
```

Definition at line 112 of file rpki_engine.py.

8.173.2.9 def rpki.rpki_engine.rpkid_context.irdb_query_roa_requests (*self*, *self_handle*, *callback*, *errback*)

```
Ask IRDB about self's ROA requests.
```

Definition at line 134 of file rpki_engine.py.

8.173.2.10 def rpki.rpki_engine.rpkid_context.left_right_handler (*self*, *query*, *path*, *cb*)

```
Process one left-right PDU.
```

Definition at line 146 of file rpki_engine.py.

8.173.2.11 def rpki.rpki_engine.rpkid_context.start_cron (*self*)

```
Start clock for rpkid's internal cron process.
```

Definition at line 73 of file rpki_engine.py.

8.173.2.12 def rpki.rpki_engine.rpkid_context.up_down_handler (*self*, *query*, *path*, *cb*)

```
Process one up-down PDU.
```

Definition at line 172 of file rpki_engine.py.

8.173.3 Member Data Documentation

8.173.3.1 rpki.rpki_engine.rpkid_context.bpki_ta

Definition at line 48 of file rpki_engine.py.

8.173.3.2 rpki.rpki_engine.rpkid_context.cron_keepalive

Definition at line 68 of file rpki_engine.py.

8.173.3.3 rpki.rpki_engine.rpkid_context.cron_period

Definition at line 67 of file rpki_engine.py.

8.173.3.4 rpki.rpki_engine.rpkid_context.cron_timeout

Definition at line 71 of file rpki_engine.py.

8.173.3.5 rpki.rpki_engine.rpkid_context.cron_timer

Definition at line 79 of file rpki_engine.py.

8.173.3.6 rpki.rpki_engine.rpkid_context.https_server_host

Definition at line 56 of file rpki_engine.py.

8.173.3.7 rpki.rpki_engine.rpkid_context.https_server_port

Definition at line 57 of file rpki_engine.py.

8.173.3.8 rpki::rpki_engine.rpkid_context::https_ta_cache = None [static]

HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.

Definition at line 277 of file rpki_engine.py.

8.173.3.9 rpki.rpki_engine.rpkid_context.initial_delay

Definition at line 63 of file rpki_engine.py.

8.173.3.10 rpki.rpki_engine.rpkid_context.irbe_cert

Definition at line 50 of file rpki_engine.py.

8.173.3.11 rpki.rpki_engine.rpkid_context.irdb_cert

Definition at line 49 of file rpki_engine.py.

8.173.3.12 rpki.rpki_engine.rpkid_context.irdb_url

Definition at line 54 of file rpki_engine.py.

8.173.3.13 rpki.rpki_engine.rpkid_context.publication_kludge_base

Definition at line 59 of file rpki_engine.py.

8.173.3.14 rpki.rpki_engine.rpkid_context.rpkid_cert

Definition at line 51 of file rpki_engine.py.

8.173.3.15 rpki.rpki_engine.rpkid_context.rpkid_key

Definition at line 52 of file rpki_engine.py.

8.173.3.16 rpki.rpki_engine.rpkid_context.sql

Definition at line 46 of file rpki_engine.py.

8.173.3.17 tuple rpki.rpki_engine.rpkid_context.up_down_url_regexp = re.compile("/up-down/([-A-Z0-9_]+)/([-A-Z0-9_]+)$", re.I) [static]

Definition at line 170 of file rpki_engine.py.

8.173.3.18 rpki.rpki_engine.rpkid_context.use_internal_cron

Definition at line 61 of file rpki_engine.py.

The documentation for this class was generated from the following file:

- rpki_engine.py (3107)

8.174 rpki.sql.session Class Reference

Inherits object.

Collaboration diagram for rpki.sql.session:



Public Member Functions

- def __init__
- def assert_pristine
- def cache_clear
- def close
- def connect
- def execute
- def executemany
- def fetchall
- def lastrowid
- def ping
- def sweep

Public Attributes

- cache
- cur
- database
- db
- dirty
- password
- username

Private Member Functions

- def _wrap_execute

Static Private Attributes

- _exceptions_enabled = False

8.174.1 Detailed Description

```
SQL session layer.
```

Definition at line 50 of file sql.py.

8.174.2 Member Function Documentation

8.174.2.1 def rpki.sql.session.__init__ (*self*, *cfg*)

Definition at line 57 of file sql.py.

8.174.2.2 def rpki.sql.session._wrap_execute (*self*, *func*, *query*, *args*) [private]

Definition at line 88 of file sql.py.

8.174.2.3 def rpki.sql.session.assert_pristine (*self*)

```
Assert that there are no dirty objects in the cache.
```

Definition at line 112 of file sql.py.

8.174.2.4 def rpki.sql.session.cache_clear (*self*)

```
Clear the object cache.
```

Definition at line 108 of file sql.py.

8.174.2.5 def rpki.sql.session.close (*self*)

Definition at line 77 of file sql.py.

8.174.2.6 def rpki.sql.session.connect (*self*)

Definition at line 72 of file sql.py.

8.174.2.7 def rpki.sql.session.execute (*self*, *query*, *args* = `None`)

Definition at line 96 of file sql.py.

8.174.2.8 def rpki.sql.session.executemany (*self*, *query*, *args*)

Definition at line 99 of file sql.py.

8.174.2.9 def rpki.sql.session.fetchall (*self*)

Definition at line 102 of file sql.py.

8.174.2.10 def rpki.sql.session.lastrowid (*self*)

Definition at line 105 of file sql.py.

8.174.2.11 def rpki.sql.session.ping (*self*)

Definition at line 85 of file sql.py.

8.174.2.12 def rpki.sql.session.sweep (*self*)

```
Write any dirty objects out to SQL.
```

Definition at line 116 of file sql.py.

8.174.3 Member Data Documentation

8.174.3.1 rpki.sql.session._exceptions_enabled = False [static, private]

Definition at line 55 of file sql.py.

8.174.3.2 rpki.sql.session.cache

Definition at line 67 of file sql.py.

8.174.3.3 rpki.sql.session.cur

Definition at line 74 of file sql.py.

8.174.3.4 rpki.sql.session.database

Definition at line 64 of file sql.py.

8.174.3.5 rpki.sql.session.db

Definition at line 73 of file sql.py.

8.174.3.6 rpki.sql.session.dirty

Definition at line 68 of file sql.py.

8.174.3.7 rpki.sql.session.password

Definition at line 65 of file sql.py.

8.174.3.8 rpki.sql.session.username

Definition at line 63 of file sql.py.

The documentation for this class was generated from the following file:

- sql.py (2895)

8.175 rpki.sql.sql_persistent Class Reference

Inherits object.

Inherited by rpki.left_right.data_elt, rpki.publication.control_elt, rpki.rpki_engine.ca_-detail_obj, rpki.rpki_engine.ca_obj, rpki.rpki_engine.child_cert_obj, rpki.rpki_-engine.revoked_cert_obj, and rpki.rpki_engine.roa_obj.

Collaboration diagram for rpki.sql.sql_persistent:



Public Member Functions

- def sql_decode
- def sql_delete
- def sql_delete_hook
- def sql_encode
- def sql_fetch

- def sql_fetch_all
- def sql_fetch_hook
- def sql_fetch_where
- def sql_fetch_where1
- def sql_init
- def sql_insert_hook
- def sql_is_dirty
- def sql_mark_clean
- def sql_mark_deleted
- def sql_mark_dirty
- def sql_store
- def sql_update_hook

Public Attributes

- gctx

Static Public Attributes

- sql_debug = False

  Enable logging of SQL actions.

- sql_deleted = False

  Whether our cached copy of this object has been deleted.

- sql_in_db = False

  Whether this object is already in SQL or not.

8.175.1 Detailed Description

```
Mixin for persistent class that needs to be stored in SQL.
```

Definition at line 152 of file sql.py.

8.175.2 Member Function Documentation

8.175.2.1 def rpki.sql.sql_persistent.sql_decode (*self*, *vals*)

```
Initialize an object with values returned by self.sql_fetch().
This is a default version that assumes a one-to-one mapping
between column names in SQL and attribute names in Python.  If you
need something fancier, override this.
```

Reimplemented in rpki.rpki_engine.ca_detail_obj.

Definition at line 322 of file sql.py.

8.175.2.2 def rpki.sql.sql_persistent.sql_delete (*self*)

```
Delete this object from SQL.
```

Definition at line 293 of file sql.py.

8.175.2.3 def rpki.sql.sql_persistent.sql_delete_hook (*self*)

```
Customization hook.
```

Reimplemented in rpki.rpki_engine.roa_obj.

Definition at line 348 of file sql.py.

8.175.2.4 def rpki.sql.sql_persistent.sql_encode (*self*)

```
Convert object attributes into a dict for use with canned SQL
queries.  This is a default version that assumes a one-to-one
mapping between column names in SQL and attribute names in Python.
If you need something fancier, override this.
```

Definition at line 309 of file sql.py.

8.175.2.5 def rpki.sql.sql_persistent.sql_fetch (*cls*, *gctx*, *id*)

```
Fetch one object from SQL, based on its primary key.

Since in this one case we know that the primary index is also the
cache key, we check for a cache hit directly in the hope of
bypassing the SQL lookup entirely.
```

```
This method is usually called via a one-line class-specific
wrapper.  As a convenience, we also accept an id of None, and just
return None in this case.
```

Definition at line 173 of file sql.py.

8.175.2.6 def rpki.sql.sql_persistent.sql_fetch_all (*cls*, *gctx*)

```
Fetch all objects of this type from SQL.
```

Definition at line 211 of file sql.py.

8.175.2.7 def rpki.sql.sql_persistent.sql_fetch_hook (*self*)

```
Customization hook.
```

Reimplemented in rpki.rpki_engine.roa_obj.

Definition at line 335 of file sql.py.

8.175.2.8 def rpki.sql.sql_persistent.sql_fetch_where (*cls*, *gctx*, *where*, *args* = `None`, *also_from* = `None`)

```
Fetch objects of this type matching an arbitrary SQL WHERE expression.
```

Definition at line 216 of file sql.py.

8.175.2.9 def rpki.sql.sql_persistent.sql_fetch_where1 (*cls*, *gctx*, *where*, *args* = `None`, *also_from* = `None`)

```
Fetch one object from SQL, based on an arbitrary SQL WHERE expression.
```

Definition at line 196 of file sql.py.

8.175.2.10 def rpki.sql.sql_persistent.sql_init (*cls*, *gctx*, *row*, *key*)

```
Initialize one Python object from the result of a SQL query.
```

Definition at line 243 of file sql.py.

8.175.2.11 def rpki.sql.sql_persistent.sql_insert_hook (*self*)

```
Customization hook.
```

Reimplemented in rpki.rpki_engine.roa_obj.

Definition at line 339 of file sql.py.

8.175.2.12 def rpki.sql.sql_persistent.sql_is_dirty (*self*)

```
Query whether this object needs to be written back to SQL.
```

Definition at line 263 of file sql.py.

8.175.2.13 def rpki.sql.sql_persistent.sql_mark_clean (*self*)

```
Mark this object as not needing to be written back to SQL.
```

Definition at line 259 of file sql.py.

8.175.2.14 def rpki.sql.sql_persistent.sql_mark_deleted (*self*)

```
Mark this object as needing to be deleted in SQL.
```

Definition at line 267 of file sql.py.

8.175.2.15 def rpki.sql.sql_persistent.sql_mark_dirty (*self*)

```
Mark this object as needing to be written back to SQL.
```

Definition at line 255 of file sql.py.

8.175.2.16 def rpki.sql.sql_persistent.sql_store (*self*)

```
Store this object to SQL.
```

Definition at line 271 of file sql.py.

8.175.2.17 def rpki.sql.sql_persistent.sql_update_hook (*self*)

```
Customization hook.
```

Definition at line 343 of file sql.py.

8.175.3 Member Data Documentation

8.175.3.1 rpki.sql.sql_persistent.gctx

Reimplemented in rpki.rpki_engine.ca_obj, rpki.rpki_engine.ca_detail_obj, rpki.rpki_engine.child_cert_obj, rpki.rpki_engine.revoked_cert_obj, and rpki.rpki_-engine.roa_obj.

Definition at line 248 of file sql.py.

8.175.3.2 rpki::sql.sql_persistent::sql_debug = False [static]

Enable logging of SQL actions.

Definition at line 170 of file sql.py.

8.175.3.3 rpki::sql.sql_persistent::sql_deleted = False [static]

Whether our cached copy of this object has been deleted.

Definition at line 165 of file sql.py.

8.175.3.4 rpki::sql.sql_persistent::sql_in_db = False [static]

Whether this object is already in SQL or not.

Definition at line 160 of file sql.py.

The documentation for this class was generated from the following file:

- sql.py (2895)

8.176 rpki.sql.template Class Reference

Inherits object.

Collaboration diagram for rpki.sql.template:



Public Member Functions

- def __init__

Public Attributes

- columns
- delete
- index
- insert
- map

- select
- table
- update

8.176.1 Detailed Description

```
SQL template generator.
```

Definition at line 128 of file sql.py.

8.176.2 Member Function Documentation

8.176.2.1 def rpki.sql.template.__init__ (*self*, *table_name*, *index_column*, *data_columns*)

```
Build a SQL template.
```

Definition at line 133 of file sql.py.

8.176.3 Member Data Documentation

8.176.3.1 rpki.sql.template.columns

Definition at line 140 of file sql.py.

8.176.3.2 rpki.sql.template.delete

Definition at line 150 of file sql.py.

8.176.3.3 rpki.sql.template.index

Definition at line 139 of file sql.py.

8.176.3.4 rpki.sql.template.insert

Definition at line 143 of file sql.py.

8.176.3.5 rpki.sql.template.map

Definition at line 141 of file sql.py.

8.176.3.6 rpki.sql.template.select

Definition at line 142 of file sql.py.

8.176.3.7 rpki.sql.template.table

Definition at line 138 of file sql.py.

8.176.3.8 rpki.sql.template.update

Definition at line 146 of file sql.py.

The documentation for this class was generated from the following file:

- sql.py (2895)

8.177 rpki.sundial.datetime Class Reference

Inherits pydatetime::datetime.

Collaboration diagram for rpki.sundial.datetime:



Public Member Functions

- def __add__
- def __radd__
- def __rsub__
- def __str__
- def __sub__

- def earlier
- def from_sql
- def fromASN1tuple
- def fromdatetime
- def fromGeneralizedTime
- def fromUTCTime
- def fromXMLtime
- def later
- def to_sql
- def toASN1tuple
- def toGeneralizedTime
- def totimestamp
- def toUTCTime
- def toXMLtime

Static Public Attributes

- tuple PKIX_threshhold = pydatetime.datetime(2050, 1, 1)

  Threshold specified in RFC 3280 for switchover from UTCTime to GeneralizedTime.

8.177.1 Detailed Description

```
RPKI extensions to standard datetime.datetime class.  All work here
is in UTC, so we use naive datetime objects.
```

Definition at line 54 of file sundial.py.

8.177.2 Member Function Documentation

8.177.2.1 def rpki.sundial.datetime.__add__ (*x*, *y*)

Definition at line 163 of file sundial.py.

8.177.2.2 def rpki.sundial.datetime.__radd__ (*x*, *y*)

Definition at line 164 of file sundial.py.

8.177.2.3 def rpki.sundial.datetime.__rsub__ (*x*, *y*)

Definition at line 165 of file sundial.py.

8.177.2.4 def rpki.sundial.datetime.__str__ (*self*)

Definition at line 124 of file sundial.py.

8.177.2.5 def rpki.sundial.datetime.__sub__ (*x*, *y*)

Definition at line 166 of file sundial.py.

8.177.2.6 def rpki.sundial.datetime.earlier (*self*, *other*)

```
Return the earlier of two timestamps.
```

Definition at line 159 of file sundial.py.

8.177.2.7 def rpki.sundial.datetime.from_sql (*cls*, *x*)

```
Convert from SQL storage format.
```

Definition at line 136 of file sundial.py.

8.177.2.8 def rpki.sundial.datetime.fromASN1tuple (*cls*, *x*)

```
Convert from ASN.1 tuple representation.
```

Definition at line 86 of file sundial.py.

8.177.2.9 def rpki.sundial.datetime.fromdatetime (*cls*, *x*)

```
Convert a datetime.datetime object into this subclass.  This is
whacky due to the weird constructors for datetime.
```

Definition at line 128 of file sundial.py.

8.177.2.10 def rpki.sundial.datetime.fromGeneralizedTime (*cls*, *x*)

```
Convert from ASN.1 GeneralizedTime.
```

Definition at line 77 of file sundial.py.

8.177.2.11 def rpki.sundial.datetime.fromUTCTime (*cls*, *x*)

```
Convert from ASN.1 UTCTime.
```

Definition at line 68 of file sundial.py.

8.177.2.12 def rpki.sundial.datetime.fromXMLtime (*cls*, *x*)

```
Convert from XML time representation.
```

Definition at line 111 of file sundial.py.

8.177.2.13 def rpki.sundial.datetime.later (*self*, *other*)

```
Return the later of two timestamps.
```

Definition at line 155 of file sundial.py.

8.177.2.14 def rpki.sundial.datetime.to_sql (*self*)

```
Convert to SQL storage format.

There's something whacky going on in the MySQLdb module, it throws
range errors when storing a derived type into a DATETIME column.
Investigate some day, but for now brute force this by copying the
relevant fields into a datetime.datetime for MySQLdb's
consumption.
```

Definition at line 140 of file sundial.py.

8.177.2.15 def rpki.sundial.datetime.toASN1tuple (*self*)

```
Convert to ASN.1 tuple representation.
```

Definition at line 101 of file sundial.py.

8.177.2.16 def rpki.sundial.datetime.toGeneralizedTime (*self*)

```
Convert to ASN.1 GeneralizedTime.
```

Definition at line 81 of file sundial.py.

8.177.2.17 def rpki.sundial.datetime.totimestamp (*self*)

```
Convert to seconds from epoch (like time.time()).  Conversion
method is a bit silly, but avoids time module timezone whackiness.
```

Definition at line 60 of file sundial.py.

8.177.2.18 def rpki.sundial.datetime.toUTCTime (*self*)

```
Convert to ASN.1 UTCTime.
```

Definition at line 72 of file sundial.py.

8.177.2.19 def rpki.sundial.datetime.toXMLtime (*self*)

```
Convert to XML time representation.
```

Definition at line 120 of file sundial.py.

8.177.3 Member Data Documentation

8.177.3.1 rpki::sundial.datetime::PKIX_threshhold = pydatetime.datetime(2050, 1, 1) [static]

Threshold specified in RFC 3280 for switchover from UTCTime to GeneralizedTime.

Definition at line 99 of file sundial.py.

The documentation for this class was generated from the following file:

- sundial.py (3107)

8.178 rpki.sundial.timedelta Class Reference

Inherits pydatetime::timedelta.

Collaboration diagram for rpki.sundial.timedelta:



Public Member Functions

- def __abs__
- def __add__
- def __div__
- def __floordiv__
- def __mul__

- def __neg__
- def __pos__
- def __radd__
- def __rdiv__
- def __rfloordiv__
- def __rmul__
- def __rsub__
- def __sub__
- def convert_to_seconds
- def fromtimedelta
- def parse

Static Public Attributes

- tuple regexp

  Hideously ugly regular expression to parse the complex text form.

- int years_to_seconds = 31556926

  Conversion factor from years to seconds (value furnished by the "units" program).

8.178.1 Detailed Description

```
Timedelta with text parsing.  This accepts two input formats:

- A simple integer, indicating a number of seconds.

- A string of the form "uY vW wD xH yM zS" where u, v, w, x, y, and z
  are integers and Y, W, D, H, M, and S indicate years, weeks, days,
  hours, minutes, and seconds.  All of the fields are optional, but
  at least one must be specified.  Eg,"3D4H" means "three days plus
  four hours".

There is no "months" format, because the definition of a month is too
fuzzy to be useful (what day is six months from August 30th?)

Similarly, the "years" conversion may produce surprising results, as
"one year" in conventional English does not refer to a fixed interval
but rather a fixed (and in some cases undefined) offset within the
Gregorian calendar (what day is one year from February 29th?)  1Y as
implemented by this code refers to a specific number of seconds.
If you mean 365 days or 52 weeks, say that instead.
```

Definition at line 168 of file sundial.py.

8.178.2 Member Function Documentation

8.178.2.1 def rpki.sundial.timedelta.__abs__ (*x*)

Definition at line 243 of file sundial.py.

8.178.2.2 def rpki.sundial.timedelta.__add__ (*x*, *y*)

Definition at line 244 of file sundial.py.

8.178.2.3 def rpki.sundial.timedelta.__div__ (*x*, *y*)

Definition at line 245 of file sundial.py.

8.178.2.4 def rpki.sundial.timedelta.__floordiv__ (*x*, *y*)

Definition at line 246 of file sundial.py.

8.178.2.5 def rpki.sundial.timedelta.__mul__ (*x*, *y*)

Definition at line 247 of file sundial.py.

8.178.2.6 def rpki.sundial.timedelta.__neg__ (*x*)

Definition at line 248 of file sundial.py.

8.178.2.7 def rpki.sundial.timedelta.__pos__ (*x*)

Definition at line 249 of file sundial.py.

8.178.2.8 def rpki.sundial.timedelta.__radd__ (*x*, *y*)

Definition at line 250 of file sundial.py.

8.178.2.9 def rpki.sundial.timedelta.__rdiv__ (*x*, *y*)

Definition at line 251 of file sundial.py.

8.178.2.10 def rpki.sundial.timedelta.__rfloordiv__ (*x*, *y*)

Definition at line 252 of file sundial.py.

8.178.2.11 def rpki.sundial.timedelta.__rmul__ (*x*, *y*)

Definition at line 253 of file sundial.py.

8.178.2.12 def rpki.sundial.timedelta.__rsub__ (*x*, *y*)

Definition at line 254 of file sundial.py.

8.178.2.13 def rpki.sundial.timedelta.__sub__ (*x*, *y*)

Definition at line 255 of file sundial.py.

8.178.2.14 def rpki.sundial.timedelta.convert_to_seconds (*self*)

```
Convert a timedelta interval to seconds.
```

Definition at line 234 of file sundial.py.

8.178.2.15 def rpki.sundial.timedelta.fromtimedelta (*cls*, *x*)

```
Convert a datetime.timedelta object into this subclass.
```

Definition at line 239 of file sundial.py.

8.178.2.16 def rpki.sundial.timedelta.parse (*cls*, *arg*)

```
Parse text into a timedelta object.
```

Definition at line 213 of file sundial.py.

8.178.3 Member Data Documentation

8.178.3.1 rpki::sundial.timedelta::regexp [static]

Initial value:

```
re.compile("\\s*".join(("^",
                                    "(?:(?P<years>\\d+)Y)?",
                                    "(?:(?P<weeks>\\d+)W)?",
                                    "(?:(?P<days>\\d+)D)?",
                                    "(?:(?P<hours>\\d+)H)?",
                                    "(?:(?P<minutes>\\d+)M)?",
                                    "(?:(?P<seconds>\\d+)S)?",
                                    "$")),
                        re.I)
```

Hideously ugly regular expression to parse the complex text form.

Tags are intended for use with re.MatchObject.groupdict() and map directly to the keywords expected by the timedelta constructor.

Definition at line 196 of file sundial.py.

8.178.3.2 rpki::sundial.timedelta::years_to_seconds = 31556926 [static]

Conversion factor from years to seconds (value furnished by the "units" program).

Definition at line 210 of file sundial.py.

The documentation for this class was generated from the following file:

- sundial.py (3107)

8.179 rpki.up_down.base_elt Class Reference

Inherits object.

Inherited by rpki.up_down.certificate_elt, rpki.up_down.class_elt, rpki.up_down.class_response_syntax, rpki.up_down.error_response_pdu, rpki.up_down.issue_pdu, rpki.up_down.list_pdu, rpki.up_down.message_pdu, and rpki.up_down.revoke_syntax.

Collaboration diagram for rpki.up_down.base_elt:



Public Member Functions

- def check_response
- def endElement
- def make_b64elt
- def make_elt
- def serve_pdu
- def startElement

8.179.1 Detailed Description

```
Generic PDU object.

Virtual class, just provides some default methods.
```

Definition at line 43 of file up_down.py.

8.179.2 Member Function Documentation

8.179.2.1 def rpki.up_down.base_elt.check_response (*self*)

```
Placeholder for response checking.
```

Reimplemented in rpki.up_down.issue_response_pdu, and rpki.up_down.error_response_pdu.

Definition at line 91 of file up_down.py.

8.179.2.2 def rpki.up_down.base_elt.endElement (*self*, *stack*, *name*, *text*)

```
Ignore endElement() if there's no specific handler.

If we don't need to do anything else, just pop the stack.
```

Reimplemented in rpki.up_down.certificate_elt, rpki.up_down.class_elt, rpki.up_down.issue_pdu, and rpki.up_down.error_response_pdu.

Definition at line 59 of file up_down.py.

8.179.2.3 def rpki.up_down.base_elt.make_b64elt (*self*, *elt*, *name*, *value* = `None`)

```
Construct a sub-element with Base64 text content.
```

Definition at line 78 of file up_down.py.

8.179.2.4 def rpki.up_down.base_elt.make_elt (*self*, *name*, *attrs*)

```
Construct a element, copying over a set of attributes.
```

Definition at line 67 of file up_down.py.

8.179.2.5 def rpki.up_down.base_elt.serve_pdu (*self*, *q_msg*, *r_msg*, *child*, *callback*, *errback*)

```
Default PDU handler to catch unexpected types.
```

Reimplemented in rpki.up_down.list_pdu, rpki.up_down.issue_pdu, rpki.up_down.revoke_pdu, rootd.list_pdu, rootd.issue_pdu, and rootd.revoke_pdu.

Definition at line 87 of file up_down.py.

8.179.2.6 def rpki.up_down.base_elt.startElement (*self*, *stack*, *name*, *attrs*)

```
Ignore startElement() if there's no specific handler.

Some elements have no attributes and we only care about their
text content.
```

Reimplemented in rpki.up_down.certificate_elt, rpki.up_down.class_elt, rpki.up_down.class_response_syntax, rpki.up_down.issue_pdu, rpki.up_down.revoke_syntax, and rpki.up_down.message_pdu.

Definition at line 50 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.180 rpki.up_down.certificate_elt Class Reference

Inherits rpki::up_down::base_elt.

Collaboration diagram for rpki.up_down.certificate_elt:



Public Member Functions

- def endElement
- def startElement
- def toXML

Public Attributes

- cert
- cert_url
- req_resource_set_as
- req_resource_set_ipv4
- req_resource_set_ipv6

8.180.1 Detailed Description

```
Up-Down protocol representation of an issued certificate.
```

Definition at line 128 of file up_down.py.

8.180.2 Member Function Documentation

8.180.2.1 def rpki.up_down.certificate_elt.endElement (*self*, *stack*, *name*, *text*)

```
Handle text content of a <certificate/> element.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 143 of file up_down.py.

8.180.2.2 def rpki.up_down.certificate_elt.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle attributes of <certificate/> element.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 133 of file up_down.py.

8.180.2.3 def rpki.up_down.certificate_elt.toXML (*self*)

```
Generate a <certificate/> element.
```

Definition at line 151 of file up_down.py.

8.180.3 Member Data Documentation

8.180.3.1 rpki.up_down.certificate_elt.cert

Definition at line 148 of file up_down.py.

8.180.3.2 rpki.up_down.certificate_elt.cert_url

Definition at line 138 of file up_down.py.

8.180.3.3 rpki.up_down.certificate_elt.req_resource_set_as

Definition at line 139 of file up_down.py.

8.180.3.4 rpki.up_down.certificate_elt.req_resource_set_ipv4

Definition at line 140 of file up_down.py.

8.180.3.5 rpki.up_down.certificate_elt.req_resource_set_ipv6

Definition at line 141 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.181 rpki.up_down.class_elt Class Reference

Inherits rpki::up_down::base_elt.

Collaboration diagram for rpki.up_down.class_elt:



Public Member Functions

- def __init__
- def endElement
- def from_resource_bag
- def startElement
- def to_resource_bag
- def toXML

Public Attributes

- cert_url
- certs
- class_name
- resource_set_as
- resource_set_ipv4
- resource_set_ipv6
- resource_set_notafter
- suggested_sia_head

Static Public Attributes

- issuer = None

8.181.1 Detailed Description

```
Up-Down protocol representation of a resource class.
```

Definition at line 160 of file up_down.py.

8.181.2 Member Function Documentation

8.181.2.1 def rpki.up_down.class_elt.__init__ (*self*)

```
Initialize class_elt.
```

Definition at line 167 of file up_down.py.

8.181.2.2 def rpki.up_down.class_elt.endElement (*self*, *stack*, *name*, *text*)

```
Handle <class/> elements and their children.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 191 of file up_down.py.

8.181.2.3 def rpki.up_down.class_elt.from_resource_bag (*self*, *bag*)

```
Set resources of this class element from a resource_bag.
```

Definition at line 222 of file up_down.py.

8.181.2.4 def rpki.up_down.class_elt.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle <class/> elements and their children.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 172 of file up_down.py.

8.181.2.5 def rpki.up_down.class_elt.to_resource_bag (*self*)

```
Build a resource_bag from from this <class/> element.
```

Definition at line 213 of file up_down.py.

8.181.2.6 def rpki.up_down.class_elt.toXML (*self*)

```
Generate a <class/> element.
```

Definition at line 201 of file up_down.py.

8.181.3 Member Data Documentation

8.181.3.1 rpki.up_down.class_elt.cert_url

Definition at line 184 of file up_down.py.

8.181.3.2 rpki.up_down.class_elt.certs

Definition at line 170 of file up_down.py.

8.181.3.3 rpki.up_down.class_elt.class_name

Definition at line 183 of file up_down.py.

8.181.3.4 rpki.up_down.class_elt.issuer = None [static]

Definition at line 165 of file up_down.py.

8.181.3.5 rpki.up_down.class_elt.resource_set_as

Definition at line 186 of file up_down.py.

8.181.3.6 rpki.up_down.class_elt.resource_set_ipv4

Definition at line 187 of file up_down.py.

8.181.3.7 rpki.up_down.class_elt.resource_set_ipv6

Definition at line 188 of file up_down.py.

8.181.3.8 rpki.up_down.class_elt.resource_set_notafter

Definition at line 189 of file up_down.py.

8.181.3.9 rpki.up_down.class_elt.suggested_sia_head

Definition at line 185 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.182 rpki.up_down.class_response_syntax Class Reference

Inherits rpki::up_down::base_elt.

Inherited by rpki.up_down.issue_response_pdu, and rpki.up_down.list_response_pdu.

Collaboration diagram for rpki.up_down.class_response_syntax:



Public Member Functions

- def __init__
- def startElement
- def toXML

Public Attributes

- classes

8.182.1 Detailed Description

```
Syntax for Up-Down protocol "list_response" and "issue_response" PDUs.
```

Definition at line 284 of file up_down.py.

8.182.2 Member Function Documentation

8.182.2.1 def rpki.up_down.class_response_syntax.__init__ (*self*)

```
Initialize class_response_syntax.
```

Definition at line 289 of file up_down.py.

8.182.2.2 def rpki.up_down.class_response_syntax.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle "list_response" and "issue_response" PDUs.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 296 of file up_down.py.

8.182.2.3 def rpki.up_down.class_response_syntax.toXML (*self*)

```
Generate payload of "list_response" and "issue_response" PDUs.
```

Definition at line 306 of file up_down.py.

8.182.3 Member Data Documentation

8.182.3.1 rpki.up_down.class_response_syntax.classes

Definition at line 294 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.183 rpki.up_down.cms_msg Class Reference

Inherits rpki::x509::XML_CMS_object.

Inherited by rootd.cms_msg.

Collaboration diagram for rpki.up_down.cms_msg:



Static Public Attributes

- string encoding = "UTF-8"
- saxify = sax_handler.saxify
- schema = rpki.relaxng.up_down

8.183.1 Detailed Description

```
Class to hold a CMS-signed up-down PDU.
```

Definition at line 682 of file up_down.py.

8.183.2 Member Data Documentation

8.183.2.1 string rpki.up_down.cms_msg.encoding = "UTF-8" [static]

Definition at line 687 of file up_down.py.

8.183.2.2 rpki.up_down.cms_msg.saxify = sax_handler.saxify [static]

Reimplemented in rootd.cms_msg.

Definition at line 689 of file up_down.py.

8.183.2.3 rpki.up_down.cms_msg.schema = rpki.relaxng.up_down [static]

Definition at line 688 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.184 rpki.up_down.error_response_pdu Class Reference

Inherits rpki::up_down::base_elt.

Collaboration diagram for rpki.up_down.error_response_pdu:



Public Member Functions

- def __init__
- def check_response
- def endElement
- def toXML

Public Attributes

- description
- status

Static Public Attributes

- dictionary codes
- dictionary exceptions

8.184.1 Detailed Description

```
Up-Down protocol "error_response" PDU.
```

Definition at line 502 of file up_down.py.

8.184.2 Member Function Documentation

8.184.2.1 def rpki.up_down.error_response_pdu.__init__ (*self*, *exception* = `None`)

```
Initialize an error_response PDU from an exception object.
```

Definition at line 521 of file up_down.py.

8.184.2.2 def rpki.up_down.error_response_pdu.check_response (*self*)

```
Handle an error response.  For now, just raise an exception,
perhaps figure out something more clever to do later.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 561 of file up_down.py.

8.184.2.3 def rpki.up_down.error_response_pdu.endElement (*self*, *stack*, *name*, *text*)

```
Handle "error_response" PDU.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 530 of file up_down.py.

8.184.2.4 def rpki.up_down.error_response_pdu.toXML (*self*)

```
Generate payload of "error_response" PDU.
```

Definition at line 546 of file up_down.py.

8.184.3 Member Data Documentation

8.184.3.1 dictionary rpki.up_down.error_response_pdu.codes [static]

Initial value:

```
{
    1101 : "Already processing request",
    1102 : "Version number error",
    1103 : "Unrecognised request type",
    1201 : "Request - no such resource class",
    1202 : "Request - no resources allocated in resource class",
    1203 : "Request - badly formed certificate request",
    1301 : "Revoke - no such resource class",
    1302 : "Revoke - no such key",
    2001 : "Internal Server Error - Request not performed" }
```

Definition at line 507 of file up_down.py.

8.184.3.2 rpki.up_down.error_response_pdu.description

Definition at line 528 of file up_down.py.

8.184.3.3 dictionary rpki.up_down.error_response_pdu.exceptions [static]

Initial value:

```
{
    rpki.exceptions.NoActiveCA : 1202 }
```

Definition at line 518 of file up_down.py.

8.184.3.4 rpki.up_down.error_response_pdu.status

Definition at line 527 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.185 rpki.up_down.issue_pdu Class Reference

Inherits rpki::up_down::base_elt.

Inherited by rootd.issue_pdu.

Collaboration diagram for rpki.up_down.issue_pdu:



Public Member Functions

- def endElement
- def query
- def serve_pdu
- def startElement
- def toXML

Public Attributes

- class_name
- pkcs10
- req_resource_set_as
- req_resource_set_ipv4
- req_resource_set_ipv6

8.185.1 Detailed Description

```
Up-Down protocol "issue" PDU.
```

Definition at line 316 of file up_down.py.

8.185.2 Member Function Documentation

8.185.2.1 def rpki.up_down.issue_pdu.endElement (*self*, *stack*, *name*, *text*)

```
Handle "issue" PDU.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 331 of file up_down.py.

8.185.2.2 def rpki.up_down.issue_pdu.query (*cls*, *parent*, *ca*, *ca_detail*, *callback*, *errback*)

```
Send an "issue" request to parent associated with ca.
```

Definition at line 417 of file up_down.py.

8.185.2.3 def rpki.up_down.issue_pdu.serve_pdu (*self*, *q_msg*, *r_msg*, *child*, *callback*, *errback*)

```
Serve one issue request PDU.
```

Reimplemented from rpki.up_down.base_elt.

Reimplemented in rootd.issue_pdu.

Definition at line 348 of file up_down.py.

8.185.2.4 def rpki.up_down.issue_pdu.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle "issue" PDU.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 321 of file up_down.py.

8.185.2.5 def rpki.up_down.issue_pdu.toXML (*self*)

```
Generate payload of "issue" PDU.
```

Definition at line 339 of file up_down.py.

8.185.3 Member Data Documentation

8.185.3.1 rpki.up_down.issue_pdu.class_name

Definition at line 326 of file up_down.py.

8.185.3.2 rpki.up_down.issue_pdu.pkcs10

Definition at line 336 of file up_down.py.

8.185.3.3 rpki.up_down.issue_pdu.req_resource_set_as

Definition at line 327 of file up_down.py.

8.185.3.4 rpki.up_down.issue_pdu.req_resource_set_ipv4

Definition at line 328 of file up_down.py.

8.185.3.5 rpki.up_down.issue_pdu.req_resource_set_ipv6

Definition at line 329 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.186 rpki.up_down.issue_response_pdu Class Reference

Inherits rpki::up_down::class_response_syntax.

Collaboration diagram for rpki.up_down.issue_response_pdu:



Public Member Functions

- def check_response

8.186.1 Detailed Description

```
Up-Down protocol "issue_response" PDU.
```

Definition at line 429 of file up_down.py.

8.186.2 Member Function Documentation

8.186.2.1 def rpki.up_down.issue_response_pdu.check_response (*self*)

```
Check whether this looks like a reasonable issue_response PDU.
XML schema should be tighter for this response.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 434 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.187 rpki.up_down.list_pdu Class Reference

Inherits rpki::up_down::base_elt.

Inherited by rootd.list_pdu.

Collaboration diagram for rpki.up_down.list_pdu:



Public Member Functions

- def query

- def serve_pdu
- def toXML

8.187.1 Detailed Description

```
Up-Down protocol "list" PDU.
```

Definition at line 231 of file up_down.py.

8.187.2 Member Function Documentation

8.187.2.1 def rpki.up_down.list_pdu.query (*cls*, *parent*, *cb*, *eb*)

```
Send a "list" query to parent.
```

Definition at line 273 of file up_down.py.

8.187.2.2 def rpki.up_down.list_pdu.serve_pdu (*self*, *q_msg*, *r_msg*, *child*, *callback*, *errback*)

```
Serve one "list" PDU.
```

Reimplemented from rpki.up_down.base_elt.

Reimplemented in rootd.list_pdu.

Definition at line 240 of file up_down.py.

8.187.2.3 def rpki.up_down.list_pdu.toXML (*self*)

```
Generate (empty) payload of "list" PDU.
```

Definition at line 236 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.188 rpki.up_down.list_response_pdu Class Reference

Inherits rpki::up_down::class_response_syntax.

Collaboration diagram for rpki.up_down.list_response_pdu:



8.188.1 Detailed Description

```
Up-Down protocol "list_response" PDU.
```

Definition at line 310 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.189 rpki.up_down.message_pdu Class Reference

Inherits rpki::up_down::base_elt.

Inherited by rootd.message_pdu.

Collaboration diagram for rpki.up_down.message_pdu:



Public Member Functions

- def __str__
- def log_query
- def make_query
- def serve_error
- def serve_top_level

- def startElement
- def toXML

Public Attributes

- payload
- recipient
- sender
- type
- version

Static Public Attributes

- dictionary name2type
- tuple type2name = dict((v, k) for k, v in name2type.items())
- int version = 1

8.189.1 Detailed Description

```
Up-Down protocol message wrapper PDU.
```

Definition at line 568 of file up_down.py.

8.189.2 Member Function Documentation

8.189.2.1 def rpki.up_down.message_pdu.__str__ (*self*)

```
Convert a message PDU to a string.
```

Definition at line 610 of file up_down.py.

8.189.2.2 def rpki.up_down.message_pdu.log_query (*self*, *child*)

```
Log query we're handling.  Separate method so rootd can override.
```

Reimplemented in rootd.message_pdu.

Definition at line 639 of file up_down.py.

8.189.2.3 def rpki.up_down.message_pdu.make_query (*cls*, *payload*, *sender*, *recipient*)

```
Construct one message PDU.
```

Definition at line 657 of file up_down.py.

8.189.2.4 def rpki.up_down.message_pdu.serve_error (*self*, *exception*)

```
Generate an error_response message PDU.
```

Definition at line 645 of file up_down.py.

8.189.2.5 def rpki.up_down.message_pdu.serve_top_level (*self*, *child*, *callback*)

```
Serve one message request PDU.
```

Definition at line 614 of file up_down.py.

8.189.2.6 def rpki.up_down.message_pdu.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle message PDU.

Payload of the <message/> element varies depending on the "type"
attribute, so after some basic checks we have to instantiate the
right class object to handle whatever kind of PDU this is.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 594 of file up_down.py.

8.189.2.7 def rpki.up_down.message_pdu.toXML (*self*)

```
Generate payload of message PDU.
```

Definition at line 586 of file up_down.py.

8.189.3 Member Data Documentation

8.189.3.1 dictionary rpki.up_down.message_pdu.name2type [static]

Initial value:

```
{
    "list"            : list_pdu,
    "list_response"   : list_response_pdu,
    "issue"           : issue_pdu,
    "issue_response"  : issue_response_pdu,
    "revoke"          : revoke_pdu,
    "revoke_response" : revoke_response_pdu,
    "error_response"  : error_response_pdu }
```

Reimplemented in rootd.message_pdu.

Definition at line 575 of file up_down.py.

8.189.3.2 rpki.up_down.message_pdu.payload

Definition at line 607 of file up_down.py.

8.189.3.3 rpki.up_down.message_pdu.recipient

Definition at line 605 of file up_down.py.

8.189.3.4 rpki.up_down.message_pdu.sender

Definition at line 604 of file up_down.py.

8.189.3.5 rpki.up_down.message_pdu.type

Definition at line 606 of file up_down.py.

8.189.3.6 tuple rpki.up_down.message_pdu.type2name = dict((v, k) for k, v in name2type.items()) [static]

Reimplemented in rootd.message_pdu.

Definition at line 584 of file up_down.py.

8.189.3.7 rpki.up_down.message_pdu.version

Definition at line 603 of file up_down.py.

8.189.3.8 int rpki.up_down.message_pdu.version = 1 `[static]`

Definition at line 573 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.190 rpki.up_down.multi_uri Class Reference

Inherits list.

Collaboration diagram for rpki.up_down.multi_uri:



Public Member Functions

- def __init__
- def __str__
- def rsync

8.190.1 Detailed Description

```
Container for a set of URIs.
```

Definition at line 95 of file up_down.py.

8.190.2 Member Function Documentation

8.190.2.1 def rpki.up_down.multi_uri.__init__ (*self*, *ini*)

```
Initialize a set of URIs, which includes basic some syntax checking.
```

Definition at line 100 of file up_down.py.

8.190.2.2 def rpki.up_down.multi_uri.__str__ (*self*)

```
Convert a multi_uri back to a string representation.
```

Definition at line 115 of file up_down.py.

8.190.2.3 def rpki.up_down.multi_uri.rsync (*self*)

```
Find first rsync://... URI in self.
```

Definition at line 119 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.191 rpki.up_down.revoke_pdu Class Reference

Inherits rpki::up_down::revoke_syntax.

Inherited by rootd.revoke_pdu.

Collaboration diagram for rpki.up_down.revoke_pdu:



Public Member Functions

- def get_SKI
- def query
- def serve_pdu

Public Attributes

- class_name
- ski

8.191.1 Detailed Description

```
Up-Down protocol "revoke" PDU.
```

Definition at line 456 of file up_down.py.

8.191.2 Member Function Documentation

8.191.2.1 def rpki.up_down.revoke_pdu.get_SKI (*self*)

```
Convert g(SKI) encoding from PDU back to raw SKI.
```

Definition at line 461 of file up_down.py.

8.191.2.2 def rpki.up_down.revoke_pdu.query (*cls*, *ca*, *gski*, *cb*, *eb*)

```
Send a "revoke" request for certificate(s) named by gski to parent associated with ca.
```

Definition at line 485 of file up_down.py.

8.191.2.3 def rpki.up_down.revoke_pdu.serve_pdu (*self*, *q_msg*, *r_msg*, *child*, *cb*, *eb*)

```
Serve one revoke request PDU.
```

Reimplemented from rpki.up_down.base_elt.

Reimplemented in rootd.revoke_pdu.

Definition at line 465 of file up_down.py.

8.191.3 Member Data Documentation

8.191.3.1 rpki.up_down.revoke_pdu.class_name

Reimplemented from rpki.up_down.revoke_syntax.

Definition at line 491 of file up_down.py.

8.191.3.2 rpki.up_down.revoke_pdu.ski

Reimplemented from rpki.up_down.revoke_syntax.

Definition at line 492 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.192 rpki.up_down.revoke_response_pdu Class Reference

Inherits rpki::up_down::revoke_syntax.

Collaboration diagram for rpki.up_down.revoke_response_pdu:



8.192.1 Detailed Description

```
Up-Down protocol "revoke_response" PDU.
```

Definition at line 495 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.193 rpki.up_down.revoke_syntax Class Reference

Inherits rpki::up_down::base_elt.

Inherited by rpki.up_down.revoke_pdu, and rpki.up_down.revoke_response_pdu.

Collaboration diagram for rpki.up_down.revoke_syntax:



Public Member Functions

- def startElement
- def toXML

Public Attributes

- class_name
- ski

8.193.1 Detailed Description

```
Syntax for Up-Down protocol "revoke" and "revoke_response" PDUs.
```

Definition at line 442 of file up_down.py.

8.193.2 Member Function Documentation

8.193.2.1 def rpki.up_down.revoke_syntax.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle "revoke" PDU.
```

Reimplemented from rpki.up_down.base_elt.

Definition at line 447 of file up_down.py.

8.193.2.2 def rpki.up_down.revoke_syntax.toXML (*self*)

```
Generate payload of "revoke" PDU.
```

Definition at line 452 of file up_down.py.

8.193.3 Member Data Documentation

8.193.3.1 rpki.up_down.revoke_syntax.class_name

Reimplemented in rpki.up_down.revoke_pdu.

Definition at line 449 of file up_down.py.

8.193.3.2 rpki.up_down.revoke_syntax.ski

Reimplemented in rpki.up_down.revoke_pdu.

Definition at line 450 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.194 rpki.up_down.sax_handler Class Reference

Inherits rpki::xml_utils::sax_handler.

Inherited by rootd.sax_handler.

Collaboration diagram for rpki.up_down.sax_handler:



Static Public Attributes

- string name = "message"
- pdu = message_pdu
- string version = "1"

8.194.1 Detailed Description

```
SAX handler for Up-Down protocol.
```

Definition at line 673 of file up_down.py.

8.194.2 Member Data Documentation

8.194.2.1 string rpki.up_down.sax_handler.name = "message" [static]

Definition at line 679 of file up_down.py.

8.194.2.2 rpki.up_down.sax_handler.pdu = message_pdu [static]

Reimplemented in rootd.sax_handler.

Definition at line 678 of file up_down.py.

8.194.2.3 string rpki.up_down.sax_handler.version = "1" [static]

Definition at line 680 of file up_down.py.

The documentation for this class was generated from the following file:

- up_down.py (3144)

8.195 rpki.x509.CMS_object Class Reference

Inherits rpki::x509::DER_object.

Inherited by rpki.x509.DER_CMS_object, and rpki.x509.XML_CMS_object.

Collaboration diagram for rpki.x509.CMS_object:

Public Member Functions

- def extract
- def get_content
- def get_DER
- def get_POW
- def set_content

- def sign
- def verify

Public Attributes

- content
- DER

  DER value of this object.

- POW

Static Public Attributes

- debug_cms_certs = False

  Set this to True to log a lot of chatter about CMS certificates.

- dump_on_verify_failure = True

  Set this to True to get dumpasn1 dumps of ASN.1 on CMS verify failures.

- tuple econtent_oid = POWify_OID("id-data")
- tuple formats = ("DER", "POW")

  Formats supported in this object.

- tuple other_clear = ("content",)

  Other attributes that self.clear() should whack.

- tuple pem_converter = PEM_converter("CMS")

  PEM converter for this object.

- print_on_der_error = True

  Set this to True to log alleged DER when we have trouble parsing it, in case it's really a Perl backtrace or something.

- require_crls = False

  Set this to False to make CMS CRLs optional in the cases where we would otherwise require them.

8.195.1 Detailed Description

```
Class to hold a CMS-wrapped object.

CMS-wrapped objects are a little different from the other DER_object
types because the signed object is CMS wrapping inner content that's
also ASN.1, and due to our current minimal support for CMS we can't
just handle this as a pretty composite object.  So, for now anyway,
a CMS_object is the outer CMS wrapped object so that the usual DER
and PEM operations do the obvious things, and the inner content is
handle via separate methods.
```

Definition at line 735 of file x509.py.

8.195.2 Member Function Documentation

8.195.2.1 def rpki.x509.CMS_object.extract (*self*)

```
Extract and store inner content from CMS wrapper without verifying
the CMS.

DANGER WILL ROBINSON!!!

Do not use this method on unvalidated data.  Use the verify()
method instead.

If you don't understand this warning, don't use this method.
```

Definition at line 886 of file x509.py.

8.195.2.2 def rpki.x509.CMS_object.get_content (*self*)

```
Get the inner content of this CMS_object.
```

Definition at line 797 of file x509.py.

8.195.2.3 def rpki.x509.CMS_object.get_DER (*self*)

```
Get the DER value of this CMS_object.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 776 of file x509.py.

8.195.2.4 def rpki.x509.CMS_object.get_POW (*self*)

```
Get the POW value of this CMS_object.
```

Definition at line 788 of file x509.py.

8.195.2.5 def rpki.x509.CMS_object.set_content (*self*, *content*)

```
Set the (inner) content of this CMS_object, clearing the wrapper.
```

Definition at line 805 of file x509.py.

8.195.2.6 def rpki.x509.CMS_object.sign (*self*, *keypair*, *certs*, *crls* = `None`, *no_certs* = `False`)

```
Sign and wrap inner content.
```

Definition at line 914 of file x509.py.

8.195.2.7 def rpki.x509.CMS_object.verify (*self*, *ta*)

```
Verify CMS wrapper and store inner content.
```

Definition at line 812 of file x509.py.

8.195.3 Member Data Documentation

8.195.3.1 rpki.x509.CMS_object.content

Reimplemented in rpki.x509.DER_CMS_object, and rpki.x509.XML_CMS_object.

Definition at line 810 of file x509.py.

8.195.3.2 rpki::x509.CMS_object::debug_cms_certs = False [static]

Set this to True to log a lot of chatter about CMS certificates.

Definition at line 761 of file x509.py.

8.195.3.3 rpki.x509.CMS_object.DER

DER value of this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 784 of file x509.py.

8.195.3.4 rpki::x509.CMS_object::dump_on_verify_failure = True [static]

Set this to True to get dumpasn1 dumps of ASN.1 on CMS verify failures.

Definition at line 756 of file x509.py.

8.195.3.5 tuple rpki.x509.CMS_object.econtent_oid = POWify_OID("id-data") [static]

Reimplemented in rpki.x509.SignedManifest, rpki.x509.ROA, and rpki.x509.XML_-CMS_object.

Definition at line 750 of file x509.py.

8.195.3.6 tuple rpki.x509.CMS_object.formats = ("DER", "POW") [static]

Formats supported in this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 748 of file x509.py.

8.195.3.7 tuple rpki.x509.CMS_object.other_clear = ("content",) [static]

Other attributes that self.clear() should whack.

Reimplemented from rpki.x509.DER_object.

Definition at line 749 of file x509.py.

8.195.3.8 tuple rpki.x509.CMS_object.pem_converter = PEM_converter("CMS") [static]

PEM converter for this object.

Reimplemented from rpki.x509.DER_object.

Reimplemented in rpki.x509.SignedManifest, and rpki.x509.ROA.

Definition at line 751 of file x509.py.

8.195.3.9 rpki.x509.CMS_object.POW

Definition at line 794 of file x509.py.

8.195.3.10 rpki::x509.CMS_object::print_on_der_error = True [static]

Set this to True to log alleged DER when we have trouble parsing it, in case it's really a Perl backtrace or something.

Definition at line 774 of file x509.py.

8.195.3.11 rpki::x509.CMS_object::require_crls = False [static]

Set this to False to make CMS CRLs optional in the cases where we would otherwise require them.

Some day this option should go away and CRLs should be uncondtionally mandatory in such cases.

Definition at line 768 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.196 rpki.x509.CRL Class Reference

Inherits rpki::x509::DER_object.

Collaboration diagram for rpki.x509.CRL:



Public Member Functions

- def generate
- def get_DER
- def get_POW
- def get_POWpkix
- def getIssuer
- def getNextUpdate
- def getThisUpdate

Public Attributes

- DER

  DER value of this object.

- POW
- POWpkix

Static Public Attributes

- tuple formats = ("DER", "POW", "POWpkix")

  Formats supported in this object.

- tuple pem_converter = PEM_converter("X509 CRL")

  PEM converter for this object.

8.196.1 Detailed Description

```
Class to hold a Certificate Revocation List.
```

Definition at line 1140 of file x509.py.

8.196.2 Member Function Documentation

8.196.2.1 def rpki.x509.CRL.generate (*cls*, *keypair*, *issuer*, *serial*, *thisUpdate*, *nextUpdate*, *revokedCertificates*, *version* = `1`, *digestType* = `"sha256WithRSAEncryption"`)

```
Generate a new CRL.
```

Definition at line 1196 of file x509.py.

8.196.2.2 def rpki.x509.CRL.get_DER (*self*)

```
Get the DER value of this CRL.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 1148 of file x509.py.

8.196.2.3 def rpki.x509.CRL.get_POW (*self*)

```
Get the POW value of this CRL.
```

Definition at line 1163 of file x509.py.

8.196.2.4 def rpki.x509.CRL.get_POWpkix (*self*)

```
Get the POW.pkix value of this CRL.
```

Definition at line 1172 of file x509.py.

8.196.2.5 def rpki.x509.CRL.getIssuer (*self*)

```
Get issuer value of this CRL.
```

Definition at line 1191 of file x509.py.

8.196.2.6 def rpki.x509.CRL.getNextUpdate (*self*)

```
Get nextUpdate value from this CRL.
```

Definition at line 1187 of file x509.py.

8.196.2.7 def rpki.x509.CRL.getThisUpdate (*self*)

```
Get thisUpdate value from this CRL.
```

Definition at line 1183 of file x509.py.

8.196.3 Member Data Documentation

8.196.3.1 rpki.x509.CRL.DER

DER value of this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 1156 of file x509.py.

8.196.3.2 tuple rpki.x509.CRL.formats = ("DER", "POW", "POWpkix") [static]

Formats supported in this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 1145 of file x509.py.

8.196.3.3 tuple rpki.x509.CRL.pem_converter = PEM_converter("X509 CRL") [static]

PEM converter for this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 1146 of file x509.py.

8.196.3.4 rpki.x509.CRL.POW

Definition at line 1169 of file x509.py.

8.196.3.5 rpki.x509.CRL.POWpkix

Definition at line 1180 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.197 rpki.x509.DeadDrop Class Reference

Inherits object.

Collaboration diagram for rpki.x509.DeadDrop:



Public Member Functions

- def __init__
- def dump

Public Attributes

- maildir
- pid

8.197.1 Detailed Description

```
Dead-drop utility for storing copies of CMS messages for debugging or
audit.  At the moment this uses Maildir mailbox format, as it has
approximately the right properties and a number of useful tools for
manipulating it already exist.
```

Definition at line 1035 of file x509.py.

8.197.2 Member Function Documentation

8.197.2.1 def rpki.x509.DeadDrop.__init__ (*self*, *name*)

Definition at line 1043 of file x509.py.

8.197.2.2 def rpki.x509.DeadDrop.dump (*self*, *obj*)

Definition at line 1047 of file x509.py.

8.197.3 Member Data Documentation

8.197.3.1 rpki.x509.DeadDrop.maildir

Definition at line 1044 of file x509.py.

8.197.3.2 rpki.x509.DeadDrop.pid

Definition at line 1045 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.198 rpki.x509.DER_CMS_object Class Reference

Inherits rpki::x509::CMS_object.

Inherited by rpki.x509.ROA, and rpki.x509.SignedManifest.

Collaboration diagram for rpki.x509.DER_CMS_object:



Public Member Functions

- def decode

- def encode

Public Attributes

- content

8.198.1 Detailed Description

```
Class to hold CMS objects with DER-based content.
```

Definition at line 950 of file x509.py.

8.198.2 Member Function Documentation

8.198.2.1 def rpki.x509.DER_CMS_object.decode (*self*, *der*)

```
Decode DER and set inner content.
```

Definition at line 959 of file x509.py.

8.198.2.2 def rpki.x509.DER_CMS_object.encode (*self*)

```
Encode inner content for signing.
```

Definition at line 955 of file x509.py.

8.198.3 Member Data Documentation

8.198.3.1 rpki.x509.DER_CMS_object.content

Reimplemented from rpki.x509.CMS_object.

Definition at line 965 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.199 rpki.x509.DER_object Class Reference

Inherits object.

Inherited by rpki.x509.CMS_object, rpki.x509.CRL, rpki.x509.PKCS10, rpki.x509.RSA, rpki.x509.RSApublic, and rpki.x509.X509.

Collaboration diagram for rpki.x509.DER_object:



Public Member Functions

- def __cmp__
- def __init__
- def clear
- def dumpasn1
- def empty
- def from_sql
- def gAKI
- def get_3779resources
- def get_AIA
- def get_aia_uri
- def get_AKI
- def get_Base64
- def get_basicConstraints
- def get_DER
- def get_PEM
- def get_SIA
- def get_sia_directory_uri
- def get_sia_manifest_uri
- def get_SKI
- def gSKI
- def hAKI
- def hSKI
- def is_CA
- def set
- def to_sql

Public Attributes

- DER

  DER value of this object.

Static Public Attributes

- tuple formats = ("DER",)

  Formats supported in this object.

- tuple other_clear = ()

  Other attributes that self.clear() should whack.

- pem_converter = None

  PEM converter for this object.

8.199.1 Detailed Description

```
Virtual class to hold a generic DER object.
```

Definition at line 117 of file x509.py.

8.199.2 Member Function Documentation

8.199.2.1 def rpki.x509.DER_object.__cmp__ (*self*, *other*)

```
Compare two DER-encoded objects.
```

Definition at line 212 of file x509.py.

8.199.2.2 def rpki.x509.DER_object.__init__ (*self*, *kw*)

```
Initialize a DER_object.
```

Definition at line 150 of file x509.py.

8.199.2.3 def rpki.x509.DER_object.clear (*self*)

```
Make this object empty.
```

Definition at line 143 of file x509.py.

8.199.2.4 def rpki.x509.DER_object.dumpasn1 (*self*)

```
Pretty print an ASN.1 DER object using cryptlib dumpasn1 tool.
Use a temporary file rather than popen4() because dumpasn1 uses
seek() when decoding ASN.1 content nested in OCTET STRING values.
```

Definition at line 341 of file x509.py.

8.199.2.5 def rpki.x509.DER_object.empty (*self*)

```
Test whether this object is empty.
```

Definition at line 134 of file x509.py.

8.199.2.6 def rpki.x509.DER_object.from_sql (*cls*, *x*)

```
Convert from SQL storage format.
```

Definition at line 333 of file x509.py.

8.199.2.7 def rpki.x509.DER_object.gAKI (*self*)

```
Calculate g(AKI) for this object.  Only work for subclasses
that implement get_AKI().
```

Definition at line 248 of file x509.py.

8.199.2.8 def rpki.x509.DER_object.get_3779resources (*self*)

```
Get RFC 3779 resources as rpki.resource_set objects.  Only works
for subclasses that support getExtensions().
```

Definition at line 320 of file x509.py.

8.199.2.9 def rpki.x509.DER_object.get_AIA (*self*)

```
Get the SIA extension from this object.  Only works for subclasses
that support getExtension().
```

Definition at line 291 of file x509.py.

8.199.2.10 def rpki.x509.DER_object.get_aia_uri (*self*)

```
Get AIA (id-ad-caIssuers) URI from this object.
Only works for subclasses that support getExtension().
```

Definition at line 298 of file x509.py.

8.199.2.11 def rpki.x509.DER_object.get_AKI (*self*)

```
Get the AKI extension from this object.  Only works for subclasses
that support getExtension().
```

Definition at line 255 of file x509.py.

8.199.2.12 def rpki.x509.DER_object.get_Base64 (*self*)

```
Get the Base64 encoding of the DER value of this object.
```

Definition at line 204 of file x509.py.

8.199.2.13 def rpki.x509.DER_object.get_basicConstraints (*self*)

```
Get the basicConstraints extension from this object.  Only works
for subclasses that support getExtension().
```

Definition at line 305 of file x509.py.

8.199.2.14 def rpki.x509.DER_object.get_DER (*self*)

```
Get the DER value of this object.

Subclasses will almost certainly override this method.
```

Reimplemented in rpki.x509.X509, rpki.x509.PKCS10, rpki.x509.RSA, rpki.x509.RSApublic, rpki.x509.CMS_object, and rpki.x509.CRL.

Definition at line 193 of file x509.py.

8.199.2.15 def rpki.x509.DER_object.get_PEM (*self*)

```
Get the PEM representation of this object.
```

Definition at line 208 of file x509.py.

8.199.2.16 def rpki.x509.DER_object.get_SIA (*self*)

```
Get the SIA extension from this object.  Only works for subclasses
that support getExtension().
```

Definition at line 270 of file x509.py.

8.199.2.17 def rpki.x509.DER_object.get_sia_directory_uri (*self*)

```
Get SIA directory (id-ad-caRepository) URI from this object.
Only works for subclasses that support getExtension().
```

Definition at line 277 of file x509.py.

8.199.2.18 def rpki.x509.DER_object.get_sia_manifest_uri (*self*)

```
Get SIA manifest (id-ad-rpkiManifest) URI from this object.
Only works for subclasses that support getExtension().
```

Definition at line 284 of file x509.py.

8.199.2.19 def rpki.x509.DER_object.get_SKI (*self*)

```
Get the SKI extension from this object.  Only works for subclasses
that support getExtension().
```

Reimplemented in rpki.x509.RSA, and rpki.x509.RSApublic.

Definition at line 263 of file x509.py.

8.199.2.20 def rpki.x509.DER_object.gSKI (*self*)

```
Calculate g(SKI) for this object.  Only work for subclasses
that implement get_SKI().
```

Definition at line 233 of file x509.py.

8.199.2.21 def rpki.x509.DER_object.hAKI (*self*)

```
Return hexadecimal string representation of AKI for this
object.  Only work for subclasses that implement get_AKI().
```

Definition at line 240 of file x509.py.

8.199.2.22 def rpki.x509.DER_object.hSKI (*self*)

```
Return hexadecimal string representation of SKI for this object.
Only work for subclasses that implement get_SKI().
```

Definition at line 225 of file x509.py.

8.199.2.23 def rpki.x509.DER_object.is_CA (*self*)

```
Return True if and only if object has the basicConstraints
extension and its cA value is true.
```

Definition at line 312 of file x509.py.

8.199.2.24 def rpki.x509.DER_object.set (*self*, *kw*)

```
Set this object by setting one of its known formats.

This method only allows one to set one format at a time.
Subsequent calls will clear the object first.  The point of all
this is to let the object's internal converters handle mustering
the object into whatever format you need at the moment.
```

Definition at line 158 of file x509.py.

8.199.2.25 def rpki.x509.DER_object.to_sql (*self*)

```
Convert to SQL storage format.
```

Definition at line 337 of file x509.py.

8.199.3 Member Data Documentation

8.199.3.1 rpki::x509.DER_object::DER

DER value of this object.

Reimplemented in rpki.x509.X509, rpki.x509.PKCS10, rpki.x509.RSA, rpki.x509.RSApublic, rpki.x509.CMS_object, and rpki.x509.CRL.

Definition at line 176 of file x509.py.

8.199.3.2 tuple rpki.x509.DER_object.formats = ("DER",) [static]

Formats supported in this object.

Reimplemented in rpki.x509.X509, rpki.x509.PKCS10, rpki.x509.RSA, rpki.x509.RSApublic, rpki.x509.CMS_object, and rpki.x509.CRL.

Definition at line 123 of file x509.py.

8.199.3.3 tuple rpki.x509.DER_object.other_clear = () [static]

Other attributes that self.clear() should whack.

Reimplemented in rpki.x509.CMS_object.

Definition at line 129 of file x509.py.

8.199.3.4 rpki.x509.DER_object.pem_converter = None [static]

PEM converter for this object.

Reimplemented in rpki.x509.X509, rpki.x509.PKCS10, rpki.x509.RSA, rpki.x509.RSApublic, rpki.x509.CMS_object, rpki.x509.SignedManifest, rpki.x509.ROA, and rpki.x509.CRL.

Definition at line 126 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.200 rpki.x509.PEM_converter Class Reference

Inherits object.

Collaboration diagram for rpki.x509.PEM_converter:



Public Member Functions

- def __init__
- def looks_like_PEM
- def to_DER

- def to_PEM

Public Attributes

- b
- e

8.200.1 Detailed Description

```
Convert between DER and PEM encodings for various kinds of ASN.1 data.
```

Definition at line 62 of file x509.py.

8.200.2 Member Function Documentation

8.200.2.1 def rpki.x509.PEM_converter.__init__ (*self*, *kind*)

```
Initialize PEM_converter.
```

Definition at line 67 of file x509.py.

8.200.2.2 def rpki.x509.PEM_converter.looks_like_PEM (*self*, *text*)

```
Guess whether text looks like a PEM encoding.
```

Definition at line 74 of file x509.py.

8.200.2.3 def rpki.x509.PEM_converter.to_DER (*self*, *pem*)

```
Convert from PEM to DER.
```

Definition at line 81 of file x509.py.

8.200.2.4 def rpki.x509.PEM_converter.to_PEM (*self*, *der*)

```
Convert from DER to PEM.
```

Definition at line 94 of file x509.py.

8.200.3 Member Data Documentation

8.200.3.1 rpki.x509.PEM_converter.b

Definition at line 71 of file x509.py.

8.200.3.2 rpki.x509.PEM_converter.e

Definition at line 72 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.201 rpki.x509.PKCS10 Class Reference

Inherits rpki::x509::DER_object.

Collaboration diagram for rpki.x509.PKCS10:



Public Member Functions

- def check_valid_rpki
- def create
- def create_ca
- def get_DER
- def get_POWpkix
- def getPublicKey

Public Attributes

- DER

  DER value of this object.

- POWpkix

Static Public Attributes

- tuple formats = ("DER", "POWpkix")

  Formats supported in this object.

- tuple pem_converter = PEM_converter("CERTIFICATE REQUEST")

  PEM converter for this object.

8.201.1 Detailed Description

```
Class to hold a PKCS #10 request.
```

Definition at line 534 of file x509.py.

8.201.2 Member Function Documentation

8.201.2.1 def rpki.x509.PKCS10.check_valid_rpki (*self*)

```
Check this certification request to see whether it's a valid
request for an RPKI certificate.  This is broken out of the
up-down protocol code because it's somewhat involved and the
up-down code doesn't need to know the details.

Throws an exception if the request isn't valid, so if this method
returns at all, the request is ok.
```

Definition at line 569 of file x509.py.

8.201.2.2 def rpki.x509.PKCS10.create (*cls*, *keypair*, *exts* = `None`)

```
Create a new request for a given keypair, including given extensions.
```

Definition at line 629 of file x509.py.

8.201.2.3 def rpki.x509.PKCS10.create_ca (*cls*, *keypair*, *sia* = `None`)

```
Create a new request for a given keypair, including given SIA value.
```

Definition at line 616 of file x509.py.

8.201.2.4 def rpki.x509.PKCS10.get_DER (*self*)

```
Get the DER value of this certification request.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 542 of file x509.py.

8.201.2.5 def rpki.x509.PKCS10.get_POWpkix (*self*)

```
Get the POW.pkix value of this certification request.
```

Definition at line 554 of file x509.py.

8.201.2.6 def rpki.x509.PKCS10.getPublicKey (*self*)

```
Extract the public key from this certification request.
```

Definition at line 565 of file x509.py.

8.201.3 Member Data Documentation

8.201.3.1 rpki.x509.PKCS10.DER

DER value of this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 550 of file x509.py.

8.201.3.2 tuple rpki.x509.PKCS10.formats = ("DER", "POWpkix") [static]

Formats supported in this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 539 of file x509.py.

8.201.3.3 tuple rpki.x509.PKCS10.pem_converter = PEM_converter("CERTIFICATE REQUEST") [static]

PEM converter for this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 540 of file x509.py.

8.201.3.4 rpki.x509.PKCS10.POWpkix

Definition at line 562 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.202 rpki.x509.ROA Class Reference

Inherits rpki::x509::DER_CMS_object.

Collaboration diagram for rpki.x509.ROA:



Public Member Functions

- def build

Static Public Attributes

- content_class = rpki.roa.RouteOriginAttestation

- tuple econtent_oid = POWify_OID("id-ct-routeOriginAttestation")
- tuple pem_converter = PEM_converter("ROUTE ORIGIN ATTESTATION")

  PEM converter for this object.

8.202.1 Detailed Description

```
Class to hold a signed ROA.
```

Definition at line 1007 of file x509.py.

8.202.2 Member Function Documentation

8.202.2.1 def rpki.x509.ROA.build (*cls*, *asn*, *ipv4*, *ipv6*, *keypair*, *certs*, *version* = 0)

```
Build a ROA.
```

Definition at line 1017 of file x509.py.

8.202.3 Member Data Documentation

8.202.3.1 rpki.x509.ROA.content_class = rpki.roa.RouteOriginAttestation [static]

Definition at line 1013 of file x509.py.

8.202.3.2 tuple rpki.x509.ROA.econtent_oid = POWify_OID("id-ct-routeOriginAttestation") [static]

Reimplemented from rpki.x509.CMS_object.

Definition at line 1014 of file x509.py.

8.202.3.3 tuple rpki.x509.ROA.pem_converter = PEM_converter("ROUTE ORIGIN ATTESTATION") [static]

PEM converter for this object.

Reimplemented from rpki.x509.CMS_object.

Definition at line 1012 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.203 rpki.x509.RSA Class Reference

Inherits rpki::x509::DER_object.

Collaboration diagram for rpki.x509.RSA:



Public Member Functions

- def generate
- def get_DER
- def get_POW
- def get_public_DER
- def get_RSApublic
- def get_SKI

Public Attributes

- DER

  DER value of this object.

- POW

Static Public Attributes

- tuple formats = ("DER", "POW")

  Formats supported in this object.

- tuple pem_converter = PEM_converter("RSA PRIVATE KEY")

  PEM converter for this object.

8.203.1 Detailed Description

```
Class to hold an RSA key pair.
```

Definition at line 643 of file x509.py.

8.203.2 Member Function Documentation

8.203.2.1 def rpki.x509.RSA.generate (*cls*, *keylength* = 2048)

```
Generate a new keypair.
```

Definition at line 673 of file x509.py.

8.203.2.2 def rpki.x509.RSA.get_DER (*self*)

```
Get the DER value of this keypair.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 651 of file x509.py.

8.203.2.3 def rpki.x509.RSA.get_POW (*self*)

```
Get the POW value of this keypair.
```

Definition at line 663 of file x509.py.

8.203.2.4 def rpki.x509.RSA.get_public_DER (*self*)

```
Get the DER encoding of the public key from this keypair.
```

Definition at line 680 of file x509.py.

8.203.2.5 def rpki.x509.RSA.get_RSApublic (*self*)

```
Convert the public key of this keypair into a RSApublic object.
```

Definition at line 688 of file x509.py.

8.203.2.6 def rpki.x509.RSA.get_SKI (*self*)

```
Calculate the SKI of this keypair.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 684 of file x509.py.

8.203.3 Member Data Documentation

8.203.3.1 rpki.x509.RSA.DER

DER value of this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 659 of file x509.py.

8.203.3.2 tuple rpki.x509.RSA.formats = ("DER", "POW") [static]

Formats supported in this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 648 of file x509.py.

8.203.3.3 tuple rpki.x509.RSA.pem_converter = PEM_converter("RSA PRIVATE KEY") [static]

PEM converter for this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 649 of file x509.py.

8.203.3.4 rpki.x509.RSA.POW

Definition at line 669 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.204 rpki.x509.RSApublic Class Reference

Inherits rpki::x509::DER_object.

Collaboration diagram for rpki.x509.RSApublic:



Public Member Functions

- def get_DER
- def get_POW
- def get_SKI

Public Attributes

- DER

  DER value of this object.

- POW

Static Public Attributes

- tuple formats = ("DER", "POW")

  Formats supported in this object.

- tuple pem_converter = PEM_converter("RSA PUBLIC KEY")

  PEM converter for this object.

8.204.1 Detailed Description

```
Class to hold an RSA public key.
```

Definition at line 692 of file x509.py.

8.204.2 Member Function Documentation

8.204.2.1 def rpki.x509.RSApublic.get_DER (*self*)

```
Get the DER value of this public key.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 700 of file x509.py.

8.204.2.2 def rpki.x509.RSApublic.get_POW (*self*)

```
Get the POW value of this public key.
```

Definition at line 712 of file x509.py.

8.204.2.3 def rpki.x509.RSApublic.get_SKI (*self*)

```
Calculate the SKI of this public key.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 721 of file x509.py.

8.204.3 Member Data Documentation

8.204.3.1 rpki.x509.RSApublic.DER

DER value of this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 708 of file x509.py.

8.204.3.2 tuple rpki.x509.RSApublic.formats = ("DER", "POW") [static]

Formats supported in this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 697 of file x509.py.

8.204.3.3 tuple rpki.x509.RSApublic.pem_converter = PEM_converter("RSA PUBLIC KEY") [static]

PEM converter for this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 698 of file x509.py.

8.204.3.4 rpki.x509.RSApublic.POW

Definition at line 718 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.205 rpki.x509.SignedManifest Class Reference

Inherits rpki::x509::DER_CMS_object.

Collaboration diagram for rpki.x509.SignedManifest:



Public Member Functions

- def build
- def getNextUpdate
- def getThisUpdate

Static Public Attributes

- content_class = rpki.manifest.Manifest
- tuple econtent_oid = POWify_OID("id-ct-rpkiManifest")
- tuple pem_converter = PEM_converter("RPKI MANIFEST")

  PEM converter for this object.

8.205.1 Detailed Description

```
Class to hold a signed manifest.
```

Definition at line 967 of file x509.py.

8.205.2 Member Function Documentation

8.205.2.1 def rpki.x509.SignedManifest.build (*cls*, *serial*, *thisUpdate*, *nextUpdate*, *names_and_objs*, *keypair*, *certs*, *version* = 0)

```
Build a signed manifest.
```

Definition at line 985 of file x509.py.

8.205.2.2 def rpki.x509.SignedManifest.getNextUpdate (*self*)

```
Get nextUpdate value from this manifest.
```

Definition at line 980 of file x509.py.

8.205.2.3 def rpki.x509.SignedManifest.getThisUpdate (*self*)

```
Get thisUpdate value from this manifest.
```

Definition at line 976 of file x509.py.

8.205.3 Member Data Documentation

8.205.3.1 rpki.x509.SignedManifest.content_class = rpki.manifest.Manifest [static]

Definition at line 973 of file x509.py.

8.205.3.2 tuple rpki.x509.SignedManifest.econtent_oid = POWify_OID("id-ct-rpkiManifest") [static]

Reimplemented from rpki.x509.CMS_object.

Definition at line 974 of file x509.py.

8.205.3.3 tuple rpki.x509.SignedManifest.pem_converter = PEM_converter("RPKI MANIFEST") [static]

PEM converter for this object.

Reimplemented from rpki.x509.CMS_object.

Definition at line 972 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.206 rpki.x509.X509 Class Reference

Inherits rpki::x509::DER_object.

Collaboration diagram for rpki.x509.X509:



Public Member Functions

- def cross_certify
- def expired
- def get_DER
- def get_POW
- def get_POWpkix

- def getIssuer
- def getNotAfter
- def getNotBefore
- def getPublicKey
- def getSerial
- def getSubject
- def issue
- def normalize_chain

Public Attributes

- DER

  DER value of this object.

- POW
- POWpkix

Static Public Attributes

- tuple formats = ("DER", "POW", "POWpkix")

  Formats supported in this object.

- tuple pem_converter = PEM_converter("CERTIFICATE")

  PEM converter for this object.

8.206.1 Detailed Description

```
X.509 certificates.

This class is designed to hold all the different representations of
X.509 certs we're using and convert between them.  X.509 support in
Python a nasty maze of half-cooked stuff (except perhaps for
cryptlib, which is just different).  Users of this module should not
have to care about this implementation nightmare.
```

Definition at line 360 of file x509.py.

8.206.2 Member Function Documentation

8.206.2.1 def rpki.x509.X509.cross_certify (*self*, *keypair*, *source_cert*, *serial*, *notAfter*, *now* = `None`, *pathLenConstraint* = `0`)

```
Issue a certificate with values taking from an existing certificate.
This is used to construct some kinds oF BPKI certificates.
```

Definition at line 492 of file x509.py.

8.206.2.2 def rpki.x509.X509.expired (*self*)

```
Test whether this certificate has expired.
```

Definition at line 433 of file x509.py.

8.206.2.3 def rpki.x509.X509.get_DER (*self*)

```
Get the DER value of this certificate.
```

Reimplemented from rpki.x509.DER_object.

Definition at line 374 of file x509.py.

8.206.2.4 def rpki.x509.X509.get_POW (*self*)

```
Get the POW value of this certificate.
```

Definition at line 389 of file x509.py.

8.206.2.5 def rpki.x509.X509.get_POWpkix (*self*)

```
Get the POW.pkix value of this certificate.
```

Definition at line 398 of file x509.py.

8.206.2.6 def rpki.x509.X509.getIssuer (*self*)

```
Get the issuer of this certificate.
```

Definition at line 409 of file x509.py.

8.206.2.7 def rpki.x509.X509.getNotAfter (*self*)

```
Get the expiration time of this certificate.
```

Definition at line 421 of file x509.py.

8.206.2.8 def rpki.x509.X509.getNotBefore (*self*)

```
Get the inception time of this certificate.
```

Definition at line 417 of file x509.py.

8.206.2.9 def rpki.x509.X509.getPublicKey (*self*)

```
Extract the public key from this certificate.
```

Definition at line 429 of file x509.py.

8.206.2.10 def rpki.x509.X509.getSerial (*self*)

```
Get the serial number of this certificate.
```

Definition at line 425 of file x509.py.

8.206.2.11 def rpki.x509.X509.getSubject (*self*)

```
Get the subject of this certificate.
```

Definition at line 413 of file x509.py.

8.206.2.12 def rpki.x509.X509.issue (*self*, *keypair*, *subject_key*, *serial*, *sia*, *aia*, *crldp*, *notAfter*, *cn* = `None`, *resources* = `None`, *is_ca* = `True`)

```
Issue a certificate.
```

Definition at line 437 of file x509.py.

8.206.2.13 def rpki.x509.X509.normalize_chain (*cls*, *chain*)

```
Normalize a chain of certificates into a tuple of X509 objects.
Given all the glue certificates needed for BPKI cross
certification, it's easiest to allow sloppy arguments to the HTTPS
and CMS validation methods and provide a single method that
normalizes the allowed cases.  So this method allows X509, None,
lists, and tuples, and returns a tuple of X509 objects.
```

Definition at line 521 of file x509.py.

8.206.3 Member Data Documentation

8.206.3.1 rpki.x509.X509.DER

DER value of this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 382 of file x509.py.

8.206.3.2 tuple rpki.x509.X509.formats = ("DER", "POW", "POWpkix") `[static]`

Formats supported in this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 371 of file x509.py.

8.206.3.3 tuple rpki.x509.X509.pem_converter = PEM_converter("CERTIFICATE") `[static]`

PEM converter for this object.

Reimplemented from rpki.x509.DER_object.

Definition at line 372 of file x509.py.

8.206.3.4 rpki.x509.X509.POW

Definition at line 395 of file x509.py.

8.206.3.5 rpki.x509.X509.POWpkix

Definition at line 406 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.207 rpki.x509.XML_CMS_object Class Reference

Inherits rpki::x509::CMS_object.

Inherited by rpki.left_right.cms_msg, rpki.publication.cms_msg, and rpki.up_-down.cms_msg.

Collaboration diagram for rpki.x509.XML_CMS_object:



Public Member Functions

- def decode
- def dump_to_disk
- def encode
- def pretty_print_content
- def schema_check

- def unwrap
- def wrap

Public Attributes

- content

Static Public Attributes

- dump_inbound_cms = None

  If set, we write all inbound XML-CMS PDUs to disk, for debugging.

- dump_outbound_cms = None

  If set, we write all outbound XML-CMS PDUs to disk, for debugging.

- tuple econtent_oid = POWify_OID("id-ct-xml")

8.207.1 Detailed Description

```
Class to hold CMS-wrapped XML protocol data.
```

Definition at line 1058 of file x509.py.

8.207.2 Member Function Documentation

8.207.2.1 def rpki.x509.XML_CMS_object.decode (*self*, *xml*)

```
Decode XML and set inner content.
```

Definition at line 1081 of file x509.py.

8.207.2.2 def rpki.x509.XML_CMS_object.dump_to_disk (*self*, *prefix*)

```
Write DER of current message to disk, for debugging.
```

Definition at line 1099 of file x509.py.

8.207.2.3 def rpki.x509.XML_CMS_object.encode (*self*)

```
Encode inner content for signing.
```

Definition at line 1077 of file x509.py.

8.207.2.4 def rpki.x509.XML_CMS_object.pretty_print_content (*self*)

```
Pretty print XML content of this message.
```

Definition at line 1085 of file x509.py.

8.207.2.5 def rpki.x509.XML_CMS_object.schema_check (*self*)

```
Handle XML RelaxNG schema check.
```

Definition at line 1089 of file x509.py.

8.207.2.6 def rpki.x509.XML_CMS_object.unwrap (*cls*, *der*, *ta*, *pretty_print* = **False**)

```
Unwrap a CMS-wrapped XML PDU and return Python objects.
```

Definition at line 1125 of file x509.py.

8.207.2.7 def rpki.x509.XML_CMS_object.wrap (*cls*, *msg*, *keypair*, *certs*, *crls* = **None**, *pretty_print* = **False**)

```
Build a CMS-wrapped XML PDU and return its DER encoding.
```

Definition at line 1108 of file x509.py.

8.207.3 Member Data Documentation

8.207.3.1 rpki.x509.XML_CMS_object.content

Reimplemented from rpki.x509.CMS_object.

Definition at line 1083 of file x509.py.

8.207.3.2 rpki::x509.XML_CMS_object::dump_inbound_cms = None [static]

If set, we write all inbound XML-CMS PDUs to disk, for debugging.

If set, value should be a DeadDrop object.

Definition at line 1075 of file x509.py.

8.207.3.3 rpki::x509.XML_CMS_object::dump_outbound_cms = None [static]

If set, we write all outbound XML-CMS PDUs to disk, for debugging.

If set, value should be a DeadDrop object.

Definition at line 1069 of file x509.py.

8.207.3.4 tuple rpki.x509.XML_CMS_object.econtent_oid = POWify_OID("id-ct-xml") [static]

Reimplemented from rpki.x509.CMS_object.

Definition at line 1063 of file x509.py.

The documentation for this class was generated from the following file:

- x509.py (3107)

8.208 rpki.xml_utils.base_elt Class Reference

Inherits object.

Inherited by rpki.left_right.list_received_resources_elt, rpki.left_right.list_resources_-elt, rpki.left_right.list_roa_requests_elt, rpki.publication.publication_object_elt, rpki.xml_utils.data_elt, and rpki.xml_utils.text_elt.

Collaboration diagram for rpki.xml_utils.base_elt:



Public Member Functions

- def __str__
- def endElement

- def make_b64elt
- def make_elt
- def make_pdu
- def read_attrs
- def startElement
- def toXML

Static Public Attributes

- tuple attributes = ()

  XML attributes for this element.

- tuple booleans = ()

  Boolean attributes (value "yes" or "no") for this element.

- tuple elements = ()

  XML elements contained by this element.

8.208.1 Detailed Description

```
Virtual base class for XML message elements.  The left-right and
publication protocols use this.  At least for now, the up-down
protocol does not, due to different design assumptions.
```

Definition at line 126 of file xml_utils.py.

8.208.2 Member Function Documentation

8.208.2.1 def rpki.xml_utils.base_elt.__str__ (*self*)

```
Convert a base_elt object to string format.
```

Reimplemented in rpki.publication.report_error_elt.

Definition at line 201 of file xml_utils.py.

8.208.2.2 def rpki.xml_utils.base_elt.endElement (*self*, *stack*, *name*, *text*)

```
Default endElement() handler: just pop the stack.
```

Reimplemented in rpki.left_right.child_elt, rpki.publication.client_elt, rpki.publication.publication_object_elt, rpki.xml_utils.text_elt, and rpki.xml_-utils.data_elt.

Definition at line 153 of file xml_utils.py.

8.208.2.3 def rpki.xml_utils.base_elt.make_b64elt (*self*, *elt*, *name*, *value* = `None`)

```
Constructor for Base64-encoded subelement.
```

Definition at line 192 of file xml_utils.py.

8.208.2.4 def rpki.xml_utils.base_elt.make_elt (*self*)

```
XML element constructor.
```

Definition at line 178 of file xml_utils.py.

8.208.2.5 def rpki.xml_utils.base_elt.make_pdu (*cls*, *kargs*)

```
Generic PDU constructor.
```

Definition at line 208 of file xml_utils.py.

8.208.2.6 def rpki.xml_utils.base_elt.read_attrs (*self*, *attrs*)

```
Template-driven attribute reader.
```

Definition at line 166 of file xml_utils.py.

8.208.2.7 def rpki.xml_utils.base_elt.startElement (*self*, *stack*, *name*, *attrs*)

```
Default startElement() handler: just process attributes.
```

Reimplemented in rpki.left_right.list_resources_elt, rpki.left_right.list_roa_requests_-elt, and rpki.publication.config_elt.

Definition at line 145 of file xml_utils.py.

8.208.2.8 def rpki.xml_utils.base_elt.toXML (*self*)

```
Default toXML() element generator.
```

Reimplemented in rpki.left_right.list_resources_elt, rpki.publication.publication_-object_elt, rpki.xml_utils.text_elt, and rpki.xml_utils.data_elt.

Definition at line 160 of file xml_utils.py.

8.208.3 Member Data Documentation

8.208.3.1 rpki::xml_utils.base_elt::attributes = () [static]

XML attributes for this element.

Reimplemented in rpki.left_right.self_elt, rpki.left_right.bsc_elt, rpki.left_-right.repository_elt, rpki.left_right.parent_elt, rpki.left_right.child_elt, rpki.left_-right.list_resources_elt, rpki.left_right.list_roa_requests_elt, rpki.left_right.list_-published_objects_elt, rpki.left_right.list_received_resources_elt, rpki.left_-right.report_error_elt, rpki.publication.config_elt, rpki.publication.client_elt, rpki.publication.publication_object_elt, and rpki.publication.report_error_elt.

Definition at line 135 of file xml_utils.py.

8.208.3.2 rpki::xml_utils.base_elt::booleans = () [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented in rpki.left_right.self_elt, rpki.left_right.bsc_elt, rpki.left_-right.parent_elt, and rpki.left_right.child_elt.

Definition at line 143 of file xml_utils.py.

8.208.3.3 rpki::xml_utils.base_elt::elements = () [static]

XML elements contained by this element.

Reimplemented in rpki.left_right.self_elt, rpki.left_right.bsc_elt, rpki.left_-right.repository_elt, rpki.left_right.parent_elt, rpki.left_right.child_elt, rpki.publication.config_elt, and rpki.publication.client_elt.

Definition at line 139 of file xml_utils.py.

The documentation for this class was generated from the following file:

- xml_utils.py (2836)

8.209 rpki.xml_utils.data_elt Class Reference

Inherits rpki::xml_utils::base_elt.

Inherited by rpki.left_right.data_elt, and rpki.publication.control_elt.

Collaboration diagram for rpki.xml_utils.data_elt:



Public Member Functions

- def endElement
- def make_reply
- def make_reply_clone_hook
- def serve_create
- def serve_destroy

- def serve_destroy_hook
- def serve_dispatch
- def serve_fetch_one
- def serve_get
- def serve_list
- def serve_post_save_hook
- def serve_pre_save_hook
- def serve_set
- def toXML
- def unimplemented_control

8.209.1 Detailed Description

```
Virtual base class for PDUs that map to SQL objects.  These objects
all implement the create/set/get/list/destroy action attribute.
```

Definition at line 243 of file xml_utils.py.

8.209.2 Member Function Documentation

8.209.2.1 def rpki.xml_utils.data_elt.endElement (*self*, *stack*, *name*, *text*)

```
Default endElement handler for SQL-based objects.  This assumes
that sub-elements are Base64-encoded using the sql_template
mechanism.
```

Reimplemented from rpki.xml_utils.base_elt.

Reimplemented in rpki.left_right.child_elt, and rpki.publication.client_elt.

Definition at line 249 of file xml_utils.py.

8.209.2.2 def rpki.xml_utils.data_elt.make_reply (*self*, *r_pdu* = `None`)

```
Construct a reply PDU.
```

Definition at line 275 of file xml_utils.py.

8.209.2.3 def rpki.xml_utils.data_elt.make_reply_clone_hook (*self*, *r_pdu*)

```
Overridable hook.
```

Reimplemented in rpki.left_right.data_elt.

Definition at line 292 of file xml_utils.py.

8.209.2.4 def rpki.xml_utils.data_elt.serve_create (*self*, *r_msg*, *cb*, *eb*)

```
Handle a create action.
```

Definition at line 314 of file xml_utils.py.

8.209.2.5 def rpki.xml_utils.data_elt.serve_destroy (*self*, *r_msg*, *cb*, *eb*)

```
Handle a destroy action.
```

Definition at line 384 of file xml_utils.py.

8.209.2.6 def rpki.xml_utils.data_elt.serve_destroy_hook (*self*, *cb*, *eb*)

```
Overridable hook.
```

Reimplemented in rpki.left_right.child_elt.

Definition at line 378 of file xml_utils.py.

8.209.2.7 def rpki.xml_utils.data_elt.serve_dispatch (*self*, *r_msg*, *cb*, *eb*)

```
Action dispatch handler.
```

Reimplemented in rpki.publication.control_elt.

Definition at line 395 of file xml_utils.py.

8.209.2.8 def rpki.xml_utils.data_elt.serve_fetch_one (*self*)

```
Find the object on which a get, set, or destroy method should
operate.
```

Definition at line 296 of file xml_utils.py.

8.209.2.9 def rpki.xml_utils.data_elt.serve_get (*self*, *r_msg*, *cb*, *eb*)

```
Handle a get action.
```

Definition at line 360 of file xml_utils.py.

8.209.2.10 def rpki.xml_utils.data_elt.serve_list (*self*, *r_msg*, *cb*, *eb*)

```
Handle a list action for non-self objects.
```

Definition at line 369 of file xml_utils.py.

8.209.2.11 def rpki.xml_utils.data_elt.serve_post_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Overridable hook.
```

Reimplemented in rpki.left_right.self_elt, rpki.left_right.parent_elt, rpki.left_-right.child_elt, and rpki.publication.client_elt.

Definition at line 310 of file xml_utils.py.

8.209.2.12 def rpki.xml_utils.data_elt.serve_pre_save_hook (*self*, *q_pdu*, *r_pdu*, *cb*, *eb*)

```
Overridable hook.
```

Reimplemented in rpki.left_right.data_elt, and rpki.left_right.bsc_elt.

Definition at line 306 of file xml_utils.py.

8.209.2.13 def rpki.xml_utils.data_elt.serve_set (*self*, *r_msg*, *cb*, *eb*)

```
Handle a set action.
```

Reimplemented in rpki.publication.config_elt.

Definition at line 337 of file xml_utils.py.

8.209.2.14 def rpki.xml_utils.data_elt.toXML (*self*)

```
Default element generator for SQL-based objects.  This assumes
that sub-elements are Base64-encoded DER objects.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 263 of file xml_utils.py.

8.209.2.15 def rpki.xml_utils.data_elt.unimplemented_control (*self*, *controls*)

```
Uniform handling for unimplemented control operations.
```

Definition at line 408 of file xml_utils.py.

The documentation for this class was generated from the following file:

- xml_utils.py (2836)

8.210 rpki.xml_utils.msg Class Reference

Inherits list.

Inherited by rpki.left_right.msg, and rpki.publication.msg.

Collaboration diagram for rpki.xml_utils.msg:



Public Member Functions

- def __str__
- def endElement
- def is_query
- def is_reply
- def query
- def reply
- def startElement
- def toXML

Public Attributes

- type
- version

8.210.1 Detailed Description

```
Generic top-level PDU.
```

Definition at line 416 of file xml_utils.py.

8.210.2 Member Function Documentation

8.210.2.1 def rpki.xml_utils.msg.__str__ (*self*)

```
Convert msg object to string.
```

Definition at line 442 of file xml_utils.py.

8.210.2.2 def rpki.xml_utils.msg.endElement (*self*, *stack*, *name*, *text*)

```
Handle top-level PDU.
```

Definition at line 434 of file xml_utils.py.

8.210.2.3 def rpki.xml_utils.msg.is_query (*self*)

```
Is this msg a query?
```

Definition at line 468 of file xml_utils.py.

8.210.2.4 def rpki.xml_utils.msg.is_reply (*self*)

```
Is this msg a reply?
```

Definition at line 472 of file xml_utils.py.

8.210.2.5 def rpki.xml_utils.msg.query (*cls*, *args*)

```
Create a query PDU.
```

Definition at line 455 of file xml_utils.py.

8.210.2.6 def rpki.xml_utils.msg.reply (*cls*, *args*)

```
Create a reply PDU.
```

Definition at line 462 of file xml_utils.py.

8.210.2.7 def rpki.xml_utils.msg.startElement (*self*, *stack*, *name*, *attrs*)

```
Handle top-level PDU.
```

Definition at line 421 of file xml_utils.py.

8.210.2.8 def rpki.xml_utils.msg.toXML (*self*)

```
Generate top-level PDU.
```

Definition at line 446 of file xml_utils.py.

8.210.3 Member Data Documentation

8.210.3.1 rpki.xml_utils.msg.type

Definition at line 427 of file xml_utils.py.

8.210.3.2 rpki.xml_utils.msg.version

Reimplemented in rpki.left_right.msg, and rpki.publication.msg.

Definition at line 426 of file xml_utils.py.

The documentation for this class was generated from the following file:

- xml_utils.py (2836)

8.211 rpki.xml_utils.sax_handler Class Reference

Inherits xml::sax::handler::ContentHandler.

Inherited by rpki.left_right.sax_handler, rpki.publication.sax_handler, and rpki.up_-down.sax_handler.

Collaboration diagram for rpki.xml_utils.sax_handler:



Public Member Functions

- def __init__
- def characters
- def create_top_level
- def endElement
- def endElementNS
- def saxify
- def startElement
- def startElementNS

Public Attributes

- result
- stack
- text

8.211.1 Detailed Description

```
SAX handler for RPKI protocols.

This class provides some basic amenities for parsing protocol XML of
the kind we use in the RPKI protocols, including whacking all the
protocol element text into US-ASCII, simplifying accumulation of
text fields, and hiding some of the fun relating to XML namespaces.

General assumption: by the time this parsing code gets invoked, the
XML has already passed RelaxNG validation, so we only have to check
for errors that the schema can't catch, and we don't have to play as
many XML namespace games.
```

Definition at line 38 of file xml_utils.py.

8.211.2 Member Function Documentation

8.211.2.1 def rpki.xml_utils.sax_handler.__init__ (*self*)

```
Initialize SAX handler.
```

Definition at line 53 of file xml_utils.py.

8.211.2.2 def rpki.xml_utils.sax_handler.characters (*self*, *content*)

```
Accumulate a chuck of element content (text).
```

Definition at line 69 of file xml_utils.py.

8.211.2.3 def rpki.xml_utils.sax_handler.create_top_level (*self*, *name*, *attrs*)

```
Handle top-level PDU for this protocol.
```

Definition at line 119 of file xml_utils.py.

8.211.2.4 def rpki.xml_utils.sax_handler.endElement (*self*, *name*)

```
Handle endElement() events.  Mostly this means handling any
accumulated element text.
```

Definition at line 101 of file xml_utils.py.

8.211.2.5 def rpki.xml_utils.sax_handler.endElementNS (*self*, *name*, *qname*)

```
Redirect endElementNS() events to endElement().
```

Definition at line 65 of file xml_utils.py.

8.211.2.6 def rpki.xml_utils.sax_handler.saxify (*cls*, *elt*)

```
Create a one-off SAX parser, parse an ETree, return the result.
```

Definition at line 111 of file xml_utils.py.

8.211.2.7 def rpki.xml_utils.sax_handler.startElement (*self*, *name*, *attrs*)

```
Handle startElement() events.

We maintain a stack of nested elements under construction so that
we can feed events directly to the current element rather than
having to pass them through all the nesting elements.

If the stack is empty, this event is for the outermost element, so
we call a virtual method to create the corresponding object and
that's the object we'll be returning as our final result.
```

Definition at line 73 of file xml_utils.py.

8.211.2.8 def rpki.xml_utils.sax_handler.startElementNS (*self*, *name*, *qname*, *attrs*)

```
Redirect startElementNS() events to startElement().
```

Definition at line 61 of file xml_utils.py.

8.211.3 Member Data Documentation

8.211.3.1 rpki.xml_utils.sax_handler.result

Definition at line 97 of file xml_utils.py.

8.211.3.2 rpki.xml_utils.sax_handler.stack

Definition at line 59 of file xml_utils.py.

8.211.3.3 rpki.xml_utils.sax_handler.text

Definition at line 58 of file xml_utils.py.

The documentation for this class was generated from the following file:

- xml_utils.py (2836)

8.212 rpki.xml_utils.text_elt Class Reference

Inherits rpki::xml_utils::base_elt.

Inherited by rpki.left_right.list_published_objects_elt, rpki.left_right.report_error_elt, and rpki.publication.report_error_elt.

Collaboration diagram for rpki.xml_utils.text_elt:



Public Member Functions

- def endElement
- def toXML

Static Public Attributes

- text_attribute = None

  Name of the class attribute that holds the text value.

8.212.1 Detailed Description

```
Virtual base class for XML message elements that contain text.
```

Definition at line 219 of file xml_utils.py.

8.212.2 Member Function Documentation

8.212.2.1 def rpki.xml_utils.text_elt.endElement (*self*, *stack*, *name*, *text*)

```
Extract text from parsed XML.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 228 of file xml_utils.py.

8.212.2.2 def rpki.xml_utils.text_elt.toXML (*self*)

```
Insert text into generated XML.
```

Reimplemented from rpki.xml_utils.base_elt.

Definition at line 235 of file xml_utils.py.

8.212.3 Member Data Documentation

8.212.3.1 rpki::xml_utils.text_elt::text_attribute = None [static]

Name of the class attribute that holds the text value.

Reimplemented in rpki.left_right.list_published_objects_elt, rpki.left_right.report_-error_elt, and rpki.publication.report_error_elt.

Definition at line 226 of file xml_utils.py.

The documentation for this class was generated from the following file:

- xml_utils.py (2836)

8.213 Sequence Class Reference

Inherited by rpki.manifest.FileAndHash, rpki.manifest.Manifest, rpki.roa.ROAIPAddress, rpki.roa.ROAIPAddressFamily, and rpki.roa.RouteOriginAttestation.

The documentation for this class was generated from the following file:

- roa.py (2424)

8.214 SequenceOf Class Reference

Inherited by rpki.manifest.FilesAndHashes, rpki.roa.ROAIPAddresses, and rpki.roa.ROAIPAddressFamilies.

The documentation for this class was generated from the following file:

- roa.py (2424)

8.215 TextWrapper Class Reference

Inherited by irbe_cli.UsageWrapper.

The documentation for this class was generated from the following file:

- irbe_cli.py (3107)

8.216 ContentHandler Class Reference

Inherited by rpki.xml_utils.sax_handler.

The documentation for this class was generated from the following file:

- xml_utils.py (2836)

9 File Documentation

9.1 __init__.py File Reference

Packages

- package rpki

9.2 async.py File Reference

Classes

- class rpki.async.gc_summary
- class rpki.async.iterator
- class rpki.async.sync_wrapper
- class rpki.async.timer

Packages

- package rpki.async

Functions

- def rpki::async._raiseExitNow
- def rpki::async.defer
- def rpki::async.event_loop
- def rpki::async.exit_event_loop
- def rpki::async.run_deferred

Variables

- list rpki::async.deferred_queue = [ ]

  List to hold deferred actions.

- rpki::async.ExitNow = asyncore.ExitNow

9.3 cli.py File Reference

Classes

- class rpki.cli.Cmd

Packages

- package rpki.cli

Functions

- def rpki::cli.yes_or_no

Variables

- dictionary rpki::cli._yes_or_no_prompts
- rpki::cli.have_readline = True

9.4 config.py File Reference

Classes

- class rpki.config.parser

Packages

- package rpki.config

9.5 exceptions.py File Reference

Classes

- class rpki.exceptions.BadClassNameSyntax
- class rpki.exceptions.BadClientURL
- class rpki.exceptions.BadContactURL
- class rpki.exceptions.BadExtension
- class rpki.exceptions.BadIRDBReply
- class rpki.exceptions.BadIssueResponse
- class rpki.exceptions.BadPKCS10
- class rpki.exceptions.BadPublicationReply
- class rpki.exceptions.BadQuery
- class rpki.exceptions.BadSender
- class rpki.exceptions.BadStatusCode
- class rpki.exceptions.BadURISyntax
- class rpki.exceptions.BSCNotFound
- class rpki.exceptions.BSCNotReady

- class rpki.exceptions.ChildNotFound
- class rpki.exceptions.ClassNameMismatch
- class rpki.exceptions.ClassNameUnknown
- class rpki.exceptions.ClientNotFound
- class rpki.exceptions.CMSContentNotSet
- class rpki.exceptions.CMSCRLNotSet
- class rpki.exceptions.CMSVerificationFailed
- class rpki.exceptions.DBConsistancyError
- class rpki.exceptions.DERObjectConversionError
- class rpki.exceptions.DuplicateObject
- class rpki.exceptions.EmptyPEM
- class rpki.exceptions.EmptyROAPrefixList
- class rpki.exceptions.ForbiddenURI
- class rpki.exceptions.HandleTranslationError
- class rpki.exceptions.HTTPRequestFailed
- class rpki.exceptions.HTTPSBadVersion
- class rpki.exceptions.HTTPSClientAborted
- class rpki.exceptions.HTTPSUnexpectedState
- class rpki.exceptions.MissingCMSCRL
- class rpki.exceptions.MissingCMSEEcert
- class rpki.exceptions.MultipleTLSEECert
- class rpki.exceptions.MustBePrefix
- class rpki.exceptions.NoActiveCA
- class rpki.exceptions.NoCoveringCertForROA
- class rpki.exceptions.NoObjectAtURI
- class rpki.exceptions.NotACertificateChain
- class rpki.exceptions.NotFound
- class rpki.exceptions.NotImplementedYet
- class rpki.exceptions.NotInDatabase
- class rpki.exceptions.ReceivedTLSCACert
- class rpki.exceptions.RPKI_Exception
- class rpki.exceptions.ServerShuttingDown
- class rpki.exceptions.SKIMismatch
- class rpki.exceptions.SubprocessError
- class rpki.exceptions.TLSValidationError
- class rpki.exceptions.UnexpectedCMSCerts
- class rpki.exceptions.UnexpectedCMSCRLs
- class rpki.exceptions.UnparsableCMSDER
- class rpki.exceptions.UpstreamError
- class rpki.exceptions.WrongEContentType

Packages

- package rpki.exceptions

9.6 https.py File Reference

Classes

- class rpki.https.caller
- class rpki.https.http_client
- class rpki.https.http_listener
- class rpki.https.http_message
- class rpki.https.http_queue
- class rpki.https.http_request
- class rpki.https.http_response
- class rpki.https.http_server
- class rpki.https.http_stream

Packages

- package rpki.https

Functions

- def rpki::https.build_https_ta_cache
- def rpki::https.client
- def rpki::https.log_method
- def rpki::https.server

Variables

- dictionary rpki::https.client_queues = { }
- rpki::https.debug_http = False
- rpki::https.debug_tls_certs = False
- tuple rpki::https.default_client_timeout = rpki.sundial.timedelta(minutes = 15)
- tuple rpki::https.default_http_version = (1, 0)
- tuple rpki::https.default_server_timeout = rpki.sundial.timedelta(minutes = 20)
- string rpki::https.rpki_content_type = "application/x-rpki"
- tuple rpki::https.supported_address_families = (socket.AF_INET, socket.AF_-INET6)
- rpki::https.want_persistent_client = False
- rpki::https.want_persistent_server = False

9.7 ipaddrs.py File Reference

Classes

- class rpki.ipaddrs.v4addr
- class rpki.ipaddrs.v6addr

Packages

- package rpki.ipaddrs

9.8 irbe_cli.py File Reference

Classes

- class irbe_cli.bsc_elt
- class irbe_cli.certificate_elt
- class irbe_cli.child_elt
- class irbe_cli.client_elt
- class irbe_cli.cmd_elt_mixin
- class irbe_cli.cmd_msg_mixin
- class irbe_cli.config_elt
- class irbe_cli.crl_elt
- class irbe_cli.left_right_cms_msg
- class irbe_cli.left_right_msg
- class irbe_cli.left_right_proto
- class irbe_cli.left_right_sax_handler
- class irbe_cli.list_published_objects_elt
- class irbe_cli.list_received_resources_elt
- class irbe_cli.manifest_elt
- class irbe_cli.parent_elt
- class irbe_cli.publication_cms_msg
- class irbe_cli.publication_msg
- class irbe_cli.publication_proto
- class irbe_cli.publication_sax_handler
- class irbe_cli.reply_elt_mixin
- class irbe_cli.report_error_elt
- class irbe_cli.report_error_elt
- class irbe_cli.repository_elt
- class irbe_cli.roa_elt
- class irbe_cli.self_elt
- class irbe_cli.UsageWrapper

Packages

- package irbe_cli

Functions

- def irbe_cli.usage

Variables

- list irbe_cli.argv = sys.argv[1:]
- tuple irbe_cli.call_pubd
- tuple irbe_cli.call_rpkid
- tuple irbe_cli.cfg = rpki.config.parser(cfg_file, "irbe_cli")
- string irbe_cli.cfg_file = "irbe.conf"
- irbe_cli.pem_out = None
- irbe_cli.q_msg = q_msg_left_right
- list irbe_cli.q_msg_left_right = [ ]
- list irbe_cli.q_msg_publication = [ ]
- list irbe_cli.q_pdu = left_right_msg.pdus[argv[0]]
- list irbe_cli.top_opts = ["config=", "help", "pem_out=", "quiet", "verbose"]
- tuple irbe_cli.usage_fill = UsageWrapper(subsequent_indent = " " ∗ 4)
- irbe_cli.verbose = True

9.9 irdbd.py File Reference

Packages

- package irdbd

Functions

- def irdbd.handle_list_resources
- def irdbd.handle_list_roa_requests
- def irdbd.handler

Variables

- tuple irdbd.bpki_ta = rpki.x509.X509(Auto_file = cfg.get("bpki-ta"))
- tuple irdbd.cfg = rpki.config.parser(cfg_file, "irdbd")
- string irdbd.cfg_file = "irdbd.conf"

- tuple irdbd.client_ta = (bpki_ta, rpkid_cert)
- tuple irdbd.cur = db.cursor()
- tuple irdbd.db
- dictionary irdbd.handle_dispatch
- tuple irdbd.handlers = ((u.path, handler),)
- string irdbd.host = "localhost"
- tuple irdbd.irdbd_cert = rpki.x509.X509(Auto_file = cfg.get("irdbd-cert"))
- tuple irdbd.irdbd_key = rpki.x509.RSA(Auto_file = cfg.get("irdbd-key"))
- int irdbd.port = 443
- tuple irdbd.rpkid_cert = rpki.x509.X509(Auto_file = cfg.get("rpkid-cert"))
- irdbd.server_cert = irdbd_cert,
- tuple irdbd.startup_msg = cfg.get("startup-message", "")
- tuple irdbd.u = urlparse.urlparse(cfg.get("https-url"))

9.10 left_right.py File Reference

Classes

- class rpki.left_right.bsc_elt
- class rpki.left_right.child_elt
- class rpki.left_right.cms_msg
- class rpki.left_right.data_elt
- class rpki.left_right.left_right_namespace
- class rpki.left_right.list_published_objects_elt
- class rpki.left_right.list_received_resources_elt
- class rpki.left_right.list_resources_elt
- class rpki.left_right.list_roa_requests_elt
- class rpki.left_right.msg
- class rpki.left_right.parent_elt
- class rpki.left_right.report_error_elt
- class rpki.left_right.repository_elt
- class rpki.left_right.sax_handler
- class rpki.left_right.self_elt

Packages

- package rpki.left_right

Variables

- rpki::left_right.enforce_strict_up_down_xml_sender = False

9.11 log.py File Reference

Classes

- class rpki.log.logger

Packages

- package rpki.log

Functions

- def rpki::log.init
- def rpki::log.set_trace
- def rpki::log.trace
- def rpki::log.traceback

Variables

- tuple rpki::log.debug = logger(syslog.LOG_DEBUG)
- rpki::log.enable_trace = False

  Whether call tracing is enabled.

- tuple rpki::log.error = logger(syslog.LOG_ERR)
- tuple rpki::log.info = logger(syslog.LOG_INFO)
- tuple rpki::log.note = logger(syslog.LOG_NOTICE)
- int rpki::log.pid = 0
- string rpki::log.tag = ""
- rpki::log.use_syslog = True

  Whether to use syslog.

- tuple rpki::log.warn = logger(syslog.LOG_WARNING)

9.12 manifest.py File Reference

Classes

- class rpki.manifest.FileAndHash
- class rpki.manifest.FilesAndHashes
- class rpki.manifest.Manifest

Packages

- package rpki.manifest

9.13 oids.py File Reference

Packages

- package rpki.oids

Variables

- tuple rpki::oids.name2oid = dict((v, k) for k, v in oid2name.items())

  Mapping table of string names to OIDs.

- dictionary rpki::oids.oid2name

  Mapping table of OIDs to conventional string names.

9.14 pubd.py File Reference

Classes

- class pubd.pubd_context

Packages

- package pubd

Functions

- def pubd.main

Variables

- string pubd.cfg_file = "pubd.conf"
- pubd.profile = False

9.15 publication.py File Reference

Classes

- class rpki.publication.certificate_elt
- class rpki.publication.client_elt
- class rpki.publication.cms_msg
- class rpki.publication.config_elt
- class rpki.publication.control_elt
- class rpki.publication.crl_elt
- class rpki.publication.manifest_elt
- class rpki.publication.msg
- class rpki.publication.publication_namespace
- class rpki.publication.publication_object_elt
- class rpki.publication.report_error_elt
- class rpki.publication.roa_elt
- class rpki.publication.sax_handler

Packages

- package rpki.publication

9.16 relaxng.py File Reference

Packages

- package rpki.relaxng

Variables

- tuple rpki::relaxng.left_right

  Parsed RelaxNG left_right schema.

- tuple rpki::relaxng.publication

  Parsed RelaxNG publication schema.

- tuple rpki::relaxng.up_down

  Parsed RelaxNG up_down schema.

9.17 resource_set.py File Reference

Classes

- class rpki.resource_set.resource_bag
- class rpki.resource_set.resource_range
- class rpki.resource_set.resource_range_as
- class rpki.resource_set.resource_range_ip
- class rpki.resource_set.resource_range_ipv4
- class rpki.resource_set.resource_range_ipv6
- class rpki.resource_set.resource_set
- class rpki.resource_set.resource_set_as
- class rpki.resource_set.resource_set_ip
- class rpki.resource_set.resource_set_ipv4
- class rpki.resource_set.resource_set_ipv6
- class rpki.resource_set.roa_prefix
- class rpki.resource_set.roa_prefix_ipv4
- class rpki.resource_set.roa_prefix_ipv6
- class rpki.resource_set.roa_prefix_set
- class rpki.resource_set.roa_prefix_set_ipv4
- class rpki.resource_set.roa_prefix_set_ipv6

Packages

- package rpki.resource_set

Functions

- def rpki::resource_set._bs2long
- def rpki::resource_set._long2bs
- def rpki::resource_set._rsplit
- def rpki::resource_set.test1
- def rpki::resource_set.test2

Variables

- string rpki::resource_set.inherit_token = "<inherit>"

  Token used to indicate inheritance in read and print syntax.

9.18 roa.py File Reference

Classes

- class rpki.roa.ROAIPAddress
- class rpki.roa.ROAIPAddresses
- class rpki.roa.ROAIPAddressFamilies
- class rpki.roa.ROAIPAddressFamily
- class rpki.roa.RouteOriginAttestation

Packages

- package rpki.roa

9.19 rootd.py File Reference

Classes

- class rootd.cms_msg
- class rootd.issue_pdu
- class rootd.list_pdu
- class rootd.message_pdu
- class rootd.revoke_pdu
- class rootd.sax_handler

Packages

- package rootd

Functions

- def rootd.compose_response
- def rootd.del_subject_cert
- def rootd.del_subject_pkcs10
- def rootd.get_root_cert
- def rootd.get_subject_cert
- def rootd.get_subject_pkcs10
- def rootd.issue_subject_cert_maybe
- def rootd.root_newer_than_subject
- def rootd.set_subject_cert
- def rootd.set_subject_pkcs10
- def rootd.up_down_handler

Variables

- tuple rootd.bpki_ta = rpki.x509.X509(Auto_file = cfg.get("bpki-ta"))
- tuple rootd.cfg = rpki.config.parser(cfg_file, "rootd")
- string rootd.cfg_file = "rootd.conf"
- tuple rootd.child_bpki_cert = rpki.x509.X509(Auto_file = cfg.get("child-bpki-cert"))
- tuple rootd.client_ta = (bpki_ta, child_bpki_cert)
- rootd.handlers = up_down_handler)
- rootd.host = https_server_host,
- tuple rootd.https_server_host = cfg.get("server-host", "")
- tuple rootd.https_server_port = int(cfg.get("server-port"))
- rootd.port = https_server_port,
- tuple rootd.rootd_bpki_cert = rpki.x509.X509(Auto_file = cfg.get("rootd-bpki-cert"))
- tuple rootd.rootd_bpki_crl = rpki.x509.CRL(Auto_file = cfg.get("rootd-bpki-crl"))
- tuple rootd.rootd_bpki_key = rpki.x509.RSA(Auto_file = cfg.get("rootd-bpki-key"))
- tuple rootd.rpki_base_uri = cfg.get("rpki-base-uri", "rsync://" + rpki_class_name + ".invalid/")
- tuple rootd.rpki_class_name = cfg.get("rpki-class-name", "wombat")
- rootd.rpki_root_cert = None
- tuple rootd.rpki_root_cert_file = cfg.get("rpki-root-cert")
- tuple rootd.rpki_root_cert_uri = cfg.get("rpki-root-cert-uri", rpki_base_uri + "Root.cer")
- tuple rootd.rpki_root_crl = cfg.get("rpki-root-crl", "Root.crl")
- tuple rootd.rpki_root_dir = cfg.get("rpki-root-dir")
- tuple rootd.rpki_root_key = rpki.x509.RSA(Auto_file = cfg.get("rpki-root-key"))
- tuple rootd.rpki_root_manifest = cfg.get("rpki-root-manifest", "Root.mnf")
- tuple rootd.rpki_subject_cert = cfg.get("rpki-subject-cert", "Child.cer")
- tuple rootd.rpki_subject_lifetime = rpki.sundial.timedelta.parse(cfg.get("rpki-subject-lifetime", "30d"))
- tuple rootd.rpki_subject_pkcs10 = cfg.get("rpki-subject-pkcs10", "Child.pkcs10")
- tuple rootd.rpki_subject_regen = rpki.sundial.timedelta.parse(cfg.get("rpki-subject-regen", rpki_subject_lifetime.convert_to_seconds() / 2))
- rootd.server_cert = rootd_bpki_cert,

9.20 rpki_engine.py File Reference

Classes

- class rpki.rpki_engine.ca_detail_obj
- class rpki.rpki_engine.ca_obj
- class rpki.rpki_engine.child_cert_obj
- class rpki.rpki_engine.publication_queue
- class rpki.rpki_engine.revoked_cert_obj
- class rpki.rpki_engine.roa_obj
- class rpki.rpki_engine.rpkid_context

Packages

- package rpki.rpki_engine

9.21 rpkid.py File Reference

Packages

- package rpkid

Functions

- def rpkid.main

Variables

- string rpkid.cfg_file = "rpkid.conf"
- rpkid.profile = None

9.22 sql.py File Reference

Classes

- class rpki.sql.session
- class rpki.sql.sql_persistent
- class rpki.sql.template

Packages

- package rpki.sql

9.23 sundial.py File Reference

Classes

- class rpki.sundial.datetime
- class rpki.sundial.timedelta

Packages

- package rpki.sundial

Functions

- def rpki::sundial._cast
- def rpki::sundial.now
- def rpki::sundial.test

9.24 up_down.py File Reference

Classes

- class rpki.up_down.base_elt
- class rpki.up_down.certificate_elt
- class rpki.up_down.class_elt
- class rpki.up_down.class_response_syntax
- class rpki.up_down.cms_msg
- class rpki.up_down.error_response_pdu
- class rpki.up_down.issue_pdu
- class rpki.up_down.issue_response_pdu
- class rpki.up_down.list_pdu
- class rpki.up_down.list_response_pdu
- class rpki.up_down.message_pdu
- class rpki.up_down.multi_uri
- class rpki.up_down.revoke_pdu
- class rpki.up_down.revoke_response_pdu
- class rpki.up_down.revoke_syntax
- class rpki.up_down.sax_handler

Packages

- package rpki.up_down

Variables

- dictionary rpki::up_down.nsmap = { None : xmlns }
- string rpki::up_down.xmlns = "http://www.apnic.net/specs/rescerts/up-down/"

9.25 x509.py File Reference

Classes

- class rpki.x509.CMS_object
- class rpki.x509.CRL
- class rpki.x509.DeadDrop
- class rpki.x509.DER_CMS_object
- class rpki.x509.DER_object
- class rpki.x509.PEM_converter
- class rpki.x509.PKCS10
- class rpki.x509.ROA
- class rpki.x509.RSA
- class rpki.x509.RSApublic
- class rpki.x509.SignedManifest
- class rpki.x509.X509
- class rpki.x509.XML_CMS_object

Packages

- package rpki.x509

Functions

- def rpki::x509._find_xia_uri
- def rpki::x509.calculate_SKI
- def rpki::x509.POWify_OID

9.26 xml_utils.py File Reference

Classes

- class rpki.xml_utils.base_elt
- class rpki.xml_utils.data_elt
- class rpki.xml_utils.msg
- class rpki.xml_utils.sax_handler
- class rpki.xml_utils.text_elt

Packages

- package rpki.xml_utils

Index

__abs__
  rpki::sundial::timedelta, 492
__add__
  rpki::sundial::datetime, 485
  rpki::sundial::timedelta, 492
__call__
  irbe_cli::UsageWrapper, 135
  rpki::async::iterator, 155
  rpki::async::sync_wrapper, 159
  rpki::https::caller, 233
  rpki::log::logger, 330
__cmp__
  rpki::async::timer, 163
  rpki::resource_set::resource_range, 378
  rpki::resource_set::roa_prefix, 404
  rpki::x509::DER_object, 556
__del__
  rpki::async::timer, 163
__div__
  rpki::sundial::timedelta, 492
__eq__
  rpki::resource_set::resource_bag, 374
__floordiv__
  rpki::sundial::timedelta, 492
__init__
  pubd::pubd_context, 137
  rpki::async::gc_summary, 153
  rpki::async::iterator, 155
  rpki::async::sync_wrapper, 159
  rpki::async::timer, 163
  rpki::cli::Cmd, 168
  rpki::config::parser, 172
  rpki::https::caller, 233
  rpki::https::http_client, 236
  rpki::https::http_listener, 242
  rpki::https::http_message, 245
  rpki::https::http_queue, 248
  rpki::https::http_request, 252
  rpki::https::http_response, 255
  rpki::https::http_server, 257
  rpki::https::http_stream, 262
  rpki::log::logger, 330
  rpki::manifest::FileAndHash, 332
  rpki::manifest::FilesAndHashes, 333
  rpki::manifest::Manifest, 335
  rpki::resource_set::resource_bag, 374
  rpki::resource_set::resource_range, 378
  rpki::resource_set::resource_set, 390
  rpki::resource_set::roa_prefix, 404
  rpki::resource_set::roa_prefix_set, 412
  rpki::roa::ROAIPAddress, 418
  rpki::roa::ROAIPAddresses, 420
  rpki::roa::ROAIPAddressFamilies, 421
  rpki::roa::ROAIPAddressFamily, 422
  rpki::roa::RouteOriginAttestation, 424
  rpki::rpki_engine::child_cert_obj, 443
  rpki::rpki_engine::publication_-queue, 448
  rpki::rpki_engine::revoked_cert_obj, 451
  rpki::rpki_engine::roa_obj, 455
  rpki::rpki_engine::rpkid_context, 463
  rpki::sql::session, 470
  rpki::sql::template, 482
  rpki::up_down::class_elt, 502
  rpki::up_down::class_response_-syntax, 506
  rpki::up_down::error_response_pdu, 511
  rpki::up_down::multi_uri, 529
  rpki::x509::DeadDrop, 551
  rpki::x509::DER_object, 556
  rpki::x509::PEM_converter, 563
  rpki::xml_utils::sax_handler, 606

__init__.py(3107), 612
__mul__
rpki::sundial::timedelta, 492
__ne__
rpki::resource_set::resource_bag, 374
__neg__
rpki::sundial::timedelta, 492
__new__
rpki::ipaddrs::v4addr, 268
rpki::ipaddrs::v6addr, 270
__pos__
rpki::sundial::timedelta, 492
__radd__
rpki::sundial::datetime, 485
rpki::sundial::timedelta, 492
__rdiv__
rpki::sundial::timedelta, 493
__repr__
rpki::async::iterator, 156
rpki::async::timer, 163
__rfloordiv__
rpki::sundial::timedelta, 493
__rmul__
rpki::sundial::timedelta, 493
__rsub__
rpki::sundial::datetime, 485
rpki::sundial::timedelta, 493
__str__
rpki::https::http_message, 245
rpki::ipaddrs::v4addr, 268
rpki::ipaddrs::v6addr, 270
rpki::publication::report_error_elt, 366
rpki::resource_set::resource_bag, 375
rpki::resource_set::resource_range_-as, 380
rpki::resource_set::resource_range_-ip, 383
rpki::resource_set::resource_set, 390
rpki::resource_set::roa_prefix, 404
rpki::resource_set::roa_prefix_set, 412
rpki::sundial::datetime, 486
rpki::up_down::message_pdu, 525
rpki::up_down::multi_uri, 530
rpki::xml_utils::base_elt, 593
rpki::xml_utils::msg, 603
__sub__
rpki::sundial::datetime, 486
rpki::sundial::timedelta, 493
_add
rpki::rpki_engine::publication_-queue, 448
_bs2long
rpki::resource_set, 72
_cast
rpki::sundial, 77
_comm
rpki::resource_set::resource_set, 390
_exceptions_enabled
rpki::sql::session, 471
_find_xia_uri
rpki::x509, 81
_long2bs
rpki::resource_set, 73
_prefixlen
rpki::resource_set::resource_range_-ip, 383
_raiseExitNow
rpki::async, 52
_regexp
rpki::config::parser, 174
_repl
rpki::config::parser, 172
_rsplit
rpki::resource_set, 73
_wrap_execute
rpki::sql::session, 470
_yes_or_no_prompts
rpki::cli, 54

activate
rpki::rpki_engine::ca_detail_obj, 428
address
rpki::roa::ROAIPAddress, 419
addresses
rpki::roa::ROAIPAddressFamily, 423
addressFamily

rpki::roa::ROAIPAddressFamily, 423
af
rpki::https::http_client, 238
afi
rpki::resource_set::resource_set_-ipv4, 400
rpki::resource_set::resource_set_-ipv6, 402
argv
irbe_cli, 34
asID
rpki::roa::RouteOriginAttestation, 424
asn
rpki::left_right::list_resources_elt, 298
rpki::resource_set::resource_bag, 376
rpki::rpki_engine::roa_obj, 458
assert_pristine
rpki::sql::session, 470
async.py(3107), 612
asynchat::async_chat, 84
asyncore::dispatcher, 84
attributes
rpki::left_right::bsc_elt, 274
rpki::left_right::child_elt, 280
rpki::left_right::list_published_-objects_elt, 292
rpki::left_right::list_received_-resources_elt, 294
rpki::left_right::list_resources_elt, 298
rpki::left_right::list_roa_requests_-elt, 300
rpki::left_right::parent_elt, 308
rpki::left_right::report_error_elt, 313
rpki::left_right::repository_elt, 317
rpki::left_right::self_elt, 327
rpki::publication::client_elt, 341
rpki::publication::config_elt, 348
rpki::publication::publication_-object_elt, 363
rpki::publication::report_error_elt, 367
rpki::xml_utils::base_elt, 595
b
rpki::x509::PEM_converter, 564
base_uri
rpki::publication::client_elt, 341
bits
rpki::ipaddrs::v4addr, 268
rpki::ipaddrs::v6addr, 271
body
rpki::https::http_message, 246
booleans
rpki::left_right::bsc_elt, 274
rpki::left_right::child_elt, 280
rpki::left_right::parent_elt, 308
rpki::left_right::self_elt, 327
rpki::xml_utils::base_elt, 595
bpki_cert
irbe_cli::cmd_elt_mixin, 98
rpki::left_right::child_elt, 280
rpki::left_right::repository_elt, 317
rpki::left_right::self_elt, 327
rpki::publication::client_elt, 342
bpki_cms_cert
irbe_cli::cmd_elt_mixin, 98
rpki::left_right::parent_elt, 308
bpki_cms_glue
irbe_cli::cmd_elt_mixin, 98
rpki::left_right::parent_elt, 308
bpki_crl
irbe_cli::config_elt, 102
bpki_glue
irbe_cli::cmd_elt_mixin, 98
rpki::left_right::child_elt, 280
rpki::left_right::repository_elt, 317
rpki::left_right::self_elt, 327
rpki::publication::client_elt, 342
bpki_https_cert
irbe_cli::cmd_elt_mixin, 98
rpki::left_right::parent_elt, 309
bpki_https_glue
irbe_cli::cmd_elt_mixin, 98
rpki::left_right::parent_elt, 309
bpki_ta
irdbd, 38
pubd::pubd_context, 138

rootd, 46
rpki::rpki_engine::rpkid_context, 465
bsc
rpki::left_right::data_elt, 285
bscs
rpki::left_right::self_elt, 323
buffer
rpki::https::http_stream, 265
build
rpki::x509::ROA, 570
rpki::x509::SignedManifest, 580
build_https_ta_cache
pubd::pubd_context, 137
rpki::https, 59
rpki::rpki_engine::rpkid_context, 463

ca
rpki::rpki_engine::ca_detail_obj, 428
ca_cert_uri
rpki::rpki_engine::ca_detail_obj, 432
ca_detail
rpki::rpki_engine::child_cert_obj, 443
rpki::rpki_engine::revoked_cert_obj, 451
rpki::rpki_engine::roa_obj, 455
ca_detail_id
rpki::rpki_engine::child_cert_obj, 445
rpki::rpki_engine::revoked_cert_obj, 452
rpki::rpki_engine::roa_obj, 458
ca_details
rpki::rpki_engine::ca_obj, 436
ca_from_class_name
rpki::left_right::child_elt, 278
ca_id
rpki::rpki_engine::ca_detail_obj, 432
cache
rpki::sql::session, 472
cache_clear
rpki::sql::session, 470
calculate_SKI
rpki::x509, 81
call_pubd
irbe_cli, 34
rpki::left_right::repository_elt, 316
rpki::rpki_engine::publication_-queue, 448
call_rpkid
irbe_cli, 35
callback
rpki::https::http_request, 252
caller_function
rpki::async::iterator, 156
cancel
rpki::async::timer, 163
cas
rpki::left_right::parent_elt, 306
cb
rpki::async::sync_wrapper, 159
cert
rpki::https::http_client, 238
rpki::https::http_listener, 242
rpki::https::http_queue, 249
rpki::rpki_engine::child_cert_obj, 445
rpki::rpki_engine::roa_obj, 458
rpki::up_down::certificate_elt, 500
cert_url
rpki::up_down::certificate_elt, 500
rpki::up_down::class_elt, 503
certs
rpki::up_down::class_elt, 503
cfg
irbe_cli, 35
irdbd, 38
rootd, 46
rpki::config::parser, 174
cfg_file
irbe_cli, 35
irdbd, 39
pubd, 42
rootd, 46
rpkid, 84
characters
rpki::xml_utils::sax_handler, 606

check_allowed_uri
rpki::publication::client_elt, 340
check_for_updates
rpki::rpki_engine::ca_obj, 436
check_response
rpki::up_down::base_elt, 496
rpki::up_down::error_response_pdu, 511
rpki::up_down::issue_response_pdu, 519
check_valid_rpki
rpki::x509::PKCS10, 566
checkpoint
rpki::rpki_engine::rpkid_context, 463
child
rpki::rpki_engine::child_cert_obj, 443
child_bpki_cert
rootd, 46
child_certs
rpki::left_right::child_elt, 278
rpki::rpki_engine::ca_detail_obj, 428
child_id
rpki::rpki_engine::child_cert_obj, 445
children
rpki::left_right::bsc_elt, 273
rpki::left_right::self_elt, 323
chunk_body
rpki::https::http_stream, 262
chunk_discard_crlf
rpki::https::http_stream, 262
chunk_discard_trailer
rpki::https::http_stream, 262
chunk_handler
rpki::https::http_stream, 265
chunk_header
rpki::https::http_stream, 262
class_name
rpki::up_down::class_elt, 503
rpki::up_down::issue_pdu, 516
rpki::up_down::revoke_pdu, 533
rpki::up_down::revoke_syntax, 536
classes
rpki::up_down::class_response_-syntax, 507
clear
rpki::async::timer, 163
rpki::x509::DER_object, 556
clear_https_ta_cache
pubd::pubd_context, 137
rpki::left_right::child_elt, 280
rpki::publication::client_elt, 342
rpki::rpki_engine::rpkid_context, 463
cli.py(3074), 612
client
rpki::https, 59
rpki::https::http_queue, 249
client_cert
rpki::https::caller, 233
client_getopt
irbe_cli::cmd_elt_mixin, 96
client_handler
pubd::pubd_context, 138
client_key
rpki::https::caller, 233
client_poll
rpki::left_right::self_elt, 323
client_query_bpki_cert
irbe_cli::cmd_elt_mixin, 96
client_query_bpki_cms_cert
irbe_cli::cmd_elt_mixin, 96
client_query_bpki_crl
irbe_cli::config_elt, 102
client_query_bpki_https_cert
irbe_cli::cmd_elt_mixin, 97
client_query_cms_glue
irbe_cli::cmd_elt_mixin, 97
client_query_glue
irbe_cli::cmd_elt_mixin, 97
client_query_https_glue
irbe_cli::cmd_elt_mixin, 97
client_query_signing_cert
irbe_cli::bsc_elt, 87
client_query_signing_cert_crl
irbe_cli::bsc_elt, 87
client_queues
rpki::https, 59
client_reply_decode

irbe_cli::bsc_elt, 87
irbe_cli::reply_elt_mixin, 126
client_reply_show
irbe_cli::reply_elt_mixin, 127
client_ta
irdbd, 39
rootd, 47
client_url_regexp
pubd::pubd_context, 138
close
rpki::https::http_stream, 262
rpki::sql::session, 470
cmd
rpki::https::http_request, 252
cmd::Cmd, 84
cmdloop_with_history
rpki::cli::Cmd, 168, 170
cms_msg
irbe_cli::left_right_proto, 108
irbe_cli::publication_proto, 123
code
rpki::https::http_response, 255
codes
rpki::up_down::error_response_pdu, 512
collect_incoming_data
rpki::https::http_stream, 262
columns
rpki::sql::template, 482
complete_help
rpki::cli::Cmd, 168
completenames
rpki::cli::Cmd, 168
compose_response
rootd, 45
config.py(3107), 613
config_id
rpki::publication::config_elt, 348
connect
rpki::sql::session, 470
construct_sia_uri
rpki::rpki_engine::ca_obj, 437
contains
rpki::resource_set::resource_set, 391
content
rpki::x509::CMS_object, 543
rpki::x509::DER_CMS_object, 553
rpki::x509::XML_CMS_object, 591
content_class
rpki::x509::ROA, 570
rpki::x509::SignedManifest, 581
control_handler
pubd::pubd_context, 138
convert_to_seconds
rpki::sundial::timedelta, 493
create
rpki::rpki_engine::ca_detail_obj, 428
rpki::rpki_engine::ca_obj, 437
rpki::x509::PKCS10, 566
create_ca
rpki::x509::PKCS10, 566
create_top_level
rpki::xml_utils::sax_handler, 607
crl_interval
rpki::left_right::self_elt, 328
crl_published
rpki::rpki_engine::ca_detail_obj, 432
crl_published_callback
rpki::rpki_engine::ca_detail_obj, 428
crl_uri
rpki::rpki_engine::ca_detail_obj, 428
crl_uri_tail
rpki::rpki_engine::ca_detail_obj, 429
cron
rpki::left_right::self_elt, 323
rpki::rpki_engine::rpkid_context, 463
cron_keepalive
rpki::rpki_engine::rpkid_context, 465
cron_period
rpki::rpki_engine::rpkid_context, 465
cron_timeout
rpki::rpki_engine::rpkid_context, 465
cron_timer

rpki::rpki_engine::rpkid_context, 465
cronjob_handler
rpki::rpki_engine::rpkid_context, 463
cross_certify
rpki::x509::X509, 583
cur
irdbd, 39
rpki::sql::session, 472

database
rpki::sql::session, 472
datum_type
rpki::resource_set::resource_range_-as, 380
rpki::resource_set::resource_range_-ipv4, 386
rpki::resource_set::resource_range_-ipv6, 388
db
irdbd, 39
rpki::sql::session, 472
debug
rpki::https::caller, 234
rpki::log, 65
debug_cms_certs
rpki::x509::CMS_object, 543
debug_http
rpki::https, 59
debug_tls_certs
rpki::https, 60
decode
rpki::x509::DER_CMS_object, 553
rpki::x509::XML_CMS_object, 589
default_client_timeout
rpki::https, 60
default_http_version
rpki::https, 60
default_pubd_handler
rpki::left_right::repository_elt, 316
default_section
rpki::config::parser, 175
default_server_timeout
rpki::https, 60
defer
rpki::async, 52
deferred_queue
rpki::async, 53
del_subject_cert
rootd, 45
del_subject_pkcs10
rootd, 45
delete
rpki::rpki_engine::ca_detail_obj, 429
rpki::rpki_engine::ca_obj, 437
rpki::sql::template, 482
DER
rpki::x509::CMS_object, 544
rpki::x509::CRL, 549
rpki::x509::DER_object, 561
rpki::x509::PKCS10, 567
rpki::x509::RSA, 574
rpki::x509::RSApublic, 578
rpki::x509::X509, 586
description
rpki::up_down::error_response_pdu, 512
detach
rpki::https::http_queue, 248
difference
rpki::resource_set::resource_set, 391
dirty
rpki::sql::session, 472
do_EOF
rpki::cli::Cmd, 169
do_exit
rpki::cli::Cmd, 169
do_quit
rpki::cli::Cmd, 170
doit
rpki::async::iterator, 156
done_callback
rpki::async::iterator, 156
dump
rpki::x509::DeadDrop, 551
dump_inbound_cms
rpki::x509::XML_CMS_object, 591
dump_on_verify_failure
rpki::x509::CMS_object, 544
dump_outbound_cms

rpki::x509::XML_CMS_object, 591
dump_to_disk
rpki::x509::XML_CMS_object, 589
dumpasn1
rpki::x509::DER_object, 556
dynamic_ta
rpki::https::http_listener, 242

e
rpki::x509::PEM_converter, 564
earlier
rpki::sundial::datetime, 486
eb
rpki::async::sync_wrapper, 159
econtent_oid
rpki::x509::CMS_object, 544
rpki::x509::ROA, 570
rpki::x509::SignedManifest, 581
rpki::x509::XML_CMS_object, 591
element_name
rpki::left_right::bsc_elt, 275
rpki::left_right::child_elt, 280
rpki::left_right::list_published_-objects_elt, 292
rpki::left_right::list_received_-resources_elt, 294
rpki::left_right::list_resources_elt, 298
rpki::left_right::list_roa_requests_-elt, 300
rpki::left_right::parent_elt, 309
rpki::left_right::report_error_elt, 313
rpki::left_right::repository_elt, 317
rpki::left_right::self_elt, 328
rpki::publication::certificate_elt, 338
rpki::publication::client_elt, 342
rpki::publication::config_elt, 348
rpki::publication::crl_elt, 353
rpki::publication::manifest_elt, 355
rpki::publication::report_error_elt, 367
rpki::publication::roa_elt, 370
elements
rpki::left_right::bsc_elt, 275
rpki::left_right::child_elt, 281
rpki::left_right::parent_elt, 309
rpki::left_right::repository_elt, 318
rpki::left_right::self_elt, 328
rpki::publication::client_elt, 342
rpki::publication::config_elt, 349
rpki::xml_utils::base_elt, 595
empty
rpki::resource_set::resource_bag, 375
rpki::x509::DER_object, 556
emptyline
rpki::cli::Cmd, 169
emptyline_repeats_last_command
rpki::cli::Cmd, 170
enable_trace
rpki::log, 65
encode
rpki::x509::DER_CMS_object, 553
rpki::x509::XML_CMS_object, 589
encoding
rpki::left_right::cms_msg, 283
rpki::publication::cms_msg, 345
rpki::up_down::cms_msg, 509
endElement
rpki::left_right::child_elt, 279
rpki::publication::client_elt, 340
rpki::publication::publication_-object_elt, 361
rpki::up_down::base_elt, 496
rpki::up_down::certificate_elt, 499
rpki::up_down::class_elt, 502
rpki::up_down::error_response_pdu, 511
rpki::up_down::issue_pdu, 515
rpki::xml_utils::base_elt, 593
rpki::xml_utils::data_elt, 598
rpki::xml_utils::msg, 603
rpki::xml_utils::sax_handler, 607
rpki::xml_utils::text_elt, 610
endElementNS
rpki::xml_utils::sax_handler, 607
enforce_strict_up_down_xml_sender
rpki::left_right, 63
EOF_exits_command_loop
rpki::cli::Cmd, 170
err
rpki::async::sync_wrapper, 159

errback
rpki::async::timer, 163, 165
rpki::https::http_request, 253
error
rpki::log, 66
error_code
rpki::left_right::report_error_elt, 313
rpki::publication::report_error_elt, 367
error_text
rpki::left_right::report_error_elt, 313
rpki::publication::report_error_elt, 367
event_loop
rpki::async, 52
Exception, 84
exceptions
rpki::up_down::error_response_pdu, 512
exceptions.py(2907), 613
excludes
irbe_cli::bsc_elt, 88
irbe_cli::cmd_elt_mixin, 98
irbe_cli::list_published_objects_elt, 112
irbe_cli::list_received_resources_elt, 114
execute
rpki::sql::session, 470
executemany
rpki::sql::session, 471
exit_event_loop
rpki::async, 52
ExitNow
rpki::async, 53
expect_close
rpki::https::http_client, 238
rpki::https::http_server, 258
expired
rpki::x509::X509, 584
expires
rpki::rpki_engine::revoked_cert_obj, 452
explicitVersion
rpki::manifest::Manifest, 335
rpki::roa::RouteOriginAttestation, 424
extract
rpki::x509::CMS_object, 542

fetch
rpki::publication::config_elt, 347
rpki::rpki_engine::child_cert_obj, 444
fetch_active
rpki::rpki_engine::ca_obj, 437
fetch_deprecated
rpki::rpki_engine::ca_obj, 438
fetch_issue_response_candidates
rpki::rpki_engine::ca_obj, 438
fetch_pending
rpki::rpki_engine::ca_obj, 438
fetch_revoked
rpki::rpki_engine::ca_obj, 438
fetchall
rpki::sql::session, 471
file
rpki::manifest::FileAndHash, 332
fileHashAlg
rpki::manifest::Manifest, 335
fileList
rpki::manifest::Manifest, 335
filename
rpki::config::parser, 175
filename_complete
rpki::cli::Cmd, 169
find_handler
rpki::https::http_server, 257
format
rpki::https::http_message, 245
format_first_line
rpki::https::http_request, 252
rpki::https::http_response, 255
formats
rpki::x509::CMS_object, 544
rpki::x509::CRL, 549
rpki::x509::DER_object, 561
rpki::x509::PKCS10, 567
rpki::x509::RSA, 574
rpki::x509::RSApublic, 578
rpki::x509::X509, 586

found_terminator
rpki::https::http_stream, 262
from_bytes
rpki::ipaddrs::v4addr, 268
rpki::ipaddrs::v6addr, 270
from_exception
rpki::left_right::report_error_elt, 312
rpki::publication::report_error_elt, 366
from_resource_bag
rpki::up_down::class_elt, 502
from_rfc3779_tuples
rpki::resource_set::resource_bag, 375
from_sql
rpki::resource_set::resource_set, 391
rpki::resource_set::roa_prefix_set, 412
rpki::sundial::datetime, 486
rpki::x509::DER_object, 557
fromASN1tuple
rpki::sundial::datetime, 486
fromdatetime
rpki::sundial::datetime, 486
fromGeneralizedTime
rpki::sundial::datetime, 487
fromtimedelta
rpki::sundial::timedelta, 493
fromUTCTime
rpki::sundial::datetime, 487
fromXMLtime
rpki::sundial::datetime, 487
func
rpki::async::sync_wrapper, 159

gAKI
rpki::x509::DER_object, 557
gc_debug
rpki::async::timer, 165
gctx
rpki::rpki_engine::ca_detail_obj, 432
rpki::rpki_engine::ca_obj, 440
rpki::rpki_engine::child_cert_obj, 445
rpki::rpki_engine::revoked_cert_obj, 452
rpki::rpki_engine::roa_obj, 459
rpki::sql::sql_persistent, 479
generate
rpki::rpki_engine::roa_obj, 456
rpki::x509::CRL, 547
rpki::x509::RSA, 573
generate_crl
rpki::rpki_engine::ca_detail_obj, 429
generate_manifest
rpki::rpki_engine::ca_detail_obj, 429
generate_manifest_cert
rpki::rpki_engine::ca_detail_obj, 429
get
rpki::config::parser, 173
get_3779resources
rpki::x509::DER_object, 557
get_AIA
rpki::x509::DER_object, 557
get_aia_uri
rpki::x509::DER_object, 557
get_AKI
rpki::x509::DER_object, 558
get_Base64
rpki::x509::DER_object, 558
get_basicConstraints
rpki::x509::DER_object, 558
get_buffer
rpki::https::http_stream, 263
get_content
rpki::x509::CMS_object, 542
get_DER
rpki::x509::CMS_object, 542
rpki::x509::CRL, 547
rpki::x509::DER_object, 558
rpki::x509::PKCS10, 567
rpki::x509::RSA, 573
rpki::x509::RSApublic, 577
rpki::x509::X509, 584
get_PEM
rpki::x509::DER_object, 558
get_POW

rpki::x509::CMS_object, 542
rpki::x509::CRL, 548
rpki::x509::RSA, 573
rpki::x509::RSApublic, 577
rpki::x509::X509, 584
get_POWpkix
rpki::x509::CRL, 548
rpki::x509::PKCS10, 567
rpki::x509::X509, 584
get_public_DER
rpki::x509::RSA, 574
get_root_cert
rootd, 45
get_RSApublic
rpki::x509::RSA, 574
get_SIA
rpki::x509::DER_object, 559
get_sia_directory_uri
rpki::x509::DER_object, 559
get_sia_manifest_uri
rpki::x509::DER_object, 559
get_SKI
rpki::up_down::revoke_pdu, 532
rpki::x509::DER_object, 559
rpki::x509::RSA, 574
rpki::x509::RSApublic, 577
get_subject_cert
rootd, 45
get_subject_pkcs10
rootd, 45
getboolean
rpki::config::parser, 173
getint
rpki::config::parser, 173
getIssuer
rpki::x509::CRL, 548
rpki::x509::X509, 584
getlong
rpki::config::parser, 173
getNextUpdate
rpki::x509::CRL, 548
rpki::x509::SignedManifest, 580
getNotAfter
rpki::x509::X509, 584
getNotBefore
rpki::x509::X509, 585
getPublicKey
rpki::x509::PKCS10, 567
rpki::x509::X509, 585
getSerial
rpki::x509::X509, 585
getSubject
rpki::x509::X509, 585
getThisUpdate
rpki::x509::CRL, 548
rpki::x509::SignedManifest, 580
gSKI
rpki::x509::DER_object, 559

hAKI
rpki::x509::DER_object, 560
handle_accept
rpki::https::http_listener, 242
handle_body
rpki::https::http_stream, 263
handle_close
rpki::https::http_client, 236
rpki::https::http_stream, 263
handle_connect
rpki::https::http_client, 237
handle_dispatch
irdbd, 39
handle_error
rpki::https::http_client, 237
rpki::https::http_listener, 242
rpki::https::http_stream, 263
handle_list_resources
irdbd, 38
handle_list_roa_requests
irdbd, 38
handle_message
rpki::https::http_client, 237
rpki::https::http_server, 257
handle_no_content_length
rpki::https::http_client, 237
rpki::https::http_server, 258
handle_read
rpki::https::http_stream, 263
handle_timeout
rpki::https::http_client, 237
rpki::https::http_stream, 263
handle_write

rpki::https::http_stream, 263
handler
irdbd, 38
rpki::async::gc_summary, 153
rpki::async::timer, 164, 166
handler_common
pubd::pubd_context, 138
handlers
irdbd, 39
rootd, 47
rpki::https::http_listener, 242
rpki::https::http_server, 258
rpki::rpki_engine::publication_-queue, 449
handles
rpki::left_right::bsc_elt, 275
rpki::left_right::child_elt, 281
rpki::left_right::data_elt, 287
rpki::left_right::parent_elt, 309
rpki::left_right::repository_elt, 318
rpki::left_right::self_elt, 328
has_option
rpki::config::parser, 173
has_section
rpki::config::parser, 174
hash
rpki::manifest::FileAndHash, 332
have_readline
rpki::cli, 54
headers
rpki::https::http_message, 246
help_help
rpki::cli::Cmd, 169
histfile
rpki::cli::Cmd, 170
host
irdbd, 40
rootd, 47
hostport
rpki::https::http_client, 238
rpki::https::http_queue, 249
hSKI
rpki::x509::DER_object, 560
https.py(3131), 615
https_server_host
pubd::pubd_context, 139
rootd, 47
rpki::rpki_engine::rpkid_context, 466
https_server_port
pubd::pubd_context, 139
rootd, 47
rpki::rpki_engine::rpkid_context, 466
https_ta_cache
pubd::pubd_context, 139
rpki::rpki_engine::rpkid_context, 466

identchars
rpki::cli::Cmd, 170
ignore
rpki::async::iterator, 156
index
rpki::sql::template, 482
info
rpki::log, 66
inherit
rpki::resource_set::resource_set, 392
rpki::resource_set::resource_set_as, 395
rpki::resource_set::resource_set_ip, 398
inherit_token
rpki::resource_set, 73
init
rpki::log, 65
initial_delay
rpki::rpki_engine::rpkid_context, 466
initiate_send
rpki::https::http_stream, 264
insert
rpki::sql::template, 482
intersection
rpki::resource_set::resource_bag, 375
rpki::resource_set::resource_set, 391
interval
rpki::async::gc_summary, 153
ipAddrBlocks

rpki::roa::RouteOriginAttestation, 424
ipaddrs.py(2424), 616
ipv4
rpki::left_right::list_resources_elt, 298
rpki::left_right::list_roa_requests_-elt, 301
rpki::rpki_engine::roa_obj, 459
ipv6
rpki::left_right::list_resources_elt, 298
rpki::left_right::list_roa_requests_-elt, 301
rpki::rpki_engine::roa_obj, 459
irbe_cert
pubd::pubd_context, 139
rpki::rpki_engine::rpkid_context, 466
irbe_cli, 32
argv, 34
call_pubd, 34
call_rpkid, 35
cfg, 35
cfg_file, 35
pem_out, 35
q_msg, 35
q_msg_left_right, 36
q_msg_publication, 36
q_pdu, 36
top_opts, 36
usage, 34
usage_fill, 36
verbose, 36
irbe_cli.py(3107), 616
irbe_cli::bsc_elt, 85
client_query_signing_cert, 87
client_query_signing_cert_crl, 87
client_reply_decode, 87
excludes, 88
signing_cert, 88
signing_cert_crl, 88
irbe_cli::certificate_elt, 88
irbe_cli::child_elt, 90
irbe_cli::client_elt, 92
irbe_cli::cmd_elt_mixin, 94
bpki_cert, 98
bpki_cms_cert, 98
bpki_cms_glue, 98
bpki_glue, 98
bpki_https_cert, 98
bpki_https_glue, 98
client_getopt, 96
client_query_bpki_cert, 96
client_query_bpki_cms_cert, 96
client_query_bpki_https_cert, 97
client_query_cms_glue, 97
client_query_glue, 97
client_query_https_glue, 97
excludes, 98
is_cmd, 99
usage, 97
irbe_cli::cmd_msg_mixin, 99
usage, 100
irbe_cli::config_elt, 100
bpki_crl, 102
client_query_bpki_crl, 102
irbe_cli::crl_elt, 102
irbe_cli::left_right_cms_msg, 104
saxify, 105
irbe_cli::left_right_msg, 105
pdus, 107
irbe_cli::left_right_proto, 107
cms_msg, 108
msg, 108
irbe_cli::left_right_sax_handler, 109
pdu, 110
irbe_cli::list_published_objects_elt, 110
excludes, 112
irbe_cli::list_received_resources_elt, 112
excludes, 114
irbe_cli::manifest_elt, 114
irbe_cli::parent_elt, 116
irbe_cli::publication_cms_msg, 118
saxify, 120
irbe_cli::publication_msg, 120
pdus, 122
irbe_cli::publication_proto, 122
cms_msg, 123
msg, 123
irbe_cli::publication_sax_handler, 124
pdu, 125

irbe_cli::reply_elt_mixin, 125
client_reply_decode, 126
client_reply_show, 127
is_cmd, 127
irbe_cli::report_error_elt, 127
irbe_cli::repository_elt, 128
irbe_cli::roa_elt, 130
irbe_cli::self_elt, 132
irbe_cli::UsageWrapper, 134
__call__, 135
irdb_cert
rpki::rpki_engine::rpkid_context, 466
irdb_query
rpki::rpki_engine::rpkid_context, 464
irdb_query_child_resources
rpki::rpki_engine::rpkid_context, 464
irdb_query_roa_requests
rpki::rpki_engine::rpkid_context, 464
irdb_url
rpki::rpki_engine::rpkid_context, 466
irdbd, 37
bpki_ta, 38
cfg, 38
cfg_file, 39
client_ta, 39
cur, 39
db, 39
handle_dispatch, 39
handle_list_resources, 38
handle_list_roa_requests, 38
handler, 38
handlers, 39
host, 40
irdbd_cert, 40
irdbd_key, 40
port, 40
rpkid_cert, 40
server_cert, 40
startup_msg, 40
u, 41
irdbd.py(2913), 617
irdbd_cert
irdbd, 40
irdbd_key
irdbd, 40
is_CA
rpki::x509::DER_object, 560
is_cmd
irbe_cli::cmd_elt_mixin, 99
irbe_cli::reply_elt_mixin, 127
is_query
rpki::xml_utils::msg, 603
is_reply
rpki::xml_utils::msg, 603
is_set
rpki::async::timer, 164
issubset
rpki::resource_set::resource_set, 391
issue
rpki::rpki_engine::ca_detail_obj, 430
rpki::x509::X509, 585
issue_ee
rpki::rpki_engine::ca_detail_obj, 430
issue_subject_cert_maybe
rootd, 45
issuer
rpki::up_down::class_elt, 504
issuperset
rpki::resource_set::resource_set, 392
item_callback
rpki::async::iterator, 156
iterator
rpki::async::iterator, 156

key
rpki::https::http_client, 238
rpki::https::http_listener, 243
rpki::https::http_queue, 249

last_crl_sn
rpki::rpki_engine::ca_obj, 440
last_issued_sn
rpki::rpki_engine::ca_obj, 440
last_manifest_sn
rpki::rpki_engine::ca_obj, 440

lastrowid
rpki::sql::session, 471
later
rpki::sundial::datetime, 487
latest_ca_cert
rpki::rpki_engine::ca_detail_obj, 432
latest_crl
rpki::rpki_engine::ca_detail_obj, 432
latest_manifest
rpki::rpki_engine::ca_detail_obj, 433
latest_manifest_cert
rpki::rpki_engine::ca_detail_obj, 433
left_right
rpki::relaxng, 70
left_right.py(3107), 618
left_right_handler
rpki::rpki_engine::rpkid_context, 464
log
rpki::https::http_listener, 243
rpki::https::http_queue, 250
rpki::https::http_stream, 265
log.py(3107), 619
log_cert
rpki::https::http_stream, 264
log_method
rpki::https, 59
log_query
rootd::message_pdu, 148
rpki::up_down::message_pdu, 525
long, 135
looks_like_PEM
rpki::x509::PEM_converter, 563

maildir
rpki::x509::DeadDrop, 551
main
pubd, 42
rpkid, 83
make_b64elt
rpki::up_down::base_elt, 496
rpki::xml_utils::base_elt, 594
make_elt
rpki::up_down::base_elt, 496
rpki::xml_utils::base_elt, 594
make_pdu
rpki::xml_utils::base_elt, 594
make_prefix
rpki::resource_set::resource_range_-ip, 383
make_publish
rpki::publication::publication_-object_elt, 361
make_query
rpki::up_down::message_pdu, 525
make_reply
rpki::left_right::list_published_-objects_elt, 291
rpki::left_right::list_received_-resources_elt, 294
rpki::xml_utils::data_elt, 598
make_reply_clone_hook
rpki::left_right::data_elt, 285
rpki::xml_utils::data_elt, 598
make_withdraw
rpki::publication::publication_-object_elt, 362
manifest.py(2424), 619
manifest_private_key_id
rpki::rpki_engine::ca_detail_obj, 433
manifest_public_key
rpki::rpki_engine::ca_detail_obj, 433
manifest_published
rpki::rpki_engine::ca_detail_obj, 433
manifest_published_callback
rpki::rpki_engine::ca_detail_obj, 430
manifest_uri
rpki::rpki_engine::ca_detail_obj, 430
manifestNumber
rpki::manifest::Manifest, 335
map
rpki::sql::template, 483
max

rpki::resource_set::resource_range, 378
rpki::resource_set::roa_prefix, 404
max_prefixlen
rpki::resource_set::roa_prefix, 405
maxLength
rpki::roa::ROAIPAddress, 419
min
rpki::resource_set::resource_range, 378
rpki::resource_set::resource_range_-as, 381
rpki::resource_set::roa_prefix, 405
msg
irbe_cli::left_right_proto, 108
irbe_cli::publication_proto, 123
rpki::https::http_stream, 265
msgs
rpki::rpki_engine::publication_-queue, 449
multiget
rpki::config::parser, 174

name
rpki::left_right::sax_handler, 320
rpki::publication::sax_handler, 372
rpki::up_down::sax_handler, 539
name2oid
rpki::oids, 68
name2type
rootd::message_pdu, 148
rpki::up_down::message_pdu, 527
next_crl_number
rpki::rpki_engine::ca_obj, 438
next_manifest_number
rpki::rpki_engine::ca_obj, 439
next_serial_number
rpki::rpki_engine::ca_obj, 439
nextUpdate
rpki::manifest::Manifest, 335
rpki::rpki_engine::ca_detail_obj, 433
normalize_chain
rpki::x509::X509, 586
normalize_headers
rpki::https::http_message, 245
note
rpki::log, 66
now
rpki::sundial, 77
nsmap
rpki::left_right::left_right_-namespace, 288
rpki::publication::publication_-namespace, 359
rpki::up_down, 79

obj
rpki::left_right::list_published_-objects_elt, 292
object, 135
oid2name
rpki::oids, 68
oids.py(2424), 620
other_clear
rpki::x509::CMS_object, 544
rpki::x509::DER_object, 561
oversized
rpki::resource_set::resource_bag, 375

parent
rpki::rpki_engine::ca_obj, 439
parent_id
rpki::rpki_engine::ca_obj, 440
parent_resource_class
rpki::rpki_engine::ca_obj, 440
parents
rpki::left_right::bsc_elt, 273
rpki::left_right::child_elt, 279
rpki::left_right::repository_elt, 317
rpki::left_right::self_elt, 323
parse
rpki::sundial::timedelta, 494
parse_first_line
rpki::https::http_request, 252
rpki::https::http_response, 255
parse_from_wire
rpki::https::http_message, 245
parse_rfc3779_tuple
rpki::resource_set::resource_set_as, 394

rpki::resource_set::resource_set_ip, 397
parse_str
rpki::resource_set::resource_set_as, 394
rpki::resource_set::resource_set_ip, 397
rpki::resource_set::roa_prefix_set, 412
parse_type
rpki::https::http_client, 239
rpki::https::http_server, 259
parse_version
rpki::https::http_message, 246
password
rpki::sql::session, 472
path
rpki::https::http_request, 253
payload
rpki::publication::publication_-object_elt, 363
rpki::up_down::message_pdu, 527
payload_type
rpki::publication::certificate_elt, 338
rpki::publication::crl_elt, 353
rpki::publication::manifest_elt, 355
rpki::publication::publication_-object_elt, 363
rpki::publication::roa_elt, 370
pdu
irbe_cli::left_right_sax_handler, 110
irbe_cli::publication_sax_handler, 125
rootd::sax_handler, 152
rpki::left_right::sax_handler, 320
rpki::publication::sax_handler, 372
rpki::up_down::sax_handler, 539
pdus
irbe_cli::left_right_msg, 107
irbe_cli::publication_msg, 122
rpki::left_right::msg, 303
rpki::publication::msg, 357
pem_converter
rpki::x509::CMS_object, 545
rpki::x509::CRL, 549
rpki::x509::DER_object, 561
rpki::x509::PKCS10, 568
rpki::x509::ROA, 570
rpki::x509::RSA, 575
rpki::x509::RSApublic, 578
rpki::x509::SignedManifest, 581
rpki::x509::X509, 586
pem_out
irbe_cli, 35
persistent
rpki::https::http_message, 246
pid
rpki::log, 66
rpki::x509::DeadDrop, 551
ping
rpki::sql::session, 471
pkcs10
rpki::up_down::issue_pdu, 516
pkcs10_request
rpki::left_right::bsc_elt, 275
PKIX_threshhold
rpki::sundial::datetime, 489
port
irdbd, 40
rootd, 47
POW
rpki::x509::CMS_object, 545
rpki::x509::CRL, 549
rpki::x509::RSA, 575
rpki::x509::RSApublic, 578
rpki::x509::X509, 587
POWify_OID
rpki::x509, 81
POWpkix
rpki::x509::CRL, 549
rpki::x509::PKCS10, 568
rpki::x509::X509, 587
prefix
rpki::resource_set::roa_prefix, 405
prefix_type
rpki::resource_set::roa_prefix_set_-ipv4, 415
rpki::resource_set::roa_prefix_set_-ipv6, 417
prefixlen
rpki::resource_set::roa_prefix, 406
pretty_print_content

rpki::x509::XML_CMS_object, 590
print_on_der_error
rpki::x509::CMS_object, 545
priority
rpki::log::logger, 330
private_key_id
rpki::left_right::bsc_elt, 275
rpki::rpki_engine::ca_detail_obj, 433
profile
pubd, 42
rpkid, 84
proto
rpki::https::caller, 234
pubd, 41
cfg_file, 42
main, 42
profile, 42
pubd.py(3107), 620
pubd::pubd_context, 135
__init__, 137
bpki_ta, 138
build_https_ta_cache, 137
clear_https_ta_cache, 137
client_handler, 138
client_url_regexp, 138
control_handler, 138
handler_common, 138
https_server_host, 139
https_server_port, 139
https_ta_cache, 139
irbe_cert, 139
pubd_cert, 139
pubd_key, 139
publication_base, 139
publication_multimodule, 140
sql, 140
pubd_cert
pubd::pubd_context, 139
pubd_key
pubd::pubd_context, 139
public_key
rpki::rpki_engine::ca_detail_obj, 434
publication
rpki::relaxng, 70
publication.py(3107), 621
publication_base
pubd::pubd_context, 139
publication_kludge_base
rpki::rpki_engine::rpkid_context, 467
publication_multimodule
pubd::pubd_context, 140
publish
rpki::rpki_engine::publication_-queue, 448
published
rpki::rpki_engine::child_cert_obj, 445
rpki::rpki_engine::roa_obj, 459
published_callback
rpki::rpki_engine::child_cert_obj, 444
rpki::rpki_engine::roa_obj, 456
pydatetime::datetime, 140
pydatetime::timedelta, 140

q_msg
irbe_cli, 35
q_msg_left_right
irbe_cli, 36
q_msg_publication
irbe_cli, 36
q_pdu
irbe_cli, 36
query
rpki::up_down::issue_pdu, 515
rpki::up_down::list_pdu, 521
rpki::up_down::revoke_pdu, 532
rpki::xml_utils::msg, 603
query_up_down
rpki::left_right::parent_elt, 306
queue
rpki::async::timer, 166
rpki::https::http_client, 239
rpki::https::http_queue, 250

raise_if_error
rpki::publication::publication_-object_elt, 362

rpki::publication::report_error_elt, 367
range_type
rpki::resource_set::resource_set_as, 395
rpki::resource_set::resource_set_-ipv4, 400
rpki::resource_set::resource_set_-ipv6, 402
rpki::resource_set::roa_prefix_ipv4, 408
rpki::resource_set::roa_prefix_ipv6, 410
read_attrs
rpki::xml_utils::base_elt, 594
readable
rpki::https::http_stream, 264
reason
rpki::https::http_response, 255
recipient
rpki::up_down::message_pdu, 527
recv
rpki::https::http_stream, 264
regen_margin
rpki::left_right::self_elt, 328
regenerate
rpki::rpki_engine::roa_obj, 456
regenerate_crls_and_manifests
rpki::left_right::self_elt, 324
regexp
rpki::sundial::timedelta, 494
reissue
rpki::rpki_engine::child_cert_obj, 444
rekey
rpki::rpki_engine::ca_obj, 439
relaxng.py(3110), 621
replace
rpki::rpki_engine::publication_-queue, 449
reply
rpki::xml_utils::msg, 604
repositories
rpki::left_right::bsc_elt, 274
rpki::left_right::self_elt, 324
rpki::rpki_engine::publication_-queue, 449
repository
rpki::left_right::parent_elt, 307
req_resource_set_as
rpki::up_down::certificate_elt, 500
rpki::up_down::issue_pdu, 516
req_resource_set_ipv4
rpki::up_down::certificate_elt, 500
rpki::up_down::issue_pdu, 516
req_resource_set_ipv6
rpki::up_down::certificate_elt, 500
rpki::up_down::issue_pdu, 516
request
rpki::https::http_queue, 248
require_crls
rpki::x509::CMS_object, 545
res
rpki::async::sync_wrapper, 160
resource_set.py(3107), 622
resource_set_as
rpki::up_down::class_elt, 504
resource_set_ipv4
rpki::up_down::class_elt, 504
resource_set_ipv6
rpki::up_down::class_elt, 504
resource_set_notafter
rpki::up_down::class_elt, 504
resource_set_type
rpki::resource_set::roa_prefix_set_-ipv4, 415
rpki::resource_set::roa_prefix_set_-ipv6, 417
restart
rpki::https::http_queue, 249
rpki::https::http_stream, 264
result
rpki::xml_utils::sax_handler, 608
retried
rpki::https::http_request, 253
retry_read
rpki::https::http_client, 239
rpki::https::http_server, 259
rpki::https::http_stream, 265
retry_write
rpki::https::http_client, 239

rpki::https::http_server, 259
rpki::https::http_stream, 265
return_result
rpki::https::http_queue, 249
revoke
rpki::rpki_engine::ca_detail_obj, 430
rpki::rpki_engine::ca_obj, 439
rpki::rpki_engine::child_cert_obj, 444
rpki::rpki_engine::revoked_cert_obj, 451
rpki::rpki_engine::roa_obj, 456
revoked
rpki::rpki_engine::revoked_cert_obj, 452
revoked_certs
rpki::rpki_engine::ca_detail_obj, 431
roa
rpki::rpki_engine::roa_obj, 459
roa.py(2424), 623
roas
rpki::left_right::self_elt, 324
rpki::rpki_engine::ca_detail_obj, 431
root_newer_than_subject
rootd, 45
rootd, 42
bpki_ta, 46
cfg, 46
cfg_file, 46
child_bpki_cert, 46
client_ta, 47
compose_response, 45
del_subject_cert, 45
del_subject_pkcs10, 45
get_root_cert, 45
get_subject_cert, 45
get_subject_pkcs10, 45
handlers, 47
host, 47
https_server_host, 47
https_server_port, 47
issue_subject_cert_maybe, 45
port, 47
root_newer_than_subject, 45
rootd_bpki_cert, 47
rootd_bpki_crl, 48
rootd_bpki_key, 48
rpki_base_uri, 48
rpki_class_name, 48
rpki_root_cert, 48
rpki_root_cert_file, 48
rpki_root_cert_uri, 48
rpki_root_crl, 49
rpki_root_dir, 49
rpki_root_key, 49
rpki_root_manifest, 49
rpki_subject_cert, 49
rpki_subject_lifetime, 49
rpki_subject_pkcs10, 50
rpki_subject_regen, 50
server_cert, 50
set_subject_cert, 46
set_subject_pkcs10, 46
up_down_handler, 46
rootd.py(2913), 623
rootd::cms_msg, 140
saxify, 142
rootd::issue_pdu, 142
serve_pdu, 144
rootd::list_pdu, 144
serve_pdu, 146
rootd::message_pdu, 146
log_query, 148
name2type, 148
type2name, 148
rootd::revoke_pdu, 149
serve_pdu, 150
rootd::sax_handler, 150
pdu, 152
rootd_bpki_cert
rootd, 47
rootd_bpki_crl
rootd, 48
rootd_bpki_key
rootd, 48
rpki, 50
rpki.async, 51
rpki.cli, 53
rpki.config, 54

rpki.exceptions, 55
rpki.https, 57
rpki.ipaddrs, 61
rpki.left_right, 62
rpki.log, 63
rpki.manifest, 67
rpki.oids, 67
rpki.publication, 69
rpki.relaxng, 70
rpki.resource_set, 71
rpki.roa, 74
rpki.rpki_engine, 75
rpki.sql, 75
rpki.sundial, 76
rpki.up_down, 78
rpki.x509, 80
rpki.xml_utils, 82
rpki::async
    _raiseExitNow, 52
    defer, 52
    deferred_queue, 53
    event_loop, 52
    exit_event_loop, 52
    ExitNow, 53
    run_deferred, 52
rpki::async::gc_summary, 152
    __init__, 153
    handler, 153
    interval, 153
    threshold, 153
    timer, 153
rpki::async::iterator, 154
    __call__, 155
    __init__, 155
    __repr__, 156
    caller_function, 156
    doit, 156
    done_callback, 156
    ignore, 156
    item_callback, 156
    iterator, 156
    unwind_stack, 157
rpki::async::sync_wrapper, 157
    __call__, 159
    __init__, 159
    cb, 159
    eb, 159
    err, 159
    func, 159
    res, 160
rpki::async::timer, 160
    __cmp__, 163
    __del__, 163
    __init__, 163
    __repr__, 163
    cancel, 163
    clear, 163
    errback, 163, 165
    gc_debug, 165
    handler, 164, 166
    is_set, 164
    queue, 166
    run_debug, 166
    runq, 164
    seconds_until_wakeup, 164
    set, 164
    set_errback, 165
    set_handler, 165
    trace, 165
    when, 166
rpki::cli
    _yes_or_no_prompts, 54
    have_readline, 54
    yes_or_no, 54
rpki::cli::Cmd, 166
    __init__, 168
    cmdloop_with_history, 168, 170
    complete_help, 168
    completenames, 168
    do_EOF, 169
    do_exit, 169
    do_quit, 170
    emptyline, 169
    emptyline_repeats_last_command, 170
    EOF_exits_command_loop, 170
    filename_complete, 169
    help_help, 169
    histfile, 170
    identchars, 170
rpki::config::parser, 170
    __init__, 172

_regexp, 174
_repl, 172
cfg, 174
default_section, 175
filename, 175
get, 173
getboolean, 173
getint, 173
getlong, 173
has_option, 173
has_section, 174
multiget, 174
set_global_flags, 174
rpki::exceptions::BadClassNameSyntax, 175
rpki::exceptions::BadClientURL, 176
rpki::exceptions::BadContactURL, 177
rpki::exceptions::BadExtension, 178
rpki::exceptions::BadIRDBReply, 179
rpki::exceptions::BadIssueResponse, 180
rpki::exceptions::BadPKCS10, 181
rpki::exceptions::BadPublicationReply, 182
rpki::exceptions::BadQuery, 183
rpki::exceptions::BadSender, 184
rpki::exceptions::BadStatusCode, 185
rpki::exceptions::BadURISyntax, 186
rpki::exceptions::BSCNotFound, 187
rpki::exceptions::BSCNotReady, 188
rpki::exceptions::ChildNotFound, 189
rpki::exceptions::ClassNameMismatch, 190
rpki::exceptions::ClassNameUnknown, 191
rpki::exceptions::ClientNotFound, 192
rpki::exceptions::CMSContentNotSet, 193
rpki::exceptions::CMSCRLNotSet, 195
rpki::exceptions::CMSVerificationFailed, 196
rpki::exceptions::DBConsistancyError, 197
rpki::exceptions::DERObjectConversionError, 198
rpki::exceptions::DuplicateObject, 199
rpki::exceptions::EmptyPEM, 200
rpki::exceptions::EmptyROAPrefixList, 201
rpki::exceptions::ForbiddenURI, 202
rpki::exceptions::HandleTranslationError, 203
rpki::exceptions::HTTPRequestFailed, 204
rpki::exceptions::HTTPSBadVersion, 205
rpki::exceptions::HTTPSClientAborted, 206
rpki::exceptions::HTTPSUnexpectedState, 207
rpki::exceptions::MissingCMSCRL, 208
rpki::exceptions::MissingCMSEEcert, 209
rpki::exceptions::MultipleTLSEECert, 210
rpki::exceptions::MustBePrefix, 211
rpki::exceptions::NoActiveCA, 212
rpki::exceptions::NoCoveringCertForROA, 213
rpki::exceptions::NoObjectAtURI, 214
rpki::exceptions::NotACertificateChain, 215
rpki::exceptions::NotFound, 216
rpki::exceptions::NotImplementedYet, 217
rpki::exceptions::NotInDatabase, 218
rpki::exceptions::ReceivedTLSCACert, 219
rpki::exceptions::RPKI_Exception, 221
rpki::exceptions::ServerShuttingDown, 222
rpki::exceptions::SKIMismatch, 223
rpki::exceptions::SubprocessError, 224
rpki::exceptions::TLSValidationError, 225
rpki::exceptions::UnexpectedCMSCerts, 227
rpki::exceptions::UnexpectedCMSCRLs, 228
rpki::exceptions::UnparsableCMSDER, 229
rpki::exceptions::UpstreamError, 230
rpki::exceptions::WrongEContentType, 231

rpki::https
build_https_ta_cache, 59
client, 59
client_queues, 59
debug_http, 59
debug_tls_certs, 60
default_client_timeout, 60
default_http_version, 60
default_server_timeout, 60
log_method, 59
rpki_content_type, 60
server, 59
supported_address_families, 60
want_persistent_client, 60
want_persistent_server, 61
rpki::https::caller, 232
__call__, 233
__init__, 233
client_cert, 233
client_key, 233
debug, 234
proto, 234
server_cert, 234
server_ta, 234
url, 234
rpki::https::http_client, 234
__init__, 236
af, 238
cert, 238
expect_close, 238
handle_close, 236
handle_connect, 237
handle_error, 237
handle_message, 237
handle_no_content_length, 237
handle_timeout, 237
hostport, 238
key, 238
parse_type, 239
queue, 239
retry_read, 239
retry_write, 239
send_request, 237
set_state, 237
start, 238
state, 239
ta, 239
timeout, 239
tls, 240
tls_connect, 238
rpki::https::http_listener, 240
__init__, 242
cert, 242
dynamic_ta, 242
handle_accept, 242
handle_error, 242
handlers, 242
key, 243
log, 243
ta, 243
rpki::https::http_message, 243
__init__, 245
__str__, 245
body, 246
format, 245
headers, 246
normalize_headers, 245
parse_from_wire, 245
parse_version, 246
persistent, 246
software_name, 246
version, 246
rpki::https::http_queue, 247
__init__, 248
cert, 249
client, 249
detach, 248
hostport, 249
key, 249
log, 250
queue, 250
request, 248
restart, 249
return_result, 249
send_request, 249
ta, 250
rpki::https::http_request, 250
__init__, 252
callback, 252
cmd, 252
errback, 253
format_first_line, 252

parse_first_line, 252
path, 253
retried, 253
rpki::https::http_response, 253
__init__, 255
code, 255
format_first_line, 255
parse_first_line, 255
reason, 255
rpki::https::http_server, 256
__init__, 257
expect_close, 258
find_handler, 257
handle_message, 257
handle_no_content_length, 258
handlers, 258
parse_type, 259
retry_read, 259
retry_write, 259
send_error, 258
send_message, 258
send_reply, 258
timeout, 259
tls, 259
tls_accept, 258
rpki::https::http_stream, 260
__init__, 262
buffer, 265
chunk_body, 262
chunk_discard_crlf, 262
chunk_discard_trailer, 262
chunk_handler, 265
chunk_header, 262
close, 262
collect_incoming_data, 262
found_terminator, 262
get_buffer, 263
handle_body, 263
handle_close, 263
handle_error, 263
handle_read, 263
handle_timeout, 263
handle_write, 263
initiate_send, 264
log, 265
log_cert, 264
msg, 265
readable, 264
recv, 264
restart, 264
retry_read, 265
retry_write, 265
send, 264
timer, 266
tls, 266
update_timeout, 264
writeable, 265
rpki::ipaddrs::v4addr, 266
__new__, 268
__str__, 268
bits, 268
from_bytes, 268
to_bytes, 268
rpki::ipaddrs::v6addr, 269
__new__, 270
__str__, 270
bits, 271
from_bytes, 270
to_bytes, 270
rpki::left_right
enforce_strict_up_down_xml_-sender, 63
rpki::left_right::bsc_elt, 271
attributes, 274
booleans, 274
children, 273
element_name, 275
elements, 275
handles, 275
parents, 273
pkcs10_request, 275
private_key_id, 275
repositories, 274
serve_pre_save_hook, 274
signing_cert, 275
signing_cert_crl, 276
sql_template, 276
rpki::left_right::child_elt, 276
attributes, 280
booleans, 280
bpki_cert, 280
bpki_glue, 280

ca_from_class_name, 278
child_certs, 278
clear_https_ta_cache, 280
element_name, 280
elements, 281
endElement, 279
handles, 281
parents, 279
serve_destroy_hook, 279
serve_post_save_hook, 279
serve_up_down, 279
sql_template, 281
rpki::left_right::cms_msg, 281
encoding, 283
saxify, 283
schema, 283
rpki::left_right::data_elt, 283
bsc, 285
handles, 287
make_reply_clone_hook, 285
self, 285
self_handle, 287
self_id, 287
serve_fetch_all, 286
serve_fetch_handle, 286
serve_fetch_one_maybe, 286
serve_pre_save_hook, 286
rpki::left_right::left_right_namespace, 287
nsmap, 288
xmlns, 288
rpki::left_right::list_published_objects_-elt, 289
attributes, 292
element_name, 292
make_reply, 291
obj, 292
serve_dispatch, 291
text_attribute, 292
rpki::left_right::list_received_resources_-elt, 292
attributes, 294
element_name, 294
make_reply, 294
serve_dispatch, 294
rpki::left_right::list_resources_elt, 295
asn, 298
attributes, 298
element_name, 298
ipv4, 298
ipv6, 298
startElement, 297
toXML, 297
valid_until, 298
rpki::left_right::list_roa_requests_elt, 299
attributes, 300
element_name, 300
ipv4, 301
ipv6, 301
startElement, 300
rpki::left_right::msg, 301
pdus, 303
serve_top_level, 303
version, 303
rpki::left_right::parent_elt, 304
attributes, 308
booleans, 308
bpki_cms_cert, 308
bpki_cms_glue, 308
bpki_https_cert, 309
bpki_https_glue, 309
cas, 306
element_name, 309
elements, 309
handles, 309
query_up_down, 306
repository, 307
serve_post_save_hook, 307
serve_rekey, 307
serve_revoke, 307
serve_revoke_forgotten, 307
sql_template, 309
rpki::left_right::report_error_elt, 310
attributes, 313
element_name, 313
error_code, 313
error_text, 313
from_exception, 312
self_handle, 313
tag, 313
text_attribute, 313
rpki::left_right::repository_elt, 314

attributes, 317
bpki_cert, 317
bpki_glue, 317
call_pubd, 316
default_pubd_handler, 316
element_name, 317
elements, 318
handles, 318
parents, 317
sql_template, 318
rpki::left_right::sax_handler, 318
name, 320
pdu, 320
version, 320
rpki::left_right::self_elt, 320
attributes, 327
booleans, 327
bpki_cert, 327
bpki_glue, 327
bscs, 323
children, 323
client_poll, 323
crl_interval, 328
cron, 323
element_name, 328
elements, 328
handles, 328
parents, 323
regen_margin, 328
regenerate_crls_and_manifests, 324
repositories, 324
roas, 324
serve_fetch_all, 324
serve_fetch_handle, 325
serve_fetch_one_maybe, 325
serve_post_save_hook, 325
serve_publish_world_now, 325
serve_rekey, 326
serve_revoke, 326
serve_revoke_forgotten, 326
serve_run_now, 326
sql_template, 328
update_children, 326
update_roas, 327
use_hsm, 329
rpki::log
debug, 65
enable_trace, 65
error, 66
info, 66
init, 65
note, 66
pid, 66
set_trace, 65
tag, 66
trace, 65
traceback, 65
use_syslog, 66
warn, 66
rpki::log::logger, 329
__call__, 330
__init__, 330
priority, 330
rpki::manifest::FileAndHash, 331
__init__, 332
file, 332
hash, 332
rpki::manifest::FilesAndHashes, 332
__init__, 333
rpki::manifest::Manifest, 334
__init__, 335
explicitVersion, 335
fileHashAlg, 335
fileList, 335
manifestNumber, 335
nextUpdate, 335
thisUpdate, 336
version, 336
rpki::oids
name2oid, 68
oid2name, 68
rpki::publication::certificate_elt, 336
element_name, 338
payload_type, 338
rpki::publication::client_elt, 338
attributes, 341
base_uri, 341
bpki_cert, 342
bpki_glue, 342
check_allowed_uri, 340
clear_https_ta_cache, 342
element_name, 342

elements, 342
endElement, 340
serve_fetch_all, 341
serve_fetch_one_maybe, 341
serve_post_save_hook, 341
sql_template, 342
rpki::publication::cms_msg, 343
encoding, 345
saxify, 345
schema, 345
rpki::publication::config_elt, 345
attributes, 348
config_id, 348
element_name, 348
elements, 349
fetch, 347
serve_fetch_one_maybe, 347
serve_set, 348
sql_template, 349
startElement, 348
wired_in_config_id, 349
rpki::publication::control_elt, 349
serve_dispatch, 351
rpki::publication::crl_elt, 351
element_name, 353
payload_type, 353
rpki::publication::manifest_elt, 353
element_name, 355
payload_type, 355
rpki::publication::msg, 355
pdus, 357
serve_top_level, 357
version, 357
rpki::publication::publication_-namespace, 358
nsmap, 359
xmlns, 359
rpki::publication::publication_object_elt, 359
attributes, 363
endElement, 361
make_publish, 361
make_withdraw, 362
payload, 363
payload_type, 363
raise_if_error, 362
serve_dispatch, 362
serve_publish, 362
serve_withdraw, 362
toXML, 363
uri_to_filename, 363
rpki::publication::report_error_elt, 364
__str__, 366
attributes, 367
element_name, 367
error_code, 367
error_text, 367
from_exception, 366
raise_if_error, 367
tag, 368
text_attribute, 368
rpki::publication::roa_elt, 368
element_name, 370
payload_type, 370
rpki::publication::sax_handler, 370
name, 372
pdu, 372
version, 372
rpki::relaxng
left_right, 70
publication, 70
up_down, 71
rpki::resource_set
_bs2long, 72
_long2bs, 73
_rsplit, 73
inherit_token, 73
test1, 73
test2, 73
rpki::resource_set::resource_bag, 372
__eq__, 374
__init__, 374
__ne__, 374
__str__, 375
asn, 376
empty, 375
from_rfc3779_tuples, 375
intersection, 375
oversized, 375
undersized, 375
union, 376
v4, 376

v6, 376
valid_until, 376
rpki::resource_set::resource_range, 377
__cmp__, 378
__init__, 378
max, 378
min, 378
rpki::resource_set::resource_range_as, 379
__str__, 380
datum_type, 380
min, 381
to_rfc3779_tuple, 380
rpki::resource_set::resource_range_ip, 381
__str__, 383
_prefixlen, 383
make_prefix, 383
to_rfc3779_tuple, 383
rpki::resource_set::resource_range_ipv4, 384
datum_type, 386
rpki::resource_set::resource_range_ipv6, 386
datum_type, 388
rpki::resource_set::resource_set, 388
__init__, 390
__str__, 390
_comm, 390
contains, 391
difference, 391
from_sql, 391
inherit, 392
intersection, 391
issubset, 391
issuperset, 392
symmetric_difference, 392
union, 392
rpki::resource_set::resource_set_as, 393
inherit, 395
parse_rfc3779_tuple, 394
parse_str, 394
range_type, 395
to_rfc3779_tuple, 394
rpki::resource_set::resource_set_ip, 395
inherit, 398
parse_rfc3779_tuple, 397
parse_str, 397
to_rfc3779_tuple, 397
rpki::resource_set::resource_set_ipv4, 398
afi, 400
range_type, 400
rpki::resource_set::resource_set_ipv6, 400
afi, 402
range_type, 402
rpki::resource_set::roa_prefix, 402
__cmp__, 404
__init__, 404
__str__, 404
max, 404
max_prefixlen, 405
min, 405
prefix, 405
prefixlen, 406
to_resource_range, 405
to_roa_tuple, 405
rpki::resource_set::roa_prefix_ipv4, 406
range_type, 408
rpki::resource_set::roa_prefix_ipv6, 408
range_type, 410
rpki::resource_set::roa_prefix_set, 410
__init__, 412
__str__, 412
from_sql, 412
parse_str, 412
to_resource_set, 412
to_roa_tuple, 413
rpki::resource_set::roa_prefix_set_ipv4, 413
prefix_type, 415
resource_set_type, 415
rpki::resource_set::roa_prefix_set_ipv6, 415
prefix_type, 417
resource_set_type, 417
rpki::roa::ROAIPAddress, 417
__init__, 418
address, 419
maxLength, 419
rpki::roa::ROAIPAddresses, 419

__init__, 420
rpki::roa::ROAIPAddressFamilies, 420
__init__, 421
rpki::roa::ROAIPAddressFamily, 421
__init__, 422
addresses, 423
addressFamily, 423
rpki::roa::RouteOriginAttestation, 423
__init__, 424
asID, 424
explicitVersion, 424
ipAddrBlocks, 424
version, 424
rpki::rpki_engine::ca_detail_obj, 425
activate, 428
ca, 428
ca_cert_uri, 432
ca_id, 432
child_certs, 428
create, 428
crl_published, 432
crl_published_callback, 428
crl_uri, 428
crl_uri_tail, 429
delete, 429
gctx, 432
generate_crl, 429
generate_manifest, 429
generate_manifest_cert, 429
issue, 430
issue_ee, 430
latest_ca_cert, 432
latest_crl, 432
latest_manifest, 433
latest_manifest_cert, 433
manifest_private_key_id, 433
manifest_public_key, 433
manifest_published, 433
manifest_published_callback, 430
manifest_uri, 430
nextUpdate, 433
private_key_id, 433
public_key, 434
revoke, 430
revoked_certs, 431
roas, 431
sql_decode, 431
sql_template, 434
state, 434
update, 431
rpki::rpki_engine::ca_obj, 434
ca_details, 436
check_for_updates, 436
construct_sia_uri, 437
create, 437
delete, 437
fetch_active, 437
fetch_deprecated, 438
fetch_issue_response_candidates, 438
fetch_pending, 438
fetch_revoked, 438
gctx, 440
last_crl_sn, 440
last_issued_sn, 440
last_manifest_sn, 440
next_crl_number, 438
next_manifest_number, 439
next_serial_number, 439
parent, 439
parent_id, 440
parent_resource_class, 440
rekey, 439
revoke, 439
sia_uri, 441
sql_template, 441
rpki::rpki_engine::child_cert_obj, 441
__init__, 443
ca_detail, 443
ca_detail_id, 445
cert, 445
child, 443
child_id, 445
fetch, 444
gctx, 445
published, 445
published_callback, 444
reissue, 444
revoke, 444
sql_template, 446
uri, 444
uri_tail, 445

rpki::rpki_engine::publication_queue, 446
__init__, 448
_add, 448
call_pubd, 448
handlers, 449
msgs, 449
publish, 448
replace, 449
repositories, 449
uris, 449
withdraw, 449
rpki::rpki_engine::revoked_cert_obj, 450
__init__, 451
ca_detail, 451
ca_detail_id, 452
expires, 452
gctx, 452
revoke, 451
revoked, 452
serial, 452
sql_template, 452
rpki::rpki_engine::roa_obj, 453
__init__, 455
asn, 458
ca_detail, 455
ca_detail_id, 458
cert, 458
gctx, 459
generate, 456
ipv4, 459
ipv6, 459
published, 459
published_callback, 456
regenerate, 456
revoke, 456
roa, 459
self, 457
self_id, 459
sql_delete_hook, 457
sql_fetch_hook, 457
sql_insert_hook, 457
sql_template, 459
update, 458
uri, 458
uri_tail, 458
rpki::rpki_engine::rpkid_context, 460
__init__, 463
bpki_ta, 465
build_https_ta_cache, 463
checkpoint, 463
clear_https_ta_cache, 463
cron, 463
cron_keepalive, 465
cron_period, 465
cron_timeout, 465
cron_timer, 465
cronjob_handler, 463
https_server_host, 466
https_server_port, 466
https_ta_cache, 466
initial_delay, 466
irbe_cert, 466
irdb_cert, 466
irdb_query, 464
irdb_query_child_resources, 464
irdb_query_roa_requests, 464
irdb_url, 466
left_right_handler, 464
publication_kludge_base, 467
rpkid_cert, 467
rpkid_key, 467
sql, 467
start_cron, 464
up_down_handler, 465
up_down_url_regexp, 467
use_internal_cron, 467
rpki::sql::session, 468
__init__, 470
_exceptions_enabled, 471
_wrap_execute, 470
assert_pristine, 470
cache, 472
cache_clear, 470
close, 470
connect, 470
cur, 472
database, 472
db, 472
dirty, 472
execute, 470
executemany, 471

fetchall, 471
lastrowid, 471
password, 472
ping, 471
sweep, 471
username, 472
rpki::sql::sql_persistent, 473
gctx, 479
sql_debug, 479
sql_decode, 475
sql_delete, 476
sql_delete_hook, 476
sql_deleted, 479
sql_encode, 476
sql_fetch, 476
sql_fetch_all, 477
sql_fetch_hook, 477
sql_fetch_where, 477
sql_fetch_where1, 477
sql_in_db, 480
sql_init, 477
sql_insert_hook, 478
sql_is_dirty, 478
sql_mark_clean, 478
sql_mark_deleted, 478
sql_mark_dirty, 478
sql_store, 479
sql_update_hook, 479
rpki::sql::template, 480
__init__, 482
columns, 482
delete, 482
index, 482
insert, 482
map, 483
select, 483
table, 483
update, 483
rpki::sundial
_cast, 77
now, 77
test, 78
rpki::sundial::datetime, 483
__add__, 485
__radd__, 485
__rsub__, 485
__str__, 486
__sub__, 486
earlier, 486
from_sql, 486
fromASN1tuple, 486
fromdatetime, 486
fromGeneralizedTime, 487
fromUTCTime, 487
fromXMLtime, 487
later, 487
PKIX_threshhold, 489
to_sql, 487
toASN1tuple, 488
toGeneralizedTime, 488
totimestamp, 488
toUTCTime, 488
toXMLtime, 488
rpki::sundial::timedelta, 489
__abs__, 492
__add__, 492
__div__, 492
__floordiv__, 492
__mul__, 492
__neg__, 492
__pos__, 492
__radd__, 492
__rdiv__, 493
__rfloordiv__, 493
__rmul__, 493
__rsub__, 493
__sub__, 493
convert_to_seconds, 493
fromtimedelta, 493
parse, 494
regexp, 494
years_to_seconds, 494
rpki::up_down
nsmap, 79
xmlns, 79
rpki::up_down::base_elt, 495
check_response, 496
endElement, 496
make_b64elt, 496
make_elt, 496
serve_pdu, 497
startElement, 497

rpki::up_down::certificate_elt, 497
cert, 500
cert_url, 500
endElement, 499
req_resource_set_as, 500
req_resource_set_ipv4, 500
req_resource_set_ipv6, 500
startElement, 499
toXML, 499
rpki::up_down::class_elt, 500
__init__, 502
cert_url, 503
certs, 503
class_name, 503
endElement, 502
from_resource_bag, 502
issuer, 504
resource_set_as, 504
resource_set_ipv4, 504
resource_set_ipv6, 504
resource_set_notafter, 504
startElement, 503
suggested_sia_head, 504
to_resource_bag, 503
toXML, 503
rpki::up_down::class_response_syntax, 505
__init__, 506
classes, 507
startElement, 506
toXML, 506
rpki::up_down::cms_msg, 507
encoding, 509
saxify, 509
schema, 509
rpki::up_down::error_response_pdu, 509
__init__, 511
check_response, 511
codes, 512
description, 512
endElement, 511
exceptions, 512
status, 512
toXML, 512
rpki::up_down::issue_pdu, 513
class_name, 516
endElement, 515
pkcs10, 516
query, 515
req_resource_set_as, 516
req_resource_set_ipv4, 516
req_resource_set_ipv6, 516
serve_pdu, 515
startElement, 515
toXML, 516
rpki::up_down::issue_response_pdu, 517
check_response, 519
rpki::up_down::list_pdu, 519
query, 521
serve_pdu, 521
toXML, 521
rpki::up_down::list_response_pdu, 522
rpki::up_down::message_pdu, 523
__str__, 525
log_query, 525
make_query, 525
name2type, 527
payload, 527
recipient, 527
sender, 527
serve_error, 526
serve_top_level, 526
startElement, 526
toXML, 526
type, 527
type2name, 527
version, 528
rpki::up_down::multi_uri, 528
__init__, 529
__str__, 530
rsync, 530
rpki::up_down::revoke_pdu, 530
class_name, 533
get_SKI, 532
query, 532
serve_pdu, 532
ski, 533
rpki::up_down::revoke_response_pdu, 533
rpki::up_down::revoke_syntax, 535
class_name, 536
ski, 536

startElement, 536
toXML, 536
rpki::up_down::sax_handler, 537
name, 539
pdu, 539
version, 539
rpki::x509
_find_xia_uri, 81
calculate_SKI, 81
POWify_OID, 81
rpki::x509::CMS_object, 539
content, 543
debug_cms_certs, 543
DER, 544
dump_on_verify_failure, 544
econtent_oid, 544
extract, 542
formats, 544
get_content, 542
get_DER, 542
get_POW, 542
other_clear, 544
pem_converter, 545
POW, 545
print_on_der_error, 545
require_crls, 545
set_content, 543
sign, 543
verify, 543
rpki::x509::CRL, 546
DER, 549
formats, 549
generate, 547
get_DER, 547
get_POW, 548
get_POWpkix, 548
getIssuer, 548
getNextUpdate, 548
getThisUpdate, 548
pem_converter, 549
POW, 549
POWpkix, 549
rpki::x509::DeadDrop, 550
__init__, 551
dump, 551
maildir, 551
pid, 551
rpki::x509::DER_CMS_object, 552
content, 553
decode, 553
encode, 553
rpki::x509::DER_object, 554
__cmp__, 556
__init__, 556
clear, 556
DER, 561
dumpasn1, 556
empty, 556
formats, 561
from_sql, 557
gAKI, 557
get_3779resources, 557
get_AIA, 557
get_aia_uri, 557
get_AKI, 558
get_Base64, 558
get_basicConstraints, 558
get_DER, 558
get_PEM, 558
get_SIA, 559
get_sia_directory_uri, 559
get_sia_manifest_uri, 559
get_SKI, 559
gSKI, 559
hAKI, 560
hSKI, 560
is_CA, 560
other_clear, 561
pem_converter, 561
set, 560
to_sql, 560
rpki::x509::PEM_converter, 562
__init__, 563
b, 564
e, 564
looks_like_PEM, 563
to_DER, 563
to_PEM, 563
rpki::x509::PKCS10, 564
check_valid_rpki, 566
create, 566
create_ca, 566

DER, 567
formats, 567
get_DER, 567
get_POWpkix, 567
getPublicKey, 567
pem_converter, 568
POWpkix, 568
rpki::x509::ROA, 568
build, 570
content_class, 570
econtent_oid, 570
pem_converter, 570
rpki::x509::RSA, 571
DER, 574
formats, 574
generate, 573
get_DER, 573
get_POW, 573
get_public_DER, 574
get_RSApublic, 574
get_SKI, 574
pem_converter, 575
POW, 575
rpki::x509::RSApublic, 575
DER, 578
formats, 578
get_DER, 577
get_POW, 577
get_SKI, 577
pem_converter, 578
POW, 578
rpki::x509::SignedManifest, 579
build, 580
content_class, 581
econtent_oid, 581
getNextUpdate, 580
getThisUpdate, 580
pem_converter, 581
rpki::x509::X509, 581
cross_certify, 583
DER, 586
expired, 584
formats, 586
get_DER, 584
get_POW, 584
get_POWpkix, 584
getIssuer, 584
getNotAfter, 584
getNotBefore, 585
getPublicKey, 585
getSerial, 585
getSubject, 585
issue, 585
normalize_chain, 586
pem_converter, 586
POW, 587
POWpkix, 587
rpki::x509::XML_CMS_object, 587
content, 591
decode, 589
dump_inbound_cms, 591
dump_outbound_cms, 591
dump_to_disk, 589
econtent_oid, 591
encode, 589
pretty_print_content, 590
schema_check, 590
unwrap, 590
wrap, 590
rpki::xml_utils::base_elt, 591
__str__, 593
attributes, 595
booleans, 595
elements, 595
endElement, 593
make_b64elt, 594
make_elt, 594
make_pdu, 594
read_attrs, 594
startElement, 594
toXML, 595
rpki::xml_utils::data_elt, 596
endElement, 598
make_reply, 598
make_reply_clone_hook, 598
serve_create, 599
serve_destroy, 599
serve_destroy_hook, 599
serve_dispatch, 599
serve_fetch_one, 599
serve_get, 600
serve_list, 600

serve_post_save_hook, 600
serve_pre_save_hook, 600
serve_set, 600
toXML, 601
unimplemented_control, 601
rpki::xml_utils::msg, 601
__str__, 603
endElement, 603
is_query, 603
is_reply, 603
query, 603
reply, 604
startElement, 604
toXML, 604
type, 604
version, 604
rpki::xml_utils::sax_handler, 605
__init__, 606
characters, 606
create_top_level, 607
endElement, 607
endElementNS, 607
result, 608
saxify, 607
stack, 608
startElement, 607
startElementNS, 608
text, 608
rpki::xml_utils::text_elt, 609
endElement, 610
text_attribute, 610
toXML, 610
rpki_base_uri
rootd, 48
rpki_class_name
rootd, 48
rpki_content_type
rpki::https, 60
rpki_engine.py(3107), 625
rpki_root_cert
rootd, 48
rpki_root_cert_file
rootd, 48
rpki_root_cert_uri
rootd, 48
rpki_root_crl
rootd, 49
rpki_root_dir
rootd, 49
rpki_root_key
rootd, 49
rpki_root_manifest
rootd, 49
rpki_subject_cert
rootd, 49
rpki_subject_lifetime
rootd, 49
rpki_subject_pkcs10
rootd, 50
rpki_subject_regen
rootd, 50
rpkid, 82
cfg_file, 84
main, 83
profile, 84
rpkid.py(2913), 625
rpkid_cert
irdbd, 40
rpki::rpki_engine::rpkid_context, 467
rpkid_key
rpki::rpki_engine::rpkid_context, 467
rsync
rpki::up_down::multi_uri, 530
run_debug
rpki::async::timer, 166
run_deferred
rpki::async, 52
runq
rpki::async::timer, 164

saxify
irbe_cli::left_right_cms_msg, 105
irbe_cli::publication_cms_msg, 120
rootd::cms_msg, 142
rpki::left_right::cms_msg, 283
rpki::publication::cms_msg, 345
rpki::up_down::cms_msg, 509
rpki::xml_utils::sax_handler, 607
schema
rpki::left_right::cms_msg, 283

rpki::publication::cms_msg, 345
rpki::up_down::cms_msg, 509
schema_check
rpki::x509::XML_CMS_object, 590
seconds_until_wakeup
rpki::async::timer, 164
select
rpki::sql::template, 483
self
rpki::left_right::data_elt, 285
rpki::rpki_engine::roa_obj, 457
self_handle
rpki::left_right::data_elt, 287
rpki::left_right::report_error_elt, 313
self_id
rpki::left_right::data_elt, 287
rpki::rpki_engine::roa_obj, 459
send
rpki::https::http_stream, 264
send_error
rpki::https::http_server, 258
send_message
rpki::https::http_server, 258
send_reply
rpki::https::http_server, 258
send_request
rpki::https::http_client, 237
rpki::https::http_queue, 249
sender
rpki::up_down::message_pdu, 527
Sequence, 611
SequenceOf, 611
serial
rpki::rpki_engine::revoked_cert_obj, 452
serve_create
rpki::xml_utils::data_elt, 599
serve_destroy
rpki::xml_utils::data_elt, 599
serve_destroy_hook
rpki::left_right::child_elt, 279
rpki::xml_utils::data_elt, 599
serve_dispatch
rpki::left_right::list_published_-objects_elt, 291
rpki::left_right::list_received_-resources_elt, 294
rpki::publication::control_elt, 351
rpki::publication::publication_-object_elt, 362
rpki::xml_utils::data_elt, 599
serve_error
rpki::up_down::message_pdu, 526
serve_fetch_all
rpki::left_right::data_elt, 286
rpki::left_right::self_elt, 324
rpki::publication::client_elt, 341
serve_fetch_handle
rpki::left_right::data_elt, 286
rpki::left_right::self_elt, 325
serve_fetch_one
rpki::xml_utils::data_elt, 599
serve_fetch_one_maybe
rpki::left_right::data_elt, 286
rpki::left_right::self_elt, 325
rpki::publication::client_elt, 341
rpki::publication::config_elt, 347
serve_get
rpki::xml_utils::data_elt, 600
serve_list
rpki::xml_utils::data_elt, 600
serve_pdu
rootd::issue_pdu, 144
rootd::list_pdu, 146
rootd::revoke_pdu, 150
rpki::up_down::base_elt, 497
rpki::up_down::issue_pdu, 515
rpki::up_down::list_pdu, 521
rpki::up_down::revoke_pdu, 532
serve_post_save_hook
rpki::left_right::child_elt, 279
rpki::left_right::parent_elt, 307
rpki::left_right::self_elt, 325
rpki::publication::client_elt, 341
rpki::xml_utils::data_elt, 600
serve_pre_save_hook
rpki::left_right::bsc_elt, 274
rpki::left_right::data_elt, 286
rpki::xml_utils::data_elt, 600
serve_publish

rpki::publication::publication_-
object_elt, 362
serve_publish_world_now
rpki::left_right::self_elt, 325
serve_rekey
rpki::left_right::parent_elt, 307
rpki::left_right::self_elt, 326
serve_revoke
rpki::left_right::parent_elt, 307
rpki::left_right::self_elt, 326
serve_revoke_forgotten
rpki::left_right::parent_elt, 307
rpki::left_right::self_elt, 326
serve_run_now
rpki::left_right::self_elt, 326
serve_set
rpki::publication::config_elt, 348
rpki::xml_utils::data_elt, 600
serve_top_level
rpki::left_right::msg, 303
rpki::publication::msg, 357
rpki::up_down::message_pdu, 526
serve_up_down
rpki::left_right::child_elt, 279
serve_withdraw
rpki::publication::publication_-
object_elt, 362
server
rpki::https, 59
server_cert
irdbd, 40
rootd, 50
rpki::https::caller, 234
server_ta
rpki::https::caller, 234
set
rpki::async::timer, 164
rpki::x509::DER_object, 560
set_content
rpki::x509::CMS_object, 543
set_errback
rpki::async::timer, 165
set_global_flags
rpki::config::parser, 174
set_handler
rpki::async::timer, 165
set_state
rpki::https::http_client, 237
set_subject_cert
rootd, 46
set_subject_pkcs10
rootd, 46
set_trace
rpki::log, 65
sia_uri
rpki::rpki_engine::ca_obj, 441
sign
rpki::x509::CMS_object, 543
signing_cert
irbe_cli::bsc_elt, 88
rpki::left_right::bsc_elt, 275
signing_cert_crl
irbe_cli::bsc_elt, 88
rpki::left_right::bsc_elt, 276
ski
rpki::up_down::revoke_pdu, 533
rpki::up_down::revoke_syntax, 536
software_name
rpki::https::http_message, 246
sql
pubd::pubd_context, 140
rpki::rpki_engine::rpkid_context,
467
sql.py(2895), 625
sql_debug
rpki::sql::sql_persistent, 479
sql_decode
rpki::rpki_engine::ca_detail_obj,
431
rpki::sql::sql_persistent, 475
sql_delete
rpki::sql::sql_persistent, 476
sql_delete_hook
rpki::rpki_engine::roa_obj, 457
rpki::sql::sql_persistent, 476
sql_deleted
rpki::sql::sql_persistent, 479
sql_encode
rpki::sql::sql_persistent, 476
sql_fetch
rpki::sql::sql_persistent, 476
sql_fetch_all

rpki::sql::sql_persistent, 477
sql_fetch_hook
rpki::rpki_engine::roa_obj, 457
rpki::sql::sql_persistent, 477
sql_fetch_where
rpki::sql::sql_persistent, 477
sql_fetch_where1
rpki::sql::sql_persistent, 477
sql_in_db
rpki::sql::sql_persistent, 480
sql_init
rpki::sql::sql_persistent, 477
sql_insert_hook
rpki::rpki_engine::roa_obj, 457
rpki::sql::sql_persistent, 478
sql_is_dirty
rpki::sql::sql_persistent, 478
sql_mark_clean
rpki::sql::sql_persistent, 478
sql_mark_deleted
rpki::sql::sql_persistent, 478
sql_mark_dirty
rpki::sql::sql_persistent, 478
sql_store
rpki::sql::sql_persistent, 479
sql_template
rpki::left_right::bsc_elt, 276
rpki::left_right::child_elt, 281
rpki::left_right::parent_elt, 309
rpki::left_right::repository_elt, 318
rpki::left_right::self_elt, 328
rpki::publication::client_elt, 342
rpki::publication::config_elt, 349
rpki::rpki_engine::ca_detail_obj, 434
rpki::rpki_engine::ca_obj, 441
rpki::rpki_engine::child_cert_obj, 446
rpki::rpki_engine::revoked_cert_obj, 452
rpki::rpki_engine::roa_obj, 459
sql_update_hook
rpki::sql::sql_persistent, 479
stack
rpki::xml_utils::sax_handler, 608
start
rpki::https::http_client, 238
start_cron
rpki::rpki_engine::rpkid_context, 464
startElement
rpki::left_right::list_resources_elt, 297
rpki::left_right::list_roa_requests_-elt, 300
rpki::publication::config_elt, 348
rpki::up_down::base_elt, 497
rpki::up_down::certificate_elt, 499
rpki::up_down::class_elt, 503
rpki::up_down::class_response_-syntax, 506
rpki::up_down::issue_pdu, 515
rpki::up_down::message_pdu, 526
rpki::up_down::revoke_syntax, 536
rpki::xml_utils::base_elt, 594
rpki::xml_utils::msg, 604
rpki::xml_utils::sax_handler, 607
startElementNS
rpki::xml_utils::sax_handler, 608
startup_msg
irdbd, 40
state
rpki::https::http_client, 239
rpki::rpki_engine::ca_detail_obj, 434
status
rpki::up_down::error_response_pdu, 512
suggested_sia_head
rpki::up_down::class_elt, 504
sundial.py(3107), 626
supported_address_families
rpki::https, 60
sweep
rpki::sql::session, 471
symmetric_difference
rpki::resource_set::resource_set, 392

ta
rpki::https::http_client, 239
rpki::https::http_listener, 243
rpki::https::http_queue, 250

table
rpki::sql::template, 483
tag
rpki::left_right::report_error_elt, 313
rpki::log, 66
rpki::publication::report_error_elt, 368
test
rpki::sundial, 78
test1
rpki::resource_set, 73
test2
rpki::resource_set, 73
text
rpki::xml_utils::sax_handler, 608
text_attribute
rpki::left_right::list_published_-objects_elt, 292
rpki::left_right::report_error_elt, 313
rpki::publication::report_error_elt, 368
rpki::xml_utils::text_elt, 610
textwrap::TextWrapper, 611
thisUpdate
rpki::manifest::Manifest, 336
threshold
rpki::async::gc_summary, 153
timeout
rpki::https::http_client, 239
rpki::https::http_server, 259
timer
rpki::async::gc_summary, 153
rpki::https::http_stream, 266
tls
rpki::https::http_client, 240
rpki::https::http_server, 259
rpki::https::http_stream, 266
tls_accept
rpki::https::http_server, 258
tls_connect
rpki::https::http_client, 238
to_bytes
rpki::ipaddrs::v4addr, 268
rpki::ipaddrs::v6addr, 270
to_DER
rpki::x509::PEM_converter, 563
to_PEM
rpki::x509::PEM_converter, 563
to_resource_bag
rpki::up_down::class_elt, 503
to_resource_range
rpki::resource_set::roa_prefix, 405
to_resource_set
rpki::resource_set::roa_prefix_set, 412
to_rfc3779_tuple
rpki::resource_set::resource_range_-as, 380
rpki::resource_set::resource_range_-ip, 383
rpki::resource_set::resource_set_as, 394
rpki::resource_set::resource_set_ip, 397
to_roa_tuple
rpki::resource_set::roa_prefix, 405
rpki::resource_set::roa_prefix_set, 413
to_sql
rpki::sundial::datetime, 487
rpki::x509::DER_object, 560
toASN1tuple
rpki::sundial::datetime, 488
toGeneralizedTime
rpki::sundial::datetime, 488
top_opts
irbe_cli, 36
totimestamp
rpki::sundial::datetime, 488
toUTCTime
rpki::sundial::datetime, 488
toXML
rpki::left_right::list_resources_elt, 297
rpki::publication::publication_-object_elt, 363
rpki::up_down::certificate_elt, 499
rpki::up_down::class_elt, 503
rpki::up_down::class_response_-syntax, 506
rpki::up_down::error_response_pdu, 512

rpki::up_down::issue_pdu, 516
rpki::up_down::list_pdu, 521
rpki::up_down::message_pdu, 526
rpki::up_down::revoke_syntax, 536
rpki::xml_utils::base_elt, 595
rpki::xml_utils::data_elt, 601
rpki::xml_utils::msg, 604
rpki::xml_utils::text_elt, 610
toXMLtime
rpki::sundial::datetime, 488
trace
rpki::async::timer, 165
rpki::log, 65
traceback
rpki::log, 65
type
rpki::up_down::message_pdu, 527
rpki::xml_utils::msg, 604
type2name
rootd::message_pdu, 148
rpki::up_down::message_pdu, 527

u
irdbd, 41
undersized
rpki::resource_set::resource_bag, 375
unimplemented_control
rpki::xml_utils::data_elt, 601
union
rpki::resource_set::resource_bag, 376
rpki::resource_set::resource_set, 392
unwind_stack
rpki::async::iterator, 157
unwrap
rpki::x509::XML_CMS_object, 590
up_down
rpki::relaxng, 71
up_down.py(3144), 626
up_down_handler
rootd, 46
rpki::rpki_engine::rpkid_context, 465
up_down_url_regexp
rpki::rpki_engine::rpkid_context, 467
update
rpki::rpki_engine::ca_detail_obj, 431
rpki::rpki_engine::roa_obj, 458
rpki::sql::template, 483
update_children
rpki::left_right::self_elt, 326
update_roas
rpki::left_right::self_elt, 327
update_timeout
rpki::https::http_stream, 264
uri
rpki::rpki_engine::child_cert_obj, 444
rpki::rpki_engine::roa_obj, 458
uri_tail
rpki::rpki_engine::child_cert_obj, 445
rpki::rpki_engine::roa_obj, 458
uri_to_filename
rpki::publication::publication_-object_elt, 363
uris
rpki::rpki_engine::publication_-queue, 449
url
rpki::https::caller, 234
usage
irbe_cli, 34
irbe_cli::cmd_elt_mixin, 97
irbe_cli::cmd_msg_mixin, 100
usage_fill
irbe_cli, 36
use_hsm
rpki::left_right::self_elt, 329
use_internal_cron
rpki::rpki_engine::rpkid_context, 467
use_syslog
rpki::log, 66
username
rpki::sql::session, 472

v4

rpki::resource_set::resource_bag, 376
v6
rpki::resource_set::resource_bag, 376
valid_until
rpki::left_right::list_resources_elt, 298
rpki::resource_set::resource_bag, 376
verbose
irbe_cli, 36
verify
rpki::x509::CMS_object, 543
version
rpki::https::http_message, 246
rpki::left_right::msg, 303
rpki::left_right::sax_handler, 320
rpki::manifest::Manifest, 336
rpki::publication::msg, 357
rpki::publication::sax_handler, 372
rpki::roa::RouteOriginAttestation, 424
rpki::up_down::message_pdu, 528
rpki::up_down::sax_handler, 539
rpki::xml_utils::msg, 604

want_persistent_client
rpki::https, 60
want_persistent_server
rpki::https, 61
warn
rpki::log, 66
when
rpki::async::timer, 166
wired_in_config_id
rpki::publication::config_elt, 349
withdraw
rpki::rpki_engine::publication_queue, 449
wrap
rpki::x509::XML_CMS_object, 590
writeable
rpki::https::http_stream, 265

x509.py(3107), 627
xml::sax::handler::ContentHandler, 611
xml_utils.py(2836), 627
xmlns
rpki::left_right::left_right_namespace, 288
rpki::publication::publication_namespace, 359
rpki::up_down, 79

years_to_seconds
rpki::sundial::timedelta, 494
yes_or_no
rpki::cli, 54