



# Role-Based Access Control for Clustered Data ONTAP

Jeff Asher, Steve Ryles, Hadrian Baron, Bryan Walsh, Mrinal Devadas  
January 2015 | TR-4368

Version 1.0

## Abstract

One of the most challenging problems in managing access to data within organizations is the complexity of security administration and user-profile management. Role-based access control has become the predominant model for advanced access control because it reduces the complexity and cost of administration.

## TABLE OF CONTENTS

<b>1</b>	<b>Introduction.....</b>	<b>4</b>
<b>2</b>	<b>How RBAC Works in Clustered Data ONTAP.....</b>	<b>4</b>
2.1	Users and Accounts .....	5
2.2	Roles .....	5
2.3	Capabilities .....	6
2.4	Login Applications and Authentication Methods .....	6
<b>3</b>	<b>Aligning Roles and Access Control with Microsoft Windows Active Directory Servers.....</b>	<b>7</b>
<b>4</b>	<b>Protecting Data by Segregating Responsibilities.....</b>	<b>10</b>
<b>5</b>	<b>Design Considerations.....</b>	<b>10</b>
5.1	Existing Data ONTAP Operating in 7-Mode Environments .....	10
5.2	New and Existing Clustered Data ONTAP Environments .....	11
<b>6</b>	<b>RBAC Implementation Planning.....</b>	<b>13</b>
<b>7</b>	<b>Application Integration and Custom Roles.....</b>	<b>16</b>
7.1	Custom Roles and Security Logins .....	16
7.2	Demonstration of Custom Roles Using OnCommand System Manager .....	20
7.2.1	Readonly role with volume creation.....	20
7.2.2	Full Access Role with Volume Deletion Denied .....	22
7.3	Determining Required Permissions, Directories, and Commands .....	25
7.3.1	SPI web interface.....	25
7.4	Demonstration of Custom Roles Using OnCommand Unified Manager and OnCommand Performance Manager.....	26
7.4.1	Prerequisites.....	26
7.4.2	Creating the OnCommand Unified Manager role.....	26
7.4.3	Creating the OnCommand Unified Manager User.....	27
7.4.4	Creating the OnCommand Performance Manager Role.....	27
7.4.5	Creating the OnCommand Performance Manager User.....	27
7.4.6	Outputs for OnCommand Unified Manager User and Roles .....	28
7.4.7	Outputs for OnCommand Performance Manager User and Roles.....	28
<b>8</b>	<b>RBAC User Creator .....</b>	<b>29</b>
8.1.1	Creating a Custom Role from the Graphical User Interface (GUI).....	30
8.1.2	Creating a Custom Role Using XML Files.....	33
<b>9</b>	<b>Summary.....</b>	<b>35</b>
	<b>Appendix .....</b>	<b>35</b>
	<b>Version History.....</b>	<b>36</b>

## LIST OF FIGURES

Figure 1) Basic security model in role-based access control. ....	5
Figure 2) Transitioning 7-Mode security roles to clustered Data ONTAP roles. ....	11
Figure 3) Correlation between number of roles and memory usage. ....	12
Figure 4) Example of using custom roles with OnCommand System Manager. ....	20

## LIST OF TABLES

Table 1) Predefined roles for cluster users. ....	5
Table 2) Access methods for creating user account. ....	6
Table 3) Default roles in clustered Data ONTAP 8.3. ....	8
Table 4) Map of default security groups in Windows 2012 servers to roles in clustered Data ONTAP. ....	9

## 1 Introduction

The NetApp® clustered Data ONTAP® operating system offers an exponential improvement to security management for users and groups managing hardware, software, and data on NetApp systems. This document furnishes the reader with a practical approach to understanding and implementing this new security model. This report focuses on clustered Data ONTAP 8.3.

Role-based access control (RBAC) is a method for managing the set of actions that a user or a group of users might perform in a computing environment. Within most computing environments, it is necessary to control access to data and other system objects so that only users with the appropriate permissions can view or alter them. In general, users who access a system fall into at least two categories, or roles: administrators and nonadministrators. For example, only the system administrator should be allowed to add new user accounts to the system.

Having two categories of users might not be sufficient. Organizations have multiple system administrators who require different privileges depending on the system resources they need to administer. You can control all access to system resources by selectively granting or revoking privileges to individual users and groups; however, it is difficult and time consuming to manage the set of capabilities granted to each administrator as the number of system administrators grows. RBAC solves this management problem. It is an approach to restricting system access to authorized users based on their job function and with it you can implement mandatory access control or discretionary access control.

## 2 How RBAC Works in Clustered Data ONTAP


Although the overall concept of role-based access control is applicable to a wide range of operating systems and applications, the details of how RBAC is implemented vary depending on the operating system or application in use. This section describes the specific terminology and architecture used in clustered Data ONTAP. It is important that you understand these concepts and definitions because the terminology and architecture in clustered Data ONTAP might be different from implementations you used in the past.

The strategy to follow is: **A**ccounts are assigned **r**oles and **r**oles are assigned **c**apabilities (A.R.C.).

You define sets of capabilities that are assigned to any particular user. Users are assigned to roles based on their job functions and each role is granted the set of rules required to perform those functions. Using this method, the only configuration an individual administrator must make is to make sure that the user or group is a member of the appropriate roles. The administrator will then inherit all the correct capabilities because of the member's group membership and the roles assigned to those roles.

Refer to product documentation for Data ONTAP 8.3 for specific information on creating custom roles and assigning them to users and groups that belong to your Windows® Active Directory® domain.

Figure 1) Basic security model in role-based access control.



Also, see [Figure 3, Example of creating custom roles using OnCommand System Manager](#).

## 2.1 Users and Accounts

A user is defined as an account that is authenticated on the NetApp system. A domain user is defined as a nonlocal user who belongs to a Windows domain and is authenticated by the domain. Both local users and domain users represent individual, authenticated humans. The user accounts discussed in this document are assumed to be administrative user accounts and not data access user accounts. Data access user account management is covered in the [System Administration Guide for SVM Administrators](#).

Clustered Data ONTAP implements user accounts differently than Data ONTAP operating in 7-Mode. In clustered Data ONTAP, user accounts are created as either cluster accounts or storage virtual machine (SVM) accounts. Cluster user accounts can administer the cluster and all SVMs in that cluster. SVM user accounts are limited to executing commands that only show or affect objects in that SVM. A user logged in to an SVM user account only has access to that storage virtual machine.

User accounts must be created with a specified method to access the cluster or SVM. Table 1 lists the access methods and who can use them.

## 2.2 Roles

A role is defined as a named set of capabilities. Clustered Data ONTAP defines roles across a cluster and for individual SVMs. There are several predefined roles for each context and each role has a predefined set of capabilities. Each role can execute different sets of commands and has different access levels that can be used with those commands.

Table 1) Predefined roles for cluster users.

Role	Capability
admin	Has full administrative capabilities on the cluster and all SVMs in that cluster
autosupport	Allows users to generate and send NetApp AutoSupport™ messages and has no additional capabilities
backup	Permits only the commands required to configure NDMP and NDMP-related commands
readonly	Shows most settings and objects on the cluster, but the only change that a user with the <i>readonly</i> role can make is to his or her own password

The first role that an administrator becomes familiar with is the *admin* role. The default cluster administration user, *admin*, is assigned to the role *admin*.

Note that in some cases the user name and role name are identical, but this is not always the case. The user *admin* and role *admin* are different objects and should not be confused. Additional cluster administrator user accounts can be created, and you can also assign those accounts to the *admin* role.

There are also predefined roles that are scoped to individual SVMs that are present by default when the SVM is created. The *vsadmin* role allows a user almost full administrative control over an SVM and its objects. The commands that are restricted from the *vsadmin* role, such as *volume move*, affect the cluster or other SVMs, which can negatively affect the performance of the nodes serving that volume and by extension other SVMs.

**Note:** The *vsadmin* role cannot be used for direct SVM credentials in the Virtual Storage Console (VSC). This role is used mostly in multi-tenancy environments/infrastructures; however, it is not an access solution for every application in a given infrastructure. The VSC has specific privilege requirements that surpass what *vsadmin* privileges provide. For [OffTap](#) products, it is highly recommended using the ONTAP RBAC User Creator tool to craft a role and user tailored not just to VSC, but to the particular operations that VSC is expected to perform. See *Section 8, RBAC User Creator*.

Other predefined roles for SVMs include the *vsadmin-volume* role, the *vsadmin-protocol* role, the *vsadmin-backup* role, and the *vsadmin-readonly* role. You can find additional information on all predefined roles in the “Managing Access to the Cluster” section of the [System Administration Guide for Cluster Administrators](#).

Roles can also be created by a cluster administrator and privileges can be assigned to or restricted from those roles. Whether the role is applied to the cluster or an SVM, it can be created only by cluster administrator users whose roles have that capability. An administrator user for an SVM cannot create a role within that SVM.

## 2.3 Capabilities

The combination of a command and an access level is called a *capability*. It should be noted that the capabilities of the predefined roles cannot be changed.

A *command* is a specific instruction; however, when defining roles, a *command* can also be an entire command tree. For example, the *volume* command encompasses all commands available under that tree, while *volume snapshot policy show* is also a command.

The access levels available to be used with a command are *all*, *readonly*, and *none*. The *all* access level permits full access to all commands, while the *readonly* access level permits access only to the show commands under that command tree. The *none* access level does not permit the use of the specified command at all. In effect, that command does not exist for that role. If a user tries to execute a command that has an access level of *none* assigned to that user’s role, an error message stating that the command is not recognized is returned.

## 2.4 Login Applications and Authentication Methods

In clustered Data ONTAP, to access the cluster or SVM you must link user accounts with an application. Cluster user accounts can use all methods, while SVM user accounts can use only HTTP, ONTAPI, SNMP, and SSH.

Table 2) Access methods for creating user account.

Access Method	Cluster User Account	SVM User Account
console	✓	
http (includes https)	✓	✓
ontapi	✓	✓

Access Method	Cluster User Account	SVM User Account
rsh (disabled by default)	✓	
service-processor	✓	
snmp	✓	✓
ssh	✓	✓
telnet (disabled by default)	✓	

When the user account is created, an authentication method must also be specified. A user account can have different authentication methods for each access method. Valid authentication methods are:

- SSL certificate
- SNMP community strings
- Windows Active Directory authentication
- LDAP or NIS authentication
- User password
- SSH public key authentication
- SNMP user-based security model

When you create a new user account with the authentication method of “password,” you must enter a password for the user. Any subsequent access methods that you configure for that user that use the password authentication method will use the user’s latest password.

### 3 Aligning Roles and Access Control with Microsoft Windows Active Directory Servers

In this section we will attempt to show similarities between the security model followed by Microsoft in Windows Server and clustered Data ONTAP.

In a single Active Directory (AD) domain environment, Microsoft’s implementation of RBAC leverages different security group scopes:

- Global security groups: Domain security groups with global scope represent business roles or job functions within the domain. These groups might contain accounts and other global groups from the same domain, and they can be used by resources in any domain in the forest. They can be changed frequently without causing global catalog replication.
- Domain local security groups: Domain security groups with domain local scope describe the low-level permissions or user rights to which they are assigned. These groups can be used only by systems in the same domain. Domain local groups might may contain accounts, global groups, and universal groups from any domain, as well as domain local groups from the same domain.

Clustered Data ONTAP uses [AGDLP](#)<sup>1</sup> (account, global, domain local, permission). Security roles are defined for cluster and SVM users with the expectation that these roles will hardly ever change; however, membership of these roles will change as people move through the organization. Once a role is defined and access criteria specified, it is easy to manage the role.

Typically, once role access specifications are defined they are not changed; however, membership in a role can change to adapt to a user's responsibilities. The guiding principle is to keep administration at the role level to allow more efficient management of access control.

By default, clustered Data ONTAP 8.3 has 10 security roles: 5 roles apply to the cluster and 5 to the SVM. Microsoft® Windows 2012 Server has 14 default security groups. For details, see <http://technet.microsoft.com/en-us/library/cc771990.aspx>.

**Table 3) Default roles in clustered Data ONTAP 8.3.**

Role Name (Scope)	Explanation
admin (cluster)	Super user for the cluster
autosupport (cluster)	Allows customization and viewing of AutoSupport settings
backup (cluster)	Allows configuration of NDMP services and viewing user capabilities
none (cluster)	No access to commands on the clustershell
readonly (cluster)	Read-only access to all commands on the clustershell
vsadmin (SVM)	Super user for the SVM
vsadmin-backup (SVM)	Backup user with access to manipulate NDMP settings
vsadmin-protocol (SVM)	Admin user with access to manage user credentials, protocol configuration, and settings for the SVM
vsadmin-volume (SVM)	Similar capabilities as the <code>vsadmin-protocol</code> role but with additional privileges to manage name services of the SVM
vsadmin-readonly (SVM)	Ability to view all configuration information of the SVM

The default roles give us some indication of the security roles that can be defined on the cluster or an SVM. We can use the 14 default security groups in Microsoft Windows Active Directory on a Microsoft Windows 2012 Server (<http://technet.microsoft.com/en-us/library/cc771990.aspx>) as reference to define security roles in Data ONTAP to segregate user responsibilities.

Table 4 lists the default security groups available in Microsoft Windows Active Directory with a brief explanation of how the role could be interpreted in a clustered Data ONTAP deployment.

---

<sup>1</sup> [AGDLP](#) (an acronym for "account, global, domain local, permission") briefly summarizes Microsoft's recommendations for implementing role-based access control (RBAC) using nested groups in a native-mode Active Directory (AD) domain: User and computer accounts are members of global groups that represent business roles, which are members of domain local groups that describe resource permissions or user rights assignments. Retrieved November 22, 2014, from Wikipedia, the free encyclopedia <http://en.wikipedia.org/wiki/AGDLP>.



Since Microsoft Windows servers have a different set of capabilities than Data ONTAP, not all the roles have an equivalent. The security roles listed below are in addition to the default roles described in the previous table.

**Table 4) Map of default security groups in Windows 2012 servers to roles in clustered Data ONTAP.**

Windows Security Group	Possible Equivalent Security Role in Data ONTAP
Administrators	<p>Similar to the <i>admin</i> and <i>vsadmin</i> roles. The role can be defined for cluster and SVM users.</p> <p>Ability to create new aggregates and remove nodes from the cluster. The role can be defined for cluster users.</p> <p>Ability to create new aggregates and remove nodes from the cluster. The role can be defined for cluster users.</p>
Backup Operators	<p>Some of the capability is covered by the cluster level role of backup and some by the SVM-level <i>vsadmin-backup</i> role.</p> <p>A new security role can be created to allow the user to create cluster and SVM peer relations, set up and initialize NetApp SnapMirror® and SnapVault® relations, define retention policies, manage NDMP configuration, and perform restore operations. The role can be defined for cluster and SVM users.</p>
Cryptographic Operators	<p>Ability to manage SSL certificates for SVMs. The role can be defined for SVM users.</p> <p>Ability to manage the Kerberos configuration of the SVM. The role can be defined for cluster users.</p> <p>Ability to lock and unlock cluster and SVM admins. The role can be defined for cluster and SVM users.</p>
Guests	
Users	
Power Users	<p>Ability to create and manage policies for Quality of Service (QoS), SnapMirror, SnapVault, and NetApp Snapshot® copies. The role can be defined for SVM users.</p> <p>Ability to add or remove user accounts to defined security roles. This role does not create security roles. The role can be defined for cluster and SVM users.</p> <p>Ability to create and delete SVMs. The role can be defined for cluster users.</p>
Network Configuration Operators	<p>Ability to manage LIF attributes of the cluster and SVM. This includes creation, modification, and deletion of LIFs that belong to the cluster and SVM. The role can be defined for cluster users.</p>
Performance Log Users	
Performance Monitor Users	<p>Ability to create and modify QoS policies used by an SVM. There is some overlap of this role with the Group Policy Creators Owners role. The role can be defined for SVM users.</p>
Remote Desktop Users	
IIS_IUSRS	
Replicator	
Offer Remote Assistance Helpers	

## 4 Protecting Data by Segregating Responsibilities

Using RBAC in clustered Data ONTAP leads to enhanced data protection through the concept of Segregation of Duties (SoD), or Separation of Duties, as it is also known. This concept prevents a single administrator from affecting access to data or other objects, such as logical interfaces, by limiting access using the principle of least privilege. The principle of least privilege simply states that a user or process should have the level of access required to perform his or her legitimate functions and no more. The principles of Segregation of Duties and the principle of least privilege are applied mostly in larger IT departments with distributed responsibilities, but smaller environments can take advantage of these features particularly with system accounts and the processes and functions they perform. These principles prevent a security incident on one system from spreading to others.

Following are to examples of how these concepts are applied using clustered Data ONTAP.

- Create a new role that allows a Windows administrator access to just the CIFS commands on a particular SVM to prevent that administrator from changing NFS configurations.
- Create a network administrator role at the cluster level that has access only to network commands. This role permits users to configure features such as DNS load-balancing without permitting those users to modify or even view data-container objects.

SoD is enforced by default in clustered Data ONTAP in several functional areas. An SVM administrator with the *vsadmin* role cannot perform volume move or LIF migrate operations, because those operations affect the load on individual hardware resources and can therefore affect the access that users of other SVMs have to those resources. For this reason the network administrator role in the example provided is defined at the cluster level and not at the SVM level.

Clustered Data ONTAP allows and, in some cases, enforces SoD through the various predefined SVM roles:

- The *vsadmin-readonly* role is used by auditors, and by definition they should have no access to make changes to operations.
- The *vsadmin-backup* role has access to all of the commands required to perform backups of an SVM and no more.
- The *vsadmin-protocol* role allows an administrator to perform functions at the data access layer, but the administrator is not able to modify data-container objects.

## 5 Design Considerations

This section focuses on the design considerations for creating the security policy for cluster and SVM users. Design considerations address the following environments:

- Existing Data ONTAP environments operating in 7-Mode
- New and existing clustered Data ONTAP environments

### 5.1 Existing Data ONTAP Operating in 7-Mode Environments


Data ONTAP operating in 7-Mode implements the following RBAC strategy: Accounts are assigned to groups, groups are assigned roles, and roles are assigned capabilities (A.G.R.C.).

Term	Description
Accounts	Users who interact with the administrative path of Data ONTAP. The two types of accounts are local account and domain user account. <ul style="list-style-type: none"><li>• Local: An account that is authenticated in Data ONTAP.</li><li>• Domain user: A nonlocal user who belongs to a Windows domain and is authenticated by the domain.</li></ul>

Term	Description
Group	A collection of local and/or domain user accounts. Groups can be assigned one or more roles.
Role	A named set of capabilities.
Capabilities	A privilege that designates the task(s) a user can perform. Data ONTAP operating in 7-Mode supports the following capability types: login, cli, security, api, and compliance.

The primary focus for transitioning security roles from Data ONTAP operating in 7-Mode to clustered Data ONTAP is to separate the roles based on its scope. The following diagram illustrates how to analyze 7-Mode roles to determine if the role applies to a user who will administer a cluster or an SVM.


Figure 2) Transitioning 7-Mode security roles to clustered Data ONTAP roles.



## 5.2 New and Existing Clustered Data ONTAP Environments

Careful measurements by NetApp have shown that the number of custom roles in the cluster have a direct correlation to the memory consumed by the management daemon (mgwd), a design consideration for custom roles for cluster and SVM users. These tests show that although there is a cost (memory footprint) to creating custom roles for users on the cluster it should be balanced by the benefits of segregating user responsibilities on the cluster. The number of custom roles that provide this balance will vary based on the version of clustered Data ONTAP. Consult with your NetApp team to determine the level of customization that works best for your organization.

Figure 3) Correlation between number of roles and memory usage.



## 6 RBAC Implementation Planning

This table is a reference for specific versions of NetApp tools and indicates whether the versions support RBAC for logging into the tool itself or whether the tool supports RBAC when communicating with the storage cluster. This matrix provides an at-a-glance view of RBAC support of the solution as a whole.

### Header Legend

- Tool-Specific MS AD Support: Ability to log into the tool using AD credentials instead of a local user.
- Tool-Specific RBAC Support: Ability to log into the tool using a non-admin role.
- Other\* MS AD RBAC Support: Tool can communicate with the storage cluster using Microsoft AD account with non-admin role.
- Other\* SVM RBAC Support: Tool can communicate with the storage virtual machine using non-admin role.
- Other\* Non-Admin Account Support: Tool can communicate with the storage cluster using a non-default-administrator role.

\***Other** is defined as support between the clustered Data ONTAP cluster and third-party products, applications, and tools.

Table 5) RBAC tool matrix view by application.

Application	Tool-Specific MS AD Support	Tool-Specific RBAC Support	Other MS AD RBAC Support	Other SVM RBAC Support	Other Non-Admin-Account Support	RBAC User Creator Tool Support
Clustered Data ONTAP	N/A	N/A	Yes	Yes	Yes	No
NetApp Cluster-Interconnect Switch CN1610 1.1.0.4	No	No	N/A	N/A	N/A	No
NetApp Virtual Storage Console 5.0 VMware® vSphere®	Yes	Yes	Yes	No	Yes	Yes
NetApp Virtual Storage Console 4.2.1	Yes	No	Yes	No	Yes	Yes
NetApp SnapDrive® 7.0—Linux®	No	No	No	Yes	Yes	No
NetApp SnapDrive 7.0—Windows	N/A	No	Yes	Yes	Yes	No
NetApp SnapManager® 2.2	No	No	No	Yes	Yes	No

Application	Tool-Specific MS AD Support	Tool-Specific RBAC Support	Other MS AD RBAC Support	Other SVM RBAC Support	Other Non-Admin-Account Support	RBAC User Creator Tool Support
for Oracle						
NetApp SnapManager for MS-SQL 7.0	Yes	No	Yes	Yes	Yes	No
NetApp OCUM 6.1	Yes	Yes	Yes	No	Yes	No
NetApp OPM 1.0	Yes	No	Yes	No	Yes	No
NetApp OCC 5.2	Yes	No	Yes	No	Yes	No
NetApp AV Connector 1.0	N/A	No	Yes			No
Cisco® UCS® Director		Yes				No
VMware vCACs		Yes				N/A
VMware vCops vs. Blue Medora Monitoring Platform						N/A
NetApp WFA 2.2RC1	Yes	Yes	Yes	Yes	Yes	N/A
Custom Linux Scripts—SMO FlexClone® from SnapMirror Target	No	No	No	Yes	Yes	No
Symantec™ NetBackup™	Yes		Yes	No, planned	Yes	No

Table 6) RBAC tool matrix view by privileges.

Privilege	cDOT 8.2.2	SVM	OCUM 6.2	OPM 1.1	VSC 5.1	System Manager 3.0
RBAC User Creator Tool Support						
Local User Database	Yes	Yes	Yes	Yes	No	Yes
Local User Non-Admin Role Allowed	Yes	Yes			N/A	No?
Local User Customized Role Allowed	Yes	Yes			N/A	No?
MS-AD Authentication	Yes	Yes			Yes	Yes
MS-AD Non-Admin Authentication	Yes	Yes			Yes (vSphere 5.x)	No?
MS-AD Customized Role Authentication	Yes	Yes			Yes (vSphere 5.x)	No?
Tool->Storage Cluster MS-AD Authentication	N/A	N/A			Yes	Yes
Tool->Storage Cluster MS-AD Non-Admin Authentication	N/A	N/A			Yes	Maybe—untested
Tool->Storage Cluster MS-AD Customized Role Authentication	N/A	N/A			Yes	Maybe—untested
Tool->SVM MS-AD Authentication	N/A	N/A			Partial (backup requires cluster-wide priv)	No
Tool->SVM MS-AD Non-Admin Authentication	N/A	N/A			Partial (backup requires cluster-wide priv)	No
Tool->SVM MS-AD Customized Role Authentication	N/A	N/A			Partia (backup requires cluster-wide priv)	No
openLDAP Authentication						No
openLDAP Non-Admin Authentication						No
openLDAP Customized Role Authentication						No
Tool->Storage	N/A	N/A				No

Privilege	cDOT 8.2.2	SVM	OCUM 6.2	OPM 1.1	VSC 5.1	System Manager 3.0
Cluster openLDAP Authentication						
Tool->Storage Cluster openLDAP Non-Admin Authentication	N/A	N/A				No
Tool->Storage Cluster openLDAP Customized Role Authentication	N/A	N/A				No
Tool->SVM openLDAP Authentication	N/A	N/A				No
Tool->SVM openLDAP Non-Admin Authentication	N/A	N/A				No
Tool->SVM openLDAP Customized Role Authentication	N/A	N/A				No

## 7 Application Integration and Custom Roles

There are many instances in which you need to integrate NetApp products and third-party products, and those third-party products use a different access method. The ability to include specific commands and capabilities using custom roles allows clustered Data ONTAP to support a very diverse set of role-based access controls.

NetApp management products such as OnCommand® System Manager, OnCommand Unified Manager, OnCommand Workflow Automation, and many others utilize an access method known as the NetApp Manage ONTAP® storage development kit, formerly referred to as the NetApp ONTAPI® library. These management products are generally designed to manage clustered Data ONTAP or to perform specific functions. They typically make assumptions that the product has been given access to manage the solution using a higher-level admin account that has the scope and permission to manage the entire solution.

This section discusses the customization of clustered Data ONTAP roles using the Manage ONTAP framework.

**Note:** Custom roles defined for products that use the Manage ONTAP (ONTAPI) method need to be reevaluated when new versions of either clustered Data ONTAP or the integrated product are released. This is needed to confirm that the custom roles appropriately support any new capabilities that become available and that existing capabilities remain functional post-upgrade.

### 7.1 Custom Roles and Security Logins

Clustered Data ONTAP has several predefined default administration accounts such as `admin` for cluster management and `vsadmin` for storage virtual machine (SVM) management. These default logins use the Manage ONTAP application definition to define them as having either the *admin* role or the *vsadmin* role to give the login complete administrative control over that object.



The `security login create` command creates a login method for the management utility. A login method consists of a user name, an application (access method), and an authentication method. A user name can be associated with multiple applications. It can optionally include an access-control role name.

To see the set of security logins that are currently defined enter `security login show`.

```
cluster02::> security login show
```

```
Vserver: jd_nfs_test
```

UserName	Application	Authentication Method	Role Name	Acct Locked
vsadmin	ontapi	password	vsadmin	no
vsadmin	ssh	password	vsadmin	no

```
Vserver: source_wfa2_DR
```

UserName	Application	Authentication Method	Role Name	Acct Locked
vsadmin	ontapi	password	vsadmin	yes
vsadmin	ssh	password	vsadmin	yes

```
Vserver: cluster02
```

UserName	Application	Authentication Method	Role Name	Acct Locked
admin	console	password	admin	no
admin	http	password	admin	no
admin	ontapi	password	admin	no
admin	service-processor	password	admin	no
admin	ssh	password	admin	no
autosupport	console	password	autosupport	yes
lab\user1	ssh	domain	admin	-
lab\user2	ssh	domain	admin	-
public	snmp	community	readonly	-

13 entries were displayed.

To see the set of commands and access levels that a given role has defined enter `security login role show`.

```
cluster02::> security login role show
```

Vserver	Role Name	Command/Directory	Access Query Level
source_wfa2_DR	vsadmin	DEFAULT	none
source_wfa2_DR	vsadmin	dashboard health vservers	
readonly			
source_wfa2_DR	vsadmin	df	
readonly			
source_wfa2_DR	vsadmin	event generate-autosupport-log	all
source_wfa2_DR	vsadmin	job	all
source_wfa2_DR	vsadmin	job schedule	
readonly			
source_wfa2_DR	vsadmin	job schedule cron	none
source_wfa2_DR	vsadmin	job schedule interval	none
source_wfa2_DR	vsadmin	lun	all
source_wfa2_DR	vsadmin	network connections	
readonly			
source_wfa2_DR	vsadmin	network connections active show-clients	none
source_wfa2_DR	vsadmin	network connections active show-protocols	none
source_wfa2_DR	vsadmin	network connections active show-services	none
source_wfa2_DR	vsadmin	network interface	
readonly			

Although the *admin* role has full or complete access to all commands and directories in the cluster, the *vsadmin* role gives specific access to various commands and directories within the SVM.

Products such as OnCommand System Manager or OnCommand Unified Manager use these default security logins for the Manage ONTAP application. Both of these default login accounts have an ONTAPI

application method defined. Most, if not all, of these management applications assume that their scope of management is complete and thus require access to all commands and directories.

The access levels available for definition in clustered Data ONTAP are *none*, *readonly*, and *all*. You can define an access level for a directory or command, and those definitions are inherited from the parent object. However, the net access level for a subdirectory or lower level in a command tree are cumulative, and if a more or less restrictive command is defined at a lower level it will still have an effect. For example, the *vsadmin* role has the command and *volume* directory tree set to a DEFAULT access level of *none* and then specific exceptions are added.

The same approach cannot be taken for applications such as the OnCommand suite because they were designed to administer the cluster. First, define a role that has the command and directory tree set with a DEFAULT access level of *readonly* or *all*, depending on whether or not you want to specifically allow or deny a capability. This definition for the role allows these products and all other products that use the Manage ONTAP solution or ONTAPI application method to access the information in the cluster. Next, allow or deny access to specific commands and directories.

To begin, create a custom security role using the `security login role create` command.

```
cluster02::> security login role create ?
[ -vserver <vserver name> ]  Vserver (default: cluster02)
[ -role ] <text>              Role Name
[ -cmddirname ] <text>       Command / Directory
[ [-access] <Access> ]       Access Level (default: all)
[ -query <query> ]          Query (default: "")
```

It is important to check if the custom role applies to the cluster or an SVM in the cluster. As an example, if you want to be very restrictive and allow only specific exceptions to commands, then define the DEFAULT access to the command tree to have the *readonly* access level and then define specific exceptions to allow operations such as volume creation. This method is demonstrated later with OnCommand System Manager.

To create a base custom role with restrictive *readonly* access enter:

```
cluster02::> security login role create -vserver cluster02 -role
MyCustomRole_defaultRestrictive -cmddirname DEFAULT -access readonly

cluster02::> security login role show -role MyCustomRole_defaultRestrictive
Role          Command/          Access

Vserver      Name          Directory          Query Level
-----
cluster02 MyCustomRole_defaultRestrictive DEFAULT          readonly
```

Now that a base role has been created to permit either full or *readonly* access, you can then tailor the directories and commands available to these roles. To do so, continue to add additional entries for the directories and commands you specifically desire to either restrict access to or allow access to.

To set the stage, the more restrictive custom role (*MyCustomRole\_defaultRestrictive*) will be allowed to create NetApp FlexVol® volumes, but nothing else. The less restrictive role (*MyCustomRole\_defaultAll*) will be able to administer all cluster objects, but it will be denied the ability to delete FlexVol volumes or take them offline.

To start with the more restrictive role that allows volume creation, enter the command shown below. Note that upon entering this command you are informed that this entry will also affect the *volume modify* and *volume show* commands. In this instance that is okay, but if it were not you would need to make additional entries to further tailor the role.

```
cluster02::> security login role create -vserver cluster02 -role
MyCustomRole_defaultRestrictive -cmddirname "volume create" -access all
```

```
Warning: This operation will also affect the following commands:
"volume modify"
```

```

"volume show"
cluster02::> security login role show -role MyCustomRole_defaultRestrictive
Role          Command/          Access
Vserver      Name          Directory          Query Level
-----
cluster02 MyCustomRole_defaultRestrictive DEFAULT          readonly
cluster02 MyCustomRole_defaultRestrictive volume create      all
cluster02 MyCustomRole_defaultRestrictive volume modify      all
cluster02 MyCustomRole_defaultRestrictive volume show          all
4 entries were displayed.

```

If you want to be less restrictive and allow a broader set of capabilities but then later specifically deny certain commands such as volume deletion, then define the DEFAULT command with the *all* access level. This method will be demonstrated later with OnCommand System Manager.

To create a base custom role with full access enter the following command:

```

cluster02::> security login role create -vserver cluster02 -role
MyCustomRole_defaultAll -cmddirname DEFAULT -access all

cluster02::> security login role show -role MyCustomRole_defaultAll
Role          Command/          Access
Vserver      Name          Directory          Query Level
-----
cluster02 MyCustomRole_defaultAll DEFAULT          all

```

Next we will modify the custom role that has full capabilities by default and restrict that role from deleting FlexVol volumes or taking them offline. Start by entering the following command:

```

cluster02::> security login role create -vserver cluster02 -role
MyCustomRole_defaultAll -cmddirname "volume delete" -access none

cluster02::> security login role create -vserver cluster02 -role
MyCustomRole_defaultAll -cmddirname "volume offline" -access none

cluster02::> security login role show
show          show-ontapi
cluster02::> security login role show -role MyCustomRole_defaultAll
Role          Command/          Access
Vserver      Name          Directory          Query Level
-----
cluster02
MyCustomRole_defaultAll
DEFAULT          all
cluster02
MyCustomRole_defaultAll
volume delete      none
cluster02
MyCustomRole_defaultAll
volume offline      none
3 entries were displayed.

```

After the custom roles have been defined, you next need to create some security logins to use these roles. These logins will only have the application method of Manage ONTAP or ONTAPI defined. We will demonstrate these custom roles using OnCommand System Manager with Active Directory-based logins.

To create a security login for the restrictive role that only allows volume creation enter:

```

cluster02::> security login create -vserver cluster02 -user netapp\OnlyVolumeCreate -
application ontapi -authmethod domain -role MyCustomRole_defaultRestrictive

cluster02::> security login show -vserver cluster02

```

```

Vserver: cluster02
Authentication
User/Group Name Application Method          Role Name          Acct
Locked

```

```

-----
netapp\OnlyVolumeCreate ontapi domain MyCustomRole_defaultRestrictive
no
admin console password admin no
admin http password admin no
admin ontapi password admin no
admin service-processor password admin no
admin ssh password admin no
autosupport console password autosupport no
7 entries were displayed.

```

To create a security login for the less restrictive role that allows everything except for volume deletion enter:

```

cluster02::> security login create -vserver cluster02 -user netapp\NoVolumeDelete -
application ontapi -authmethod domain -role MyCustomRole_defaultAll
cluster02::> security login show -vserver cluster02

```

```


Vserver: cluster02
User/Group Name Application Authentication Method Role Name Acct Locked
-----
netapp\NoVolumeDelete ontapi domain MyCustomRole_defaultAll no
admin console password admin no
admin http password admin no
admin ontapi password admin no
admin service-processor password admin no
admin ssh password admin no
autosupport console password autosupport no
7 entries were displayed.

```

## 7.2 Demonstration of Custom Roles Using OnCommand System Manager

This section demonstrates the custom roles and security logins created in the previous section using OnCommand System Manager.


Figure 4) Example of using custom roles with OnCommand System Manager.




### 7.2.1 Readonly Role with Volume Creation

Here we demonstrate that the netapp\OnlyVolumeCreate user has only the capability to create FlexVol volumes.


We will log in with the netapp\OnlyVolumeCreate user.





Next we navigate to the appropriate SVM and create a NAS FlexVol volume.



This command succeeds and mounts the volume to the namespace.




We then try to share the FlexVol volume using CIFS, which fails.




### 7.2.2 Full Access Role with Volume Deletion Denied

Here we demonstrate that netapp\NoVolumeDelete user has the capability to do everything except delete volumes or take them offline.


We log in with the netapp\OnlyVolumeCreate user.





We create a new FlexVol volume with the name MyOtherTestVol.




We then share this volume through CIFS.



Now let's assume that you no longer need this FlexVol volume and wish to remove it. Go to Shares, select the volume, and right-click to Stop Sharing the I volume. The command succeeds.




Next, unmount the volume.





Then set the volume to offline. After asking you to confirm your action, the system responds with an error because the user does not have permission to take that action.




### 7.3 Determining Required Permissions, Directories, and Commands

Many products that integrate with clustered Data ONTAP, including both NetApp products and third-party products, do not document the minimum required set of directories and commands that are required for the product to function with clustered Data ONTAP. The only method available to determine the minimum required directory and/or command list required is trial and error. Fortunately we can use some of our native auditing tools to assist us. For reference review NetApp Knowledge Base article [KB3014168](#).

#### 7.3.1 SPI Web Interface

The Service Processor Infrastructure (SPI) web interface is a method of enabling access to a cluster or node's log files from a browser and is described in the "Data ONTAP 8.3 System Administration Guide for Cluster Administrators." Note that the SPI web interface is enabled by default in clustered Data ONTAP 8.3.



Navigate to `<nodename>/logs/mlog/command-history.log` and open the file to review any access-denied messages. This will obviously be more challenging on active or production clusters.

```
0000000f.0016ae1b 03cfc1b7 Mon Aug 18 2014 13:51:06 +01:00 [kern_command-
history:info:974] ssh :: 10.68.56.193 :: admin :: security login role create -vserver
```

```

sptech-cluster02 -role MyCustomRole_defaultAll -cmddirname DEFAULT -access all ::
Pending

0000000f.0016ae1d 03cfc1b7 Mon Aug 18 2014 13:51:06 +01:00 [kern_command-
history:info:974] ssh :: 10.68.56.193 :: admin :: security login role create -vserver
sptech-cluster02 -role MyCustomRole_defaultAll -cmddirname DEFAULT -access all ::
Success

0000000f.0016ae48 03cfc454 Mon Aug 18 2014 13:52:13 +01:00 [kern_command-
history:info:974] ssh :: 10.68.56.193 :: admin :: security login role create -vserver
sptech-cluster02 -role MyCustomRole_defaultAll -cmddirname DEFAULT -access all ::
Pending

0000000f.0016ae4b 03cfc454 Mon Aug 18 2014 13:52:13 +01:00 [kern_command-
history:info:974] ssh :: 10.68.56.193 :: admin :: security login role create -vserver
sptech-cluster02 -role MyCustomRole_defaultAll -cmddirname DEFAULT -access all ::
Error: duplicate entry

```

Note that the SPI web interface is not available on clustered Data ONTAP simulators.

From here there is nothing more to do than use the product and, upon feature failure, review the *command-history.log* files to determine the appropriate command or directory with which to enable your default-restricted role.

## 7.4 Demonstration of Custom Roles Using OnCommand Unified Manager and OnCommand Performance Manager

This section provides the clustered Data ONTAP 8.3 commands used for creating roles and users using OnCommand Unified Manager 6.2 and OnCommand Performance Manager. The role must support the following features:

- All the usual monitoring abilities of Unified Manager
- Allow NetApp SnapRestore® technology to function for restores within the same volume (production cluster)
- Allow NDMP restore from other volumes (for example, from SnapVault clusters or disaster recovery clusters)

### 7.4.1 Prerequisites

The role requires that the command `vserver services ndmp` is turned on for the cluster to enable NDMP restores to work.

The command shown here checks and enables NDMP services on the SVM:

```

cluster02::> vserver services ndmp show -vserver cluster02 -fields enable
cluster02::> vserver services ndmp on -vserver cluster02

```

Creating a user called ocum for Unified Manager that can also turn NDMP on results in a relatively unrestricted account:

UserName	Application	Method	Role	Name
ocum	console	password	admin	
ocum	ontapi	password	admin	
ocum	ssh	password	backup	

### 7.4.2 Creating the OnCommand Unified Manager Role

The commands below create a role called ocum:

```

cluster02::> security login role create -role ocum -cmddirname DEFAULT -
access readonly

cluster02::> security login role create -role ocum -cmddirname "volume file
show-disk-usage" -access all

```

```
cluster02::> security login role create -role ocum -cmddirname "volume
snapshot restore-file" -access all

cluster02::> security login role create -role ocum -cmddirname "storage
aggregate check_spare_low" -access all

cluster02::> security login role create -role ocum -cmddirname "storage disk
show" -access all
```

Command lines 1 and 2 are required by OnCommand Unified Manager for monitoring. Command line 4 was added because we saw an alert for `aggr-check-spare-low` with Insufficient privileges in the `command-history.log`.

The second and third lines are required for SnapRestore functionality to work correctly.

Line 5 was added because we saw an error from `storage-shelf-list-info` in the `command-history.log` with Enclosure services not ready at this time. Adding `storage disk show all` also affects `storage disk modify`.

### 7.4.3 Creating the OnCommand Unified Manager User

The commands below create a user called `ocum`:

```
cluster02::> security login create -username ocum -application ontapi -role
ocum -authmethod password

cluster02::> security login create -username ocum -application ssh -role
backup -authmethod password
```

The second line is required because only users with application `ssh` and the role *admin* or *backup* can run the command `vserver services ndmp generate-password`, which is required for NDMP restores to function (also the backup role comes with `vserver services ndmp` all access).

### 7.4.4 Creating the OnCommand Performance Manager Role

The commands below create a role called `opm` for OnCommand Performance Manager:

```
cluster02::> security login role create -role opm -cmddirname DEFAULT -access
readonly

cluster02::> security login role create -role opm -cmddirname "cluster
application-record" -access all

cluster02::> security login role create -role opm -cmddirname "volume modify"
-access all

cluster02::> security login role create -role opm -cmddirname "storage disk
show" -access all
```

The role is constructed by resolving clustered Data ONTAP errors as seen in the `command-history.log`. Insufficient privileges errors were seen for `cluster-application-record-create`, `volume-modify-iter`, and `storage-shelf-list-info`. Adding `volume modify all` also effects `volume create` and `volume show`. Adding `storage disk show all` also affects `storage disk modify`.

### 7.4.5 Creating the OnCommand Performance Manager User

The command below creates a user called `opm`:

```
cluster02::> security login create -username opm -application ontapi -role
opm -authmethod password
```

## 7.4.6 Outputs for OnCommand Unified Manager User and Roles

The commands below show the user called ocum and its role:

```
cluster02::> security login role show -role ocum
```

Role Name	Command/Directory	Query	Access Level
ocum	DEFAULT		readonly
ocum	storage aggregate check_spare_low		all
ocum	storage disk modify		all
ocum	storage disk show		all
ocum	volume file show-disk-usage		all
ocum	volume snapshot restore-file		all

6 entries were displayed.

```
cluster02::> security login role show -role backup
```

Role Name	Command/Directory	Query	Access Level
backup	DEFAULT		none
backup	volume		readonly
backup	vserver services ndmp		all

3 entries were displayed.

```
cluster02::> security login show -user ocum
```

UserName	Application	Authentication Method	Role Name	Acct Locked
ocum	ontapi	password	ocum	no
ocum	ssh	password	backup	no

2 entries were displayed.

**Note:** Backup is a default role and cannot be modified.

## 7.4.7 Outputs for OnCommand Performance Manager User and Roles

The commands below show the user called ocum and its role:

```
cluster02::> security login role show -role opm
```

Role Name	Command/Directory	Query	Access Level
opm	DEFAULT		readonly
opm	cluster application-record		all
opm	storage disk modify		all
opm	storage disk show		all
opm	volume create		all
opm	volume modify		all
opm	volume show		all

7 entries were displayed.

```
cluster02::> security login show -user opm
```

UserName	Application	Authentication Method	Role Name	Acct Locked
opm	ontapi	password	opm	no

## 8 RBAC User Creator

Use the application RBAC User Creator for clustered Data ONTAP to easily create both roles and users for common applications. Currently version 2.7 of RBAC User Creator creates Data ONTAP users and roles for the following applications:

- Virtual Storage Console for VMware vSphere (4.0, 4.1, 4.2, 4.2.1, and 5.0)
- NetApp Snap Creator® Framework (3.6.0 and 4.0.0)
- SnapDrive for Windows (6.4.2)
- Storage Replication Adapter for VMware vCenter™ Site Recovery Manager™ (2.1)
- Virtual Storage Console for Citrix XenServer (2.0 and 2.0.1)
- Virtual Storage Console for Red Hat Enterprise Virtualization (1.0)
- NetApp Recovery Manager for Citrix ShareFile (1.0)
- VMTurbo Operations Manager (2.0)
- OnCommand Balance
- SnapDrive for Windows

RBAC User Creator requires a Windows host to run. The RBAC User Creator tool is a free tool located in the NetApp MySupport Toolchest. It is supported on a best-effort volunteer basis through the communities: <https://communities.netapp.com/docs/DOC-19074>.

The RBAC User Creator tool was created to reduce error and improve the speed of provisioning of custom application-based roles for the NetApp Virtual Storage Console. The tool is structured to support extensible updates by the end user with an XML-based INI file.

Because of this flexibility, numerous precreated roles are defined in the current release of the RBAC User Creator tool. It is important to note that this tool supports both Data ONTAP systems operating in 7-Mode and clustered Data ONTAP systems. Some roles, such as DFM 5.2, are only for Data ONTAP systems operating in 7-Mode and will fail to provision against clustered Data ONTAP systems. This can be explicitly validated by reviewing the easy-to-read INI files.

The following section provides an example workflow of provisioning an SVM-specific role for Virtual Storage Console 4.2.1 with clustered Data ONTAP 8.3.

### 8.1.1 Creating a Custom Role from the Graphical User Interface (GUI)

1. Enter the admin credentials for the cluster and click **Login**.

RBAC User Creator for Data ONTAP®

Welcome to the RBAC User Creator for Data ONTAP® v2.7

**Storage System**  
Enter the storage system hostname/IP address, and the root/admin credentials.

Storage system : cluster01

Port : 443 ☒ use SSL

User name : admin

Password : ..... **Login**

**Product Selection**  
Select the product to create the user for

Select product

Select product version

**Username to create**

Vserver : Select Vserver

Role name : Select role name

User name : Select user name

Password :

**Select the Data ONTAP® privilege role :**

**Preview**

☐ Offline Mode

☐ Generate commands for scripting

**Cancel** **Submit**

Connected admin @ cluster01 : 443 [Data ONTAP 8.2.1 Clustered Data ONTAP]

2. Select the product, version, and capabilities in the right-hand pane.
3. Choose the storage virtual machine (formerly known as Vserver) and enter text for the new role name and the new user name.

**Note:** Do not press the drop-down for role name and user name. Enter new text here.

RBAC User Creator for Data ONTAP®

Welcome to the RBAC User Creator for Data ONTAP® v2.7

Storage System

Enter the storage system hostname/IP address, and the root/admin credentials.

Storage system : cluster01

Port : 443 ☒ use SSL

User name : admin

Password : .....

Login

Product Selection

Select the product to create the user for

VSC for VMware

VSC 4.2.1

Select the Data ONTAP® privilege role :

☒ All

- ☒ Discovery
- ☒ Create Clones
- ☒ Create Storage
- ☒ Modify Storage
- ☒ Destroy Storage
- ☒ Backup-Recovery

Preview

Username to create

Vserver : vs1

Role name : vsc\_vmware\_role

User name : vsc\_vmware\_user

Password : .....


☐ Offline Mode
☐ Generate commands for scripting

Cancel


Submit

Connected admin @ cluster01 : 443 [Data ONTAP 8.2.1 Clustered Data ONTAP]





Allow the RBAC User Creator tool to provision APIs. Do not close until you see the Success message.



#### 4. Check at the command line interface to see if the user was created.

```
cluster01::> security login role show -role vsc_role
```

Vserver	Role Name	Command/Directory	Access Query Level
cluster01	vsc_role	DEFAULT	none
cluster01	vsc_role	job history show	all
cluster01	vsc_role	job show-completed	readonly
cluster01	vsc_role	lun comment	all
cluster01	vsc_role	lun create	all
cluster01	vsc_role	lun delete	all
cluster01	vsc_role	lun geometry	readonly




```

cluster01 vsc_role lun igroup add all
cluster01 vsc_role lun igroup create all
cluster01 vsc_role lun igroup delete all
cluster01 vsc_role lun igroup modify all
cluster01 vsc_role lun igroup new all
cluster01 vsc_role lun igroup set all
cluster01 vsc_role lun igroup show all
cluster01 vsc_role lun map all
cluster01 vsc_role lun mapped show all
cluster01 vsc_role lun modify all
cluster01 vsc_role lun move all
cluster01 vsc_role lun new all
cluster01 vsc_role lun show all
20 entries were displayed.

```

## 5. Enter and test credentials in the vSphere VSC tool.



As discussed in earlier sections, not all management tools support SVM-level credentials or all features working with SVM-level credentials. Always review the management tool “Installation and Administration Guides and Release Notes” for up-to-date guidance.

Using the RBAC User Creator tool:

- Implement the role.
- Configure your tools.
- Test the tool.
- Review the audit log after deployment to validate that everything works correctly.

### 8.1.2 Creating a Custom Role Using XML Files

RBAC User Creator uses an XML file called `ontapPrivs.xml` to define which privileges a product requires.

You can create privileges for custom products by adding your own XML to the `ontapPrivs.xml` file, before the `</privs>` end-tag.

In the following example we create a template for the custom OCUM role that was defined earlier in this document. You can use this template to roll out the same custom role to multiple clusters within your environment.


```

<product id="customocum" label="Custom Unified Manager User" description="">
  <customocum id="customocum10" label="Custom OCUM User v1.0">
    <cluster-mode>
      <admin-vserver>
        <role id="cOCUM" label="Unified Manager User Role" description="">
          <read-only>
            <ontap-dependent value="8.2+">
              <command>DEFAULT</command>
            </ontap-dependent>
          </read-only>
          <all-access>
            <ontap-dependent value="8.2+">
              <command>volume file show-disk-usage</command>
              <command>volume snapshot restore-file</command>
              <command>storage aggregate check_spare_low</command>
              <command>storage disk show</command>
            </ontap-dependent>
          </all-access>
        </role>
      </admin-vserver>
    </cluster-mode>
  </customocum>
</product>

```

In this example we define which release of clustered Data ONTAP this custom role can be applied to by using the `<ontap-dependent value="8.2+">` tag. This information is important because releases can have variations in command syntax.

With the Custom OCUM User XML added to the `ontapPrivs.xml` file, you can now use the RBAC User Creator tool to create the custom role on your storage systems.



## 9 Summary

Role-Based Access Control changes clustered Data ONTAP to a distributed set of delegated authorities to execute discrete tasks. This change removes the risk inherent in a centralized model.

RBAC offers a secure method for efficiently managing users. Benefits of an RBAC solution include:

**Increased security:** User profiles and privileges can be modified rapidly. Changing policies and updating user profiles in a timely manner can help maintain high levels of security.

**Security of complex organizations:** RBAC provides the ability to model complex organizations through the creation of roles and the delegation of their administration. Changes can be made quickly as the organization and its security policies evolve.

**Reduced complexity:** Distributing administration to delegated administrators is a centralized method for managing large groups of users, thus reducing the complexity of the process.

**Reduced costs:** Administering authorization data is cumbersome and can create a long-term financial burden. By using delegated administrators, a company can outsource the workload to administrators within customer, supplier, and partner organizations, ultimately reducing costs.

## Appendix

### Resources

- [RBAC Creator for Data ONTAP](#)  
This tool is a C# application that assists you in creating RBAC user names for Data ONTAP in both 7-Mode and clustered Data ONTAP environments.
- [Managing access to the cluster \(8.3\)](#)
- [What is clustered Data ONTAP audit information and control?](#)
- [SPI information: Clustered Data ONTAP 8.3 System Administration Guide \(page 48\)](#)
- [Clustered Data ONTAP 8.3 Commands: Manual Page Reference](#)

### Acronyms, Terminology

Acronyms, Terminology	Explanation
OffTap	OnCommand, all NetApp Snap products, VSC, DSM, Opens Systems SnapVault (OSSV)
Transition, Transitioning to clustered Data ONTAP	The 'end-to-end' process of moving Data ONTAP 7G/7-Mode and third-party environments to clustered Data ONTAP. To support, all inclusively, a successful move to clustered Data ONTAP, transition includes: <ul style="list-style-type: none"><li>• Process</li><li>• Policy and technology offerings used during the assessment</li><li>• Planning</li><li>• Migration</li><li>• Operational phases to support a successful move to clustered Data ONTAP.</li></ul>

## Version History

Version	Date	Document Version History
Version 1.0 prerelease reviews	August 2014	First release of draft copy for review
	November 2014	Updated for clustered Data ONTAP 8.3
	January 2015	Updated per team review comments

Feedback for this document can be sent to any of its authors or posted on <https://forums.netapp.com/community/acs/sx/cdot>.

Refer to the [Interoperability Matrix Tool \(IMT\)](#) on the NetApp Support site to validate that the exact product and feature versions described in this document are supported for your specific environment. The NetApp IMT defines the product components and versions that can be used to construct configurations that are supported by NetApp. Specific results depend on each customer's installation in accordance with published specifications.

## Copyright Information

Copyright © 1994–2015 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NetApp, the NetApp logo, Go Further, Faster, ASUP, AutoSupport, Campaign Express, Cloud ONTAP, Customer Fitness, Data ONTAP, DataMotion, Fitness, Flash Accel, Flash Cache, Flash Pool, FlashRay, FlexArray, FlexCache, FlexClone, FlexPod, FlexScale, FlexShare, FlexVol, FPolicy, GetSuccessful, LockVault, Manage ONTAP, Mars, MetroCluster, MultiStore, NetApp Insight, OnCommand, ONTAP, ONTAPI, RAID DP, SANtricity, SecureShare, Simplicity, Simulate ONTAP, Snap Creator, SnapCopy, SnapDrive, SnapIntegrator, SnapLock, SnapManager, SnapMirror, SnapMover, SnapProtect, SnapRestore, Snapshot, SnapValidator, SnapVault, StorageGRID, Tech OnTap, Unbound Cloud, and WAFL are trademarks or registered trademarks of NetApp, Inc., in the United States and/or other countries. A current list of NetApp trademarks is available on the Web at <http://www.netapp.com/us/legal/netapptmlist.aspx>.

Cisco and the Cisco logo are trademarks of Cisco in the U.S. and other countries. All other brands or products are trademarks or registered trademarks of their respective holders and should be treated as such. TR-4368-0115

