Give an agent its own Google account profile

Connect one Google account to the `gws` command-line tool so an agent can read that account's Drive and Docs, and nothing else.

Kind Walkthrough | Changed 2026-11-09 | For Anyone connecting a Google account to a helper

You are here: drasticstatic lab › `my-template` › `walkthroughs` › `GOOGLE-WORKSPACE-CLI-NEW-PROFILE.md` · public · `main` is the working branch

TL;DR

1. **One account, one profile.** Each account gets its own folder, its own Cloud project and its own login, so a mistake in one can never touch another.
2. **Read-only first.** The agent can look at Drive and Docs but not change anything, until you widen it on purpose.
3. **Who does what:** an agent can prepare the folder and the wrapper. Signing in, passwords and consent screens are always done by a person.
4. **Prove the account before you trust it** (step 6). If the address is not `ACCOUNT`, stop.


> ***Handing this to your AI helper?*** *Say: "Read GOOGLE-WORKSPACE-CLI-NEW-PROFILE.md and prepare steps 1 and 6 for me. I will do the browser steps myself."*

You need: about 15 minutes, a browser signed in to the target account, and `gws` already installed (check with `gws --version`).

Throughout, replace:

Placeholder	Meaning	Example
`ACCOUNT`	the Google account being connected	`you@yourorg.org`
`NAME`	a short label for this profile	`acme`

How the pieces fit



1. Make the isolated folder and wrapper

```
mkdir -m 700 -p ~/.config/gws-NAME
mkdir -p ~/.local/bin
cat > ~/.local/bin/gwsNAME <<'EOF'
```

```
#!/bin/sh
GOOGLE_WORKSPACE_CLI_CONFIG_DIR="$HOME/.config/gws-NAME" exec gws "$@"
EOF
chmod +x ~/.local/bin/gwsNAME
gwsNAME auth status
```

You should see: `auth status` report `"auth_method": "none"` and point only at `~/.config/gws-NAME`. That is the smoke test: the profile is isolated and empty. Never use a bare `gws` once you have more than one account.

2. Create the Cloud project

1. Open https://console.cloud.google.com/projectcreate.
2. Click your picture, top right, and confirm it shows `ACCOUNT`. The console opens on whichever account the browser used last, and this is the easiest step to get wrong.
3. Replace the default "My Project 12345" with a real name, because the project ID comes from it and cannot be changed later. Choose the organization if one is offered, and click **Create**.

You should see: the new project's name in the console's project picker, under `ACCOUNT`.

If the page says you lack permission to create projects, a Workspace administrator has to create it for you or grant the Project Creator role. Google may also ask for your password again here. That is normal.

3. Turn on only the APIs you need

APIs & Services → Library. For a read-only start, enable **Google Drive API** and **Google Docs API**. Add others later if a real need appears.

You should see: both APIs listed under **APIs & Services → Enabled APIs & services**.

4. Create the desktop login

1. Open **Google Auth Platform** (search for it in the console's top bar) and click **Get started**.
2. **App Information:** give the app a name and choose `ACCOUNT` as the support email.
3. **Audience:** on a Workspace account choose **Internal**, which limits the app to your organization. On a personal account choose **External** and afterward add `ACCOUNT` under **Audience → Test users**, even if you own the project.
4. **Contact Information:** enter `ACCOUNT`.
5. **Finish:** read and tick the Google API Services User Data Policy yourself, then **Continue** and **Create**.
6. **Clients → Create client.** Application type **Desktop app**, name it, leave "Use this client for an AI-powered agent" unticked, and click **Create**.
7. Click **Download JSON** in the dialog that appears. Do this before closing it, and do not screenshot that dialog.
8. Move it into the profile, using the file you just downloaded:

```
mv ~/Downloads/client_secret_*.json ~/.config/gws-NAME/client_secret.json
chmod 600 ~/.config/gws-NAME/client_secret.json
```

You should see: `ls -l ~/.config/gws-NAME` list `client_secret.json` with `-rw-------`.

> ***Warning.*** *This file is a credential. Never commit it, paste it into a chat, or show it on a screen share.*

5. Sign in, read-only

```
gwsNAME auth login --readonly -s drive,docs
```

A browser opens. Choose `ACCOUNT` and approve. `--readonly` means the agent can look but not change anything, and you can widen it later on purpose.

You should see: the terminal confirm the login, and `gwsNAME auth status` no longer report `"auth_method": "none"`.

6. Prove it is the right account

```
gwsNAME drive about get --params '{"fields":"user(emailAddress)"}'
```

The address must be `ACCOUNT`. If it is anything else, stop and start again at step 2.

Then read one document you are allowed to see:

```
gwsNAME docs documents get --params '{"documentId":"DOC_ID","fields":"title"}'
```

You should see: that document's title, and nothing else.

If something goes wrong

What you see	What it means
`invalid_grant` or 401	The login expired. Run step 5 again. External apps in Testing expire after about a week.
`Error 403: access_denied` at sign-in	`ACCOUNT` is not listed as a test user (step 4).
`403` on a Drive or Docs call	That API is not enabled in this project (step 3).
A password box when opening the console	Google wants you to confirm it is you. Type it yourself.
`Access blocked` naming another app	You are using the wrong wrapper for this account.

Taking it away

Revoke access at https://myaccount.google.com/permissions, then move `~/.config/gws-NAME` aside. Deleting the Cloud project removes the login for good.

See also

- Gemini CLI access: the sibling walkthrough, for when the same kind of account should also run Gemini in the terminal, and for its Workspace administrator.
- Connect Google Drive: the simpler built-in connections, when the helper only needs to read.

- `pir-devine-news` › GWS_SETUP.md (a private repository; the same page is public in `pir-devine-news-public`): a committee's profile, with its sync script and several profiles side by side.
- GWS_SETUP.md, the first worked profile (in a private repository of the lab's): written before this general version, with several profiles in one table.

Suggest a change

Noticed something wrong, or know a better way? Open an issue or a pull request against `main`; the lab steward reads them, and a person with the role merges with a merge commit so your name stays on it. Not on GitHub? Tell any steward you know, or your helper, in your own words.

One of the walkthroughs in `my-template`, in the shape of `walkthroughs-template/`. Icons: Phosphor duotone (MIT). The PDF in `pdf/` is rendered from this page; edit the markdown, not the PDF.