Table 1: Equal-family mean AUROC and AP for all 25 core PU configurations.

Block 1: nonboosting PU				
Method	AUROC OS	AUROC TS	AP OS	AP TS
Logistic probability correction	0.712	0.711	0.397	0.394
uPU logistic	0.711	0.710	0.397	0.392
nnPU logistic	0.711	0.710	0.397	0.393

Block 2: boosting				
Method	AUROC OS	AUROC TS	AP OS	AP TS
Naive AdaBoost	0.704	0.703	0.380	0.375
Naive GBM	0.706	0.705	0.380	0.373
Naive XGBoost	0.710	0.709	0.392	0.385
Naive LightGBM	0.700	0.699	0.376	0.367
Naive CatBoost	0.714	0.713	0.397	0.391
Corrected AdaBoost	0.704	0.703	0.380	0.375
Corrected GBM	0.706	0.705	0.380	0.373
Corrected XGBoost	0.710	0.709	0.392	0.385
Corrected LightGBM	0.700	0.699	0.376	0.367
Corrected CatBoost	0.714	0.713	0.397	0.391
RN AdaBoost	0.699	0.699	0.368	0.366
RN GBM	0.697	0.697	0.352	0.349
RN XGBoost	0.700	0.699	0.366	0.362
RN LightGBM	0.696	0.696	0.356	0.353
RN CatBoost	0.703	0.702	0.367	0.363
CS AdaBoost	0.704	0.703	0.381	0.375
CS GBM	0.706	0.705	0.384	0.377
CS XGBoost	0.710	0.709	0.392	0.385
CS LightGBM	0.700	0.699	0.378	0.370
CS CatBoost	0.714	0.713	0.397	0.391

Block 3: native PU				
Method	AUROC OS	AUROC TS	AP OS	AP TS
AdaPU	0.693	0.694	0.382	0.381
PU gradient boosting	0.687	0.696	0.366	0.370

Note. First average settings within each family, then weight all ten families equally. Every scenario/method mean has 100 repetitions. OS: one-sample; TS: two-sample.