Table 1: Effect of additional positive-label information: budget 0.20 minus 0.05, in percentage points. Differences are computed between within-dataset split means before averaging equally across eight datasets.

Method	AUROC OS	AUROC TS	AP OS	AP TS
Logistic probability correction	+2.970 (8/8)	+2.745 (8/8)	+3.559 (8/8)	+3.241 (8/8)
nnPU logistic	+2.373 (8/8)	+2.220 (8/8)	+2.841 (8/8)	+2.454 (8/8)
Naive CatBoost	+2.473 (8/8)	+2.202 (8/8)	+3.627 (8/8)	+3.066 (8/8)
CS CatBoost	+3.015 (8/8)	+2.497 (8/8)	+4.456 (8/8)	+3.569 (8/8)
RN CatBoost	+1.691 (7/8)	+1.492 (8/8)	+1.903 (7/8)	+1.713 (7/8)
PU gradient boosting	+5.957 (8/8)	+3.232 (8/8)	+8.378 (8/8)	+4.719 (8/8)

Parentheses give the number of datasets with a positive change. Each budget has 20 archived splits per condition; differences compare budget-specific means and are not assumed to pair identical observations across budgets. Dataset-specific values and negative/zero counts are retained in the CSV. No population-level inference is attached.