Table 1: Matched neural-minus-linear real-data ranking differences, in percentage points. For each dataset, 20 paired split differences are averaged within each condition, then the four design-budget conditions are weighted equally. The final row weights the eight datasets equally.

uPU

	AUROC difference		AP difference	
Dataset	Label-AUC	PU-risk	Label-AUC	PU-risk
Credit Default	+0.956	+0.212	+0.781	+0.092
Dry Bean	-0.388	-0.313	-1.095	-0.912
HTRU2	-0.638	-1.699	+0.089	-1.610
Online Shoppers	+0.303	+0.723	+0.394	+0.770
Optical Digits	+3.613	+3.414	+4.091	+4.067
Phishing Websites	+0.801	+2.197	+0.573	+1.930
Rice	-0.332	-0.837	-0.596	-0.919
Spambase	+0.930	+1.047	+1.563	+2.191
Equal-dataset mean	+0.656	+0.593	+0.725	+0.701

nnPU

	AUROC difference		AP difference	
Dataset	Label-AUC	PU-risk	Label-AUC	PU-risk
Credit Default	+0.837	+0.240	+0.476	+0.126
Dry Bean	-0.243	-0.016	-0.727	-0.089
HTRU2	-0.243	-0.108	+0.566	+0.228
Online Shoppers	+0.600	+0.840	+0.602	+0.832
Optical Digits	+3.970	+2.697	+4.672	+3.316
Phishing Websites	+0.966	+1.525	+0.771	+1.257
Rice	-0.122	-0.143	-0.399	-0.271
Spambase	+0.552	+1.604	+1.003	+2.488
Equal-dataset mean	+0.790	+0.830	+0.871	+0.986

Label-AUC selects on observed validation P/U labels, not hidden true Y. PU-risk selects on the empirical PU risk. These are matched extension linear baselines, not substitutions for the core catalog. Repeated splits overlap; no population-inference interval is shown. This is the preserved fixed-budget study: 522/5,120 selections reached 3,000 epochs, and the original numerical cap gate was not passed; execution/metric checks passed. No convergence claim is made.