

# Reinforcement Learning

## Monte Carlo Control (RLAI 5)

Christopher Simpkins

Kennesaw State University



# Monte Carlo Control

Monte Carlo methods are ways of solving the reinforcement learning problem based on averaging sample returns.

- ▶ Monte carlo prediction of  $v_\pi$  and  $q_\pi$  values
- ▶ Policy improvement via monte carlo estimation of action values
- ▶ Monte carlo control via approximate policy and action-value functions

# First Visit Monte Carlo Prediction of State Values

## First-visit MC prediction, for estimating $V \approx v_\pi$

Input: a policy  $\pi$  to be evaluated

Initialize:

$V(s) \in \mathbb{R}$ , arbitrarily, for all  $s \in \mathcal{S}$

$Returns(s) \leftarrow$  an empty list, for all  $s \in \mathcal{S}$

Loop forever (for each episode):

Generate an episode following  $\pi$ :  $S_0, A_0, R_1, S_1, A_1, R_2, \dots, S_{T-1}, A_{T-1}, R_T$

$G \leftarrow 0$

Loop for each step of episode,  $t = T-1, T-2, \dots, 0$ :

$G \leftarrow \gamma G + R_{t+1}$

Unless  $S_t$  appears in  $S_0, S_1, \dots, S_{t-1}$ :

Append  $G$  to  $Returns(S_t)$

$V(S_t) \leftarrow \text{average}(Returns(S_t))$


## Example: Blackjack

```
{=late x } \begin{cards} \crdpair{\crdKs}{\crdtenh}% \end{cards}
```

# Monte Carlo Prediction of Action Values

Foo


# Monte Carlo Control



## Value Backups

In dynamic programming MDP solution, values are backed up from each possible successor states:

$$v_{\pi} = \sum_a \pi(a | s) \sum_{s', r} p(s', r | s, a) [r + \gamma v_{\pi}(s')]$$




DP one-step, all successors value backup




MC full single trajectory backup

# Monte Carlo Control





# Monte Carlo Control



# Monte Carlo Control

Monte Carlo ES (Exploring Starts), for estimating  $\pi \approx \pi_*$

Initialize:

$\pi(s) \in \mathcal{A}(s)$  (arbitrarily), for all  $s \in \mathcal{S}$

$Q(s, a) \in \mathbb{R}$  (arbitrarily), for all  $s \in \mathcal{S}, a \in \mathcal{A}(s)$

$Returns(s, a) \leftarrow$  empty list, for all  $s \in \mathcal{S}, a \in \mathcal{A}(s)$

Loop forever (for each episode):

Choose  $S_0 \in \mathcal{S}, A_0 \in \mathcal{A}(S_0)$  randomly such that all pairs have probability  $> 0$

Generate an episode from  $S_0, A_0$ , following  $\pi$ :  $S_0, A_0, R_1, \dots, S_{T-1}, A_{T-1}, R_T$

$G \leftarrow 0$

Loop for each step of episode,  $t = T-1, T-2, \dots, 0$ :

$G \leftarrow \gamma G + R_{t+1}$





Unless the pair  $S_t, A_t$  appears in  $S_0, A_0, S_1, A_1, \dots, S_{t-1}, A_{t-1}$ :

Append  $G$  to  $Returns(S_t, A_t)$

$Q(S_t, A_t) \leftarrow \text{average}(Returns(S_t, A_t))$

$\pi(S_t) \leftarrow \arg\max_a Q(S_t, a)$

# Monte Carlo Control



# Monte Carlo Control

**On-policy first-visit MC control (for  $\varepsilon$ -soft policies), estimates  $\pi \approx \pi_*$**

Algorithm parameter: small  $\varepsilon > 0$

Initialize:

$\pi \leftarrow$  an arbitrary  $\varepsilon$ -soft policy

$Q(s, a) \in \mathbb{R}$  (arbitrarily), for all  $s \in \mathcal{S}$ ,  $a \in \mathcal{A}(s)$

$Returns(s, a) \leftarrow$  empty list, for all  $s \in \mathcal{S}$ ,  $a \in \mathcal{A}(s)$

Repeat forever (for each episode):

Generate an episode following  $\pi$ :  $S_0, A_0, R_1, \dots, S_{T-1}, A_{T-1}, R_T$

$G \leftarrow 0$

Loop for each step of episode,  $t = T-1, T-2, \dots, 0$ :

$G \leftarrow \gamma G + R_{t+1}$

Unless the pair  $S_t, A_t$  appears in  $S_0, A_0, S_1, A_1, \dots, S_{t-1}, A_{t-1}$ :

Append  $G$  to  $Returns(S_t, A_t)$


$Q(S_t, A_t) \leftarrow \text{average}(Returns(S_t, A_t))$

$A^* \leftarrow \operatorname{argmax}_a Q(S_t, a)$  (with ties broken arbitrarily)


For all  $a \in \mathcal{A}(S_t)$ :

$$\pi(a|S_t) \leftarrow \begin{cases} 1 - \varepsilon + \varepsilon/|\mathcal{A}(S_t)| & \text{if } a = A^* \\ \varepsilon/|\mathcal{A}(S_t)| & \text{if } a \neq A^* \end{cases}$$

# Monte Carlo Control



# Monte Carlo Control



# Monte Carlo Control

## Off-policy MC prediction (policy evaluation) for estimating $Q \approx q_\pi$

Input: an arbitrary target policy  $\pi$

Initialize, for all  $s \in \mathcal{S}$ ,  $a \in \mathcal{A}(s)$ :

$Q(s, a) \in \mathbb{R}$  (arbitrarily)

$C(s, a) \leftarrow 0$

Loop forever (for each episode):

$b \leftarrow$  any policy with coverage of  $\pi$

Generate an episode following  $b$ :  $S_0, A_0, R_1, \dots, S_{T-1}, A_{T-1}, R_T$

$G \leftarrow 0$

$W \leftarrow 1$

Loop for each step of episode,  $t = T-1, T-2, \dots, 0$ , while  $W \neq 0$ :

$G \leftarrow \gamma G + R_{t+1}$

$C(S_t, A_t) \leftarrow C(S_t, A_t) + W$

$Q(S_t, A_t) \leftarrow Q(S_t, A_t) + \frac{W}{C(S_t, A_t)} [G - Q(S_t, A_t)]$

$W \leftarrow W \frac{\pi(A_t|S_t)}{b(A_t|S_t)}$

# Monte Carlo Control

## Off-policy MC control, for estimating $\pi \approx \pi_*$

Initialize, for all  $s \in \mathcal{S}$ ,  $a \in \mathcal{A}(s)$ :

$Q(s, a) \in \mathbb{R}$  (arbitrarily)

$C(s, a) \leftarrow 0$

$\pi(s) \leftarrow \operatorname{argmax}_a Q(s, a)$  (with ties broken consistently)

Loop forever (for each episode):

$b \leftarrow$  any soft policy

Generate an episode using  $b$ :  $S_0, A_0, R_1, \dots, S_{T-1}, A_{T-1}, R_T$

$G \leftarrow 0$

$W \leftarrow 1$

Loop for each step of episode,  $t = T-1, T-2, \dots, 0$ :

$G \leftarrow \gamma G + R_{t+1}$

$C(S_t, A_t) \leftarrow C(S_t, A_t) + W$

$Q(S_t, A_t) \leftarrow Q(S_t, A_t) + \frac{W}{C(S_t, A_t)} [G - Q(S_t, A_t)]$

$\pi(S_t) \leftarrow \operatorname{argmax}_a Q(S_t, a)$  (with ties broken consistently)

If  $A_t \neq \pi(S_t)$  then exit inner Loop (proceed to next episode)

$W \leftarrow W \frac{1}{b(A_t|S_t)}$



# Monte Carlo Control

