

function LIKELIHOOD-WEIGHTING(X, \mathbf{e}, bn, N) **returns** an estimate of $\mathbf{P}(X \mid \mathbf{e})$

inputs: X , the query variable

\mathbf{e} , observed values for variables \mathbf{E}

bn , a Bayesian network specifying joint distribution $\mathbf{P}(X_1, \dots, X_n)$

N , the total number of samples to be generated

local variables: \mathbf{W} , a vector of weighted counts for each value of X , initially zero

for $j = 1$ **to** N **do**

$\mathbf{x}, w \leftarrow \text{WEIGHTED-SAMPLE}(bn, \mathbf{e})$

$\mathbf{W}[j] \leftarrow \mathbf{W}[j] + w$ where x_j is the value of X in \mathbf{x}

return $\text{NORMALIZE}(\mathbf{W})$

function WEIGHTED-SAMPLE(bn, \mathbf{e}) **returns** an event and a weight

$w \leftarrow 1$; $\mathbf{x} \leftarrow$ an event with n elements, with values fixed from \mathbf{e}

for $i = 1$ **to** n **do**

if X_i is an evidence variable with value x_{ij} in \mathbf{e}

then $w \leftarrow w \times P(X_i = x_{ij} \mid \text{parents}(X_i))$

else $\mathbf{x}[i] \leftarrow$ a random sample from $\mathbf{P}(X_i \mid \text{parents}(X_i))$

return \mathbf{x}, w