



Untitled diff

- 5 removals

195 lines

```
1 name: Deploy materialize-master (CF
  Gen2 + Cloud Scheduler)
2
3 on:
4   workflow_dispatch:
5   push:
6     branches: [ main ]
7     paths:
8       - 'cloud_function/materialize-
master/**'
9       - '.github/workflows/deploy-
materialize-master.yml'
10
11 permissions:
12   contents: read
13   id-token: write
14
15 env:
16   PROJECT_ID: ${vars.PROJECT_ID}
17   REGION: ${vars.REGION}
18   FUNCTION_NAME: materialize-master
19   FUNCTION_DIR:
cloud_function/materialize-master
20   ENTRY_POINT: materialize_http
21   RUNTIME: python312
22   BUCKET_NAME: ${vars.BUCKET_NAME}
23   TIMEOUT_SECONDS: "900"
24   MEMORY: "2Gi"
25   STRUCTURED_PREFIX: "structured"
26   RUNTIME_SA: ${vars.RUNTIME_SA}
27   DEPLOYER_SA: ${vars.DEPLOYER_SA}
28   WORKLOAD_IDENTITY_PROVIDER: ${vars.WORKLOAD_IDENTITY_PROVIDER}
29   SCHEDULE_BODY: ${vars.MATERIALIZE_BODY || '{}'}
30   CRON_EXPR: "15 * * * *" # :15 each
  hour
```

+ 5 additions

195 lines

```
1 name: Deploy materialize-master-llm (CF
  Gen2 + Cloud Scheduler)
2
3 on:
4   workflow_dispatch:
5   push:
6     branches: [ main ]
7     paths:
8       - 'cloud_function/materialize-
master-llm/**'
9       - '.github/workflows/deploy-
materialize-master-llm.yml'
10
11 permissions:
12   contents: read
13   id-token: write
14
15 env:
16   PROJECT_ID: ${vars.PROJECT_ID}
17   REGION: ${vars.REGION}
18   FUNCTION_NAME: materialize-master-llm
19   FUNCTION_DIR:
cloud_function/materialize-master-llm
20   ENTRY_POINT: materialize_http
21   RUNTIME: python312
22   BUCKET_NAME: ${vars.BUCKET_NAME}
23   TIMEOUT_SECONDS: "900"
24   MEMORY: "2Gi"
25   STRUCTURED_PREFIX: "structured"
26   RUNTIME_SA: ${vars.RUNTIME_SA}
27   DEPLOYER_SA: ${vars.DEPLOYER_SA}
28   WORKLOAD_IDENTITY_PROVIDER: ${vars.WORKLOAD_IDENTITY_PROVIDER}
29   SCHEDULE_BODY: ${vars.MATERIALIZE_BODY || '{}'}
30   CRON_EXPR: "15 * * * *" # :15 each
  hour
```

```
31
32 jobs:
33   deploy:
34     runs-on: ubuntu-latest
35     steps:
36       - uses: actions/checkout@v4
37
38       - name: Auth (WIF)
39         uses: google-github-
          actions/auth@v2
40       with:
41         workload_identity_provider:
42           ${{ env.WORKLOAD_IDENTITY_PROVIDER }}
43         service_account: ${{
44           env.DEPLOYER_SA }}
45         create_credentials_file: true
46         export_environment_variables:
47           true
48       - name: Setup gcloud
49         uses: google-github-
          actions/setup-gcloud@v2
50       with:
51         project_id: ${{
52           env.PROJECT_ID }}
53       - name: Verify source
54         shell: bash
55         run: |
56           set -euo pipefail
57           ls -la "${FUNCTION_DIR}"
58           test -f
59             "${FUNCTION_DIR}/main.py"
60           test -f
61             "${FUNCTION_DIR}/requirements.txt"
62       - name: Deploy Cloud Function
63         (Gen2)
64         shell: bash
65         run: |
66           set -euo pipefail
67           SA_ARGS=()
68           if [[ -n "${RUNTIME_SA:-}"
69             ]]; then
70             gcloud iam service-accounts
71             describe "${RUNTIME_SA}" >/dev/null
72             2>&1
73           SA_ARGS=(--service-
74             account="${RUNTIME_SA}")
```

```
31
32 jobs:
33   deploy:
34     runs-on: ubuntu-latest
35     steps:
36       - uses: actions/checkout@v4
37
38       - name: Auth (WIF)
39         uses: google-github-
          actions/auth@v2
40       with:
41         workload_identity_provider:
42           ${{ env.WORKLOAD_IDENTITY_PROVIDER }}
43         service_account: ${{
44           env.DEPLOYER_SA }}
45         create_credentials_file: true
46         export_environment_variables:
47           true
48       - name: Setup gcloud
49         uses: google-github-
          actions/setup-gcloud@v2
50       with:
51         project_id: ${{
52           env.PROJECT_ID }}
53       - name: Verify source
54         shell: bash
55         run: |
56           set -euo pipefail
57           ls -la "${FUNCTION_DIR}"
58           test -f
59             "${FUNCTION_DIR}/main.py"
60           test -f
61             "${FUNCTION_DIR}/requirements.txt"
62       - name: Deploy Cloud Function
63         (Gen2)
64         shell: bash
65         run: |
66           set -euo pipefail
67           SA_ARGS=()
68           if [[ -n "${RUNTIME_SA:-}"
69             ]]; then
70             gcloud iam service-accounts
71             describe "${RUNTIME_SA}" >/dev/null
72             2>&1
73           SA_ARGS=(--service-
74             account="${RUNTIME_SA}")
```

```

67         fi
68
69         gcloud functions deploy
        "${FUNCTION_NAME}" \
70             --gen2 \
71             --region="${REGION}" \
72             --runtime="${RUNTIME}" \
73             --source="${FUNCTION_DIR}"
        \
74             --entry-
        point="${ENTRY_POINT}" \
75             --trigger-http \
76             --no-allow-unauthenticated
        \
77             --
        timeout="${TIMEOUT_SECONDS}" \
78             --memory="${MEMORY}" \
79             "${SA_ARGS[@]}" \
80             --set-env-
        vars="PROJECT_ID=${PROJECT_ID},GCS_BUCKET=${BUCKET_NAME},STRUCTURED_PREFIX=${STRUCTURED_PREFIX}"
81
82         - name: Grant invoker to deployer
        & runtime SAs
83         shell: bash
84         run: |
85             set -euo pipefail
86             gcloud functions add-invoker-
        policy-binding "${FUNCTION_NAME}" \
87                 --gen2 --region "${REGION}"
        \
88                 --
        member="serviceAccount:${DEPLOYER_SA}"
89         if [[ -n "${RUNTIME_SA:-}"
        ]]; then
90             gcloud functions add-
        invoker-policy-binding
        "${FUNCTION_NAME}" \
91                 --gen2 --region
        "${REGION}" \
92                 --
        member="serviceAccount:${RUNTIME_SA}"
93         fi
94
95         - name: Get Function URL
96         id: cfurl
97         shell: bash
98         run: |

```

```

67         fi
68
69         gcloud functions deploy
        "${FUNCTION_NAME}" \
70             --gen2 \
71             --region="${REGION}" \
72             --runtime="${RUNTIME}" \
73             --source="${FUNCTION_DIR}"
        \
74             --entry-
        point="${ENTRY_POINT}" \
75             --trigger-http \
76             --no-allow-unauthenticated
        \
77             --
        timeout="${TIMEOUT_SECONDS}" \
78             --memory="${MEMORY}" \
79             "${SA_ARGS[@]}" \
80             --set-env-
        vars="PROJECT_ID=${PROJECT_ID},GCS_BUCKET=${BUCKET_NAME},STRUCTURED_PREFIX=${STRUCTURED_PREFIX}"
81
82         - name: Grant invoker to deployer
        & runtime SAs
83         shell: bash
84         run: |
85             set -euo pipefail
86             gcloud functions add-invoker-
        policy-binding "${FUNCTION_NAME}" \
87                 --gen2 --region "${REGION}"
        \
88                 --
        member="serviceAccount:${DEPLOYER_SA}"
89         if [[ -n "${RUNTIME_SA:-}"
        ]]; then
90             gcloud functions add-
        invoker-policy-binding
        "${FUNCTION_NAME}" \
91                 --gen2 --region
        "${REGION}" \
92                 --
        member="serviceAccount:${RUNTIME_SA}"
93         fi
94
95         - name: Get Function URL
96         id: cfurl
97         shell: bash
98         run: |

```

```
99      set -euo pipefail
100      URL=$(gcloud functions
describe "${FUNCTION_NAME}" --gen2 --
region "${REGION}" --
format='value(serviceConfig.uri)')
101      echo "url=${URL}" >>
"$GITHUB_OUTPUT"
102      echo "Function URL: ${URL}"
103
104      - name: Ensure Scheduler API
enabled
105      shell: bash
106      run: |
107          set -euo pipefail
108          gcloud services list --
enabled --
filter="cloudscheduler.googleapis.com"
--format="value(config.name)" | grep -q
cloudscheduler.googleapis.com \
109          || gcloud services enable
cloudscheduler.googleapis.com
110
111      - name: Bootstrap IAM for
Scheduler OIDC (runtime SA)
112      shell: bash
113      run: |
114          set -euo pipefail
115          if [[ -z "${RUNTIME_SA:-}"
]]]; then
116              echo "::error::RUNTIME_SA
is not set. Add repo variable
RUNTIME_SA."
117          exit 1
118      fi
119
120      PROJECT_NUMBER="$(gcloud
projects describe "${PROJECT_ID}" --
format='value(projectNumber)')"
121
122      SCHED_AGENT="service-${PROJECT_NUMBER}@
gcp-sa-
cloudscheduler.iam.gserviceaccount.com"
122      echo "Scheduler agent:
${SCHED_AGENT}"
123
124      # 1) Scheduler may mint OIDC
tokens as the runtime SA
125      if ! gcloud iam service-
accounts add-iam-policy-binding
```

```
99      set -euo pipefail
100      URL=$(gcloud functions
describe "${FUNCTION_NAME}" --gen2 --
region "${REGION}" --
format='value(serviceConfig.uri)')
101      echo "url=${URL}" >>
"$GITHUB_OUTPUT"
102      echo "Function URL: ${URL}"
103
104      - name: Ensure Scheduler API
enabled
105      shell: bash
106      run: |
107          set -euo pipefail
108          gcloud services list --
enabled --
filter="cloudscheduler.googleapis.com"
--format="value(config.name)" | grep -q
cloudscheduler.googleapis.com \
109          || gcloud services enable
cloudscheduler.googleapis.com
110
111      - name: Bootstrap IAM for
Scheduler OIDC (runtime SA)
112      shell: bash
113      run: |
114          set -euo pipefail
115          if [[ -z "${RUNTIME_SA:-}"
]]]; then
116              echo "::error::RUNTIME_SA
is not set. Add repo variable
RUNTIME_SA."
117          exit 1
118      fi
119
120      PROJECT_NUMBER="$(gcloud
projects describe "${PROJECT_ID}" --
format='value(projectNumber)')"
121
122      SCHED_AGENT="service-${PROJECT_NUMBER}@
gcp-sa-
cloudscheduler.iam.gserviceaccount.com"
122      echo "Scheduler agent:
${SCHED_AGENT}"
123
124      # 1) Scheduler may mint OIDC
tokens as the runtime SA
125      if ! gcloud iam service-
accounts add-iam-policy-binding
```

```
"${RUNTIME_SA}" \
126      --
      member="serviceAccount:${SCHED_AGENT}"
      \
127      --
      role="roles/iam.serviceAccountTokenCrea
tor"; then
128      echo "::error::Permission
denied adding tokenCreator to
${RUNTIME_SA}. Run (once as project
owner):"
129      echo "gcloud iam service-
accounts add-iam-policy-binding
\"${RUNTIME_SA}\" --
member=\"serviceAccount:${SCHED_AGENT}\"
" --
      role=\"roles/iam.serviceAccountTokenCrea
tor\"""
130      exit 1
131    fi
132
133    # 2) Deployer may 'actAs' the
runtime SA to create/update the job
134    if ! gcloud iam service-
accounts add-iam-policy-binding
"${RUNTIME_SA}" \
135      --
      member="serviceAccount:${DEPLOYER_SA}"
      \
136      --
      role="roles/iam.serviceAccountUser";
then
137      echo "::error::Permission
denied adding ServiceAccountUser for
${DEPLOYER_SA} on ${RUNTIME_SA}. Run:"
138      echo "gcloud iam service-
accounts add-iam-policy-binding
\"${RUNTIME_SA}\" --
member=\"serviceAccount:${DEPLOYER_SA}\"
" --
      role=\"roles/iam.serviceAccountUser\"""
139      exit 1
140    fi
141
142    - name: Create/Update Cloud
Scheduler job (:15 ET, OIDC)
143      shell: bash
144      run: |
145        set -euo pipefail
```

```
"${RUNTIME_SA}" \
126      --
      member="serviceAccount:${SCHED_AGENT}"
      \
127      --
      role="roles/iam.serviceAccountTokenCrea
tor"; then
128      echo "::error::Permission
denied adding tokenCreator to
${RUNTIME_SA}. Run (once as project
owner):"
129      echo "gcloud iam service-
accounts add-iam-policy-binding
\"${RUNTIME_SA}\" --
member=\"serviceAccount:${SCHED_AGENT}\"
" --
      role=\"roles/iam.serviceAccountTokenCrea
tor\"""
130      exit 1
131    fi
132
133    # 2) Deployer may 'actAs' the
runtime SA to create/update the job
134    if ! gcloud iam service-
accounts add-iam-policy-binding
"${RUNTIME_SA}" \
135      --
      member="serviceAccount:${DEPLOYER_SA}"
      \
136      --
      role="roles/iam.serviceAccountUser";
then
137      echo "::error::Permission
denied adding ServiceAccountUser for
${DEPLOYER_SA} on ${RUNTIME_SA}. Run:"
138      echo "gcloud iam service-
accounts add-iam-policy-binding
\"${RUNTIME_SA}\" --
member=\"serviceAccount:${DEPLOYER_SA}\"
" --
      role=\"roles/iam.serviceAccountUser\"""
139      exit 1
140    fi
141
142    - name: Create/Update Cloud
Scheduler job (:15 ET, OIDC)
143      shell: bash
144      run: |
145        set -euo pipefail
```

```
146     JOB_NAME="${FUNCTION_NAME}-
hourly"
147     URL="${{
steps.cfurl.outputs.url }}"
148     [[ -z "${URL}" ]] && { echo
"Function URL empty"; exit 1; }
149
150     if gcloud scheduler jobs
describe "$JOB_NAME" --
location="${REGION}" >/dev/null 2>&1;
then
151         gcloud scheduler jobs
update http "$JOB_NAME" \
152             --location="${REGION}" \
153             --schedule="${CRON_EXPR}"
\
154             --time-
zone="America/New_York" \
155             --uri="${URL}" \
156             --http-method=POST \
157             --message-body='${{
env.SCHEDULE_BODY }}' \
158             --attempt-
deadline="${TIMEOUT_SECONDS}s" \
159             --oidc-service-account-
email="${RUNTIME_SA}" \
160             --oidc-token-
audience="${URL}"
161     else
162         gcloud scheduler jobs
create http "$JOB_NAME" \
163             --location="${REGION}" \
164             --schedule="${CRON_EXPR}"
\
165             --time-
zone="America/New_York" \
166             --uri="${URL}" \
167             --http-method=POST \
168             --message-body='${{
env.SCHEDULE_BODY }}' \
169             --attempt-
deadline="${TIMEOUT_SECONDS}s" \
170             --oidc-service-account-
email="${RUNTIME_SA}" \
171             --oidc-token-
audience="${URL}"
172     fi
173
```

```
146     JOB_NAME="${FUNCTION_NAME}-
hourly"
147     URL="${{
steps.cfurl.outputs.url }}"
148     [[ -z "${URL}" ]] && { echo
"Function URL empty"; exit 1; }
149
150     if gcloud scheduler jobs
describe "$JOB_NAME" --
location="${REGION}" >/dev/null 2>&1;
then
151         gcloud scheduler jobs
update http "$JOB_NAME" \
152             --location="${REGION}" \
153             --schedule="${CRON_EXPR}"
\
154             --time-
zone="America/New_York" \
155             --uri="${URL}" \
156             --http-method=POST \
157             --message-body='${{
env.SCHEDULE_BODY }}' \
158             --attempt-
deadline="${TIMEOUT_SECONDS}s" \
159             --oidc-service-account-
email="${RUNTIME_SA}" \
160             --oidc-token-
audience="${URL}"
161     else
162         gcloud scheduler jobs
create http "$JOB_NAME" \
163             --location="${REGION}" \
164             --schedule="${CRON_EXPR}"
\
165             --time-
zone="America/New_York" \
166             --uri="${URL}" \
167             --http-method=POST \
168             --message-body='${{
env.SCHEDULE_BODY }}' \
169             --attempt-
deadline="${TIMEOUT_SECONDS}s" \
170             --oidc-service-account-
email="${RUNTIME_SA}" \
171             --oidc-token-
audience="${URL}"
172     fi
173
```

```
174      # Mint an ID token via the Auth
      action (no TokenCreator needed)
175      - name: Mint ID token for smoke
176        id: auth-smoke
177        uses: google-github-
      actions/auth@v2
178        with:
179          workload_identity_provider:
            {{{ env.WORKLOAD_IDENTITY_PROVIDER }}}
180          service_account: {{{
env.DEPLOYER_SA }}}
181          token_format: "id_token"
182          id_token_audience: {{{
steps.cfurl.outputs.url }}}
183          id_token_include_email: true
184
185      - name: Smoke invoke
      (authenticated with ID token)
186        shell: bash
187        run: |
188          set -euo pipefail
189          URL="{{{
steps.cfurl.outputs.url }}"
190          TOKEN="{{{ steps.auth-
smoke.outputs.id_token }}"
191          echo "POST $URL"
192          curl -i -sS -X POST "$URL" \
193            -H "Authorization: Bearer
            ${TOKEN}" \
194            -H "Content-Type:
application/json" \
195            -d '{{{ env.SCHEDULE_BODY
            }}}' || true
```

```
174      # Mint an ID token via the Auth
      action (no TokenCreator needed)
175      - name: Mint ID token for smoke
176        id: auth-smoke
177        uses: google-github-
      actions/auth@v2
178        with:
179          workload_identity_provider:
            {{{ env.WORKLOAD_IDENTITY_PROVIDER }}}
180          service_account: {{{
env.DEPLOYER_SA }}}
181          token_format: "id_token"
182          id_token_audience: {{{
steps.cfurl.outputs.url }}}
183          id_token_include_email: true
184
185      - name: Smoke invoke
      (authenticated with ID token)
186        shell: bash
187        run: |
188          set -euo pipefail
189          URL="{{{
steps.cfurl.outputs.url }}"
190          TOKEN="{{{ steps.auth-
smoke.outputs.id_token }}"
191          echo "POST $URL"
192          curl -i -sS -X POST "$URL" \
193            -H "Authorization: Bearer
            ${TOKEN}" \
194            -H "Content-Type:
application/json" \
195            -d '{{{ env.SCHEDULE_BODY
            }}}' || true
```