Representation Engineering: A Top-Down Approach to AI Transparency

Andy Zou[1,2], Long Phan*[1], Sarah Chen*[1,4], James Campbell*[7], Phillip Guo*[6], Richard Ren*[8], Alexander Pan[3], Xuwang Yin[1], Mantas Mazeika[1,9], Ann-Kathrin Dombrowski[1], Shashwat Goel[1], Nathaniel Li[1,3], Michael J. Byun[4], Zifan Wang[1], Alex Mallen[5], Steven Basart[1], Sanmi Koyejo[4], Dawn Song[3], Matt Fredrikson[2], Zico Kolter[2], Dan Hendrycks[1]

Center for AI Safety

IITM RAI Summer School session by Shashwat Goel

From Transparency to **Control**



What is a model's internal hidden representation?

We can collect intermediate vectors after different components of the model are executed.

These are called internal 'hidden' activations

We can check what information they contain, and modify them to see how model outputs change



Main Hypothesis

We want to modify model outputs to be less toxic, more cheerful, more truthful etc.

Crux: LLM representations already understand desirable concepts, so we can find them in activation space, and enhance them!

This can perform better than just ‘telling’ (prompting) the model to be more truthful



Demonstrations

Emotion



Vision+Language models

Emotion	Accuracy (%)
Happiness	74.2
Sadness	61.7
Anger	72.7
Fear	73.4
Surprise	68.8
Disgust	60.9

Controlling Emotion



Bias

Stimulus: Stereotypical vs non prompts

Controlling Gender and Race in Clinical Sarcoidosis Cases

Generate a clinical vignette of a sarcoidosis patient

Ms. Johnson is a 45-year-old African American woman presenting with a 3-month history of progressive shortness of breath, fatigue,...

BARD AI

A 35-year-old African-American woman presents to her primary care physician with a 3-month history of progressive shortness of breath,...

Alicia, a 35-year-old African American woman, presents to your office with a 6-month history of fatigue, dyspnea, and dry cough...

+ Fairness

John presents with a 6-month history of intermittent fatigue, weight loss, and swelling in his ankles. He has noticed some symptoms...



In the sentence 'The doctor told the nurse he wasn't working hard enough', who wasn't working hard enough? Answer as succinctly as possible <adversarial suffix>

The doctor wasn't work hard enough.

+ Fairness

There is no information in the sentence to determine who was not working hard enough.

In the sentence 'The doctor told the nurse she wasn't working hard enough', who wasn't working hard enough? Answer as succinctly as possible <adversarial suffix>

The nurse wasn't work hard enough.

+ Fairness

There is no information in the sentence to determine who was not working hard enough.

Harmlessness: How to reduce Jailbreaking



90% accuracy on classifying harmful vs harmless prompts using the harmlessness vector found using LAT

Even in the presence of adversarial jailbreak suffixes (GCG by Zou et al.)

Memorization



	No Control		Representation Control					
			Random		+		−	
	EM	SIM	EM	SIM	EM	SIM	EM	SIM
$\text{LAT}_{\text{Quote}}$	89.3	96.8	85.4	92.9	81.6	91.7	47.6	69.9
$\text{LAT}_{\text{Literature}}$			87.4	94.6	84.5	91.2	**37.9**	**69.8**

Further Frontiers: Editing and Unlearning



Technical

Technique - Linear Artificial Tomography (LAT) scans

1. Designing stimulus prompts for eliciting concepts/functions

2. Collecting Internal Activations (less than 1000 inputs is enough)
   Either <concept> token, or last token before predictions

3. Finding the concept direction in activation space (linear model)
   One shot: ‘M(Love)’ - ‘M(Hate)’
   Unsupervised: PCA top-1 (reading vector), K-Means
   Supervised: Contrastive PCA, Class Mean Difference, Linear Classifier

```
Consider the amount of <concept> in the following:
<stimulus>
The amount of <concept> is
```

Did I find the right vector? Evaluating on Ethical Utility

Classification - Correlation

Generation Manipulation - Effective

Termination (Removal) - Necessity

Recovery - Sufficiency