

Ultra Light Stabilized Gimbal Camera


SR-Z50

■ Main Feature

- Ultra Light for UAV Application
- Full HD / HD Color Camera
- Thermal Imaging Camera
- Laser Range Finder
- MEMS Gyro Stabilization
- Image Stabilization Software
- Auto Tracker (Option)

- Gyro Motion Stabilization
- BIT (Built In Test)
- GPS & Digital Compass

- Thermal Camera
 - 1280x720 Super Resolution
 - 4x D Zoom



- HD Color Camera
 - 1280x720 HD Color Camera
 - 1920x1080 (Optional)
 - 20x Zoom, 2x D-Zoom




- Laser Range Finder
 - Detection Range 3.4km
 - 1.7km for Nato Target
 - Eye-safe



Auto Tracking (Option)

Auto video Tracking



Geo Lock Feature



■ Application



Drone



UAV



Ground Robot

Ultra Light Stabilized Gimbal Camera

SR-Z50

ITEM		SR-Z50 EO/IR/LRF	SR-Z50 EO/IR
			
Thermal Camera*	Spectral Range:	Uncooled, 8 to 14 μ m	Uncooled, 8 to 14 μ m
	Output Resolution	1280x720 (Super Resolution)	1280x720 (Super Resolution)
	Focal Length:	25mm	25mm
	F Number:	f/1.2	f/1.2
	Horizontal Field of View:	18°	18°
	Digital Zoom:	1x to 4x Digital Zoom	1x to 4x Digital Zoom
	Pixel Pitch:	12 μ m	12 μ m
	NETD:	$\leq$ 50 mK	$\leq$ 50 mK
	Video Format:	NTSC/PAL	NTSC/PAL
	Frame Rate:	60 Hz (30 fps)	60 Hz (30 fps)
	Focus System:	Fixed Focus	Fixed Focus
Color Camera	Sensor Type	1/3.2 inch CMOS	1/3.2 inch CMOS
	Image Resolution	1280 x 720 (1920x1080 Optional)	1280 x 720 (1920x1080 Optional)
	Zoom	20x Zoom, 2x D-Zoom	20x Zoom, 2x D-Zoom
	HFOV	H 60°(Wide) ~ 3°(Tele), 1.5°(D Zoom)	H 60°(Wide) ~ 3°(Tele), 1.5°(D Zoom)
LRF	Detection Range	3.4km Max (1.7km Nato Target)	N/A
	Accuracy	1 ~ 1.5m	N/A
Gimbal	Diameter	72 mm	70 mm
	Height (B/Deck)	105 mm	90 mm
	Weight:	< 400g	< 300g
	Pan Range : Tilt Range :	+180° ~ -180° -45° ~ +90°	+180° ~ -180° -45° ~ +90°
	Max Speed:	Pan : 60°/s, Tilt : 30°/s	Pan : 60°/s, Tilt : 30°/s
	Power	12-34 VDC, 10 W or less	12-34 VDC, 10 W or less
	Operating Temp:	-30°C to +43°C	-30°C to +43°C
	Gyro:	2 Axis Gyro Stabilization	2 Axis Gyro Stabilization