Layered Architecture

Data Network

2026-04-14

Table of contents

1 ? 2
- 1.1 Nuts & Bolts . . . 2
- 1.2 Service . . . 2
- 1.3 Protocol . . . 2

2 Network Edge & Access Networks 2
- 2.1 3 . . . 2
- 2.2 Host . . . 3
- 2.3 . . . 3
- 2.4 (Physical Media) . . . 3

3 Network Core 3
- 3.1 Packet Switching . . . 3
  - 3.1.1 Store-and-Forward . . . 4
  - 3.1.2 Queueing Delay & Loss . . . 4
  - 3.1.3 Two Key Functions . . . 4
- 3.2 Circuit Switching . . . 4
  - 3.2.1 FDM vs TDM . . . 4
- 3.3 Packet vs Circuit Switching . . . 4
  - 3.3.1 — . . . 5
- 3.4 Internet Structure: Network of Networks . . . 5

4 Delay, Loss, Throughput 5
- 4.1 4 . . . 5
- 4.2 Traffic Intensity . . . 6
- 4.3 Throughput ( ) . . . 6

5 Protocol Layers & Service Models 7
- 5.1 . . . 7
- 5.2 Internet 5-Layer Stack . . . 7
- 5.3 OSI 7 . . . 7
- 5.4 Encapsulation ( ) . . . 8
- 5.5 Hop-by-Hop . . . 8

6 Network Security **9**
6.1 9
6.2 9
6.2.1 Malware 9
6.2.2 DoS / DDoS 9
6.2.3 Packet Sniffing 9
6.2.4 IP Spoofing 9

7 **10**

1 ?

1.1 Nuts & Bolts

host(end system) communication link packet switch .

- **Host**: PC, ,
- **Communication link**: fiber, copper, radio, satellite — **bandwidth(, bps)**
- **Packet switch**: — **router**(network core), **switch**(link layer)

"network of networks" , ISP(Internet Service Provider) .

1.2 Service

(API) .
Web, VoIP, email, , e-commerce .

1.3 Protocol

Protocol: , ,

- : TCP, IP, HTTP, 802.11 (WiFi)
- **RFC(Request for Comments)** **IETF(Internet Engineering Task Force)**

---

2 Network Edge & Access Networks

2.1 3

Network edge	hosts(clients & servers),
Access network	end system edge router

Network core	mesh

2.2 Host

Host **L bits** .

$$d_{trans} = \frac{L \text{ (bits)}}{R \text{ (bits/sec)}}$$

R link transmission rate(= link capacity = link bandwidth) .

2.3

- *DSL/* : , HFC(Hybrid Fiber Coax)
- *Ethernet*: / , 10 Mbps ~ 10 Gbps

- *Wireless LAN (802.11 WiFi)*: ~100 ft, 11/54/450 Mbps
- *Wide-area wireless*: tens of km, 1~10 Mbps (3G, 4G LTE)

2.4 (Physical Media)

Twisted pair (TP)	Cat5: 100 Mbps/1 Gbps, Cat6: 10 Gbps
Coaxial cable	, (broadband), HFC
Fiber optic	, 10s~100s Gbps,
Radio	, / /

3 Network Core

3.1 Packet Switching

store-and-forward .

3.1.1 Store-and-Forward

.

$$d_{end\text{-}end} = N \cdot \frac{L}{R} \quad \text{(N hop, propagation)}$$

3.1.2 Queueing Delay & Loss

- > →
- **drop( )**

3.1.3 Two Key Functions

Forwarding	→	(local)
Routing	-	(, global)

3.2 Circuit Switching

/ end-to-end **(dedicated)** .

3.2.1 FDM vs TDM

FDM (Frequency Division Multiplexing)
TDM (Time Division Multiplexing)

3.3 Packet vs Circuit Switching

	Packet Switching	Circuit Switching
	(on-demand)	(dedicated) (: 10 /1 Mbps)
QoS		
	Bursty data	/

3.3.1 —

1 Mb/s , 1 100 kb/s, 10%

- Circuit switching: **10**
- Packet switching: **35** , P(10) < 0.0004

$$P(X > 10) = \sum_{k=11}^{35} \binom{35}{k} (0.1)^k (0.9)^{35-k} \approx 0.0004$$

$X \sim \text{Binomial}(35,\ 0.1)$, $E[X] = 3.5$

3.4 Internet Structure: Network of Networks

ISP $O(N^2)$.

$$\binom{N}{2} = \frac{N(N-1)}{2} \approx \frac{(10^6)^2}{2} = 5 \times 10^{11}$$

:

```
Tier-1 ISP   IXP   Tier-1 ISP
     |                  |
Regional ISP          Regional ISP
     |                  |
Access ISP            Access ISP
```

- **IXP (Internet Exchange Point)**: ISP peering
- **Content provider network** (Google, Akamai): Tier-1

---

4 Delay, Loss, Throughput

4.1 4

$$d_{nodal} = d_{proc} + d_{queue} + d_{trans} + d_{prop}$$

d_{proc}	—	+	$<$ msec
d_{queue}	$\propto \frac{\rho}{1-\rho}$		,
d_{trans}	L/R		.
d_{prop}	d/s		($s \approx 2 \times 10^8$ m/s)

! d_{trans} vs d_{prop}

- d_{trans}: — 10 Gbps
- d_{prop}: — →

4.2 Traffic Intensity

$$\rho = \frac{La}{R}$$

- L: (bits)
- a: (packets/sec)
- R: (bits/sec)
- La:

ρ	
$\rho \approx 0$	, 0
$\rho \to 1$	, $\to \infty$
$\rho > 1$	$\to$ **packet drop**

M/M/1 :

$$E[W] = \frac{\rho}{\mu(1-\rho)}, \quad \mu = R/L$$

4.3 Throughput ( )

$$\text{throughput} = \min(R_c,\ R_s,\ R/N)$$

R_c	
R_s	
R/N N	R per-connection

(bottleneck link) .

5 Protocol Layers & Service Models

5.1

.

1. —
2. — (transparent)
3. : ,

5.2 Internet 5-Layer Stack

`Application`	`HTTP, FTP, SMTP, DNS`
`Transport`	`TCP, UDP`
`Network`	`IP,`
`Link`	`Ethernet, 802.11 (WiFi), PPP`
`Physical`	`bits "on the wire"`

5.3 OSI 7

Internet Stack	OSI	
Application	Application	
( )	Presentation	, ,
( )	Session	,
Transport	Transport	Process-to-Process
Network	Network	Host-to-Host
Link	Data Link	Hop-to-Hop
Physical	Physical	

Internet Session/Presentation

End-to-End Argument (Saltzer, Reed, Clark, 1984): , end system . Presentation (,) Session ( ) Application .

OSI	Internet
Presentation	TLS/SSL
Presentation	HTTP `Content-Encoding: gzip`

Session	HTTP Cookie, WebSocket

5.4 Encapsulation ( )

, .

$$M \xrightarrow{\text{Transport}} H_t|M \xrightarrow{\text{Network}} H_n|H_t|M \xrightarrow{\text{Link}} H_l|H_n|H_t|M|\text{FCS}$$

PDU		
Message	Application	—
Segment (TCP) / Datagram (UDP)	Transport	src/dst port, seq#, checksum
Datagram (IP Packet)	Network	src/dst IP, TTL, protocol
Frame	Link	src/dst MAC, type, FCS
Bit	Physical	—

5.5 Hop-by-Hop

L1~L3 , L1~L2 .

```
[ ]
  Physical: bits → Frame
  Link:     FCS   → H_l   (decapsulation)

[ ]
  Network:  H_n  dst IP → Forwarding Table
            TTL   (0   )

[ ]
  Link:       H_l'   (  hop  MAC  )
  Physical: bits
```

!

- H_l: hop (MAC)
- H_n: TTL , src/dst IP end-to-end (NAT)
- H_t, M**: — end-to-end

6 Network Security

6.1

“ ” . , .

6.2

6.2.1 Malware

Virus	,
Worm	( ) ,

botnet spam , DDoS .

6.2.2 DoS / DDoS

· bogus .

→ `botnet` →

6.2.3 Packet Sniffing

NIC **promiscuous mode** .

- —
- Broadcast medium **WiFi** ( )
- : (TLS, WPA3)

6.2.4 IP Spoofing

src IP . .

- DDoS
- : Ingress filtering (RFC 2827)

Sniffing	( ) (,)
Spoofing	( ) ,

7

$$d_{nodal} = d_{proc} + d_{queue} + d_{trans} + d_{prop}$$

$$d_{trans} = \frac{L}{R}, \quad d_{prop} = \frac{d}{s}$$

$$\rho = \frac{La}{R} \quad \Rightarrow \quad E[W]_{M/M/1} = \frac{\rho}{\mu(1-\rho)}$$

$$\text{Throughput} = \min(R_c,\ R_s,\ R/N)$$

$$P(\text{packet switching} \quad) = \sum_{k=k_0}^{N} \binom{N}{k} p^k (1-p)^{N-k}$$

$$(\text{full mesh}) = \binom{N}{2} = \frac{N(N-1)}{2} = O(N^2)$$