

AGGREGATE	PARAMETERS	SWARAJ TARGET 630 4WD	SWARAJ TARGET 625 4WD	SWARAJ TARGET 625 2WD	
ENGINE	Make & Type	Yanmar/Liquid Cooled, Direct Injection	Yanmar / Liquid Cooled, Direct Injection		
	Engine Power (HP)	29 @2800 ERPM	25 @2400 ERPM		
	No of Cylinders	3	3		
	Total Displacement (cc)	1331	1331		
	Air Cleaner	Dry Type, Dual element	Dry Type, Dual element		
	Maximum torque (Nm)	87	83.1		
TRANSMISSION	Clutch	Main Transmission-Single Dry Clutch PTO - Independent Wet Clutch	Main Transmission-Single Dry Clutch PTO - Independent Wet Clutch (Optional)		
	No. of Speeds	9 Forward & 3 Reverse	9 Forward & 3 Reverse		
	Brakes	Oil Immersed Brakes	Oil Immersed Brakes		
	Final Reduction	Bull Gear Reduction	Bull Gear Reduction		
	Mechanical differential lock	Yes	Yes		
HYDRAULICS	Hydraulic Control System	Automatic Depth & Draft control	Automatic Depth & Draft control		
	Three Point hitch Category	Category 1	Category 1		
	Max Lift Capacities @hitch point	980 kgf	980 kgf		
	Transport lock	Yes	Yes		
PTO	PTO On-Off Control	Switch Operated	Manual Lever / Switch Operated (Optional)		
	PTO Speeds	540 & 540E /540 + R	540 & 540E		
	PTO Power (HP)	24	19		
Front Axle & Steering	Front Axle Type	4wd-Portal type	4wd-Portal type	2wd	
	4wd Engagement type	Mechanical with lever	Mechanical with lever	NA	
	Steering Type	Balanced Power Steering	Balanced Power Steering		
Dimensions	Wheelbase (mm)	1555	1555	1595	
	Front Track width (mm)	Standard - 840	Standard - 835	Standard - 840	
		Optional - 755 (Narrow rim)	Optional - 755 (Narrow rim)	Optional - 750	
	Rear Track width (mm)	Standard - 797	Standard - 797		
		Option 1 - 710	Option 1 - 710		
		Option 2 - 910	Option 2 - 910		
*Weight (kg)	910	910	870		
Tyres	Front Tyre	Standard - 180/85D12	Standard - 180/85D12	Standard - 5.25 x 14	
		Optional - 180/85D12 with Narrow rim	Optional - 180/85D12 with Narrow rim / 5 x 12 (Optional)		
	Rear Tyre	Standard - 8.30 x 20	8.30 x 20 / Optional - 8 x 18		
		Option 1 - 9.50 x 20			
		Option 2 - 9.50 x 20 High Lug			
Others	Fuel Tank Capacity (ltrs) Seat type	27	27		
		Sliding adjustable	Sliding adjustable		



Swaraj Division

Phase IV, Industrial Area, S.A.S Nagar (Mohali),
Punjab -160055

Phone: 0172 2271620-27 | 0172 2270820-23

Website: www.swarajtractors.com

Authorised Dealer

For improvement purposes, the details given above can be changed. The images used are only for representation purposes. The actual product might be different. The accessories and implements shown here may not be part of the standard product.



जोश का राज मेरा





POWER PARTNERING WITH TECHNOLOGY

AB HAR TARGET HAI MUMKIN

NOW AVAILABLE IN

 **TARGET 630 & 625** NEW

THE UNPARALLELED PARTNERSHIP OF POWER AND TECHNOLOGY

For decades, Swaraj has won the hearts of the farmers by giving them indomitable power to conquer the terrain across the nation.

Now, we leap into a future where power gets super-charged by the best-in-class technology.

This convergence will enable the new-age farmers to meet all their targets for farming and life.

Presenting Swaraj Target, the culmination of path-breaking power and technology that will revolutionise not just the compact lightweight tractor category in India but also the entire agricultural landscape.

Now, it is possible for the modern farmer to achieve every target of Spraying and Interculture.



POWER THAT MAKES EVERY TARGET POSSIBLE



Powerful 1331 cm³ (cc) engine
to ensure minimum RPM drop
even during heavy-duty work

*For TARGET 630 only.



**Highest PTO power in its class – 17.9 kW
(24 HP)** to ensure uniform mist-like spray
even with imported double-fan sprayers*



22 LPM hydraulic flow
for quicker lift/drop of the
implement*



Powerful DI Engine*

An engine with 87 Nm (Target 630) and 83.1 Nm (Target 625) torque to effortlessly pull trailed sprayers of up to 800 Ltr even in the muddiest terrain.



Maxlift

980 kgf Lift capacity makes it possible to lift even the heaviest of implements with ease*.



ADDC Hydraulics

Ensures uniform depth control in draft implements such as Duckfoot cultivator, MB plough, and others.



Narrowest FlexiTrack

Category's narrowest 3 feet overall width.
Option to adjust track width as 28, 32 or 36 basis the crop (values are in inch).

Spray Saver Switch*

Switch technology can save up to 10% of the expensive spray.



Wet IPTO Clutch*

Technology which enables continuous operation of PTO implements even when the main clutch is pressed.



Sync-Shift Transmission*

Get the comfort of car-type gear shifting.



MaxCool

A 20% larger radiator ensures non-stop tractor usage for hours.



*For TARGET 630 only.

TECHNOLOGY THAT MAKES EVERY TARGET POSSIBLE



Engine Key Stop to turn on/off the engine with a key.



Balanced Power Steering reduces fatigue during frequent turns in row crop fields.



Clear and powerful Headlamps give day-like brightness in dark.



Stylish Digital Cluster makes it easier to read information, even in low-light.



Fully Sealed 4wd Portal Axle gives better ground clearance as well as no mud entry in axle.



Dual PTO – 540 & 540 E
Economy PTO allows to save fuel while using lighter equipment like alternators and water pumps.