

SPECIFICATIONS

Model	742XT	
Engine	Rated Engine Speed	2000
	Displacement	3307
	Bore (mm)	110
	Stroke (mm)	116
	Service Interval (h)	400
Transmission	GB type	Sliding Mesh/PCM
	No. of Gears & Shift Pattern	8F + 2R Centre Shift 8F + 2R Side Shift
	Clutch Type	SC/DC/IPTO
	Front Axle Type	Adjustable/Fixed
	Front Axle Drive	2WD
	Steering	Power/Mechanical
PTO & Hydraulics	PTO	540 with 4 Multispeed forward and 1 Reverse speed
	Hydraulics (kg)	1700
Brakes	Type	Oil Immersed Brakes
Tyre Size	Front-2WD	152.40 mm x 406.40 mm (6.00 x 16)
	Rear-2WD	378.46 mm x 711.20 mm (14.9 x 28)
	Front-4WD	-
	Rear-4WD	-
		-
Electrical	Battery (Ah)	80
	Head Lamps Type	Glass
	Fender & Tail Lamps Type	Regular
	Total Length (mm)	3455
Dimensions & Capacities 2WD*	Total Width (mm)	1915
	Wheelbase (mm)	2085
	Fuel Tank capacity (L)	56

*Specifications are subject to change without notice for product improvement. The model shown here is for representational purpose only. The actual product may vary. Accessories and implements shown here may not be part of standard product.



SWARAJ DIVISION

Phase IV, Industrial Area, S.A.S Nagar (Mohali),
Punjab - 160055. Phone: 0172 2271620 to 27; 0172 2270820 to 23
Website: www.swarajtractors.com, Toll free number -1800 425 0735

Authorised Dealer:

