



# On the Capacity Region of Broadcast Packet Erasure Relay Networks with Feedback

Quan Geng  
Hieu T. Do  
Rui Wu  
Mindi Yuan  
Yun Li  
Wei Ding

Google Research, New York  
Ericsson Research, Stockholm  
University of Illinois, Urbana-Champaign  
University of Illinois, Urbana Champaign  
University of Illinois, Urbana Champaign  
Google Research, New York




IEEE International Conference on Communications  
20-24 May 2019 // Shanghai, China  
Empowering Intelligent Communications

# Outline

- **Background**
  - Broadcast Packet Erasure Channel (PEC)
  - **Multiple-Input** Broadcast Packet Erasure Channel
- **Model**
  - **Multiple-Input** Broadcast Packet Erasure Channel with **Feedback**
  - Broadcast Packet Erasure Relay Network *with Feedback*
- **Our Contributions**
  - New Outer-bounds on
    - Multiple Input Broadcast PEC with Feedback
    - Broadcast Packet Erasure Relay Networks with Feedback
  - Tightness of the outer bounds
    - Outer bounds achieved via network coding across sub-channels
    - Engineering implication: the network coding packets should be sent over correlated broadcast subchannels


# Background

- Broadcast Packet Erasure Channel
  - single transmitter/source
  - multiple receivers/destinations
  - the same packet is sent over the communication channels to destinations
- each receiver receives
  - either the entire packet
  - or no packet
- packet erasure events are independent over the time (memoryless)



# Background

- Broadcast Packet Erasure Channel
  - **Capacity region achieved by timesharing**




**Capacity Region**

$$\{(R_1, R_2) \mid \frac{R_1}{1 - \epsilon_1} + \frac{R_2}{1 - \epsilon_2} \leq 1\}$$


# Background

- Multiple-Input Broadcast Packet Erasure Channel
  - **one** transmitter
  - **n** receivers
  - **m** broadcast packet erasure sub-channels
  - no interference at each receiver



# Background

- Multiple-Input Broadcast Packet Erasure Channel




[Dana&Hassibi] Capacity region achieved by timesharing.

$$\mathcal{R}_T = \bigcup_{\underline{\alpha}} \{ (R_1, \dots, R_n) \mid 0 \leq R_j < \sum_{i=1}^m \alpha_{ij} (1 - \epsilon_{ij}) \},$$

- 1)  $\alpha_{ij} \geq 0$
- 2)  $\sum_{j=1}^n \alpha_{ij} = 1$  for all inputs  $1 \leq i \leq m$ .

# Background

- Broadcast Packet Erasure Channel with **Feedback**
  - [Georgiadis&Tassiulas] Feedback can improve the capacity region



## Capacity Region without Feedback


$$\{(R_1, R_2) \mid \frac{R_1}{1 - \epsilon_1} + \frac{R_2}{1 - \epsilon_2} \leq 1\}$$

## Capacity Region with Feedback

$$\{(R_1, R_2) \mid \frac{R_1}{1 - \epsilon_1 \epsilon_2} + \frac{R_2}{1 - \epsilon_2} \leq 1, \frac{R_1}{1 - \epsilon_1} + \frac{R_2}{1 - \epsilon_1 \epsilon_2} \leq 1\}$$

# Model

- Multiple-Input Broadcast Packet Erasure Channel with **Feedback**
  - **one** transmitter
  - **n** receivers
  - **m** broadcast packet erasure sub-channels
  - no interference at each receiver
  - channel output feedback at the transmitter





# Outer bound

- Multiple-Input Broadcast Packet Erasure Channel with **Feedback**

**Theorem 1.** *For any achievable rate tuple  $\mathbf{R} \triangleq (R_1, R_2, \dots, R_K)$ , it must hold that for any permutation function  $\pi : [K] \rightarrow [K]$ ,*

$$\mathbf{R} \in \mathbf{C}_\pi,$$

where

$$\mathbf{C}_\pi \triangleq \left\{ (R_1, R_2, \dots, R_K) \mid \sum_{j=1}^K \frac{R_{i\pi(j)}}{1 - \epsilon_{i\pi([j])}} \leq 1, \right.$$

$$\left. R_k = \sum_{m=1}^M R_{mk}, R_{i\pi(k)} \geq 0, \forall i \in [M], k \in [K]. \right\}$$

# Outer bound

- Multiple-Input Broadcast Packet Erasure Channel with **Feedback**

**Theorem 1.** For any achievable rate tuple  $\mathbf{R} \triangleq (R_1, R_2, \dots, R_K)$ , it must hold that for any permutation function  $\pi : [K] \rightarrow [K]$ ,

$$\mathbf{R} \in \mathbf{C}_\pi,$$

where


$$\mathbf{C}_\pi \triangleq \left\{ (R_1, R_2, \dots, R_K) \mid \sum_{j=1}^K \frac{R_{i\pi(j)}}{1 - \epsilon_{i\pi(j)}} \leq 1, \right.$$

$$\left. R_k = \sum_{m=1}^M R_{mk}, R_{i\pi(k)} \geq 0, \forall i \in [M], k \in [K]. \right\}$$

**Proof:** For any permutation function  $\pi$ , we construct new multiple input broadcast erasure channels with feedback by creating information pipes connecting node  $t_{\pi(j)}$  to node  $t_{\pi(j+1)}$ , so that  $t_{\pi(j+1)}$  will get all packets node  $t_{\pi(j)}$  receives, for all  $j \in [K - 1]$ .

This creates a physically degraded channel, for which feedback does not improve the capacity. Then apply the result in [Dana&Hassibi].

# Tightness of the Outer bound




Erasure events on the first sub-channel is **independent**

Erasure events on the second sub-channel is **the same**.

**Theorem 3.** *If  $\epsilon_2 \geq 1 - \frac{(1-\epsilon_1)\epsilon_1}{2}$  and  $0 < \epsilon_1, \epsilon_2 < 1$ , then the maximum sum rate of the outer bound in Theorem 1 is tight and can be achieved by coding across subchannels, which thus characterizes the sum capacity of this channel. In addition, the inner bound without coding across subchannels is strictly sub-optimal.*

# Inner bound without coding across sub-channels



$$\{(R_{11}, R_{12}) \mid \frac{R_{11}}{1 - \epsilon_1} + \frac{R_{12}}{1 - \epsilon_1^2} \leq 1, R_{11}, R_{12} \geq 0\}$$


and

$$\{(R_{11}, R_{12}) \mid \frac{R_{11}}{1 - \epsilon_1^2} + \frac{R_{12}}{1 - \epsilon_1} \leq 1, R_{11}, R_{12} \geq 0\}$$



$$R_{sum}^{inner} = \frac{2(1 - \epsilon_1^2)}{2 + \epsilon_1} + 1 - \epsilon_2$$

# Outer bound on Sum Capacity



$$\max_{(R_1, R_2) \in \mathcal{V}} R_1 + R_2.$$

$$\mathcal{V} \triangleq \mathcal{V}_1 \cap \mathcal{V}_2.$$

$$\mathcal{V}_1 \triangleq \{(R_1, R_2) \mid \frac{R_{11}}{1 - \epsilon_1^2} + \frac{R_{12}}{1 - \epsilon_1} \leq 1, \\ R_{21} + R_{22} \leq 1 - \epsilon_2, \\ R_1 = R_{11} + R_{21}, \\ R_2 = R_{12} + R_{22}, \\ R_{ij} \geq 0, \forall i, j \in [2]\},$$


and

$$\mathcal{V}_2 \triangleq \{(R_1, R_2) \mid \frac{R_{11}}{1 - \epsilon_1} + \frac{R_{12}}{1 - \epsilon_1^2} \leq 1, \\ R_{21} + R_{22} \leq 1 - \epsilon_2, \\ R_1 = R_{11} + R_{21}, \\ R_2 = R_{12} + R_{22}, \\ R_{ij} \geq 0, \forall i, j \in [2]\}.$$




$$R_{sum}^{outer} = \frac{2(2 - \epsilon_1 - \epsilon_2)(1 + \epsilon_1)}{2 + \epsilon_1}.$$

# Inner bound < Outer bound




$$R_{sum}^{inner} = \frac{2(1 - \epsilon_1^2)}{2 + \epsilon_1} + 1 - \epsilon_2$$

$$R_{sum}^{outer} = \frac{2(2 - \epsilon_1 - \epsilon_2)(1 + \epsilon_1)}{2 + \epsilon_1}.$$



$$\begin{aligned} R_{sum}^{outer} - R_{sum}^{inner} &= \frac{2(2 - \epsilon_1 - \epsilon_2)(1 + \epsilon_1)}{2 + \epsilon_1} - \left( \frac{2(1 - \epsilon_1^2)}{2 + \epsilon_1} + 1 - \epsilon_2 \right) \\ &= \frac{\epsilon_1(1 - \epsilon_2)}{2 + \epsilon_1} > 0, \end{aligned}$$

# Outer bound achievable by network coding




$$N^* = \frac{(1 - \epsilon_1)\epsilon_1 - 2(1 - \epsilon_2)}{2 - \epsilon_1 - \epsilon_2} N$$

which is positive when  $\epsilon_2 \geq 1 - \frac{(1-\epsilon_1)\epsilon_1}{2}$ .

# Broadcast Packet Erasure Relay Networks with Feedback

- one source
- multiple destinations
- broadcast erasure channels connecting nodes
- channel output feedback at each transmitter



A three-layer 1 to K broadcast erasure relay networks with feedback.



# Broadcast Packet Erasure Relay Networks with Feedback

- New outer bound based on multiple-input broadcast packet erasure channels with feedback
- Convert the network to multiple-input broadcast PEC with feedback






Fig. 3. A 1-to-2 broadcast packet erasure relay network.

# Broadcast Packet Erasure Relay Networks with Feedback

- Convert the network to multiple-input broadcast PEC with feedback




- Merge  $s, r_a, r_b, r_c$  into a super node  $s$
- remove  $r_d$ , and connect with  $s$  to  $t_1, t_2$  directly with the correlated broadcast erasure channel with erasure probability  $\epsilon_2$




# Broadcast Packet Erasure Relay Networks with Feedback

- Convert the network to multiple-input broadcast PEC with feedback



$$R_{sum}^{router} = \frac{2(2 - \epsilon_1 - \epsilon_2)(1 + \epsilon_1)}{2 + \epsilon_1}.$$

- Merge  $s, r_a, r_b, r_c$  into a super node  $s$
- remove  $r_d$ , and connect with  $s$  to  $t_1, t_2$  directly with the correlated broadcast erasure channel with erasure probability  $\epsilon_2$



# Summary

- **Background**

- Broadcast Packet Erasure Channel (PEC)
- Multiple-Input Broadcast Packet Erasure Channel

- **Model**

- Multiple-Input Broadcast Packet Erasure Channel with Feedback
- Broadcast Packet Erasure Relay Network *with Feedback*

- **Our Contributions**

- New Outer-bounds on
  - Multiple Input Broadcast PEC with Feedback
  - Broadcast Packet Erasure Relay Networks with Feedback
- Tightness of the outer bounds
  - Outer bounds achieved via network coding across sub-channels
  - Engineering implication: the network coding packets should be sent over correlated broadcast subchannels

Thank you!