EMC TEST REPORT

Applicant	KAISSEN TECHNOLOGY LLC
FCC ID	SIT-KT570
Product	MOBILE POS DEVICE
Model	KT570
Report No.	R1912A0735-E1V3
Issue Date	July 3, 2020

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2018)/ ANSI C63.4 (2014)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Wei Liu

Performed by: Wei Liu/ Manager

Guangchang Fan

Approved by: Guangchang Fan/ Director

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Test Date: December 16, 2019 ~ December 30, 2019			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

Note: This revised report (Report No.: R1912A0735-E1V3) supersedes and replaces the previously issued report (Report No.: R1912A0735-E1V2). Please discard or destroy the previously issued report and dispose of it accordingly.

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Testing Location

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Fan Guangchang
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	fanguangchang@ta-shanghai.com

2 General Description of Equipment under Test

2.1 Applicant and Manufacturer Information

Applicant	KAISSEN TECHNOLOGY LLC
Applicant address	7412 sw 48 st suite b MIAMI 33155, USA
Manufacturer	Asiatelco Technologies Co.
Manufacturer address	No. 68 Huatuo Road, Building-8, Zhangjiang Hi-Tech Park, Pudong, Shanghai 201203, China

2.2 General information

EUT Description			
Device Type:	Mobile Device		
Model:	KT570		
IMEI:	1#		
HW Version:	725-0741-001-2		
SW Version:	8.1.0		
Antenna Type:	Internal Antenna		
Frequency:	Band	Tx (MHz)	Rx (MHz)
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 12	699 ~ 716	729 ~ 746
	Bluetooth:	2402 ~ 2480	2402 ~ 2480
	WIFI 2.4G:	2412 ~ 2462	2412 ~ 2462
	WIFI 5G(U-NII-1):	5150 ~ 5250	5150 ~ 5250
	WIFI 5G(U-NII-3):	5725 ~ 5850	5725 ~ 5850
EUT Accessory			
Adapter	Manufacturer: Aquilstar Precision Industry (Shenzhen) Co., Ltd. Model: ASSA55a-050200		
USB Cable	Model: WT10200663 800mm±30 Cable, Shielded		
Auxiliary test equipment			

PC	PC Manufacturer: Dell Model: E5450 (SN : P48G001)
Note: The information of the EUT is declared by the manufacturer.	

2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards
FCC Code CFR47 Part15B (2018)
ANSI C63.4 (2014)

2.4 Test Mode

Test Mode	
Mode 1	Adapter + EUT + USB cable + Bluetooth on+ WCDMA on
Mode 2	Adapter + EUT + USB cable + Bluetooth on+ LTE on
Mode 3	Adapter + EUT + USB cable + Wi-Fi on+ WCDMA on
Mode 4	Adapter + EUT + USB cable + Wi-Fi on+ LTE on
Mode 5	Adapter + EUT + USB cable + idle

During the test, the preliminary test was performed in all modes, mode 5 for RE and CE are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

3 Test Case Results

3.1 Radiated Emission

Ambient condition

Temperature	Relative humidity	Pressure
24°C~26°C	45%~50%	102.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.
The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.
Set the spectrum analyzer in the following:
Below 1GHz:
RBW=100 kHz / VBW=300 kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO
(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

Test Setup

Below 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

Limits

Frequency (MHz)	Field Strength (dBμV/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5th harmonic of the highest frequency or 40GHz,which is lower	54 74	Average Peak

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 1.96.

Frequency	Uncertainty
30MHz~200MHz	4.02 dB
200MHz~1000MHz	3.28 dB
1GHz~18GHz	3.70 dB
18GHz~26.5GHz	5.78 dB
26.5GHz~40GHz	5.82 dB

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier, the Emissions in the frequency band 18GHz- 26.5GHz is more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software.
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.



Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
53.064906	29.79	100.0	V	18.0	0.4	10.21	40.00
77.454281	26.28	122.0	V	203.0	-6.2	13.72	40.00
160.063838	24.73	198.0	H	124.0	-7.1	18.77	43.50
193.882335	27.17	100.0	V	181.0	-4.3	16.34	43.50
372.036250	32.78	100.0	H	93.0	1.6	13.22	46.00
959.665500	38.32	125.0	H	210.0	8.7	7.68	46.00

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)
2. Margin = Limit – Quasi-Peak



Radiated Emission from 1GHz to 8GHz

Frequency (MHz)	Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
1499.375000	---	29.36	54.00	24.64	100.0	H	167.0	-8.7
1499.375000	45.25	---	74.00	28.75	100.0	H	167.0	-8.7
1799.000000	---	33.86	54.00	20.14	100.0	V	164.0	-7.0
1801.125000	50.54	---	74.00	23.46	200.0	V	177.0	-7.0
2700.000000	46.51	---	74.00	27.49	100.0	V	294.0	-3.6
2999.625000	---	33.16	54.00	20.84	100.0	H	211.0	-1.9
3297.125000	44.00	---	74.00	30.00	100.0	V	244.0	-1.7
3307.750000	---	37.02	54.00	16.98	200.0	V	328.0	-1.7
6765.125000	---	34.86	54.00	19.14	200.0	V	100.0	6.0
6769.375000	45.66	---	74.00	28.34	200.0	V	312.0	6.0
10673.000000	---	37.67	54.00	16.33	100.0	H	199.0	9.7
10681.500000	47.93	---	74.00	26.07	100.0	V	107.0	9.7

3.2 Conducted Emission

Ambient condition

Temperature	Relative humidity	Pressure
24°C ~26°C	50%~55%	102.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

Test Setup

Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46
5 - 30	60	50
*: Decreases with the logarithm of the frequency.		

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 1.96. U= 2.57 dB.

Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.19	---	34.21	54.11	19.90	1000.0	9.000	L1	ON	19
0.19	55.03	---	64.02	8.99	1000.0	9.000	L1	ON	19
0.37	29.35	---	58.49	29.14	1000.0	9.000	L1	ON	19
0.79	---	15.00	46.00	31.00	1000.0	9.000	L1	ON	19
0.99	---	16.99	46.00	29.01	1000.0	9.000	L1	ON	19
1.19	23.87	---	56.00	32.13	1000.0	9.000	L1	ON	19
3.16	---	17.22	46.00	28.78	1000.0	9.000	L1	ON	19
4.98	29.52	---	56.00	26.48	1000.0	9.000	L1	ON	19
7.04	---	27.44	50.00	22.56	1000.0	9.000	L1	ON	19
11.51	27.38	---	60.00	32.62	1000.0	9.000	L1	ON	19
12.88	36.33	---	60.00	23.67	1000.0	9.000	L1	ON	20
12.89	---	24.20	50.00	25.80	1000.0	9.000	L1	ON	20

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.19	---	34.41	54.11	19.70	1000.0	9.000	N	ON	19
0.20	53.24	---	63.63	10.39	1000.0	9.000	N	ON	19
0.38	27.76	---	58.39	30.63	1000.0	9.000	N	ON	19
0.80	---	24.00	46.00	22.00	1000.0	9.000	N	ON	19
1.20	31.19	---	56.00	24.81	1000.0	9.000	N	ON	19
1.20	---	24.23	46.00	21.77	1000.0	9.000	N	ON	19
3.19	---	31.77	46.00	14.23	1000.0	9.000	N	ON	19
4.92	28.57	---	56.00	27.43	1000.0	9.000	N	ON	19
7.13	---	26.09	50.00	23.91	1000.0	9.000	N	ON	19
12.38	36.34	---	60.00	23.66	1000.0	9.000	N	ON	19
12.70	37.20	---	60.00	22.80	1000.0	9.000	N	ON	19
12.90	---	23.67	50.00	26.33	1000.0	9.000	N	ON	19

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30 MHz

4 Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Time
Spectrum Analyzer	R&S	FSV40	15195-01-00	2019-05-19	2020-05-18
EMI Test Receiver	R&S	ESCI	100948	2019-05-19	2020-05-18
Trilog Antenna	SCHWARZBECK	VULB 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Standard Gain Horn	ETS-Lindgren	3160-09	00102643	2018-06-20	2020-06-19
Standard Gain Horn	STEATITE	QSH-SL-26-40-K-15	16779	2017-07-20	2020-07-19
EMI Test Receiver	R&S	ESR	101667	2019-05-19	2020-05-18
LISN	R&S	ENV216	101171	2019-12-15	2022-12-14
Bore Sight Antenna mast	ETS	2171B	00058752	/	/
Test software	EMC32	R&S	9.26.0	/	/

******END OF REPORT ******