



EUROFINS ELECTRICAL TESTING SERVICE (SHENZHEN) CO., LTD.

EMC TEST- REPORT

FCC Compliance Test Report for

Product name: Portable PC

Model name: CoreBook X

FCC ID: 2AHLZ-COERBOOKX

TEST REPORT NUMBER: EFGX22030020-IE-01-E08



Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Phone: +86-0755-82911867
Fax : +86-0755-82910749
Page 1 of 15

CONTENTS

1	General Information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of approval holder	4
1.4	Details of manufacturer	4
1.5	Application details	4
1.6	Test item	4
1.7	Test standards	4
2	Technical test	5
2.1	Summary of test results	5
2.2	Test environment	5
2.3	Test mode	5
2.4	List of Test equipment	6
2.5	System Measurement Uncertainty	6
2.6	Test results	7
3	Emission Test	8
3.1	Radiated emission	8
3.2	Conducted Emission	12

1 General Information

1.1 Notes

The results of this test report relate exclusively to the item tested as specified in chapter "Description of test item" and are not transferable to any other test items.

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. is not responsible for any generalisations and conclusions drawn from this report. Any modification of the test item can lead to invalidity of test results and this test report may therefore be not applicable to the modified test item.

The test report may only be reproduced or published in full. Reproducing or publishing extracts of the report requires the prior written approval of the Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

This document is subject to the General Terms and Conditions and the Testing and Certification System of Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. available on request or accessible at www.eurofins.com.

Operator:

2022-03-12

Bruce Zheng / Project Engineer



Date

Eurofins-Lab.


Name / Title

Signature

Technical responsibility for area of testing:

2022-03-12

Tom Tian / EMC Supervisor



Date

Eurofins-Lab.

Name / Title

Signature

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

1.2 Testing laboratory

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park, No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Telephone : +86-0755-82911867

Fax : +86-0755-82910749

1.3 Details of approval holder

Name : CHUWI TECHNOLOGY (ShenZhen) CO., LIMITED
Address : 2 Floor Building 3 LiJinCheng Industrial park the east of Gongye road LongHua, Shenzhen, China
Telephone : +86 755 29706511
Fax : N/A

1.4 Details of manufacturer

Name : CHUWI TECHNOLOGY (ShenZhen) CO., LIMITED
Address : 2 Floor Building 3 LiJinCheng Industrial park the east of Gongye road LongHua, Shenzhen, China
Telephone : +86 755 29706511
Fax : N/A

1.5 Application details

Date of receipt of test item : 2022-03-01
Date of receipt of test sample : 2022-03-01
Date of test : 2022-03-01 to 2022-03-11
Date of issue : 2022-03-12

1.6 Test item

Product type : Portable PC
Model name : CoreBook X
Brand name : CHUWI
Sample ID : 220301-126-003
Ratings : 100-240V~, 19V DC 3.42A
Test voltage : 120V~ 60Hz
Additional information : ./.

(General disclaimer:

The above sample(s) and sample information was/were submitted and identified on behalf of the applicant. Eurofins assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information and technical documents.)

1.7 Test standards

FCC 47 CFR Part 15, Subpart B

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	:	15	...	35 °C
Relative humidity content	:	30	...	60%
Air pressure	:	86	...	103kPa

2.3 Test mode

TM1: USB Link + Earphone

2.4 List of Test equipment

EQUIPMENT ID	EQUIPMENT NAME	MODEL NO.	CAL. DUE DATE
23-2-13-05	EMI Test Receiver	ESR3	2022-03-15
23-2-13-06	LISN	NNLK 8127 RC	2022-03-15
23-2-10-16	Attenuator	VTSD 9561-F	2022-03-16
23-2-13-01	EMI Test Receiver	ESR7	2022-03-15
23-2-13-02	Signal Analyzer	N9020B-544	2022-03-15
23-2-12-02	TRILOG Broadband Antenna	VULB9168	2022-04-27
23-2-12-03	Horn Antenna	3117	2022-05-11
23-2-12-04	Horn Antenna	BBHA 9170	2022-05-11
23-2-10-01	Preamplifier	BBV9745	2022-03-16
23-2-10-02	Preamplifier	TAP01018048	2022-03-16
23-2-10-03	Preamplifier	TAP18040048	2022-03-22
23-2-10-14	Switch and Control Unit	ERIT-E-JS0806-SF1	N/A
23-2-18-005	Test software	TS+VER2.1-JS32-CE	N/A
23-2-18-007	Test software	TS+VER2.1-JS32-RE	N/A
23-2-10-69	PC	M4000E-16	N/A
23-2-10-70	LED Monitor	D18215FD0	N/A
23-2-10-71	PC	M4000E-16	N/A
23-2-10-72	LED Monitor	V193HQV	N/A

2.5 System Measurement Uncertainty

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.56dB; Vertical: 4.55dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-6000MHz	Horizontal: 4.22dB; Vertical: 4.21dB;
Uncertainty for Conducted Emission 150kHz-30MHz	1.96dB
Uncertainty for Conducted Emission 150kHz-30MHz (for test using High Voltage Probe TK9420(VT9420))	2.18 dB

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

2.6 Test results

☒ 1st test☐ test after modification☐ production test

Test case	Subclause	Required	Test passed	Test failed
Conducted Emission	FCC part 15.107 ANSI C63.4: 2014	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission	FCC part 15.109 ANSI C63.4: 2014	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

3 Emission Test

3.1 Radiated emission

This clause lays down the general requirements for the measurement of Radiated disturbance produced at the space of apparatus.

3.1.1 Limits

Frequency range	Limits at 3m
MHz	dB (μV/m)
30 to 88	40.0
88 to 216	43.5
216 to 960	46.0
Above 960	54.0


The tighter limit applies at the band edges.

Note 1: Result Level= Read Level + Corrector Factor

Note 2: Below 1GHz: Corrector factor = Antenna Factor + Cable Loss - Amplifier Gain.

Note 3: Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain.

3.1.2 Measurement procedure



1. The radiated emissions test was conducted in a semi-anechoic chamber. The EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
2. Before get the final emission results with quasi-peak(QP) detector, a pre-scan was performed with the peak(PK) detector to find out the maximum emission data plots of the EUT.
3. The frequencies of maximum emission were determined in the final radiated emissions measurement, the physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization. Test was performed at 3 m distance.

Test Report No.: EFGX22030020-IE-01-E08


Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

3.1.3 Test environment

Temperature : 24.6 °C
 Relative humidity content : 57.6 %
 Air pressure : 101.5 kPa

3.1.4 Results

Below 1GHz




NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	31.9419	-17.14	38.36	50.00	11.64	Vertical	PASS
2	48.4484	-15.39	37.76	50.00	12.24	Vertical	PASS
3	160.1101	-15.66	26.64	53.50	26.86	Vertical	PASS
4	479.5596	-17.50	37.00	56.00	19.00	Vertical	PASS
5	589.2793	-3.48	39.49	56.00	16.51	Vertical	PASS
6	895.1351	-4.26	48.58	56.00	7.42	Vertical	PASS

Horizontal Polarity Test Data

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China



NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	56.2162	-15.85	31.29	50.00	18.71	Horizontal	PASS
2	161.0811	-15.73	27.79	53.50	25.71	Horizontal	PASS
3	239.7297	-17.70	32.64	56.00	23.36	Horizontal	PASS
4	360.1301	-15.71	31.20	56.00	24.80	Horizontal	PASS
5	479.5596	-17.50	41.19	56.00	14.81	Horizontal	PASS
6	960.1902	-3.92	40.80	60.00	19.20	Horizontal	PASS

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Above 1GHz
Vertical Polarity Test Data

PK Data List								
NO.	Freq. [MHz]	Level [dB μ V/m]	Factor [dB/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1318.3183	40.55	-26.66	74.00	33.45	150	304	Vertical
2	1628.6286	40.49	-25.79	74.00	33.51	150	262	Vertical
3	2119.1191	43.21	-22.38	74.00	30.79	150	72	Vertical
4	2923.9239	46.43	-19.20	74.00	27.57	150	172	Vertical
5	3732.7327	48.42	-16.37	74.00	25.58	150	253	Vertical
6	4945.9459	49.44	-14.63	74.00	24.56	150	206	Vertical

Horizontal Polarity Test Data

PK Data List								
NO.	Freq. [MHz]	Level [dB μ V/m]	Factor [dB/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1360.3604	40.34	-26.61	74.00	33.66	150	289	Horizontal
2	1830.8308	41.73	-24.07	74.00	32.27	150	46	Horizontal
3	2979.9800	46.78	-18.83	74.00	27.22	150	326	Horizontal
4	3858.8589	49.20	-15.77	74.00	24.80	150	309	Horizontal
5	4477.4775	49.27	-15.19	74.00	24.73	150	319	Horizontal
6	5057.0571	49.90	-14.84	74.00	24.10	150	0	Horizontal

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

3.2 Conducted Emission


This clause lays down the general requirements for the measurement of disturbance voltage produced at the terminals of apparatus.

3.2.1 Limits

Frequency range MHz	At mains terminals dB (μV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note 1: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 30 MHz.
Note 2: The lower limit is applicable at the transition frequency.

3.2.2 Measurement procedure




1. The mains terminal disturbance voltage was measured with the EUT in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $(50 \mu H + 5 \Omega) \parallel 50 \Omega$ linear impedance. The power cables of all other units of the EUT was connected to a second LISN, which was bonded to the ground reference plane in the same way as the LISN for the unit being measured.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.

3.2.3 Test environment

Temperature : 25.2 °C
 Relative humidity content : 57.1 %
 Air pressure : 101.5 kPa

3.2.4 Results -Measurement Data

Live line test data




NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1671	10.25	52.79	65.11	12.32	38.88	55.11	16.23	L	PASS
2	0.4297	10.25	53.79	57.26	3.47	42.79	47.26	4.47	L	PASS
3	0.4474	10.26	52.80	56.92	4.12	42.10	46.92	4.82	L	PASS
4	0.8410	10.28	41.87	56.00	14.13	31.44	46.00	14.56	L	PASS
5	2.3510	10.35	46.60	56.00	9.40	34.90	46.00	11.10	L	PASS
6	2.6205	10.37	47.60	56.00	8.40	36.67	46.00	9.33	L	PASS
7	2.8597	10.37	51.23	56.00	4.77	38.46	46.00	7.54	L	PASS
8	5.0538	10.41	41.77	60.00	18.23	31.53	50.00	18.47	L	PASS
9	10.5462	10.54	44.92	60.00	15.08	37.11	50.00	12.89	L	PASS

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Neutral line test data



NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1788	10.24	54.72	64.54	9.82	43.00	54.54	11.54	N	PASS
2	0.4150	10.25	51.90	57.55	5.65	42.29	47.55	5.26	N	PASS
3	0.6410	10.26	46.43	56.00	9.57	37.72	46.00	8.28	N	PASS
4	0.7895	10.26	43.76	56.00	12.24	34.37	46.00	11.63	N	PASS
5	2.7175	10.32	48.98	56.00	7.02	35.96	46.00	10.04	N	PASS
6	2.9291	10.32	52.37	56.00	3.63	39.39	46.00	6.61	N	PASS
7	4.3677	10.35	41.54	56.00	14.46	31.73	46.00	14.27	N	PASS
8	10.8924	10.50	42.93	60.00	17.07	34.54	50.00	15.46	N	PASS

---End of Report---

Test Report No.: EFGX22030020-IE-01-E08

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China