Johns Hopkins Engineering

Introduction to GPU Programming

Module 11 Lecture 11A An Introduction to OpenCL Platforms

JOHNS HOPKINS
WHITING SCHOOL
of ENGINEERING

JOHNS HOPKINS
WHITING SCHOOL
of ENGINEERING

Chancellor T. Pascale
Computer Science Department

Overview

1. OpenCL Platforms

JOHNS HOPKINS
WHITING SCHOOL of ENGINEERING

11.1 OpenCL Platforms

The material in this video is subject to the copyright of the owners of the material and is being provided for educational purposes under rules of fair use for registered students in this course only. No additional copies of the copyrighted work may be made or distributed.

OpenCL Platforms

- Cl_int clGetPlatformIDs (cl_uint num_entries,
  cl_platform id * platforms,
  cl_uint * num_platforms)
  - Used to query the set of available platforms
  - If platforms parameter is NULL than number of platforms is returned.
  - If num_entries and num_platforms parameters are set to 0 and NULL than number of available platforms is returned.
  - platforms will hold the platform IDs for the available platforms, the size of the which is determined by num_entries

OpenCL Platforms

- Cl_int clGetPlatformIDs(cl_platform_id platform,
  cl_platform_info param_name,
  size_t param_value_size,
  void * param_value,
  size_t * param_value_size_ret)
  - Table 3.1 in the book shows valid queries
  - Set param_value_size and param_value to 0 and NULL to get the size of a returned value