
GATEX


Build better.

PRODUCTLIST

Fiberglass Catalogue

English





GATEX

CARBON NEUTRAL

Printed on paper containing 20% recycled material

REACH Compliant

FOR A SUSTAINABLE FUTURE

Stronger Together: Fiberglass Innovation.

At GATEX, innovation is a continuous process built around the manufacturing of high-performance fiberglass reinforcement mesh. Our in-house manufacturing process covers warping, weaving, coating/impregnation, drying/curing, finishing and final inspection, ensuring consistent quality and full traceability. With approximately 4.5 million square meters of fiberglass mesh produced during the reference period, GATEX serves insulation system manufacturers and construction distributors across European markets. Our production facility combines modern machinery, precision coating technology and alkali-resistant coating formulations designed to support long-term durability and reliable performance under demanding conditions.

What We Do

We manufacture high-performance fiberglass reinforcement mesh for ETICS systems, façade reinforcement and thermal insulation. At our production facility in Kosovo, our in-house process covers warping, weaving, coating/impregnation, drying/curing, finishing and final inspection, ensuring consistent quality and total traceability. Our environmental approach is guided by responsible manufacturing, efficient use of materials and energy, and continuous improvement under ISO 14001 — principles reflected in our internal Climate Positive Policy. Our qualifying fiberglass mesh products are ETA-assessed and CE marked, while GATEX operates certified management systems according to ISO 9001, ISO 14001 and ISO 45001. Designed for durability and reliable installation, our reinforcement mesh is supplied across European markets.

~4,500,000 m²	**Annual Mesh Production** 4,500,000+ m² fiberglass mesh/year across all product types
~1,255 m²	**Production Facility Size** ~1,255 m² production facility for warping, weaving, coating and packaging
21+	**Export Markets** Active in 21+ countries, including Italy, Germany, Poland, Greece, Albania, Croatia, Spain, Cyprus, Malta, Belgium, France, Portugal...



Where Quality Meets Climate Awareness

ETA-Assessed Excellence

We are a trusted manufacturer of fiberglass reinforcement mesh, with qualifying products assessed under European Technical Assessment ETA 24/0211, based on EAD 040016-01-0404, and CE marked. GATEX operates certified ISO 9001, ISO 14001 and ISO 45001 management systems through TÜV NORD, supporting consistent quality, environmental responsibility and workplace safety. From Kaçanik, Western Balkans, we maintain a culture of engineering precision, traceability and care across every roll we produce at our facility.



Who We Are

We are a dedicated team of engineers, technicians and production specialists committed to manufacturing reinforcement mesh with consistency, precision and care. Based in Kaçanik, Western Balkans, we combine textile engineering, materials knowledge and construction expertise within an integrated production process covering warping, weaving, coating, finishing and final inspection.

Our Mission

To manufacture ETA-assessed and CE-marked fiberglass reinforcement mesh through a controlled, integrated production process — supporting energy-efficient construction, durable façades and reliable supply across Europe. We empower our partners through consistent quality, responsiveness and long-term collaboration.

Our Vision

We aim to be more than a manufacturer — we strive to be a strategic partner in building the future. At GATEX, we envision a construction industry that is sustainable, efficient and high-performing, supported by technically sound materials, responsible practices and collaborative growth. As a regional manufacturer, we are committed to responsible production, innovation and shared progress across European markets.

build better.

Standards, Certifications & Commitments

Our Recognized Standards, Certifications & Commitments

GATEX products are supported by technical and regulatory documentation applicable to their respective specifications and intended use. Qualifying reinforcement mesh products are covered by European Technical Assessment, corresponding Declarations of Performance and CE marking. GATEX operates certified ISO 9001, ISO 14001 and ISO 45001 management systems. Product-specific technical documentation, including Technical Datasheets and relevant performance information, is available to support procurement, engineering and installation requirements. For distributors, we also provide product guidance and branding support to ensure clear and consistent product communication.

CE
European Technical Assessment
ETA-24/0211

EOTA
Conforms to ETAG 004
European Technical Approval ETAG 004 - (EOTA): 2011

TÜVNORD
ISO 9001 2015 ISO 14001 2015 ISO 45001 2018
Integrated Management System

Climate Positive

REACH Compliant


CO_2 CARBON NEUTRAL

SIST EN ISO 1716:2018
Reaction to Fire

*GATEX environmental policies and commitments; not third-party certifications.

Fiberglass Products

At GATEX, fiberglass reinforcement mesh is at the core of what we do—combining strength, flexibility and durability for modern External Thermal Insulation Composite Systems (ETICS) and façade applications. Our product range is developed to support reliable reinforcement, dimensional stability and efficient installation across a wide variety of construction requirements. Available in different weights, mesh configurations, colours and roll formats, GATEX fiberglass mesh is designed to meet both standard and demanding façade applications. Through precision manufacturing, continuous quality control and ongoing product development, we deliver reinforcement solutions that combine consistent performance, workability and long-term reliability.



GATEX G–75

Standard


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 75g/m²

The GATEX G-75 Standard fiberglass mesh is a high-performance reinforcement fabric developed for use in External Thermal Insulation Composite Systems (ETICS) and under-plaster applications. Supplied in 50 m rolls with a width of 1 m and a material weight of 75 g/m², it offers an optimal combination of tensile strength, flexibility, and ease of application, making it ideal for a wide range of façade insulation projects. Engineered to reinforce base coat layers, the G-75 mesh provides exceptional protection against cracking, deformation, and surface stress. Its stable 5×5 mm weave pattern ensures uniform reinforcement, maintaining dimensional stability throughout the lifespan of the system. The lightweight yet durable fiberglass structure offers excellent resistance to both mechanical impact and thermal expansion, ensuring consistent façade performance under demanding conditions. Coated with an alkali-resistant finish, G-75 delivers long-lasting durability even in challenging environments. Its flexibility allows for effortless handling, cutting, and embedding into base coats, reducing installation time while maintaining precision and reliability. Designed for both new constructions and renovation works, the GATEX G-75 Standard creates a robust, crack-resistant foundation for smooth and stable plaster finishes. By integrating this mesh into ETICS layers, you ensure lasting protection, structural reinforcement, and an enhanced façade appearance. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info. It contains detailed specifications, application guidelines, and safety recommendations to ensure proper use and long-term system reliability.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 75 g/m²
Mesh size	approx. 5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–75

Professional


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 75g/m²

The GATEX G-75 Professional fiberglass mesh is a premium-grade reinforcement fabric designed for high-performance façade insulation systems and demanding under-plaster applications. Supplied in 50 m rolls, 1 m wide, and with a material weight of 75 g/m², it combines superior tensile strength, flexibility, and precision to meet the rigorous standards of professional ETICS installations. Developed for heavy-duty use, G-75 Professional provides exceptional resistance to cracking, deformation, and thermal stress throughout the lifespan of the façade system. Its dense 5×5 mm mesh structure ensures complete dimensional stability and even load distribution, effectively reinforcing base coat layers and maintaining consistent surface integrity. Constructed from top-grade, alkali-resistant fiberglass yarns and coated with an advanced protective finish, G-75 Professional guarantees long-term durability and reliable performance even under extreme environmental conditions. The mesh's stable yet elastic structure allows for quick handling and perfect embedding into plaster systems, resulting in flawless surface finishes and reduced installation time. Ideal for large-scale construction, public buildings, and high-performance façade systems, the GATEX G-75 Professional delivers maximum structural reinforcement, excellent adhesion, and enduring façade protection. It represents the highest level of reliability and efficiency within the G-75 product range. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info. It contains detailed specifications, application guidelines, and safety recommendations to ensure proper use and long-term system reliability.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 75 g/m²
Mesh size	approx. 5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–110

Standard


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 110g/m²

The GATEX G-110 Standard fiberglass mesh is a premium reinforcement fabric engineered for advanced façade insulation and under-plaster applications within External Thermal Insulation Composite Systems (ETICS). Supplied in 50 m rolls, 1 m in width, and with a material weight of 110 g/m², it combines outstanding tensile strength, flexibility, and dimensional precision—offering exceptional performance for professional and large-scale construction projects. Developed for demanding insulation systems, G-110 Standard provides superior resistance to cracking, deformation, and surface stress caused by mechanical or thermal impact. Its precise 10×10 mm mesh structure ensures uniform force distribution and complete dimensional stability, maintaining long-term façade integrity and preventing deterioration across the plaster surface. Manufactured from top-grade, alkali-resistant fiberglass yarns and coated with a high-performance protective finish, G-110 Standard offers exceptional durability and compatibility with cementitious materials. The mesh's dense yet elastic structure allows quick handling and effortless embedding, ensuring optimal adhesion, consistent reinforcement, and a smooth, impact-resistant finish. Ideal for public buildings, commercial developments, and high-performance ETICS systems, the GATEX G-110 Standard delivers maximum structural reinforcement, long-term façade protection, and reliable performance under extreme conditions. It stands as the most advanced and durable solution within the G-110 product range. For detailed technical specifications and installation guidelines, please refer to the technical data sheet available at www.gatex.info



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 110 g/m²
Mesh size	10.0 (±1.0) mm × 10 (±1.0) mm
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–110
Professional


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 110g/m²

The GATEX G-110 Professional fiberglass mesh is a premium reinforcement fabric engineered for advanced façade insulation and under-plaster applications within External Thermal Insulation Composite Systems (ETICS). Supplied in 50 m rolls, 1 m in width, and with a material weight of 110 g/m², it combines outstanding tensile strength, flexibility, and dimensional precision—offering exceptional performance for professional and large-scale construction projects. Developed for demanding insulation systems, G-110 Professional provides superior resistance to cracking, deformation, and surface stress caused by mechanical or thermal impact. Its precise 10×10 mm mesh structure ensures uniform force distribution and complete dimensional stability, maintaining long-term façade integrity and preventing deterioration across the plaster surface. Manufactured from top-grade, alkali-resistant fiberglass yarns and coated with a high-performance protective finish, G-110 Professional offers exceptional durability and compatibility with cementitious materials. The mesh's dense yet elastic structure allows quick handling and effortless embedding, ensuring optimal adhesion, consistent reinforcement, and a smooth, impact-resistant finish. Ideal for public buildings, commercial developments, and high-performance ETICS systems, the GATEX G-110 Professional delivers maximum structural reinforcement, long-term façade protection, and reliable performance under extreme conditions. It stands as the most advanced and durable solution within the G-110 product range. For detailed technical specifications and installation guidelines, please refer to the technical data sheet available at www.gatex.info



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 110 g/m²
Mesh size	10.0 (±1.0) mm × 10 (±1.0) mm
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–125

Classic


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 125g/m²

The GATEX G-125 Classic fiberglass mesh is a reliable, durable reinforcement fabric developed for standard use in External Thermal Insulation Composite Systems (ETICS) and under-plaster applications. Supplied in 50 m rolls, 1 m wide, and weighing 125 g/m², it delivers a balanced combination of strength, flexibility, and ease of use for everyday façade reinforcement. Designed as a cost-efficient solution for residential and moderate-load façades, G-125 Classic effectively minimizes cracks and surface deformation caused by temperature fluctuations or light mechanical impact. Its uniform 10×10 mm mesh pattern ensures stable coverage, even tension distribution, and consistent plaster adhesion. Manufactured from alkali-resistant fiberglass yarns, the mesh maintains its structural integrity when embedded in cementitious base coats, ensuring reliable long-term performance under normal environmental exposure. Lightweight and easy to embed, G-125 Classic enables efficient installation while maintaining a smooth, uniform surface finish Ideal for small to mid-scale projects and standard ETICS systems, the GATEX G-125 Classic provides dependable reinforcement and durable protection—delivering proven quality at an accessible cost. For comprehensive information on product performance, composition, and correct installation procedures, please consult the official technical data sheet available at www.gatex-.info. The document includes detailed technical parameters, application recommendations, and safety guidelines essential for ensuring optimal system performance and long-term façade durability.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 125 g/m²
Mesh size	approx. 5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–125
Standard


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 125g/m²

The GATEX G-125 Standard fiberglass mesh is a high-performance reinforcement fabric developed for use in External Thermal Insulation Composite Systems (ETICS) and under-plaster applications. Supplied in 50 m rolls, 1 m in width, and with a material weight of 125 g/m², it offers excellent tensile strength, dimensional stability, and ease of installation for professional façade applications. Engineered to reinforce base coat layers, G-125 Standard provides strong protection against cracking, deformation, and surface stress caused by thermal expansion or mechanical impact. Its stable 10×10 mm mesh structure ensures uniform load distribution and long-term stability across the entire façade surface. Constructed from alkali-resistant fiberglass yarns, the G-125 Standard guarantees lasting durability and compatibility with cementitious materials. The mesh's flexible and lightweight composition allows for effortless cutting, handling, and embedding, ensuring smooth plaster finishes and a consistent appearance. Designed for both new constructions and renovation works, the GATEX G-125 Standard provides a reliable, mid-to-high performance solution that enhances structural stability, reduces façade maintenance, and extends system lifespan. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info. It contains detailed specifications, application guidelines, and safety recommendations to ensure proper use and long-term system reliability.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 125 g/m²
Mesh size	approx. 5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



For more information, refer to the technical data sheet.
All technical data sheets and product descriptions listed must be strictly followed to ensure proper application and performance.

GATEX G–125
Professional


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 125g/m²

The GATEX G-125 Professional fiberglass mesh is a premium-grade reinforcement fabric designed for high-performance ETICS and under-plaster applications. Supplied in 50 m rolls, 1 m wide, and weighing 125 g/m², it combines exceptional tensile strength, flexibility, and dimensional precision—ensuring maximum façade protection and long-term reliability. Developed for demanding construction environments, G-125 Professional offers superior resistance to cracking, surface deformation, and stress caused by thermal and mechanical loads. Its reinforced 10×10 mm mesh structure provides complete dimensional control, ensuring even load transfer and maintaining façade integrity under extreme conditions. Produced from top-quality, alkali-resistant fiberglass yarns and finished with an advanced protective coating, G-125 Professional ensures exceptional chemical stability, moisture resistance, and compatibility with cement-based systems. The mesh's dense yet flexible weave allows for fast embedding, precise installation, and a smooth, durable plaster finish. Ideal for public buildings, commercial façades, and high-performance insulation systems, the GATEX G-125 Professional represents the highest level of reinforcement within the G-125 range—delivering unmatched strength, durability, and performance for long-lasting façade protection. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info. It contains detailed specifications, application guidelines, and safety recommendations to ensure proper use and long-term system reliability.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 125 g/m²
Mesh size	approx. 5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



ETAG 004 (EOTA):2011

CARBON NEUTRAL

GATEX G–145

Standard


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 145g/m²

The GATEX G-145 Standard fiberglass mesh is a high-performance reinforcement fabric specifically designed for External Thermal Insulation Composite Systems (ETICS) and under-plaster applications. Supplied in 50 m rolls, 1 m wide, and with a material weight of 145 g/m², it delivers robust tensile strength, reliable durability, and efficient installability—ideal for professional façade insulation solutions. Engineered to reinforce base coat layers, the G-145 Standard provides strong resistance against cracking, deformation, and surface stress caused by both thermal fluctuations and mechanical impact. Its dense 5×5 mm mesh structure ensures uniform force distribution and dimensional stability across the insulation layer. Manufactured using alkali-resistant fiberglass yarns and finished with a protective coating, the G-145 Standard offers long-term protection against weathering, chemical exposure, and façade loads. Despite its strength, the mesh remains flexible and easy to handle, enabling clean embedding, excellent adhesion, and smooth plaster finishes—enhancing installation speed and surface quality. Ideal for new construction and renovation projects seeking reliable, high-grade façade reinforcement, the GATEX G-145 Standard ensures consistent performance, extended service life, and visual integrity for modern ETICS systems. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info. It contains detailed specifications, application guidelines, and safety recommendations to ensure proper use and long-term system reliability.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 145 g/m²
Mesh size	5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–145

Standard (Red)


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 145g/m²

The GATEX G-145 Standard (Red) fiberglass mesh is a high-strength reinforcement fabric developed for professional use in External Thermal Insulation Composite Systems (ETICS) and under-plaster applications. Supplied in 50 m rolls, 1 m wide, and weighing 145 g/m², it combines superior tensile strength, dimensional stability, and workability—making it ideal for durable and long-lasting façade reinforcement. Engineered to provide reliable performance under demanding conditions, G-145 Standard (Red) minimizes cracking, deformation, and surface stress caused by temperature variations or mechanical loads. Its 5×5 mm mesh structure ensures even stress distribution and complete dimensional stability, enhancing the lifespan and structural integrity of ETICS systems. Manufactured from high-quality, alkali-resistant fiberglass yarns and finished with a distinctive red protective coating, this mesh offers excellent chemical resistance and long-term protection against environmental wear. Despite its robustness, the material remains flexible and easy to handle, allowing for smooth embedding, efficient installation, and a uniform plaster finish. Ideal for both new constructions and renovation projects, GATEX G-145 Standard (Red) ensures optimal reinforcement and mechanical performance across various façade systems. It represents a professional-grade solution for achieving durable, crack-free, and visually consistent surface finishes. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info. It contains detailed specifications, application guidelines, and safety recommendations to ensure proper use and long-term system reliability.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 145 g/m²
Mesh size	5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	Red (other colors available)
Packaging	Shrink-wrapped rolls with label



GATEX G–145
Professional


ETA-Certified Fiberglass Mesh for External Thermal Insulation Systems / 145 g/m²

The GATEX G-145 Professional fiberglass mesh is a high-quality, ETA-certified reinforcement fabric specifically designed for External Thermal Insulation Composite Systems (ETICS) and under-plaster applications. Supplied in 50 m rolls, 1 m wide, and weighing 145 g/m², it combines exceptional tensile strength, dimensional stability, and flexibility—making it an essential component for reliable and long-lasting façade insulation systems. Engineered to reinforce base coat layers, G-145 Professional provides strong resistance against cracking, deformation, and surface stress caused by mechanical impact and temperature fluctuations. Its dense 5×5 mm mesh structure ensures even load distribution and complete dimensional stability, maintaining consistent adhesion and performance throughout the lifespan of the insulation system. Manufactured from high-grade, alkali-resistant fiberglass yarns and coated with a protective finish, G-145 Professional delivers outstanding resistance to environmental stress, moisture, and alkalinity. Despite its robust structure, the mesh remains flexible and easy to handle, allowing for quick embedding, clean installation, and a smooth, uniform plaster surface. Ideal for both new constructions and renovation projects, the GATEX G-145 Professional offers dependable reinforcement, enhanced façade protection, and long-term structural stability. It represents the optimal balance between strength, workability, and efficiency—making it a trusted choice for professional ETICS applications. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info.



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 145 g/m²
Mesh size	5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–145
Professional (Red)


ETA-Certified Fiberglass Mesh for External Thermal Insulation Systems / 145 g/m²

The GATEX G-145 Professional (Red) fiberglass mesh is a premium, ETA-certified reinforcement fabric developed for high-performance façade insulation and demanding under-plaster applications within External Thermal Insulation Composite Systems (ETICS). Supplied in 50 m rolls, 1 m wide, and weighing 145 g/m², it combines outstanding tensile strength, dimensional accuracy, and flexibility—ensuring reliable performance and long-term structural integrity across the entire façade system. Specifically engineered for professional and large-scale projects, G-145 Professional (Red) provides maximum resistance against cracking, deformation, and surface stress caused by mechanical loads or thermal expansion. Its reinforced 5×5 mm mesh structure ensures even stress distribution and full dimensional stability, maintaining consistent adhesion and façade protection under challenging environmental conditions. Manufactured from top-grade, alkali-resistant fiberglass yarns and coated with a distinctive red polymer finish, G-145 Professional offers exceptional resistance to weathering, alkalinity, and moisture. Despite its robust and dense composition, the mesh remains flexible and easy to handle, allowing for fast embedding, precise alignment, and smooth plaster application with minimal effort. Designed for the most demanding ETICS systems, the GATEX G-145 Professional (Red) represents the highest level of performance within the G-145 range—combining durability, strength, and efficiency to deliver superior façade reinforcement and long-lasting surface protection. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 145 g/m²
Mesh size	5 × 5 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	Red (other colors available)
Packaging	Shrink-wrapped rolls with label



GATEX G–160
Standard


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 160g/m²

The GATEX G-160 Standard fiberglass mesh is a high-performance reinforcement fabric specifically engineered for use in External Thermal Insulation Composite Systems (ETICS) and under-plaster applications. Supplied in 50 m rolls, 1 m wide, and with a material weight of 160 g/m², it offers superior tensile strength, outstanding dimensional stability, and reliable durability—making it ideal for professional façade insulation and demanding construction environments. Designed to reinforce base coat layers, G-160 Standard provides exceptional resistance against cracking, deformation, and surface stress resulting from mechanical loads or thermal expansion. Its dense 4x4 mm mesh structure ensures uniform load distribution and maintains dimensional integrity across the entire insulation surface, enhancing system strength and longevity. Manufactured from alkali-resistant fiberglass yarns and coated with a high-performance protective layer, G-160 Standard guarantees long-term resistance to alkalinity, weathering, and chemical exposure. Despite its robust composition, the mesh remains flexible and easy to handle, ensuring fast, precise embedding and a clean, uniform plaster finish. Perfect for new builds, refurbishment projects, and high-performance façade systems, the GATEX G-160 Standard provides maximum reinforcement efficiency, long-lasting protection, and a stable foundation for high-quality plaster surfaces. It is the trusted choice for projects requiring enhanced strength and durability under challenging conditions. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 160 g/m²
Mesh size	4 × 4 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



For more information, refer to the technical data sheet.
All technical data sheets and product descriptions listed must be strictly followed to ensure proper application and performance.

GATEX G–160
Standard (Red)


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 160g/m²

The GATEX G-160 Standard (Red) fiberglass mesh is a high-performance reinforcement fabric designed for professional ETICS and under-plaster applications that demand superior strength and long-term durability. Supplied in 50 m rolls, 1 m wide, and weighing 160 g/m², it combines exceptional tensile performance, dimensional accuracy, and workability—making it ideal for high-quality façade insulation systems. Engineered for robust reinforcement of base coat layers, G-160 Standard (Red) provides excellent protection against cracking, deformation, and surface stress caused by thermal expansion, vibrations, and mechanical impact. Its dense 4x4 mm mesh pattern ensures even load distribution and dimensional stability across the entire insulation system, reinforcing the façade against long-term wear and environmental challenges. Produced from alkali-resistant fiberglass yarns and coated with a distinctive red polymer finish, G-160 Standard (Red) offers advanced resistance to alkalinity, weathering, and chemical exposure. Despite its heavy-duty strength, the mesh remains flexible and easy to cut, handle, and embed—enabling smooth installation and clean plaster application with consistent adhesion. Perfect for large-scale construction projects, commercial buildings, and renovation works, the GATEX G-160 Standard (Red) ensures maximum structural reinforcement, façade integrity, and surface protection. It represents the optimal balance between power, precision, and efficiency—delivering long-term stability and aesthetic quality in modern ETICS systems. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 160 g/m²
Mesh size	4 × 4 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	Red (other colors available)
Packaging	Shrink-wrapped rolls with label



GATEX G–160
Professional


ETA-Certified Fiberglass Mesh for External Thermal Insulation Systems / 160 g/m²

The GATEX G-160 Professional fiberglass mesh is a premium, ETA-certified reinforcement fabric developed for high-performance façade insulation and advanced under-plaster applications within External Thermal Insulation Composite Systems (ETICS). Supplied in 50 m rolls, 1 m wide, and weighing 160 g/m², it combines exceptional tensile strength, dimensional precision, and flexibility—ensuring unmatched performance and long-term structural stability in professional construction environments. Specifically designed for large-scale and demanding projects, G-160 Professional provides maximum protection against cracking, deformation, and surface stress resulting from thermal expansion, vibrations, or mechanical impact. Its reinforced 4x4 mm mesh structure ensures uniform force distribution and complete dimensional stability, preserving façade integrity and durability even under extreme conditions. Manufactured from top-grade, alkali-resistant fiberglass yarns and coated with a high-performance protective layer, G-160 Professional offers outstanding resistance to alkalinity, weathering, and moisture. Despite its dense and durable composition, the mesh maintains excellent flexibility, allowing for quick handling, precise embedding, and smooth plaster application with consistent adhesion. Ideal for high-end insulation systems, public infrastructure, and commercial façades, the GATEX G-160 Professional represents the top standard within the G-160 range—combining strength, longevity, and technical reliability to ensure superior façade reinforcement and long-lasting surface protection. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 160 g/m²
Mesh size	4 × 4 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	White (standard)
Packaging	Shrink-wrapped rolls with label



GATEX G–160

Professional (Red)


Reinforcing Mesh for External Thermal Insulation Systems (ETICS) / 160g/m²

The GATEX G-160 Professional (Red) fiberglass mesh is a premium, ETA-certified reinforcement fabric engineered for the most demanding façade insulation and under-plaster applications within External Thermal Insulation Composite Systems (ETICS). Supplied in 50 m rolls, 1 m wide, and weighing 160 g/m², it combines outstanding tensile strength, dimensional stability, and flexibility—delivering superior reinforcement performance and long-term façade protection in professional-grade systems. Developed for large-scale, high-performance construction projects, G-160 Professional (Red) ensures maximum resistance against cracking, deformation, and stress caused by thermal fluctuations and mechanical impact. Its reinforced 4x4 mm mesh structure guarantees even load transfer and full dimensional control, maintaining façade integrity under extreme environmental conditions. Manufactured from high-quality, alkali-resistant fiberglass yarns and coated with a distinctive red polymer finish, G-160 Professional (Red) provides exceptional resistance to alkalinity, weathering, and chemical exposure. Despite its robust structure, the mesh remains flexible and easy to apply, allowing for fast embedding, accurate alignment, and a smooth, uniform plaster finish. Designed for professional ETICS systems where performance, precision, and durability are paramount, the GATEX G-160 Professional (Red) represents the highest standard of reinforcement within the G-160 range—ensuring maximum strength, longevity, and reliability across all façade applications. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

Key Features:	
Weight per unit area	approx. 160 g/m²
Mesh size	4 × 4 mm (±1%)
Width	100 cm
Length per roll	50 m
Color	Red (other colors available)
Packaging	Shrink-wrapped rolls with label



GATEX G–5090

Fiber Glass Joint Tape


Alkali-Resistant Fiberglass Mesh with Self-Adhesive Backing 48 / 100 mm, 90 m



• Soft & flexible • Alkali-resistant • Slip proof
• Tear-resistant • Anti-snag • Weatherproof

The GATEX G-5090 Fiberglass Joint Tape is a high-performance, alkali-resistant reinforcement tape developed for professional drywall finishing applications. Designed to strengthen gypsum board joints and prevent surface cracking, it provides long-term stability and a smooth, even finish in wall and ceiling systems. Supplied in 90 m rolls with widths of 48 mm and 100 mm, G-5090 ensures clean application, strong adhesion, and reliable joint reinforcement in both bedding and finishing layers. Engineered for precise embedding into gypsum joint compounds or ready-mixed finishing compounds, G-5090 provides consistent reinforcement and dimensional stability across drywall joints and corner intersections. Its self-adhesive fiberglass backing ensures quick installation, reducing preparation time while maintaining firm placement during application. Manufactured from high-grade, alkali-resistant fiberglass mesh with a durable self-adhesive coating, GATEX G-5090 offers high tensile strength, excellent adhesion, and compatibility with a wide range of gypsum-based systems. The lightweight structure allows effortless handling, while the open mesh design ensures complete bonding and smooth compound coverage. Designed for professional drywall systems requiring high strength and precision, the GATEX G-5090 Fiberglass Joint Tape guarantees a seamless finish, long-term crack prevention, and optimal surface preparation for painting or decorative coatings. It is supplied in individually wrapped rolls for protection and storage convenience. For comprehensive information on product performance, composition, and correct installation procedures, please refer to the official technical data sheet available at www.gatex.info

Key Features:	
Weight per unit area	approx. 75 g/m²
Mesh size	4 × 4 mm (±1%)
Width	48 mm / 100 mm
Length per roll	90 m
Color	White (standard)
Packaging	Individually wrapped rolls




Standards & Certifications

Our Established Product Qualities

Each GATEX product is defined by seven key performance strengths: Thermal Efficiency, offering minimal heat conduction for optimal energy retention; Fire Endurance, maintaining integrity under extreme temperatures; Electrical Neutrality, ensuring complete insulation and safety; Material Harmony, perfectly bonding with organic matrices to enhance structural cohesion; Superior Strength-to-Weight, combining lightness with durability that exceeds steel by specific resistance; Structural Precision, guaranteeing dimensional stability under mechanical or thermal stress; and Environmental Resilience, providing long-term protection against moisture, UV exposure, and chemical influence.

Every GATEX product is supported by comprehensive technical and regulatory documentation to facilitate procurement, engineering, and installation. We provide CE marking, ETAG 004 declarations, ETA certifications, TÜV testing, and full compliance with ISO 9001 / 14001 management systems. Each mesh type includes its own Technical Datasheet, Safety Data Sheet (SDS), and mechanical performance charts. For distributors, GATEX offers installation guidelines, training materials, and branding resources, ensuring your team can implement and promote our fiberglass systems with confidence and precision.



build better.

From raw yarn to certified strength.

Engineering Precision

At GATEX, we specialize in the manufacturing of fiberglass reinforcement mesh through an integrated, fully controlled process — from warping and weaving to coating/impregnation, drying/curing, finishing, and final packaging. Every stage is optimized for accuracy, efficiency, and traceability, ensuring consistent quality, reliable performance, and control throughout production.



Advanced Production Technology

Our production lines combine advanced automation with continuous process monitoring to support consistent tensile strength, uniform mesh openings, and dimensional stability. Computer-controlled weaving and coating equipment provides precise process control, while our in-house quality laboratory performs regular testing and verification to support conformity of qualifying products with applicable ETA and CE requirements.


Sustainable Manufacturing

GATEX is committed to sustainability through responsible energy use, process efficiency, and environmental improvement. Our facility in Kaçanik operates under ISO 9001 and ISO 14001 management systems, integrating environmental responsibility with manufacturing. By improving resource efficiency and practices, we aim to reduce our environmental footprint while maintaining product reliability.

From Fiber to Façade

Each roll of GATEX fiberglass mesh reflects technical development, manufacturing precision, and documented performance. Through continuous improvement and quality control, our products deliver reliable reinforcement, strength, and flexibility — essential for modern ETICS façade applications across European markets.

Color-Coded Mesh Customization



Organized workflows begin with color clarity.

At GATEX, we understand the importance of clarity and efficiency on construction sites. That's why we offer fiberglass mesh in a wide range of customer-specified colours, matched to RAL or PANTONE references, including white, orange, yellow, blue, red, green and other custom tones. These colour-coded options help project managers and installers distinguish between mesh types, weight classes or intended applications—supporting clearer identification, reducing errors and improving workflow throughout installation.

End-to-End Customisation Process

From customer colour selection to weaving, controlled colour coating/impregnation, drying/curing, finishing and cutting, we manage the full production process in-house. This integrated approach enables consistent colour reproduction, batch control and full traceability to the manufacturing lot, ensuring each roll meets the specified reinforcement and visual requirements.

Enhanced Functionality and Visual Integration

Colour-coded mesh offers more than visual customisation. Different colours can be produced according to customer requirements, helping distinguish reinforcement grades, product types or intended applications. This supports clearer identification, improved site organisation and easier quality control throughout installation and subsequent system inspection.

A Collaborative Approach for Your Project

Whether for new construction, refurbishment or specialised façade systems, our team works with customers to define the required colour, mesh weight and weave specification. GATEX can manufacture reinforcement mesh in customer-specified colours while maintaining the required technical characteristics, consistency and traceability across each production batch.ty—all in one solution.

Logistics & Delivery

Reliable Export Logistics

At GATEX, logistics is an integral part of our production and customer service process. Finished mesh rolls are packed, labelled, palletised and prepared for transport according to product specifications and customer requirements. Each shipment is organised to support safe handling, efficient loading and reliable delivery across domestic and European markets.



Integrated Production & Dispatch

From final inspection to packaging and dispatch, GATEX coordinates each stage within a controlled workflow. Finished products are identified and prepared with full batch traceability, supporting accurate order fulfilment, export documentation and efficient coordination between production, warehousing and transport.

Secure Handling & Transport

Fiberglass reinforcement mesh requires careful handling throughout storage and transportation. Our packaging and palletisation procedures are designed to protect roll geometry, product integrity and identification during loading, transit and unloading. This helps ensure that products arrive ready for storage, distribution or installation.

Partnering for Reliable Delivery

Working with distributors, system manufacturers and construction partners across European markets, GATEX coordinates production schedules and deliveries according to individual order requirements. Through responsive planning, clear documentation and reliable logistics coordination, we support consistent supply and long-term commercial partnerships.

GATEXX

Build better.

PRODUCTLIST

sales@gatex.info
+38348266366
National Rd. Kaçanik – Ferizaj
km 14 XK, 71000, Kosovo
www.gatex.info

CARBON NEUTRAL

Printed on paper containing 20% recycled material

REACH Compliant

FOR A SUSTAINABLE FUTURE