

Introduction to Web Science – Assignment 1

Group hotel

Andrea Mildes 212100201 mildes@uni-koblenz.de

Sebastian Blei 211100448 sblei@uni-koblenz.de

1 Ethernet Frame

- Source MAC Address (6 bytes): 00 13 10 e8 dd 52
- Destination MAC Address (6 bytes): 00 27 10 21 fa 48
- Protocol inside the data payload (2 bytes): 08 06 (Address Resolution Protocol (ARP) (for IP and for CHAOS))
- last 2 fields:
 - 28 bytes arp request or arp reply
(source hardware address/srouce proctocl address/target hardware address/target protocol address)
00 01 08 00 06 04 00 01
00 13 10 e8 dd 25 c0 a8
02 01 00 00 00 00 00 00
c0 a8 02 67
 - 10 bytes padding (filler bytes to reach minimum of 46 bytes)
00 00 00 00 00 00 00 00
00 00

2 Cable Issue

$$speed \cdot time = distance \quad (1)$$

$$speed = 300\,000\,000 \frac{m}{s} \quad (2)$$

$$distance = 20m \quad (3)$$

$$time = unknown \quad (4)$$

$$100 \frac{Mbit}{s}:$$

$$300000000 \frac{m}{s} \cdot t_{100} \cdot 10^{-8} = 20m \quad (5)$$

$$t_{100} = \frac{200s}{3 \frac{m}{s}} = 6.666s \quad (6)$$

$$10 \frac{Mbit}{s}:$$

$$300000000 \frac{m}{s} \cdot t_{10} \cdot 10^{-7} = 20m \quad (7)$$

$$t_{10} = \frac{200s}{3 \frac{m}{s}} = 66.666s \quad (8)$$

3 Basic Network Tools

4 Simple Python Programming

```
# assignment 1 task4
# Andrea Mildes - mildes@uni-koblenz.de
# Sebastian Blei - sblei@uni-koblenz.de

import random
import math
import matplotlib.pyplot as plt
import matplotlib.patches as lpatches

sin = []
cosin = []
xcoord = []

plt.axis([0, 90, 0, 1])
plt.xlabel('x [radian]')
plt.ylabel('y')

for i in range(0, 10):
    x = random.randint(0,90)
    xcoord.append(x)
    sin.append(math.sin(math.radians(x)))
    cosin.append(math.cos(math.radians(x)))

plt.plot(xcoord, sin, "ro", label = "sinus")
plt.plot(xcoord, cosin, "g^", label = "cosinus")

plt.legend(bbox_to_anchor = (1.05, 1), loc = 2, borderaxespad = 0)

plt.show()
```