



Introduction to Web Science – Assignment 1

Group hotel

Andrea Mildes 212100201 mildes@uni-koblenz.de

Sebastian Blei 211100448 sblei@uni-koblenz.de



1 Ethernet Frame

- Source MAC Address (6 bytes): 00 13 10 e8 dd 52
- Destination MAC Address (6 bytes): 00 27 10 21 fa 48
- Protocol inside the data payload (2 bytes): 08 06 (Address Resolution Protocol (ARP) (for IP and for CHAOS))
- last 2 fields:
 - 28 bytes arp request or arp reply
(source hardware address/srouce protocl address/target hardware address/target protocol address)
 - 00 01 08 00 06 04 00 01
 - 00 13 10 e8 dd 25 c0 a8
 - 02 01 00 00 00 00 00 00
 - c0 a8 02 67
 - 10 bytes padding (filler bytes to reach minimum of 46 bytes)
 - 00 00 00 00 00 00 00 00
 - 00 00



2 Cable Issue

$$speed \cdot time = distance \quad (1)$$

$$speed = 300\,000\,000 \frac{m}{s} \quad (2)$$

$$distance = 20m \quad (3)$$

$$time = unknown \quad (4)$$

$$100 \frac{Mbit}{s}:$$

$$300000000 \frac{m}{s} \cdot t_{100} \cdot 10^{-8} = 20m \quad (5)$$

$$t_{100} = \frac{200s}{3 \frac{m}{s}} = 6.666s \quad (6)$$

$$10 \frac{Mbit}{s}:$$

$$300000000 \frac{m}{s} \cdot t_{10} \cdot 10^{-7} = 20m \quad (7)$$

$$t_{10} = \frac{200s}{3 \frac{m}{s}} = 66.666s \quad (8)$$

3 Basic Network Tools

4 Simple Python Programming

```
# assignment 1 task4
# Andrea Mildes - mildes@uni-koblenz.de
# Sebastian Blei - sblei@uni-koblenz.de

import random
import math
import matplotlib.pyplot as plt
import matplotlib.patches as lpatches

sin = []
cosin = []
xcoord = []

plt.axis([0, 90, 0, 1])
plt.xlabel('x [radian]')
plt.ylabel('y')

for i in range(0, 10):
    x = random.randint(0,90)
    xcoord.append(x)
    sin.append(math.sin(math.radians(x)))
    cosin.append(math.cos(math.radians(x)))

plt.plot(xcoord, sin, "ro", label = "sinus")
plt.plot(xcoord, cosin, "g^", label = "cosinus")

plt.legend(bbox_to_anchor = (1.05, 1), loc = 2, borderaxespad = 0)

plt.show()
```