

# Working with Image Data

## Bootcamp Section 1

Joseph Adler, Drew Conway, Jake Hofman, Hilary Mason

February 1, 2011



Creative Commons Attribution-Share Alike 3.0

# Acquiring image data

YAHOO! DEVELOPER NETWORK jake.hofman | Sign Out | Help

Home Documentation My Projects

Developer > APIs and Tools > Yahoo! Query Language > Console

**YOUR YQL STATEMENT** [permalink](#) [Create Query Alias](#)

```
select * from flickr.photos.search(100) where tags="kittens" and sort="interestingness-desc"
```

XML  JSON cbfunc  Diagnostics [TEST](#)

**FORMATTED** [TREE](#)  Wrap Text [flickr.photos.search](#)

```
{
  "results": [
    {
      "farm": "3",
      "id": "4220856234",
      "isfamily": "0",
      "isfriend": "0",
      "ispublic": "1",
      "owner": "36587311@N08",
      "secret": "029e5b8348",
      "server": "2570",
      "title": "Cuba Gallery: Cat / evil / kitten / pets / animal / cute / photography"
    },
    {
      "farm": "4",
      "id": "4220856234",
      "isfamily": "0",
      "isfriend": "0",
      "ispublic": "1",
      "owner": "36587311@N08",
      "secret": "029e5b8348",
      "server": "2570",
      "title": "Cuba Gallery: Cat / evil / kitten / pets / animal / cute / photography"
    }
  ]
}
```

**THE REST QUERY** [How do I use this?](#) [hide](#)

```
http://query.yahooapis.com/v1/public/yql?q=select%20*%20from%20flickr.photos.search(100)%20where%20tags%3D%22kitte
```

**EXAMPLE QUERIES**

- get my friends sorted by nickname
- get 10 flickr "cat" photos
- get a flickr photo by photo ID
- get the flickr image url by photo ID
- get san francisco geo data
- get san francisco woeid
- get geo details about san francisco


**DATA TABLES** (162)

Show Community Tables [What's this?](#)




[Filter Tables](#)

- flickr.people.info2
- flickr.people.publicphotos
- flickr.photos.exif
- flickr.photos.info
- flickr.photos.interestingness
- flickr.photos.recent
- flickr.photos.search
- flickr.photos.size
- flickr.photosets.info


## Image features




## Clustering pixels



# Clustering images



## Classifying images



# Outline

1 Acquiring image data

2 Image features

3 Clustering

4 Classification

# Simple screen scraping

One-liner to scrape images from a webpage

```
wget -O- http://bit.ly/gpCSQi |  
tr ' ' '\"= ' '\n' |  
egrep '^http.*(png|jpg|gif)' |  
xargs wget
```

# Simple screen scraping

## One-liner to scrape images from a webpage

```
wget -O- http://bit.ly/gpCSQi |  
tr ' ' '\"'=' '\n' |  
egrep '^http.*(png|jpg|gif)' |  
xargs wget
```

- ▶ get page source
- ▶ translate quotes and = to newlines
- ▶ match urls with image extensions
- ▶ download qualifying images

# Simple screen scraping

One-liner to download ESL digit data

```
wget -Nr --level=1 --no-parent http://bit.ly/fsymq6
```

"cat flickr | xargs wget"?

flickr® from YAHOO!

You aren't signed in [Sign In](#) [Help](#)

Home The Tour Sign Up Explore | [Upload](#)

Search | ▾

## Explore / Interestingness / January 2011

[◀ December 2010](#) [January 2011](#) [▶ February 2011](#)

SUN	MON	TUE	WED	THU	FRI	SAT
						
						
						
						
						
						



[Home](#) | [API](#) | [Community](#) | [Business](#) | [Attributions](#)

[Flickr API Changelog](#)

## Getting Started

To begin using the [Flickr API](#):

**1** Request an API key, to sign your API requests.

**2** Read the [Community Guidelines](#) and the [API Terms of Use](#).

**3** Build, build, build. Test, test, test.

**4** Launch (and if it's an app of interest to the Flickr community, create a profile for your app in the [Flickr App Garden](#)).

YQL: SELECT \* FROM Internet<sup>1</sup>

## What is YQL?

The Yahoo! Query Language is an expressive SQL-like language that lets you query, filter, and join data across Web services. With YQL, *apps run faster with fewer lines of code and a smaller network footprint.*

<http://developer.yahoo.com/yql>

---

<sup>1</sup><http://oreillynet.com/pub/e/1369>

# YQL: Console

YAHOO! DEVELOPER NETWORK jake.hofman | Sign Out | Help

Home Documentation My Projects

Developer > APIs and Tools > Yahoo Query Language > Console

**YOUR YQL STATEMENT** [permalink](#) [Create Query Alias](#)

```
select * from flickr.photos.search(100) where tags="kittens" and sort="interestingness-desc"
```

XML  JSON cbfunc  Diagnostics **TEST**

**FORMATTED** **TREE**  Wrap Text **flickr.photos.search**

```
},  
  "results": {  
    "photo": [  
      {  
        "farm": "3",  
        "id": "4220856234",  
        "isfamily": "0",  
        "isfriend": "0",  
        "ispublic": "1",  
        "owner": "36587311@N08",  
        "secret": "029e5b8348",  
        "server": "2570",  
        "title": "Cuba Gallery: Cat / evil / kitten / pets / animal / cute / photography"  
      },  
      {  
        "farm": "4".  
    }],  
  }
```

**THE REST QUERY** [How do I use this?](#) [hide](#)

```
http://query.yahooapis.com/v1/public/yql?q=select%20*%20from%20flickr.photos.search(100)%20where%20tags%3D%22kitten%22&sort=interestingness-desc
```

**EXAMPLE QUERIES**

- get my friends sorted by nickname
- get 10 flickr "cat" photos
- get a flickr photo by photo ID
- get the flickr image url by photo ID
- get san francisco geo data
- get san francisco woeid
- get geo details about san francisco

**DATA TABLES** (162)

Show Community Tables [What's this?](#)

[Filter Tables](#)

- flickr.people.info2
- flickr.people.publicphotos
- flickr.photos.exif
- flickr.photos.info
- flickr.photos.interestingness
- flickr.photos.recent
- flickr.photos.search
- flickr.photos.sizes
- flickr.photosets.info

<http://developer.yahoo.com/yql/console>

## Python function for public YQL queries

```
YQL_PUBLIC = 'http://query.yahooapis.com/v1/public/yql'

def yql_public(query):
    # escape query
    query_str = urlencode({'q': query, 'format': 'json'})

    # fetch results
    url = '%s?%s' % (YQL_PUBLIC, query_str)
    result = urlopen(url)

    # parse json and return
    return json.load(result)['query']['results']
```

---

<sup>2</sup>See <http://python-yql.org/> for a more robust client

# YQL + Python + Flickr

Fetch info for “interestingness” photos

```
./simpleyql.py ``select * from  
flickr.photos.interestingness(100)''
```

Download thumbnails for photos tagged with “vivid”

```
./download_flickr.py vivid 500
```

# Outline

1 Acquiring image data


2 Image features

3 Clustering

4 Classification

## Images as arrays

Grayscale images  $\leftrightarrow$  2-d arrays of  $M \times N$  pixel intensities



# Images as arrays

Grayscale images  $\leftrightarrow$  2-d arrays of  $M \times N$  pixel intensities

```
array([[ -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ,
       -0.643, 0.625, 0.815, -0.533, -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -0.441,
       0.951, 1. , 0.902, -0.111, -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -0.724, 0.776,
       1. , 0.622, -0.736, -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , 0.389, 1. ,
       0.739, -0.908, -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -0.387, 0.985,
       0.943, -0.598, -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -0.824, 0.728,
       1. , -0.044, -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , 0.364, 1. ,
       0.54, -0.972, -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -0.441, 0.999,
       0.854, -0.675, -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -0.925, 0.8 ,
       0.995, -0.121, -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -0.495, 0.999,
       0.782, -0.99, -0.852, -0.172, 0.208, -0.038, -0.516, -1. ,
       -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. , -1. ],
      [-1. , -1. , -0.179, 1. , 0.125, -0.242, 0.773, 1. ,
       1. , 1. , 0.998, 0.534, -0.628, -1. , -1. , -1. , -1. ],
      [-1. , -1. , -0.339, 1. , 0.756, 0.993, 0.99, 0.571,
       -0.05, -0.317, -0.106, 0.666, 0.845, -0.699, -1. , -1. ],
      [-1. , -1. , -0.773, 0.945, 1. , 0.858, -0.304, -1. ,
       -1. , -1. , -0.967, 0.327, 1. , -0.079, -1. , -1. , -1. ],
      [-1. , -1. , -1. , 0.418, 1. , -0.126, -0.995, -1. ,
       -0.986, -0.57, 0.494, 1. , 0.957, -0.737, -1. , -1. , -1. ],
      [-1. , -1. , -1. , -0.752, 0.297, 0.995, -0.698, 0.646,
       0.724, 1. , 1. , 0.912, -0.358, -1. , -1. , -1. , -1. ],
      [-1. , -1. , -1. , -1. , -1. , -0.607, 0.351, 0.585,
       0.841, 0.595, 0.312, -0.797, -1. , -1. , -1. , -1. ]])
```

## Images as arrays

Color images  $\leftrightarrow$  3-d arrays of  $M \times N \times 3$  RGB pixel intensities



```
import matplotlib.image as mpimg  
I = mpimg.imread('chairs.jpg')
```

# Images as arrays

Color images  $\leftrightarrow$  3-d arrays of  $M \times N \times 3$  RGB pixel intensities

```
array([[[106, 114,  63],
       [119, 129,  69],
       [135, 146,  77],
       ...,
       [ 12,   12,  12],
       [ 12,   12,  12],
       [ 12,   12,  12]],

      [[126, 134,  87],
       [129, 138,  83],
       [132, 143,  77],
       ...,
       [ 19,   19,  19],
       [ 19,   19,  19],
       [ 19,   19,  19]],


      [[124, 131,  87],
       [121, 129,  78],
       [116, 126,  63],
       ...,
       [ 31,   31,  31],
       [ 31,   31,  31],
       [ 31,   31,  31]],

      ...,
      [[122, 156,  69],
       [128, 162,  75],
       [144, 178,  91],
       ...,
       [157, 187, 127],
       [160, 190, 128],
       [156, 187, 120]]],
```

```
import matplotlib.image as mpimg
I = mpimg.imread('chairs.jpg')
```


## Intensity histograms

Disregard all spatial information, simply count pixels by intensities  
(e.g. lots of bright green and dark blue pixels)



# Intensity histograms

How many bins for pixel intensities?



**Too many** bins gives a noisy, **overly complex** representation of the data, while using **too few** bins results in an **overly simple** one

# Outline

1 Acquiring image data

2 Image features

3 Clustering

4 Classification

# Clustering images

Clustering is an *unsupervised* learning task by which we look for structure in the data, grouping similar examples together



e.g., find groups of similar pixels within a single image

# Clustering images


Clustering is an *unsupervised* learning task by which we look for structure in the data, grouping similar examples together



e.g., find groups of similar images across a collection of images

## K-means clustering

K-means: represent each cluster by the average of its points



Learn by iteratively updating cluster means and point assignments

# K-means clustering

K-means:


Choose number of clusters

Initialize cluster centers

While not converged:

    Assign each point to closest cluster

    Update cluster centers



# K-means clustering

K-means:


Choose number of clusters

Initialize cluster centers

While not converged:

Assign each point to closest cluster

Update cluster centers



# K-means clustering

K-means:


Choose number of clusters

Initialize cluster centers

While not converged:

    Assign each point to closest cluster

    Update cluster centers



# K-means clustering

K-means:


Choose number of clusters

Initialize cluster centers

While not converged:

    Assign each point to closest cluster

    Update cluster centers



# K-means clustering

K-means:


Choose number of clusters

Initialize cluster centers

While not converged:

    Assign each point to closest cluster

    Update cluster centers



## Clustering pixels

Find groups of similar pixels within a single image  
(e.g. “the bright red circles”)






Represent each pixel as a separate example  
with its (R,G,B) value as a 3-d feature vector

# Clustering pixels

Group pixels within candy.jpg into 7 clusters

```
./cluster_pixels.py candy.jpg 7
```



# Clustering images

Find groups of similar images within a collection of images  
(e.g. “warm sunsets”)



Represent each image with a binned RGB intensity histogram

# Clustering images

Group 'vivid' images into 3 clusters

```
./cluster_flickr.py flickr_vivid 3 10
```



# Outline


1 Acquiring image data

2 Image features


3 Clustering

4 Classification

# Classifying images



# Classifying images



8