


<div>12Thermal Camera</div> <div>https://github.com/drewsum/Thermal_Camera</div>					
01. Table of Contents					
02. POS12 Input	POS12_Input	14. Battery Management	Battery Management	26. PGOOD LEDs	PGOOD LEDs
03. POS12 Telemetry	POS12 Telemetry	15. PIC32MZ DA Programming	PIC32MZ DA Programming	27. Status LEDs	Status LEDs
04. POS3P0 Power Supply	POS3P0 Power Supply	16. PIC32MZ DA Clocking	PIC32MZ DA Clocking	28. Mechanical	Mechanical
05. POS3P0 Telemetry	POS3P0 Telemetry	17. PIC32MZ DA Power	PIC32MZ DA Power		
06. POS1P8 Power Supply	POS1P8 Power Supply	18. PIC32MZ DA 1	PIC32MZ DA 1		
07. POS1P8 Telemetry	POS1P8 Telemetry	19. PIC32MZ DA 2	PIC32MZ DA 2		
08. POS2P8 Power Supply	POS2P8 Power Supply	20. External Storage	External Storage		
09. POS2P8 Telemetry	POS2P8 Telemetry	21. Graphic LCD	Graphic LCD		
10. POS1P2 Power Supply	POS1P2 Power Supply	22. USB UART	USB UART		
11. POS1P2 Telemetry	POS1P2 Telemetry	23. Elapsed Time Counter	Elapsed Time Counter		
12. LCD Backlight Power Supply	LCD Backlight Power Supply	24. FLIR Lepton Sensor	FLIR Lepton Sensor		
13. LCD Backlight Telemetry	LCD Backlight Telemetry	25. USB Hub	USB Hub		
<div>Drew Maatman and Michael Laffin</div> <div>Sheet: /</div> <div>File: Thermal_Camera.kicad_sch</div> <div>Title: Thermal Camera</div> <div><div>Size: ADate: 2023-11-13</div><div>Rev: PRELIM</div></div> <div><div>KiCad E.D.A. kicad 7.0.9</div><div>Id: 1/28</div></div>					

Switch to +3.0V logic?

UVLO threshold set to 10.8V
OVLO threshold set to 13.2V
MODE set to Circuit Breaker with Auto-Retry
Output Current Limit set to 1.2A

Drew Maatman and Michael Laffin
Sheet: /POS12_Input/
File: POS12_Input.kicad_sch
Title: Thermal Camera
Size: A Date: 2023-11-13 Rev: PRELIM
KiCad E.D.A. kicad 7.0.9 Id: 2/28

Id: 2/28



Drew Maatman and Michael Laffin


Sheet: /POS12 Telemetry/
File: POS12_Telemetry.kicad_sch

Title: Thermal Camera

Size: A Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9

Rev: PRELIM
Id: 3/28

figure out sequencing



Drew Maatman and Michael Laffin

Sheet: /POS3P0 Power Supply/
File: POS3P0_Power_Supply.kicad_sch

Title: Thermal Camera

Size: A Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9

Rev: PRELIM
Id: 4/28





figure out sequencing



Drew Maatman and Michael Laffin

Sheet: /POS1P8 Power Supply/
File: POS1P8_Power_Supply.kicad_sch


Title: Thermal Camera

Size: A	Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9	

Rev: PRELIM
Id: 6/28

The figure is a large rectangular area with a grid of 5 columns and 4 rows. The columns are labeled 1, 2, 3, 4, and 5 from left to right. The rows are labeled A, B, C, and D from top to bottom. The grid is composed of thin black lines. In the bottom right corner, there is a title block with the following text:

Drew Maatman and Michael Laffin		
Sheet: /POS1P8 Telemetry/		
File: POS1P8_Telemetry.kicad_sch		
Title: Thermal Camera		
Size: A	Date: 2023-11-13	Rev: PRELIM
KiCad E.D.A. kicad 7.0.9	Id: 7/28	




Drew Maatman and Michael Laffin

Sheet: /POS2P8 Power Supply/
File: POS2P8_Power_Supply.kicad_sch

Title: Thermal Camera

Size: A Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9


Rev: PRELIM
Id: 8/28




Rev: PRELIM
Id: 10/28

1					2					3					4					5					
A																									A
B																									B
C																									C
D																									D
1					2					3					4					5					

Drew Maatman and Michael Laffin		
Sheet: /POS1P2 Telemetry/ File: POS1P2_Telemetry.kicad_sch		
Title: Thermal Camera		
Size: A	Date: 2023-11-13	Rev: PRELIM
KiCad E.D.A. kicad 7.0.9		Id: 11/28






Drew Maatman and Michael Laffin


Sheet: /LCD Backlight Telemetry/
File: LCD_Backlight_Telemetry.kicad_sch

Title: Thermal Camera

Size: A	Date: 2023-11-13	Rev: PRELIM
KiCad E.D.A. kicad 7.0.9		Id: 13/28





Drew Maatman and Michael Laffin		
Sheet: /Battery Management/ File: Battery_Management.kicad_sch		
Title: Thermal Camera		
Size: A	Date: 2023-11-13	Rev: PRELIM
KiCad E.D.A. kicad 7.0.9		Id: 14/28





Rev: PRELIM
Id: 15/28

COPIED FROM PIC32MZ EF FIX FOR PIC32MZ DA CHANGE TO +3.0V CLOCKS



MUST BE 24MHZ



Drew Maatman and Michael Laffin

Sheet: /PIC32MZ DA Clocking/

File: PIC32MZ_DA_Clocking.kicad_sch

Title: Thermal Camera



Size: A

Date: 2023-11-13

KiCad E.D.A. kicad 7.0.9

Rev: PRELIM

Id: 16/28



COPIED FROM PIC32MZ EF
FIX FOR PIC32MZ DA
CHANGE TO +3.0V

FIGURE OUT HOW TO USE THIS

Drew Maatman and Michael Laffin

Sheet: /PIC32MZ DA Power/
File: PIC32MZ_DA_Power.kicad_sch

Title: Thermal Camera


Size: A Date: 2023-11-13

KiCad E.D.A. kicad 7.0.9


Rev: PRELIM

Id: 17/28

See TABLE 36-1:RGB COLOR MAPPING for Graphic LCD Pin Mapping



DOUBLE CHECK
SOSC PIN



Drew Maatman and Michael Laffin


Sheet: /PIC32MZ DA 1/
File: PIC32MZ_DA_1.kicad_sch

Title: Thermal Camera

Size: A Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9

Rev: PRELIM
Id: 18/28

See TABLE 36-1:RGB COLOR MAPPING for Graphic LCD Pin Mapping




Drew Maatman and Michael Laffin

Sheet: /PIC32MZ DA 2/
File: PIC32MZ_DA_2.kicad_sch


Title: Thermal Camera

Size: A Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9

Rev: PRELIM
Id: 19/28



Add SD card power switching?



SD CARD, SPI FLASH

BREAK OUT A SPI TO SD CARD AS INSURANCE

BREAK OUT FLASH SPI TO A HEADER FOR PROGRAMMING

Draw: Michael and Michael

Sheet: /External Storage/

File: External_Storage.kicad_sch


Title: Thermal Camera

Size: A Date: 2023-11-13

KiCad E.D.A. kicad 7.0.9

Rev: PRELIM

Id: 20/28



Drew Maatman and Michael Laffin

Sheet: /Graphic LCD/
File: Graphic_LCD.kicad_sch


Title: Thermal Camera


Size: A Date: 2023-11-13

KiCad E.D.A. kicad 7.0.9

Rev: PRELIM

Id: 21/28





I2C 7-Bit Address:
0x6B

Drew Maatman and Michael Laffin


Sheet: /Elapsed Time Counter/
File: Elapsed_Time_Counter.kicad_sch

Title: Thermal Camera

Size: A Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9

Rev: PRELIM
Id: 23/28

Power Supply Considerations:
VDDC: 1.20V (1.14V min, 1.26V max), 50mVpp max ripple, 110mA max draw
VDD: 2.80V (2.72V min, 2.88V max), 30mVpp max ripple, 16mA max draw
VDDIO: 2.8V min, 3.1V max, 50mVpp max ripple, 310mA max draw



I2C 7-Bit Address:
0x2A

See FLIR document #110-0144-04 for I2C register map



Drew Maatman and Michael Laffin

Sheet: /FLIR Lepton Sensor/
File: FLIR_Lepton_Sensor.kicad_sch


Title: Thermal Camera

Size: A Date: 2023-11-13


KiCad E.D.A. kicad 7.0.9

Rev: PRELIM


Id: 24/28



Drew Maatman and Michael Laffin		
Sheet: /USB Hub/		
File: USB_Hub.kicad_sch		
Title: Thermal Camera		
Size: A	Date: 2023-11-13	Rev: PRELIM
KiCad E.D.A. kicad 7.0.9		Id: 25/28



**MUST USE
OUTPUT COMPARE
PIN**




Drew Maatman and Michael Laffin

Sheet: /Status_LEDs/
File: Status_LEDs.kicad_sch

Title: Thermal Camera

Size: A Date: 2023-11-13
KiCad E.D.A. kicad 7.0.9

Rev: PRELIM
Id: 27/28



Drew Maatman and Michael Laffin

Sheet: /Mechanical/
File: Mechanical.kicad_sch

Title: Thermal Camera

Size: A Date: 2023-11-13

KiCad E.D.A. kicad 7.0.9

Rev: PRELIM

Id: 28/28