
Fully connected NN

Remi Chassagnol

March 5, 2025

1 Notations

- w_{jk}^l is the weight of the k^{th} neuron in the layer (l-1) to the j^{th} neuron in the layer l
- b_j^l is the bias of the j^{th} neuron on the layer l.
- a_j^l is the activation of the j^{th} neuron on the layer l.
- ullet act is the activation function.
- \bullet cost is the cost function.
- δ^l_j is the error of the j^{th} neuron on the layer l.
- \bullet L is the last layer.



2 **Definitions**

Transition from the layer (l-1) to the layer l:

$$z_{j}^{l} = \sum_{k} w_{jk}^{l} a_{k}^{l-1} + b_{j}^{l} \tag{1}$$

$$a_j^l = act(z_j^l) \tag{2}$$

The error of a neuron can be define as:

$$\delta_j^l \equiv \frac{\partial cost}{\partial z_j^l} \tag{3}$$

We define δ_j^L the error on the output layer as the following:

$$\delta_j^L = \frac{\partial cost}{\partial a_j^l} act'(z_j^L) \tag{4}$$

Then we have δ^L which is a vector that contains the errors of all the output neurons:

$$\delta^L = \nabla_a cost \odot act'(z^L) \tag{5}$$

Here, we can deduce the value of δ^l :

$$\delta^l = ((w^{l+1})^T \delta^{l+1}) \odot act'(z^l)$$
(6)

Now that we have this, we can define the error in terms of w and b:

$$\frac{\partial cost}{\partial b_j^l} = \delta_j^l \tag{7}$$

$$\frac{\partial cost}{\partial b_j^l} = \delta_j^l \tag{7}$$

$$\frac{\partial cost}{\partial w_{jk}^l} = a_k^{l-1} \delta_j^l \tag{8}$$

3 Algorithms

First we wan to apply the model to the input by making the data flow threw the network using the feed forward algorithm.

Algorithm 1 FeedForward

```
 \begin{aligned} & \textbf{procedure} \text{ FeedForward}(weights, biases, input) \\ & a = input \\ & as = [a] \\ & zs = [] \end{aligned}   \begin{aligned} & \textbf{for } w, b \text{ in } (weights, biases) \textbf{ do} \\ & z = w \times a + b \\ & \text{append}(zs, z) \\ & a = \text{act}(z) \\ & \text{append}(as, a) \end{aligned}   \end{aligned}   \begin{aligned} & \textbf{end for} \\ & \textbf{return } as, zs \\ & \textbf{end procedure} \end{aligned}
```

Then we compute the gradiant of all the nodes using the back propagation (propagate the result error back in the network).

Algorithm 2 Back propagation algorithm

```
procedure BackPropagate(as, zs, weights, biases)
deltas = \cos'(as[len(as) - 1], expected\_solution) \odot act'(zs[len(zs) - 1])
grads\_b[L - 1] = deltas
grads\_w[L - 1] = \text{matmul}(deltas, as[len(as) - 2])
for \ l \ in \ 2.. \le L \ do
deltas = \text{matmul}(T(weights[L - l + 1]), deltas) \odot act'(zs[len(zs) - l])
grads\_b[L - l] = deltas
grads\_w[L - l] = \text{matmul}(deltas, as[len(as) - l - 1])
end \ for
return \ grads\_w, \ grads\_b
end \ procedure
```

The last component we need is the optimize function that will update the weights and the biases. There are various ways to do this, here is an example for a stochastic gradiant descant:

Algorithm 3 Optimization for a stochastic gradiant descant

```
 \begin{array}{c} \textbf{procedure} \ \mathsf{OPTIMIZE}(weights, biases, grads\_w, grads\_b, l\_rate) \\ \textbf{for} \ l \ \text{in} \ 0.. < L \ \textbf{do} \\ weights[l] := l\_rate \times grads\_w[l] \\ biases[l] := l\_rate \times grads\_b[l] \\ \textbf{end} \ \textbf{for} \\ \textbf{return} \ weights, biases \\ \textbf{end} \ \textbf{procedure} \\ \end{array}
```

To train, we usually use minibatches. This means that we compute the average error on all the minibatches before updating the weights and biases.

Algorithm 4 Update the weights using a minibatch

```
grads_w_total = 0
grads_b_total = 0

for minibatch in minibatches do
    as, zs = FeedForward(weights, biases, minibatch)
    grads_w, grads_b = BackPropagate(as, zs, weights, biases)
    grads_w_total += grads_w
    grads_b_total += grads_b
end for
grads_w = grads_w_total / size(minibatches)
grads_b = grads_b_total / size(minibatches)
weights, biases = Optimize(weights, biases, grads_w, grads_b, l_rate)

return weights, biases
end procedure
```

4 Proofs

4.0.1 Error on the output layer δ_j^L

Let's prove the following:

$$\delta_j^L = \frac{\partial cost}{\partial a_j^L} act'(z_j^L) \tag{9}$$

$$= \frac{\partial cost}{\partial a_j^L} \frac{\partial act}{\partial z_j^L} \tag{10}$$

The definition of the error is:

$$\delta_j^L = \frac{\partial cost}{\partial z_i^L} \tag{11}$$

$$= \sum_{k} \frac{\partial cost}{\partial a_{k}^{L}} \frac{\partial a_{k}^{L}}{\partial z_{j}^{L}} \tag{12}$$

Since $a_k^L=act(z_k^L)$, if $j\neq k$, then $\frac{\partial a_k^L}{\partial z_j^L}=0$. Which gives the result expression:

$$\delta_j^L = \frac{\partial cost}{\partial a_j^L} \frac{\partial a_j^L}{\partial z_j^L} \tag{13}$$

4.0.2 Error on internal layers δ_j^l

 δ_j^l is defined as:

$$\delta_j^l = \frac{\partial cost}{\partial z_j^l} \tag{14}$$

$$=\sum_{k}\frac{\partial cost}{\partial z_{k}^{l+1}}\frac{\partial z_{k}^{l+1}}{\partial z_{j}^{l}}\tag{15}$$

$$= \sum_{k} \delta_{k}^{l+1} \frac{\partial z_{k}^{l+1}}{\partial z_{j}^{l}} \tag{16}$$

We can then define z_k^{l+1} as:

$$z_k^{l+1} = \sum_{i} w_{kj}^{l+1} act(z_j^l) + b_k^{l+1}$$
 (17)

so the derivative is:

$$\frac{z_k^{l+1}}{z_j^l} = w_{kj}^{l+1} act'(z_j^l) \tag{18}$$

Substituing back to the original formula:

$$\delta_{j}^{l} = \sum_{k} w_{kj}^{l+1} \delta_{k}^{l+1} act'(z_{j}^{l})$$
(19)

4.0.3 Bias gradiant $\frac{\partial cost}{\partial b_{j}^{l}}$

We prove the following:

$$\frac{\partial cost}{\partial b_j^l} = \delta_j^l \tag{20}$$

We can rewrite it like the following:

$$\frac{\partial cost}{\partial b_j^l} = \sum_{k} \frac{\partial cost}{\partial z_k^{l+1}} \frac{\partial z_k^{l+1}}{\partial z_j^l} \frac{\partial z_j^l}{\partial b_j^l}$$
(21)

since $\frac{\partial z_j^l}{\partial b_j^l} = 1$, then:

$$\frac{\partial cost}{\partial b_j^l} = \sum_k \frac{\partial cost}{\partial z_k^{l+1}} \frac{\partial z_k^{l+1}}{\partial z_j^l}$$
 (22)

$$=\delta_i^l \tag{23}$$

4.0.4 Bias gradiant $\frac{\partial cost}{\partial w_{jk}^l}$

We prove the following:

$$\frac{\partial cost}{\partial w_{jk}^l} = a_k^{l-1} \delta_j^l \tag{24}$$

We can rewrite it like the following:

$$\frac{\partial cost}{\partial w_{jk}^{l}} = \sum_{k} \frac{\partial cost}{\partial z_{k}^{l+1}} \frac{\partial z_{k}^{l+1}}{\partial z_{j}^{l}} \frac{\partial z_{j}^{l}}{\partial w_{jk}^{l}}$$
(25)

since $\frac{\partial z_j^l}{\partial w_{jk}^l} = a_k^{l-1}$, then:

$$\begin{split} \frac{\partial cost}{\partial w_{jk}^{l}} &= \sum_{k} \frac{\partial cost}{\partial z_{k}^{l+1}} \frac{\partial z_{k}^{l+1}}{\partial z_{j}^{l}} a_{k}^{l-1} \\ &= \delta_{j}^{l} a_{k}^{l-1} \end{split} \tag{26}$$

5 References

 $\bullet \ \mathtt{http://neuralnetworksanddeeplearning.com/chap2.html}$