



Week 7

Diana Gage

www-personal.umich.edu/~drgage

slides by Leah Bar-On Simmons and
Diana Gage

Course Evals

- Thanks to those of you who filled them out!
- I got some good feedback...
 - More practice problems!
 - Do you guys want to do some 2D past exam questions today?

How's Project 3 Going?

- Any general questions I can answer?
- Specific questions?
 - Assignment 3 should be very helpful

Projects going forward


- For project 4 you can also work with a partner!
- After that, there is the Final Project, which is in groups of 4

Discussion Plan

- Any exam questions?
- 2-dimensional arrays review
 - Practice problems
- File Input/Output Intro

2 Dimensional Arrays

- You can visualize these like a matrix, or game board!
 - ALWAYS: `arr[row][col]`
 - *You'll often see 'col' in place of column*



1	2	3
4	5	6
7	8	9

Initializing all to 0

- 1-dimensional array:
`int board[3] = {0};`
- **2-dimensional array:**
`int board[3][5] = {0};`
- Both of these initialize every element in the array to 0
- this only works with 0 – any other number within the curly braces is interpreted as just setting the first element in the array

Initializing directly

```
const int HEIGHT = 3;  
const int WIDTH = 4;
```

```
int board[HEIGHT][WIDTH] = {  
    {1, 2, 3, 4},  
    {5, 6, 7, 8},  
    {9, 10, 11, 12}  
};
```

- You can also initialize all to the same thing, using nested loops

When initializing...

Which of these is **invalid**?

`int data[10][2];`

`int data [4][];`

`int data [] [8];`

When initializing...

Which of these is **invalid**?

```
int data[10][2];
```

```
int data [4] []; //compile error
```

```
int data [] [8];
```

When initializing...

```
int data[10][2];
```


```
int data [4][]; //compile error
```

```
int data [][8];
```

- ◉ With a 2-dimensional array, the compiler absolutely needs to know the **column** (the second parameter) **size** at compile time
- ◉ **The row is optional**

How do we iterate through a 2-d array


- What if we want to print every element in as in the picture?



How do we iterate through a 2-d array

- What if we want to print every element as in the picture. We print each element in each row, and start a new line for each row so it looks like a matrix.


```
for (int i = 0; i < 3; ++i){  
    for (int j = 0; j < 3; ++j){  
        cout << my_arr[i][j] << " ";  
    }  
    cout << endl;  
}
```



How do we iterate through a 2-d array

- Now what if we want to print the values **backwards**, keeping the matrix form?

```
int my_arr[3][3] = { {1, 2, 3}, {4, 5, 6}, {7, 8, 9} };
```




9	8	7
6	5	4
3	2	1

How do we iterate through a 2-d array

- Now what if we want to print the values **backwards**, keeping the matrix form?

```
int my_arr[3][3] = { {1, 2, 3}, {4, 5, 6}, {7, 8, 9} };
```

```
for (int i = 2; i >= 0; --i){  
    for (int j = 2; j >= 0; --j){  
        cout << my_arr[i][j] << " ";  
    }  
    cout << endl;  
}
```



How do we iterate through a 2-d array


- Now what if we want to **only reverse each column**, not the entire array?
- What is this equivalent to? What will be the net result?

```
int my_arr[3][3] = { {1, 2, 3}, {4, 5, 6}, {7, 8, 9} };
```


How do we iterate through a 2-d array

- Now what if we want to only **reverse each column**, not the entire array?
- What is this equivalent to? What will be the net result? **Reversing the order of the rows**

```
int my_arr[3][3] = { {1, 2, 3}, {4, 5, 6}, {7, 8, 9} };
```




7	8	9
4	5	6
1	2	3

How do we iterate through a 2-d array

- Now what if we want to only **reverse each column**, not the entire array?

```
int my_arr[3][3] = { {1, 2, 3}, {4, 5, 6}, {7, 8, 9} };
```

```
for (int i = 2; i >= 0; --i){  
    for (int j = 0; j < 3; ++j){  
        cout << my_arr[i][j] << " ";  
    }  
    cout << endl;  
}
```



7	8	9
4	5	6
1	2	3

File I/O

- Will be key in your next project/some of the final projects!
- Alternative to standard I/O
 - Reading in from keyboard, printing to screen
- File input – reading in from a file
- File output – writing to a file

File I/O

- **#include <fstream>** to have access to these datatypes:
 - Ifstream
 - Ofstream
- With these, you can declare variables so that you can read from/write to files!

<iostream> vs <fstream>

```
#include <iostream>
using namespace std;
```

```
int main() {
    int x;

    cin >> x;

}
```

```
#include <fstream>
using namespace std;
```

```
int main() {
    int x;
    ifstream input_file;
    input_file.open("filename");
    input_file >> x;
    input_file.close();

}
```

My suggestion:
name your
ifstream **"fin"**

What about writing to files?

```
#include <fstream>
using namespace std;

int main() {
    int x = 42;
    ofstream output_file;
    output_file.open("filename");
    output_file << x;
    output_file.close();
}
```

My suggestion:
name your
ofstream **"fout"**